

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12406575

Kind Code

B1

Date of Patent

September 02, 2025

Inventor(s)

Harris; Nathan Alan et al.

Systems and methods for automated vehicle recognition at service facilities

Abstract

Technical solutions are directed to a system including one or more processors, coupled with memory. The one or more processors can maintain a plurality of vehicle profiles for a plurality of vehicles. The one or more processors can capture one or more images of at least a portion of a vehicle, identify, using the one or more images, a first sequence of characters of a license plate of the vehicle and determine one or more characters of the first sequence of characters that satisfy a character replacement schema. The one or more processors can generate a second sequence of characters including one or more corresponding replacement characters in the first sequence of characters, identify, a vehicle profile of the vehicle based on executing a query using the generated second sequence of characters, and transmit, to a device, data included in the vehicle profile based on identifying the vehicle profile.

Inventors: Harris; Nathan Alan (Washington, DC), Dotson; Joshua Richard (Cuyahoga Falls, OH), McAliley; James Hodges (Charleston, SC), Clint; Aaron Mykal (Stewartsville, MT), Hester; Jonathan David (Charlotte, NC)

Applicant: MW POS, Inc. (Arlington, VA)

Family ID: 96882254

Assignee: MW POS, Inc. (Arlington, VA)

Appl. No.: 19/188968

Filed: April 24, 2025

Related U.S. Application Data

continuation parent-doc US 19081757 20250317 PENDING child-doc US 19188968

us-provisional-application US 63738281 20241223

us-provisional-application US 63699778 20240926

Publication Classification

Int. Cl.: G08G1/017 (20060101); G06T7/00 (20170101); G06V20/62 (20220101)

U.S. Cl.:

CPC G08G1/0175 (20130101); G06T7/001 (20130101); G06V20/625 (20220101);

Field of Classification Search

CPC: G06V (20/00); G06V (20/62); G06V (20/625)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9405988	12/2015	Alves	N/A	G06V 10/987
2002/0140577	12/2001	Kavner	340/928	G07B 15/063
2006/0180647	12/2005	Hansen	235/375	G07F 17/20
2009/0057401	12/2008	Brott	235/382	G06Q 20/28
2011/0288909	12/2010	Hedley	705/13	G07B 15/06
2015/0049914	12/2014	Alves	382/105	G06V 20/63
2017/0140237	12/2016	Voeller	N/A	G06V 20/63
2019/0043201	12/2018	Strong	N/A	G06V 10/96
2020/0294052	12/2019	Cacciami	N/A	G07B 15/00
2021/0150499	12/2020	Fazio	N/A	G07F 17/20
2023/0249653	12/2022	Stoel	705/1.1	G07F 17/0035
2024/0331393	12/2023	Petrey, Jr.	N/A	G08B 27/003
2024/0378925	12/2023	Nichols	N/A	G06N 7/01

Primary Examiner: Wilburn; Molly

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS (1) This application claims the benefit of priority under 35 U.S.C. § 120 and is a continuation of to U.S. Non-Provisional patent application Ser. No. 19/081,757, filed Mar. 17, 2025, which claims the benefit of priority under 35 U.S.C. § 119 to U.S. Provisional Patent Application No. 63/699,778, filed Sep. 26, 2024, and to U.S. Provisional Patent Application No. 63/738,281, filed Dec. 23, 2024, all of which are hereby incorporated by reference herein in their entirety and for all purposes.

BACKGROUND

(1) Vehicle service facilities, including car wash establishments, have evolved to meet the growing demand for efficient and convenient vehicle care. These facilities can include various devices, systems and machinery to automate different aspects of the services provided, including various car wash systems for servicing different vehicles.

SUMMARY

(2) Technical solutions described herein are directed to systems and methods for automating vehicle service facility operations using advanced image recognition, intelligent traffic management, and customized service delivery. Automated vehicle service facilities, such as car wash facilities, can experience technical challenges, such as when identifying vehicles with pre-paid services when vehicle license plates are deformed or obscured or when detecting fraudulent license plate changes between vehicles, all of which can hinder efficient and error-free operations. These issues can lead to various operational challenges, involving client misidentification, inefficient traffic flow management, and difficulties in automating service customization based on vehicle data, leading to corrective actions to redo these operations, thereby wasting system resources and energy.

(3) To overcome these challenges, the technical solutions utilize an image capture and recognition system to provide a reliable license plate identification, improving the traffic management, and automating resource allocation for services. In doing so, the technical solutions allow for improved automation and reduction of operational errors, resulting in resource and energy savings and improved customer satisfaction. The technical solutions can provide rapid license plate reading using character substitution for quick lookup. This system can provide image capture devices to obtain vehicle license plate images upon entry to a facility. The captured images can be processed using character recognition tools, which can include a substitution or an encoding mechanism for commonly mistaken characters (e.g., “0” for “O”, “1” for “I” or “l”). This substitution or encoding approach can allow for more efficient and improved license plate identification, even in challenging conditions, such as when plates are muddy or deformed.

(4) At least one aspect of the technical solutions is directed to a system. The system can include one or more processors, coupled with memory. The one or more processors can maintain, in a database, a plurality of vehicle profiles for a plurality of vehicles, each vehicle profile of the plurality of vehicle profiles including license plate information of a respective vehicle of the plurality of vehicles. The one or more processors can capture, via an image capture device, one or more images of at least a portion of a vehicle positioned within a region of interest of a service facility and identify, using the one or more images, a first sequence of characters of a license plate of the vehicle. The one or more processors can determine one or more characters of the first sequence of characters that satisfy a character replacement schema and generate a second sequence of characters by replacing the one or more characters that satisfy the character replacement schema with one or more corresponding replacement characters in the first sequence of characters. The one or more processors can identify, from the plurality of vehicle profiles maintained in the database, a vehicle profile of the vehicle positioned within the region of interest based on executing a query using the generated second sequence of characters and transmit, to a device, data included in the vehicle profile based on identifying the vehicle profile.

(5) In some implementations, the data transmitted to the device is data for presentation at the device and wherein the device is one of an operator device, an administrator device or a point of sale device of a third party server. To transmit, to the device, data can include the one or more processors being configured to transmit, to a car wash controller, instructions to cause the car wash to provide a car wash type corresponding to the vehicle profile of the vehicle. The one or more processors can compare, using a lookup table, the one or more characters of the first sequence with a plurality of replacement characters comprising the one or more corresponding replacement characters, match, using the comparison, the one or more characters of the first sequence with the one or more corresponding replacement characters, and determine, based on the match, that the one or more characters of the first sequence satisfies the character replacement schema. The one or more processors can select, using a lookup table configured to relate characters of license plates with replacement characters for the license plates, one or more representative character pairs corresponding to the one or more characters of the first sequence and generate the second sequence

of characters, responsive to the selection.

(6) In some implementations, the lookup table relates the one or more characters of the first sequence with the one or more corresponding replacement characters and the one or more representative character pairs include relate at least one of: a character “1” and a character “I”, a character “2” and a character “Z”, a character “5” and a character “S”, a character “0” and a character “O”, or a character “A” and a character “4”. The one or more processors can retrieve, based on the vehicle profile, a setting for a car wash routine of a vehicle service at the service facility and actuate a component controlling access to the service facility to initiate the car wash routine, based on the setting. The one or more processors can identify, based on the one or more images, a characteristic of the vehicle, compare the characteristic with one or more characteristics of the vehicle determined based on prior captured images, and detect, based on the comparison, a discrepancy between the characteristic and the one or more characteristics. The one or more processors can detect, based on the discrepancy, a fraudulent activity and generate an alert to display on a device to indicate the fraudulent activity.

(7) In some implementations, the one or more processors can determine, based on the discrepancy, that multiple vehicles have used the license plate for services of the service facility and update information on the vehicle profile responsive to the determination that the multiple vehicles have used the license plate. The one or more processors can maintain an image log of the vehicle, the image log comprising one or more prior captured images indexed according to the license plate information and compare the one or more images of the vehicle with the one or more prior captured images to detect discrepancies in vehicle characteristics. The one or more processors can identify, based on the vehicle profile, a service setting for the vehicle, generate, based on the service setting, a service to be provided to the vehicle, and provide, for display on a device, a prompt for the service to be provided. The one or more processors can receive, responsive to the prompt, an update to the service to be provided and store, in the vehicle profile, the updated service as the service setting.

(8) At least one aspect of the technical solutions is directed to a method. The method can include maintaining, by one or more processors, in a database, a plurality of vehicle profiles for a plurality of vehicles, each vehicle profile of the plurality of vehicle profiles including license plate information of a respective vehicle of the plurality of vehicles. The method can include capturing, by the one or more processors, via an image capture device, one or more images of at least a portion of a vehicle positioned within a region of interest of a service facility and identifying, by the one or more processors, using the one or more images, a first sequence of characters of a license plate of the vehicle. The method can include determining, by the one or more processors, one or more characters of the first sequence of characters that satisfy a character replacement schema and generating, by the one or more processors, a second sequence of characters by replacing the one or more characters that satisfy the character replacement schema with one or more corresponding replacement characters in the first sequence of characters. The method can include identifying, by the one or more processors, from the plurality of vehicle profiles maintained in the database, a vehicle profile of the vehicle positioned within the region of interest based on executing a query using the generated second sequence of characters and transmitting, by the one or more processors, to a device, data included in the vehicle profile based on identifying the vehicle profile.

(9) In some implementations, the method includes selecting, by the one or more processors, using a lookup table configured to relate characters of license plates with replacement characters for the license plates, one or more representative character pairs corresponding to the one or more characters of the first sequence and generating, by the one or more processors, the second sequence of characters, responsive to the selection. The lookup table can relate the one or more characters of the first sequence with the one or more corresponding replacement characters and the one or more representative character pairs include relate at least one of: a character “1” and a character “I”, a

character “2” and a character “Z”, a character “5” and a character “S”, a character “0” and a character “O”, or a character “A” and a character “4”. The method can include identifying, by the one or more processors, based on the vehicle profile, a service setting for the vehicle, generating, by the one or more processors, based on the service setting, a service to be provided to the vehicle, and providing, by the one or more processors, for display on a device, a prompt for the service to be provided. The method can include receiving, by the one or more processors, responsive to the prompt, an update to the service to be provided and storing, by the one or more processors, in the vehicle profile, the updated service as the service setting.

(10) At least one aspect of the technical solutions is directed to a non-transitory computer-readable media. The non-transitory computer-readable media includes instructions that when executed by one or more processors, can cause the one or more processors to maintain, in a database, a plurality of vehicle profiles for a plurality of vehicles, each vehicle profile of the plurality of vehicle profiles including license plate information of a respective vehicle of the plurality of vehicles. The one or more processors can be caused to capture, via an image capture device, one or more images of at least a portion of a vehicle positioned within a region of interest of a service facility and identify, using the one or more images, a first sequence of characters of a license plate of the vehicle. The one or more processors can be caused to determine one or more characters of the first sequence of characters that satisfy a character replacement schema and generate a second sequence of characters by replacing the one or more characters that satisfy the character replacement schema with one or more corresponding replacement characters in the first sequence of characters. The one or more processors can be caused to identify, from the plurality of vehicle profiles maintained in the database, a vehicle profile of the vehicle positioned within the region of interest based on executing a query using the generated second sequence of characters and transmit, to a device, data included in the vehicle profile based on identifying the vehicle profile.

(11) In some implementations, to transmit, to the device, data includes the one or more processors being configured to transmit, to a car wash controller, instructions to cause the car wash to provide a car wash type corresponding to the vehicle profile of the vehicle.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is an example block diagram of a system for automated operation platform for a vehicle service facility.

(2) FIG. 2 is an example of a data processing system of the computing environment that can be used for implementing the technical solutions.

(3) FIG. 3 is an example block diagram of a computing environment in which the data processing system and the features of the technical solutions can be implemented.

(4) FIG. 4 is an example block diagram of a system for automated vehicle recognition at service facilities.

(5) FIG. 5 is an example flow diagram of a method for automated vehicle recognition at service facilities.

(6) FIG. 6 is an example diagram of a portion of a vehicle service facility.

(7) FIGS. 7A-C are example screenshots of a user interface for automated vehicle recognition at service facilities.

DETAILED DESCRIPTION

(8) For purposes of reading the description of the various implementations below, the following descriptions of the sections of the specification and their respective contents may be helpful:

Section A describes an overview of a service facility and its computing environment. Section B describes systems and methods for automated vehicle recognition at service facilities.

(9) Vehicle service facilities, particularly automated car wash facilities, can face numerous technical challenges in maintaining energy and time efficient and error-free operations. These challenges can include reliably identifying vehicles with pre-paid services when license plates are deformed (e.g., bent), stained, or obscured, leading to license plate misidentification that trigger service disruptions and waste of system energy and resources. Additionally, facilities can struggle with automatically controlling vehicle traffic flow based on vehicle types, queues, and traffic conditions, which can result in inefficient use of resources, longer wait times and waste of resources and energy. Automating service customization based on prior data or vehicle characteristics as well as implementing effective mobile device features for facility operators can be challenging to implement, yet beneficial to such facilities. These technical hurdles can impede the operation of automated vehicle service facilities and can cause reduced energy efficiency, increased errors, and diminished customer satisfaction.

(10) To address these challenges, the technical solutions of this disclosure provide an automated platform that improves the reliability of operations of the facility at improved energy efficiency and customer satisfaction. The solutions can utilize image capture and recognition technology, which can include character image recognition or machine learning to accurately identify license plates even in challenging conditions. This improved recognition capability can reduce instances of vehicle misidentification, thus reducing down times and unnecessary gate actuation, thereby improving efficiency and conserving energy and other resources. The technical solutions can load balance and optimize vehicle flow based on traffic monitoring, reducing idle time and energy consumption of the vehicles waiting for their services. Furthermore, the technical solutions can automate service customization to identified vehicles facilitating allocation of exact resources to each individual vehicle, preventing wasteful overuse of water, soap, and electricity. The technical solutions can provide a mobile device application with features that can allow operators to improve their ability to monitor and control facility operations remotely, reducing the need for constant on-site presence and associated resource inefficiencies. As a result, the technical solutions allow for operating of a more energy-efficient, environmentally friendly, and cost-effective vehicle service facility, than was the case with vehicle service systems.

(11) A. Overview of a Service Facility Computing Environment

(12) The system of the technical solutions can include a computing environment having any combination of hardware and software for providing automated vehicle recognition at service facilities.

(13) FIG. 1 illustrates an example block diagram of a facility **100**, which can be referred to as a facility system or an environment, for providing a service to vehicles **130** or vehicle drivers. The facility **100** can include any combination of an indoor or outdoor area of a facility, space or a structure (e.g., a building) that can be configured or used as a location for deploying service systems, such as a car wash tunnel system **105** configured to provide services, such as car wash services, to vehicles **130** or their drivers. The facility **100** can include one or more outdoor areas that can include pathways or lanes **134** for directing or controlling the vehicles **130** arriving for service to be performed by the service system, such as the car wash tunnel system **105**, at which the vehicle services are provided. The facility **100** can be, or include any type of a service facility, such as a car wash facility, a vehicle technical or a maintenance service facility (e.g., a system-based or automated oil change establishment), a fast food restaurant with a drive through for servicing drivers in the vehicles, an automated parking garage, a gas station, an event venue (e.g., a sports stadium) having vehicle parking centers, or any other facility managing or providing services involving vehicles or their drivers (e.g., drivers).

(14) The facility **100** can include one or more of car wash tunnel systems **105** that can have one or more tunnels **140** with service equipment **110** configured to provide vehicle services, such as car washing, to various vehicles **130** passing through the tunnel **140**. Each tunnel **140** can include one or more conveyor systems **116** over or onto which the vehicles **130** can be transported, passed or

moved. For instance, a vehicle **130N** identified by a license plate **132N** can be coupled or latched with the conveyor system **116** and moved, pushed or passed through the tunnel **140** as the service equipment **110** of the car wash tunnel system **105** provides automated car wash service. The car wash tunnel system **105** can include one or more car wash controllers **104** for controlling the one or more service equipment **110**, which can include, for example, various car wash machines **112** and resource dispensers **114** for performing the automated car wash operations.

(15) The facility **100** can include one or more lanes **134** for directing vehicle traffic towards the car wash tunnel system **105**. For example, a facility **100** can include an external or outdoor space having a first lane **134A** on which a first vehicle **130A** identified by a first license plate **132A** can move towards a first gate **160A**. The facility **100** can include a second lane **134B** on which a second vehicle **130B** identified by a second license plate **132B** can move towards a second gate **160B**. The first lane **134A** can include or encompass a first region of interest **135A** that can be viewed, recorded or monitored by a first gate camera **120A** capturing images or videos of the vehicle **130A** as this vehicle approaches or passes the gate **160A** controlling this vehicle's access to a queue **142** for entering tunnel **140** of the car wash tunnel system **105**. Similarly, the lane **134B** can include a second region of interest **135B** that can be recorded or monitored by a second gate camera **120B** capturing images or videos of the vehicle **130B** as it approaches or passes the gate **160B** controlling this vehicle's access to the queue **142**.

(16) The facility can include one or more quick response (QR) codes **166**, which can be deployed at any location in the facility environment (e.g., along or adjacent to lanes **134**, gates **160** or a structure housing a car wash tunnel system **105**). A QR code **166** can include any two-dimensional barcode that can store or represent data such as URLs, text, or other types of information that can be read by a smartphone of a driver of the vehicle **130** or other QR code reader. When a user (e.g., a driver) takes a picture of the QR code **166** or otherwise captures the QR code with their mobile device, the QR code **166** can (e.g., include data) be used to cause the mobile device of the user to open an application or a webpage corresponding to the QR in which the user can select services to utilize, change their service type (e.g., monthly or annual subscription), and configure particular services (e.g., polishing of the vehicle, special type of washing service). The QR code **166** can be used to facilitate interaction between the user and the service provider, improving the user experience by providing an efficient way to access and manage services.

(17) The gate cameras **120** and the gates **160** can be communicatively coupled with a data processing system **118**, via one or more networks **101** of the facility system **100**. The network **101** can communicatively couple and provide communication medium for one or more operator devices **150** executing applications **152**, one or more third party servers **190** executing third party services (e.g., transaction operations) and one or more administrative devices **162** for providing administrative overview and services to the facility system **100**. The network **101** can provide, enable, or otherwise facilitate the connections for communications between the data processing system **118** and gate cameras **120** to provide images or videos of the vehicles **130** and their license plates **132** to the data processing system to identify the service according to the entity profiles associated with the vehicles **130**.

(18) Facility **100** can include any combination of an indoor or outdoor area of a facility, space, or structure configured for deploying service systems, such as a car wash tunnel system **105**. Facility **100** can be a car wash facility, a vehicle maintenance service facility, a fast food restaurant with a drive-through, an automated parking garage, a gas station, or an event venue with vehicle parking centers. Facility **100** can include pathways or lanes **134** for directing vehicles **130** arriving for service to be performed by the service system, such as car wash tunnel system **105**. For instance, facility **100** can have outdoor areas with lanes **134** guiding vehicles **130** towards car wash tunnel system **105**. Facility **100** can manage or provide services involving vehicles or their drivers, such as drivers. Facility **100** can include regions of interest **135** monitored by gate cameras **120** to capture images or videos of vehicles **130** as they approach or pass gates **160**. Facility **100** can be

communicatively coupled with data processing system **118**, operator devices **150**, third party servers **190**, and admin devices **162** via network **101**.

(19) The facility **100** can include a building, a structure, or a service center at which vehicles **130** are cleaned, serviced, upgraded, or repaired or at which drivers of the vehicles receive services. The facility **100** can include, for example, exits and entrances, wash lanes, a wash tunnel, service bays, staffing, sensors, wash components, automated kiosks, among others to provide a service to a customer in the content of a washing, or any other, service. The facility **100** can include systems or processes, involving for example, service equipment **110** data processing systems **118**, which can be overseen, managed, run, or otherwise controlled by operators, which can be authorized personnel, such as users of the operator devices **150** or admin device **162**. The operators can include workers, technicians, managers, administrators, among other authorized personnel.

(20) Car wash tunnel system **105** can include one or more tunnels **140** with service equipment **110** configured to provide vehicle services, such as car washing services. For example, car wash tunnel system **105** can have tunnels **140** with conveyor systems **116** over which vehicles **130** can be moved, guided or transported. Car wash tunnel system **105** can include car wash controllers **104** for controlling service equipment **110**, which can include car wash machines **112** and resource dispensers **114**. For instance, a vehicle **130** identified by a license plate **132** can be coupled with conveyor system **116** and moved through tunnel **140** as service equipment **110** provides automated car wash service. For instance, upon identifying a vehicle **130A**, the car wash tunnel system **105** can be instructed to apply a particular set of car wash operations by the service equipment **110** in accordance with the settings or configurations for the account of the vehicle. Car wash tunnel system **105** can perform various automated car wash operations using car wash machines **112** and resource dispensers **114**. Car wash tunnel system **105** can be deployed within a building or a structure at a facility **100**, which can be accessed via lanes **134** and gates **160** controlling the flow of vehicles **130** to the tunnel **140**. Car wash tunnel system **105** can be communicatively coupled with data processing system **118** to receive instructions for controlling service equipment **110**.

(21) Car wash controller **104** can include any combination of hardware and software for controlling service equipment **110** in car wash tunnel system **105**. For example, car wash controller **104** can control car wash machines **112** and resource dispensers **114** to perform automated car wash operations. Car wash controller **104** can receive instructions from data processing system **118** to execute car wash routines based on vehicle features and license plate information. Car wash controller **104** can selectively control the deployment of car wash actuation components based on vehicle features identified from images captured by gate cameras **120** and tunnel cameras **122**. For instance, car wash controller **104** can control the application of fluids or physical contact materials onto the vehicle during the car wash routine. Car wash controller **104** can be communicatively coupled with car wash tunnel system **105**, data processing system **118**, and other components of facility **100** via network **101**. Car wash controller **104** can control the service equipment **110** to perform the car was services according to car was types designated or dedicated to the operator device. The car wash controller **104** can ensure that the car wash service is performed according to the service request generated by data processing system **118**.

(22) Service equipment **110** can include any combination of devices and machinery configured to provide vehicle services in car wash tunnel system **105**. For example, service equipment **110** can include car wash machines **112**, such as brush rollers, high pressure washers and drying blowers, as well as resource dispensers **114**, such as soap and water dispensers, wax dispensers or tire shine dispensers, each of which can be utilized for performing automated car wash operations. Service equipment **110** can be controlled by car wash controller **104** to execute car wash routines based on vehicle features and license plate information. For instance, service equipment **110** can include brushes, sprayers, and dryers that clean and dry the vehicle as it passes through tunnel **140**. Service equipment **110** can be configured to apply fluids or physical contact materials onto the vehicle during the car wash routine. Service equipment **110** can be part of car wash tunnel system **105** and

can be accessed via lanes **134** and gates **160**. Service equipment **110** can be communicatively coupled with car wash controller **104** and data processing system **118** to receive instructions for performing car wash operations.

(23) Car wash machines **112** can include any combination of mechanical devices configured to perform automated car wash operations in car wash tunnel system **105**. For example, car wash machines **112** can include automated machinery, such as brushes, rollers, and sprayers that clean the vehicle as the vehicle **130** passes through tunnel **140**. Carwash machines **112** can include brush rollers, high-pressure washers, foam applicators, undercarriage washers, wheel cleaners, drying blowers, polishers, wax applicators and tire shiners. Car wash machines **112** can be arranged or deployed within or along the tunnel **140** to provide their designated operations or services to the vehicles **130** passing down the conveyor system **116**. Car wash machines **112** can be controlled by car wash controller **104** to execute car wash routines based on vehicle features and license plate information. For instance, car wash machines **112** can apply soap, water, and wax to the vehicle during the car wash routine. Car wash machines **112** can be part of service equipment **110** and can be accessed via lanes **134** and gates **160**. Car wash machines **112** can be configured to selectively control the application of fluids or physical contact materials onto the vehicle based on instructions from car wash controller **104**. Car wash machines **112** can be communicatively coupled with car wash controller **104** and data processing system **118** to receive instructions for performing car wash operations.

(24) Resource dispenser **114** can include any combination of devices configured to dispense resources, such as fluids, energy or materials, during the car wash routine in car wash tunnel system **105**. For example, resource dispenser **114** can include automated dispensers of resources, including sprayers, nozzles, and dispensers that apply soap, water, and wax to the vehicle **130**. Resource dispensers **114** can include dispensers for soap, water, wax, foam, tire shine, polish, spot-free rinse, conditioners, sealants, air, including heated air or any other resource used for vehicle service. Resource dispenser **114** can be controlled by car wash controller **104** to execute car wash routines based on vehicle features and license plate information. For instance, resource dispenser **114** can selectively control the application of fluids onto the vehicle during the car wash routine. Resource dispenser **114** can be part of service equipment **110** and can be accessed via lanes **134** and gates **160**. Resource dispenser **114** can be configured to apply fluids or materials onto the vehicle based on instructions from car wash controller **104**. Resource dispenser **114** can be communicatively coupled with car wash controller **104** and data processing system **118** to receive instructions for performing car wash operations.

(25) Tunnel **140** can include any combination of structures and pathways configured to guide vehicles **130** through car wash tunnel system **105**. The tunnel **140** can include a conveyor system **116** or a conveyor belt on which vehicles **130** can be moved, pushed or transported as the car washing is provided by the service equipment **110**. Tunnel **140** can include any configurations or arrangements of service equipment **110**, such as car wash machines **112** and resource dispensers **114**, positioned to provide automated car wash services. For instance, a vehicle **130** identified by a license plate **132** can be coupled with conveyor system **116** and moved through tunnel **140** as service equipment **110** can provide automated car wash services to the vehicle. Tunnel **140** can be part of car wash tunnel system **105** and can be accessed via lanes **134** and gates **160**. Tunnel **140** can be configured to guide vehicles **130** through the car wash process based on instructions from car wash controller **104**. Tunnel **140** can be communicatively coupled with car wash controller **104** and data processing system **118** to receive instructions for performing car wash operations.

(26) Conveyor system **116** can include any combination of structures and pathways configured to transport vehicles **130** through tunnel **140** in car wash tunnel system **105**. The conveyor system **116** can include conveyor belts, tracks, or rollers that move vehicles **130** through tunnel **140**. Conveyor system **116** can be controlled by car wash controller **104** to execute car wash routines based on vehicle features and license plate information. For instance, a vehicle **130** identified by a license

plate **132** can be coupled with conveyor system **116** and moved through tunnel **140** as service equipment **110** provides car wash services. Conveyor system **116** can be part of tunnel **140** and can be accessed via lanes **134** and gates **160**. Conveyor system **116** can be configured to transport vehicles **130** through the car wash process based on instructions from car wash controller **104**. Conveyor system **116** can be controlled by a car wash controller **104** allowing vehicles **130** from the queue **142** to enter the tunnel **140**. For instance, a conveyor system **116** can be communicatively coupled with a car wash controller **104** or a data processing system **118** to receive instructions to allow vehicles **130** to access or enter the tunnel **140** to receive the services by the car wash tunnel system **105**. The conveyor system **116** can include or be coupled with one or more processors that can control one or more components of the conveyor system **116**, such as a conveyor belt. The one or more processors can execute one or more instructions to cause the conveyor system **116** to move or propagate a vehicle **130** through the tunnel **140**. The conveyor system **116** can include a ramp onto which a vehicle can be driven. The conveyor system **116** can include a conveyor belt mechanism pulling, guiding or moving a vehicle **130** in response to an instruction that the vehicle **130** is to be propagated through the tunnel **140**. This can be done, for example, in response to updates to the queue of the car wash tunnel system **105**.

(27) Vehicle **130** can include any type of vehicle that can receive services at facility **100**. For example, vehicle **130** can be a car, truck, van, or a motorcycle. Vehicle **130** can be identified by a license plate **132** and can be directed through lanes **134** towards car wash tunnel system **105**. For instance, a vehicle **130** identified by a license plate **132** can be coupled with conveyor system **116** and moved through tunnel **140** as service equipment **110** provides car wash services. Vehicle **130** can be monitored by gate cameras **120** and tunnel cameras **122** to capture images or videos of the vehicle and its license plate **132**. Vehicle **130** can be part of queue **142** and can receive car wash services based on instructions from car wash controller **104**. Vehicle **130** can be communicatively coupled with data processing system **118** to receive services according to the entity profiles associated with the vehicle.

(28) License plate **132** can include any plate having a combination of characters or symbols to identify a vehicle **130**. For example, a license plate **132** can include alphanumeric characters that uniquely identify a vehicle **130** from a plurality of other vehicles **130**. License plate **132** can be captured by gate cameras **120** and tunnel cameras **122** and its characters can be used for identifying the account or profile associated with the vehicle **130**. The profile or account identified based on the characteristics of the license plate **132** can identify user information, vehicle information or for instance, a vehicle **130** identified by a license plate **132** can be coupled with conveyor system **116** and moved through tunnel **140** as service equipment **110** provides car wash services. License plate **132** can be used by data processing system **118** to identify the vehicle profile and generate a car wash service request. License plate **132** can be part of the vehicle profile stored in data processing system **118**. License plate **132** can be used to determine the identity of the vehicle **130** based on images captured by gate cameras **120** and tunnel cameras **122**.

(29) Gate camera **120** can include any combination of hardware and software for capturing images or videos of vehicles **130** and their license plates **132**. For example, gate camera **120** can be positioned at the entrance of facility **100** to capture images of vehicles **130** as they approach or pass gates **160**. Gate camera **120** can be directed towards region of interest **135**, such as a portion of a lane **134** or an area of the lane **134** before a gate **160** barring the vehicle **130** from accessing the car wash tunnel system **105**. The gate camera **120** can include a license plate recognition (LPR) camera, including for example at or near a traffic lane **134**, at or near a tunnel **140** to facilitate in recognizing license plates **132**. Gate camera **120** can be used to identify vehicle features (e.g., colors, shapes, sizes, add-ons or other structures) of vehicles **130** approaching or entering facility **100** or the car wash tunnel system **105**. For instance, gate camera **120** can capture images of a vehicle **130** identified by a license plate **132** and transmit the images to data processing system **118**. The data processing system **118** can process the images and manage the camera. Gate camera **120**

can be communicatively coupled with data processing system **118** to provide images or videos of vehicles **130** and their license plates **132**. Gate camera **120** can be used to monitor regions of interest **135** and capture images of vehicles **130** as they enter or merge from various lanes **134** into a queue **142**. Gate camera **120** can be coupled with the network **101** of facility system **100** and can provide images for identifying the service to the operator devices **150** according to the entity profiles associated with vehicles **130**.

(30) Tunnel camera **122** can include any combination of hardware and software for capturing images or videos of vehicles **130** and their license plates **132** at or near an entrance of a tunnel **140** or within the tunnel **140**. For example, tunnel camera **122** can be positioned or directed to a region of interest **135** at an entrance of a tunnel **140** (e.g., at an entrance to the car wash tunnel system **105** building or a structure). The tunnel camera **122** can include a license plate recognition (LPR) camera, including for example at or near a traffic lane **134**, at or near a tunnel **140** to facilitate in recognizing license plates **132**. The tunnel camera **122** can be positioned inside tunnel **140** to capture images of vehicles **130** as they pass through car wash tunnel system **105**. Tunnel camera **122** can be used to identify the license plate **132** and vehicle features of vehicles **130** receiving car wash services. For instance, tunnel camera **122** can capture images of a vehicle **130** identified by a license plate **132** and transmit the images to the data processing system **118**. The data processing system **118** can process the images and manage the camera. Tunnel camera **122** can be communicatively coupled with data processing system **118** to provide images or videos of vehicles **130** and their license plates **132**. Tunnel camera **122** can be used to monitor the vehicles **130** forming the queue **142** as well as observe the car wash process and capture images of vehicles **130** as they move into or through the tunnel **140**. Tunnel camera **122** can be coupled with the network **101** of facility system **100** and can provide images for identifying the service according to the entity profiles associated with vehicles **130**.

(31) Queue **142** can include any order or arrangements of vehicles **130** in a line leading into the tunnel **140** of the car wash tunnel system **105**. For example, queue **142** can include an order or arrangement of a plurality of vehicles, one following the other, as the vehicles are lined up to enter the tunnel **140**. The vehicles **130** can arrive to the queue **142** from lanes **134**, as managed or permitted to access by the gates **160** tunnel **140**. Queue **142** can be controlled by a data processing system **118** via a car wash controller **104** to manage the entry of vehicles **130** to the tunnel **140** using control of the gates **160**. For instance, a vehicle **130** identified by a license plate **132** can be permitted to proceed to the queue **142** by controlling the gate **160** to allow the vehicle **130** to access the queue **142**. The data processing system **118** can maintain the queue **142** representation (e.g., vehicle order) using images from the cameras **120** or **122**. The queue **142** can be monitored by both the gate cameras **120** and tunnel cameras **122** to keep track of any changes to the queue **142**, using features for recognizing license plates **132**. Queue **142** can be maintained and managed by the data processing system **118** to ensure that each vehicle receives its own designated service.

(32) Lanes **134** can include any combination of pathways and structures configured to direct vehicle traffic towards car wash tunnel system **105**. For example, lanes **134** can include outdoor areas with pathways guiding vehicles **130** towards gates **160** and tunnel **140**. Lanes **134** can be used to manage the flow of vehicles **130** arriving for service at facility **100**. For instance, lanes **134** can include a first lane **134A** guiding a first vehicle **130A** identified by a first license plate **132A** towards a first gate **160A**. Lanes **134** can include a second lane **134B** guiding a second vehicle **130B** identified by a second license plate **132B** towards a second gate **160B**. Lanes **134** can include regions of interest **135** monitored by gate cameras **120** to capture images or videos of vehicles **130** as they approach or pass gates **160**. Lanes **134** can be part of facility **100** and can be accessed via pathways and outdoor areas. Lanes **134** can be communicatively coupled with data processing system **118** to manage the flow of vehicles **130** towards the car wash tunnel system **105**. It should be appreciated that lanes can include any pathway on which vehicles can move and the lanes may not be defined using barriers or other physical structures or demarcations. It should also be

understood that the lanes may not directly guide or direct the vehicles.

(33) Gates **160** can include any combination of structures and mechanisms configured to control the access of vehicles **130** to queue **142** and tunnel **140** in car wash tunnel system **105**. For example, gates **160** can include barriers, turnstiles, visible indicators/lights, or electronic gates that regulate the entry of vehicles **130**. Gates **160** can be controlled by car wash controller **104** to manage the access of vehicles **130** based on vehicle features and license plate information. For instance, a vehicle **130** identified by a license plate **132** can be allowed to pass through gate **160** and enter queue **142** based on instructions from car wash controller **104**. The instructions can be generated based on a successful processing of a transaction by the third party server **190** operating as a point of sale (POS) device for the facility **100**. Gates **160** can be monitored by gate cameras **120** to capture images or videos of vehicles **130** as they approach or pass the gates. Gates **160** can be part of facility **100** and can be accessed via lanes **134** and pathways. Gates **160** can be communicatively coupled with data processing system **118** to control the access of vehicles **130** to queue **142** and tunnel **140** based on instructions from car wash controller **104**.

(34) Regions of interest **135** can include any areas and zones within facility **100** that are monitored or recorded by cameras, such as for capturing images or videos of vehicles **130**. For example, regions of interest **135** can include areas near gates **160**, lanes **134**, and tunnel **140**. Regions of interest **135** can be monitored by gate cameras **120** and tunnel cameras **122** to capture images or videos of vehicles **130** and their license plates **132**. For instance, a region of interest **135A** can be viewed by a gate camera **120A** capturing images of a vehicle **130A** identified by a license plate **132A** as it approaches gate **160A**. Regions of interest **135** can be used to identify vehicle features and license plate information for generating car wash service requests. Regions of interest **135** can be part of facility **100** and can be accessed via pathways and outdoor areas. Regions of interest **135** can be communicatively coupled with data processing system **118** to provide images or videos of vehicles **130** for identifying the service according to the entity profiles associated with the vehicles.

(35) Data processing system **118** can include any combination of hardware and software for processing data and managing the operations of facility **100**. Data processing system **118** can include one or more computing environments, servers, databases, and applications for storing and processing vehicle profiles, license plate information, and service requests. The data processing system **118** can be any computing device, collection of servers, data centers, among others, which include one or more processors coupled with memory storing instructions and data configured to implement or complete the tasks and processes described herein. The data processing system **118** can be electrically coupled to each of the components within the service facility **100** to control or monitor the reception and transmission of different data or signals within the service facility **100**. The data processing system **118** can be deployed or provided within building or a structure housing the car wash tunnel system **105**, or outside of it, such on a cloud based system, including a Software as a Service (SaaS). The data processing system **118** can be connected to the devices **150** via the network **101** (e.g., the internet or a Wi-Fi network).

(36) Data processing system **118** can be used to identify vehicle features and generate car wash service requests based on images captured by gate cameras **120** and tunnel cameras **122**. Data processing system **118** can receive images of a vehicle **130** identified by a license plate **132** and generate a car wash service request based on the vehicle profile. Data processing system **118** can be communicatively coupled with car wash controller **104**, gate cameras **120**, tunnel cameras **122**, operator devices **150**, third party servers **190**, and admin devices **162** via network **101**. Data processing system **118** can manage the operations of facility **100** by processing data and providing instructions for performing car wash operations, including sending instructions to car wash controller **104** to adjust, manage or operate various services equipment **110**. Data processing system **118** can ensure that the car wash service is performed according to the service request generated based on the entity profiles associated with the vehicles **130**.

(37) Admin device **162** can include any combination of hardware and software for providing

administrative overview and services to the facility system **100** or any of its components (e.g., data processing system **118**, operator devices **150**. For example, admin device **162** can include computers, tablets, or smartphones used by administrators to monitor and manage the operations of facility **100**. Admin device **162** can be used to access data processing system **118**, car wash controller **104**, and other components of facility **100**. For instance, admin device **162** can be used to view images or videos captured by gate cameras **120** and tunnel cameras **122**, monitor the status of queue **142**, and manage the flow of vehicles **130** through lanes **134** and gates **160**. Admin device **162** can be communicatively coupled with data processing system **118**, operator devices **150**, and third party servers **190** via network **101**. Admin device **162** can provide administrative services such as updating vehicle profiles, generating reports, and managing entity profiles. Admin device **162** can ensure that the operations of facility **100** are performed efficiently and according to the service requests generated based on the entity profiles associated with the vehicles **130**.

(38) Third party servers **190** can include any combination of hardware and software for executing third party services, such as transactions or POS operations for the facility system **100**. For example, third party servers **190** can include servers, databases, and applications used by third party service providers to process transaction operations (e.g., exchange and validate credit card payment data of drivers of the vehicles), manage entity profiles, and provide additional services. Third party servers **190** can be used to execute transaction operations based on the service requests generated by data processing system **118**. For instance, third party servers **190** can process payments for car wash services provided to vehicles **130** identified by license plates **132**. Third party servers **190** can be communicatively coupled with data processing system **118**, operator devices **150**, and admin devices **162** via network **101**. Third party servers **190** can provide additional services such as loyalty programs, promotions, and customer support. Third party servers **190** can ensure that the transaction operations and additional services are performed according to the service requests generated based on the entity profiles associated with the vehicles **130**.

(39) Operator devices **150** can include any combination of hardware and software used by operators of the facility **100** to interact with the facility system **100**. Operator devices **150** can include smartphones, tablets, laptops, or desktop computers operated by users, such as employees or service providers of the facility **100**. Operator devices **150** can execute applications **152** that allow users to access services provided by facility **100**, including scheduling car wash services, providing attention to entity accounts of the drivers of the vehicles **130** or managing vehicle data or gate access at gates **160**. For example, a user (e.g., an operator) can use a mobile application executing on an operator device **150** to access a graphical user interface to review the state of the lanes **134** or to schedule a car wash service for a vehicle **130** identified by a license plate **132**. Operator devices **150** can be communicatively coupled with data processing system **118**, car wash controller **104**, and third party servers **190** (e.g., POS devices) via one or more networks **101**. Operator devices **150** can receive and display data from data processing system **118** or gate cameras **120** and tunnel cameras **122**, including images or videos of the vehicles at various lanes **134** and display this data to the user via a graphical user interface (GUI) of the operator device **150**. Operator devices **150** can transmit data to data processing system **118**, such as service requests or updates to entity accounts. Operator devices **150** can provide users with a convenient way to access and manage the services or vehicle data utilized at the facility **100**.

(40) Applications **152** can include any combination of software programs executed on operator devices **150** to provide users (e.g., operators or employees of the facility) with access to the services of facility system **100**. For example, applications **152** can include mobile applications, web applications, or desktop applications. Applications **152** can provide graphical user interfaces (GUIs) that allow users to interact with the services provided by facility **100**. For instance, a mobile application **152** can present a GUI that displays data objects representing vehicles **130** in different lanes **134**, including images and license plate information of the vehicles **130**. Applications **152** can

allow users to schedule car wash services, manage client accounts, and view the status of their vehicles **130**. Applications **152** can be communicatively coupled with data processing system **118**, car wash controller **104**, and third party servers **190** via network **101**. Applications **152** can receive data from data processing system **118**, such as service requests or updates to vehicle profiles, and display this data to the user. Applications **152** can provide a GUI to the user to generate or select instructions, such as an instruction to open a gate **160**, or provide notifications, such as a notification that a particular vehicle **130** in a particular lane **134** is receiving assistance for a pending issue. Applications **152** can provide users with a user-friendly interface to access and manage the services provided by facility **100**.

(41) Network **101** can include any combination of wired and wireless network types and connections for facilitating communication within facility system **100**. For example, network **101** can include wired connections such as Ethernet cables, fiber optic cables, and coaxial cables to provide high-speed and reliable data transmission between components like data processing system **118**, car wash controller **104**, and third party servers **190**. Network **101** can include wireless connections such as Wi-Fi, Bluetooth, and cellular networks to enable flexible and convenient communication with operator devices **150** and admin devices **162**. For instance, Wi-Fi can be used to connect gate cameras **120** and tunnel cameras **122** to data processing system **118**, allowing for real-time transmission of images and videos of vehicles **130** and their license plates **132**. Network **101** can support various network protocols and standards to ensure seamless integration and interoperability between different components of facility system **100**. Additionally, network **101** can provide secure and encrypted communication channels to protect sensitive data and ensure the privacy of client accounts associated with vehicles **130**. By incorporating both wired and wireless connections, network **101** can offer a robust and versatile infrastructure for managing the operations of facility **100**.

(42) FIG. 2 illustrates an example system **200** for implementing the technical solutions of the facility system **100**. The example system **200** can include a computing environment for implementing various functionalities of the technical solutions, such as automated vehicle license plate recognition, service facility queue adjustment based on a queue of a remote application, graphical user interface based management of vehicle lanes traffic at service facilities, or automated control of car wash services. The example system **200** can include one or more data processing systems **118**, operator devices **150**, third party servers **164** and car wash tunnel systems **105** that can be configured to communicate with each other via a network **101**.

(43) A data processing system **118** can include one or more of camera managers **206** to manage image capture devices, such as gate cameras **120** or tunnel cameras **122** to capture image or video data for processing by the data processing system. The data processing system **118** can include one or more of license plate processors **202** to apply image recognition to images captured by the cameras **120**. A license plate processor **202** and a camera manager **206** can utilize machine learning to identify license plate characters or specific vehicle characteristics, as well as implement character replacement schema functionalities to utilize replacement characters to more reliably and efficiently identify license plates **132** for various vehicles **130**.

(44) The data processing system **118** can include one or more of profile managers **204** for managing profiles of vehicles or entities (e.g., data on vehicles and drivers), which can be used to facilitate automation of vehicle services customized for individual vehicles or drivers. The data processing system **118** can include one or more car wash service managers **208** for providing or managing car wash routines for different types of car wash services, based on the vehicle **130** (e.g., identified using a license plate processor **202**) or entity profiles (e.g., data of the specific vehicle specifying car wash routines or preferences for the vehicle).

(45) The data processing system **118** can include one or more queue managers **210** for monitoring or managing queues **142** (e.g., queues of the car wash tunnel system **105**) to ensure that the designated vehicles **130** receive their intended and assigned services. A queue manager **210** can

utilize machine learning and integrate with the license plate processor **202** and the camera manager **206** to track individual vehicles **130** at the facility and continuously update the vehicle queue to track the vehicles entering the tunnel **140** and maintain the order of their corresponding car wash routines.

(46) The data processing system **118** can include one or more graphical user interface (GUI) managers **212** for managing graphical user interfaces (GUIs) **250** of the applications **152** executing on operator devices **150**. The GUIs **250** can be configured to provide updated information on vehicles passing through the facility, including keeping track of vehicles **130** at the lanes **134** and facilitating timely and efficient management addressing of issues among the operators (e.g., facility staff) of the operator devices **150**. The data processing system **118** can include one or more log managers **214** for generating and maintain logs or reports for the given services, as well as one or more communication interfaces **216** for facilitating interfacing or communication with other components of the system **200**, such as via the network **101**. The log manager **214** can log vehicle visits to the facility, maintain a series of videos or images of the vehicles **130** utilized during the visits and provide data on the vehicle over time. The data processing system **118** can include one or more machine learning (ML) frameworks **220** that can include one or more ML models **222** that can be trained by one or more ML trainers **224** to perform various tasks or operations of the data processing system components, such as for example license plate data recognition of a license plate processor **202** or vehicle identification for maintaining a queue of a queue manager **210**.

(47) An operator device **150** can be used by an operator (e.g., an employee of the facility) and execute one or more applications **152** having one or more GUIs **250** that can allow the operators to monitor the statuses of the lanes **134** or the vehicles **130** and timely address any pending issues. The issues may involve or relate to, for example, operation functions **260**, such as POS transactions that can be executed via third party servers **164** (e.g., POS terminals) which the vehicle drivers may utilize to access or setup car wash services. The operation function **260** can include or provide operations for processing a credit card transaction or triggering a billing action of an account associated with the vehicle. The car wash tunnel system **105** can be controlled, managed, monitored or operated by the data processing system **118** or operator devices **150** to improve the system operation or facilitate the timely execution of operation functions **260**.

(48) ML framework **220** can include any combination of hardware and software for providing or implementing any type and form of ML or artificial intelligence (AI) functionalities of the data processing system. The ML framework **220** can manage and provide ML trainers **224** for training ML models **222** to perform functionalities of any of the components of the data processing system **118** (e.g., license plate processor **202**, license plate data manager **426**, camera manager **206**, queue manager **210**, or any other data processing system component or feature). For example, an ML framework **220** can utilize an ML trainer **224** to train an ML model **222** to detect, determine or identify license plate data or vehicle characteristics or features in order to identify vehicles. The ML trainers **224** can train the ML models **222** to detect updates in the order of vehicles in a queue entering a tunnel **140** of a car wash facility, thereby maintaining a correct representation of the order vehicles entering the car wash tunnel. ML models **222** can be trained to select or arrange one or more (e.g., a sequence of) car wash routines for implementing a particular (e.g., customized or desired) car wash service to the vehicle, based on the vehicle data or profile preferences.

(49) The ML models **222** can include any combination of one or more neural networks, decision-making models, linear regression models, natural language models, random forests, classification models, generative AI models, reinforcement learning models, clustering models, neighbor models, decision trees, probabilistic models, classifier models, or other such models. For example, the models **222** include natural language processing (e.g., support vector machine (SVM), Bag of Words, Counter Vector, Word2Vec, k-nearest neighbors (KNN) classification, long short term memory (LSTM)), object detection and image identification models (e.g., mask region-based convolutional neural network (R-CNN), CNN, single shot detector (SSD), deep learning CNN with

Modified National Institute of Standards and Technology (MNIST), RNN based long short term memory (LSTM), Hidden Markov Models, You Only Look Once (YOLO), LayoutLM) (classification and clustering models (e.g., random forest, XGBoost, k-means clustering, DBScan, isolation forests, segmented regression, sum of subsets 0/1 Knapsack, Backtracking, Time series, transferable contextual bandit) or other models such as named entity recognition, term frequency-inverse document frequency (TF-IDF), stochastic gradient descent, Naïve Bayes Classifier, cosine similarity, multi-layer perceptron, sentence transformer, data parser, conditional random field model, Bidirectional Encoder Representations from Transformers (BERT), among others.

(50) The ML models **222** can include generative AI models, also referred to as generative AI models **222**, which can include any machine learning systems configured to create new content, such as text, images, or audio, by learning patterns from the data stored in a storage or a database (e.g., training datasets). The generative AI models **222** can be trained using techniques, such as supervised learning, unsupervised learning, and reinforcement learning. Generative AI models **222** can utilize data set from the stored data to create logical inferences between various complex structures in the data set to generate coherent outputs for prompts input into the models **222**.

(51) The ML models **222** implemented as generative AI models can include any machine learning (ML) or artificial intelligence (AI) model designed to generate content or new content, such as text, images, or code, by learning patterns and structures from existing data. Such ML model **222** (e.g., a generative AI models) can include any model, a computational system or an algorithm that can learn patterns from data (e.g., chunks of data from various input images, videos, documents, computer code, templates, forms, etc.) and make predictions or perform tasks without being explicitly programmed to perform such tasks. The generative AI model **222** can include, utilize or refer to a large language model. The generative AI model **222** can be trained using a dataset of documents (e.g., text, images, videos, audio or other data). The generative AI model **222** can be designed to understand and extract relevant information from the dataset. The generative AI model **222** can leverage natural language processing techniques and pattern recognition to comprehend the context and intent of a prompt (e.g., one or more instructions), which can be used as input into the ML model **222** to trigger the desired output or result.

(52) The ML model **222**, including for example a generative AI model, can be designed, constructed, utilize or include a transformer architecture with one or more of a self-attention mechanism (e.g., allowing the model to weigh the importance of different words or tokens in a sentence when encoding a word at a particular position), positional encoding, encoder and decoder (multiple layers containing multi-head self-attention mechanisms and feedforward neural networks). For example, each layer in the encoder and decoder can include a fully connected feed-forward network, applied independently to each position. The data processing system **118** can apply layer normalization to the output of the attention and feed-forward sub-layers to stabilize and improve the speed with which the generative AI model **222** is trained. The data processing system **118** can leverage any residual connections to facilitate preserving gradients during backpropagation, thereby aiding in the training of the deep networks. Transformer architecture can include, for example, a generative pre-trained transformer, a bidirectional encoder representations from transformers, transformer-X L (e.g., using recurrence to capture longer-term dependencies beyond a fixed-length context window), text-to-text transfer transformer,

(53) ML trainers **224** can include any combination of hardware and software for training ML models **222**. ML trainers **224** can use datasets including images, videos, documents or character strings to identify, detect or monitor license plate data, vehicle data, user data, vehicle queues or any other set of information handled by the data processing system **118**. Through training, a generative ML model **222**, also referred to as a generative AI model **222**, can learn or adjust its understanding of mapping embeddings to particular issues (e.g., vehicle features or characteristics identified via images), by adjusting its internal parameters. For example, the model **222** can be trained using datasets comprising vehicle or license plate data. The internal parameters can include

numerical values of a generative AI model that the model learns and adjusts during training to optimize its performance and make more accurate predictions. Such training can include iteratively presenting the various data chunks or documents of the dataset (e.g., or their chunks, embeddings) to the generative AI model **222**, comparing its predictions with the known correct answers, and updating the model's parameters to minimize the prediction errors. By learning from the embeddings of the dataset data chunks, the generative AI model **222** can gain the ability to generalize its knowledge and make accurate predictions or provide relevant insights when presented with prompts.

(54) FIG. **3** illustrates an example block diagram of a computing environment **300**, also referred to as a computing or a computer system **300**, using which any of the computational components of the example system **200** can be implemented. For instance, the computing environment **300** can be utilized to implement or execute any portion of a data processing system **118**, an operator device **150**, a third party server **190** or a car wash tunnel system **105**. Computer system **300** can include or be used to implement any computation or processing (e.g., operation, command, protocol, or data processing) described herein, including any component of a data processing system **118**. For instance, instructions, computer code or data stored in memories of the computing system **300** (e.g., **315**, **320** or **325**) can be utilized to configure processors of the computing system (e.g., **310**) to execute any of the functionalities of the data processing system **118** described herein.

(55) Computing system **300** can include at least one bus data bus **305** or other communication component for communicating information and at least one processor **310** or processing circuit coupled to the data bus **305** for processing information. Computing system **300** can include one or more processors **310** or processing circuits coupled to the data bus **305** for exchanging or processing data or information. The processors **310** can include any processing circuitry, including, for example, graphics processing units (GPUs) or any circuitry or processors configured for executing machine learning or artificial intelligence models. Computing system **300** can include one or more main memories **315**, such as a random-access memory (RAM), dynamic RAM (DRAM) or other dynamic storage device, which can be coupled to the data bus **305** for storing information and instructions to be executed by the processor(s) **310**. Main memory **315** can be used for storing information (e.g., data, computer code, commands, or instructions) during execution of instructions by the processor(s) **310**.

(56) Computing system **300** can include one or more read only memories (ROMs) **320** or other static storage device coupled to the bus **305** for storing static information and instructions for the processor(s) **310**. Storage **325** can include any storage device, such as a solid-state device, magnetic disk, or optical disk, which can be coupled to the data bus **305** to persistently store information and instructions. Storage **325** can be used, for example, to provide data repositories.

(57) Computing system **300** can be coupled via the data bus **305** to one or more output devices **335**, such as speakers or displays (e.g., liquid crystal display or active-matrix display) for displaying or providing information to a user. Input devices **330**, such as keyboards, touch screens or voice interfaces, can be coupled to the data bus **305** for communicating information and commands to the processor(s) **310**. Input device **330** can include, for example, a touch screen display (e.g., output device **335**). Input device **330** can include a cursor control, such as a mouse, a trackball, or cursor direction keys, for communicating direction information and command selections to the processor(s) **310** for controlling cursor movement on a display.

(58) Computer system **300** can include input/output ports **340**, also referred to as I/O ports **340**, can include physical interfaces that facilitate or provide communication between external or peripheral devices and processor(s) **310** and/or memory **315**. I/O ports **340** can be connected to data bus **305**, allowing the transfer of data between the processor(s) **310**, memories **315**, and any external devices (e.g., keyboards, mice, printers, and external storage devices). Computer system **300** can include one or more network interfaces **345** coupled via data buses **305**. Network interfaces **345** can include any physical or virtual components enabling communication between the computer system

300 and any external networks (e.g., the Internet). Network interface **345** can provide transfer of data between the processor(s) **310**, memories **315** and any external networks.

(59) The processes, systems and methods described herein can be implemented by the computing system **300** in response to the processor **310** executing an arrangement of instructions contained in main memory **315**. Such instructions can be read into main memory **315** from another computer-readable medium, such as the storage device **325**. Execution of the arrangement of instructions contained in main memory **315** causes the computing system **300** to perform the illustrative processes described herein. One or more processors **310** in a multi-processing arrangement can be employed to execute the instructions contained in main memory **315**. Hard-wired circuitry can be used in place of or in combination with software instructions together with the systems and methods described herein. describes systems and methods described herein are not limited to any specific combination of hardware circuitry and software.

(60) Although an example computing system has been described in FIG. 3, the subject matter including the operations described in this specification can be implemented in other types of digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them.

B. Systems and Methods for Rapid License Plate Reading via Character Substitution

(61) When a vehicle **130** enters a region of interest **135** within a proximity of a gate **160**, the technical solutions can utilize a gate camera **120** to capture one or more images or video streams of the vehicle. Once captured, the image data processing system can analyze this visual data to identify a portion of the vehicle **130** that includes identifiers, such as a license plate **132** or a vehicle identification number (VIN). For instance, upon identification of the identifiers, the data processing system **118** can implement a character recognition functionality to identify the characters within a license plate. Sometimes, the vehicle can be muddy, wet, dusty or include scratches, bends or various other obstructions that make it challenging for the to recognize the characters of the license plate. In such instances, the data processing system can mistakenly identify a character “0” as a character “O”, a character “5” as a character “S”, a character “1” as a character “I”, or a character “A” as a character “4”.

(62) To overcome such challenges, the technical solutions of this disclosure can encode the license plate data to substitute or replace the characters that are prone to misreading by characters for which the likelihood of error or misidentification is reduced, thereby improving the reliability of the vehicle identification. In particular, the technical solutions can provide a license plate processor that can identify the characters of a detected license plate data that satisfy a character replacement schema. Based on the character replacement schema, the technical solutions can generate a replacement license plate data in which replacement characters are substituted or inserted instead of the characters triggering or satisfying the character replacement schema (e.g., characters that can be confused with other characters and should be replaced into a uniform format). The replacement license plate data can then be stored and used for more reliably recognizing the vehicle based on the images of the license plate when the license plate or the vehicle is subjected to non-ideal conditions or weather elements.

(63) FIG. 4 illustrates an example system **400** for implementing the technical solutions of the facility system **100**. The example system **400** can include a computing environment for a system to implement automated vehicle license plate recognition for use at service facilities, such as a car wash facility. The example system **400** include one or more data processing systems **118**, which can be integrated using any combination of one or more instances of the system **200** of FIG. 2 or the system **300** of FIG. 3, in the context of a facility **100** of FIG. 1. The data processing systems **118** can include one or more of the ML models **222** to perform operations of the data processing system **118**, such as vehicle license plate data processing by license plate processor **202** or vehicle identification via camera managers **206**.

(64) The data processing system **118** can include one or more license plate processors **202** for capturing and processing original character sequences **424** of vehicle license plates **132**. The data processing system **118** can include one or more profile managers **204** which can include one or more databases storing one or more vehicle profiles **402** for one or more vehicles **130**. Each vehicle profile **402** can include various vehicle data, such as one or more of license plate data **404** (e.g., license plate information, license plate number), car wash type **406** (e.g., types of car wash services to apply to the vehicle), service settings **408** (e.g., settings for the vehicle services to apply to the vehicle), or various information **412** (e.g., any additional information on the vehicle). The data processing system **118** can include one or more of car wash service managers **208** providing services **410** to the vehicle. The data processing system **118** can include one or more camera managers **206** communicatively coupled to at least the one or more gate cameras **120**. The camera manager **206** can capture and determine one or more images **416** (e.g., images of the vehicle **130**), one or more vehicle characteristics **418** (e.g., features of the vehicle), and one or more discrepancies (e.g., differences between images and prior captures images of the vehicle). The data processing system **118** can include one or more car wash service managers **208** which can include one or more services **410** (e.g., services provided to the vehicle) to execute. The data processing system **118** can include one or more GUI managers **212** which can generate one or more prompts **414** (e.g., to be provided for display on a device). The data processing system **118** can include one or more log managers **214** which can store one or more image logs **420** (e.g., storing images provided by the camera manager **206**). The data processing system **118** can include one or more license plate data managers **426** using at least one of a character replacement schema **428** and a lookup table **430** to generate one or more replacement character sequences **432** from the original character sequences **424**. The license plate data manager **426** can execute queries **434** (e.g., code, questions) to determine a vehicle profile.

(65) The license plate processor **202** can individually, or in conjunction with a license plate data manager **426**, process and determine the original character sequence **424** and identify its corresponding replacement character sequence **432**. Original character sequence **424** can be any sequence of characters (e.g., numerical, alphabetical) on a license plate (e.g., license plate **132**) of the vehicle **130**. The original character sequence **424** can refer to a license plate number on the license plate **132** of the vehicle **130**, and can be correlated to the license plate data **404**. The license plate processor **202** can receive the images **416** from the camera manager **206** and determine the original character sequence **424** from the images **416**. For example, the license plate processor **202** can include at least one ML model **222** including one or more character recognition models, algorithms, or software, such as optical character recognition (OCR) to determine the original character sequence **424** from the images **416**. The license plate processor **202** can input the images **416** into a ML model **222**, and the ML model **222** can output the original character sequence **424** or provide the corresponding replacement character sequences **432**.

(66) The profile manager **204** can store and provide various vehicle profiles **402**. A vehicle profile **402** can include various vehicle data. For example, the vehicle profile **402** can include license plate data **404** of a respective vehicle **130** of the plurality of vehicles **130**. The license plate data **404** can include at least one of a license plate number, jurisdiction information (e.g., state, province, country), or registration (e.g., tag, sticker, date) of the vehicle **130**.

(67) Each of the vehicle profiles **402** maintained by the profile manager **204** can include the car wash type **406**. For example, the car wash type **406** refers to a type of wash to be performed on the vehicle **130** associated with the vehicle profile **402**. The car wash type **406** can be set by at least one of the operator, the driver, or determined based on a type of the vehicle **130** (e.g., car, truck, van, or a motorcycle). For example, the profile manager **204** can select and set the car wash type **406** for the vehicle profile **402** based on the type of the vehicle **130**, which can be stored in the vehicle profile **402**. The car wash type **406** can include at least one of “Express wash,” “Platinum wash,” “Silver wash,” etc. For example, the car wash type **406** includes multiple levels of car

washes including express wash, platinum wash, and silver wash. Each level of the car wash type **406** can include a different type or number of services. For example, the platinum wash can include wheel polish, an underbody rinse, and a wax service while the express service includes a cleansing foam and a rinse.

(68) Each of the vehicle profiles **402** can include the service setting **408** for each of the vehicles **130**. The service setting **408** can include and/or indicate a service **410** to be provided to the vehicle **130**. The service **410** can correspond to the car wash type **406**. For example, the service setting **408** includes an indication of the service **410** to be provided to the vehicle **130**, and the service **410** can include express wash, platinum wash, or silver wash. The service setting **408** can include, for example, a type of soap for the service **410** to use depending on a type of paint or coating of the vehicle **130**, which can be indicated in the vehicle profile **402**. The service setting **408** can include other parameters related to the service **410**, such as a temperature of water, which of the service equipment **110** to use, etc.

(69) Each of the vehicle profiles **402** can include information **412** associated with each of the vehicles **130**. The information **412** can include various additional information of each of the vehicles **130**. For example, the information **412** can include, but not limited to, the vehicle **130** type (e.g., car, truck, van, motorcycle) the vehicle **130** model (e.g., manufacturer design), type of wheel on the vehicle **130**, number of car washes performed on the vehicle **130**, etc. In some implementations, the information **412** includes the car wash type **406**, the service setting **408**, and/or the service **410**. In some implementations, the information **412** includes information related to a driver or owner of the vehicle **130**, such as name and payment information. The information **412** can indicate a membership to the service facility **100** of the vehicle **130**. For example, the vehicles **130** corresponding to the vehicle profiles **130** can have prepaid for a certain amount of services from the service facility **100**.

(70) The camera manager **206** can capture and store various images **416**. The camera manager **206** is communicatively coupled to an image capture device (e.g., gate cameras **120**), and can capture one or more images **416** of at least a portion of a vehicle **130** positioned within a region of interest (e.g., regions of interest **135**) of a service facility (e.g., service facility **100**). The camera manager **206** can monitor the region of interest **135**, and transmit instructions to the image capture devices to capture the images **416** of the vehicle **130**. The camera manager **206** can then receive and store the images **416**. For example, the camera manager **206** includes a database (e.g., log) in which the images **416** are stored. In other implementations, the camera manager **206** provides the images **416** to the log manager **214** to store in the image log **420**.

(71) Based on the images **416**, the camera manager **206** can identify a vehicle characteristic **418** (e.g., characteristic of a vehicle **130**). The camera manager **206** can include the ML models **222** to determine the vehicle characteristic **418**. For example, the ML model **222** can be an image recognition model configured or trained to recognize vehicles from images **416**. For instance, the camera manager **206** can input the images **416** into the ML model **222**, and the ML model **222** can output the vehicle characteristic **418**. The vehicle characteristic **418** can include features of the vehicle **130**. For example, the vehicle characteristic **418** can include, but not limited to, a width, length, height of the vehicle **130** as well as features, such as whether the vehicle **130** includes a trunk bed, a rack on the roof, etc. The vehicle characteristic **418** can include a color of the vehicle **130**, such as black, white, gray, etc. To identify the vehicle characteristic **418**, the camera manager **206** can include or utilize at least one ML model **222** (e.g., an image recognition model, algorithm, or software) trained to recognize vehicle characteristics. For example, the camera manager **206** can include at least one machine learning model to receive the images **416** as an input, and provide as output, one or more the vehicle characteristic **418** to identify or track the vehicle.

(72) The license plate data manager **426** can process license plate data, including the sequences of characters of license plates to identify or recognize a vehicle. For example, the license plate data manager **426** can receive and process character sequences of a license plate, and can encode,

substitute or replace characters of the character sequence which can be prone to misreading or error. To do so, the license plate data manager **426** includes a character replacement schema **428** (e.g., rules, guidelines for substitution of characters prone to misreading or misidentification). The character replacement schema **428** can indicate to the license plate data manager **426** which characters of a character sequence to replace and which to keep (e.g., maintain).

(73) Following identification of the original character sequence **424**, the license plate processor **202** can provide the original character sequence **424** to the license plate data manager **426**. The license plate data manager **426** can determine one or more characters of the original character sequence **424** that satisfy the character replacement schema **428**. The license plate data manager **426** can include a lookup table **430** that maps original characters of the license plates with replacement characters of a replacement schema **428**. For instance, the character replacement schema **428** can utilize a lookup table **430** that relates each of the characters to be substituted or replaced with their corresponding replacement characters. The lookup table **430** can include a selection of characters of various license plates **132** that correspond to or relate to their corresponding replacement characters. For example, the lookup table **430** relates the one or more characters of the original character sequence **424** with one or more corresponding replacement characters that can be used as substitution for the original characters of the license plate. The one or more characters and one or more corresponding replacement characters can be referred to as one or more representative character pairs that can be mapped in the lookup table **430**. For instance, the one or more representative character pairs can relate at least one of a character “1” and (e.g., with) a character “I”, a character “2” and a character “Z”, a character “5” and a character “S”, a character “0” and a character “O”, or a character “A” and a character “4.” In some embodiments, the vehicle profile can store both the vehicle license plate data with the replacement characters and the vehicle license plate data using the original characters (e.g., prior to their replacement).

(74) Using the lookup table **430**, the license plate data manager **426** can determine whether one or more characters of the license plate satisfy a character replacement schema (e.g., include one or more original characters that correspond to one or more replacement characters). For instance, the license plate data manager **426** can check whether any of the characters of the license plate have a corresponding replacement character. The license plate data manager **426** can map the one or more characters of the original character sequence **424** with the one or more of the corresponding replacement characters. The characters of the license plate that satisfy a character replacement schema can have one or more corresponding replacement characters in the lookup table **430** for replacing the one or more characters of the original character sequence **424**. The license plate data manager **426** can identify, match, or select, based on the mapping, the one or more replacement characters that correspond to the characters of the original character sequence **424** satisfying the replacement schema. For example, the license plate data manager **426** can determine that an original character sequence **424** of a license plate includes a character “2” and a character “0” that satisfy the character replacement schema (e.g., correspond to replacement characters). Responsive to determining that the original character sequence **424** includes characters with corresponding replacement characters (e.g., characters included in the lookup table **430**), the license plate data manager **426** determines that the one or more characters of the original character sequence **424** satisfies the character replacement schema **428**.

(75) Upon determining that the one or more characters of the original character sequence **424** satisfy the character replacement schema **428**, the license plate data manager **426** generates a replacement character sequence **432** (e.g., second sequence of characters). The license plate data manager **426** generates the replacement character sequence **432** by replacing the one or more characters of the original character sequence **424** that satisfy the character replacement schema **428** with the one or more corresponding replacement characters based at least partially on the lookup table **430**. For example, the license plate data manager **426** can select the one or more representative character pairs corresponding to the one or more characters of the original character

sequence **424** using the lookup table **430**.

(76) For example, the license plate data manager **426** can process, encode, substitute or replace characters using the ML model **222**. The license plate data manager **426** can input the original character sequence **424**, and the ML model **222** can generate the replacement character sequence **432**. The ML model **222** can be trained to use, for example, the character replacement schema **428** to generate the replacement character sequence **432** based on the original character sequence **424** used as input, or based on images of the license plate used as input (e.g., implementing optical character recognition in the process).

(77) After selecting the representative character pairs, the license plate data manager **426** generates the replacement character sequence **432**. The license plate data manager **426** uses the representative character pairs to replace characters of the original character sequence **424** with replacement characters. For example, responsive to determining that the original character sequence **424** includes a “5” and an “A,” the license plate data manager **426** selects the representative character pairs “5” and “S” and “A” and “4.” The license plate data manager **426** then generates the replacement character sequence **432** by replacing “5” with “S” and “A” and “4” in the original character sequence **424**. The replacement character sequence **432** is thus the original character sequence **424** with one or more replaced characters according to the character replacement schema **428**.

(78) The license plate data manager **426** can include a query **434** (e.g., question, instruction). The license plate data manager **426** can execute the query **434** using the replacement character sequence **432** and identify, from the vehicle profiles **402** maintained in the profile manager **204**, a vehicle profile **402** of the vehicle **130** positioned within the region of interest **135**. For example, the query **434** includes the replacement character sequence **432**, and the license plate data manager **426** executes the query **434** by transmitting the query **434** to the profile manager **204**. The license plate data manager **426** can then identify the vehicle profile **402** of the vehicle **130** positioned within the region of interest **135** by at least one of receiving the vehicle profiles **402** from the profile manager **204** or the profile manager **204** can use the query **434** to identify the vehicle profile **402** associated with the vehicle **130** in the region of interest **135**. At least one of the profile manager **204** or the license plate data manager **426** can use the lookup table of the character replacement schema **428** to match (e.g., correspond) the replacement character sequence **432** to the encoded license plate sequence in the respective vehicle profile **402**. For instance, a vehicle profile **402** can be identified or accessed based at least partially on a match between the replacement characters and the license plate data **404** stored in the vehicle profile **402**. At least one of the profile manager **204** or the license plate data manager **426** can compare the license plate data **404** stored in the vehicle profiles **402** to the replacement character sequence **432** to identify or authenticate a vehicle profile **402** of a vehicle **130**, responsive to the query **434**.

(79) The license plate data manager **426** can utilize character replacement schema **428** to detect a change of a vehicle license plate **132** on a vehicle **130**. For example, a license plate data manager **426** can apply a character replacement schema **428** and information stored in vehicle profiles **402** (e.g., vehicle make, model, color or images) to identify, detect or determine that a vehicle **130** has changed a license plate **132**. For instance, the license plate data manager **426** can utilize an image of a vehicle license plate from an image log **420** to identify a string of characters on the license plate. Using one or more rules of the character replacement schema **428**, the license plate data manager **426** can determine (e.g., via a look up table **430**) that one or more of the characters from the image have one or more corresponding replacement characters. The license plate data manager **426** can, in response to this determination, generate a replacement character sequence **432** replacing those characters that are subject to the character replacement schema **428**. The license plate data manager **426** can then utilize the replacement character sequence **432** to identify or select a vehicle profile **402** corresponding to the license plate data **404** storing the matching replacement character sequence **432**.

(80) To detect the change of the vehicle license plate, the profile manager **204** can utilize information **412** from the vehicle profile **402** that is identified or selected using the replacement character sequence **432**. For instance, using a current image of the vehicle, the data processing system **118** can extract characteristics of the vehicle, such as the vehicle make and model, type of vehicle (e.g., sedan, sport utility vehicle or a truck) or a color of the vehicle to make a comparison between the vehicle having the replacement character sequence **432** and the characteristics of that vehicle stored in the vehicle profile **402**.

(81) For instance, the profile manager **204** and the license plate data manager **426** can determine that the replacement character sequence **432**, while matching the license plate data **404**, does not match one or more information **412** on the vehicle. For instance, the replacement character sequence **432** can match the license plate data **404** (e.g., storing the same replacement character sequence), but the information **412** may be not matching the characteristics of the vehicle from the image captured. For instance, the image of the vehicle with the replacement character sequence **432** may have a different color, a different make or model type, or a different configuration than the vehicle described in the information **412** of the vehicle profile **204**. In response to the vehicle having the license plate with a matching replacement character sequence **432** having characteristics (e.g., color, type, make and mode) that do not match the characteristics of the vehicle in the information **412**, the profile manager **204** or the license plate data manager **426** can determine that the license plate was swapped or replaced onto a different vehicle.

(82) The license plate data manager **426** can utilize the replacement characteristic sequence **432** to identify or validate the vehicle entering the facility **100**. For instance, the license plate data manager **426** can utilize the character replacement schema **428** and the corresponding replacement characters to identify the vehicles **130** and identify or select their vehicle profiles **402**. Upon generating a replacement character sequence **432**, the license plate data manager **426** can send the replacement character sequence **432** to the profile manager **204** to identify a vehicle profile **402** having a matching replacement character sequence **432** in the license plate data **404**. In response to identifying the match between the replacement character sequence **432** and the license plate data **404**, the profile manager **204** can validate the vehicle **130** and provide any requested access to the vehicle profile **402** (e.g., to access the car wash type **406**, service setting **408** or information **412**). In some instances, in response to validating the identity of the vehicle, the profile manager **204** can prepopulate the service settings **408**, such as by selecting the most desired service for the vehicle, the most commonly selected service for the vehicle or the most recently selected service that the vehicle user had selected during a preceding visit. Prepopulating the vehicle service order can include selecting specific service settings **408** for the system to provide a desired type of car wash, type of soap or selection of shine to the vehicle.

(83) The license plate data manager **426** can match the replacement character sequences **432** of the license plates with the vehicle characteristics (e.g., color, vehicle type and make and model) of the vehicle profile **402** to validate vehicles entering the facility. For example, the license plate data manager **426** and the profile manager **204** can compare the replacement character sequence **432** with the license plate data **404** to identify a match. The camera manager **206** can also utilize machine learning to identify vehicle characteristics which the data processing system can compare with the characteristics of the vehicle stored in the profile manager **204**. Upon determining that the vehicle characteristics determined from the current image match those stored in the vehicle profile **402** and also determining that the replacement character sequence **432** matches the stored license plate data **404**, the data processing system **118** can validate or confirm that the vehicle **130** is the vehicle of the vehicle profile **402**. Responsive to the validation, the system can apply specific actions, such as prepopulating the car wash type **406** or automating the service settings **408** for the prepopulated car wash type.

(84) In some implementations, instead of, or in conjunction with, generating the replacement character sequence **432**, the license plate data manager **426** can utilize information stored in the

vehicle profile **402** to detect or identify a vehicle **130** (e.g., within the region of interest **135**). For example, the license plate data manager **426** can receive the original character sequence **424** from the license plate processor **202**, and compare the original character sequence **424** to the license plate data **404** stored in the vehicle profiles **402**. Upon determining that the original character sequence **424** is different from each license plate number (e.g., license plate character sequence) in the license plate data **404**, the license plate data manager **426** can shorten the original character sequence **424**. For example, a last character in the original character sequence **424** can be removed such that a length of the original character sequence **424** is adjusted from 6 characters to 5 characters. The license plate data manager **426** can compare the shortened original character sequence **424** with the license plate data **404**. The license plate data manager **426** can include and utilize a character sequence length threshold. The character sequence length threshold can indicate a minimum length of the shortened original character sequence **424**, such as 4. For example, if the license plate data manager **426** shortens the shortened original character sequence **424** to 4 and the shortened original character sequence **424** remains different from the license plate data **404**, the license plate data manager **426** compares the original character sequence **424** to the character replacement schema **428** to identify the vehicle **130**.

(85) In some implementations, the original character sequence **424** matches the license plate number in one vehicle profile **402**. In such cases, the license plate data manager **426** can determine that the one vehicle profile **402** corresponds to the vehicle **130**. For instance, license plate recognition system can utilize a positional search methodology. This can include configuring a positional search with a minimum starting sequence, such as four characters, to improve the accuracy of license plate matches. In some situations, license plates can be obscured or difficult to read, due to dirt, glare, obstructions or other challenges. In such scenarios, when a camera scans a plate, the camera manager can incorrectly output a license plate string of characters, such as for example “ABC123.” The system can first check the database for an exact match of all six characters against various license plate entries in the system. If no exact match is found, the system can perform positional searches by progressively reducing the number of characters from the string considered. For instance, the system can remove one of the six license plate characters to repeat the search with five of the six string characters, such as by starting with “ABC12” to see if there is a match. In the event that no matches are identified, the system can reduce another characters and continue with “BC12” and so on. This reduction of characters can allow the system to identify potential matches even when the exact plate number is not available, thereby increasing the recognition and decreasing the chance of false negatives.

(86) The positional searching can incorporate utilization, processing and evaluation of metadata to further refine the search results and improve the reliability of the recognitions. Metadata utilized can include, for example, plate region, vehicle color, make, model, and type, each of which can be considered during the search process and determining of the vehicle identity. For example, if the initial search for “ABC123” returns no results, the system can perform a positional search for “ABC12,” which may yield multiple results. These results can be further filtered based on vehicle characteristics, such as the vehicle color, body style or other features, allowing the system to identify the vehicle based on the metadata. In some instances, the system can rank the multiple matching results based on the metadata matches to which weights are applied. The system can apply a higher weight given to matches in the plate region, followed by matches based on the vehicle color, make, and type. This ranking technique can allow for the most relevant matches to be prioritized, improving the overall accuracy and reliability of the license plate recognition system.

(87) For example, a camera can scan a plate with the value “ABC123” in the region VA, and the vehicle can be a white Chevrolet Silverado pickup. The system can perform a search for license plate data using the initial search for “ABC123”, resulting in no results. In response to receiving no results, the data processing system can then proceed to implement a positional search using a portion of the license plate (e.g., subset of the characters) as the input. In such a step, the data

processing system can determine that for “ABC12” there may be several matches, including “ABC12E”, “ABC125”, and “ABC122” of the same state or country. The data processing system can then have each of these matches ranked based on the metadata corresponding to the vehicle data of each of these license plates. For instance, “ABC12E” can receive the highest score due to matching the region (e.g., state), make, color, and vehicle type, thereby being identified as the most likely result. This refined search process can improve the system's ability to accurately recognize license plates, even in cases where the exact plate number is not available. In another example, upon determining that the shortened original character sequence **424** is the same as at least one license plate number in the license plate data **404**, the license plate data manager **426** receives the vehicle characteristic **418** from the camera manager **206** based on the images **416**. The vehicle characteristic **418** can include at least one of a region of the license plate **132** (e.g., state), color, make, model, or type (e.g., metadata) of the vehicle **130**. Once received, the license plate data manager **426** can compare the vehicle characteristic **418** to at least one of the license plate data **404** and the information **412** stored in the vehicle profiles **402**. For example, the license plate data manager **426** compares the region of the license plate **132** of the vehicle **130** in the images **416** to regions in the license plate data **404** to identify the vehicle profile **402** associated with the vehicle **130**. The license plate data manager **426** compares the vehicle characteristic **418** to data stored in the vehicle profiles **402** with the vehicle profiles **402** matching the shortened original character sequence **424**. The license plate data manager **426** can include weights with the vehicle characteristic **418** for comparing the vehicle **130** to the vehicle profiles **402**. For example, a weight of the region of the license plate **132** can be higher than a weight of the color, make, model, or type. The license plate data manager **426** identifies a match percentage between the vehicle characteristic **418** and the vehicle profiles **402**, and determines the vehicle profile **402** corresponding to the vehicle **130** based on a highest match percentage. For example, the license plate data manager **426** determines a difference between each of the region, make, model, color, and type of the vehicle **130** with the region, make, model, color, and type of vehicle stored in each of the vehicle profiles **402**, weighs the differences, and determines the match percentage for each of the vehicle profiles **402** with the vehicle **130** based on the weighted difference.

(88) Following identification of the vehicle profile **402**, the license plate data manager **426** can transmit (e.g., the operator device **150**, the admin device **162**) data to a device included in the vehicle profile **402** based on (e.g., in response to) identifying the vehicle profile **402**. The data included in the vehicle profile **402** can include at least one of the license plate data **404**, the car wash type **406**, the service setting **408**, the service **410**, or the information **412**. The data can be displayed on the device. For example, the license plate data manager **426** can transmit the data for presentation at the device. The device can be at least one of the operator device **150**, the administrator device **162**, or a point of sale device (e.g., cash register) of the third party server **190**. For example, the operator device **150** can display the car wash type **406**. In some implementations, the license plate data manager **426** provides the data to the GUI manager **212** for display on at least one of the operator device **150**, the administrator device **162**, or the point of sale device of the third party server **190**.

(89) The license plate data manager **426** transmitting the data to the device can include transmitting, to the car wash service manager **208**, instructions to cause the car wash tunnel system **105** (e.g., the car wash) to provide the car wash type **406** corresponding to the vehicle profile **402** to the respective vehicle **130**. The instructions can include the car wash type **406**, and can be stored in the vehicle profiles **402**. Responsive to identifying the vehicle **130**, at least one of the profile manager **204** can determine the car wash type **406** associated with the vehicle profile **402** of the vehicle **130** in the region of interest **135**, and instruct the car wash service manager **208** to provide the vehicle **130** with the car wash type **406**. In some implementations, the profile manager **204** includes the ML model **222** to determine the car wash type **406** based on, for example, the replacement character sequence **432** or one or more images of the vehicle **130** or the vehicle license

plate **132**. The car wash service manager **208** can store services **410**. Each of the services **410** can correspond to at least one car wash type **406**. For example, the car wash service manager **208** can receive the car wash type **406**, determine the service **410** correlating to the car wash type **406**, and transmit instructions to the car wash controller **104** to implement the service **410** for the vehicle **130**. In some implementations, the profile manager **204** determines the service setting **408** and provides the service setting **408** to the car wash service manager **208**. Based on the service setting **408**, the car wash service manager **208** can determine and transmit the service **410** to the car wash controller **104**.

(90) In some implementations, the GUI manager **212** generates the prompt **414** corresponding to the service **410**. The prompt **414** can include an indication of the service **410** to be provided to the vehicle **130**. In some implementations, the GUI manager **212** receives an update to the service **410** to be provided. The update can include an adjustment to the service setting **408** or the service **410**, and can be provided by a driver or an operator. The GUI manager **212** can provide the update to the profile manager **204**. The profile manager **204** can then store the update (e.g., updated service) in the vehicle profile **402** as the service setting **408**. For example, the update includes an additional add-on service such as a tire shine, and the profile manager **204** includes the update in the service setting **408**.

(91) In some implementations, the profile manager **204** includes and tracks a discrepancy counter associated with each of the vehicle profiles **402**. For example, after detecting the discrepancy **422**, the camera manager **206** adds to the discrepancy counter maintained in the profile manager **204**. The discrepancy counter can represent a number of times that the discrepancy **422** was detected for the license plate data **404** (e.g., license plate **132**) associated with the vehicle profile **402**. The profile manager **204** can maintain the discrepancy counter and compare a value of the discrepancy counter to a discrepancy threshold. Responsive to the value being below the discrepancy threshold, the profile manager **204** continues to maintain the discrepancy counter. Responsive to the value being at or above the discrepancy threshold, the profile manager **204** can generate an alert for at least one of the operator device **150** or the admin device **162**. The profile manager **204** can then mark (e.g., flag) the vehicle profile **402** associated with the value of the discrepancy counter being at or above the discrepancy threshold. Once marked, responsive to the profile manager **204** identifying the vehicle profile **402** based on the replacement character sequence **432** and determining that the vehicle profile **402** is marked, the profile manager **204** can transmit instructions to the data processing system **118** to not allow (e.g., not actuate the gates **160**) the vehicle **130** into car wash vehicle queue. The profile manager **204** can generate an alert for at least one of the operator device **150** or the admin device **162** based on determining that the vehicle profile **402** is marked. The alert can indicate that the vehicle **130** in the region of interest **135** has a marked vehicle profile **402**.

(92) Data processing system **118** can include the functionality for utilizing QR codes **166** to allow for vehicle identification, verification, and user selection and customization of vehicle services. For example, upon driving up to a lane **134** or a gate **160** of a facility **100**, a user (e.g., a driver) can scan the QR code **166** using their smartphone. The QR code **166** can be positioned at any location at the facility **100**, including on, adjacent to, or along a lane **134**, a gate **160**, entrance to a tunnel **140** or car wash tunnel system **105**. Upon scanning, the QR code **166** can direct the smartphone of the user to a webpage where the user can select from a variety of car wash services of the facility **100**, including a basic wash, a premium wash, or a special polishing service. The user can also choose to upgrade their service type from a one-time wash to a monthly or annual subscription. The webpage or the application provided via the QR code **166** can allow the user to configure specific preferences associated with the vehicle profile **402** or vehicle data or information **412**, such as opting for a tire shine or an underbody wash. Once the user has made their selections, the data processing system **118** can process the request and update the user's profile with the chosen services, ensuring that the car wash tunnel system **105** is prepared to provide the selected services

when the vehicle enters the tunnel **140**.

(93) The QR code **166** can be used in conjunction with a license plate processor **202** to enhance security and personalization of services. For instance, when the user scans the QR code **166**, the data processing system **118** can verify the user's identity by matching the data (e.g., identifier) of the smartphone that scanned the QR code with the license plate data captured by the license plate processor **202**. The identifier can include, for example, the phone's unique device ID, the user's account information, or a session token generated by the application. This verification process can validate the smartphone with the recognized license plate data to ensure that the services are provided to the correct vehicle and user. For instance, if the license plate processor **202** recognizes the license plate of the vehicle and matches it with the phone identifier, the data processing system **118** can grant access to the user's profile or account, allowing them to manage their services and preferences. This feature can provide an additional layer of security and personalization, ensuring that the services are tailored to the specific needs and preferences of the user.

(94) For example, the feature can be implemented by positioning a QR code **166** next to a gate **160**, where a user can scan the QR code **166** with their smartphone. For example, the feature can be implemented by positioning a QR code **166** next to a gate **160**, where a user can scan the QR code **166** using their smartphone. The data processing system **118** can then allow the user to continue following the prompts from the link provided via the QR code to authenticate the user. Once authenticated, the smartphone of the user can be assigned an identifier for the smartphone. This identifier can be used to verify the user's identity. For instance, the system can match the phone identifier received via the smartphone using the QR code **166** with the license plate data captured by the license plate processor **202**. Upon successful verification, the data processing system **118** can grant access to the user's profile, allowing them to select and configure car wash services, change their service type, and update their preferences. The car wash tunnel system **105** can then be prepared to provide the selected services when the vehicle enters the tunnel, ensuring a personalized and efficient car wash experience.

(95) Data processing system **118** can be configured to utilize Bluetooth beacons, other wireless beacons, or transponder devices to identify users and vehicles within the facility **100**. Car beacons can be installed in vehicles and can transmit a unique identifier (e.g., unique vehicle identifier) that can be detected by the facility's beacon receivers or reader devices. When a vehicle equipped with a car beacon or transponder device enters the facility **100** (e.g., premises or a car wash building), the beacon receiver or reader device can capture the unique identifier and transmit it to the data processing system **118**. The data processing system **118** can then match the unique identifier with the vehicle profile **402** or vehicle data **412** stored in the system, allowing for seamless identification and verification of the vehicle. In response to the identification and verification, the system can allow the user to access vehicle data or client account and make changes, such as service configures or service selections for the vehicle. This can allow the system to provide personalized services and streamline the user experience by automatically recognizing the vehicle and its associated preferences.

(96) The transponder devices can include at least one radio-frequency identification (RFID) tag which includes the unique identifier. The reader device can emit radio signals, and the RFID tag can receive the radio signals and return the unique identifier. The reader device can capture the unique identifier and transmit the unique identifier to the data processing system to identify and verify the vehicle. As with other transponder device examples, the RFID tags can be utilized to uniquely identify a user or the vehicle and can be used in combination with other techniques (e.g., license plate recognition or QR code scanning) to validate identification of the user and provide access to user data and service control functionalities.

(97) For instance, phone beacons, transponders or RFID tags can be used to identify users based on the unique identifier or signal transmitted by their smartphones. For instance, a phone beacon can be any wireless device that transmits a unique identifier from a smartphone, allowing the data

processing system **118** to detect and identify the user based on the transmitted identifier. When a user with a phone beacon-enabled smartphone, or an RFID tag, enters the facility, the beacon receiver or reader device can detect the unique identifier and send it to the data processing system **118**. The data processing system **118** can match the unique identifier with the user's profile or account information, allowing for personalized service customization and verification. For example, the system can grant access to the user's profile, enabling them to select and configure car wash services, change their service type, and update their preferences. This integration of phone beacons can improve security and personalization, providing for services that the users can tailor to their specific needs and preferences.

(98) For example, the feature can be implemented by installing car beacons or transponder devices in vehicles and configuring the data processing system **118** to detect the unique identifier transmitted by the car beacon or transponder device (e.g., RFID tag) when the vehicle enters the facility. The beacon receiver or reader device can capture the unique identifier and transmit it to the data processing system **118**, which can then match the identifier with the vehicle profile **402** or vehicle data **412**. Upon successful identification, the data processing system **118** can grant access to the user's profile, allowing them to select and configure car wash services, change their service type, and update their preferences. The car wash tunnel system **105** can then be prepared to provide the selected services when the vehicle enters the tunnel, ensuring a personalized and efficient car wash experience.

(99) The car beacon or transponder devices (e.g., RFID tags) can be used in conjunction with a license plate processor **202** or QR codes **166** to enhance security and personalization of services. For instance, when a radio signal (e.g., beacon signal) from a car beacon or transponder device indicates or identifies a particular vehicle or a user associated with a vehicle, the data processing system **118** can verify or validate the user's identity by matching the data of the radio signal with a license plate data determined by a license plate processor **202** or a scanned the QR code. The data of the radio or beacon signal can include signal information or code uniquely identifying a vehicle or user of the vehicle, which can be matched with QR code data or license plate data to validate or verify the identification. This verification process can improve the security of the system and ensure that the services are provided to the correct vehicle and user. For instance, if the license plate processor **202** recognizes the license plate of the vehicle and matches it with the beacon signal, the data processing system **118** can grant access to the user's profile or account, allowing them to manage their services and preferences.

(100) Upon identifying vehicle characteristics **418**, the camera manager **206** can compare the vehicle characteristic **418** to one or more characteristics of the vehicle **130** (e.g., vehicle characteristics **418**) determined from prior captured images. The log manager **214** can maintain (e.g., include) the image log **420** (e.g., image database) of vehicles **130** which can include one or more prior captured images (e.g., images **416**) indexed according to the license plate data **404**. For example, the prior captured images are categorized and associated with license plate data **404** of each of the vehicle profiles **402**. The camera manger **206** can compare the vehicle characteristic **418** using the ML model **222**, and determine, for example, a difference or similarity value between the vehicle characteristic **418** and the characteristics in the prior captured images. The camera manager **206** can extract the prior captured images from the image log **420** to compare the vehicle characteristic **418**. In some implementations, the prior captured images are stored in the vehicle profiles **402** as a type of information **412**. For example, each of the vehicle profiles **402** can include the image log **420**.

(101) A log manager **214** can include any number of image logs **420**, which can include any collection of images of vehicles captured over time. A log manager **214** can maintain images of each vehicle associated with each of the vehicle profiles **402** that may be captured over time. For instance, a log manager **214** can maintain a log of images of a vehicle **130** associated with a vehicle profile **402** captured during each of the visits of the vehicle to the facility **100**. The images of the

vehicle from the image log **420** can be stored within or associated with the vehicle profile **402** and can be used for a quick lookup of the vehicle **130**. For instance, when a vehicle **130** enters a facility **100**, the camera manager **206** can capture a recent image of the vehicle **130**, which can be used by the license plate data manager **426** for detecting the license plate (e.g., via character replacement schema **428** and the replacement character sequence **432**) and comparing vehicle characteristics **418** from the recent image (e.g., using machine learning) and comparing the recent characteristics with the previously stored characteristics of the vehicle profile **402**. The log manager **214** can facilitate quick lookups or verification of the vehicle **130** identity using image logs **420** for comparison of the vehicle data with the data stored in the vehicle profile **402**.

(102) Based on the comparison between the vehicle characteristics **418** and of prior captured images of the vehicle **130**, the camera manager **206** can determine (e.g., detect) a discrepancy **422** (e.g., difference, error). For example, the camera manager **206** compares the one or more images **416** of the vehicle **130** with the prior captured images of the vehicle **130** to determine the discrepancy **422**. As another example, the camera manager **206** can include the ML model **222** which can receive the images **418** and the prior captured images, and determine the discrepancy **422** as an output. The camera manager **206** can determine the vehicle characteristics **418** for the images **416** and the prior captured images, and then determine a difference between the vehicle characteristics **418** of the images **416** and the prior captured images. The camera manager **206** can compare the determined difference to a threshold and responsive to the difference exceeding a threshold, the camera manager **206** can identify, determine or detect the discrepancy **422**. In some implementations, the vehicle characteristic **418** is stored in the image log **420**, and each of the prior captured images has a respective vehicle characteristic **418**. For example, the camera manager **206** determines the vehicle characteristics **418** as the images **416** are received, and stores both the vehicle characteristic **418** and the image **416** into the image log **420**. In some embodiments, the vehicle profile of a vehicle can include one or more vehicle characteristics **418**, including car brand, car type, car model, year, color, number of doors, and any accessories, add-ons, or modifications to the vehicle **130**. The vehicle profile can also store one or more visual deformities to the vehicle, for instance, scratch of driver door, paint discoloration on roof, etc. In some such embodiments, the camera manager **206** can determine the discrepancy **422** by comparing characteristics **418** with the information stored in the vehicle profile instead of comparing it to previously stored or captured images of the vehicle. In some embodiments, the camera manager **206** can determine the discrepancy **422** by comparing characteristics **418** with the information stored in the vehicle profile and to previously stored or captured images of the vehicle.

(103) In response to detecting the discrepancy **422**, the camera manager **206** can detect (e.g., determine or identify) a fraudulent activity (e.g., false, deceiving activity). The fraudulent activity can include, for example, multiple vehicles **130** (e.g., a car, a van, a motorcycle) using a same license plate (e.g., license plate **132**) to receive services **410** from the service facility **100**. The fraudulent activity can be due to the license plate **132** being meant for only a single vehicle **130**, thereby rendering the remaining vehicles using the same license plate **132** fraudulently using the services. The detected or determined discrepancy **422** can include an indication of the fraudulent activity, such as a degree of difference between the vehicle characteristics **418** of the images **416** and the prior captured images. For example, the discrepancy **422** can include indications of an amount (e.g., value, degree) of difference between the color, size, features, etc. of the vehicle characteristics **418** of the images **416** compared to the prior captured images. As such, the camera manager **206** can determine the fraudulent activity by comparing the amount of difference included in the discrepancy **422** to one or more thresholds. For example, the camera manager **206** can store one or more fraudulent activities corresponding to one or more thresholds related to the amount of threshold. The camera manager **206** can then determine the fraudulent activity based on comparing the amount of difference to the one or more thresholds.

(104) The camera manager **206** can determine the fraudulent activity using the ML model **222**. For

instance, one or more ML models **222** can receive as inputs one or more images of capturing one or more vehicle features (e.g., vehicle color or shape) and a license plate. The one or more ML models **222** can determine that the vehicle features do not match the vehicle license plate associated with a vehicle profile **402**. The one or more ML models **222** can determine, in response to this determination, that a fraudulent transaction or action has occurred or is being attempted and provide output, such as an alert or an indication of the fraudulent action (e.g., on one or more GUIs **250** at operator devices **150**).

(105) Responsive to determining the fraudulent activity (e.g., multiple vehicles **130** using the same license plate **132**), the camera manager **206** can transmit an instruction to the profile manager **204** to update the information **412** on the vehicle profile **402**. The update to the information **412** can include an indication of the fraudulent activity or discrepancy **422**. The update can include an indication to not allow (e.g., not actuate the gates **160** for) the vehicles **130** with the same license plate **132** into the tunnel **140**. In some implementations, the update includes an amount of time (e.g., time interval) for which the vehicle **130** with the same license plate **132** is not allowed into the tunnel **140**. For example, responsive to determining the discrepancy **422**, the camera manager **206** sets and transmits to the profile manager **204** an amount of time that the vehicle **130** will not be provided with services from the service facility **100**.

(106) The profile manager **204** can be configured to prepopulate orders (e.g., car wash type **406** or service settings **408**) based on vehicle identification. For instance, the profile manager **204** and the license plate data manager **426** can utilize the comparison of the replacement character sequence **432** and the license plate data **404** to automate car wash type **406** selection or automate service setting **408** instructions for the car wash tunnel system **105**. For example, a profile manager **204** can store prior user selections of services provided in the form of preferred car wash type **406**. In response to identifying the vehicle **130** and identifying or selecting the vehicle profile **402**, the profile manager **204** can prepopulate the selection of the car wash type **406** (e.g., type of service to provide), automatically generating instructions for the service setting **408** to be used by the car wash tunnel system **105** in providing the desired service.

(107) The GUI manager **212** can generate and provide various information for display on devices. For example, the GUI manager **212** can generate a prompt **414**. The prompt **414** can be associated with at least one of the car wash type **406**, the service setting **408**, and/or the service **410** stored in the vehicle profiles **402**. Following determination of the service **410** to be provided to the vehicle **130** based on the vehicle profile **402**, the profile manager **204** can instruct the GUI manager **212** to provide the prompt **414** for display on a device (e.g., operator device **150**, admin device **162**). The prompt **414** can indicate the service **410** to be provided to the vehicle **130**. In some implementations, the prompt **414** indicates a time until the service **410** is to be provided to the vehicle **130**. For example, the profile manager **204** can receive a length of time left for a preceding vehicle in the car wash tunnel system **105**, and include the length of time in the prompt **414**.

(108) In response to detecting the discrepancy **422** and the fraudulent activity, the camera manager **206** can transmit an instruction to the GUI manager **212** to generate an alert based on the discrepancy **422** and the fraudulent activity. The GUI manager **212** can transmit the alert for display on a device (e.g., the operator device **150**, the admin device **162**) to indicate (e.g., notify of) the fraudulent activity. In some implementations, the alert can include a text string related to the determined fraudulent activity.

(109) FIG. 5 is an example method **500** for implementing at least one of the systems **200**, **300**, or **400** as described above. For instance, the example method **500** can be implemented using one or more processors (e.g., **310**) executing instructions or data stored in one or more memories (e.g., **315**, **320** or **325**) of a computing device or an environment. The method **500** can include acts or operations indicated by blocks **502-512**, which can be performed in any order or out of order illustrated in FIG. 5. For instance, depending on implementation, any of the acts corresponding to blocks **502-512** can be performed multiple times, omitted or performed in any order.

(110) At block **502**, the method **500** can include maintaining a plurality of vehicle profiles (e.g., vehicle profiles **402**). The plurality of vehicle profiles can be maintained for a plurality of vehicles (e.g., vehicle **130**). Each vehicle profile of the plurality of vehicle profiles can include license plate information (e.g., license plate data **404**) of a respective vehicle of the plurality of vehicles. Each vehicle profile of the plurality of vehicle profiles can include additional vehicle information, such as a make, model, and type of the vehicle. In some implementations, a service (e.g., car wash type, car wash service), can be stored in each vehicle profile.

(111) At block **504**, the method **500** can include capturing one or more images of at least a portion of a vehicle. The at least a portion of the vehicle can be positioned within a region of interest (e.g., region of interest **135**) of a service facility (e.g., service facility **100**). One or more cameras can capture the images, such as gate cameras or tunnel cameras positioned at various regions of interest or tunnel entrance. The images can be stored in an image log. The images can be captured by the cameras responsive to the vehicle entering the region of interest or field of view of a tunnel camera at the tunnel entrance. For example, responsive to no vehicle being within the region of interest the cameras may not capture images.

(112) At block **506**, the method **500** can include identifying a first sequence of characters (e.g., original character sequence **424**) of a license plate (e.g., license plate **132**) of the vehicle. The data processing system can identify a first sequence of characters from the images of the vehicle. An image recognition model, such as OCR, can be used to identify and extract the first sequence of characters. The data processing system can identify the sequence of characters of the license plate using, for example, one or more ML models trained to recognize characters or identify the license plate original character sequence from the images.

(113) For example, the method can include identifying a characteristic of the vehicle based on the images input into one or more ML models trained to identify vehicle characteristics from the images of the vehicle. The characteristic can include, for example, a width, height, or color of the vehicle, as well as shape of the vehicle or a portion of the vehicle, configurations added to the vehicle (e.g., roof rack or spoiler) or any other features that can distinguish one vehicle from another. In some implementations, the vehicle profile includes or stores various characteristics of the vehicle. The characteristics of the vehicles can include characteristics identified from prior captured images, which can be stored in the image log. Upon identifying the characteristic of the vehicles from the images, the data processing system can store the characteristic in the vehicle profile.

(114) At block **508**, the method **500** can include determining one or more characters of the first sequence that satisfy a character replacement schema (e.g., character replacement schema **428**). The one or more characters that satisfy the character replacement schema can be determined using a lookup table. For example, the data processing system can compare one or more characters of the first sequence with one or more replacement characters (e.g., characters that satisfy the character replacement schema) to the lookup table. The lookup table can relate the one or more characters of the first sequence with the one or more corresponding replacement characters. The lookup table can include one or more representative character pairs which can relate at least one of: a character “1” and a character “I”, a character “2” and a character “Z”, a character “5” and a character “S”, a character “0” and a character “O”, or a character “A” and a character. Using the comparison, the data processing system can match the one or more characters of the first sequence with the one or more corresponding replacement characters. Based on the match, the one or more characters of the first sequence that satisfy the character replacement schema can be determined.

(115) The data processing system can utilize one or more ML models to detect, identify or determine one or more characters of the first sequence that satisfy a character replacement schema. For instance, a license plate processor or a license plate data manager can utilize one or more ML models trained to detect and identify original character sequences that are subject to the character replacement schema. The one or more ML models can detect, within the original character

sequence, one or more characters that are subject to the character replacement schema (e.g., characters to be replaced in the sequence), such as character: “O” or “0”, character “1” or “I” or character “2” or “Z”.

(116) In some implementations, based on the comparison of the characteristics of the vehicle between the images and prior captured images, the data processing system can detect a discrepancy. The discrepancy can indicate a difference between the characteristics of the images and the prior captured images. For example, the characteristic of the vehicle of the images can include that the vehicle is a blue color while the characteristic of the vehicle of the prior captured images indicate that the vehicle is white. For example, a camera manager can utilize one or more ML models to detect vehicle characteristics (e.g., vehicle shape, color, customized additions) or any prior damage to the vehicle. The ML models can be trained to compare current images from the cameras on the facility against other images of prior vehicle visits (e.g., on prior dates). The one or more ML models can be trained to compare vehicle characteristics of the vehicle having the same license plate between the current visit and prior visits and identify any changes in the characteristics (e.g., changes in the color, a recently installed or removed roof rack or a damage to the vehicle that was not present during the prior vehicle visit).

(117) At block **510**, the method **500** can include generating a second sequence of characters (e.g., replacement character sequence **432**). The second sequence of characters can be generated by replacing the one or more characters that satisfy the character replacement schema with one or more corresponding replacement characters in the first sequence of characters. Using a lookup table, the data processing system can select one or more representative character pairs that correspond to the one or more characters of the first sequence. The lookup table can relate characters of license plates with replacement characters for the license plates. For example, the lookup table can include the one or more representative character pairs which relate at least one of: a character “1” and a character “I”, a character “2” and a character “Z”, a character “5” and a character “S”, a character “0” and a character “O”, or a character “A” and a character “4”. Responsive to the selection, the second sequence of characters can be generated. For example, the second sequence of characters can be the first sequence of characters with replacement characters based on the lookup table.

(118) At block **512**, the method **500** can include identifying a vehicle profile (e.g., the vehicle profile **402**) using the second sequence of characters. The data processing system can identify the vehicle profile from a plurality of vehicle profiles maintained in a database, and the vehicle profile can be identified based on executing a query (e.g., **434**) using the generated second sequence of characters (e.g., the replacement character sequence). The vehicle profile can be associated with the vehicle positioned within the region of interest. In some implementations, in response to the discrepancy being identified, the method can include detecting a fraudulent activity (e.g., a mismatch between characteristics of a vehicle and license plate data of the vehicle). For example, one or more ML models can detect that a difference between the vehicle characteristics for the same license plate between two different events (e.g., current event a prior event) is greater than a predetermined threshold for the characteristic difference. In response to the vehicle characteristics of the vehicles associated with the same license plate data being greater than a threshold, the one or more ML models can determine a discrepancy.

(119) In response to a detected discrepancy, the data processing system can generate an alert for display or sounding on a device, such as an operator device, to indicate the fraudulent activity following identification of the vehicle profile. Based on the discrepancy, the method can include determining that multiple vehicles have used the license plate for services of the service facility. For example, the vehicle profile includes a discrepancy counter which indicates a number of times a discrepancy has been detected for a respective vehicle. Information on the vehicle can then be updated responsive to the determination that the multiple vehicles have used the license plate. The information can include the discrepancy counter and can include an indication to not allow the

vehicle into a car wash tunnel system.

(120) In some implementations, the data processing system can maintain an image log of the vehicle. The image log can include one or more prior captured images indexed according to the license plate information. The image log can be included in each vehicle profile. The one or more images of the vehicle can be compared with the one or more prior captured images to detect discrepancies in vehicle characteristics. In some implementations, based on the vehicle profile, a service setting for the vehicle can be identified. The service setting can refer to a car wash type, a type of service, or a number of services, among others, and can be stored in each vehicle profile. Based on the service setting, the data processing system can generate a service to be provided to the vehicle. The service can be transmitted to a car wash controller to provide the service to the vehicle.

(121) At block **514**, the method **500** can include transmitting data included in the vehicle profile based on identifying the vehicle profile to a device (e.g., operator device **150**, admin device **162**). The data transmitted to the device can be data for presentation at the device. The device can be at least one of an operator device, an administrator device, or a point of sale device of a third party server. To transmit the data, the method **500** can include transmitting instructions to a car wash controller to cause the service facility to provide a car wash type corresponding to the vehicle profile of the vehicle. A setting, such as the service setting, can be retrieved from the vehicle profile for the car wash routine of a vehicle service at the service facility. Based on the setting, the data processing system can actuate a component controlling access to the service facility, such as a gate, to initiate the car wash routine. A prompt for the service to be provided can be provided for display on a device, such as the operator device. Responsive to the prompt, an update can be received to the service to be provided. The update can be provided by a driver. Responsive to receiving the updated service, the data processing system can store the update the vehicle profile as the service setting.

(122) Referring now to FIG. **6**, FIG. **6** depicts an example portion **600** of the service facility **100** which can include the gates **160**, the region of interest **135**, the lane **134**, and the gate camera **120**. The example portion **600** can include one or more loops which can detect a presence of the vehicle **130**. The gates **160** can include a gate barrier arm and a housing. The gate camera **120** can be mounted onto a pole and face a direction of the gate **160**.

(123) Referring now to FIGS. **7A-7C**, implementations of screenshots of one or more user interfaces of one or more applications for providing or implementing various features of the automated operation platform for a vehicle service facility are illustrated. Specifically, the screenshots of FIGS. **7A-7C** illustrate an example user profile for recording and tracking a make, model, and license plate of the car, as well as times at which the user has had their car washed. The one or more applications may track changes between the make, model, and license plate of the car to determine whether a user may have switched license plates to wash their car more often than their subscription (e.g., service setting) allows. For example, responsive to determining that the license plate has switched more than twice in a span of one month, the application may generate a notification to the car operator, and not allow the car to enter the car wash tunnel (e.g., by not opening the gate).

(124) A screenshot **700** can include an indication of the discrepancy **422** on the GUI **250**. For example, upon detecting the discrepancy **422**, the camera manager **206** transmits the discrepancy **422** to the GUI manager **212**. The GUI manager **212** can generate a node based on the discrepancy **422** to notify the operator of at least one operator device **150**. A screenshot **720** can include information on a number of washes the vehicle **130** for which the discrepancy **422** was detected has received along with a date and time of each wash. A screenshot **730** can include the vehicle profile **402** including at least the license plate data **404** and the information **412**.

(125) The systems described above can provide multiple ones of any or each of those components and these components can be provided on either a standalone system or on multiple instantiations

in a distributed system. In addition, the systems and methods described above can be provided as one or more computer-readable programs or executable instructions embodied on or in one or more articles of manufacture. The article of manufacture can be cloud storage, a hard disk, a CD-ROM, a flash memory card, a PROM, a RAM, a ROM, or a magnetic tape. In general, the computer-readable programs can be implemented in any programming language or a script, such as Python, JavaScript, LISP, PERL, C, C++, C#, PROLOG, or JAVA. The software programs or executable instructions can be stored on or in one or more articles of manufacture as object code.

(126) Example and non-limiting module implementation elements can include or use input providing devices, such as touchscreens, computer selection devices (e.g., computer mouse), detectors or sensors that can provide any value determined herein, as well as sensors providing any value that is a precursor to a value determined herein, datalink or network hardware including communication processors, circuits or chips, oscillating crystals, communication links, cables, twisted pair wiring, coaxial wiring, shielded wiring, transmitters, receivers, or transceivers, logic circuits, hard-wired logic circuits, reconfigurable logic circuits in a particular non-transient state configured according to the module specification, any actuator including at least an electrical, hydraulic, or pneumatic actuator, a solenoid, an op-amp, analog control elements (springs, filters, integrators, adders, dividers, gain elements), or digital control elements.

(127) The subject matter and the operations described in this specification can be implemented in digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them. The subject matter described in this specification can be implemented as one or more computer programs, e.g., one or more sets of computer program instructions, encoded on one or more computer storage media for execution by, or to control the operation of, data processing apparatuses. The program instructions can be encoded on an artificially generated propagated signal, e.g., a machine-generated electrical, optical, or electromagnetic signal that is generated to encode information for transmission to suitable receiver apparatus for execution by a data processing apparatus. A computer storage medium can be, or be included in, a computer-readable storage device, a computer-readable storage substrate, a random or serial access memory array or device, or a combination of one or more of them. While a computer storage medium is not a propagated signal, a computer storage medium can be a source or destination of computer program instructions encoded in an artificially generated propagated signal. The computer storage medium can be, or be included in, one or more separate components or media (e.g., multiple CDs, disks, or other storage devices including cloud storage). The operations described in this specification can be implemented as operations performed by a data processing apparatus on data stored on one or more computer-readable storage devices or received from other sources.

(128) The terms “computing device,” “computing environment,” “component” or “data processing apparatus” or the like encompass various apparatuses, devices, and machines for processing data, including by way of example a programmable processor, a memory, a computer, a system on a chip, or multiple ones, or combinations of the foregoing. The apparatus can include special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit). The apparatus can include, in addition to hardware, code that creates an execution environment for the computer program in question, e.g., code that constitutes processor firmware, a protocol stack, a database management system, an operating system, a cross-platform runtime environment, a virtual machine, or a combination of one or more of them. The apparatus and execution environment can realize various different computing model infrastructures, such as web services, distributed computing and grid computing infrastructures.

(129) A computer program (also known as a program, software, software application, app, script, or code) can be written in any form of programming language, including compiled or interpreted languages, declarative or procedural languages, and can be deployed in any form, including as a stand-alone program or as a module, component, subroutine, object, or other unit suitable for use in

a computing environment. A computer program can correspond to a file in a file system. A computer program can be stored in a portion of a file that holds other programs or data (e.g., one or more scripts stored in a markup language document), in a single file dedicated to the program in question, or in multiple coordinated files (e.g., files that store one or more modules, sub programs, or portions of code). A computer program can be deployed to be executed on one computer or on multiple computers that are located at one site or distributed across multiple sites and interconnected by a communication network.

(130) The processes and logic flows described in this specification can be performed by one or more programmable processors executing one or more computer programs to perform actions by operating on input data and generating output. The processes and logic flows can be performed by, and apparatuses can be implemented as, special purpose logic circuitry, e.g., an FPGA (field programmable gate array) or an ASIC (application specific integrated circuit). Devices suitable for storing computer program instructions and data can include non-volatile memory, media, and memory devices, including by way of example semiconductor memory devices, e.g., EPROM, EEPROM, and flash memory devices; magnetic disks, e.g., internal hard disks or removable disks; magneto optical disks; and CD ROM and DVD-ROM disks. The processor and the memory can be supplemented by, or incorporated in, special purpose logic circuitry.

(131) The subject matter described herein can be implemented in a computing system that includes a back end component, e.g., as a data server, or that includes a middleware component, e.g., an application server, or that includes a front end component, e.g., a client computer having a graphical user interface or a web browser through which a user can interact with an implementation of the subject matter described in this specification, or a combination of one or more such back end, middleware, or front end components. The components of the system can be interconnected by any form or medium of digital data communication, e.g., a communication network. Examples of communication networks include a local area network (“LAN”) and a wide area network (“WAN”), an inter-network (e.g., the Internet), and peer-to-peer networks (e.g., ad hoc peer-to-peer networks).

(132) While operations are depicted in the drawings in a particular order, such operations are not required to be performed in the particular order shown or in sequential order, and all illustrated operations are not required to be performed. Actions described herein can be performed in a different order. Furthermore, the terms “based on” or “responsive to” can imply both direct and indirect relationships, meaning that an action can be directly or indirectly based on or responsive to another action.

(133) Having now described some illustrative implementations, it is apparent that the foregoing is illustrative and not limiting, having been presented by way of example. In particular, although many of the examples presented herein involve specific combinations of method acts or system elements, those acts or operations and those elements can be combined in other ways to accomplish the same objectives. Acts, elements, and features discussed in connection with one implementation are not intended to be excluded from a similar role in other implementations or implementations.

(134) The phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including” “comprising” “having” “contained” “involving” “characterized by” “characterized in that” and variations thereof herein, is meant to encompass the items listed thereafter, equivalents thereof, and additional items, as well as alternate implementations consisting of the items listed thereafter exclusively. In one implementation, the systems and methods described herein consist of one, each combination of more than one, or all of the described elements, acts, or components.

(135) Any references to implementations or elements or acts of the systems and methods herein referred to in the singular can embrace implementations including a plurality of these elements from any section or paragraph, and any references in plural to any implementation or element or act herein can embrace implementations including only a single element. References in the singular or plural form are not intended to limit the presently disclosed systems or methods, their components,

acts, or elements to single or plural configurations. References to any act or element being based on any information, act or element may include implementations where the act or element is based at least in part on any information, act, or element.

(136) Any implementation disclosed herein may be combined with any other implementation or implementation, and references to “an implementation”, “an implementation,” “some implementations,” “one implementation” or the like are not necessarily mutually exclusive and are intended to indicate that a particular feature, structure, or characteristic described in connection with the implementation may be included in at least one implementation or implementation. Such terms as used herein are not necessarily all referring to the same implementation. Any implementation may be combined with any other implementation, inclusively or exclusively, in any manner consistent with the aspects and implementations disclosed herein.

(137) References to “or” may be construed as inclusive so that any terms described using “or” may indicate any of a single, more than one, and all of the described terms. References to at least one of a conjunctive list of terms may be construed as an inclusive OR to indicate any of a single, more than one, and all of the described terms. For example, a reference to “at least one of ‘A’ and ‘B’” can include only ‘A,’ only ‘B,’ as well as both ‘A’ and ‘B’. Such references used in conjunction with “comprising” or other open terminology can include additional items.

(138) Where technical features in the drawings, detailed description or any claim are followed by reference signs, the reference signs have been included to increase the intelligibility of the drawings, detailed description, and claims. Accordingly, neither the reference signs nor their absence has any limiting effect on the scope of any claim elements.

(139) Modifications of described elements and acts such as variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, numbers of inputs or outputs, use of materials, colors, orientation can occur without materially departing from the teachings and advantages of the subject matter disclosed herein. For example, elements shown as integrally formed can be constructed of multiple parts or elements, the position of elements can be reversed or otherwise varied, and the nature or number of discrete elements or positions can be altered or varied. Other substitutions, modifications, changes, and omissions can be made in the design, operating conditions and arrangement of the disclosed elements and operations without departing from the scope of the present disclosure.

(140) For example, descriptions of positive and negative electrical characteristics may be reversed. For example, a positive or a negative parameter, input, or difficulty direction with respect to a testing system can be increased or decreased, as desired. Elements described as negative or decreasing in value can instead be configured as positive or increasing in value and vice versa. For example, elements described as having a lower difficulty level can have a higher difficulty level and vice versa. Further relative parameter values described with respect to other values can include variations within $\pm 10\%$ or ± 10 degrees of a pure stated value, such as with ± 10 degrees of a pure vertical, parallel, or perpendicular positioning or a signal value. References to “approximately,” “substantially” or other terms of degree include variations of $\pm 10\%$ from the given measurement, unit, or range unless explicitly indicated otherwise. Coupled elements can be electrically, communicatively, mechanically, or physically coupled with one another directly or with intervening elements.

(141) While the disclosure has been described with respect to specific implementations, one skilled in the art will recognize that numerous modifications are possible. For instance, although specific examples of rules (including triggering conditions and/or resulting actions) and processes for generating suggested rules are described, other rules and processes can be implemented. Implementations of the disclosure can be realized using a variety of computer systems and communication technologies including but not limited to specific examples described herein.

(142) Implementations of the present disclosure can be realized using any combination of dedicated components and/or programmable processors and/or other programmable devices. The various

processes described herein can be implemented on the same processor or different processors in any combination. Where components are described as being configured to perform certain operations, such configuration can be accomplished, e.g., by designing electronic circuits to perform the operation, by programming programmable electronic circuits (such as microprocessors) to perform the operation, or any combination thereof. Further, while the implementations described above may make reference to specific hardware and software components, those skilled in the art will appreciate that different combinations of hardware and/or software components can be used and that particular operations described as being implemented in hardware can be implemented in software or vice versa.

(143) Computer programs incorporating various features of the present disclosure may be encoded and stored on various computer readable storage media; suitable media include magnetic disk or tape, optical storage media such as compact disk (CD) or DVD (digital versatile disk), flash memory, and other non-transitory media. Computer readable media encoded with the program code may be packaged with a compatible electronic device, or the program code may be provided separately from electronic devices (e.g., via Internet download or as a separately packaged computer-readable storage medium).

(144) Thus, although the disclosure has been described with respect to specific implementations, it will be appreciated that the disclosure is intended to cover all modifications and equivalents within the scope of the following claims.

(145) The machine learning model may be periodically and/or continuously trained. For instance, as the recommendations (or other predictions and derived information) are presented to the end-user, the system may monitor the end-user's behavior (e.g., whether a recommendation was accepted/rejected or whether a predicted attribute was revised). The monitored data may be fed back into the machine learning model to improve its accuracy. The machine learning model can recalibrate itself accordingly, such that the results are customized for the end-user.

(146) It should be understood that the disclosed implementations are not representative of all claimed innovations. As such, certain aspects of the disclosure have not been discussed herein. That alternate implementations may not have been presented for a specific portion of the innovations or that further undescribed alternate implementations may be available for a portion is not to be considered a disclaimer of those alternate implementations. Thus, it is to be understood that other implementations can be utilized and functional, logical, operational, organizational, structural and/or topological modifications may be made without departing from the scope of the disclosure. As such, all examples and/or implementations are deemed to be non-limiting throughout this disclosure.

(147) Some implementations described herein relate to methods. It should be understood that such methods can be computer implemented methods (e.g., instructions stored in memory and executed on processors). Where methods described above indicate certain events occurring in a certain order, the ordering of certain events can be modified. Additionally, certain of the events can be performed repeatedly, concurrently in a parallel process, when possible, as well as performed sequentially as described above. Furthermore, certain implementations can omit one or more described events.

(148) All definitions, as defined and used herein, should be understood to control over dictionary definitions, definitions in documents incorporated by reference, and/or ordinary meanings of the defined terms.

(149) In the implementations, as well as in the specification above, all transitional phrases such as “comprising,” “including,” “carrying,” “having,” “containing,” “involving,” “holding,” “composed of,” and the like are to be understood to be open-ended, i.e., to mean including but not limited to. Only the transitional phrases “consisting of” and “consisting essentially of” shall be closed or semi-closed transitional phrases, respectively, as set forth in the United States Patent Office Manual of Patent Examining Procedures, Section 2111.03.

Claims

1. A system, comprising: one or more processors, coupled with memory, to: maintain, in a database, a plurality of vehicle profiles for a plurality of vehicles, each vehicle profile of the plurality of vehicle profiles including license plate information of a respective vehicle of the plurality of vehicles, the license plate information encoded in accordance with a character replacement schema; capture, via an image capture device, one or more images of at least a portion of a vehicle positioned within a region of interest of a service facility; identify, using the one or more images, a first sequence of characters of a license plate of the vehicle; determine one or more characters of the first sequence of characters that satisfy the character replacement schema; generate a second sequence of characters by replacing the one or more characters that satisfy the character replacement schema with one or more corresponding replacement characters in the first sequence of characters; identify, from the plurality of vehicle profiles maintained in the database, a vehicle profile of the vehicle positioned within the region of interest based on executing a query using the generated second sequence of characters to compare with the license plate information encoded in accordance with the character replacement schema of the plurality of vehicle profiles; and transmit, to a device, data included in the vehicle profile based on identifying the vehicle profile.
2. The system of claim 1, wherein the data transmitted to the device is data for presentation at the device and wherein the device is one of an operator device, an administrator device or a point of sale device of a third party server.
3. The system of claim 1, wherein to transmit, to the device, data comprises the one or more processors configured to transmit, to a car wash controller, instructions to cause the service facility to provide a car wash type corresponding to the vehicle profile of the vehicle.
4. The system of claim 1, comprising the one or more processors to: compare, using a lookup table, the one or more characters of the first sequence with a plurality of replacement characters of the license plate information encoded in accordance with the character replacement schema and comprising the one or more corresponding replacement characters; match, using the comparison of the one or more characters of the first sequence with the plurality of replacement characters, the one or more characters of the first sequence with the one or more corresponding replacement characters; and determine, based on the match, that the one or more characters of the first sequence satisfies the character replacement schema.
5. The system of claim 1, comprising the one or more processors to: select, using a lookup table configured to relate characters of license plates with replacement characters for the license plates, one or more representative character pairs corresponding to the one or more characters of the first sequence; and generate the second sequence of characters, responsive to the selection.
6. The system of claim 5, wherein the lookup table relates the one or more characters of the first sequence with the one or more corresponding replacement characters and the one or more representative character pairs include relate at least one of: a character “1” and a character “I”, a character “2” and a character “Z”, a character “5” and a character “S”, a character “0” and a character “O”, or a character “A” and a character “4”.
7. The system of claim 1, comprising the one or more processors to: retrieve, based on the vehicle profile, a setting for a car wash routine of a vehicle service at the service facility; and actuate a component controlling access to the service facility to initiate the car wash routine, based on the setting.
8. The system of claim 1, comprising the one or more processors to: identify, based on the one or more images, a characteristic of the vehicle; compare the characteristic with one or more characteristics of the vehicle determined based on prior captured images; and detect, based on the comparison of the characteristics with the one or more characteristics of the vehicle, a discrepancy between the characteristic and the one or more characteristics.

9. The system of claim 8, comprising the one or more processors to: detect, based on the discrepancy, a fraudulent activity; and generate an alert to display on a device to indicate the fraudulent activity.

10. The system of claim 8, comprising the one or more processors to: determine, based on the discrepancy, that multiple vehicles have used the license plate for services of the service facility; and update information on the vehicle profile responsive to the determination that the multiple vehicles have used the license plate.

11. The system of claim 1, comprising the one or more processors to: maintain an image log of the vehicle, the image log comprising one or more prior captured images indexed according to the license plate information; and compare the one or more images of the vehicle with the one or more prior captured images to detect discrepancies in vehicle characteristics.

12. The system of claim 1, comprising the one or more processors to: identify, based on the vehicle profile, a service setting for the vehicle; generate, based on the service setting, a service to be provided to the vehicle; and provide, for display on a device, a prompt for the service to be provided.

13. The system of claim 12, comprising the one or more processors to: receive, responsive to the prompt, an update to the service to be provided; and store, in the vehicle profile, the updated service as the service setting.

14. A method, comprising: maintaining, by one or more processors, in a database, a plurality of vehicle profiles for a plurality of vehicles, each vehicle profile of the plurality of vehicle profiles including license plate information of a respective vehicle of the plurality of vehicles, the license plate information encoded in accordance with a character replacement schema; capturing, by the one or more processors, via an image capture device, one or more images of at least a portion of a vehicle positioned within a region of interest of a service facility; identifying, by the one or more processors, using the one or more images, a first sequence of characters of a license plate of the vehicle; determining, by the one or more processors, one or more characters of the first sequence of characters that satisfy the character replacement schema; generating, by the one or more processors, a second sequence of characters by replacing the one or more characters that satisfy the character replacement schema with one or more corresponding replacement characters in the first sequence of characters; identifying, by the one or more processors, from the plurality of vehicle profiles maintained in the database, a vehicle profile of the vehicle positioned within the region of interest based on executing a query using the generated second sequence of characters to compare with the license plate information encoded in accordance with the character replacement schema of the plurality of vehicle profiles; and transmitting, by the one or more processors, to a device, data included in the vehicle profile based on identifying the vehicle profile.

15. The method of claim 14, further comprising: selecting, by the one or more processors, using a lookup table configured to relate characters of license plates with replacement characters for the license plates, one or more representative character pairs corresponding to the one or more characters of the first sequence; and generating, by the one or more processors, the second sequence of characters, responsive to the selection.

16. The method of claim 15, wherein the lookup table relates the one or more characters of the first sequence with the one or more corresponding replacement characters and the one or more representative character pairs include relate at least one of: a character “1” and a character “I”, a character “2” and a character “Z”, a character “5” and a character “S”, a character “0” and a character “O”, or a character “A” and a character “4”.

17. The method of claim 14, further comprising: identifying, by the one or more processors, based on the vehicle profile, a service setting for the vehicle; generating, by the one or more processors, based on the service setting, a service to be provided to the vehicle; and providing, by the one or more processors, for display on a device, a prompt for the service to be provided.

18. The method of claim 17, further comprising: receiving, by the one or more processors,

responsive to the prompt, an update to the service to be provided; and storing, by the one or more processors, in the vehicle profile, the updated service as the service setting.

19. A non-transitory computer-readable medium comprising instructions that, when executed by one or more processors, cause the one or more processors to: maintain, in a database, a plurality of vehicle profiles for a plurality of vehicles, each vehicle profile of the plurality of vehicle profiles including license plate information of a respective vehicle of the plurality of vehicles, the license plate information encoded in accordance with a character replacement schema; capture, via an image capture device, one or more images of at least a portion of a vehicle positioned within a region of interest of a service facility; identify, using the one or more images, a first sequence of characters of a license plate of the vehicle; determine one or more characters of the first sequence of characters that satisfy the character replacement schema; generate a second sequence of characters by replacing the one or more characters that satisfy the character replacement schema with one or more corresponding replacement characters in the first sequence of characters; identify, from the plurality of vehicle profiles maintained in the database, a vehicle profile of the vehicle positioned within the region of interest based on executing a query using the generated second sequence of characters to compare with the license plate information encoded in accordance with the character replacement schema of the plurality of vehicle profiles; and transmit, to a device, data included in the vehicle profile based on identifying the vehicle profile.

20. The non-transitory computer-readable medium of claim 19, wherein to transmit, to the device, the data comprises the one or more processors configured to transmit, to a car wash controller, instructions to cause the service facility to provide a car wash type corresponding to the vehicle profile of the vehicle.
