

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12384008
Kind Code	B2
Date of Patent	August 12, 2025
Inventor(s)	Osawa; Yusuke et al.

Fastening tool

Abstract

A fastening tool includes: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; a motor configured to move the bit holding portion along the axial direction; and a control unit configured to control a position of the bit holding portion along the axial direction by the number of rotations of the motor. The control unit is configured to execute an initialization operation of setting a standby position of the bit holding portion along the axial direction, and control a position of the bit holding portion along the axial direction from the standby position by the number of rotations of the motor.

Inventors:	Osawa; Yusuke (Tokyo, JP), Takeuchi; Kazuya (Tokyo, JP)
Applicant:	MAX CO., LTD. (Tokyo, JP)
Family ID:	83283185
Assignee:	Max Co., Ltd. (Tokyo, JP)
Appl. No.:	17/942754
Filed:	September 12, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230082435 A1	Mar. 16, 2023

Foreign Application Priority Data

JP	2021-149655	Sep. 14, 2021
JP	2021-149656	Sep. 14, 2021
JP	2021-149657	Sep. 14, 2021
JP	2022-067701	Apr. 15, 2022
JP	2022-067704	Apr. 15, 2022

Publication Classification

Int. Cl.: **B25B21/00** (20060101); **B25F5/00** (20060101); **H02P23/04** (20060101); **H02P23/14** (20060101); B25B23/00 (20060101); B25B23/04 (20060101); B25B23/06 (20060101)

U.S. Cl.:

CPC **B25B21/008** (20130101); **B25B21/002** (20130101); **B25B21/007** (20130101); **B25F5/001** (20130101); **H02P23/04** (20130101); **H02P23/14** (20130101); B25B23/0035 (20130101); B25B23/04 (20130101); B25B23/06 (20130101)

Field of Classification Search

CPC: B25F (5/002); B25B (23/0064); B25B (23/045); B25B (23/06); B25B (23/04); B25B (23/0035); B25B (21/007); B25B (21/00); B25B (21/002); B25B (21/008); H02P (23/14); H02P (23/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2013/0255447	12/2012	Po	81/57.11	B25B 23/045
2015/0135907	12/2014	Hirabayashi et al.	N/A	N/A
2020/0100799	12/2019	Delman et al.	N/A	N/A
2020/0139424	12/2019	Yabuguchi et al.	N/A	N/A
2020/0391367	12/2019	Tsai	N/A	B25C 1/06
2022/0305603	12/2021	Rajzer	N/A	B23Q 17/0961

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110769950	12/2019	CN	N/A
2644322	12/2012	EP	N/A
3170626	12/2016	EP	N/A
4052848	12/2021	EP	N/A
S50-143170	12/1974	JP	N/A
H04-075881	12/1991	JP	N/A
H10-034448	12/1997	JP	N/A
2002307320	12/2001	JP	N/A
2004136390	12/2003	JP	N/A
2013018067	12/2012	JP	N/A
5262461	12/2012	JP	N/A
2015066661	12/2014	JP	N/A
6197547	12/2016	JP	N/A
2020006452	12/2019	JP	N/A
98/10900	12/1997	WO	N/A
2013/183433	12/2012	WO	N/A

OTHER PUBLICATIONS

Primary Examiner: Wittenschlaeger; Thomas M

Attorney, Agent or Firm: Banner & Witcoff, Ltd.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) This application is based on and claims priority under 35 USC 119 from Japanese Patent Application No. 2021-149655 filed on Sep. 14, 2021, Japanese Patent Application No. 2021-149656 filed on Sep. 14, 2021, Japanese Patent Application No. 2021-149657 filed on Sep. 14, 2021, Japanese Patent Application No. 2022-067701 filed on Apr. 15, 2022, and Japanese Patent Application No. 2022-067704 filed on Apr. 15, 2022, the contents of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to a fastening tool in which a driver bit is engaged with a screw, the screw is pressed against a fastening target by the driver bit, and the driver bit is rotated to screw.

BACKGROUND

(3) There is a tool called a portable striking machine which uses an air pressure of compressed air supplied from an air compressor or a combustion pressure of gas to sequentially strike connection stoppers loaded in a magazine from a tip end of a driver guide.

(4) As a tool which rotates a bit to tighten a screw and moves the bit in a direction of tightening the screw, a pneumatic screw driving machine is proposed in the related art, in which the bit is rotated by an air motor and moved in a direction of tightening the screw by an air pressure (for example, see Publication of Japanese Patent No. 5262461).

(5) A screwdriver is proposed in which a spring is compressed by a driving force of a motor which rotates a screw, and the screw is driven by biasing of the spring (for example, see Publication of Japanese Patent No. 6197547).

(6) In both of the screw driving machine which uses the air pressure and the screwdriver which drives the screw by biasing of the spring, it is difficult to control a movement end position of the driver bit by an operation of moving the driver bit in a direction of tightening the screw, and it is difficult to implement, by control, a state in which a head portion of the screw is flush with a fastening target.

(7) The present disclosure is made to solve such a problem, and an object of the present disclosure is to provide a fastening tool capable of controlling a movement end position of a driver bit by an operation of moving the driver bit in a direction of tightening a screw.

SUMMARY

(8) A first aspect of the present disclosure relates to a fastening tool including: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; a motor configured to move the bit holding portion along the axial direction; and a control unit configured to control a position of the bit holding portion along the axial direction by the number of rotations of the motor. The control unit is configured to execute an initialization operation of setting a standby position of the bit holding portion along the axial direction, and control a position of the bit holding portion along the axial direction from the standby position by the number of rotations of the motor.

- (9) A second aspect of the present disclosure relates to a fastening tool including: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; a motor configured to perform at least one of rotation of the bit holding portion and movement of the bit holding portion along the axial direction; a contact member which contacts a fastening target; and a control unit configured to control a timing at which driving of the motor is stopped based on a movement amount of the contact member in the axial direction when the contact member contacts the fastening target.
- (10) A third aspect of the present disclosure relates to a fastening tool including: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; the motor configured to rotate the bit holding portion; a fluctuation detection unit configured to detect a factor causing a fluctuation in a rotation speed of the motor; and a control unit configured to perform control to prevent the fluctuation in the rotation speed of the motor, when the fluctuation detection unit detects a factor causing the fluctuation in the rotation speed of the motor.
-

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1A is a side cross-sectional view showing an example of an internal structure of a fastening tool according to the present embodiment.
- (2) FIG. 1B is a top cross-sectional view showing an example of the internal structure of the fastening tool according to the present embodiment.
- (3) FIG. 1C is a front cross-sectional view showing an example of the internal structure of the fastening tool according to the present embodiment.
- (4) FIG. 2A is an exploded perspective view showing an example of the internal structure of the fastening tool according to the present embodiment.
- (5) FIG. 2B is an external perspective view showing an example of the fastening tool according to the present embodiment.
- (6) FIG. 3A is a perspective view showing an example of configurations of main parts of the fastening tool according to the present embodiment.
- (7) FIG. 3B is a perspective view showing an example of configurations of main parts of the fastening tool according to the present embodiment.
- (8) FIG. 4A is a cross-sectional perspective view showing an example of configurations of main parts of the fastening tool according to the present embodiment.
- (9) FIG. 4B is a cross-sectional perspective view showing an example of configurations of main parts of the fastening tool according to the present embodiment.
- (10) FIG. 4C is a cross-sectional perspective view showing an example of configurations of main parts of the fastening tool according to the present embodiment.
- (11) FIG. 5 is a top cross-sectional view showing an example of configurations of main parts of the fastening tool according to the present embodiment.
- (12) FIG. 6A is a top cross-sectional view showing an example of the internal structure of the fastening tool according to the present embodiment.
- (13) FIG. 6B is a top cross-sectional view showing an example of the internal structure of the fastening tool according to the present embodiment.
- (14) FIG. 7A is a cross-sectional view showing an example of an attachment and detachment holding mechanism.
- (15) FIG. 7B is a cross-sectional view showing an example of the attachment and detachment holding mechanism.
- (16) FIG. 8A is a perspective view showing an example of the attachment and detachment holding

mechanism.

(17) FIG. **8B** is a perspective view showing an example of the attachment and detachment holding mechanism.

(18) FIG. **9** is a perspective view showing an example of a screw feeding portion and a nose portion according to the present embodiment.

(19) FIG. **10A** is a perspective view showing an example of the fastening tool according to the present embodiment as viewed from a rear side.

(20) FIG. **10B** is a perspective view showing an example of the fastening tool according to the present embodiment as viewed from the rear side.

(21) FIG. **10C** is a perspective view showing an example of the fastening tool according to the present embodiment as viewed from the rear side.

(22) FIG. **11** is a perspective view showing an example of a setting portion.

(23) FIG. **12** is a block diagram showing an example of the fastening tool according to the present embodiment.

(24) FIG. **13A** is a side cross-sectional view showing an example of an operation of the fastening tool according to the present embodiment.

(25) FIG. **13B** is a top cross-sectional view showing an example of the operation of the fastening tool according to the present embodiment.

(26) FIG. **14** is a flowchart showing an example of the operation of the fastening tool according to the present embodiment.

(27) FIG. **15A** is a cross-sectional view showing a fastening state of a screw.

(28) FIG. **15B** is a cross-sectional view showing a fastening state of the screw.

(29) FIG. **15C** is a cross-sectional view showing a fastening state of the screw.

(30) FIG. **16A** is a diagram showing an example of an operation of setting a standby position of a holding member and a moving member in a first initialization operation.

(31) FIG. **16B** is a diagram showing an example of the operation of setting the standby position of the holding member and the moving member in the first initialization operation.

(32) FIG. **16C** is a diagram showing an example of the operation of setting the standby position of the holding member and the moving member in the first initialization operation.

(33) FIG. **16D** is a diagram showing an example of the operation of setting the standby position of the holding member and the moving member in the first initialization operation.

(34) FIG. **17A** is a diagram showing an example of an operation of moving the holding member and the moving member to the standby position in a second initialization operation.

(35) FIG. **17B** is a diagram showing an example of the operation of moving the holding member and the moving member to the standby position in the second initialization operation.

(36) FIG. **17C** is a diagram showing an example of the operation of moving the holding member and the moving member to the standby position in the second initialization operation.

(37) FIG. **18** is a flowchart showing an example of an operation of selecting the first initialization operation and the second initialization operation.

(38) FIG. **19** is a flowchart showing a modification of the operation of the fastening tool according to the present embodiment.

(39) FIG. **20** is a graph showing a relationship between output of a contact switch portion and control over a bit rotation motor and a bit movement motor.

(40) FIG. **21** is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment.

(41) FIG. **22A** is a graph showing a relationship between a load and control over the bit rotation motor.

(42) FIG. **22B** is a graph showing a relationship between a load and control over the bit rotation motor.

(43) FIG. **23** is a flowchart showing another modification of the operation of the fastening tool

according to the present embodiment.

(44) FIG. 24A is a graph showing a relationship between rotation speeds of the bit rotation motor and the bit movement motor under feedback control.

(45) FIG. 24B is a graph showing a relationship between a moving speed of the screw by rotation of the bit rotation motor and a moving speed of a driver bit by the bit movement motor under the feedback control.

(46) FIG. 25 is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment.

(47) FIG. 26A is a graph showing a relationship between a load and control over the bit movement motor.

(48) FIG. 26B is a graph showing a relationship between a load and control over the bit movement motor.

(49) FIG. 27 is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment.

(50) FIG. 28 is an external side view showing another modification of the fastening tool according to the present embodiment.

(51) FIG. 29 is a block diagram showing another modification of the fastening tool according to the present embodiment.

(52) FIG. 30 is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment.

(53) FIG. 31 is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment.

(54) FIG. 32 is a graph showing a relationship between a position state of a contact member and control over the bit rotation motor and the bit movement motor.

(55) FIG. 33 is a block diagram showing another modification of the fastening tool according to the present embodiment.

DESCRIPTION OF EMBODIMENTS

(56) Hereinafter, an embodiment of a fastening tool according to the present disclosure will be described with reference to the drawings.

Configuration Example of Fastening Tool According to Present Embodiment

(57) FIG. 1A is a side cross-sectional view showing an example of an internal structure of the fastening tool according to the present embodiment.

(58) FIG. 1B is a top cross-sectional view showing an example of the internal structure of the fastening tool according to the present embodiment.

(59) FIG. 1C is a front cross-sectional view showing an example of the internal structure of the fastening tool according to the present embodiment.

(60) FIG. 2A is an exploded perspective view showing an example of the internal structure of the fastening tool according to the present embodiment.

(61) FIG. 2B is an external perspective view showing an example of the fastening tool according to the present embodiment.

(62) The fastening tool **1** according to the present embodiment includes a bit holding portion **3** that holds a driver bit **2** so as to be rotatable and movable in an axial direction, a first drive unit **4** that rotates the driver bit **2** held by the bit holding portion **3**, and a second drive unit **5** that moves the driver bit **2** held by the bit holding portion **3** in the axial direction.

(63) The fastening tool **1** includes a screw accommodating portion **6** in which a screw **200** is accommodated, a screw feeding portion **7** that feeds the screw accommodated in the screw accommodating portion **6**, and a nose portion **8** that is pressed against a fastening target to which the screw **200** is fastened and into which the screw is injected.

(64) Further, the fastening tool **1** includes a tool body **10** and a handle **11**. The fastening tool **1** includes a battery attachment portion **13** to which a battery **12** is detachably attached at an end

portion of the handle **11**.

(65) In the fastening tool **1**, the tool body **10** extends in one direction along the axial direction of the driver bit **2** indicated by arrows **A1** and **A2**, and the handle **11** extends in another direction intersecting an extending direction of the tool body **10**. In the fastening tool **1**, a direction in which the tool body **10** extends, that is, the axial direction of the driver bit **2** indicated by the arrows **A1** and **A2** is a front-rear direction. In the fastening tool **1**, a direction in which the handle **11** extends is an upper-lower direction. Further, in the fastening tool **1**, a direction orthogonal to the extending direction of the tool body **10** and an extending direction of the handle **11** is a left-right direction.

(66) The first drive unit **4** is provided on a rear side, which is one side of the tool body **10**, with the handle **11** interposed therebetween.

(67) The second drive unit **5** is provided on a front side, which is the other side of the tool body **10**, with the handle **11** interposed therebetween.

(68) In the screw accommodating portion **6**, a plurality of screws **200** are connected by a connecting band, and a connecting screw wound in a spiral shape is accommodated.

(69) FIGS. **3A** and **3B** are perspective views showing an example of configurations of main parts of the fastening tool according to the present embodiment. FIGS. **4A** to **4C** are cross-sectional perspective views showing an example of configurations of main parts of the fastening tool according to the present embodiment. FIG. **5** is a top cross-sectional view showing an example of configurations of main parts of the fastening tool according to the present embodiment, and shows details of the bit holding portion **3** and the first drive unit **4**. Next, the bit holding portion **3** and the first drive unit **4** will be described with reference to the drawings.

(70) The bit holding portion **3** is an example of a tip end tool holding portion, and includes a holding member **30** that detachably holds the driver bit **2**, which is an example of a tip end tool, a rotation guide member **31** that supports the holding member **30** so as to be movable in the front-rear direction indicated by the arrows **A1** and **A2** along the axial direction of the driver bit **2** and rotates together with the holding member **30**, a moving member **32** that moves the holding member **30** in the front-rear direction along the rotation guide member **31**, and a biasing member **33** that biases the moving member **32** in a rear direction indicated by the arrow **A2**.

(71) The holding member **30** has an outer diameter slightly smaller than an inner diameter of the rotation guide member **31**, and is formed of, for example, a columnar member inserted inside the rotation guide member **31**. In the holding member **30**, an opening **30a** having a shape matching a cross-sectional shape of the driver bit **2** is provided at an end portion on a front side along the axial direction of the driver bit **2**. The holding member **30** includes, in the opening **30a**, an attachment and detachment holding mechanism **30c** that detachably holds the driver bit **2**. In the holding member **30**, the opening **30a** is exposed to an inside of the rotation guide member **31**, and the driver bit **2** is detachably inserted into the opening **30a**.

(72) The rotation guide member **31** extends along the extending direction of the tool body **10**, that is, along the front-rear direction indicated by the arrows **A1** and **A2** along the axial direction of the driver bit **2**. The rotation guide member **31** has a cylindrical shape into which the holding member **30** enters, and an end portion on a front side of the rotation guide member **31** is rotatably supported by a metal front frame **10b** provided on a front side of a resin case **10a** forming an exterior of the tool body **10** via a bearing **34a** that is an example of a bearing. An end portion on a rear side of the rotation guide member **31** is connected to the first drive unit **4**.

(73) In the rotation guide member **31**, groove portions **31a** extending in the front-rear direction indicated by the arrows **A1** and **A2** along the axial direction of the driver bit **2** are formed at two positions of side portions facing each other in a radial direction. The rotation guide member **31** penetrates the holding member **30** in the radial direction, and a connecting member **30b** protruding from both sides of the holding member **30** enters the groove portions **31a**, so that the rotation guide member **31** is connected to the holding member **30** via the connecting member **30b**.

(74) The holding member **30** is provided with a hole portion penetrating in a direction

perpendicular to a rotation direction of the driver bit **2**, and the connecting member **30b** is inserted into the hole portion and fixed by a pin **30f**. The connecting member **30b** is formed of a tubular member having an oval cross-sectional shape.

(75) The connecting member **30b** is oriented with a longitudinal direction of the oval shape along an extending direction of the groove portion **31a** parallel to the axial direction of the driver bit **2** indicated by the arrows **A1** and **A2**, a lateral direction of the oval shape orthogonal to the extending direction of the groove portion **31a** indicated by arrows **B1** and **B2**, that is, along a rotation direction of the rotation guide member **31**. The connecting member **30b** is configured such that a width of the lateral direction of the oval shape, that is, a width of the rotation guide member **31** along the rotation direction is slightly smaller than a width of the groove portion **31a** along the same direction.

(76) Accordingly, the connecting member **30b** inserted into the groove portion **31a** is supported by the groove portion **31a** so as to be movable along an axial direction of the rotation guide member **31**. Movement of the connecting member **30b** along the rotation direction with respect to the rotation guide member **31** is restricted between one side surface and the other side surface of the groove portion **31a** along the extending direction of the groove portion **31a**. Therefore, by an operation of rotating the rotation guide member **31**, the connecting member **30b** is pressed by one side surface or the other side surface of the groove portion **31a** according to the rotation direction of the rotation guide member **31**, and receives a force in a circumferential direction which is the rotation direction from the rotation guide member **31**.

(77) Therefore, when the rotation guide member **31** rotates, the connecting member **30b** is pressed by the groove portion **31a** of the rotation guide member **31**, so that the holding member **30** rotates together with the rotation guide member **31**. The connecting member **30b** is guided by the groove portion **31a** of the rotation guide member **31**, and the holding member **30** moves in the front-rear direction along the axial direction of the driver bit **2**.

(78) The moving member **32** is an example of a transmission member, and includes a first moving member **32a** which rotates together with the holding member **30** and moves the holding member **30** in the front-rear direction along the rotation guide member **31**, a second moving member **32c** which is supported by the first moving member **32a** via a bearing **32b** and presses the first moving member **32a** via the bearing **32b**, and a buffer member **32d** which is attached to a rear side of the second moving member **32c**.

(79) The first moving member **32a** has an inner diameter slightly larger than an outer diameter of the rotation guide member **31**, and is formed of, for example, a cylindrical member inserted outside the rotation guide member **31**. The first moving member **32a** is connected to the holding member **30** via the connecting member **30b** protruding from the groove portion **31a** of the rotation guide member **31**, so that the first moving member **32a** is supported so as to be movable along the axial direction of the rotation guide member **31**.

(80) The bearing **32b** is an example of the bearing and is inserted between an outer circumference of the first moving member **32a** and an inner circumference of the second moving member **32c**. The first moving member **32a** forms a bearing inner ring holding member which holds an inner ring of the bearing **32b**, and the second moving member **32c** forms a bearing outer ring holding member which holds an outer ring of the bearing **32b**. In the bearing **32b**, the inner ring is supported on the outer circumference of the first moving member **32a** so as not to be movable in the rotation direction and the axial direction, and the outer ring is supported on the inner circumference of the second moving member **32c** so as not to be movable in the rotation direction and the axial direction.

(81) Accordingly, the second moving member **32c** is connected to the first moving member **32a** via the bearing **32b** in a state in which movement of the second moving member **32c** in the front-rear direction along the axial direction is restricted. The second moving member **32c** rotatably supports the first moving member **32a** via the bearing **32b**.

(82) Therefore, the first moving member 32a is pressed by the second moving member 32c via the bearing 32b by a movement operation of the second moving member 32c in the front-rear direction along the axial direction, and moves in the front-rear direction along the axial direction together with the second moving member 32c. The first moving member 32a is rotatable with respect to the second moving member 32c that is not rotatable with respect to the rotation guide member 31.

(83) The biasing member 33 is formed of a coil spring in the present example, is outside the rotation guide member 31, and is inserted between the front frame 10b provided on the front side of the case 10a of the tool body 10 and the second moving member 32c of the moving member 32, and abuts against a spring seat 32f that contacts an end surface of the outer ring of the bearing 32b. The biasing member 33 is compressed by movement of the moving member 32 in a forward direction indicated by the arrow A1, and applies a force for pressing the moving member 32 in a rearward direction indicated by the arrow A2 to the moving member 32.

(84) The first drive unit 4 includes a bit rotation motor 40 which is driven by electricity supplied from the battery 12, and a speed reducer 41. The bit rotation motor 40 is an example of a motor or a first motor, and a shaft 40a of the bit rotation motor 40 is connected to the speed reducer 41, and a shaft 41a of the speed reducer 41 is connected to the rotation guide member 31. In the first drive unit 4, the speed reducer 41 uses planetary gears, and the bit rotation motor 40 is disposed coaxially with the rotation guide member 31, the holding member 30, and the driver bit 2 held by the holding member 30.

(85) In the first drive unit 4, the bit rotation motor 40 and the speed reducer 41 are attached to a metal rear frame 10c provided on a rear side of the case 10a of the tool body 10, and the shaft 41a of the speed reducer 41 is supported by the rear frame 10c via a bearing 42. The end portion on the rear side of the rotation guide member 31 is connected to the shaft 41a of the speed reducer 41, and the shaft 41a is supported by the rear frame 10c via the bearing 42, so that the rotation guide member 31 is rotatably supported via the bearing 42, which is an example of the bearing.

(86) The bit holding portion 3 and the first drive unit 4 are integrally assembled by connecting the front frame 10b and the rear frame 10c by a coupling member 10d extending in the front-rear direction, and the front frame 10b is fixed to the case 10a of the tool body 10 by a screw 10e.

(87) In the bit holding portion 3, the end portion on the front side of the rotation guide member 31 is supported by the front frame 10b fixed to the front side of the case 10a of the tool body 10 via the bearing 34a, and the end portion on the rear side of the rotation guide member 31 is supported by the rear frame 10c fixed to the rear side of the case 10a via the shaft 41a of the speed reducer 41 and the bearing 42. Therefore, in the bit holding portion 3, the rotation guide member 31 is rotatably supported by the tool body 10.

(88) Accordingly, the first drive unit 4 rotates the rotation guide member 31 by the bit rotation motor 40. When the rotation guide member 31 rotates, the connecting member 30b is pressed by the groove portion 31a of the rotation guide member 31, so that the holding member 30 holding the driver bit 2 rotates together with the rotation guide member 31.

(89) In the bit holding portion 3, the second moving member 32c is provided with a guide member 32g. The coupling member 10d is provided with a pair of guide wall portions 10g at an interval slightly larger than a diameter of the guide member 32g, and the guide member 32g enters between the pair of guide wall portions 10g, the pair of guide wall portions 10g face a circumferential surface of the guide member 32g.

(90) Accordingly, the guide member 32g is guided by the coupling member 10d, so that the second moving member 32c is movable in the front-rear direction indicated by the arrows A1 and A2 along the axial direction of the driver bit 2, and rotation of the second moving member 32c following the rotation guide member 31 is restricted.

(91) FIGS. 6A and 6B are top cross-sectional views showing an example of an internal structure of the fastening tool according to the present embodiment, and show details of the second drive unit 5. Next, the second drive unit 5 will be described with reference to the drawings.

(92) The second drive unit 5 includes a bit movement motor 50 which is driven by electricity supplied from the battery 12, and a speed reducer 51. The bit movement motor 50 is an example of a motor or a second motor, and a shaft 50a of the bit movement motor 50 is connected to the speed reducer 51, and a shaft 51a of the speed reducer 51 is connected to a pulley 52 which is an example of the transmission member. In the second drive unit 5, the pulley 52 is supported by the tool body 10 via a bearing 53. In the second drive unit 5, the shaft 50a of the bit movement motor 50 is disposed along the extending direction of the handle 11.

(93) In the second drive unit 5, one end of a linear wire 54, which is an example of the transmission member, is connected to the pulley 52, and the wire 54 is wound around the pulley 52 by rotation of the pulley 52. The other end of the wire 54 is connected to a wire connecting portion 32h provided in the second moving member 32c of the moving member 32.

(94) Accordingly, the second drive unit 5 rotates the pulley 52 by the bit movement motor 50 to wind the wire 54, thereby moving the second moving member 32c in the forward direction indicated by the arrow A1. In the bit holding portion 3, when the second moving member 32c moves in the forward direction, the first moving member 32a is pressed via the bearing 32b, and the first moving member 32a moves in the forward direction along the axial direction together with the second moving member 32c. When the first moving member 32a moves in the forward direction, the holding member 30 connected to the first moving member 32a via the connecting member 30b moves in the forward direction, and the driver bit 2 held by the holding member 30 moves in the forward direction indicated by the arrow A1.

(95) The second drive unit 5 is offset to one side with respect to a substantially center of the fastening tool 1 in the left-right direction such that a tangential direction of a portion of the pulley 52 around which the wire 54 is wound is along an extending direction of the rotation guide member 31. That is, a center of the pulley 52, in the present example, the shaft 50a of the bit movement motor 50 is offset to one side with respect to the rotation guide member 31, and a portion 52a of the pulley 52 around which the wire 54 is wound overlaps the rotation guide member 31 when viewed from an axial direction of the pulley 52.

(96) The pulley 52 and the like are disposed such that the wire 54 between the pulley 52 and the second moving member 32c is parallel to the axial direction of the rotation guide member 31 in a radial direction of the pulley 52 as shown in FIGS. 6A and 6B, and is parallel to the axial direction of the rotation guide member 31 also in an axial direction of the bit movement motor 50 orthogonal to the radial direction of the pulley 52 as shown in FIG. 1A.

(97) Further, when the wire 54 is wound on the pulley 52 in an overlapping manner, a distance from a center of the pulley 52 to the wire 54 changes according to the number of turns, so that a movement amount of the driver bit 2 when the pulley 52 makes one rotation changes. An angle formed by a direction in which the wire 54 extends between the pulley 52 and the second moving member 32c and a moving direction of the driver bit 2 along the axial direction of the rotation guide member 31 changes.

(98) Therefore, a diameter and the like of the pulley 52 are set so that a rotation amount a of the pulley 52 necessary for moving the driver bit 2 by a predetermined amount is less than 360°.

(99) Accordingly, when the pulley 52 winds the wire 54 in order to move the driver bit 2 by a predetermined amount, as shown in FIG. 6B, the wire 54 is not wound around the pulley 52 in an overlapping manner, and the movement amount of the driver bit 2 is prevented from becoming inaccurate. A change in parallelism between the direction in which the wire 54 extends between the pulley 52 and the second moving member 32c and the moving direction of the driver bit 2 along the axial direction of the rotation guide member 31 is prevented.

(100) Therefore, a relationship between the number of rotations of the bit movement motor 50 and a movement amount of the holding member 30 becomes a one-to-one relationship in an entire movable range of the holding member 30, and the movement amount of the holding member 30 along the axial direction of the rotation guide member 31 can be controlled by controlling the

number of rotations of the bit movement motor **50**. That is, the movement amount of the driver bit **2** attached to the holding member **30** can be controlled by controlling the number of rotations of the bit movement motor **50**.

(101) Regardless of a winding amount of the wire **54**, a tension applied to the wire **54** is always parallel to the moving direction of the driver bit **2** along the axial direction of the rotation guide member **31**, and it is possible to move the driver bit **2** and prevent a decrease of transmission efficiency of a force for pressing the screw **200** via the driver bit **2**.

(102) Accordingly, the wire **54** between the pulley **52** and the second moving member **32c** extends linearly along a moving direction of the moving member **32**, and an increase in a load when the wire **54** is wound by the pulley **52** and an increase in a load when the wire **54** is pulled out from the pulley **52** are prevented.

(103) Since the wire **54** is flexible enough to be wound around the pulley **52**, the wire **54** cannot press the second moving member **32c** to move the moving member **32** rearward. Therefore, the biasing member **33** is provided which is compressed by the movement of the moving member **32** in the forward direction indicated by the arrow **A1**, and that applies the force for pressing the moving member **32** in the rearward direction indicated by the arrow **A2** to the moving member **32**.

Accordingly, the wire **54** is wound by the pulley **52** to move the driver bit **2** forward, so that the driver bit **2** after moving forward can be moved rearward.

(104) By engagement between the connecting member **30b** provided in the holding member **30** and the groove portion **31a** provided in the rotation guide member **31**, the holding member **30** holding the driver bit **2** is supported so as to be movable in the front-rear direction with respect to the rotation guide member **31** and rotates together with the rotation guide member **31**.

(105) Therefore, in a configuration in which the bit rotation motor **40** is disposed coaxially with the rotation guide member **31** and the holding member **30** and the driver bit **2** held by the holding member **30**, it is possible to implement a configuration in which the driver bit **2** is rotated and the driver bit **2** is moved in the front-rear direction without moving the bit rotation motor **40** in the front-rear direction.

(106) In the configuration in which the bit rotation motor **40** is disposed coaxially with the driver bit **2**, a configuration is considered in which a rotation operation of the bit rotation motor **40** is converted into movement of the driver bit **2** in the front-rear direction by using a feed screw.

(107) However, in the configuration using the feed screw, a forward movement amount of the driver bit **2** per rotation of the motor cannot be increased, so that it is difficult to increase a moving speed of the driver bit **2** even when a rotation speed of the motor is increased.

(108) In the fastening tool **1**, in order to shorten a time required to press the screw **200** against the fastening target by the driver bit **2**, it is necessary to increase the moving speed of the driver bit **2**. However, in the configuration using the feed screw, it is difficult to shorten the time until the screw **200** is pressed against the fastening target by the driver bit **2**.

(109) On the other hand, in the configuration in which the holding member **30** holding the driver bit **2** is supported so as to be movable in the front-rear direction with respect to the rotation guide member **31**, the pulley **52** is rotated by the second drive unit **5** to wind up the wire **54**, and the holding member **30** is moved in the forward direction, the moving speed of the driver bit **2** can be increased according to a rotation speed of the bit movement motor **50**. Therefore, it is possible to shorten the time until the screw **200** is pressed against the fastening target by the driver bit **2**.

(110) FIGS. 7A and 7B are cross-sectional views showing examples of the attachment and detachment holding mechanism. FIGS. 8A and 8B are perspective views showing examples of the attachment and detachment holding mechanism, and shows details of the attachment and detachment holding mechanism **30c**. Next, the attachment and detachment holding mechanism **30c** will be described with reference to the drawings.

(111) The attachment and detachment holding mechanism **30c** includes a ball **30d** exposed in the opening **30a** and a spring **30e** that biases the ball **30d** in a direction of exposing the ball **30d** in the

opening **30a**. The spring **30e** is formed of an annular leaf spring and is fitted to an outer circumference of the holding member **30**.

(112) When an insertion portion **20** of the driver bit **2** is inserted into the opening **30a** of the holding member **30**, the attachment and detachment holding mechanism **30c** retracts in an outer circumferential direction of the holding member **30** while the ball **30d** pressed by the insertion portion **20** deforms the spring **30e** in a direction of increasing a diameter of the annular spring **30e**.

(113) When the insertion portion **20** of the driver bit **2** is inserted into the opening **30a** of the holding member **30** to a position where a groove portion **20a** formed on an outer circumference of the insertion portion **20** faces the ball **30d**, the ball **30d** biased by the spring **30e** is fitted into the groove portion **20a**. Accordingly, the driver bit **2** is prevented from being inadvertently detached from the holding member **30**.

(114) When a force equal to or greater than a predetermined force is applied in a direction of pulling the driver bit **2** out from the holding member **30**, the ball **30d** retracts while deforming the spring **30e** in the direction of increasing the diameter of the annular spring **30e**, so that the driver bit **2** can be pulled out from the holding member **30**.

(115) In operations of inserting and removing the insertion portion **20** of the driver bit **2** into and from the opening **30a** of the holding member **30**, the ball **30d** retracts in the outer circumferential direction of the holding member **30**. Therefore, a space for the ball **30d** retracting is required in the outer circumference of the holding member **30**. On the other hand, since the holding member **30** is inserted into the tubular rotation guide member **31**, a space for the ball **30d** retracting cannot be secured between the outer circumference of the holding member **30** and an inner circumference of the rotation guide member **31**.

(116) When a diameter difference between the holding member **30** and the rotation guide member **31** is set in order to secure the space for the ball **30d** retracting between the outer circumference of the holding member **30** and the inner circumference of the rotation guide member **31**, the outer diameter of the holding member **30** cannot be reduced because a dimension of the driver bit **2** in the radial direction is determined, so that it is necessary to increase the outer diameter of the rotation guide member **31**. Therefore, a size of the device is increased.

(117) On the other hand, the rotation guide member **31** is provided with the groove portion **31a** that guides the connecting member **30b**. The groove portion **31a** penetrates from an inner circumferential side to an outer circumferential side of the rotation guide member **31** on the front and rear sides, and extends in the axial direction of the rotation guide member **31**.

(118) Therefore, in the attachment and detachment holding mechanism **30c**, the ball **30d** is provided in accordance with a position in the groove portion **31a** of the rotation guide member **31**. That is, in the holding member **30**, the connecting member **30b** and the ball **30d** of the attachment and detachment holding mechanism **30c** are provided coaxially along the axial direction of the rotation guide member **31**. Accordingly, in the attachment and detachment holding mechanism **30c**, the ball **30d** is exposed to the groove portion **31a** of the rotation guide member **31** in both operations of rotating the rotation guide member **31** and the holding member **30** and an operation of moving the holding member **30** in the axial direction with respect to the rotation guide member **31**.

(119) Therefore, when the insertion portion **20** of the driver bit **2** is inserted into or removed from the opening **30a** of the holding member **30**, the ball **30d** retracted in the outer circumferential direction of the holding member **30** enters the groove portion **31a** of the rotation guide member **31**.

(120) Therefore, in the configuration in which the holding member **30** is inserted into the tubular rotation guide member **31**, it is possible to secure the space for the ball **30d** of the attachment and detachment holding mechanism **30c** retracting. Since the groove portion **31a** into which the connecting member **30b** enters is also used as the space for the ball **30d** retracting, an area of an opening provided in the rotation guide member **31** is reduced, and strength can be secured.

(121) Further, the diameter difference between the holding member **30** and the rotation guide member **31** is increased, so that it is not necessary to secure the space for the ball **30d** retracting

between the outer circumference of the holding member **30** and the inner circumference of the rotation guide member **31**, and it is possible to prevent an increase in the size of the device.

(122) FIG. **9** is a perspective view showing an example of a screw feeding portion and a nose portion according to the present embodiment, and shows details of the screw feeding portion **7** and the nose portion **8**. Next, the screw feeding portion **7** and the nose portion **8** will be described with reference to the drawings.

(123) The screw feeding portion **7** includes a screw feeding motor **70**, pinion gears **71** attached to a shaft of the screw feeding motor **70** via a speed reducer, rack gears **72** meshing with the pinion gears **71**, and an engagement portion **73** connected to the rack gears **72** and engaged with a connecting screw fed from the screw accommodating portion **6**.

(124) In the screw feeding portion **7**, the rack gears **72** are supported so as to be movable in the upper-lower direction along a feeding direction of the connecting screw. In the screw feeding portion **7**, the screw feeding motor **70** rotates forward and reversely, so that the engagement portion **73** engaged with the connecting screw moves in the upper-lower direction, and the connecting screw is fed.

(125) The nose portion **8** includes an injection passage **80** to which the screw **200** is supplied by the screw feeding portion **7** and through which the driver bit **2** passes, a contact member **81** that has an injection port **81a** communicating with the injection passage **80** and contacts the fastening target, a contact arm **82** that moves in the front-rear direction in conjunction with the contact member **81**, and an adjustment portion **83** that restricts a movement amount of the contact arm **82**. The nose portion **8** includes a cover member **88** that openably and closably covers a path through which the screw **200** passes from the screw accommodating portion **6** to the injection passage **80**.

(126) The fastening tool **1** includes the nose portion **8** with each component forming the injection passage **80**, the contact member **81** and the contact arm **82** assembled, and the nose portion **8** is fixed to the front frame **10b** and a nose body portion **10f** forming the tool body **10**. The fastening tool **1** includes a contact switch portion **84** that is operated by being pressed by the contact arm **82**.

(127) In the nose portion **8**, the contact member **81** is supported so as to be movable in the front-rear direction indicated by the arrows **A1** and **A2**, and the contact arm **82** moves in the front-rear direction in conjunction with the contact member **81**. In the nose portion **8**, the contact member **81** is biased in the forward direction by a biasing member (not shown), and the contact member **81** that is pressed against the fastening target and moves rearward is biased by the biasing member and moves in the forward direction.

(128) In the nose portion **8**, the contact member **81** is pressed against the fastening target, the contact arm **82** moves rearward, and the movement amount of the contact arm **82** until the contact switch portion **84** is operated is adjusted by the adjustment portion **83**. The contact switch portion **84** is pressed by the contact arm **82** to switch presence or absence of an operation. In the present example, a state in which the contact switch portion **84** is not operated without being pressed by the contact arm **82** is set to OFF of the contact switch portion **84**, and a state in which the contact switch portion **84** is operated by being pressed by the contact arm **82** is set to ON of the contact switch portion **84**.

(129) Next, a configuration related to control over the fastening tool **1** and an operation of the fastening tool **1** will be described with reference to the drawings. The fastening tool **1** includes a trigger **9** that receives an operation and a trigger switch portion **90** that is operated by the operation of the trigger **9**. The trigger **9** is provided on the front side of the handle **11**, and is configured to be operable by a finger of a hand gripping the handle **11**. The trigger switch portion **90** is operated by being pressed by the trigger **9**.

(130) The trigger switch portion **90** is pressed by the trigger **9** to switch presence or absence of an operation. In the present example, a state in which the trigger switch **90** is not operated without operating the trigger **9** and without being pressed by the trigger **9** is set to OFF of the trigger switch **90**, and a state in which the trigger switch **90** is operated by operating the trigger **9** and being

pressed by the trigger **9** is set to ON of the trigger switch **90**.

(131) The fastening tool **1** includes a control unit **100** that controls the first drive unit **4**, the second drive unit **5**, and the screw feeding portion **7** based on output of the trigger switch portion **90** operated by an operation of the trigger **9** and the contact switch portion **84** operated by being pressed by the contact arm **82**.

(132) The control unit **100** is formed of a substrate on which various electronic components are mounted, and is provided in a substrate accommodating portion **111** provided on a rear surface side of the screw accommodating portion **6** between the screw accommodating portion **6** and the handle **11**.

(133) In an electric power tool used by holding a handle with a hand, an accommodating portion in which consumables such as screws are accommodated is provided in front of the handle. In order to allow the handle to be gripped by the hand, a space for fingers of the hand to enter is required between the handle and the accommodating portion.

(134) Therefore, the fastening tool **1** includes the substrate accommodating portion **111** on the rear surface side of the screw accommodating portion **6** by using the space between the screw accommodating portion **6** and the handle **11**.

(135) In an electric power tool used by holding a handle with a hand, a configuration is proposed in which a battery is attached to a lower portion of the handle and a substrate is provided between the handle and the battery. With such a configuration, a dimension in an upper-lower direction of the electric power tool along an extending direction of the handle increases.

(136) On the other hand, by providing the substrate accommodating portion **111** on the rear surface side of the screw accommodating portion **6**, a dimension of the fastening tool **1** in the upper-lower direction along the extending direction of the handle **11** is prevented from increasing. Since the connecting screw wound in a spiral shape is accommodated in the screw accommodating portion **6**, a surface of the screw accommodating portion **6** facing the handle **11** has a substantially circular shape. Accordingly, it is possible to secure a volume of the substrate accommodating portion **111** while preventing an increase in the size of the fastening tool **1**.

(137) FIGS. **10A** to **10C** are perspective views showing examples of the fastening tool according to the present embodiment as viewed from a rear side. FIG. **11** is a perspective view showing an example of a setting portion and shows details of a setting portion **110**. Next, the setting portion **110** will be described with reference to the drawings.

(138) The fastening tool **1** includes the second drive unit **5** that moves the driver bit **2** in the front-rear direction along the axial direction, in which the second drive unit **5** is driven by the bit movement motor **50**, and the moving member **32** connected to the pulley **52**, which is driven and rotated by the bit movement motor **50**, by the wire **54** and the holding member **30** connected to the moving member **32** move in the forward direction along the axial direction of the driver bit **2** along the rotation guide member **31**.

(139) Accordingly, the movement amount (forward movement amount) of the driver bit **2** can be controlled by controlling the number of rotations of the bit movement motor **50**. That is, by rotating the bit movement motor **50** in conjunction with rotation of the bit rotation motor **40** that rotates the driver bit **2** in a direction of fastening the screw **200**, it is possible to control the forward movement amount of the driver bit **2** that moves forward following the screw **200** with fastening of the screw **200** by the number of rotations of the bit movement motor **50**, and to control a stop position of the driver bit **2** along the axial direction.

(140) Therefore, the fastening tool **1** includes the setting portion **110** for setting the forward movement amount of the driver bit **2**. The setting portion **110** is an example of a setting unit, and is configured such that a desired set value can be selected from a plurality of setting values, or a desired set value can be selected steplessly.

(141) In the present example, the setting portion **110** has a configuration in which a setting value is selected by an operation portion **110a** having a button. An operation portion **110a** may have a

configuration in which a setting value is selected by a rotary dial. The setting portion **110** may be configured to display a selected setting value by a method of indicating a current value using a label, an inscription, or the like, or a method of indicating the current value on a display portion **110b** such as an LED so that an operator can easily grasp a current setting value.

(142) Setting portions **110** are respectively provided on both left and right sides of a surface on a side facing the handle **11** in the substrate accommodating portion **111** provided on the rear surface side of the screw accommodating portion **6**.

(143) Accordingly, when the fastening tool **1** is viewed from the rear side, the setting portion **110** can be visually recognized from both left and right sides of the handle **11**.

(144) In a use mode in which the handle **11** is held by hand, a surface of the screw accommodating portion **6** on a side facing the handle **11** faces the operator holding the fastening tool **1**.

Accordingly, in the substrate accommodating portion **111** provided on the rear surface side of the screw accommodating portion **6**, the setting portion **110** is provided on the surface on the side facing the handle **11**, so that the display portion **110b** provided on the setting portion **110** is easily visible. Therefore, it is possible to reduce a possibility that the operator overlooks display. Contents displayed on the display portion **110b** include, in addition to a setting value of a screw depth defined by the forward movement amount of the driver bit **2**, an ON or OFF state of a power supply, an operation mode selected from various selectable operation modes, presence or absence of a screw, a remaining amount of screws, presence or absence of an abnormality, and the like.

(145) In the use mode in which the handle **11** is held by hand, the operation portion **110a** such as a button provided on the setting portion **110** is also easily visible. Therefore, in a state in which the handle **11** is held by one hand, the operation portion **110a** can be operated by the other hand while the operation portion **110a** is visually recognized, and an operation can be reliably performed.

(146) Further, a substrate forming the control unit **100** is accommodated in the substrate accommodating portion **111**. By mounting switches and the like forming the operation portion **110a** and lamps and the like forming the display portion **110b** on a surface of the substrate facing the handle **11**, a substrate for the setting portion **110**, separately from the control unit **100**, can be omitted.

(147) FIG. **12** is a block diagram showing an example of the fastening tool according to the present embodiment. As described above, the fastening tool **1** includes the second drive unit **5** that moves the driver bit **2** in the front-rear direction along the axial direction, and the second drive unit **5** is driven by the bit movement motor **50**. The holding member **30** to which the driver bit **2** is attached is connected to the moving member **32**, and the moving member **32** is connected to the pulley **52**, which is driven and rotated by the bit movement motor **50**, by the wire **54**. The holding member **30** and the moving member **32** are configured to move in the forward direction along the axial direction of the driver bit **2** along the rotation guide member **31**.

(148) Accordingly, the control unit **100** can control the movement amount (forward movement amount) of the driver bit **2** by controlling the number of rotations of the bit movement motor **50**. That is, by rotating the bit movement motor **50** in conjunction with rotation of the bit rotation motor **40** that rotates the driver bit **2** in the direction of fastening the screw **200**, it is possible to control the forward movement amount of the driver bit **2** that moves forward following the screw **200** with fastening of the screw **200** by the number of rotations of the bit movement motor **50**, and to control the stop position of the driver bit **2** along the axial direction.

(149) The control unit **100** sets, by the setting portion **110**, the number of rotations of the bit movement motor **50** that defines the forward movement amount of the driver bit **2**. Further, the control unit **100** controls, based on a combination of ON/OFF of the contact switch portion **84** and ON/OFF of the trigger switch portion **90**, whether the bit movement motor **50** of the second drive unit **5** and the bit rotation motor **40** of the first drive unit **4** are driven.

Operation Example of Fastening Tool According to Present Embodiment

(150) FIG. **13A** is a side cross-sectional view showing an example of an operation of the fastening

tool according to the present embodiment. FIG. 13B is a top cross-sectional view showing an example of the operation of the fastening tool according to the present embodiment. FIG. 14 is a flowchart showing an example of the operation of the fastening tool according to the present embodiment. Next, a fastening operation of the fastening tool according to the present embodiment will be described with reference to the drawings.

(151) In a standby state of the fastening tool **1**, as shown in FIG. 1A, a tip end of the driver bit **2** is positioned at a standby position **P1** on a rear side of the injection passage **80**, and the screw **200** can be supplied to the injection passage **80**.

(152) In step SA1 of FIG. 14, the control unit **100** sets the number of rotations of the bit movement motor **50** that defines the forward movement amount of the driver bit **2** based on a setting value selected by the setting portion **110**. When the contact member **81** is pressed against the fastening target, the contact switch portion **84** is pressed by the contact arm **82**, the contact switch portion **84** is turned on in step SA2, the trigger **9** is operated, and the trigger switch portion **90** is turned on in step SA3, the control unit **100** drives the bit rotation motor **40** of the first drive unit **4** in step SA4, and drives the bit movement motor **50** of the second drive unit **5** in step SA5.

(153) When the bit movement motor **50** is driven to rotate in a positive direction, which is one direction, the pulley **52** rotates in the positive direction, so that the wire **54** is wound around the pulley **52**. When the wire **54** is wound around the pulley **52**, the second moving member **32c** connected to the wire **54** is guided by the rotation guide member **31** and moves in the forward direction along the axial direction. When the second moving member **32c** moves in the forward direction, the first moving member **32a** is pressed by the second moving member **32c** via the bearing **32b**, and moves in the forward direction along the axial direction together with the second moving member **32c** while compressing the biasing member **33**.

(154) When the first moving member **32a** moves in the forward direction, the holding member **30** connected to the first moving member **32a** by the connecting member **30b** moves in the forward direction along the axial direction of the driver bit **2** with the connecting member **30b** guided by the groove portion **31a** of the rotation guide member **31**.

(155) Accordingly, the driver bit **2** held by the holding member **30** moves in the forward direction indicated by the arrow **A1**, engages with the screw **200** supplied to the injection port **81a** of the nose portion **8**, moves the screw **200** in the forward direction, and presses the screw **200** against the fastening target.

(156) When the bit rotation motor **40** is driven to rotate in the positive direction, which is the one direction, the rotation guide member **31** rotates in the positive direction. When the rotation guide member **31** rotates in the positive direction, the connecting member **30b** connected to the holding member **30** is pressed by the groove portion **31a** of the rotation guide member **31**, so that the holding member **30** rotates together with the rotation guide member **31**.

(157) Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction (clockwise) and screws the screw **200** into the fastening target. The control unit **100** moves the driver bit **2** in the forward direction by the second drive unit **5** in conjunction with an operation of rotating the driver bit **2** by the first drive unit **4** to screw the screw into the fastening target based on a load applied to the bit rotation motor **40**, the number of rotations of the bit rotation motor **40**, a load applied to the bit movement motor **50**, the number of rotations of the bit movement motor **50**, and the like, thereby causing the driver bit **2** to follow the screw to be screwed into the fastening target.

(158) When the control unit **100** determines that the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** in step SA6 and the tip end of the driver bit **2** reaches a set operation end position **P2** as shown in FIGS. 13A and 13B, the control unit **100** stops driving of the bit rotation motor **40** in step SA7, stops rotation of the bit movement motor **50** in the positive direction in step SA8, and then reversely rotates the bit movement motor **50** in step SA9.

(159) When the bit movement motor **50** rotates in a reverse direction, which is another direction, the pulley **52** rotates in the reverse direction, so that the wire **54** is pulled out from the pulley **52**. When the wire **54** is pulled out from the pulley **52**, the second moving member **32c** moves in the forward direction, so that the compressed biasing member **33** extends and presses the second moving member **32c** in the rearward direction.

(160) The second moving member **32c** is pressed rearward by the biasing member **33**, thereby being guided by the rotation guide member **31** and moving rearward along the axial direction. When the second moving member **32c** moves in the rearward direction, the first moving member **32a** is pulled by the second moving member **32c** via the bearing **32b**, and moves in the rearward direction along the axial direction together with the second moving member **32c**.

(161) When the first moving member **32a** moves in the rearward direction, the holding member **30** connected to the first moving member **32a** by the connecting member **30b** moves in the rearward direction along the axial direction of the driver bit **2** with the connecting member **30b** guided by the groove portion **31a** of the rotation guide member **31**.

(162) When the bit movement motor **50** rotates reversely to an initial position where the wire **54** is pulled out from the pulley **52** by a predetermined amount and the holding member **30** and the moving member **32** move in the rearward direction to a position where the tip end of the driver bit **2** returns to the standby position **P1** in step **SA10**, the control unit **100** stops the reverse rotation of the bit movement motor **50** in step **SA11**.

(163) Since the moving member **32** includes the buffer member **32d** made of rubber or the like on the rear side of the second moving member **32c**, it is possible to prevent the second moving member **32c** from directly hitting the rear frame **10c** due to movement of the second moving member **32c** in the rear direction, and it is possible to prevent occurrence of sound or damage. When the trigger switch portion **90** is turned off, the control unit **100** rotates the screw feeding motor **70** in one direction to lower the engagement portion **73**. When the engagement portion **73** is lowered to a position where the engagement portion **73** is engaged with the next screw **200**, the control unit **100** causes the screw feeding motor **70** to rotate reversely, thereby raising the engagement portion **73** and supplying the next screw **200** to the injection passage **80**.

(164) FIGS. **15A** to **15C** are cross-sectional views showing fastening states of the screw, in which FIG. **15A** shows a so-called flush state in which a head portion **201** of the screw **200** does not float up from or is not buried in a surface of a fastening target **202**, FIG. **15B** shows a state in which the head portion **201** of the screw **200** floats from the fastening target **202**, and FIG. **15C** shows a state in which the head portion **201** of the screw **200** is buried in the fastening target **202**.

(165) In the fastening tool **1**, when the tip end of the driver bit **2** reaches the operation end position **P2**, in a case where the screw **200** is a countersunk head screw, as shown in FIG. **15A**, the forward movement amount of the driver bit **2** is preferably set such that the surface of the head portion **201** of the screw **200** is in the so-called flush state in which the surface of the head portion **201** is the same as a surface of the fastening target **202**. The screw **200** is not limited to the countersunk head screw, and if the screw **200** is a pan head, a bind, a truss, or the like, it is preferable that the forward movement amount of the driver bit **2** is set so that a seating surface of the head portion **201** of the screw **200** contacts the surface of the fastening target **202** and the head portion **201** of the screw **200** does not float from the fastening target **202**.

(166) When the tip end of the driver bit **2** reaches the operation end position **P2**, if the head portion **201** of the screw **200** is in a state of floating from the fastening target **202** as shown in FIG. **15B**, the movement amount (forward movement amount) of the driver bit **2** is set by the setting portion **110**, and the forward movement amount of the driver bit **2** is increased by increasing the number of rotations (rotation amount) of the bit movement motor **50**, and the operation end position **P2** is moved forward. On the other hand, when the head portion **201** of the screw **200** is in a state of being buried in the fastening target **202** as shown in FIG. **15C**, the movement amount (forward movement amount) of the driver bit **2** is set by the setting portion **110**, and the forward movement

amount of the driver bit **2** is decreased by decreasing the number of rotations of the bit movement motor **50**, and the operation end position P2 is retreated.

(167) As described above, the movement amount (forward movement amount) of the driver bit **2** is defined by the number of rotations of the bit movement motor **50**. The bit movement motor **50** is rotated by the number of rotations set by the setting portion **110** starting from the standby position P1, which is an initial position of the driver bit **2**, and then the rotation of the bit movement motor **50** is stopped or reversed, so that the operation end position P2 is controlled. Therefore, a tightening depth can be adjusted.

(168) Thus, in order to make it possible to advance a tip end position of the driver bit **2** held by the holding member **30** by a predetermined amount based on the number of rotations of the bit movement motor **50** with reference to the predetermined standby position P1, a standby position of the holding member **30** to which the driver bit **2** is attached and the moving member **32** that moves the holding member **30** is set. An operation of setting the standby position of the holding member **30** and the moving member **32** is referred to as a first initialization operation.

(169) The holding member **30** and the moving member **32** are moved to the set standby position before start of driving and fastening operations, and a position of the holding member **30** and the moving member **32** is controlled by the number of rotations of the bit movement motor **50** with reference to the standby position. The holding member **30** and the moving member **32** are moved forward from the set standby position by a predetermined movement amount (forward movement amount) to perform the fastening operation. An operation of moving the holding member **30** and the moving member **32** to the standby position set in the first initialization operation is referred to as a second initialization operation.

(170) It is conceivable that, as the setting unit that sets the standby position of the holding member **30** and the moving member **32** in the first initialization operation, a sensor is used, or a maximum position in a range in which the holding member **30** and the moving member **32** can move forward and rearward is used as a reference. When the sensor is used, a detection position of the sensor or a position moved from the detection position by a specified amount is set as the standby position.

(171) When the maximum position in the range in which the holding member **30** and the moving member **32** can move forward and rearward is used, a position obtained by moving the holding member **30** and the moving member **32** from a front end position or a rear end position by a specified amount is set as the standby position.

(172) FIGS. **16A** to **16D** are diagrams showing examples of an operation of setting the standby position of the holding member and the moving member in the first initialization operation. Next, the operation of setting the standby position of the holding member **30** and the moving member **32** will be described. FIGS. **16A** to **16D** show the examples of the operation of setting the standby position of the holding member **30** and the moving member **32** using the maximum position in the range in which the holding member **30** and the moving member **32** can move forward and rearward.

(173) As shown in FIG. **16A**, the control unit **100** rotates the bit movement motor **50** in the positive direction, which is the one direction, from a state in which the holding member **30** and the moving member **32** are at a desired position. When the bit movement motor **50** rotates forward, the wire **54** is wound around the pulley **52**, so that the moving member **32** and the holding member **30** connected to the moving member **32** move in the forward direction along the axial direction of the driver bit **2** along the rotation guide member **31**.

(174) As shown in FIG. **16B**, when the bit movement motor **50** rotates forward until the holding member **30** and the moving member **32** move to a front end position PF that is one end position, the control unit **100** stops the forward rotation of the bit movement motor **50** and moves the holding member **30** and the moving member **32** to the front end position PF.

(175) Next, the control unit **100** rotates the bit movement motor **50** in the reverse direction, which is the other direction. When the bit movement motor **50** rotates reversely, the wire **54** is pulled out

from the pulley 52, so that the moving member 32 is pressed in the rearward direction by the biasing member 33, and the moving member 32 and the holding member 30 connected to the moving member 32 move in the rearward direction along the axial direction of the driver bit 2 along the rotation guide member 31.

(176) As shown in FIG. 16C, when the bit movement motor 50 rotates reversely until the holding member 30 and the moving member 32 move to a rear end position PE that is another end position, the control unit 100 stops the reverse rotation of the bit movement motor 50 and moves the holding member 30 and the moving member 32 to the rear end position PE by biasing of the biasing member 33.

(177) The control unit 100 acquires a movement amount of the holding member 30 and the moving member 32 from the front end position PF to the rear end position PE as a total distance L1. The movement amount from the front end position PF to the rear end position PE is obtained from the number of rotations of the bit movement motor 50.

(178) In the control unit 100, a movement amount of the holding member 30 and the moving member 32 from the standby position to the front end position PF is set in advance as a target movement amount L2. The control unit 100 sets a standby position movement amount L3 to a difference between the total distance L1 from the front end position PF to the rear end position PE and the target movement amount L2 set in advance, and stores the standby position movement amount L3. The standby position movement amount L3 is a movement amount of the holding member 30 and the moving member 32 from the rear end position PE.

(179) As shown in FIG. 16D, the control unit 100 rotates the bit movement motor 50 forward to move the holding member 30 and the moving member 32 in the forward direction from the rear end position PE. When the bit movement motor 50 is rotated forward at the number of rotations corresponding to the standby position movement amount L3, the control unit 100 stops the forward rotation of the bit movement motor 50, moves the holding member 30 and the moving member 32 to the standby position, and moves the tip end of the driver bit 2 held by the holding member 30 to the standby position P1.

(180) When the holding member 30 and the moving member 32 are moved to the front end position PF and the rear end position PE, it is desirable to drive the holding member 30 and the moving member 32 at a low speed that does not affect durability of a tool, for example, when the second moving member 32c hits the buffer member 32d.

(181) FIGS. 17A to 17C are diagrams showing examples of an operation of moving the holding member and the moving member to the standby position in the second initialization operation. Next, the operation of moving the holding member 30 and the moving member 32 to the standby position set in advance will be described.

(182) As shown in FIG. 17A, the control unit 100 rotates the bit movement motor 50 in the reverse direction, which is the other direction, from a state in which the holding member 30 and the moving member 32 are at a desired position. When the bit movement motor 50 rotates reversely, the wire 54 is pulled out from the pulley 52, so that the moving member 32 is pressed in the rearward direction by the biasing member 33, and the moving member 32 and the holding member 30 connected to the moving member 32 move in the rearward direction along the axial direction of the driver bit 2 along the rotation guide member 31.

(183) As shown in FIG. 17B, when the bit movement motor 50 rotates reversely until the holding member 30 and the moving member 32 move to the rear end position PE, the control unit 100 stops the reverse rotation of the bit movement motor 50 and moves the holding member 30 and the moving member 32 to the rear end position PE by biasing of the biasing member 33.

(184) As shown in FIG. 17C, the control unit 100 rotates the bit movement motor 50 forward to move the holding member 30 and the moving member 32 in the forward direction from the rear end position PE. When the bit movement motor 50 is rotated forward at the number of rotations corresponding to the standby position movement amount L3, the control unit 100 stops the forward

rotation of the bit movement motor **50**, moves the holding member **30** and the moving member **32** to the standby position, and moves the tip end of the driver bit **2** held by the holding member **30** to the standby position **P1**.

(185) In the first initialization operation described with reference to FIGS. **16A** to **16D**, an operation of setting the standby position of the holding member **30** and the moving member **32** is executed in a factory, for example, at the time of shipment of a product without depending on an operation of a user, and the standby position movement amount **L3** is stored in advance.

(186) On the other hand, in the second initialization operation described with reference to FIGS. **17A** to **17C**, an operation of moving the holding member **30** and the moving member **32** to the standby position based on the standby position movement amount **L3** is preferably performed every time a power supply of the fastening tool **1** is turned on so that a stable fastening operation can be performed.

(187) Therefore, the first initialization operation and the second initialization operation, which are initialization operations related to the standby position of the holding member **30** and the moving member **32**, can be selected.

(188) FIG. **18** is a flowchart showing an example of an operation of selecting the first initialization operation and the second initialization operation.

(189) When the power supply is turned on in step **SB1** of FIG. **18**, the control unit **100** selects an initialization operation to be executed in step **SB2**. When the control unit **100** selects execution of the first initialization operation, in step **SB3**, the control unit **100** executes the first initialization operation described above with reference to FIGS. **16A** to **16D** and sets the standby position of the holding member **30** and the moving member **32**. When the control unit **100** selects execution of the second initialization operation, in step **SB4**, the control unit **100** executes the second initialization operation described above with reference to FIGS. **17A** to **17C** and moves the holding member **30** and the moving member **32** to the standby position based on the standby position movement amount **L3**. After executing the second initialization operation, the control unit **100** executes a normal fastening operation in step **SB5** according to the flowchart of FIG. **14** described above.

(190) As described above, in the first initialization operation, the holding member **30** and the moving member **32** are moved at a low speed from the front end position **PF** to the rear end position **PE**, the total distance **L1** from the front end position **PF** to the rear end position **PE** is acquired, a movement amount from the rear end position **PE**, which is determined so that a movement amount from the front end position **PF** becomes the predetermined target movement amount **L2**, is set as the standby position movement amount **L3**, and the standby position movement amount **L3** is recorded in a memory on the substrate (not shown) forming the control unit **100**. Accordingly, various variations of a machine, such as a difference in dimension within a range of tolerance, can be eliminated, and the standby position of the holding member **30** and the moving member **32** can be set to, for example, a constant position from the front end position **PF**.

(191) In the second initialization operation, the holding member **30** and the moving member **32** are moved from the rear end position **PE** to the standby position according to the standby position movement amount **L3** every time the power supply is turned on for use by the user, so that the movement amount of the holding member **30** and the moving member **32** can be minimized.

Further, in the second initialization operation, the second initialization operation can be executed in a state where the tip end of the driver bit **2** is positioned at the standby position **P1** on the rear side of the injection passage **80** and the screw **200** is supplied to the injection passage **80**.

(192) As described above, the movement amount (forward movement amount) of the driver bit **2** is defined by the number of rotations of the bit movement motor **50** starting from the standby position of the holding member **30** and the moving member **32**, that is, the standby position **P1** of the driver bit **2**. Therefore, when the standby position of the holding member **30** and the moving member **32**, that is, the standby position **P1** of the driver bit **2** varies, the tightening depth set by the setting portion **110** varies.

(193) On the other hand, by performing the second initialization operation every time the power supply is turned on, it is possible to accurately adjust the tightening depth of the screw by the operation of rotating the bit movement motor **50** by the number of rotations set by the setting portion **110** starting from the standby position of the holding member **30** and the moving member **32**, that is, the standby position **P1** of the driver bit **2**.

(194) FIG. **19** is a flowchart showing a modification of the operation of the fastening tool according to the present embodiment. FIG. **20** is a graph showing a relationship between output of the contact switch portion and control over the bit rotation motor and the bit movement motor. Next, another example of the fastening operation of the fastening tool according to the present embodiment will be described with reference to the drawings. In this modification, the bit rotation motor **40** and the bit movement motor **50** are controlled by detecting whether the fastening tool **1** floats up with respect to the fastening target from the output of the contact switch portion **84**.

(195) In the standby state of the fastening tool **1**, as shown in FIG. **1A**, the tip end of the driver bit **2** is positioned at the standby position **P1** on the rear side of the injection passage **80**, and the screw **200** can be supplied to the injection passage **80**.

(196) In step **SC1** of FIG. **19**, the control unit **100** sets the number of rotations of the bit movement motor **50** that defines the forward movement amount of the driver bit **2** based on a setting value selected by the setting portion **110**. When the contact member **81** is pressed against the fastening target, the contact switch portion **84** is pressed by the contact arm **82**, the contact switch portion **84** is turned on in step **SC2**, the trigger **9** is operated, and the trigger switch portion **90** is turned on in step **SC3**, the control unit **100** drives the bit rotation motor **40** of the first drive unit **4** in step **SC4**, and drives the bit movement motor **50** of the second drive unit **5** in step **SC5**.

(197) When the bit movement motor **50** is driven to rotate in the positive direction, which is the one direction, the pulley **52** rotates in the positive direction, so that the wire **54** is wound around the pulley **52**, and the moving member **32** in which the second moving member **32c** is connected to the wire **54** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the forward direction.

(198) Accordingly, the driver bit **2** held by the holding member **30** moves in the forward direction indicated by the arrow **A1**, engages with the screw **200** supplied to the injection port **81a** of the nose portion **8**, moves the screw **200** in the forward direction, and presses the screw **200** against the fastening target.

(199) When the bit rotation motor **40** is driven to rotate in the positive direction, which is the one direction, the holding member **30** rotates together with the rotation guide member **31**.

(200) Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction (clockwise) and screws the screw **200** into the fastening target. The control unit **100** moves the driver bit **2** in the forward direction by the second drive unit **5** in conjunction with an operation of rotating the driver bit **2** by the first drive unit **4** to screw the screw into the fastening target based on a load applied to the bit rotation motor **40**, the number of rotations of the bit rotation motor **40**, a load applied to the bit movement motor **50**, the number of rotations of the bit movement motor **50**, and the like, thereby causing the driver bit **2** to follow the screw to be screwed into the fastening target.

(201) When the control unit **100** determines in step **SC6** that the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position **P2**, the control unit **100** stops driving of the bit movement motor **50** in step **SC7**.

(202) When the control unit **100** stops driving of the bit movement motor **50** in step **SC7**, the control unit **100** determines whether the contact switch portion **84** is turned on in step **SC8**. When the contact switch portion **84** is turned on, the control unit **100** determines that the fastening tool **1** does not float up in the direction away from the fastening target, stops rotation of the bit rotation motor **40** in the positive direction in step **SC9**, and rotates the bit movement motor **50** reversely in

step SC10 in order to end the fastening operation.

(203) When the bit movement motor **50** rotates in the reverse direction, which is the other direction, the pulley **52** rotates in the reverse direction, so that the wire **54** is pulled out from the pulley **52**, and the moving member **32** in which the second moving member **32c** is pressed by the biasing member **33** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the rearward direction.

(204) When the bit movement motor **50** rotates reversely to an initial position where the wire **54** is pulled out from the pulley **52** by a predetermined amount and the holding member **30** and the moving member **32** move in the rearward direction to a position where the tip end of the driver bit **2** returns to the standby position **P1** in step SC11, the control unit **100** stops the reverse rotation of the bit movement motor **50** in step SC12.

(205) When the contact switch portion **84** is turned off in step SC8, the control unit **100** determines that the fastening tool **1** floats up in the direction away from the fastening target, and continues driving for rotating the bit rotation motor **40** in the positive direction in a state where driving of the bit movement motor **50** is stopped.

(206) Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction and further screws the screw **200** into the fastening target, so that the fastening tool **1** moves in a direction approaching the fastening target. Therefore, the fastening tool **1** moves relative to the contact arm **82**, and the contact switch portion **84** is pressed by the contact arm **82**, and the contact switch portion **84** is turned on. When the contact switch portion **84** is turned on, the control unit **100** executes processing of steps SC9 to SC12 described above in order to end the fastening operation, and performs operations of stopping the bit rotation motor **40** and returning the driver bit **2** to the standby position by the reverse rotation of the bit movement motor **50**.

(207) In a state in which the contact switch portion **84** is turned off and driving of the bit movement motor **50** is stopped, by performing control called a braking operation in which the bit movement motor **50** does not rotate by an external force during an operation of rotating the bit rotation motor **40** in the positive direction, the control unit **100** maintains a state in which the holding member **30**, the moving member **32**, and the driver bit **2** held by the holding member **30** are stopped at the operation end position **P2**.

(208) However, in a state in which driving of the bit movement motor **50** is stopped, during the operation of rotating the bit rotation motor **40** in the positive direction, the screw **200** is tightened while a force is applied in a direction of pressing the fastening tool **1** against the fastening target by the operator. Therefore, even when the braking operation is performed on the bit movement motor **50**, the holding member **30**, the moving member **32**, and the driver bit **2** held by the holding member **30** may move in the rearward direction from the operation end position **P2** due to a force applied by the operator.

(209) Therefore, the control unit **100** detects presence or absence of reverse rotation of the bit movement motor **50** in step SC13, and when the reverse rotation of the bit movement motor **50** is detected, the control unit **100** returns to step SC5, rotates the bit movement motor **50** forward, moves the holding member **30** and the moving member **32** in the forward direction, and returns the driver bit **2** to the operation end position **P2**. Then, the forward rotation of the bit movement motor **50** is stopped, and the braking operation is performed.

(210) In order to switch ON or OFF the contact switch portion **84** by the contact arm **82**, it is necessary to move the contact arm **82** by a predetermined amount. Therefore, as described above, it is detected that the contact switch portion **84** is OFF in step SC8, and in a state in which the driving of the bit movement motor **50** is stopped, the driving of rotating the bit rotation motor **40** in the positive direction is continued, and the position of the holding member **30** and the moving member **32** may fluctuate while the contact arm **82** moves until the contact switch portion **84** is switched from OFF to ON. Therefore, it is desirable to provide a detection unit that detects a position of the contact arm **82**. Rotation of the bit holding portion **3** and movement of the bit holding portion **3** in

the axial direction may be performed by a single motor. The control unit **100** may control a timing of stopping driving of the single motor based on presence or absence of an operation of the contact switch portion **84**.

(211) FIG. **21** is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment. FIGS. **22A** and **22B** are graphs showing relationships between loads and control over the bit rotation motor. Next, the other modification of the fastening operation of the fastening tool according to the present embodiment will be described with reference to the drawings. In this modification, a load applied to the bit rotation motor **40** is detected to control the bit rotation motor **40**.

(212) In the standby state of the fastening tool **1**, as shown in FIG. **1A**, the tip end of the driver bit **2** is positioned at the standby position **P1** on the rear side of the injection passage **80**, and the screw **200** can be supplied to the injection passage **80**.

(213) In step SD1 of FIG. **21**, the control unit **100** sets the number of rotations of the bit movement motor **50** that defines the forward movement amount of the driver bit **2** based on a setting value selected by the setting portion **110**. When the contact member **81** is pressed against the fastening target, the contact switch portion **84** is pressed by the contact arm **82**, the contact switch portion **84** is turned on in step SD2, the trigger **9** is operated, and the trigger switch portion **90** is turned on in step SD3, the control unit **100** drives the bit rotation motor **40** of the first drive unit **4** in step SD4, and drives the bit movement motor **50** of the second drive unit **5** in step SD5.

(214) When the bit movement motor **50** is driven to rotate in the positive direction, which is the one direction, the pulley **52** rotates in the positive direction, so that the wire **54** is wound around the pulley **52**, and the moving member **32** in which the second moving member **32c** is connected to the wire **54** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the forward direction.

(215) Accordingly, the driver bit **2** held by the holding member **30** moves in the forward direction indicated by the arrow **A1**, engages with the screw **200** supplied to the injection port **81a** of the nose portion **8**, moves the screw **200** in the forward direction, and presses the screw **200** against the fastening target.

(216) When the bit rotation motor **40** is driven to rotate in the positive direction, which is the one direction, the holding member **30** rotates together with the rotation guide member **31**.

(217) Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction (clockwise) and screws the screw **200** into the fastening target. The control unit **100** moves the driver bit **2** in the forward direction by the second drive unit **5** in conjunction with an operation of rotating the driver bit **2** by the first drive unit **4** to screw the screw into the fastening target based on a load applied to the bit rotation motor **40**, the number of rotations of the bit rotation motor **40**, a load applied to the bit movement motor **50**, the number of rotations of the bit movement motor **50**, and the like, thereby causing the driver bit **2** to follow the screw to be screwed into the fastening target.

(218) In step SD6, the control unit **100** determines whether the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position **P2**. When it is determined that the number of rotations of the bit movement motor **50** does not reach the setting value selected by the setting portion **110**, the control unit **100** detects a load applied to the bit rotation motor **40** in step SD7, and when the control unit **100** detects a predetermined load, the control unit **100** controls the bit rotation motor **40** in step SD8.

(219) A rotation speed of the driver bit **2** differs depending on a magnitude of the load applied to the bit rotation motor **40**. If a current value and a voltage value applied to the bit rotation motor **40** are the same, the higher the load applied to the bit rotation motor **40**, the lower the rotation speed. Therefore, the control unit **100**, as a fluctuation detection unit that detects a factor causing a fluctuation in a rotation speed of the bit rotation motor **40**, detects a load applied to the bit rotation

motor **40**, and decreases output of the bit rotation motor **40**, such as decreasing a voltage value applied to the bit rotation motor **40** or decreasing a current value applied to the bit rotation motor **40**, as the load applied to the bit rotation motor **40** is low, as compared with a case where the load is high.

(220) Accordingly, when the load applied to the bit rotation motor **40** is low, the rotation speed of the bit rotation motor **40** is decreased, thereby preventing an increase in the rotation speed as compared with the case where the load is high, and preventing a difference in the rotation speed of the bit rotation motor **40** due to the magnitude of the load applied to the bit rotation motor **40**. Therefore, occurrence of variation in a speed at which the screw **200** is fastened is prevented.

(221) When the control unit **100** determines that the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position P2 in step SD6, the control unit **100** stops driving of the bit rotation motor **40** in step SD9, stops rotation of the bit movement motor **50** in the positive direction in step SD10, and then reversely rotates the bit movement motor **50** in step SD11.

(222) When the bit movement motor **50** rotates in the reverse direction, which is the other direction, the pulley **52** rotates in the reverse direction, so that the wire **54** is pulled out from the pulley **52**, and the moving member **32** in which the second moving member **32c** is pressed by the biasing member **33** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the rearward direction.

(223) When the bit movement motor **50** rotates reversely to an initial position where the wire **54** is pulled out from the pulley **52** by a predetermined amount and the holding member **30** and the moving member **32** move in the rearward direction to a position where the tip end of the driver bit **2** returns to the standby position P1 in step SD12, the control unit **100** stops the reverse rotation of the bit movement motor **50** in step SD13.

(224) In control for decreasing output of the bit rotation motor **40**, as shown in FIG. 22A, after a predetermined load is detected, the output may be decreased so that the rotation speed becomes constant until the bit rotation motor **40** rotates at the number of rotations for moving the driver bit **2** to the operation end position. As shown in FIG. 22B, after the predetermined load is detected, the output may be gradually decreased so as to reach a target rotation speed until the bit rotation motor **40** rotates at the number of rotations for moving the driver bit **2** to the operation end position.

(225) A fluctuation in a power supply voltage causes a difference in the rotation speed of the driver bit **2**, and the lower the power supply voltage, the lower the rotation speed. Therefore, the control unit **100**, as the fluctuation detection unit that detects a factor causing a fluctuation in the rotation speed of the bit rotation motor **40**, detects the power supply voltage, and decreases the output of the bit rotation motor **40** as the power supply voltage is high, as compared with a case where the power supply voltage is low.

(226) Accordingly, when the power supply voltage is high, the rotation speed of the bit rotation motor **40** is decreased as compared with a case where the power supply voltage is low, so that occurrence of a difference in the rotation speed of the bit rotation motor **40** due to a fluctuation in the power supply voltage is prevented. Therefore, occurrence of variation in the speed at which the screw **200** is fastened is prevented.

(227) The control unit **100** may set the target rotation speed of the bit rotation motor **40**, detect the rotation speed of the bit rotation motor **40**, compare the detected rotation speed of the bit rotation motor **40** with the target rotation speed of the bit rotation motor **40** set in advance, and control the bit rotation motor **40** so as to achieve the target rotation speed.

(228) If the rotation speed of the bit rotation motor **40** is decreased, it becomes a factor that a working speed of fastening the screw to the fastening target is decreased. On the other hand, during a stop processing of the bit rotation motor **40** after the screw is tightened to a target screw tightening depth set by the setting portion **110**, the screw is tightened to the fastening target by rotation of the driver bit **2** until rotation of the bit rotation motor **40** is completely stopped.

Therefore, the faster the rotation speed of the bit rotation motor **40** immediately before the rotation is stopped, the more the screw is tightened beyond the target.

(229) Thus, a factor that a quality of a screw tightening operation is decreased due to the difference in the rotation speed of the bit rotation motor **40** is the rotation speed immediately before the rotation of the bit rotation motor **40** is stopped. Therefore, if the rotation speed of the bit rotation motor **40** is constant, without an influence of a load, immediately before the movement amount (forward movement amount) of the holding member **30** and the moving member **32** reaches the target screw tightening depth set by the setting portion **110**, a desired effect can be obtained.

(230) The load applied to the bit rotation motor **40** increases when tightening of the screw to the fastening target is started, but the load fluctuates depending on a material of the fastening target and the like. Therefore, after the detection of the load described above for controlling the rotation speed of the bit rotation motor **40**, control over the rotation speed of the bit rotation motor **40** described above based on the load, the power supply voltage, and the like is executed until the target screw tightening depth is reached.

(231) A timekeeping unit is provided. The control unit **100** may control the rotation speed of the bit rotation motor **40** based on the load, the power supply voltage, and the like after a predetermined time elapses from start of driving of the bit rotation motor **40** (forward rotation). A position detection unit that detects the position of the holding member **30** and the moving member **32** may be provided. After the position of the holding member **30** and the moving member **32** reaches a predetermined position, the above control over the rotation speed of the bit rotation motor **40** based on the load, the power supply voltage, and the like may be executed. The predetermined position of the holding member **30** and the moving member **32** at which the control over the rotation speed of the bit rotation motor **40** is executed is set between a position where the above load is detected and a position where the target screw tightening depth is reached for controlling the rotation speed of the bit rotation motor **40**.

(232) In a method of setting the target rotation speed of the bit rotation motor **40** and controlling output, it is considered that the target screw tightening depth is reached before the rotation speed of the bit rotation motor **40** is decreased to the target rotation speed due to an influence of a length of a control execution section or the like. Therefore, during control of decreasing the rotation speed of the bit rotation motor **40** to the target rotation speed, braking control over the bit rotation motor **40** may be performed. For example, when a deviation between the target rotation speed of the bit rotation motor **40** and a detected actual rotation speed is large, the braking control over the bit rotation motor **40** may be performed until the deviation between the actual rotation speed and the target rotation speed falls within a specified range, and when the deviation falls within the specified range, the control of decreasing the rotation speed of the bit rotation motor **40** to the target rotation speed may be performed.

(233) Further, if the driver bit **2** and the screw are disengaged after the driver bit **2** reaches the target screw tightening depth, the screw is not tightened any more even if the driver bit **2** rotate. Therefore, after the driver bit **2** moves forward until the driver bit **2** reaches the target screw tightening depth, the bit movement motor **50** may be rotated reversely before the rotation of the bit rotation motor **40** is stopped. The rotation of the bit holding portion **3** and the movement of the bit holding portion **3** in the axial direction may be performed by a single motor. The control unit **100** may detect a factor that causes a rotation speed of the motor to fluctuate, such as a load applied to the single motor, and control the motor.

(234) FIG. **23** is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment. FIG. **24A** is a graph showing a relationship between rotation speeds of the bit rotation motor and the bit movement motor under feedback (FB) control. FIG. **24B** is a graph showing a relationship between a moving speed of the screw by the rotation of the bit rotation motor and a moving speed of the driver bit by the bit movement motor under the feedback (FB) control. Next, the other modification of the fastening operation of the fastening tool

according to the present embodiment will be described with reference to the drawings. In this modification, the moving speed of the screw by the rotation of the bit rotation motor **40** and the moving speed of the driver bit by the bit movement motor **50** are synchronized by the feedback control.

(235) In the standby state of the fastening tool **1**, as shown in FIG. **1A**, the tip end of the driver bit **2** is positioned at the standby position **P1** on the rear side of the injection passage **80**, and the screw **200** can be supplied to the injection passage **80**.

(236) In step **SE1** of FIG. **23**, the control unit **100** sets the number of rotations of the bit movement motor **50** that defines the forward movement amount of the driver bit **2** based on a setting value selected by the setting portion **110**. When the contact member **81** is pressed against the fastening target, the contact switch portion **84** is pressed by the contact arm **82**, the contact switch portion **84** is turned on in step **SE2**, the trigger **9** is operated, and the trigger switch portion **90** is turned on in step **SE3**, the control unit **100** drives the bit rotation motor **40** of the first drive unit **4** in step **SE4**, and drives the bit movement motor **50** of the second drive unit **5** in step **SE5**.

(237) When the bit movement motor **50** is driven to rotate in the positive direction, which is the one direction, the pulley **52** rotates in the positive direction, so that the wire **54** is wound around the pulley **52**, and the moving member **32** in which the second moving member **32c** is connected to the wire **54** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the forward direction.

(238) Accordingly, the driver bit **2** held by the holding member **30** moves in the forward direction indicated by the arrow **A1**, engages with the screw **200** supplied to the injection port **81a** of the nose portion **8**, moves the screw **200** in the forward direction, and presses the screw **200** against the fastening target.

(239) When the bit rotation motor **40** is driven to rotate in the positive direction, which is the one direction, the holding member **30** rotates together with the rotation guide member **31**.

(240) Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction (clockwise) and screws the screw **200** into the fastening target. The control unit **100** moves the driver bit **2** in the forward direction by the second drive unit **5** in conjunction with an operation of rotating the driver bit **2** by the first drive unit **4** to screw the screw into the fastening target, thereby causing the driver bit **2** to follow the screw to be screwed into the fastening target.

(241) In step **SE6**, the control unit **100** determines whether the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position **P2**. When it is determined that the number of rotations of the bit movement motor **50** does not reach the setting value selected by the setting portion **110**, the control unit **100** detects a load applied to the bit movement motor **50** in step **SE7**, and when the control unit **100** detects a predetermined load, the control unit **100** acquires the number of rotations of the bit rotation motor **40** and the number of rotations of the bit movement motor **50** in step **SE8**.

(242) In step **SE9**, the control unit **100** obtains rotation speeds of the bit rotation motor **40** and the bit movement motor **50** based on the number of rotations of the bit rotation motor **40**, the number of rotations of the bit movement motor **50**, a gear ratio of a speed reducer, and the like so that by fastening the screw **200** to the fastening target by the rotation of the bit rotation motor **40**, the moving speed when the screw **200** is moved in the forward direction, the moving speed of the holding member **30** and the moving member **32** which move in the forward direction by the rotation of the bit movement motor **50**, and the moving speed of the driver bit **2** attached to the holding member **30** substantially coincide with one another as shown in FIG. **24B**.

(243) In step **SE10**, the control unit **100** controls the bit movement motor **50** in the present example by the feedback control based on the number of rotations of the bit rotation motor **40**, the number of rotations of the bit movement motor **50**, the gear ratio of the speed reducer, and the like. For example, the control is performed by increasing or decreasing PWM output to the bit movement

motor **50** and adjusting the rotation speed.

(244) When it is determined that the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position **P2** in step **SE6**, the control unit **100** stops driving of the bit rotation motor **40** in step **SE11**, stops rotation of the bit movement motor **50** in the positive direction in step **SE12**, and then reversely rotates the bit movement motor **50** in step **SE13**.

(245) When the bit movement motor **50** rotates in the reverse direction, which is the other direction, the pulley **52** rotates in the reverse direction, so that the wire **54** is pulled out from the pulley **52**, and the moving member **32** in which the second moving member **32c** is pressed by the biasing member **33** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the rearward direction.

(246) When the bit movement motor **50** rotates reversely to an initial position where the wire **54** is pulled out from the pulley **52** by a predetermined amount and the holding member **30** and the moving member **32** move in the rearward direction to a position where the tip end of the driver bit **2** returns to the standby position **P1** in step **SE14**, the control unit **100** stops the reverse rotation of the bit movement motor **50** in step **SE15**.

(247) The feedback control described above is control required after the fastening target and the screw **200** come into contact with each other and loads on the bit rotation motor **40** and the bit movement motor **50** fluctuate. Therefore, control when the feedback control is not executed is set as a first control mode, and control when the feedback control is executed is set as a second control mode, and the first control mode is executed before a predetermined load is detected in one or both of the bit rotation motor **40** and the bit movement motor **50**. When the predetermined load is detected in one or both of the bit rotation motor **40** and the bit movement motor **50**, the first control mode is switched to the second control mode, and the second control mode is executed.

Accordingly, it is possible to prevent a delay in an operation time.

(248) As a unit that improves responsiveness of the feedback control and implements more stable work quality, an acceleration or deceleration limit value for the bit movement motor **50** may be changed when the feedback control is executed after the load is detected and when the feedback control is not executed before the load is detected. Normally, when the PWM output is performed to the motor, by limiting an acceleration amount per unit time in order to stabilize the output of the motor, control is executed to prevent an acceleration current at the time of starting in particular from becoming excessive. However, when the above feedback control is executed while acceleration is limited at the time of starting the bit movement motor **50**, the PWM output generated by the feedback control is limited and applied to the bit movement motor **50**, so that responsiveness to the feedback control is deteriorated. Therefore, during execution of the feedback control, it is desirable to set an acceleration limit amount to be larger than that at the time of starting the motor when the feedback control is not executed.

(249) FIG. **25** is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment. FIGS. **26A** and **26B** are graphs showing relationships between loads and control over the bit movement motor. Next, the other modification of the fastening operation of the fastening tool according to the present embodiment will be described with reference to the drawings. In this modification, a load applied to the bit movement motor **50** is detected to control the bit movement motor **50**.

(250) In the standby state of the fastening tool **1**, as shown in FIG. **1A**, the tip end of the driver bit **2** is positioned at the standby position **P1** on the rear side of the injection passage **80**, and the screw **200** can be supplied to the injection passage **80**.

(251) In step **SF1** of FIG. **25**, the control unit **100** sets the number of rotations of the bit movement motor **50** that defines the forward movement amount of the driver bit **2** based on a setting value selected by the setting portion **110**. When the contact member **81** is pressed against the fastening target, the contact switch portion **84** is pressed by the contact arm **82**, the contact switch portion **84**

is turned on in step SF2, the trigger **9** is operated, and the trigger switch portion **90** is turned on in step SF3, the control unit **100** drives the bit rotation motor **40** of the first drive unit **4** in step SF4, and drives the bit movement motor **50** of the second drive unit **5** in step SF5.

(252) When the bit movement motor **50** is driven to rotate in the positive direction, which is the one direction, the pulley **52** rotates in the positive direction, so that the wire **54** is wound around the pulley **52**, and the moving member **32** in which the second moving member **32c** is connected to the wire **54** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the forward direction.

(253) Accordingly, the driver bit **2** held by the holding member **30** moves in the forward direction indicated by the arrow **A1**, engages with the screw **200** supplied to the injection port **81a** of the nose portion **8**, moves the screw **200** in the forward direction, and presses the screw **200** against the fastening target.

(254) When the bit rotation motor **40** is driven to rotate in the positive direction, which is the one direction, the holding member **30** rotates together with the rotation guide member **31**.

(255) Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction (clockwise) and screws the screw **200** into the fastening target. The control unit **100** moves the driver bit **2** in the forward direction by the second drive unit **5** in conjunction with an operation of rotating the driver bit **2** by the first drive unit **4** to screw the screw into the fastening target, thereby causing the driver bit **2** to follow the screw to be screwed into the fastening target.

(256) In step SF6, the control unit **100** determines whether the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position **P2**. When it is determined that the number of rotations of the bit movement motor **50** does not reach the setting value selected by the setting portion **110**, the control unit **100** detects a load applied to the bit movement motor **50** in step SF7, and when the control unit **100** detects a predetermined load, the control unit **100** controls the bit movement motor **50** in step SF8.

(257) When the holding member **30** and the moving member **32** move in the forward direction by driving of the bit movement motor **50**, in order to prevent occurrence of an excessive impact when the screw **200** is pressed against the fastening target, the bit rotation motor **40** performs maximum output within an assumed range in order to prevent a fastening speed from being decreased, and output of the bit movement motor **50** is limited by lowering a voltage value applied to the bit movement motor **50**, lowering a current value supplied to the bit movement motor **50**, or the like.

(258) When a ratio of a forward movement amount of the driver bit **2** per rotation of the bit movement motor **50** to a forward movement amount of the screw per rotation of the bit rotation motor **40** becomes low, the forward movement amount of the driver bit **2** by the bit movement motor **50** cannot catch up with the forward movement amount of the screw by the bit rotation motor **40**, and therefore cam-out occurs. On the other hand, when the ratio of the forward movement amount of the driver bit **2** per rotation of the bit movement motor **50** to the forward movement amount of the screw per rotation of the bit rotation motor **40** becomes high, the forward movement amount of the driver bit **2** by the bit movement motor **50** greatly exceeds the forward movement amount of the screw by the bit rotation motor **40**, and therefore an excessive force is required to press the fastening tool **1** in a fastening target direction by the operator.

(259) Therefore, as a target value of an output limitation, it is preferable that the ratio of the forward movement amount of the driver bit **2** per rotation of the bit movement motor **50** to the forward movement amount of the screw per rotation of the bit rotation motor **40** is about 0.8 time to 5 times. Accordingly, it is possible to prevent occurrence of cam-out, and without requiring an excessive force for pressing the fastening tool **1** toward the fastening target direction by the operator, it is possible to prevent occurrence of an excessive impact when the screw **200** is pressed against the fastening target.

(260) When the load on the bit movement motor **50** generated after the fastening target and the

screw **200** contact with each other is detected, the output of the bit movement motor **50** is limited, and thus, when the screw **200** is pressed against the fastening target, the holding member **30** and the moving member **32** are decelerated, so that it is possible to obtain an effect of further preventing impact.

(261) In control for limiting output of the bit movement motor **50**, as shown in FIG. **26A**, after a predetermined load is detected, the output of the bit movement motor **50** may be limited so that the rotation speed becomes constant until the bit rotation motor **40** rotates at the number of rotations for moving the driver bit **2** to the operation end position. As shown in FIG. **26B**, the bit movement motor **50** is rotated forward at a first rotation speed until the predetermined load is detected. After the predetermined load is detected, the bit movement motor **50** is rotated forward at a second rotation speed that is reduced in the rotation speed in order to weaken impact when the screw **200** is pressed against the fastening target. Further, after a predetermined buffering time elapses in which the impact when the screw **200** is pressed against the fastening target is weakened, the output may be limited so as to be a constant rotation speed at a third rotation speed that is slower than the first rotation speed and faster than the second rotation speed until the bit rotation motor **40** rotates at the number of rotations for moving the driver bit **2** to the operation end position.

(262) A fluctuation in the power supply voltage causes a difference in the moving speed (forward speed) of the holding member **30** and the moving member **32**. The higher the power supply voltage, the faster the moving speed, and the more likely an excessive impact occurs when the screw **200** is pressed against the fastening target. Therefore, the control unit **100** detects the power supply voltage, and decreases the output of the bit movement motor **50** as the power supply voltage is high, as compared with the case where the power supply voltage is low.

(263) Accordingly, occurrence of the difference in the rotation speed of the bit movement motor **50** due to the fluctuation in the power supply voltage is prevented. Therefore, when the screw **200** is pressed against the fastening target, occurrence of an excessive impact is prevented, and occurrence of variation in a speed at which the screw **200** is pressed against the fastening target is prevented.

(264) When it is determined that the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position P2 in step SF6, the control unit **100** stops driving of the bit rotation motor **40** in step SF9, stops rotation of the bit movement motor **50** in the positive direction in step SF10, and then reversely rotates the bit movement motor **50** in step SF11.

(265) When the bit movement motor **50** rotates in the reverse direction, which is the other direction, the pulley **52** rotates in the reverse direction, so that the wire **54** is pulled out from the pulley **52**, and the moving member **32** in which the second moving member **32c** is pressed by the biasing member **33** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the rearward direction.

(266) When the bit movement motor **50** rotates reversely to an initial position where the wire **54** is pulled out from the pulley **52** by a predetermined amount and the holding member **30** and the moving member **32** move in the rearward direction to a position where the tip end of the driver bit **2** returns to the standby position P1 in step SF12, the control unit **100** stops the reverse rotation of the bit movement motor **50** in step SF13.

(267) FIG. **27** is a flowchart showing another modification of the operation of the fastening tool according to the present embodiment. Next, the other modification of the fastening operation of the fastening tool according to the present embodiment will be described with reference to the drawings. In this modification, a load applied to the bit movement motor **50** or the like is detected, and driving in a state where there is no screw is prevented.

(268) In the standby state of the fastening tool **1**, as shown in FIG. **1A**, the tip end of the driver bit **2** is positioned at the standby position P1 on the rear side of the injection passage **80**, and the screw **200** can be supplied to the injection passage **80**.

(269) In step SG1 of FIG. **27**, the control unit **100** sets the number of rotations of the bit movement

motor **50** that defines the forward movement amount of the driver bit **2** based on a setting value selected by the setting portion **110**. When the contact member **81** is pressed against the fastening target, the contact switch portion **84** is pressed by the contact arm **82**, the contact switch portion **84** is turned on in step SG2, the trigger **9** is operated, and the trigger switch portion **90** is turned on in step SG3, the control unit **100** drives the bit rotation motor **40** of the first drive unit **4** in step SG4, and drives the bit movement motor **50** of the second drive unit **5** in step SG5.

(270) When the bit movement motor **50** is driven to rotate in the positive direction, which is the one direction, the pulley **52** rotates in the positive direction, so that the wire **54** is wound around the pulley **52**, and the moving member **32** in which the second moving member **32c** is connected to the wire **54** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the forward direction.

(271) Accordingly, the driver bit **2** held by the holding member **30** moves in the forward direction indicated by the arrow **A1**, engages with the screw **200** supplied to the injection port **81a** of the nose portion **8**, moves the screw **200** in the forward direction, and presses the screw **200** against the fastening target.

(272) When the bit rotation motor **40** is driven to rotate in the positive direction, which is the one direction, the holding member **30** rotates together with the rotation guide member **31**.

(273) Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction (clockwise) and screws the screw **200** into the fastening target. The control unit **100** moves the driver bit **2** in the forward direction by the second drive unit **5** in conjunction with an operation of rotating the driver bit **2** by the first drive unit **4** to screw the screw into the fastening target, thereby causing the driver bit **2** to follow the screw to be screwed into the fastening target.

(274) In step SG6, the control unit **100** determines whether the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position **P2**. When it is determined that the number of rotations of the bit movement motor **50** does not reach the setting value selected by the setting portion **110**, the control unit **100** detects a load applied to one or both of the bit rotation motor **40** and the bit movement motor **50** in step SG7. When the screw **200** is pressed against the fastening target and a predetermined load is detected, the bit movement motor **50** continues to rotate in the positive direction until the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110**.

(275) When the control unit **100** determines that the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position **P2** in step SG6, the control unit **100** stops driving of the bit rotation motor **40** in step SG8, stops rotation of the bit movement motor **50** in the positive direction in step SG9, and then reversely rotates the bit movement motor **50** in step SG10.

(276) When the bit movement motor **50** rotates in the reverse direction, which is the other direction, the pulley **52** rotates in the reverse direction, so that the wire **54** is pulled out from the pulley **52**, and the moving member **32** in which the second moving member **32c** is pressed by the biasing member **33** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the rearward direction.

(277) When the bit movement motor **50** rotates reversely to an initial position where the wire **54** is pulled out from the pulley **52** by a predetermined amount and the holding member **30** and the moving member **32** move in the rearward direction to a position where the tip end of the driver bit **2** returns to the standby position **P1** in step SG11, the control unit **100** stops the reverse rotation of the bit movement motor **50** in step SG12.

(278) When the bit rotation motor **40** and the bit movement motor **50** rotate in the positive direction in a state where the screw **200** is not in the injection port **81a**, the screw **200** is not pressed against the fastening target, so that loads applied to the bit rotation motor **40** and the bit movement motor **50** do not increase. Therefore, if a predetermined load is not detected even if the driver bit **2**

attached to the holding member **30** moves forward by a specified movement amount with reference to a length of the smallest screw **200** to be loaded, it can be determined that there is no screw **200**. (279) Therefore, in step **SG13**, the control unit **100** determines whether the bit movement motor **50** rotates by a specified movement amount with reference to the length of the smallest screw **200** to be loaded or by a specified amount of idle rotation detection by which the driver bit **2** attached to the holding member **30** moves forward. When it is determined that a predetermined load is not detected in one or both of the bit rotation motor **40** and the bit movement motor **50** and that the bit movement motor **50** rotates by the specified amount of idle rotation detection, the control unit **100** determines that there is no screw **200**, and notifies an error in step **SG14**. In processing of steps **SG8** to **SG12** described above, driving of the bit rotation motor **40** and the bit movement motor **50** is stopped.

(280) The control unit **100** may detect the load applied to one or both of the bit rotation motor **40** and the bit movement motor **50** by a change in a current flowing through the motor except for a change in the current generated at the time of starting the motor. The detection may be performed based on a change in a voltage flowing through the motor except for a change in the voltage generated at the time of starting the motor. The rotation of the bit holding portion **3** and the movement of the bit holding portion **3** in the axial direction may be performed by a single motor. The control unit **100** may detect a load applied to the single motor and prevent driving in a state in which there is no screw.

(281) Next, another modification of the fastening operation of the fastening tool according to the present embodiment will be described. Here, in order to prevent malfunction, the fastening tool **1** starts a screw tightening operation when a condition is satisfied in which both the contact arm **82** based on pressing of the contact member **81** against the fastening target and the trigger switch portion **90** based on a pulling operation of the trigger **9** are ON. In the contact arm **82**, there is a stroke until it is determined that the contact arm **82** is switched from OFF to ON. In order to reliably detect the ON of the contact arm **82**, there is a room for further pushing the contact arm **82** from an ON state in consideration of a variation in an assembly of the fastening tool. As a result, within the stroke of the contact arm **82**, positions of the contact member **81** and the contact arm **82** may fluctuate even in the same OFF or the same ON. In such a case, for example, depending on a pushed position of the contact member **81**, the screw tightening operation is executed in a state in which the contact member **81** floats up slightly with respect to the tool body **10**, so that a seating surface of a screw head may float up from a surface of a fastening target, and a driving failure may occur. Therefore, in the present modification, a technique is provided for eliminating fluctuation in ON and OFF positions of the contact arm **82** due to the variation in the assembly of the fastening tool **1** or the like, and improving ON and OFF accuracy of the contact arm **82**.

(282) FIG. **28** is a side view showing an example of the fastening tool according to a modification. In a fastening tool **1A** according to the modification, the same reference signs are given to the same configurations as those of the fastening tool **1** according to the above embodiment, and the description of the fastening tool **1** is referred to for configurations and operations that are common to those of the above embodiment, and redundant description will be omitted and simplified.

(283) As shown in FIG. **28**, the fastening tool **1A** includes the first drive unit **4** that rotates the driver bit **2** held by the bit holding portion **3**, and the second drive unit **5** that moves the driver bit **2** held by the bit holding portion **3** in the axial direction. The fastening tool **1A** includes the screw accommodating portion **6** in which the screw **200** (see FIG. **1A**) is accommodated, the nose portion **8** that is pressed against a fastening target to which the screw **200** is fastened and into which the screw is injected, the tool body **10**, the handle **11** that is attached to a lower surface of the tool body **10**, and the battery **12** that is detachably attached to a lower end portion of the handle **11**.

(284) The nose portion **8** includes the injection passage **80**, the injection port **81a**, the contact member **81** that contacts the fastening target, the contact arm **82** that moves in a front-rear direction in conjunction with the contact member **81**, and a magnet **82a** that moves in conjunction with the

contact arm **82**.

(285) The contact member **81** is supported so as to be movable in the front-rear direction indicated by the arrows **A1** and **A2**, and the contact arm **82** moves in the front-rear direction in conjunction with movement of the contact member **81**. In the nose portion **8**, the contact member **81** is biased in the forward direction by a biasing member (not shown), and the contact member **81** that is pressed against the fastening target and moves rearward is biased by the biasing member and moves in the forward direction.

(286) The fastening tool **1A** includes the magnet **82a** that moves in the front-rear direction indicated by the arrows **A1** and **A2** in conjunction with the contact arm **82** at a position that is a rear end portion of the contact arm **82** and faces a magnetic force element **130**. For example, the magnet **82a** may be attached to the rear end portion of the contact arm **82** as a separate member, or may be integrally formed with the rear end portion of the contact arm **82**.

(287) In the present embodiment, a rear end side of the contact arm **82** is branched into two parts, but a configuration may be adopted in which the magnet **82a** is attached to a portion of the contact arm **82** that is not separated.

(288) The magnetic force element **130** is provided at a position facing the magnet **82a** of the contact arm **82** on one side portion of the tool body **10** on which the contact arm **82** is provided. The magnetic force element **130** detects an analog amount of a magnetic field generated from the magnet **82a** of the contact arm **82** moving in a direction approaching the magnetic force element **130** by a pressing operation of the contact member **81** against the fastening target. Since a magnitude of the magnetic field detected by the magnetic force element **130** varies depending on a distance between the magnet **82a** provided on the contact arm and the magnetic force element **130**, a position of the contact arm **82** with respect to the magnetic force element **130** can be detected by detecting a magnetic force of the magnet **82a**.

(289) FIG. **29** is a block diagram showing an example of the fastening tool **1A** according to the present embodiment. As shown in FIG. **29**, the magnetic force element **130** and a recording unit **150** are connected to the control unit **100** in addition to the bit rotation motor **40**, the bit movement motor **50**, the trigger switch portion **90**, and the setting portion **110**.

(290) The magnetic force element **130** detects a magnetic field generated from the magnet **82a** provided on the contact arm **82** pushed toward a rear side of the tool body **10** in conjunction with the pressing operation of the contact member **81** against the fastening target, and outputs a voltage proportional to the magnitude of a detected magnetic field to the control unit **100**.

(291) The control unit **100** acquires a voltage value based on the magnetic field of the magnet **82a** output by the magnetic force element **130**. The control unit **100** has a threshold value setting mode for calculating a threshold value for determining whether the contact arm **82** is ON or OFF, and calculates a threshold value for determining whether the contact arm **82** is ON using a voltage value based on the acquired magnetic field of the magnet **82a**. The threshold value setting mode may be selectable by the setting portion **110** provided in the tool body **10**, or may be selectable by an operation portion separately provided in the tool body **10**. The threshold value setting mode may be selected and executed from an information processing device such as a personal computer or a tablet by wired or wireless communication.

(292) The control unit **100** acquires a voltage based on a magnetic field generated from the magnet **82a** of the contact arm **82** that moves to the rear side of the tool body **10** in conjunction with the pressing operation of the contact member **81** against the fastening target at the time of an actual screw tightening operation, and determines whether the contact arm **82** is ON or OFF based on a comparison result between the acquired voltage value and the threshold value calculated in the threshold value setting mode. That is, based on an ON or OFF state of the contact arm **82**, it is determined whether to start screw tightening by operating the bit rotation motor **40** or the like, not to start the screw tightening without operating the bit rotation motor **40** and the like, or to end the screw tightening.

(293) The recording unit **150** records various data such as the threshold value calculated in the threshold value setting mode executed by the control unit **100**, for example. As the recording unit **150**, for example, a magnetic storage device such as a hard disk drive (HDD), a semiconductor storage device, an optical storage device, or a magneto-optical storage device can be used.

(294) Next, an operation example when the threshold value setting mode is executed in the fastening tool **1A** will be described. FIG. **30** is a flowchart showing an example of an operation when the threshold value setting mode is executed in the fastening tool **1A**.

(295) Hereinafter, for example, a case where the threshold value setting mode is executed before shipment of the fastening tool **1A** will be described. The threshold value setting mode is performed for each fastening tool.

(296) As shown in FIG. **30**, in step SH1, in the fastening tool **1A**, the contact member **81** is pressed to a maximum pressing position, which is an example of a reference position, in a range in which the contact member **81** can be pushed against the fastening target. In the present modification, the maximum pressing position for push is a position at which a rear surface of the contact member **81** abuts against a front surface of the tool body **10**. The reference position may be a position other than the maximum pressing position for push of the contact member **81**, and may be set to a desired position in a pushable movement range (stroke) of the contact member **81**, for example. The reference position may be a plurality of positions pushed in stepwise, or may be a desired position selected from a plurality of positions. When pressing of the contact member **81** against the fastening target is completed, the processing proceeds to step SH2.

(297) In step SH2, the magnetic force element **130** detects a magnetic field generated by the magnet **82a** moved to the rear side of the tool body **10** together with the contact arm **82**, and outputs a voltage proportional to the magnetic field to the control unit **100**. Since there is a variation in an assembly for each fastening tool, a position (distance) of the magnet **82a** with respect to the magnetic force element **130** may be different for each fastening tool, and a magnitude of a voltage output from the magnetic force element **130** of each fastening tool may be different. The control unit **100** acquires the voltage value output from the magnetic force element **130**. When the voltage value is acquired, the processing proceeds to step SH3.

(298) In step SH3, the control unit **100** calculates, based on the acquired voltage value, a threshold value used in determining whether the contact arm **82** is ON or OFF. For example, in a case in which the position of the contact arm **82** when the contact member **81** is pushed to the rear side of the tool body **10** to the maximum is defined as a reference position O and a front position indicated by the arrow A1 with respect to the reference position O is defined as a positive side, the control unit **100** calculates a voltage value at a position a forward of the reference position O by $+\alpha$ mm as the threshold value (a position slightly forward of a position where the contact arm **82** is pushed to the maximum). The threshold value may have a certain range. After the threshold value is calculated, the processing proceeds to step SH4.

(299) In step SH4, the control unit **100** records the calculated threshold value in the recording unit **150**. In the present modification, the threshold value setting mode is performed for each fastening tool in consideration of variations in an assembly of the fastening tool, tolerances of components, and the like, so that a threshold value for determining ON of the contact arm **82** is calculated for each fastening tool, and the calculated threshold value is stored in the recording unit **150** of each fastening tool.

(300) Next, an operation example during the screw tightening operation by a fastening tool **1B** will be described using the threshold value for determining ON of the contact arm **82** calculated and recorded in FIG. **30**. Since a basic operation in this case is the same as the operation shown in FIG. **19**, the description of the common operation in the present modification will be omitted or simplified.

(301) FIG. **31** is a flowchart showing a modification of an operation of the fastening tool according to the present embodiment. FIG. **32** is a graph showing a relationship between a position state of

the contact arm and control over the bit rotation motor and the bit movement motor.

(302) In the standby state of the fastening tool **1B**, as shown in FIG. **1A**, the tip end of the driver bit **2** is positioned at the standby position **P1** on the rear side of the injection passage **80**, and the screw **200** can be supplied to the injection passage **80**.

(303) In step **SI1** of FIG. **31**, the control unit **100** sets the number of rotations of the bit movement motor **50** that defines the forward movement amount of the driver bit **2** based on a setting value selected by the setting portion **110**.

(304) When the contact member **81** is pressed against the fastening target by the operator, the contact arm **82** and the magnet **82a** provided on the contact arm **82** move to the rear side of the tool body **10** in conjunction with the pressing of the contact member **81**. In step **SI2**, the magnetic force element **130** detects the magnetic field of the magnet **82a** provided on the contact arm **82** moved to the rear side of the tool body **10**, and outputs a voltage proportional to a magnitude of the detected magnetic field. The control unit **100** compares a voltage value based on the magnetic field of the magnet **82a** output from the magnetic force element **130** with a threshold value calculated in advance in the threshold value setting mode, and determines that the contact arm **82** is ON when the voltage value is equal to or more than the threshold value. On the other hand, when the voltage value is less than the threshold value, it is determined that the contact arm **82** is OFF. For example, as described above, when the voltage value at the position **a** of $+\alpha$ mm from the reference position **O** is set as the threshold value and when the contact arm **82** is pushed in from the position **a** of $+\alpha$ mm, the acquired voltage value is equal to or more than the threshold value set in advance, so that it can be determined that the contact arm **82** is ON.

(305) In step **SI3**, when the contact arm **82** is ON and the trigger switch portion **90** is turned on by an operation of the trigger **9**, the control unit **100** proceeds to step **SI4**. The control unit **100** drives the bit rotation motor **40** of the first drive unit **4** in step **SI4**, and drives the bit movement motor **50** of the second drive unit **5** in step **SIS**.

(306) When the bit movement motor **50** is driven to rotate in the positive direction, which is the one direction, the pulley **52** rotates in the positive direction, so that the wire **54** is wound around the pulley **52**, and the moving member **32** in which the second moving member **32c** is connected to the wire **54** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the forward direction. Accordingly, the driver bit **2** held by the holding member **30** moves in the forward direction indicated by the arrow **A1**, engages with the screw **200** supplied to the injection port **81a** of the nose portion **8**, moves the screw **200** in the forward direction, and presses the screw **200** against the fastening target.

(307) When the bit rotation motor **40** is driven to rotate in the positive direction, which is the one direction, the holding member **30** rotates together with the rotation guide member **31**. Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction (clockwise) and screws the screw **200** into the fastening target. The control unit **100** moves the driver bit **2** in the forward direction by the second drive unit **5** in conjunction with an operation of rotating the driver bit **2** by the first drive unit **4** to screw the screw into the fastening target based on a load applied to the bit rotation motor **40**, the number of rotations of the bit rotation motor **40**, a load applied to the bit movement motor **50**, the number of rotations of the bit movement motor **50**, and the like, thereby causing the driver bit **2** to follow the screw to be screwed into the fastening target.

(308) When the control unit **100** determines in step **SI6** that the number of rotations of the bit movement motor **50** reaches the setting value selected by the setting portion **110** and the tip end of the driver bit **2** reaches the set operation end position **P2**, the control unit **100** stops driving of the bit movement motor **50** in step **SI7**.

(309) When the control unit **100** stops driving of the bit movement motor **50** in step **SI7**, the control unit **100** determines whether the contact arm **82** is ON in step **SI8**. Specifically, the control unit **100** determines whether the contact arm **82** is ON based on whether the voltage value based on the

magnetic field of the magnet **82a** is equal to or more than the threshold value set in advance. When the contact arm **82** is ON, the control unit **100** determines that the contact member **81** of the fastening tool **1A** does not float up in the direction away from the fastening target, stops rotation of the bit rotation motor **40** in the positive direction in step **SI9**, and rotates the bit movement motor **50** reversely in step **SI10** in order to end the fastening operation.

(310) When the bit movement motor **50** rotates in the reverse direction, which is the other direction, the pulley **52** rotates in the reverse direction, so that the wire **54** is pulled out from the pulley **52**, and the moving member **32** in which the second moving member **32c** is pressed by the biasing member **33** and the holding member **30** connected to the moving member **32** by the first moving member **32a** move in the rearward direction.

(311) When the bit movement motor **50** rotates reversely to an initial position where the wire **54** is pulled out from the pulley **52** by a predetermined amount and the holding member **30** and the moving member **32** move in the rearward direction to a position where the tip end of the driver bit **2** returns to the standby position **P1** in step **SI11**, the control unit **100** stops the reverse rotation of the bit movement motor **50** in step **SI12**.

(312) When the contact arm **82** is OFF in step **SI8**, the control unit **100** determines that the contact member **81** of the fastening tool **1A** floats up in the direction away from the fastening target, and continues driving for rotating the bit rotation motor **40** in the positive direction in a state where driving of the bit movement motor **50** is stopped.

(313) Accordingly, the driver bit **2** held by the holding member **30** rotates the screw **200** in the positive direction and further screws the screw **200** into the fastening target, so that the fastening tool **1A** moves in the direction approaching the fastening target. Along with this, the fastening tool **1A** moves relative to the contact arm **82**, and the control unit **100** determines that the contact arm **82** is ON. When the contact arm **82** is ON, the control unit **100** executes processing of steps **SI9** to **SI12** described above in order to end the fastening operation, and performs operations of stopping the bit rotation motor **40** and returning the driver bit **2** to the standby position by the reverse rotation of the bit movement motor **50**.

(314) When the voltage value based on the magnetic field of the magnet **82a** is less than the threshold value set in advance, the control unit **100** determines that the contact arm **82** is OFF, and in a state in which driving of the bit movement motor **50** is stopped, by performing control called a braking operation in which the bit movement motor **50** does not rotate by an external force during an operation of rotating the bit rotation motor **40** in the positive direction, the control unit **100** maintains a state in which the holding member **30**, the moving member **32**, and the driver bit **2** held by the holding member **30** are stopped at the operation end position **P**.

(315) However, in a state in which driving of the bit movement motor **50** is stopped, during an operation of rotating the bit rotation motor **40** in the positive direction, the screw **200** is tightened while a force is applied in a direction of pressing the fastening tool **1A** against the fastening target by the operator. Therefore, even when the braking operation is performed on the bit movement motor **50**, the holding member **30**, the moving member **32**, and the driver bit **2** held by the holding member **30** may move rearward from the operation end position **P2** due to a force applied by the operator.

(316) Therefore, the control unit **100** detects presence or absence of reverse rotation of the bit movement motor **50** in step **SI13**, and when the reverse rotation of the bit movement motor **50** is detected as indicated by an arrow in FIG. **32**, the control unit **100** returns to step **SIS**, rotates the bit movement motor **50** forward, moves the holding member **30** and the moving member **32** in the forward direction, and returns the driver bit **2** to the operation end position **P2**. Then, the forward rotation of the bit movement motor **50** is stopped, and the braking operation is performed.

(317) In the above embodiment, an example in which the threshold value setting mode is executed before shipment of the fastening tool **1A** is described, but the present disclosure is not limited thereto. For example, the threshold value setting mode may be executed after shipment of the

fastening tool **1A**. This is because, after shipment of the fastening tool **1A**, an assembled state of the tool may change, or shapes of the contact member **81**, the contact arm **82**, and the like may change due to aging deterioration due to use of the tool. In such a case, positions of the contact member **81** and the contact arm **82** set to ON may be different. Therefore, when the user uses the fastening tool **1A** for a certain period of time, the threshold value setting mode may be executed to recalculate and reset the threshold value when the contact arm **82** is ON.

(318) Next, a modification of the magnetic force element **130**, which is an example of the position detection unit described above, will be described. In the above embodiment, the magnetic force element **130** is used as the position detection unit that detects the position of the contact arm **82** that moves in conjunction with the pressing operation of the contact member **81**, but a distance sensor **140** may be used instead of the magnetic force element **130**. When the position detection unit is implemented by the distance sensor **140**, it is not necessary to provide the magnet **82a** at an end portion of the contact arm **82**.

(319) FIG. **33** is a block diagram showing an example of the fastening tool **1B** according to the present embodiment. As shown in FIG. **33**, a distance sensor **140** is connected to the control unit **100** in addition to the bit rotation motor **40**, the bit movement motor **50**, the trigger switch portion **90**, the setting portion **110**, and the recording unit **150**.

(320) The distance sensor **140** measures a distance that is an analog amount between the distance sensor **140** and the rear end portion of the contact arm **82** pushed toward the rear side of the tool body **10** in conjunction with the pressing operation of the contact member **81** against the fastening target, and outputs measured distance information to the control unit **100**. Since the distance measured by the distance sensor **140** corresponds to a position of the contact arm **82** with respect to the distance sensor **140**, position information of the contact member **81** and the contact arm **82** can be detected by measuring the distance to the contact arm **82**.

(321) The control unit **100** acquires distance information based on the position of the rear end portion of the contact arm **82** output from the distance sensor **140**. The control unit **100** has the threshold value setting mode for calculating a threshold value for determining whether the contact arm **82** is ON or OFF, and calculates a threshold value for determining whether the contact arm **82** is ON using the acquired distance information of the contact arm **82**. The control unit **100** acquires the distance between the distance sensor **140** and the contact arm **82** that moves to the rear side of the tool body **10** in conjunction with the contact member **81** at the time of an actual screw tightening operation, and determines whether the contact arm **82** is ON based on a comparison result between the acquired distance information and the threshold value calculated in the threshold value setting mode.

(322) The flowcharts of the fastening tool **1A** in the case of using the magnetic force element **130** shown in FIGS. **30** and **31** can be applied to processing using the distance sensor **140** according to the present modification. That is, by replacing the magnetic force element **130** with the distance sensor **140** and replacing the voltage value with the distance information, the threshold value setting mode shown in FIG. **30** and the operation at the time of the screw tightening operation shown in FIG. **31** can be implemented when the distance sensor **140** is used.

(323) Next, as a modification of the magnetic force element **130** which is an example of the position detection unit described above, the magnetic force element **130** may be implemented by a pressing force detection unit which detects a pressing force by the contact arm **82** which moves to the rear side of the tool body **10** in conjunction with the pressing operation of the contact member **81**. Also in this case, for example, the pressing force of the contact arm **82** at the time of maximum pushing of the contact member **81** may be set as a threshold value in advance, the pressing force detected by the pressing force detection unit by the pressing of the contact arm **82** may be compared with the threshold value at the time of actual screw tightening, and when the pressing force is equal to or more than the threshold value, it may be determined that the contact arm **82** is ON.

(324) As described above, according to the present modification, the threshold value is set based on the magnitude of the magnetic field of the magnet **82a** attached to the contact arm **82** with reference to the position of the contact arm **82** when the contact member **81** is pushed to the maximum position where the contact member **81** can be pushed. Therefore, accuracy of positions at which the contact arm **82** is ON or OFF increases, a position at which the contact arm **82** is ON can always be adjusted to the same position, and the position at which the contact arm **82** is ON can be set for each fastening tool without being affected by a component dimension and variation in an assembly. Accordingly, even when there is variation in an assembly or the like in the fastening tools **1A** and **1B**, it is possible to eliminate positional variation of the contact arm **82** being ON or OFF, floating-up of the contact member **81**, or the like, and it is possible to provide the fastening tools **1A** and **1B** with high accuracy of the screw tightening operation.

(325) Although the preferred embodiment of the present disclosure is described in detail with reference to the accompanying drawings, the technical scope of the present disclosure is not limited to these examples. For example, in the above embodiment, an example in which the contact member **81** and the contact arm **82** are implemented by separate components is described, but the present disclosure is not limited thereto, and the contact member **81** and the contact arm **82** may be implemented by a single component.

(326) Furthermore, the present disclosure relates to a fastening tool including: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; a motor configured to move the bit holding portion along the axial direction; and a control unit configured to control a position of the bit holding portion along the axial direction by the number of rotations of the motor. The control unit is configured to execute an initialization operation of setting a standby position of the bit holding portion along the axial direction, and control a position of the bit holding portion along the axial direction from the standby position by the number of rotations of the motor.

(327) In the present invention, by performing the initialization operation of setting the standby position in a configuration in which the position of the bit holding portion along the axial direction is controlled by the number of rotations of the motor from the standby position, the standby position serving as a reference for a movement end position of the driver bit can be set for each tool.

(328) The present disclosure further relates to a fastening tool including: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; a motor configured to rotate the bit holding portion and move the bit holding portion along the axial direction; a contact member which contacts a fastening target to which a screw engaged with the driver bit is fastened; a contact switch portion which is switched between ON and OFF according to a movement amount of the contact member in the axial direction when the contact member contacts the fastening target; and a control unit configured to control a timing at which driving of the motor is stopped based on ON or OFF of the contact switch portion.

(329) In the present invention, rotation and movement of the driver bit is prevented from ending before the driver bit reaches a movement end position.

(330) The present disclosure further relates to a fastening tool including: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; the motor configured to rotate the bit holding portion; a fluctuation detection unit configured to detect a factor causing a fluctuation in a rotation speed of the motor; and a control unit configured to perform, when the fluctuation detection unit detects a factor causing the fluctuation in the rotation speed of the motor, control to prevent the fluctuation in the rotation speed of the motor.

(331) In the present invention, after rotation of the motor is stopped, the driver bit rotates due to inertia to prevent the screw from being tightened. Therefore, a fluctuation in the rotation speed of

the motor is prevented so that the driver bit can be stopped at a movement end position.

(332) The present disclosure further relates to a fastening tool including: a bit holding portion configured to rotate in a circumferential direction of a driver bit and move in an axial direction of the driver bit; a motor configured to rotate the bit holding portion and move the bit holding portion along the axial direction; a trigger operably provided and configured to drive the motor; a contact member which contacts a fastening target and is configured to move in the axial direction; a contact arm which is movable in the axial direction in conjunction with the contact member; a position detection unit configured to detect a position of the contact arm moved in response to contact of the contact member with the fastening target; and a control unit configured to determine, based on the position of the contact arm detected by the position detection unit, whether the contact arm is ON or OFF, when a condition of both ON of the trigger and ON of the contact arm is satisfied, drive the motor, and control a timing at which driving of the motor is stopped based on an ON or OFF state of the contact arm.

(333) In the present invention, the movement end position of the driver bit can be controlled by the operation of moving the driver bit in a direction of tightening the screw.

Claims

1. A fastening tool comprising: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; a motor configured to perform at least one of rotation of the bit holding portion and movement of the bit holding portion along the axial direction; a contact member which contacts a fastening target; and a control unit configured to control a timing at which driving of the motor is stopped based on a movement amount of the contact member in the axial direction when the contact member contacts the fastening target, wherein the contact member contacts the fastening target to which a screw engaged with the driver bit is fastened, and the contact member is movable in the axial direction, wherein the fastening tool further comprises a contact switch portion which is switched between ON and OFF depending on the movement amount of the contact member in the axial direction, wherein the control unit is configured to control the timing at which the driving of the motor is stopped based on ON or OFF of the contact switch portion, and wherein the control unit determines, when the bit holding portion moves to an operation end position along the axial direction, whether the contact switch portion is ON or OFF, and when the contact switch portion is OFF, continues rotation of the motor in one direction of fastening the screw.

2. The fastening tool according to claim 1, wherein the motor includes a first motor configured to rotate the bit holding portion, and a second motor configured to move the bit holding portion along the axial direction, and the control unit is configured to control a position of the bit holding portion along the axial direction by the number of rotations of the second motor.

3. The fastening tool according to claim 1, wherein the contact member contacts the fastening target and is configured to move in the axial direction, wherein the fastening tool further comprises: a contact arm which is movable in the axial direction in conjunction with the contact member; and a position detection unit configured to detect a position of the contact arm, wherein the control unit is configured to determine, based on the position of the contact arm detected by the position detection unit, whether the contact arm is ON or OFF, when a condition of both ON of a trigger and ON of the contact arm is satisfied, drive the motor, and control a timing at which driving of the motor is stopped based on an ON or OFF state of the contact arm.

4. The fastening tool according to claim 3, wherein the control unit is configured to determine whether the contact arm is ON or OFF, based on a comparison result between the position of the contact arm detected by the position detection unit and a threshold value set based on a reference position of the contact arm.

5. The fastening tool according to claim 4, wherein the reference position is a position of the

contact arm when the contact member is pushed most against the fastening target.

6. The fastening tool according to claim 3, further comprising a magnet which moves in conjunction with the contact arm is included, wherein the position detection unit is implemented by a magnetic force element configured to detect a magnetic field generated from the magnet, and is configured to output a voltage proportional to a magnitude of the magnetic field detected by the magnetic force element to the control unit as position information of the contact arm, and wherein the control unit is configured to determine whether the contact arm is ON or OFF, based on a comparison result between the voltage and a threshold value set in advance.

7. The fastening tool according to claim 3, wherein the position detection unit is implemented by a distance sensor, and is configured to measure a distance to the contact arm, and output the distance to the control unit as the position information of the contact arm, and the control unit is configured to determine, based on a comparison result between the distance and a threshold value set in advance, whether the contact arm is ON or OFF.

8. A fastening tool comprising: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; a motor configured to perform at least one of rotation of the bit holding portion and movement of the bit holding portion along the axial direction; a contact member which contacts a fastening target; and a control unit configured to control a timing at which driving of the motor is stopped based on a movement amount of the contact member in the axial direction when the contact member contacts the fastening target, wherein the contact member contacts the fastening target to which a screw engaged with the driver bit is fastened, and the contact member is movable in the axial direction, wherein the fastening tool further comprises a contact switch portion which is switched between ON and OFF depending on the movement amount of the contact member in the axial direction, wherein the control unit is configured to control the timing at which the driving of the motor is stopped based on ON or OFF of the contact switch portion, wherein the motor includes a first motor configured to rotate the bit holding portion, and a second motor configured to move the bit holding portion along the axial direction, wherein the control unit is configured to control a position of the bit holding portion along the axial direction by the number of rotations of the second motor, and wherein the control unit is configured to rotate the first motor in one direction of fastening the screw, and rotate the second motor in one direction of moving the bit holding portion in a direction approaching the fastening target, and thereafter, based on the number of rotations of the second motor and ON or OFF of the contact switch portion, control a timing at which driving of the first motor and the second motor is stopped.

9. A fastening tool comprising: a bit holding portion which detachably holds a driver bit and is configured to rotate in a circumferential direction of the driver bit and move in an axial direction of the driver bit; a motor configured to perform at least one of rotation of the bit holding portion and movement of the bit holding portion along the axial direction; a contact member which contacts a fastening target; and a control unit configured to control a timing at which driving of the motor is stopped based on a movement amount of the contact member in the axial direction when the contact member contacts the fastening target, wherein the contact member contacts the fastening target to which a screw engaged with the driver bit is fastened, and the contact member is movable in the axial direction, wherein the fastening tool further comprises a contact switch portion which is switched between ON and OFF depending on the movement amount of the contact member in the axial direction, wherein the control unit is configured to control the timing at which the driving of the motor is stopped based on ON or OFF of the contact switch portion, wherein the motor includes a first motor configured to rotate the bit holding portion, and a second motor configured to move the bit holding portion along the axial direction, wherein the control unit is configured to control a position of the bit holding portion along the axial direction by the number of rotations of the second motor, and the control unit determines, when the second motor is rotated at the number of rotations at which the bit holding portion moves to an operation end position, whether the contact switch

portion is ON or OFF, and when the contact switch portion is OFF, continues rotation of the first motor in one direction.
