

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415420
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kim; Sungwang et al.

Vehicle and method of controlling the same

Abstract

A vehicle includes at least one holder, a communication interface configured to communicate with a user terminal, a user interface device configured to visualize and output vehicle operating information, and a controller configured to, in response to the user terminal being mounted on the at least one holder, identify a position of the user terminal, determine auxiliary information to be displayed on the user terminal from the vehicle operating information based on the position of the user terminal, and control the communication interface to transmit the auxiliary information to the user terminal.

Inventors: Kim; Sungwang (Seoul, KR), Kim; Jungdo (Seoul, KR), Moon; Jaemin (Yongin-si, KR), Park; Minjae (Seongnam-si, KR)

Applicant: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Family ID: 1000008819604

Assignee: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR)

Appl. No.: 18/493078

Filed: October 24, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240262195 A1	Aug. 08, 2024

Foreign Application Priority Data

KR	10-2023-0015058	Feb. 03, 2023
----	-----------------	---------------

Publication Classification

Int. Cl.: B60K35/00 (20240101); B60W50/14 (20200101); B60K35/81 (20240101)

U.S. Cl.:

CPC B60K35/00 (20130101); B60W50/14 (20130101); B60K35/81 (20240101); B60W2050/146 (20130101)

Field of Classification Search

CPC: B60K (35/00); B60K (35/81); B60K (35/10); B60K (35/22); B60K (35/29); B60K (35/80); B60K (35/85); B60K (2360/566); B60K (35/20); B60K (35/28); B60W (50/14); B60W (2050/146); B60R (11/0241); B60Y (2400/92)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8457883	12/2012	Chen	701/423	G01C 21/362
9098180	12/2014	Craig	N/A	G06F 3/0488
9997063	12/2017	Kim	N/A	G08C 17/02
10008016	12/2017	Naveh	N/A	G06T 11/60
10142668	12/2017	Nijim	N/A	H04N 21/41407
11400997	12/2021	Koosmann	N/A	G06F 3/0485
11693946	12/2022	Bradley	726/4	H04W 4/00
2014/0046590	12/2013	Needham et al.	N/A	N/A
2015/0127210	12/2014	Suzuki	N/A	N/A
2015/0373479	12/2014	Xia et al.	N/A	N/A
2019/0378475	12/2018	Lim	N/A	B60K 35/81
2020/0164747	12/2019	Oh	N/A	H04M 1/72406

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
20180004030	12/2017	KR	N/A
20180083073	12/2017	KR	N/A
20200060086	12/2019	KR	N/A

Primary Examiner: Camby; Richard M

Attorney, Agent or Firm: McDonnell Boehnen Hulbert & Berghoff LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application claims the benefit of priority to Korean Patent Application No. 10-2023-0015058, filed on Feb. 3, 2023 in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference.

TECHNICAL FIELD

(2) The present disclosure relates to a vehicle configured for displaying information on vehicle

operation in conjunction with a user terminal device and a method of controlling the same.

BACKGROUND

(3) In addition to basic driving functions, vehicles also feature additional functions for user convenience, such as audio, video, navigation, air conditioning, broadcasting, seat heating, and communication with user terminals.

(4) When performing a navigation function, a vehicle may display driving information on an In-Vehicle Infotainment (IVI) device, but the screen size of the IVI device is limited due to spatial constraints within the vehicle.

(5) As a result, a technology that can communicate with a user device, such as a smartphone, to additionally display driving information on the smartphone has become desirable.

SUMMARY

(6) Various aspects of the present disclosure provide a vehicle configured for determining auxiliary information to be displayed on a user terminal in response to the user terminal being mounted on a holder.

(7) Furthermore, various aspects of the present disclosure provide a vehicle configured for determining a priority among vehicle operation-related information and to determining information having the highest priority as auxiliary information.

(8) Additional aspects of the present disclosure will be set forth in part in the description which follows and, in part, will be obvious from the description, or may be learned by practice of the disclosure.

(9) In accordance with an embodiment of the present disclosure, a vehicle includes at least one holder, a communication interface configured to communicate with a user terminal, a user interface device configured to visualize and output vehicle operating information, and a controller configured to, in response to the user terminal being mounted on the at least one holder, identify a position of the user terminal, determine auxiliary information to be displayed on the user terminal from the vehicle operating information based on the position of the user terminal, and control the communication interface to transmit the auxiliary information to the user terminal.

(10) The vehicle operating information may include first information and second information, and the controller may determine priorities of the first information and the second information, and determine the first information or the second information as the auxiliary information based on the priorities.

(11) The controller may determine information continuously displayed on the user interface device as a first priority between the first information and the second information.

(12) The controller may determine information about driving guidance of the vehicle as a second priority between the first information and the second information.

(13) The vehicle operating information may include first information and second information, and the controller may receive information about the user terminal through the communication interface, determine priorities of the first information and the second information based on a position of the user terminal and the information about the user terminal, and determine, based on the priorities, the first information or the second information as the auxiliary information.

(14) The information about the user terminal may further include at least one of display size information, display resolution information, and tilt information of the user terminal.

(15) The controller may determine the first information as the auxiliary information in response to the tilt information of the user terminal being identified as a first reference value, and determine the second information as the auxiliary information in response to the tilt information of the user terminal being identified as a second reference value.

(16) The vehicle operating information may include first information and second information, and the controller may determine the first information as the auxiliary information in response to the position of the user terminal being identified as a first side of the user interface device, and determine the second information as the auxiliary information in response to the position of the

user terminal being identified as a second side of the user interface device.

(17) The controller may control the user interface device to visualize and output remaining information, excluding the auxiliary information from the vehicle operating information.

(18) The controller may control the communication interface to identify the position of the user terminal based on an ultra-wideband (UWB) communication or a Bluetooth communication.

(19) In accordance with another embodiment of the present disclosure, a method of controlling a vehicle including at least one holder, a communication interface communicating with a user terminal, a user interface device visualizing and outputting vehicle operating information is provided. The method includes identifying a position of the user terminal in response to the user terminal being mounted on the at least one holder, determining auxiliary information to be displayed on the user terminal from the vehicle operating information based on the position of the user terminal, and controlling the communication interface to transmit the auxiliary information to the user terminal.

(20) The vehicle operating information may include first information and second information, and the determining of the auxiliary information may further include determining priorities of the first information and the second information, and determining the first information or the second information as the auxiliary information based on the priorities.

(21) The determining of the priorities may further include determining information continuously displayed on the user interface device as a first priority between the first information and the second information.

(22) The determining of the priorities may further include determining information about driving guidance of the vehicle as a second priority between the first information and the second information.

(23) The vehicle operating information may include first information and second information, and the determining of the auxiliary information may further include receiving information about the user terminal through the communication interface, determining priorities of the first information and the second information based on a position of the user terminal and the information about the user terminal, and determining, based on the priorities, the first information or the second information as the auxiliary information.

(24) The information about the user terminal may further include at least one of display size information, display resolution information, and tilt information of the user terminal.

(25) The determining of the priorities may further include determining the first information as the auxiliary information in response to the tilt information of the user terminal being identified as a first reference value, and determining the second information as the auxiliary information in response to the tilt information of the user terminal being identified as a second reference value.

(26) The vehicle operating information may include first information and second information, and the determining of the priorities may further include determining the first information as the auxiliary information in response to the position of the user terminal being identified as a first side of the user interface device, and determining the second information as the auxiliary information in response to the position of the user terminal being identified as a second side of the user interface device.

(27) The method may further include controlling the user interface device to visualize and output remaining information, excluding the auxiliary information from the vehicle operating information.

(28) The identifying of the position of the user terminal may further include controlling the communication interface to identify the position of the user terminal based on an UWB communication or a Bluetooth communication.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These and/or other aspects of embodiments of the disclosure will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings, in which:
- (2) FIG. 1 is a view illustrating communication of a vehicle according to an exemplary embodiment of the present disclosure;
- (3) FIG. 2 is a view illustrating an interior of a vehicle according to an exemplary embodiment of the present disclosure;
- (4) FIG. 3 is a control block diagram illustrating a vehicle according to an exemplary embodiment of the present disclosure;
- (5) FIG. 4 is a view illustrating a user interface device and a holder of a vehicle according to an exemplary embodiment of the present disclosure;
- (6) FIG. 5 is a view illustrating that a user terminal is mounted on a holder of a vehicle according to an exemplary embodiment of the present disclosure;
- (7) FIG. 6 is a view illustrating that a user terminal is mounted on a left side holder according to an exemplary embodiment of the present disclosure;
- (8) FIG. 7 is a view illustrating a user terminal mounted on an upper side holder according to an exemplary embodiment of the present disclosure;
- (9) FIG. 8 is a view illustrating that a user terminal mounted on a right side holder according to an exemplary embodiment of the present disclosure;
- (10) FIG. 9 is a view illustrating that a user terminal is mounted on a lower side holder according to an exemplary embodiment of the present disclosure;
- (11) FIG. 10 is a view illustrating display of contents excluding auxiliary information in a user interface device of a vehicle according to an exemplary embodiment of the present disclosure;
- (12) FIG. 11 is a flowchart illustrating a method of controlling a vehicle according to an exemplary embodiment of the present disclosure;
- (13) FIG. 12 is a view illustrating that a controller of a vehicle determines priorities of information related to vehicle operation according to an exemplary embodiment of the present disclosure; and
- (14) FIG. 13 is a view illustrating that a controller of a vehicle determines a priority based on user terminal information according to an exemplary embodiment of the present disclosure.

DETAILED DESCRIPTION

- (15) Reference will now be made in detail to the embodiments of the disclosure, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout. This specification does not describe all elements of the disclosed embodiments and detailed descriptions of what is well known in the art or redundant descriptions on substantially the same configurations have been omitted. The terms ‘part’, ‘module’, ‘member’, ‘block’ and the like as used in the specification may be implemented in software or hardware. Further, a plurality of ‘part’, ‘module’, ‘member’, ‘block’ and the like may be embodied as one component. It is also possible that one ‘part’, ‘module’, ‘member’, ‘block’ and the like includes a plurality of components.
- (16) Throughout the specification, when an element is referred to as being “connected to” another element, it may be directly or indirectly connected to the other element and the “indirectly connected to” includes being connected to the other element via a wireless communication network.
- (17) Also, it is to be understood that the terms “include” and “have” are intended to indicate the existence of elements disclosed in the specification, and are not intended to preclude the possibility that one or more other elements may exist or may be added.
- (18) Throughout the specification, when a member is located “on” another member, this includes not only when one member is in contact with another member but also when another member is

present between the two members.

(19) The terms first, second, and the like are used to distinguish one component from another component, and the component is not limited by the terms described above.

(20) An expression used in the singular encompasses the expression of the plural, unless it has a clearly different meaning in the context.

(21) The reference numerals used in operations are used for descriptive convenience and are not intended to describe the order of operations and the operations may be performed in a different order unless otherwise stated.

(22) Hereinafter, embodiments of the disclosure will be described in detail with reference to the accompanying drawings.

(23) FIG. 1 is a view illustrating communication of a vehicle according to an embodiment of the disclosure.

(24) Referring to FIG. 1, a vehicle 1 according to an embodiment of the disclosure may communicate with a user terminal 3 via a network 2, which provides communication between the user terminal 3 and the vehicle 1.

(25) The user terminal 3 communicating with the vehicle 1 according to an embodiment of the disclosure may display auxiliary information, which is visually recognizable by a user, among driving information of the vehicle on a display.

(26) The user terminal 3 may include at least one of a smartphone, a tablet personal computer (PC), a mobile phone, a video phone, an e-book reader, a desktop PC, a laptop PC, a netbook computer, a personal digital assistant (PDA), a portable multimedia player (PMP), a MP3 player, a camera, a wearable device (e.g., head-mounted-device (HMD) such as electronic glasses), an electronic clothing, an electronic bracelet, an electronic necklace, an electronic accessory, a smart watch, or the like.

(27) Furthermore, the user terminal 3 according to various embodiments of the present disclosure may be a flexible device. In addition, it is obvious to those skilled in the art that the user terminal 3 according to various embodiments of the present disclosure is not limited to the aforementioned devices.

(28) A network according to one embodiment may support communication between the vehicle 1 and the user terminal 3, and may include at least one of a telecommunication network, for example, a computer network (e.g., local area network (LAN) or wide area network (WAN)), an Internet, or a telephone network. However, the type of network is not limited to the above examples, and any network for supporting communication may be included without limitation.

(29) As described above, the vehicle 1 and the user terminal 3 may communicate via a network, or may communicate directly via Bluetooth or Ultra-wideband (UWB). Accordingly, the vehicle 1 according to one embodiment may transmit auxiliary information to be displayed on the user terminal 3 among vehicle driving information to the user terminal 3.

(30) Hereinafter, an internal configuration of the vehicle 1 provided with a user interface device 100 will be described, wherein the user interface device 100 includes a holder for device (e.g., a user terminal).

(31) FIG. 2 is a view illustrating the interior of a vehicle according to an embodiment of the present disclosure.

(32) As shown in FIG. 2, the vehicle 1 may include front and rear doors 101, window glasses 102 (also referred to as windows) installed on the front and rear doors 101, respectively, and a side mirror which provides a rearward field of view of the vehicle 1 to a driver.

(33) The interior of the vehicle body may include a seat 104 on which an occupant sits, a dashboard 105, an instrument cluster (i.e. a cluster 106) disposed on the dashboard and including a tachometer, a speedometer, a coolant temperature gauge, a fuel gauge, a turn signal indicator, a high beam indicator, a warning lamp, a seat belt warning lamp, an odometer, a trip computer, an automatic shift selector indicator, a door open warning lamp, an engine oil warning lamp, and a low

fuel warning lamp, and a center fascia **107** with audio and a control panel for a heater and an air conditioner.

(34) The center fascia **107** may include the user interface device **100** including an air vent, a cigarette jack, and an audio/video/navigation (AVN) device. Herein, the user interface device **100** may be referred to as an In-Vehicle Infotainment (IVI) device.

(35) The user interface device **100** may include at least one holder (also referred to as a holder) thereon, and the user terminal **3** may be mounted on the holder. The user interface device **100** may be integrally provided with the cluster **106**, and if integrally provided, the holder may be arranged above, to the right of or below the user interface device **100**.

(36) Next, a configuration for controlling the vehicle **1** according to an exemplary embodiment of the present disclosure will be described with reference to FIG. **3**.

(37) FIG. **3** is a control block diagram illustrating a vehicle according to an exemplary embodiment of the present disclosure.

(38) Referring to FIG. **3**, the vehicle **1** may include the user interface device **100** including an AVN device **108**, a communication interface **300** performing wired/wireless communication with the user terminal **3**, and a controller **200** controlling the aforementioned components.

(39) The AVN device **108**, included in the user interface device **100**, may include an input part and an output part. The input part may receive an input **1** from a driver necessary for controlling the vehicle to transmit to the controller **200**, and the output part may include a display and visualize information related to an operation of the vehicle (hereinafter also referred to as vehicle operating information).

(40) As described above, the user interface includes the AVN device **108**, but in one embodiment, the user interface displaying vehicle operating information is not limited to the display of the AVN device **108**.

(41) The controller **200** of the vehicle **1** according to an exemplary embodiment of the present disclosure may communicate wired or wirelessly with the user terminal **3** by controlling the communication interface **300**, and transmit auxiliary information corresponding to some of the vehicle operating information to the user terminal **3**.

(42) The communication interface **300** may communicate with the user terminal **3** through direct communication or a wireless communication base station.

(43) For example, communication methods may employ second-generation (2G) communication methods, such as time division multiple access (TDMA) and code division multiple access (CDMA), third-generation (3G) communication methods, such as wideband code division multiple access (WCDMA), code division multiple access (CDMA2000), wireless broadband (Wibro), and world interoperability for microwave access (WiMAX), and fourth-generation (4G) communication methods, such as long term evolution (LTE) and wireless broadband evolution. The communication interface **300** may also employ fifth-generation (5G) communication methods.

(44) The communication interface **300** may include one or more components enabling communication with the user terminal **3**, and may include, for example, at least one of a wired communication interface **320** and a wireless communication interface **310**.

(45) The wireless communication interface **310** may include a short-range communication module. The short-distance communication module may include various short-distance communication modules for transmitting and receiving signals using a wireless communication network in a short distance, such as a Bluetooth module, an infrared communication module, a radio frequency identification (RFID) communication module, a wireless local access network (WLAN) communication module, a near field communication (NFC) module, and a Zigbee communication module, or the like.

(46) The wireless communication interface **310** may include a wireless communication module supporting various wireless communication methods, such as radio data system-traffic message channel (RDS-TMC), digital multimedia broadcasting (DMB), a WiFi module, and a wireless

broadband (WiBro) module, a global system for mobile communication (GSM) module, code division multiple access (CDMA), wideband code division multiple access (WCDMA), universal mobile telecommunications system (UMTS), time division multiple access (TDMA), LTE, or the like.

(47) The wireless communication interface **310** may include a wireless communication interface including an antenna and a receiver for receiving auxiliary information from the user terminal **3**. In addition, the wireless communication interface **310** may further include a signal conversion module for demodulating an analog type of wireless signal received through a wireless communication interface into a digital control signal.

(48) The wired communication interface **320** may include a variety of wired communication modules, such as a controller area network (CAN) communication module, a local area network (LAN) module, a wide area network (WAN) module, a value added network (VAN) module, or the like, and various cable communications, such as universal serial bus (USB), high definition multimedia interface (HDMI), digital visual interface (DVI), recommended standard 232 (RS-232), power line communication, plain old telephone service (POTS), or the like.

(49) The controller **200** may include a memory **220** for storing/temporarily storing programs and/or data, and a processor **210** for processing user input and/or metal guide detection data and/or communication data according to the programs and/or data stored in the memory **220**.

(50) The controller **200** may further include software such as programs and/or data stored in the memory **220** and processed by the processor **210**, as well as hardware such as the memory **220** and the processor **210**.

(51) The memory **220** may store/temporarily store programs and/or data. A program includes a plurality of instructions combined to perform a specific function, and data may be processed and/or manipulated by the plurality of instructions included in the program. In addition, the program and/or data may include system programs and/or system data directly related to the control of the vehicle **1** and application programs and/or application data providing convenience and entertainment to the user.

(52) The memory **220** may include a non-volatile memory **220** for storing programs and/or data for controlling components included in the vehicle **1** and a volatile memory **220** for storing temporary data generated while controlling components included in the vehicle **1**.

(53) The non-volatile memory **220** may, for example, store programs and/or data electrically, magnetically, or optically. The non-volatile memory **220** may include, for example, read only memory (ROM) and flash memory **220** for long-term storage of data. In addition, the non-volatile memory **220** may include solid state driver (SSD), hard disk drive (HDD), or optical disk drive (ODD).

(54) The volatile memory **220** may, for example, load programs and/or data from the non-volatile memory **220** and electrically store the programs and/or data. The volatile memory **220** may include, for example, static random access memory (S-RAM) or dynamic random access memory (D-RAM) for temporarily storing data.

(55) The memory **220** may store/temporarily store programs and data, such as operating system (OS), middleware, and applications, and provide programs and data to the processor **210** in response to a request of the processor **210**.

(56) The processor **210** may determine whether the user terminal **3** is mounted and/or determine the position of the user terminal **3** and/or process communication data of the communication interface **300** according to the programs and/or data stored/temporarily stored in the memory **220**. In addition, the processor **210** may generate a control signal for controlling an operation of the vehicle **1** based on data processing.

(57) The controller **200**, including the processor **210** and the memory **220** described above, may identify the position of the user terminal **3** in response to the user terminal **3** being mounted on the holder, determine auxiliary information to be displayed on the user terminal **3** from the vehicle

operating information based on the position of the user terminal **3**, and control the communication interface **300** to transmit the determined auxiliary information to the user terminal **3**.

(58) The controller **200** may determine a priority of a first information and a second information included in the vehicle operating information, and determine the first information or the second information as auxiliary information based on the priority.

(59) The controller **200** may determine information continuously displayed on the user interface device **100** as a first priority of the first information and the second information.

(60) The controller **200** may determine information about driving guidance of the vehicle **1** as a second priority of the first information and the second information.

(61) The controller **200** may receive the information on the user terminal **3** through the communication interface **300**, prioritize the first information and the second information based on the position of the user terminal **3** and the information on the user terminal **3**, and determine the first information or the second information as auxiliary information based on the priorities.

(62) The controller **200** may determine the first information as auxiliary information in response to tilt information of the user terminal **3** being identified as a first reference value, and determine the second information as auxiliary information in response to the tilt information of the user terminal **3** being identified as a second reference value.

(63) The controller **200** may determine the first information as auxiliary information in response to the position of the user terminal **3** being identified as a first side of the user interface device **100**, and determine the second information as auxiliary information in response to the position of the user terminal **3** being identified as a second side of the user interface device **100**.

(64) The controller **200** may control the user interface device **100** to visualize and output information except for the auxiliary information from the driving information of the vehicle **1**.

(65) The controller **200** may control the communication interface **300** so as to identify the position of the user terminal **3** based on UWB or Bluetooth communication.

(66) A specific control method of the controller **200** will be described in detail later, accompanied by drawings corresponding to embodiments.

(67) FIG. **4** is a view illustrating a user interface device and a holder of a vehicle according to an exemplary embodiment of the present disclosure, and FIG. **5** is a view illustrating a user terminal mounted on a holder of a vehicle according to an exemplary embodiment of the present disclosure.

(68) Referring to FIG. **4**, the user interface device **100** may include holders **109**, **109-1**, **109-2**, and **109-3** at the top, bottom, left side, and right side of the circumference thereof. The holders **109**, **109-1**, **109-2**, and **109-3** may be made of a magnetic material so that the user terminal **3** having magnetism may be mounted thereon.

(69) The user terminal **3** may be mounted by being coupled with a magnetic force to any one of the top, bottom, left, or right sides of the holders **109**, **109-1**, **109-2**, and **109-3** according to the user selection. Accordingly, the user terminal **3** made of a magnetic material or a case of the user terminal **3** made of a magnetic material may be mounted on the holder of the user interface device **100**.

(70) Referring to FIG. **5**, the user terminal **3** may be mounted on the left side holder of the user interface device **100**. As shown in FIG. **5**, when the user terminal **3** is mounted on the holder of the user interface device **100**, the information about the driving of the vehicle **1** is also displayed on the user terminal **3**, thereby affecting the enlargement of the display size of the user interface device **100**.

(71) To this end, the controller **200** may determine whether the user terminal **3** is mounted on the user interface device **100** in a magnetic manner. In particular, the controller **200** may determine whether the user terminal **3** is mounted based on a change in magnetic force or a change in permittivity according to a capacitance value.

(72) Furthermore, the controller **200** may determine the position of the user terminal **3** based on wireless communication, such as Bluetooth or UWB communication, and accordingly, may

determine that the user terminal **3** is mounted at a certain position of the user interface device **100** when the user terminal **3** is located within a predetermined distance from the user interface device **100**.

(73) Although the user terminal **3** is mounted long in the vertical direction shown in FIG. 5, the user terminal **3** may be mounted long in the left and right directions. Accordingly, the controller **200** may determine appropriate auxiliary information to be displayed on the user terminal **3** based on a mounting position and direction of the user terminal **3**. At this time, determination on the mounting direction of the user terminal **3** by the controller **200** may be determined, for example, based on an output value of a tilt sensor of the user terminal **3**, and the tilt sensor may include a gyro sensor.

(74) Furthermore, although the user interface device **100** is described in FIG. 5 as being made of a magnetic material, the user interface device **100** may be mounted in a structure that may be physically mounted by a separate mounting groove. In this case, the determination of mounting by the controller **200** may be made based on wireless communication, such as Bluetooth or UWB communication.

(75) FIG. 6 is a view illustrating that a user terminal is mounted on a left side holder according to an exemplary embodiment of the present disclosure.

(76) Referring to FIG. 6, a user of the vehicle **1** according to an exemplary embodiment of the present disclosure may mount the user terminal **3** on the left side holder **109-1** of the user interface device **100**.

(77) As described above, the controller **200** may determine whether the user terminal **3** is mounted on the holder **109-1** of the user interface device **100**, and determine the position of the user terminal **3** based on the user terminal **3** being mounted. After the position of the user terminal **3** is determined, the controller **200** may determine auxiliary information (b) to be displayed on the user terminal **3** mounted at the determined position among the vehicle operating information displayed on the user interface device **100**.

(78) At this time, the determination of the auxiliary information (b) by the controller **200**, includes determining priorities among the vehicle operating information and determining the information having a higher priority as the auxiliary information (b). In other words, the controller **200** may determine a priority of information that is continuously displayed on the user interface device **100**, such as cluster information, or information that is continuously displayed on the user interface device **100**, such as a taxi fare meter, as the first priority.

(79) Furthermore, the controller **200** may determine the priority of information about the driving guidance of the vehicle **1**, such as route information of the vehicle **1**, among the vehicle operating information displayed on the user interface device **100** as the second priority.

(80) In addition, the controller **200** may receive information about the user terminal **3** from the user terminal **3**, and the information about the user terminal **3** may include display size information, resolution information, and tilt information of the user terminal **3**. If the priorities determined above based on the received information about the user terminal **3** are the same, the controller **200** may set a higher priority.

(81) For example, as shown in FIG. 6, the controller **200** may control the user interface device **100** to display route information (a) of the vehicle operating information on the user interface device **100**. At this time, upon determining that the user terminal **3** is mounted on the left side holder **109-1**, the controller **200** may determine the auxiliary information (b) to be displayed on the user terminal **3** mounted on the left side holder **109-1** from among the route information (a) displayed on the user interface device **100**.

(82) Based on such a priority determination method, the controller **200** may determine the priority of the information continuously displayed on the user interface device **100** as the first priority, among the information displayed on the user interface device **100**. The information continuously displayed in FIG. 6 may include driving-related information including a speed of the vehicle **1** and

a current location of the vehicle **1** on a map in which the current location of the vehicle **1** is indicated by a triangle.

(83) The controller **200** may obtain a matching relationship from a storage in which the position of the user terminal **3** and the vehicle operating information are matched and stored, and based on the matching relationship, obtain the auxiliary information (b). In particular, the controller **200** may determine the route information displayed in the vertical direction on the left as the auxiliary information (b) based on the relationship that the user terminal **3** is mounted on the left side and vertically.

(84) Consequently, the controller **200** may determine the route information continuously displayed on the user interface device **100** as the auxiliary information (b) and transmit the determination to the user terminal **3**.

(85) FIG. **7** is a view illustrating a user terminal mounted on a top holder according to an exemplary embodiment of the present disclosure.

(86) As shown in FIG. **7**, the controller **200** may control the user interface device **100** to display the route information (a) of the vehicle operating information on the user interface device **100**. At this time, upon determining that the user terminal **3** is mounted on the top holder **109**, the controller **200** may determine the auxiliary information (b) to be displayed on the user terminal **3** mounted on the top holder **109** from among the information displayed on the user interface device **100**.

(87) Based on such a priority determination method, the controller **200** may determine the priority of the information continuously displayed on the user interface device **100** as the first priority among the information displayed on the user interface device **100**. The information continuously displayed in FIG. **7** may include the driving-related information including the speed of the vehicle **1** and the current location of the vehicle **1** on a map in which the current location of the vehicle **1** is indicated by a triangle.

(88) The controller **200** may obtain the matching relationship from a storage in which the position of the user terminal **3** and the vehicle operating information are matched and stored, and based on the matching relationship, obtain the auxiliary information (b). In particular, the controller **200** may determine information on a direction of the vehicle **1** closest to the user terminal **3**, which is displayed in the horizontal direction, as the auxiliary information (b) based on the relationship that the user terminal **3** is mounted on the top and horizontally.

(89) Although the information on the direction of the vehicle **1** has the second priority, the controller **200** may determine the information on the direction of the vehicle **1** as the auxiliary information (b) by increasing its priority based on the position and direction of the user terminal **3**.

(90) Consequently, the controller **200** may determine the information on the direction as the auxiliary information (b) and transmit the determination to the user terminal **3**.

(91) FIG. **8** is a view illustrating a user terminal mounted on a right holder according to an exemplary embodiment of the present disclosure.

(92) As shown in FIG. **8**, the controller **200** may control the user interface device **100** to display the route information (a) of the vehicle operating information on the user interface device **100**. At this time, upon determining that the user terminal **3** is mounted on the right holder **109-2**, the controller **200** may determine the auxiliary information (b) to be displayed on the user terminal **3** mounted on the right holder **109-2** from among the route information (a) displayed on the user interface device **100**.

(93) The controller **200** may determine the priorities of the information displayed on the user interface device **100** based on the priority determination method, but may exceptionally, based on the user selection, display information not displayed on the user interface device **100** on the user terminal **3**.

(94) For example, the controller **200** may additionally display information, such as a music playlist, in which the user desires to be displayed on the user interface device **100** but is unable to display on the user interface device **100** because navigation information is being already displayed, on the

user terminal **3**.

(95) Accordingly, by mounting the user terminal **3** on the user interface device **100**, new information, for example related to entertainment, which cannot be displayed on the user interface device **100** in a conventional manner, can be displayed on the user interface device **100**, thereby enhancing user convenience.

(96) FIG. **9** is a view illustrating that a user terminal is mounted on a bottom holder according to an exemplary embodiment of the present disclosure.

(97) As shown in FIG. **9**, the controller **200** may control the user interface device **100** to display the route information (a) of the vehicle operating information on the user interface device **100**. At this time, upon determining that the user terminal **3** is mounted on the bottom holder **109-3**, the controller **200** may determine the auxiliary information (b) to be displayed on the user terminal **3** mounted on the bottom holder **109-3** from among the route information (a) displayed on the user interface device **100**.

(98) The controller **200** may determine the priorities of the information displayed on the user interface device **100** based on the priority determination method, but may exceptionally, based on the user selection, display information not displayed on the user interface device **100** on the user terminal **3**.

(99) For example, the controller **200** may additionally display information, such as information related to air conditioning control in which the user desires to be displayed on the user interface device **100** but is unable to display on the user interface device **100** because navigation information is being already displayed, on the user terminal **3**.

(100) The controller **200** may receive an instruction input from the user terminal **3** based on communication with the user terminal **3**, so that the user may perform air conditioning control through the user terminal **3**.

(101) Accordingly, by mounting the user terminal **3** on the user interface device **100**, new information, for example related to function control, which cannot be displayed on the user interface device **100** in a conventional manner, can be displayed on the user interface device **100**, thereby enhancing user convenience.

(102) FIG. **10** is a view illustrating the display of content excluding the auxiliary information in the user interface device **100** of the vehicle according to an exemplary embodiment of the present disclosure.

(103) Referring to FIG. **10**, the controller **200** may remove the auxiliary information from the user interface device **100** based on a user selection, and enlarge and display the size of the remaining information. Consequently, the auxiliary information (b) is displayed on the user terminal **3** mounted on the holder (e.g., left holder **109-1**), and the vehicle operating information excluding the auxiliary information (b) is displayed on the user interface device **100**, thereby making map screen wider.

(104) For example, if the vehicle **1** according to one embodiment is a taxi, the controller **200** may display taxi operation information on the user interface device **100**, and may transmit auxiliary information to the user terminal **3** based on the user terminal **3** being mounted, to display information on taxi reservation and taxi fare information on the user terminal **3** as the auxiliary information.

(105) Furthermore, in response to a taxi call being received, the controller **200** may transmit auxiliary information to the user terminal **3** to display the location of a passenger as the auxiliary information to the user terminal **3**. Accordingly, according to one embodiment, the vehicle **1** may more effectively determine the location of the passenger in order to increase the passenger's boarding convenience.

(106) For another example, if the vehicle **1** according to another embodiment is the delivery vehicle **1**, the controller **200** may display information on vehicle operation for delivery on the user interface device **100**, and may transmit auxiliary information to the user terminal **3** based on the user

terminal **3** being mounted in order to display information related to a delivery list and delivery as auxiliary information. Accordingly, the vehicle **1** according to one embodiment has an effect of increasing the efficiency of the delivery business.

(107) FIG. **11** is a flowchart illustrating a method of controlling a vehicle according to an exemplary embodiment of the present disclosure.

(108) Referring to FIG. **11**, the controller **200** may display the vehicle operating information on the user interface device **100** (operation **1100**). At this time, the vehicle operating information may include route information, location information, speed information, and information suitable for the purpose of the commercial vehicle **1**.

(109) The controller **200** may determine whether a mounting signal of the user terminal **3** is received (operation **1110**). When the user terminal **3** is mounted on the holder of the user interface device **100** and the mounting signal of the user terminal **3** is received (Yes in operation **1110**), the controller **200** may determine the mounting position of the user terminal **3** based on wireless communication for determining the position of the user terminal **3** (operation **1120**). The wireless communication technology used by the controller **200** to determine the position of the user terminal **3** may include location estimation technology, such as Bluetooth or UWB communication.

(110) Thereafter, the controller **200** may receive the value output from the tilt sensor of the user terminal **3** through the communication interface **300**, determine the tilt of the user terminal **3** based on the received value of the tilt sensor, and determine the mounting direction of the user terminal **3** according to the tilt (operation **1130**).

(111) Consequently, in response to the location and direction of the mounted user terminal **3** being determined, the controller **200** may determine the priorities of the auxiliary information to be displayed on the user terminal **3** from among the vehicle operating information based on the position and direction of the user terminal **3** (operation **1140**).

(112) Thereafter, the controller **200** may determine the information having the highest priority as the auxiliary information based on the determined priorities (operation **1150**), and transmit the determined auxiliary information to the user terminal **3** (operation **1160**). As described with reference to FIG. **10**, the controller **200** may display on the user interface device **100** the remaining information, excluding the auxiliary information, from among the information about the vehicle **1** displayed on the user interface device **100** (operation **1170**).

(113) FIG. **12** is a view illustrating that a controller of a vehicle determines priorities of information related to vehicle operation according to an exemplary embodiment of the present disclosure.

(114) Referring to FIG. **12**, as in FIG. **11**, the controller **200** may receive the mounting signal of the user terminal **3** (operation **1200**). The controller **200** may determine the information continuously displayed on the user interface device **100** among the vehicle operating information displayed on the user interface device **100** based on the reception of the mounting signal of the user terminal **3** as the first priority (operation **1210**). In addition, the controller **200** may determine the information about the driving guidance of the vehicle **1** among the vehicle operating information of the vehicle **1** displayed on the user interface device **100** as the second priority (operation **1220**).

(115) As a result, the controller **200** may determine the priorities of the vehicle operating information of the vehicle **1** displayed on the user interface device **100**, and then determine the auxiliary information based on the priorities (operation **1230**). Thereafter, the controller **200** may transmit the determined auxiliary information to the user terminal **3** (operation **1240**), and accordingly the controller **200** may display the remaining information, excluding the auxiliary information from the information relating to the vehicle **1** displayed on the user interface device **100**, on the user interface device **100** (operation **1250**).

(116) FIG. **13** is a view illustrating that a controller of a vehicle, according to an exemplary embodiment of the present disclosure, determines priorities based on user terminal information.

(117) Referring to FIG. **13**, the controller **200** may receive the mounting signal of the user terminal **3** (operation **1300**). The controller **200** may control the communication interface **300** to receive the

information about the user terminal **3** including display size information, resolution information, and tilt information of the user terminal **3** (operation **1310**).

(118) The controller **200** may increase the priority of information corresponding to the display size of the user terminal **3** among the received information of the user terminal **3** (operation **1320**). For example, when determining the priorities of information to be displayed on the user terminal **3** based on the first and second priorities, the controller **200** may change the priority information of the second priority to the first priority and display in response to the display size of the user terminal **3** being smaller than the information of the first priority.

(119) In addition, the controller **200** may increase the priority of information corresponding to the display resolution of the user terminal **3** among the received information about the user terminal **3** (operation **1330**). For example, when determining the priorities of information to be displayed on the user terminal **3** based on the first and second priorities, the controller **200** may change the priority information of the second priority to the first priority and display upon determining that the resolution of the user terminal **3** does not match the information of the first priority.

(120) In addition, the controller **200** may increase the priority of information corresponding to the display tilt of the user terminal **3** among the received information about the user terminal **3** (operation **1340**). For example, when determining the priorities of information to be displayed on the user terminal **3** based on the first and second priorities, the controller **200** may determine the mounting direction of the user terminal **3** from the tilt information of the user terminal **3**, and upon determining that the mounting direction of the user terminal **3** does not match the direction included in the information of the first priority, change the priority information of the second priority to the first priority and display.

(121) The controller **200** may determine the auxiliary information based on the priorities (operation **1350**) and transmit the determined auxiliary information to the user terminal **3** (operation **1360**). Thereafter, the controller **200** may display on the user interface device **100** the remaining information, excluding the auxiliary information from the information relating to the vehicle **1** displayed on the user interface device **100** (operation **1370**).

(122) According to the vehicle according to various embodiments of the present disclosure, the controller may determine the auxiliary information to be displayed on the user terminal in consideration of the mounting location, mounting direction, and vehicle operating information of the user terminal, so that the user can view a lot of information on a wider screen.

(123) As is apparent from the above, various embodiments of the present disclosure may provide a vehicle capable of displaying additional information on the user terminal by expanding connectivity between the user terminal and the IVI device, thereby enhancing user convenience.

(124) Further, various embodiments of the present disclosure may provide a vehicle capable of displaying information used in commercial vehicles in a wider area by expanding connectivity between the user terminal and the IVI device.

(125) On the other hand, the above-described embodiments may be implemented in the form of a recording medium storing instructions executable by a computer. The instructions may be stored in the form of program code. When the instructions are executed by a processor, a program module is generated by the instructions so that the operations of the disclosed embodiments may be carried out. The recording medium may be implemented as a computer-readable recording medium.

(126) The computer-readable recording medium includes all types of recording media storing data readable by a computer system. Examples of the computer-readable recording medium include a Read Only Memory (ROM), a Random Access Memory (RAM), a magnetic tape, a magnetic disk, a flash memory, an optical data storage device, or the like.

(127) Although embodiments of the disclosure have been shown and described, it would be appreciated by those having ordinary skill in the art that changes may be made in these embodiments without departing from the principles and spirit of the disclosure, the scope of which is defined in the claims and their equivalents.

Claims

1. A vehicle, comprising: at least one holder; a communication interface configured to communicate with a user terminal; a user interface device configured to visualize and output vehicle operating information; and a controller configured to, in response to the user terminal being mounted on the at least one holder: identify a position of the user terminal; determine auxiliary information to be displayed on the user terminal from the vehicle operating information based on the position of the user terminal; and control the communication interface to transmit the auxiliary information to the user terminal.
2. The vehicle of claim 1, wherein the vehicle operating information includes first information and second information, and wherein the controller is further configured to determine priorities of the first information and the second information, and determine whether to identify the first information or the second information as the auxiliary information based on the priorities.
3. The vehicle of claim 2, wherein the controller is further configured to determine information continuously displayed on the user interface device as a first priority between the first information and the second information.
4. The vehicle of claim 3, wherein the controller is further configured to determine information about driving guidance of the vehicle as a second priority between the first information and the second information.
5. The vehicle of claim 1, wherein the vehicle operating information includes first information and second information, and wherein the controller is further configured to: receive information about the user terminal through the communication interface; determine priorities of the first information and the second information based on a position of the user terminal and the information about the user terminal; and determine, based on the priorities, whether to identify the first information or the second information as the auxiliary information.
6. The vehicle of claim 5, wherein the information about the user terminal further includes at least one of display size information, display resolution information, and tilt information of the user terminal.
7. The vehicle of claim 6, wherein the controller is further configured to: determine the first information as the auxiliary information in response to the tilt information of the user terminal being identified as a first reference value; and determine the second information as the auxiliary information in response to the tilt information of the user terminal being identified as a second reference value.
8. The vehicle of claim 1, wherein the vehicle operating information includes first information and second information, and wherein the controller is further configured to: determine the first information as the auxiliary information in response to the position of the user terminal being identified as a first side of the user interface device; and determine the second information as the auxiliary information in response to the position of the user terminal being identified as a second side of the user interface device.
9. The vehicle of claim 1, wherein the controller is further configured to control the user interface device to visualize and output remaining information, excluding the auxiliary information from the vehicle operating information.
10. The vehicle of claim 1, wherein the controller is further configured to control the communication interface to identify the position of the user terminal based on an ultra-wideband (UWB) communication or a Bluetooth communication.
11. A method of controlling a vehicle including at least one holder, a communication interface communicating with a user terminal, and a user interface device visualizing and outputting vehicle operating information, the method comprising: identifying, by a controller, a position of the user terminal in response to the user terminal being mounted on the at least one holder; determining

auxiliary information to be displayed on the user terminal from the vehicle operating information based on the position of the user terminal; and controlling the communication interface to transmit the auxiliary information to the user terminal.

12. The method of claim 11, wherein the vehicle operating information includes first information and second information, and wherein determining of the auxiliary information further comprises: determining priorities of the first information and the second information; and determining whether to identify the first information or the second information as the auxiliary information based on the priorities.

13. The method of claim 12, wherein the determining of the priorities further comprises determining information continuously displayed on the user interface device as a first priority between the first information and the second information.

14. The method of claim 13, wherein the determining of the priorities further comprises determining information about driving guidance of the vehicle as a second priority between the first information and the second information.

15. The method of claim 11, wherein the vehicle operating information includes first information and second information, and wherein the determining of the auxiliary information further comprises: receiving information about the user terminal through the communication interface; determining priorities of the first information and the second information based on a position of the user terminal and based on the information about the user terminal; and determining, based on the priorities, whether to identify the first information or the second information as the auxiliary information.

16. The method of claim 15, wherein the information about the user terminal further includes at least one of display size information, display resolution information, and tilt information of the user terminal.

17. The method of claim 16, wherein the determining of the priorities further comprises: determining the first information as the auxiliary information in response to the tilt information of the user terminal being identified as a first reference value; and determining the second information as the auxiliary information in response to the tilt information of the user terminal being identified as a second reference value.

18. The method of claim 11, wherein the vehicle operating information includes first information and second information, and wherein the determining of the priorities further comprises: determining the first information as the auxiliary information in response to the position of the user terminal being identified as a first side of the user interface device; and determining the second information as the auxiliary information in response to the position of the user terminal being identified as a second side of the user interface device.

19. The method of claim 11, further comprising controlling the user interface device to visualize and output remaining information, excluding the auxiliary information from the vehicle operating information.

20. The method of claim 11, wherein the identifying of the position of the user terminal further comprises controlling the communication interface to identify the position of the user terminal based on an ultra-wideband (UWB) communication or a Bluetooth communication.
