

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12415606
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Manson; Tim et al.

Aircraft seat assembly

Abstract

An aircraft seat arrangement includes aircraft seat devices which are arranged in an aircraft cabin section. The aircraft seat devices are designed to be at least partially different from one another and each have an aircraft seat which is designed as a full-flat seat. The aircraft seat devices in the aircraft cabin section differ in at least one comfort category, wherein the aircraft seat devices for the at least one comfort category each have a mutually different value which is caused by a different arrangement of the aircraft seats and by the at least partially different design of the aircraft seat devices.

Inventors:	Manson; Tim (Wembley, GB), Ducreux; Christophe (Aix-en-Provence, FR)
Applicant:	RECARO Aircraft Seating GmbH & Co. KG (Schwäbisch Hall, DE)
Family ID:	1000008819592
Assignee:	RECARO Aircraft Seating GmbH & Co. KG (Schwäbisch Hall, DE)
Appl. No.:	17/802039
Filed (or PCT Filed):	February 19, 2021
PCT No.:	PCT/EP2021/054217
PCT Pub. No.:	WO2021/170507
PCT Pub. Date:	September 02, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230182903 A1	Jun. 15, 2023

Foreign Application Priority Data

Publication Classification

Int. Cl.: B64C11/06 (20060101); B64D11/06 (20060101)

U.S. Cl.:

CPC B64D11/0604 (20141201); B64D11/0601 (20141201); B64D11/0641 (20141201);

Field of Classification Search

CPC: B64D (11/0604); B64D (11/0601); B64D (11/0641)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9718550	12/2016	Ko	N/A	B65G 47/917
10370108	12/2018	Williams	N/A	B64D 11/0606
10773804	12/2019	Valdes De La Garza	N/A	B64D 11/0601
11034452	12/2020	Scoley	N/A	B64D 11/0636
2003/0218095	12/2002	Saint Jalmes	244/118.5	B64D 11/00
2004/0195451	12/2003	Bentley	244/118.6	B64D 11/06
2005/0189451	12/2004	Mercier	N/A	N/A
2006/0086864	12/2005	Beroth	244/122R	B64D 11/0606
2007/0034742	12/2006	Jaeger	244/118.6	B64D 11/0601
2007/0040434	12/2006	Plant	297/354.13	B64D 11/0641
2007/0241232	12/2006	Thompson	244/118.6	B64D 11/0601
2008/0042010	12/2007	Watanabe	244/118.6	B64D 11/06
2008/0073463	12/2007	Guering	244/118.6	B64D 11/00
2008/0088160	12/2007	Johnson	297/344.21	B64D 11/06
2010/0038484	12/2009	Ersan	244/118.6	B64D 11/06
2010/0038485	12/2009	Harcup	244/118.6	B64D 11/0601
2010/0065684	12/2009	Ruiter	244/118.6	B64D 11/0641
2010/0308164	12/2009	McKeever	244/118.6	B64D 11/0641

2012/0146372	12/2011	Ferry	297/232	B64D 11/0606
2012/0223186	12/2011	Henshaw	244/118.6	B64D 11/0601
2012/0223557	12/2011	Henshaw	297/232	B60N 2/01
2012/0305705	12/2011	Vergnaud	244/118.6	B64D 11/0647
2013/0032668	12/2012	Foucher	244/118.6	B60N 2/01
2013/0105627	12/2012	Orson	244/118.5	B64D 11/0601
2013/0106156	12/2012	Orson	297/217.3	B64D 11/0641
2014/0035330	12/2013	Henshaw	297/217.3	B60N 2/01
2014/0283296	12/2013	Jerome	5/12.1	B64D 11/0604
2014/0306500	12/2013	Dryburgh	297/232	B64D 11/0601
2015/0069805	12/2014	Henshaw	N/A	N/A
2015/0166182	12/2014	Ducreux	244/118.6	B64D 11/06
2015/0166183	12/2014	Henshaw	244/118.6	B64D 11/064
2015/0166184	12/2014	Dryburgh et al.	N/A	N/A
2015/0225086	12/2014	Darbyshire	244/118.6	B64D 11/06
2015/0329208	12/2014	Eakins	703/1	G06F 30/15
2016/0059966	12/2015	Dryburgh	244/118.6	B64D 11/06
2016/0083094	12/2015	Clucas	244/118.6	B64D 11/06
2016/0297528	12/2015	Sankrithi	N/A	B64C 1/064
2017/0036765	12/2016	Braca	N/A	B64D 11/064
2017/0081030	12/2016	Clucas	N/A	B64D 11/0601
2017/0088267	12/2016	Dowty	N/A	B64D 11/0606
2017/0129611	12/2016	Morgan	N/A	B64D 11/06
2017/0259921	12/2016	Valdes De La Garza	N/A	B64D 11/0638
2017/0297719	12/2016	Lorsignol	N/A	B64D 11/0601
2018/0029712	12/2017	Sieben	N/A	B64D 11/0601
2018/0079508	12/2017	Carlioz	N/A	B64D 11/0604
2018/0265201	12/2017	Carlioz	N/A	B64D 11/0007
2018/0281959	12/2017	Braca	N/A	B64D 11/0601
2018/0281964	12/2017	Carlioz	N/A	B64D 11/0604
2019/0077512	12/2018	Bentley	N/A	B64D 11/0601

2019/0225340	12/2018	Lee	N/A	B64C 1/10
2019/0233116	12/2018	Braca	N/A	B64D 11/0639
2019/0308731	12/2018	Pozzi	N/A	B64D 11/0601
2019/0352011	12/2018	Aung	N/A	B60N 2/885
2020/0307797	12/2019	Henshaw	N/A	B64D 11/0606
2021/0027209	12/2020	Sankrithi	N/A	G06Q 10/02
2022/0332420	12/2021	Miedema	N/A	B64D 11/0601

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2014240780	12/2014	AU	B60N 2/01
60 2005 000 106	12/2004	DE	N/A
2944571	12/2014	EP	B60N 2/01
2019/179638	12/2018	WO	N/A
WO-2019179635	12/2018	WO	B64D 11/0601

OTHER PUBLICATIONS

German Search Report dated Feb. 3, 2021 issued in corresponding German Patent Application No. DE 10 2020 105 072.0 (and English translation). cited by applicant

International Search Report of the International Searching Authority mailed May 11, 2021 in corresponding International application No. PCT/EP2021/054217 (English Translation Only). cited by applicant

International Preliminary Report on Patentability of the International Searching Authority mailed Aug. 30, 2022 for the corresponding international application No. PCT/EP2021/054217 (English Translation Only). cited by applicant

European Office Action dated Oct. 8, 2024 issued for the corresponding European Patent Application No. 21709625.4 (and English translation). cited by applicant

Primary Examiner: Woldemaryam; Assres H

Attorney, Agent or Firm: Posz Law Group, PLC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application is a U.S. National Stage Application of PCT/EP2021/054217 filed on Feb. 19, 2021, which claims priority from and incorporates by reference German Patent Application DE 10 2020 105 072.0 filed on Feb. 26, 2020.

PRIOR ART

(2) The invention relates to an aircraft seat arrangement.

(3) An aircraft seat arrangement has already been proposed comprising a plurality of aircraft seat devices which are arranged in an aircraft cabin section and are designed to be at least partially different from one another and each have an aircraft seat, which is designed as a full-flat seat.

(4) It is the object of the invention in particular to provide an arrangement of the type in question with improved properties in respect of compactness and variability. The object is achieved according to the invention.

Advantages of the Invention

(5) The invention is based on an aircraft seat arrangement comprising a plurality of aircraft seat devices which are arranged in an aircraft cabin section and are designed to be at least partially different from one another and each have an aircraft seat which is designed as a full-flat seat.

(6) It is proposed that the aircraft seat devices in the aircraft cabin section differ in at least one comfort category, wherein the aircraft seat devices for the at least one comfort category each have a mutually different value which is caused by a different arrangement of the aircraft seats and by the at least partially different design of the aircraft seat devices. By means of a refinement according to the invention, an advantageously compact and variable arrangement of the plurality of aircraft seat devices can be achieved. By means of the refinement according to the invention, the plurality of aircraft seat devices can advantageously be simply combined with one another. Furthermore, by means of the refinement according to the invention, the plurality of aircraft seat devices can be positioned particularly advantageously with respect to one another. Efficient use can advantageously be made of an available space as a result. Furthermore, as a result, the aircraft seats can form an advantageously large lying surface in the lying position. Furthermore, by means of the refinement according to the invention, aircraft seat devices, in particular arranged next to one another, of the plurality of aircraft seat devices can advantageously be positioned variably with respect to one another. Particularly advantageously, it is possible to create different regions which meet individual requirements of passengers, in particular passengers traveling alone or passengers traveling in pairs. By means of the refinement according to the invention, different comfort categories can advantageously be achieved for different passenger needs. The aircraft seat arrangement is preferably configured for use in a cabin of an aircraft. The aircraft cabin is preferably intended for all passengers to be in during a flight, in particular irrespective of a reserved seat class. Examples of seat classes include economy class, premium economy class, business class and first class. The aircraft cabin preferably has at least one aircraft cabin section, in particular along an aircraft longitudinal axis. The at least one aircraft cabin section is preferably delimited along an aircraft longitudinal axis by at least one separating element, in particular a partition or a curtain, and/or by at least one aircraft cabin module, in particular a kitchen module or a toilet module. A seat class can be arranged in particular in a plurality of aircraft cabin sections. The aircraft cabin preferably has an aircraft cabin center axis. The aircraft cabin center axis is preferably in each case at the same distance from opposite outer walls of the aircraft cabin. The aircraft cabin center axis is preferably oriented parallel to a rolling axis of the aircraft. The aircraft cabin center axis is preferably oriented parallel to the floor of the aircraft cabin. An “aircraft longitudinal axis” is intended to be understood in particular as meaning an axis which extends in the direction of a greatest extent of the aircraft cabin and which is arranged within the aircraft cabin. The aircraft longitudinal axis is oriented in particular parallel to the aircraft cabin center axis. In at least one operating state, the aircraft preferably has a flight direction. The flight direction, in particular in an ideal operating state, is preferably oriented parallel to the aircraft cabin center axis and/or to an aircraft longitudinal axis. The aircraft cabin preferably has at least one aircraft cabin aisle. The at least one aircraft cabin aisle preferably extends at least substantially along an aircraft longitudinal axis. The aircraft seat devices preferably each form an aircraft seat region. An “aircraft seat region” is intended to be understood here as meaning in particular a region which is available to a passenger in the aircraft cabin, in particular while the passenger is sitting or lying on the aircraft seat. The aircraft seat devices are preferably configured to be installed on the floor of the aircraft cabin. “Configured” is intended to be understood as meaning in particular specially designed and/or equipped. That an object is configured for a certain function is intended to be understood as meaning in particular that the object carries out and/or performs this certain

function in at least one use and/or operating state. The aircraft seat devices preferably each have an aircraft seat which is configured to provide a sitting place for a passenger in the aircraft. A “different arrangement of the aircraft seats” is intended to be understood as meaning in particular that the aircraft seats of the plurality of aircraft seat devices have mutually different sitting directions and/or lying directions and/or that the aircraft seats of the plurality of aircraft seat devices are at different, in particular minimum or maximum, distances from an aisle of the aircraft cabin. Furthermore, a “different arrangement of the aircraft seats” is intended to be understood as meaning in particular a different positioning of the aircraft seats within corresponding aircraft seat regions. “Different sitting directions and/or lying directions” is intended to be understood as meaning in particular that sitting directions of the aircraft seat devices and/or lying directions of the aircraft seat devices are at an angle of greater than zero with respect to one another, wherein the sitting directions and/or the lying directions are oriented parallel to the aircraft cabin floor. Preferably, sitting directions of the aircraft seat devices and/or lying directions of the aircraft seat devices, in particular which differ in the at least one comfort category, are oriented anti-parallel or not parallel to one another. The aircraft seat devices of the plurality of aircraft seat devices are preferably arranged consecutively along an aircraft longitudinal axis and/or next to one another transversely with respect to an aircraft longitudinal axis. An arrangement, in particular a sequence, of the aircraft seat devices of the plurality of aircraft seat devices with respect to one another can preferably vary. As a result, an advantageously variable aircraft seat device with aircraft seat devices which can be combined in a versatile manner can thereby be provided. “Designed to be different from one another” is intended to be understood as meaning in particular that the aircraft seat devices have differently shaped, differently arranged and/or differently functioning identical components in the corresponding aircraft seat regions. In this connection, a “component of an aircraft seat device” is intended to be understood as meaning in particular an aircraft seat, a console, an ottoman, an enclosure, a separating unit, a table unit, a screen and/or an illuminating means. “Identical” is intended to be understood as meaning in particular that the aircraft seat devices each involve the same component. “Differently shaped” is intended to be understood as meaning in particular that a shape, in particular an outer contour, of the identical components of the aircraft seat devices differs, in particular as viewed perpendicularly to a plane which is oriented parallel to the aircraft cabin floor. However, it is not intended to be understood as meaning in particular any changed shape of components of the aircraft seat devices due to environmental conditions, for example a curved contour of an outer wall of the aircraft cabin. “Designed to be at least partially different from one another” is intended to be understood as meaning in particular that an individual aircraft seat device of the plurality of aircraft seat devices, which is designed to be different from at least one further aircraft seat device of the plurality of aircraft seat devices, can be repeatedly present in the aircraft seat arrangement, and therefore in particular a plurality of identically designed aircraft seat devices can be present in the aircraft seat arrangement. A “comfort category” is intended to be understood as meaning in particular a category which describes, in particular quantifies, a property for comfort of a passenger sitting and/or lying on the aircraft seat. The at least one comfort category is configured in particular to compare and/or to differentiate comfort between at least two of the plurality of aircraft seat devices. In principle, at least two aircraft seat devices, but in particular not all aircraft seat devices, have to differ in the at least one comfort category in the aircraft cabin section. In particular, the aircraft seat devices do not have to differ from one another in all values, in particular for a plurality of comfort categories. Preferably, in particular at least two, preferably at least three, and particularly preferably at least four differently designed aircraft seat devices of the plurality of aircraft seat devices in the aircraft cabin section differ in at least one comfort category, wherein the aircraft seat devices for the at least one comfort category each have a value which differs from one another and is caused by the different arrangement of the aircraft seats and by the at least partially different design of the aircraft seat devices. A “value” is intended to be understood as meaning preferably a physical variable which

quantitatively describes the comfort category. In principle, it is conceivable for different reservation classes and/or price classes to be assigned to the plurality of aircraft seat devices depending on the at least one comfort category. As a result, an advantageously selective reservation of a desired aircraft seat device can be undertaken, with a different revenue advantageously being able to be obtained. The aircraft seat preferably comprises a seat bottom and the backrest. The aircraft seat preferably comprises a leg support. A “sitting direction” is intended to be understood as meaning in particular a direction which is oriented at least substantially parallel to the aircraft cabin floor, in particular at a deviation of 3 degrees with respect to the aircraft cabin floor, and at least substantially perpendicularly to a theoretical, flat backrest oriented perpendicularly to the aircraft cabin floor, wherein the direction corresponds to a normal on a front side of the backrest, wherein the front side of the backrest forms a supporting surface for a passenger's back in a conventional sitting position. “Lying direction” is intended to be understood as meaning in particular a direction which runs at least substantially parallel to the aircraft cabin floor, in particular at a deviation of 3 degrees with respect to the aircraft cabin floor, and along a common center axis of the backrest and of the seat bottom in the lying position. The lying direction preferably corresponds to the sitting direction. In principle, the aircraft seat can comprise further add-on parts, such as in particular a headrest or at least one armrest. The aircraft seat devices preferably each have at least one console. Particularly preferably, the at least one console is usable by two aircraft seat devices arranged directly adjacent to each other. The at least one console preferably forms at least one foot space, at least one depositing surface and/or at least one storage space, wherein the at least one depositing surface and/or the at least one storage space are/is configured in particular for a directly adjacent aircraft seat device. The aircraft seat devices preferably each have at least one ottoman. In principle, the at least one ottoman can be coupled to the at least one console. The at least one ottoman is preferably configured as a leg rest and/or footrest for a passenger. The aircraft seat devices preferably each have at least one enclosure. The at least one enclosure is preferably designed as a shell element. The aircraft seat is preferably adjustable, in particular electromechanically, between a sitting position and a lying position. The aircraft seat devices preferably each comprise at least one adjustment unit which is configured for adjusting the aircraft seat between the sitting position and the lying position. A “sitting position” is intended to be understood as meaning in particular a position of the aircraft seat, in which a passenger can sit upright on the aircraft seat. The backrest of the aircraft seat and the seat bottom of the aircraft seat are preferably substantially perpendicular to each other, in particular at an angle of between 90 degrees and 110 degrees, in the sitting position. The sitting position preferably forms a first end position of the aircraft seat, in which the aircraft seat is adjustable to the maximum. The sitting position is preferably designed as a TTL position. A “TTL position” is intended to be understood as meaning in particular an upright position of the aircraft seat that has to be assumed for safety reasons, in particular in a taxiing phase, in a takeoff phase and in a landing phase of the aircraft. A “lying position” is intended to be understood as meaning in particular a position of the aircraft seat that is configured to provide an at least substantially horizontal lying surface for a passenger, in particular so that the passenger can assume a sleeping posture during a flight. In the lying position of the aircraft seat, the passenger preferably lies at least substantially on the aircraft seat, in particular on the seat bottom and on the backrest. The lying position preferably forms a second end position of the aircraft seat, in which the aircraft seat is adjustable to the maximum. “At least substantially” is intended to be understood as meaning in particular that a deviation from a specified value is in particular less than 25%, preferably less than 10% and particularly preferably less than 5% of the predefined value. In principle, between the sitting position and the lying position it is possible to provide further positions which in particular form a combined sitting and lying position. A “full-flat seat” is intended to be understood as meaning in particular a seat which can be transferred, preferably electromechanically, from the sitting position into the lying position and, in the lying position, forms an at least substantially flat lying surface. The flat lying surface is

preferably inclined at an angle of 3 degrees with respect to the aircraft cabin floor. Particularly preferably, in the lying position, at least the seat bottom of the aircraft seat and the backrest of the aircraft seat are oriented at least substantially parallel to the aircraft cabin floor on which the aircraft seat is installed. In the lying position, the seat bottom of the aircraft seat and the backrest of the aircraft seat preferably have a common supporting surface which is oriented at least substantially parallel to the aircraft cabin floor.

(7) Furthermore, it is proposed that each of the plurality of aircraft seat devices in each case has direct access to an aircraft cabin aisle. By means of this refinement, advantageously easy and convenient access to an aircraft seat can be achieved. As a result, a particularly advantageously high degree of comfort for a passenger can be achieved. Furthermore, by means of this refinement, an advantageously high degree of comfort for the passenger can be achieved since, by means of direct access to an aircraft cabin aisle, passengers from adjacent aircraft seat regions are not disturbed and/or adversely affected. "Direct access" is intended to be understood as meaning in particular access from an aircraft cabin aisle to an aircraft seat region, in particular to an aircraft seat, wherein the access to the aircraft seat region, in particular to the aircraft seat, does not run through an adjacent aircraft seat region. Particularly preferably, the passenger can enter the aircraft seat region directly from the aircraft cabin aisle, in particular without crossing a further aircraft seat region. The direct access is preferably assigned just to one aircraft seat device of the plurality of aircraft seat devices. The direct access is preferably usable just by one aircraft seat device of the plurality of aircraft seat devices.

(8) Furthermore, it is proposed that the at least one comfort category describes a living space, in particular a floor area, a bed length, a bed width, a foot space volume and/or a passage width, in at least one region. By means of this configuration, aircraft seat devices having comfort properties which are advantageously variable with respect to one another can be provided. As a result, an advantageously individual degree of comfort for different passenger needs can be achieved. A "living space" is intended to be understood as meaning in particular a space, in particular free space, which is usable personally by a passenger, in an aircraft seat region. Particularly preferably, the at least one comfort category is designed as a floor area of an aircraft seat device, as a depositing surface of an aircraft seat device, in particular a console, as a table surface of an aircraft seat device, as, in particular minimum or maximum, arm freedom for a passenger, in particular a delimiting, maximum angle of movement from the sitting direction in the sitting position, as an, in particular maximum, supporting surface of an aircraft seat for a passenger, in particular in the sitting position or in the lying position, as an, in particular maximum, bed length of an aircraft seat in the lying position, as an, in particular maximum, bed width of the aircraft seat in the lying position, as an, in particular maximum, foot space volume, as an aircraft seat orientation and/or as an, in particular minimum, passage width in at least one region of the aircraft seat device. The foot space volume is preferably delimited by a console. The console is preferably configured to span the foot space volume. An "aircraft seat orientation" is intended to be understood as meaning in particular the orientation of the sitting direction and/or of the lying direction with respect to an aircraft longitudinal axis and/or to the flight direction. The passage width is preferably designed as a minimum width of the direct access from an aircraft cabin aisle into the aircraft seat region, as measured directly adjacent to said aircraft cabin aisle and parallel to an aircraft longitudinal axis, and/or as a minimum width of the direct access in a region between the aircraft cabin aisle and a region which, as viewed in the sitting direction, is arranged directly behind the seat bottom. In principle, the at least one comfort category can also describe a quality, a noise level and/or an illumination. The quality can describe in particular a seat upholstery, for example a foam core or a spring core, or a contact material, for example material or leather. The noise can describe in particular shielding of the aircraft seat in relation to ambient noises from the aircraft cabin. The illumination can describe in particular a number of illuminating means and a property of the illuminating means.

(9) In addition, it is proposed that in one seat column in the aircraft cabin section, at least three, in particular at least four, aircraft seat devices of the plurality of aircraft seat devices are arranged, which differ in design from one another and in particular are arranged directly one behind another. By means of this refinement, an advantageously variable positioning of differently designed aircraft seat devices of the plurality of aircraft seat devices can be made possible. As a result, aircraft seat devices which advantageously differ in their comfort categories can be provided within one seat column. As a result, an advantageously individual degree of comfort for different passenger needs can be achieved. A “seat column” is intended to be understood as meaning in particular a region in the aircraft cabin, in which at least one aircraft seat device of the plurality of aircraft seat devices is arranged and which is delimited by at least one aircraft cabin aisle, wherein an axis which is arranged perpendicular to an aircraft longitudinal axis and parallel to the aircraft cabin floor intersects in particular just one aircraft seat within this region. The seat column preferably extends in the flight direction. Preferably, at least two aircraft seat devices arranged one behind another are arranged in one seat column, said aircraft seat devices all being intersected by the same aircraft longitudinal axis and each having direct access to the same aircraft cabin aisle. “One behind another” is intended to be understood as meaning in particular consecutive along an aircraft longitudinal axis. “Arranged directly one behind another” is intended to be understood as meaning in particular that in each case no further object, in particular no further aircraft seat device of the plurality of aircraft seat devices, is arranged between the at least three aircraft seat devices of the plurality of aircraft seat devices. The at least three aircraft seat devices, which are designed to differ from one another, of the plurality of aircraft seat devices are preferably arranged directly consecutively in the flight direction.

(10) Furthermore, it is proposed that in one seat column in the aircraft cabin section, a sitting direction of an aircraft seat device of the plurality of aircraft seat devices is arranged at least substantially parallel to an aircraft longitudinal axis, and a sitting direction of a further aircraft seat device of the plurality of aircraft seat devices is arranged angled with respect to the aircraft longitudinal axis, in particular at an angle of at least 18 degrees. By means of this refinement, an advantageously compact and variable arrangement of aircraft seat devices can be realized.

(11) Furthermore, it is proposed that in the aircraft cabin section, a sitting direction of at least one aircraft seat device of the plurality of aircraft seat devices is directed away from a directly adjacent aircraft cabin aisle. By means of this refinement, the at least one aircraft seat device can be positioned particularly advantageously in the aircraft seat arrangement. Furthermore, by means of this refinement, an advantageously large private sphere for a passenger can be provided. An advantageously high degree of comfort can thereby be achieved.

(12) In addition, it is proposed that in the aircraft cabin section, a sitting direction of at least one aircraft seat device of the plurality of aircraft seat devices is directed toward a directly adjacent aircraft cabin aisle. By means of this refinement, the at least one aircraft seat device can be positioned particularly advantageously in the aircraft seat arrangement. Furthermore, by means of this refinement, advantageously simple accessibility to the aircraft seat for a passenger can be ensured. An advantageously high degree of comfort can thereby be achieved.

(13) Furthermore, it is proposed that the sitting directions of at least two aircraft seat devices which are in particular spaced apart from one another by at least one further aircraft seat device are arranged in one seat column in a manner angled with respect to an aircraft longitudinal axis by at least substantially the same angle in terms of value, wherein the sitting directions of the aircraft seat devices are formed in mirror image to an aircraft longitudinal axis. By means of this refinement, an advantageously variable and compact aircraft seat arrangement can be achieved. Furthermore, a plurality of aircraft seat devices can thereby be advantageously compactly combined with one another. An advantageously large number of aircraft seats can thereby be provided in the aircraft cabin section.

(14) Furthermore, it is proposed that an aircraft seat of an aircraft seat device of the aircraft seat

devices which are arranged in one seat column in the aircraft cabin section is arranged on an aisle side, wherein an aircraft seat of a further aircraft seat device of the aircraft seat devices which are arranged in the seat column is arranged facing away from the aisle. By means of this refinement, an advantageously variable and compact aircraft seat arrangement can be achieved. Furthermore, a plurality of aircraft seat devices can thereby be advantageously compactly combined with one another. An advantageously large number of aircraft seats can thereby be provided in the aircraft cabin section. “Arranged on the aisle side” is intended to be understood as meaning in particular that, in the sitting position, at least a large part of the aircraft seat is arranged on a side of the aircraft seat device facing the aircraft cabin aisle, as viewed in the flight direction. “At least a large part” is intended to be understood as meaning in particular at least 55%, preferably at least 65% and particularly preferably at least 75%. “Arranged facing away from the aisle” is intended to be understood as meaning in particular that, in the sitting position, at least a large part of the aircraft seat is arranged on a side of the aircraft seat device facing away from the aircraft cabin aisle, as viewed in the flight direction. The aircraft seat, which is arranged on the aisle side, is preferably at a smaller minimum distance from the aircraft cabin aisle than a further aircraft seat, which is arranged facing away from the aisle.

(15) In addition, it is proposed that the aircraft seat arrangement has at least one seat grouping of at least three, in particular four, aircraft seat devices of the plurality of aircraft seat devices, which aircraft seat devices are arranged directly one behind another in one seat column in the aircraft cabin section and each have different sitting directions and/or whose aircraft seats are arranged on an aisle side or facing away from the aisle. By means of this refinement, a plurality of aircraft seat devices can advantageously be combined compactly and variably with one another. An advantageously large number of aircraft seats can thereby be provided in the aircraft cabin section. Furthermore, by means of this refinement, a repeatable sequence of the at least one seat grouping can be made possible. Furthermore, by means of this refinement, individual passenger needs can advantageously be taken into consideration, as a result of which a particularly advantageously high degree of comfort is made possible. A “seat grouping” is intended to be understood as meaning in particular an arrangement of the at least three, in particular four, aircraft seat devices arranged directly one behind another in one seat column in the aircraft cabin section. The at least one seat grouping preferably forms a sequence which is repeatable, in particular periodically. A plurality of identical seat groupings can be arranged directly one behind another, in particular along a longitudinal axis of the aircraft.

(16) Furthermore, it is proposed that the sitting directions of the aircraft seat devices which are arranged directly one behind another within the at least one seat grouping are arranged in an alternating manner at least substantially parallel to and in an angled manner with respect to the aircraft longitudinal axis. By means of this refinement, an advantageously variable and compact aircraft seat arrangement can be achieved. Furthermore, a plurality of aircraft seat devices can thereby be advantageously combined compactly with one another. An advantageously large number of aircraft seats can thereby be provided in the aircraft cabin section. Preferably, as viewed in the flight direction, in front of and behind an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft longitudinal axis, a respective aircraft seat device is arranged, the sitting direction of which is arranged at an angle to the aircraft longitudinal axis. Preferably, as viewed in the flight direction, in front of and behind an aircraft seat device, the sitting direction of which is arranged at an angle to the aircraft longitudinal axis, a respective aircraft seat device is arranged, the sitting direction of which is arranged at least substantially parallel to the aircraft longitudinal axis.

(17) Furthermore, it is proposed that in one seat column in the aircraft cabin section, two aircraft seat devices of the plurality of aircraft seat devices each have an aircraft seat which is arranged on an aisle side, and two further aircraft seat devices of the plurality of aircraft seat devices which, viewed in a flight direction, are arranged directly behind or in front of the two aircraft seat devices

each have an aircraft seat which is arranged facing away from the aisle. By means of this refinement, an advantageously variable and compact aircraft seat arrangement can be achieved. In addition, a plurality of aircraft seat devices can thereby be advantageously combined compactly with one another.

(18) In addition, it is proposed that in one seat column in the aircraft cabin section, at least three aircraft seat devices of the plurality of aircraft seat devices are arranged, wherein a sitting direction of an aircraft seat device of the at least three aircraft seat devices is arranged at least substantially parallel to an aircraft longitudinal axis, and sitting directions of two further aircraft seat devices of the at least three aircraft seat devices are arranged in an angled manner with respect to the aircraft longitudinal axis. By means of this refinement, an advantageously variable and compact aircraft seat arrangement can be achieved. Furthermore, a plurality of aircraft seat devices can thereby be advantageously combined compactly with one another. An advantageously large number of aircraft seats can thereby be provided in the aircraft cabin section. At least three of the aircraft seat devices are preferably arranged directly one behind another in one seat column in the aircraft cabin section, wherein sitting directions of two of the aircraft seat devices are arranged at least substantially parallel to an aircraft longitudinal axis, and a sitting direction of a further of the aircraft seat devices is arranged in an angled manner with respect to the aircraft longitudinal axis.

(19) Furthermore, it is proposed that aircraft seats of the aircraft seat devices, the sitting directions of which are arranged in an angled manner with respect to the aircraft longitudinal axis, have different distances from an aircraft cabin aisle. By means of this refinement, an advantageously compact and variable arrangement of aircraft seat devices can be realized. “Different distances from an aircraft cabin aisle” is intended to be understood as meaning in particular that the aircraft seats are arranged on the aisle side or facing away from the aisle. Preferably, aircraft seats of the aircraft seat devices, the sitting directions of which are arranged at least substantially parallel to the aircraft longitudinal axis, are at different distances from the aircraft cabin aisle.

(20) In addition, it is proposed that in at least one seat column in the aircraft cabin section, four aircraft seat devices of the plurality of aircraft seat devices, which differ from one another, are arranged directly one behind another, wherein sitting directions of two aircraft seat devices of the four aircraft seat devices are arranged at least substantially parallel to an aircraft longitudinal axis, wherein one aircraft seat of one aircraft seat device of the two aircraft seat devices is arranged on an aisle side and a further aircraft seat of a further aircraft seat device of the two aircraft seat devices is arranged facing away from the aisle, and sitting directions of two further aircraft seat devices of the four aircraft seat devices are arranged in an angled manner with respect to the aircraft longitudinal axis, wherein one aircraft seat of one aircraft seat device of the two further aircraft seat devices is arranged on the aisle side and a further aircraft seat of a further aircraft seat device of the two further aircraft seat devices is arranged facing away from the aisle. By means of this refinement, an advantageously compact and variable arrangement of the plurality of aircraft seat devices can be achieved. Furthermore, by means of this refinement, the plurality of aircraft seat devices can advantageously be simply combined with one another. Furthermore, by means of this refinement, the plurality of aircraft seat devices can be positioned particularly advantageously with respect to one another. As a result, an available space can advantageously be used efficiently. Furthermore, by means of this refinement, advantageously different comfort categories can be achieved for different passenger needs.

(21) Furthermore, it is proposed that in the aircraft cabin section, two aircraft seat devices of the plurality of aircraft seat devices form a pair of seats in two seat columns which are arranged directly next to each other, wherein sitting directions of the two aircraft seat devices are arranged at least substantially parallel to an aircraft longitudinal axis, and aircraft seats of the two aircraft seat devices are arranged facing away from an aisle, wherein at least two of the pairs of seats are arranged in the two seat columns which are arranged directly next to each other. By means of this refinement, an advantageously variable aircraft seat arrangement can be provided. As a result,

aircraft seat devices arranged next to one another of the plurality of aircraft seat devices can advantageously be positioned variably with respect to one another. Particularly advantageously, different regions can be created here which meet individual requirements of passengers, in particular passengers traveling by themselves or passengers traveling in pairs. A “pair of seats” is intended to be understood as meaning in particular an arrangement of precisely two aircraft seat devices which are arranged directly next to one another and in particular are not separated from one another by an aircraft cabin aisle. The two aircraft seat devices which are arranged directly next to one another are preferably formed in a mirror image with respect to one another, in particular via the aircraft cabin center axis. The two aircraft seat devices of the plurality of aircraft seat devices that form a pair of seats are preferably arranged flush with respect to one another in the flight direction, in particular as viewed in a plane parallel to the aircraft cabin floor. The two aircraft seat devices of the plurality of aircraft seat devices that form a pair of seats are preferably arranged in a central region of the aircraft cabin. A “central region” is intended to be understood as meaning in particular a region in the center of the aircraft cabin that is intersected by the aircraft cabin center axis. The central region is preferably delimited by two aircraft cabin aisles. Particularly preferably, two seat columns are arranged in the central region of the aircraft cabin.

(22) In addition, it is proposed that an arrangement of aircraft seat devices of the plurality of aircraft seat devices in the aircraft cabin section in at least one seat column on a first aircraft cabin side is formed asymmetrically to an arrangement of aircraft seat devices of the plurality of aircraft seat devices in at least one seat column on a second aircraft cabin side, wherein the first aircraft cabin side is separated from the second aircraft cabin side by an imaginary aircraft cabin center plane which is oriented along the aircraft cabin center axis perpendicular to an aircraft cabin floor. By means of this refinement, an advantageously variable aircraft seat arrangement can be provided. As a result, different regions can be created which meet individual requirements of passengers. The aircraft cabin center axis is preferably arranged in the aircraft cabin center plane. The first aircraft cabin side and the second aircraft cabin side preferably each have an aircraft cabin aisle. In principle, it is conceivable for the aircraft cabin to have, in the aircraft cabin section, at least one partition along the aircraft cabin center axis, which separates the first aircraft cabin side from the second aircraft cabin side.

(23) Furthermore, it is proposed that in at least one seat column, only such aircraft seat devices of the plurality of aircraft seat devices are arranged whose sitting directions are arranged in an angled manner with respect to the aircraft longitudinal axis. By means of this refinement, an advantageously compact aircraft seat arrangement can be achieved.

(24) Furthermore, it is proposed that in at least one seat column only such aircraft seat devices of the plurality of aircraft seat devices are arranged whose sitting directions are arranged at least substantially parallel to the aircraft longitudinal axis. By means of this refinement, an advantageously compact aircraft seat arrangement can be achieved.

(25) In addition, it is proposed that sitting directions of some of the plurality of aircraft seat devices in the aircraft cabin section are oriented at least substantially in an opposite direction to the flight direction. By means of this refinement, an advantageously variable aircraft seat arrangement can be achieved. Furthermore, by means of this refinement, viewing contact of passengers can advantageously be simplified. Preferably, at least four, in particular eight, aircraft seat devices formed differently from one another are arranged in the aircraft cabin section. It is conceivable here for each of the differently designed aircraft seat devices to be present in multiple form.

(26) The aircraft seat arrangement according to the invention is not intended to be restricted here to the above-described use and embodiment. In particular, in order to perform a function described herein, the aircraft seat arrangement according to the invention may have a number of individual elements, components and units which differs from a number mentioned herein.

Description

DRAWINGS

- (1) Further advantages emerge from the following description of the drawings. The drawings illustrate seven exemplary embodiments of the invention. The drawings, the description and the claims contain numerous features in combination. A person skilled in the art will expediently also consider the features individually and combine them to form further meaningful combinations.
- (2) In the drawings:
- (3) FIG. 1 shows a schematic illustration of an aircraft in a first exemplary embodiment,
- (4) FIG. 2 shows a schematic illustration of an aircraft seat arrangement according to the invention in the first exemplary embodiment,
- (5) FIG. 3 shows a schematic illustration of a detail from the aircraft seat arrangement according to the invention in the first exemplary embodiment,
- (6) FIG. 4 shows a schematic illustration of the aircraft seat arrangement according to the invention in the first exemplary embodiment, wherein the illustration apart from reference signs is identical to FIG. 2,
- (7) FIG. 5 shows a schematic illustration of an aircraft seat arrangement according to the invention in a second exemplary embodiment,
- (8) FIG. 6 shows a schematic illustration of an aircraft seat arrangement according to the invention in a third exemplary embodiment,
- (9) FIG. 7 shows a schematic illustration of an aircraft seat arrangement according to the invention in a fourth exemplary embodiment,
- (10) FIG. 8 shows a schematic illustration of an aircraft seat arrangement according to the invention in a fifth exemplary embodiment,
- (11) FIG. 9 shows a schematic illustration of an aircraft seat arrangement according to the invention in a sixth exemplary embodiment, and
- (12) FIG. 10 shows a schematic illustration of an aircraft seat arrangement according to the invention in a seventh exemplary embodiment.

DESCRIPTION OF THE EXEMPLARY EMBODIMENTS

- (13) FIG. 1 shows an aircraft **10a**. The aircraft **10a** has an aircraft cabin **12a**. The aircraft **10a** has an aircraft seat arrangement **14a**. FIGS. 2 to 4 show the aircraft seat arrangement **14a** in a first exemplary embodiment. The aircraft seat arrangement **14a** is configured for use in the aircraft cabin **12a**, partially illustrated, of the aircraft **10a**. The aircraft cabin **12a** is intended for all of the passengers to be in during a flight.
- (14) The aircraft cabin **12a** has an aircraft cabin center axis **16a**. The aircraft cabin center axis **16a** is designed as an aircraft longitudinal axis. The aircraft cabin center axis **16a** is in each case at the same distance from opposite aircraft cabin outer walls **18a**, **20a** of the aircraft cabin **12a**. The aircraft cabin center axis **16a** is oriented parallel to a rolling axis of the aircraft **10a**. The aircraft cabin center axis **16a** is oriented parallel to an aircraft cabin floor **22a** of the aircraft cabin **12a**. The aircraft **10a** has a flight direction **24a** in at least one operating state. In the present case, the flight direction **24a** is oriented in idealized form parallel to the aircraft cabin center axis **16a**.
- (15) The aircraft cabin **12a** has an aircraft cabin section **26a** along the aircraft cabin center axis **16a**. In addition, the aircraft cabin **12a** can have at least one further aircraft cabin section, in particular in front of or behind the aircraft cabin section **26a**, as viewed in the flight direction **24a**. In the present case, the aircraft cabin section **26a** is delimited by a plurality of separating elements **28a** and by a plurality of schematically illustrated aircraft cabin modules **30a** along the aircraft cabin center axis **16a**. In the present case, the separating elements **28a** are each designed as a partition. In the present case, the aircraft cabin modules **30a** are respectively designed as a kitchen module, as a toilet module, as a closet or as a front row monument.

(16) The aircraft seat arrangement **14a** comprises a plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** which are arranged in the aircraft cabin section **26a**. The aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** are configured to be installed on the floor **22a** of the aircraft cabin **12a**. In the present case, the aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** are each designed as a business class seat device. The plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** are formed differently from one another.

(17) The aircraft seat arrangement **14a** comprises a first aircraft seat device **100a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**. The first aircraft seat device **100a** has a sitting direction **110a**. The sitting direction **110a** of the first aircraft seat device **100a** is oriented in the flight direction **24a**. The sitting direction **110a** of the first aircraft seat device **100a** corresponds to the flight direction **24a**. The sitting direction **110a** of the first aircraft seat device **100a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**. The first aircraft seat device **100a** has a lying direction. In the present case, the lying direction of the first aircraft seat device **100a** corresponds to the sitting direction **110a** of the first aircraft seat device **100a**. In principle, it is also conceivable for a lying direction of an aircraft seat device to differ from a sitting direction of said aircraft seat device, in particular by an angle of at most 18 degrees. The lying direction of the first aircraft seat device **100a** is oriented in the flight direction **24a**. The lying direction of the first aircraft seat device **100a** corresponds to the flight direction **24a**. The lying direction of the first aircraft seat device **100a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**.

(18) The aircraft seat arrangement **14a** comprises a second aircraft seat device **200a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**. The second aircraft seat device **200a** has a sitting direction **210a**. The sitting direction **210a** of the second aircraft seat device **200a** has a directional component in the flight direction **24a**. The sitting direction **210a** of the second aircraft seat device **200a** differs from the flight direction **24a**. In the present case, the sitting direction **210a** of the second aircraft seat device **200a** is oriented in a manner angled by 30 degrees with respect to the aircraft cabin center axis **16a**. The second aircraft seat device **200a** has a lying direction. In the present case, the lying direction of the second aircraft seat device **200a** corresponds to the sitting direction **210a** of the second aircraft seat device **200a**. The lying direction of the second aircraft seat device **200a** has a directional component in the flight direction **24a**. The lying direction of the second aircraft seat device **200a** differs from the flight direction **24a**. In the present case, the lying direction of the second aircraft seat device **200a** is oriented in a manner angled by 30 degrees with respect to the aircraft cabin center axis **16a**.

(19) The aircraft seat arrangement **14a** comprises a third aircraft seat device **300a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**. The third aircraft seat device **300a** has a sitting direction **310a**. The sitting direction **310a** of the third aircraft seat device **300a** is oriented in the flight direction **24a**. The sitting direction **310a** of the third aircraft seat device **300a** corresponds to the flight direction **24a**. The sitting direction **310a** of the third aircraft seat device **300a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**. The third aircraft seat device **300a** has a lying direction. In the present case, the lying direction of the third aircraft seat device **300a** corresponds to the sitting direction **310a** of the third aircraft seat device **300a**. The lying direction of the third aircraft seat device **300a** is oriented in the flight direction **24a**. The lying direction of the third aircraft seat device **300a** corresponds to the flight direction **24a**. The lying direction of the third aircraft seat device **300a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**.

(20) The aircraft seat arrangement **14a** comprises a fourth aircraft seat device **400a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**. The fourth aircraft seat device **400a** has a sitting direction **410a**. The sitting direction **410a** of the fourth aircraft seat device **400a** has a directional component in the flight direction **24a**. The sitting direction **410a** of the

fourth aircraft seat device **400a** differs from the flight direction **24a**. In the present case, the sitting direction **410a** of the fourth aircraft seat device **400a** is oriented in a manner angled by 30 degrees with respect to the aircraft cabin center axis **16a**. The fourth aircraft seat device **400a** has a lying direction. In the present case, the lying direction of the fourth aircraft seat device **400a** corresponds to the sitting direction **410a** of the fourth aircraft seat device **400a**. The lying direction of the fourth aircraft seat device **400a** has a directional component in the flight direction **24a**. The lying direction of the fourth aircraft seat device **400a** differs from the flight direction **24a**. In the present case, the lying direction of the fourth aircraft seat device **400a** is oriented in a manner angled by 30 degrees with respect to the aircraft cabin center axis **16a**.

(21) The first aircraft seat device **100a**, the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a** are designed to be different from one another.

(22) The aircraft seat arrangement **14a** comprises a fifth aircraft seat device **500a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**. The fifth aircraft seat device **500a** is formed in a mirror image to the first aircraft seat device **100a** via an aircraft longitudinal axis, in particular via the aircraft cabin center axis **16a**. The fifth aircraft seat device **500a** has a sitting direction **510a**. The sitting direction **510a** of the fifth aircraft seat device **500a** is oriented in the flight direction **24a**. The sitting direction **510a** of the fifth aircraft seat device **500a** corresponds to the flight direction **24a**. The sitting direction **510a** of the fifth aircraft seat device **500a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**. The fifth aircraft seat device **500a** has a lying direction. In the present case, the lying direction of the fifth aircraft seat device **500a** corresponds to the sitting direction **510a** of the fifth aircraft seat device **500a**. The lying direction of the fifth aircraft seat device **500a** is oriented in the flight direction **24a**. The lying direction of the fifth aircraft seat device **500a** corresponds to the flight direction **24a**. The lying direction of the fifth aircraft seat device **500a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**.

(23) The aircraft seat arrangement **14a** comprises a sixth aircraft seat device **600a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**. The sixth aircraft seat device **600a** is formed in mirror image to the second aircraft seat device **200a** via an aircraft longitudinal axis, in particular via the aircraft cabin center axis **16a**. The sixth aircraft seat device **600a** has a sitting direction **610a**. The sitting direction **610a** of the sixth aircraft seat device **600a** has a directional component in the flight direction **24a**. The sitting direction **610a** of the sixth aircraft seat device **600a** differs from the flight direction **24a**. In the present case, the sitting direction **610a** of the sixth aircraft seat device **600a** is oriented in a manner angled by 30 degrees with respect to the aircraft cabin center axis **16a**. The sixth aircraft seat device **600a** has a lying direction. In the present case, the lying direction of the sixth aircraft seat device **600a** corresponds to the sitting direction **610a** of the sixth aircraft seat device **600a**. The lying direction of the sixth aircraft seat device **600a** has a directional component in the flight direction **24a**. The lying direction of the sixth aircraft seat device **600a** differs from the flight direction **24a**. In the present case, the lying direction of the sixth aircraft seat device **600a** is oriented in a manner angled by 30 degrees with respect to the aircraft cabin center axis **16a**.

(24) The aircraft seat arrangement **14a** comprises a seventh aircraft seat device **700a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**. The seventh aircraft seat device **700a** is formed in mirror image to the third aircraft seat device **300a** via an aircraft longitudinal axis, in particular via the aircraft cabin center axis **16a**. The seventh aircraft seat device **700a** has a sitting direction **710a**. The sitting direction **710a** of the seventh aircraft seat device **700a** is oriented in the flight direction **24a**. The sitting direction **710a** of the seventh aircraft seat device **700a** corresponds to the flight direction **24a**. The sitting direction **710a** of the seventh aircraft seat device **700a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**. The seventh aircraft seat device **700a** has a lying direction. In the present case, the lying direction of the seventh aircraft seat device **700a** corresponds to the sitting direction **710a** of the

seventh aircraft seat device **700a**. The lying direction of the seventh aircraft seat device **700a** is oriented in the flight direction **24a**. The lying direction of the seventh aircraft seat device **700a** corresponds to the flight direction **24a**. The lying direction of the seventh aircraft seat device **700a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**.

(25) The aircraft seat arrangement **14a** comprises an eighth aircraft seat device **800a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a**. The eighth aircraft seat device **800a** is formed in mirror image to the fourth aircraft seat device **400a** via an aircraft longitudinal axis, in particular via the aircraft cabin center axis **16a**. The eighth aircraft seat device **800a** has a sitting direction **810a**. The sitting direction **810a** of the eighth aircraft seat device **800a** has a directional component in the flight direction **24a**. The sitting direction **810a** of the eighth aircraft seat device **800a** differs from the flight direction **24a**. In the present case, the sitting direction **810a** of the eighth aircraft seat device **800a** is oriented in a manner angled by 30 degrees with respect to the aircraft cabin center axis **16a**. The eighth aircraft seat device **800a** has a lying direction. In the present case, the lying direction of the eighth aircraft seat device **800a** corresponds to the sitting direction **810a** of the eighth aircraft seat device **800a**. The lying direction of the eighth aircraft seat device **800a** has a directional component in the flight direction **24a**. The lying direction of the eighth aircraft seat device **800a** differs from the flight direction **24a**. In the present case, the lying direction of the eighth aircraft seat device **800a** is oriented in a manner angled by 30 degrees with respect to the aircraft cabin center axis **16a**.

(26) The fifth aircraft seat device **500a**, the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a** are designed to be different from one another.

(27) In the present case, the aircraft seat arrangement **14a** comprises eight aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** which are designed to be different and are each present at least once in the aircraft seat arrangement **14a**. The first aircraft seat device **100a**, the second aircraft seat device **200a**, the third aircraft seat device **300a**, the fourth aircraft seat device **400a**, the fifth aircraft seat device **500a**, the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a** are designed to be different from one another. In the present case, eight aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** which are designed to be different from one another are arranged in the aircraft cabin section **26a**.

(28) The aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** each have an aircraft seat. The first aircraft seat device **100a** has a first aircraft seat **120a**. The second aircraft seat device **200a** has a second aircraft seat **220a**. The third aircraft seat device **300a** has a third aircraft seat **320a**. The fourth aircraft seat device **400a** has a fourth aircraft seat **420a**. The fifth aircraft seat device **500a** has a fifth aircraft seat **520a**. The sixth aircraft seat device **600a** has a sixth aircraft seat **620a**. The seventh aircraft seat device **700a** has a seventh aircraft seat **720a**. The eighth aircraft seat device **800a** has an eighth aircraft seat **820a**. The aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** are each configured to provide a sitting place for a passenger, not illustrated, in the aircraft **10a**. The aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** each comprise a seat bottom. The aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** each comprise a backrest. The aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** each comprise a leg support, not illustrated specifically. The aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** each comprise an armrest. In FIG. 3, a seat bottom **140a**, a backrest **150a** and an armrest **160a** of the first aircraft seat **120a** are provided with a reference sign for illustrative purposes. In the present case, the aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** are substantially identical in design. In the present case, the aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** themselves differ only by an arrangement of the armrest on the aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a**. In addition, the aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** can each comprise further add-on parts, not illustrated specifically, for example a headrest or at least one further armrest. The aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** are each designed as a full-flat seat. The aircraft seats **120a,**

220a, 320a, 420a, 520a, 620a, 720a, 820a are each adjustable between a sitting position and a lying position. In FIGS. 2 and 3, the aircraft seats 120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a are each illustrated in the sitting position. The aircraft seats 120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a each comprise at least one adjustment unit, not illustrated specifically, which is configured to adjust the aircraft seat 120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a electromechanically between the sitting position and the lying position. In principle, further positions which in particular form a combined sitting and lying position can be provided between the sitting position and the lying position. The aircraft seats 120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a each form an at least substantially flat lying surface in the lying position.

(29) The aircraft seat devices 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a each have a console. The first aircraft seat device 100a has a first console 130a. The first console 130a is arranged facing away from the aisle. The second aircraft seat device 200a has a second console 230a. The second console 230a is arranged facing away from the aisle. The third aircraft seat device 300a has a third console 330a. The third console 330a is arranged on the aisle side. The fourth aircraft seat device 400a has a fourth console 430a. The fourth console 430a is arranged on the aisle side. The fifth aircraft seat device 500a has a fifth console 530a. The fifth console 530a is arranged facing away from the aisle. The sixth aircraft seat device 600a has a sixth console 630a. The sixth console 630a is arranged facing away from the aisle. The seventh aircraft seat device 700a has a seventh console 730a. The seventh console 730a is arranged on the aisle side. The eighth aircraft seat device 800a has an eighth console 830a. The eighth console 830a is arranged on the aisle side. The consoles 130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a are each usable by two aircraft seat devices 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a arranged directly adjacent to one another in an individual seat column. The consoles 130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a are each usable by two aircraft seat devices 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a arranged directly one behind another. The consoles 130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a each form a depositing surface. The depositing surface is configured for an aircraft seat 120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a which is directly adjacent to a corresponding console 130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a. In addition, the consoles 130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a can each form at least one storage space, in particular for a lifejacket module, for literature and/or for personal objects.

(30) The aircraft seat devices 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a each comprise a table unit. In the present case, the table unit is arranged on the console 130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a. The table unit comprises a pivotable and/or extendable table. In at least one operating state, the table can be at least partially positioned in a region above a seat bottom.

(31) The consoles 130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a each form a foot space, not illustrated specifically. The foot spaces are each assigned to the aircraft seat device arranged, as viewed in the sitting direction 110a, 210a, 310a, 410a, 510a, 610a, 710a, 810a of the corresponding aircraft seat device 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a, directly in front of said aircraft seat device 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a. The aircraft seat devices 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a each have an ottoman, not illustrated specifically. The ottomans are each arranged inside the consoles 130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a. The ottomans are each configured as a leg rest and/or footrest for a passenger. The ottomans are each assigned to the aircraft seat device arranged, as viewed in the sitting direction 110a, 210a, 310a, 410a, 510a, 610a, 710a, 810a of the corresponding aircraft seat device 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a, directly in front of said aircraft seat device 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a.

(32) The aircraft seat devices 100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a each have an enclosure. The enclosures are each designed as a shell element. The enclosures are each arranged in front of the corresponding aircraft seats 120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a, as viewed in the flight direction 24a. The enclosures are configured to separate aircraft seat devices

100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a arranged directly one behind another optically from one another. In the present case, the enclosures are each connected to a console **130a, 230a, 330a, 430a, 530a, 630a, 730a, 830a**. In principle, enclosures of a plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** can also be formed integrally with one another. (33) The aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** each comprise a screen. The screens are each arranged on a rear side of the enclosures. The screens are each assigned to the aircraft seat device arranged, as viewed in the sitting direction **110a, 210a, 310a, 410a, 510a, 610a, 710a, 810a** of the corresponding aircraft seat device **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a**, directly in front of said aircraft seat device **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a**.

(34) The aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** each have at least one separating unit which is configured to optically shield the aircraft seat region from an environment to meet requirements. As a result, a private sphere can advantageously be increased. The at least one separating unit has at least one adjustable separating element which, for example, is designed as a sliding door.

(35) The aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** each form an aircraft seat region. The corresponding aircraft seats **120a, 220a, 320a, 420a, 520a, 620a, 720a, 820a** of the aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** are in each case arranged in the aircraft seat regions. The aircraft seat regions are each intended for a passenger to be in during a flight. The aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** have differently shaped and/or differently arranged components in the corresponding aircraft seat regions. As a result, the first aircraft seat device **100a**, the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a** are designed differently from one another. Furthermore, the fifth aircraft seat device **500a**, the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a** are designed differently from one another as a result. In particular, an arrangement and an orientation of the aircraft seats **120a, 220a, 320a, 420a** in the respective aircraft seat regions differ in the first aircraft seat device **100a**, the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a**. Furthermore, in particular an arrangement and an orientation of the aircraft seats **520a, 620a, 720a, 820a** in the respective aircraft seat regions differ for the fifth aircraft seat device **500a**, the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a**.

(36) In the present case, the aircraft cabin **12a** has two aircraft cabin aisles **32a, 34a** in the aircraft cabin section **26a**. The aircraft cabin **12a** has a first aircraft cabin aisle **32a** and a second aircraft cabin aisle **34a**. Alternatively, it would also be conceivable for the aircraft cabin **12a** to have only one aircraft cabin aisle. The aircraft cabin aisles **32a, 34a** each extend at least substantially along an aircraft longitudinal axis, not illustrated specifically. Each of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** in each case has direct access to the first aircraft cabin aisle **32a** or to the second aircraft cabin aisle **34a**. The first aircraft seat device **100a** has direct access to the first aircraft cabin aisle **32a**. The second aircraft seat device **200a** has direct access to the first aircraft cabin aisle **32a**. The third aircraft seat device **300a** has direct access to the first aircraft cabin aisle **32a**. The fourth aircraft seat device **400a** has direct access to the first aircraft cabin aisle **32a**. The fifth aircraft seat device **500a** has direct access to the second aircraft cabin aisle **34a**. The sixth aircraft seat device **600a** has direct access to the second aircraft cabin aisle **34a**. The seventh aircraft seat device **700a** has direct access to the second aircraft cabin aisle **34a**. The eighth aircraft seat device **800a** has direct access to the second aircraft cabin aisle **34a**. The aircraft seat regions are in each case accessible from the first aircraft cabin aisle **32a** or the second aircraft cabin aisle **34a**.

(37) In the present case, the aircraft seat arrangement **14a** comprises four seat columns **36a, 38a, 40a, 42a**. Alternatively, it would also be conceivable for the aircraft seat arrangement **14a** to only

have two or three seat columns. The aircraft seat arrangement **14a** comprises a first outer seat column **36a** and a first inner seat column **38a**. The first outer seat column **36a** and the first inner seat column **38a** are spaced apart from each other by the first aircraft cabin aisle **32a**. The aircraft seat arrangement **14a** comprises a second inner seat column **40a** and a second outer seat column **42a**. The second outer seat column **42a** and the second inner seat column **40a** are spaced apart from each other by the second aircraft cabin aisle **34a**. In the present case, the first inner seat column **38a** is formed symmetrically with respect to the second inner seat column **40a** via the aircraft cabin center axis **16a**. In the present case, the first outer seat column **36a** is formed symmetrically with respect to the second outer seat column **42a** via the aircraft cabin center axis **16a**. The first inner seat column **38a** and the second inner seat column **40a** are arranged directly next to each other. The aircraft cabin **12a** has a central region **44a**. The central region **44a** is delimited by the two aircraft cabin aisles **32a**, **34a**. The first inner seat column **38a** and the second inner seat column **40a** are arranged in the central region **44a**. The first inner seat column **38a** and the second inner seat column **40a** form a double seat column. The first console **130a** and the fifth console **530a** are arranged directly next to each other in the central region **44a** and in particular are not spaced apart from each other by an aircraft seat. The first console **130a** and the fifth console **530a** are arranged directly next to each other in the central region **44a** and in particular are not spaced apart from each other by an aircraft seat. In principle, it would also be conceivable for just one seat column to be arranged in the central region **44a**. In principle, it is also conceivable for the first inner seat column **38a** to be exchangeable with the second outer seat column **42a** and/or for the second inner seat column **40a** to be exchangeable with the first outer seat column **36a**.

(38) The first aircraft seat device **100a** and the fifth aircraft seat device **500a** are arranged directly next to each other. The second aircraft seat device **200a** and the sixth aircraft seat device **600a** are arranged directly next to each other. The third aircraft seat device **300a** and the seventh aircraft seat device **700a** are arranged directly next to each other. The fourth aircraft seat device **400a** and the eighth aircraft seat device **800a** are arranged directly next to each other.

(39) In the present case, the aircraft seat arrangement **14a** comprises a plurality of further first aircraft seat devices **100'a** which are formed at least substantially identically to the first aircraft seat device **100a**. In this connection, "at least substantially identically" is intended to be understood as meaning in particular that the respective further aircraft seat devices are formed identically to the corresponding aircraft seat device arranged in the central region **44a** of the aircraft cabin **12a** apart from a possible modified shaping of an enclosure, a console and/or an aircraft seat necessitated by a contour of an aircraft cabin outer wall **18a**, **20a**. The further first aircraft seat devices **100'a** are in each case arranged in the first inner seat column **38a** or in the second outer seat column **42a**. In the present case, the aircraft seat arrangement **14a** comprises a plurality of further second aircraft seat devices **200'a** which are formed at least substantially identically to the second aircraft seat device **200a**. The further second aircraft seat devices **200'a** are in each case arranged in the first inner seat column **38a** or in the second outer seat column **42a**. In the present case, the aircraft seat arrangement **14a** comprises a plurality of further third aircraft seat devices **300'a** which are formed at least substantially identically to the third aircraft seat device **300a**. The further third aircraft seat devices **300'a** are in each case arranged in the first inner seat column **38a** or in the second outer seat column **42a**. In the present case, the aircraft seat arrangement **14a** comprises a plurality of further fourth aircraft seat devices **400'a** which are formed at least substantially identically to the fourth aircraft seat device **400a**. The further fourth aircraft seat devices **400'a** are in each case arranged in the first inner seat column **38a** or in the second outer seat column **42a**. In the present case, the aircraft seat arrangement **14a** comprises a plurality of further fifth aircraft seat devices **500'a** which are formed at least substantially identically to the fifth aircraft seat device **500a**. The further fifth aircraft seat devices **500'a** are in each case arranged in the second inner seat column **40a** or in the first outer seat column **36a**. In the present case, the aircraft seat arrangement **14a** comprises a plurality of further sixth aircraft seat devices **600'a** which are formed at least

substantially identically to the sixth aircraft seat device **600a**. The further sixth aircraft seat devices **600'a** are in each case arranged in the second inner seat column **40a** or in the first outer seat column **36a**. In the present case, the aircraft seat arrangement **14a** comprises a plurality of further seventh aircraft seat devices **700'a** which are formed at least substantially identically to the seventh aircraft seat device **700a**. The further seventh aircraft seat devices **700'a** are in each case arranged in the second inner seat column **40a** or in the first outer seat column **36a**. In the present case, the aircraft seat arrangement **14a** comprises a plurality of further eighth aircraft seat devices **800'a** which are formed at least substantially identically to the eighth aircraft seat device **800a**. The further eighth aircraft seat devices **800'a** are in each case arranged in the second inner seat column **40a** or in the first outer seat column **36a**. For reasons of clarity, only a selection of further aircraft seat devices **100'a**, **200'a**, **300'a**, **400'a**, **500'a**, **600'a**, **700'a**, **800'a** are provided with a reference sign in FIG. 2.

(40) In the aircraft cabin section **26a**, the sitting direction **110a** of the first aircraft seat device **100a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** in the first inner seat column **38a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**. The first aircraft seat **120a** of the first aircraft seat device **100a** of the aircraft seat devices **100a**, **200a**, **300a**, **400a** arranged in the first inner seat column **38a** in the aircraft cabin section **26a** is arranged on the aisle side.

(41) In the aircraft cabin section **26a**, the sitting direction **210a** of the second aircraft seat device **200a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a** in the first inner seat column **38a** is arranged in an angled manner at an angle of at least 18 degrees with respect to the aircraft cabin center axis **16a**. In the present case, in the aircraft cabin section **26a**, the sitting direction **210a** of the second aircraft seat device **200a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** in the first inner seat column **38a** is arranged in an angled manner at an angle of 30 degrees with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the sitting direction **210a** of the second aircraft seat device **200a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** in the first inner seat column **38a** is directed away from the directly adjacent first aircraft cabin aisle **32a**. The second aircraft seat **220a** of the second aircraft seat device **200a** of the aircraft seat devices **100a**, **200a**, **300a**, **400a** arranged in the first inner seat column **38a** in the aircraft cabin section **26a** is arranged on the aisle side.

(42) In the aircraft cabin section **26a**, the sitting direction **310a** of the third aircraft seat device **300a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** in the first inner seat column **38a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**. The third aircraft seat **320a** of the third aircraft seat device **300a** of the aircraft seat devices **100a**, **200a**, **300a**, **400a** arranged in the first inner seat column **38a** is arranged facing away from the aisle.

(43) In the aircraft cabin section **26a**, the sitting direction **410a** of the fourth aircraft seat device **400a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** in the first inner seat column **38a** is arranged in an angled manner at an angle of at least 18 degrees with respect to the aircraft cabin center axis **16a**. In the present case, in the aircraft cabin section **26a**, the sitting direction **410a** of the fourth aircraft seat device **400a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** in the first inner seat column **38a** is arranged in an angled manner at an angle of 30 degrees with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the sitting direction **410a** of the fourth aircraft seat device **400a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** in the first inner seat column **38a** is directed toward the directly adjacent first aircraft cabin aisle **32a**. The fourth aircraft seat **420a** of the fourth aircraft seat device **400a** of the aircraft seat devices **100a**, **200a**, **300a**, **400a** arranged in the first inner seat column **38a** is arranged facing away from the aisle.

(44) The sitting directions **210a**, **410a** of the second aircraft seat device **200a** and of the fourth aircraft seat device **400a** are arranged in the first inner seat column **38a** in an angled manner with respect to an aircraft longitudinal axis by an at least substantially identical angle in terms of value, wherein the sitting directions **210a**, **410a** of the second aircraft seat device **200a** and of the fourth aircraft seat device **400a** are formed in mirror image with respect to said aircraft longitudinal axis. The first aircraft seat device **100a** and the third aircraft seat device **300a** are spaced apart from each other by the second aircraft seat device **200a**. The second aircraft seat device **200a** and the fourth aircraft seat device **400a** are spaced apart from each other by the third aircraft seat device **300a**.

(45) In the aircraft cabin section **26a**, in the first inner seat column **38a**, the first aircraft seat device **100a** and the second aircraft seat device **200a** each have an aircraft seat **120a**, **220a** which is arranged on the aisle side, and the third aircraft seat device **300a** and the fourth aircraft seat device **400a**, which are arranged directly behind or in front of the two aircraft seat devices **100a**, **200a**, as viewed in the flight direction **24a**, each have an aircraft seat **320a**, **420a** which is arranged facing away from the aisle. The aircraft seats **120a**, **320a** of the aircraft seat devices **100a**, **300a**, the sitting directions **110a**, **310a** of which are arranged at least substantially parallel to the aircraft cabin center axis **16a**, are at different distances from the first aircraft cabin aisle **32a**. The aircraft seats **220a**, **420a** of the aircraft seat devices **200a**, **400a**, the sitting directions **210a**, **410a** of which are arranged in an angled manner with respect to the aircraft cabin center axis **16a**, are at different distances from the first aircraft cabin aisle **32a**.

(46) In the aircraft cabin section **26a**, at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the first aircraft seat device **100a**, the second aircraft seat device **200a** and the third aircraft seat device **300a**, are arranged in the first inner seat column **38a**, wherein the sitting directions **110a**, **310a** of the first aircraft seat device **100a** and of the third aircraft seat device **300a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and the sitting direction **210a** of the second aircraft seat device **200a** is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the first aircraft seat device **100a**, the second aircraft seat device **200a** and the third aircraft seat device **300a**, are arranged directly one behind another in the first inner seat column **38a**, wherein the sitting directions **110a**, **310a** of the first aircraft seat device **100a** and of the third aircraft seat device **300a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and the sitting direction **210a** of the second aircraft seat device **200a** is arranged in an angled manner with respect to the aircraft cabin center axis **16a**.

(47) In the aircraft cabin section **26a**, at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a**, are arranged in the first inner seat column **38a**, wherein the sitting direction **310a** of the third aircraft seat device **300a** is arranged at least substantially parallel to the aircraft cabin center axis **16a**, and sitting directions **210a**, **410a** of the second aircraft seat device **200a** and of the fourth aircraft seat device **400a** are arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a**, are arranged directly one behind another in the first inner seat column **38a**, wherein the sitting direction **310a** of the third aircraft seat device **300a** is arranged at least substantially parallel to the aircraft cabin center axis **16a**, and sitting directions **210a**, **410a** of the second aircraft seat device **200a** and of the fourth aircraft seat device **400a** are arranged in an angled manner with respect to the aircraft cabin center axis **16a**.

(48) In the aircraft cabin section **26a**, at least three aircraft seat devices of the plurality of aircraft

seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least one of the further fourth aircraft seat devices **400'a**, the first aircraft seat device **100a** and the second aircraft seat device **200a**, are arranged in the first inner seat column **38a**, wherein the sitting direction **110a** of the first aircraft seat device **100a** is arranged at least substantially parallel to the aircraft cabin center axis **16a**, and sitting directions of the second aircraft seat device **200a** and of the further fourth aircraft seat device **400'a** are arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least one of the further fourth aircraft seat devices **400'a**, the first aircraft seat device **100a** and the second aircraft seat device **200a**, are arranged directly one behind another in the first inner seat column **38a**, wherein the sitting direction **110a** of the first aircraft seat device **100a** is arranged at least substantially parallel to the aircraft cabin center axis **16a**, and sitting directions of the second aircraft seat device **200a** and of the further fourth aircraft seat device **400'a** are arranged in an angled manner with respect to the aircraft cabin center axis **16a**.

(49) In the aircraft cabin section **26a**, at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the first aircraft seat device **100a**, one of the further fourth aircraft seat devices **400'a** and one of the further third aircraft seat devices **300'a**, are arranged in the first inner seat column **38a**, wherein sitting directions of the first aircraft seat device **100a** and of the further third aircraft seat device **300'a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and a sitting direction of the further fourth aircraft seat device **400'a** is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the first aircraft seat device **100a**, one of the further fourth aircraft seat devices **400'a** and one of the further third aircraft seat devices **300'a**, are arranged directly one behind another in the first inner seat column **38a**, wherein sitting directions of the first aircraft seat device **100a** and of the further third aircraft seat device **300'a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and a sitting direction of the further fourth aircraft seat device **400'a** is arranged in an angled manner with respect to the aircraft cabin center axis **16a**.

(50) In the aircraft cabin section **26a**, four aircraft seat devices **100a**, **200a**, **300a**, **400a**, which are designed to differ from one another and are arranged directly behind one another, of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** are arranged in the first inner seat column **38a**. The four aircraft seat devices **100a**, **200a**, **300a**, **400a**, which are designed to be different from one another and are arranged in the first inner seat column **38a**, of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** are arranged directly consecutively in the flight direction **24a**.

(51) In the aircraft cabin section **26a**, the first aircraft seat device **100a**, the second aircraft seat device **200a** and the third aircraft seat device **300a** are arranged directly one behind another in the first inner seat column **38a**. In the aircraft cabin section **26a**, the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a** are arranged directly one behind another in the first inner seat column **38a**. In the first inner seat column **38a** in the aircraft cabin section **26a**, the first aircraft seat device **100a** is arranged directly behind the second aircraft seat device **200a**, as viewed in the flight direction **24a**. In the first inner seat column **38a** in the aircraft cabin section **26a**, the second aircraft seat device **200a** is arranged directly behind the third aircraft seat device **300a**, as viewed in the flight direction **24a**. In the first inner seat column **38a** in the aircraft cabin section **26a**, the third aircraft seat device **300a** is arranged directly behind the fourth aircraft seat device **400a**, as viewed in the flight direction **24a**. In principle, the fourth aircraft seat device **400a** can be arranged directly behind the first aircraft seat device **100a**, as viewed in the flight direction **24a**, in the first inner seat column **38a** in the aircraft cabin section **26a**.

(52) In the aircraft cabin section **26a**, four aircraft seat devices which are designed to be different from one another, namely the first aircraft seat device **100a**, the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a**, of the plurality of aircraft seat devices **100a, 100'a, 200a, 200'a, 300a, 300'a, 400a, 400'a, 500a, 500'a, 600a, 600'a, 700a, 700'a, 800a, 800'a** are arranged directly behind one another in the first inner seat column **38a**, wherein sitting directions **110a, 310a** of two aircraft seat devices of the four aircraft seat devices **100a, 200a, 300a, 400a**, namely of the first aircraft seat device **100a** and of the third aircraft seat device **300a**, are arranged at least substantially parallel to the aircraft cabin center axis **16a**, wherein the first aircraft seat **120a** of the first aircraft seat device **100a** is arranged on the aisle side and the third aircraft seat **320a** of the third aircraft seat device **300a** is arranged facing away from the aisle, and sitting directions **210a, 410a** of two further aircraft seat devices of the four aircraft seat devices **100a, 200a, 300a, 400a**, namely of the second aircraft seat device **200a** and of the fourth aircraft seat device **400a**, are arranged in an angled manner with respect to the aircraft cabin center axis **16a**, wherein the second aircraft seat **220a** of the second aircraft seat device **200a** is arranged on the aisle side and the fourth aircraft seat **420a** of the fourth aircraft seat device **400a** is arranged facing away from the aisle.

(53) In the aircraft cabin section **26a**, the sitting direction **510a** of the fifth aircraft seat device **500a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** in the second inner seat column **40a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**. The fifth aircraft seat **520a** of the fifth aircraft seat device **500a** of the aircraft seat devices **500a, 600a, 700a, 800a** which are arranged in the second inner seat column **40a** in the aircraft cabin section **26a** is arranged on the aisle side.

(54) In the aircraft cabin section **26a**, the sitting direction **610a** of the sixth aircraft seat device **600a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** is arranged in the second inner seat column **40a** in a manner angled at an angle of at least 18 degrees with respect to the aircraft cabin center axis **16a**. In the present case, in the second inner seat column **40a** in the aircraft cabin section **26a**, the sitting direction **610a** of the sixth aircraft seat device **600a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** is arranged in an angled manner at an angle of 30 degrees with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the sitting direction **610a** of the sixth aircraft seat device **600a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** in the second inner seat column **40a** is directed away from the directly adjacent second aircraft cabin aisle **34a**. The sixth aircraft seat **620a** of the sixth aircraft seat device **600a** of the aircraft seat devices **500a, 600a, 700a, 800a** which are arranged in the second inner seat column **40a** in the aircraft cabin section **26a** is arranged on the aisle side.

(55) In the aircraft cabin section **26a**, the sitting direction **710a** of the seventh aircraft seat device **700a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** in the second inner seat column **40a** is oriented at least substantially parallel to the aircraft cabin center axis **16a**. The seventh aircraft seat **720a** of the seventh aircraft seat device **700a** of the aircraft seat devices **500a, 600a, 700a, 800a** which are arranged in the second inner seat column **40a** is arranged facing away from the aisle.

(56) In the aircraft cabin section **26a**, the sitting direction **810a** of the eighth aircraft seat device **800a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** in the second inner seat column **40a** is arranged in an angled manner at an angle of at least 18 degrees with respect to the aircraft cabin center axis **16a**. In the present case, in the second inner seat column **40a** in the aircraft cabin section **26a**, the sitting direction **810a** of the eighth aircraft seat device **800a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a** is arranged in an angled manner at an angle of 30 degrees with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the sitting direction **810a** of the eighth aircraft seat device **800a** of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a,**

800a in the second inner seat column **40a** is directed toward the directly adjacent second aircraft cabin aisle **34a**. The eighth aircraft seat **820a** of the eighth aircraft seat device **800a** of the aircraft seat devices **500a**, **600a**, **700a**, **800a** which are arranged in the second inner seat column **40a** is arranged facing away from the aisle.

(57) The sitting directions **610a**, **810a** of the sixth aircraft seat device **600a** and of the eighth aircraft seat device **800a** are arranged in the second inner seat column **40a** in an angled manner with respect to an aircraft longitudinal axis by an at least substantially identical angle in terms of value, wherein the sitting directions **610a**, **810a** of the sixth aircraft seat device **600a** and of the eighth aircraft seat device **800a** are formed in mirror image with respect to said aircraft longitudinal axis. The fifth aircraft seat device **500a** and the seventh aircraft seat device **700a** are spaced apart from each other by the sixth aircraft seat device **600a**. The sixth aircraft seat device **600a** and the eighth aircraft seat device **800a** are spaced apart from each other by the seventh aircraft seat device **700a**.

(58) In the aircraft cabin section **26a**, in the second inner seat column **40a**, the fifth aircraft seat device **500a** and the sixth aircraft seat device **600a** each have an aircraft seat **520a**, **620a** which is arranged on the aisle side, and the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a**, which are arranged directly behind or in front of the two aircraft seat devices **500a**, **600a**, as viewed in the flight direction **24a**, each have an aircraft seat **720a**, **820a** which is arranged facing away from the aisle. The aircraft seats **520a**, **720a** of the aircraft seat devices **500a**, **700a**, the sitting directions **510a**, **710a** of which are arranged at least substantially parallel to the aircraft cabin center axis **16a**, are at different distances from the second aircraft cabin aisle **34a**. The aircraft seats **620a**, **820a** of the aircraft seat devices **600a**, **800a**, the sitting directions **610a**, **810a** of which are arranged in an angled manner with respect to the aircraft cabin center axis **16a**, are at different distances from the second aircraft cabin aisle **34a**.

(59) In the aircraft cabin section **26a**, at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the fifth aircraft seat device **500a**, the sixth aircraft seat device **600a** and the seventh aircraft seat device **700a**, are arranged in the second inner seat column **40a**, wherein the sitting directions **510a**, **710a** of the fifth aircraft seat device **500a** and of the seventh aircraft seat device **700a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and the sitting direction **610a** of the sixth aircraft seat device **600a** is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the fifth aircraft seat device **500a**, the sixth aircraft seat device **600a** and the seventh aircraft seat device **700a**, are arranged directly one behind another in the second inner seat column **40a**, wherein the sitting directions **510a**, **710a** of the fifth aircraft seat device **500a** and of the seventh aircraft seat device **700a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and the sitting direction **610a** of the sixth aircraft seat device **600a** is arranged in an angled manner with respect to the aircraft cabin center axis **16a**.

(60) In the aircraft cabin section **26a**, at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a**, are arranged in the second inner seat column **40a**, wherein the sitting direction **710a** of the seventh aircraft seat device **700a** is arranged at least substantially parallel to the aircraft cabin center axis **16a**, and sitting directions **610a**, **810a** of the sixth aircraft seat device **600a** and of the eighth aircraft seat device **800a** are arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a**, are arranged directly one behind another in the second inner seat column **40a**, wherein the

sitting direction **710a** of the seventh aircraft seat device **700a** is arranged at least substantially parallel to the aircraft cabin center axis **16a**, and sitting directions **610a**, **810a** of the sixth aircraft seat device **600a** and of the eighth aircraft seat device **800a** are arranged in an angled manner with respect to the aircraft cabin center axis **16a**.

(61) In the aircraft cabin section **26a**, at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least one of the further eighth aircraft seat devices **800'a**, the fifth aircraft seat device **500a** and the sixth aircraft seat device **600a**, are arranged in the second inner seat column **40a**, wherein the sitting direction **510a** of the fifth aircraft seat device **500a** is arranged at least substantially parallel to the aircraft cabin center axis **16a**, and sitting directions of the sixth aircraft seat device **600a** and of the further eighth aircraft seat device **800'a** are arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least one of the further eighth aircraft seat devices **800'a**, the fifth aircraft seat device **500a** and the sixth aircraft seat device **600a**, are arranged directly one behind another in the second inner seat column **40a**, wherein the sitting direction **510a** of the fifth aircraft seat device **500a** is arranged at least substantially parallel to the aircraft cabin center axis **16a**, and sitting directions of the sixth aircraft seat device **600a** and of the further eighth aircraft seat device **800'a** are arranged in an angled manner with respect to the aircraft cabin center axis **16a**.

(62) In the aircraft cabin section **26a**, at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the fifth aircraft seat device **500a**, one of the further eighth aircraft seat devices **800'a** and one of the further seventh aircraft seat devices **700'a**, are arranged in the second inner seat column **40a**, wherein sitting directions of the fifth aircraft seat device **500a** and of the further seventh aircraft seat device **700'a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and a sitting direction of the further eighth aircraft seat device **800'a** is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In the aircraft cabin section **26a**, the at least three aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely at least the fifth aircraft seat device **500a**, one of the further eighth aircraft seat devices **800'a** and one of the further seventh aircraft seat devices **700'a**, are arranged directly one behind another in the second inner seat column **40a**, wherein sitting directions of the fifth aircraft seat device **500a** and of the further seventh aircraft seat device **700'a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and a sitting direction of the further eighth aircraft seat device **800'a** is arranged in an angled manner with respect to the aircraft cabin center axis **16a**.

(63) In the aircraft cabin section **26a**, four aircraft seat devices **500a**, **600a**, **700a**, **800a**, which are designed to be different from one another and are arranged directly one behind another, of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** are arranged in the second inner seat column **40a**. The four aircraft seat devices **500a**, **600a**, **700a**, **800a**, which are designed to be different from one another and are arranged in the second inner seat column **40a**, of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** are arranged directly consecutively in the flight direction **24a**.

(64) In the aircraft cabin section **26a**, the fifth aircraft seat device **500a**, the sixth aircraft seat device **600a** and the seventh aircraft seat device **700a** are arranged directly one behind another in the second inner seat column **40a**. In the aircraft cabin section **26a**, the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a** are arranged directly one behind another in the second inner seat column **40a**. In the second inner seat column **40a** in the aircraft cabin section **26a**, the fifth aircraft seat device **500a** is arranged directly behind the sixth aircraft seat device **600a**, as viewed in the flight direction **24a**. In the second inner seat column **40a** in the aircraft cabin section **26a**, the sixth aircraft seat device **600a** is arranged directly

behind the seventh aircraft seat device **700a**, as viewed in the flight direction **24a**. In the second inner seat column **40a** in the aircraft cabin section **26a**, the seventh aircraft seat device **700a** is arranged directly behind the eighth aircraft seat device **800a**, as viewed in the flight direction **24a**. In principle, the eighth aircraft seat device **800a** can be arranged directly behind the fifth aircraft seat device **500a**, as viewed in the flight direction **24a**, in the second inner seat column **40a** in the aircraft cabin section **26a**.

(65) In the aircraft cabin section **26a**, four aircraft seat devices which are designed to be different from one another, namely the fifth aircraft seat device **500a**, the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a**, of the plurality of aircraft seat devices **100a**, **100'a**, **200a**, **200'a**, **300a**, **300'a**, **400a**, **400'a**, **500a**, **500'a**, **600a**, **600'a**, **700a**, **700'a**, **800a**, **800'a** are arranged directly one behind another in the second inner seat column **40a**, wherein sitting directions **510a**, **710a** of two aircraft seat devices of the four aircraft seat devices **500a**, **600a**, **700a**, **800a**, namely of the fifth aircraft seat device **500a** and of the seventh aircraft seat device **700a**, are arranged at least substantially parallel to the aircraft cabin center axis **16a**, wherein the fifth aircraft seat **520a** of the fifth aircraft seat device **500a** is arranged on the aisle side, and the seventh aircraft seat **720a** of the seventh aircraft seat device **700a** is arranged facing away from the aisle, and sitting directions **610a**, **810a** of two further aircraft seat devices of the four aircraft seat devices **500a**, **600a**, **700a**, **800a**, namely of the sixth aircraft seat device **600a** and of the eighth aircraft seat device **800a**, are arranged in an angled manner with respect to the aircraft cabin center axis **16a**, wherein the sixth aircraft seat **620a** of the sixth aircraft seat device **600a** is arranged on the aisle side, and the eighth aircraft seat **820a** of the eighth aircraft seat device **800a** is arranged facing away from the aisle.

(66) In the aircraft cabin section **26a**, four aircraft seat devices **500'a**, **600'a**, **700'a**, **800'a**, which are designed to be different from one another and are arranged directly one behind another, of the plurality of further aircraft seat devices **100'a**, **200'a**, **300'a**, **400'a**, **500'a**, **600'a**, **700'a**, **800'a** are arranged in the first outer seat column **36a**. The four aircraft seat devices **500'a**, **600'a**, **700'a**, **800'a**, which are designed to be different from one another and are arranged in the first outer seat column **36a**, of the plurality of further aircraft seat devices **100'a**, **200'a**, **300'a**, **400'a**, **500'a**, **600'a**, **700'a**, **800'a** are arranged directly consecutively in the flight direction **24a**.

(67) In the aircraft cabin section **26a**, four aircraft seat devices **100'a**, **200'a**, **300'a**, **400'a**, which are designed to be different from one another and are arranged directly one behind another, of the plurality of further aircraft seat devices **100'a**, **200'a**, **300'a**, **400'a**, **500'a**, **600'a**, **700'a**, **800'a** are arranged in the second outer seat column **42a**. The four aircraft seat devices **100'a**, **200'a**, **300'a**, **400'a**, which are designed to be different from one another and are arranged in the second outer seat column **42a**, of the plurality of aircraft seat devices **100'a**, **200'a**, **300'a**, **400'a**, **500'a**, **600'a**, **700'a**, **800'a** are arranged directly consecutively in the flight direction **24a**.

(68) In principle, the previous descriptions of the first inner seat column **38a** are also applicable to the second outer seat column **42a**. In principle, the previous descriptions of the second inner seat column **40a** are also applicable to the first outer seat column **36a**.

(69) In the aircraft cabin section **26a**, two aircraft seat devices of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a**, namely the third aircraft seat device **300a** and the seventh aircraft seat device **700a**, form a pair of seats **46a** in two seat columns arranged directly next to each other, namely the first inner seat column **38a** and the second inner seat column **40a**, wherein sitting directions **310a**, **710a** of the two aircraft seat devices **300a**, **700a** are arranged at least substantially parallel to the aircraft cabin center axis **16a**, and the aircraft seats **320a**, **720a** of the two aircraft seat devices **300a**, **700a** are arranged facing away from the aisle, wherein at least two of the pairs of seats **46a** are arranged in the two seat columns **38a**, **40a** which are arranged directly adjacent to each other (FIG. 4). As a result, regions for passengers traveling in pairs can advantageously be created in the aircraft cabin section **26a**. The two aircraft seat devices arranged directly next to each other, namely the third aircraft seat device **300a** and the seventh aircraft seat

device **700a**, are formed in mirror image with respect to each other via the aircraft cabin center axis **16a**. The two aircraft seat devices **300a**, **700a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** that form the pair of seats **46a** are arranged flush with respect to each other in the flight direction **24a**, as viewed in a plane parallel to the aircraft cabin floor **22a**. The two aircraft seat devices **300a**, **700a** of the plurality of aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** that form the pair of seats **46a** are arranged in the central region **44a** of the aircraft cabin **12a**. In principle, it is conceivable for the third aircraft seat device **300a** and the seventh aircraft seat device **700a** that form the pair of seats **46a** to have a common mattress, in particular in the lying position of the third aircraft seat **320a** and of the seventh aircraft seat **720a**. (70) In the first inner seat column **38a**, the second aircraft seat **220a** has a second axis **48a** which is oriented parallel to the aircraft cabin floor **22a**, and which intersects a seat bottom of the second aircraft seat **220a** of the second aircraft seat device **200a** and which is oriented parallel to the sitting direction **210a** of the second aircraft seat device **200a**, wherein the second axis **48a** intersects a seat bottom of a further eighth aircraft seat of one of the further eighth aircraft seat devices **800'a** in the second inner seat column **40a**, wherein the further eighth aircraft seat has a further eighth axis **50a** which is oriented parallel to a sitting direction of said further eighth aircraft seat device **800'a** and parallel to the second axis **48a** (FIG. 4).

(71) The aircraft seat arrangement **14a** has a first seat grouping **52a** of four aircraft seat devices arranged directly one behind another in the first inner seat column **38a** in the aircraft cabin section **26a**, namely the first aircraft seat device **100a**, the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a**, which each have different sitting directions **110a**, **210a**, **310a**, **410a** and the aircraft seats **120a**, **220a**, **320a**, **420a** of which are arranged on the aisle side or facing away from the aisle (FIGS. 3 and 4). The sitting directions **110a**, **210a**, **310a**, **410a** of the aircraft seat devices **100a**, **200a**, **300a**, **400a** which are arranged directly one behind another are arranged within the first seat grouping **52a** in an alternating manner at least substantially parallel to and in an angled manner with respect to the aircraft cabin center axis **16a**. The first seat grouping **52a** forms a periodically repetitive sequence. A plurality of identical first seat groupings **52a** can be arranged directly one behind another here along an aircraft longitudinal axis.

(72) As viewed in the flight direction **24a**, in front of and behind the first aircraft seat device **100a**, the sitting direction **110a** of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. As viewed in the flight direction **24a**, in front of and behind the second aircraft seat device **200a**, the sitting direction **210a** of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**. As viewed in the flight direction **24a**, in front of and behind the third aircraft seat device **300a**, the sitting direction **310a** of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. As viewed in the flight direction **24a**, behind the fourth aircraft seat device **400a**, the sitting direction **410a** of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**. In principle, as viewed in the flight direction **24a**, in front of and behind the fourth aircraft seat device **400a**, the sitting direction **410a** of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**, there can in each case be arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**.

(73) The aircraft seat arrangement **14a** has a second seat grouping **54a** of four aircraft seat devices

arranged directly one behind another in the second inner seat column **40a** in the aircraft cabin section **26a**, namely the fifth aircraft seat device **500a**, the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a**, which each have different sitting directions **510a**, **610a**, **710a**, **810a** and the aircraft seats **520a**, **620a**, **720a**, **820a** of which are arranged on the aisle side or facing away from the aisle (FIG. 4). The sitting directions **510a**, **610a**, **710a**, **810a** of the aircraft seat devices **500a**, **600a**, **700a**, **800a**, arranged directly one behind another, are arranged within the second seat grouping **54a** in an alternating manner at least substantially parallel to and in an angled manner with respect to the aircraft cabin center axis **16a**. The second seat grouping **54a** forms a periodically repeatable sequence. A plurality of identical second seat groupings **54a** can be arranged here directly one behind another along the aircraft cabin center axis **16a**.

(74) As viewed in the flight direction **24a**, in front of and behind the fifth aircraft seat device **500a**, the sitting direction **510a** of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. As viewed in the flight direction **24a**, in front of and behind the sixth aircraft seat device **600a**, the sitting direction **610a** of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**. As viewed in the flight direction **24a**, in front of and behind the seventh aircraft seat device **700a**, the sitting direction **710a** of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. As viewed in the flight direction **24a**, behind the eighth aircraft seat device **800a**, the sitting direction **810a** of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**. In principle, as viewed in the flight direction **24a**, in front of and behind the eighth aircraft seat device **800a**, the sitting direction **810a** of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**, there can in each case be arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16a**.

(75) The first aircraft seat device **100a**, the second aircraft seat device **200a**, the third aircraft seat device **300a** and the fourth aircraft seat device **400a** in the aircraft cabin section **26a** differ in at least one comfort category, wherein the aircraft seat devices **100a**, **200a**, **300a**, **400a** have, for the at least one comfort category, in each case a mutually different value which is caused by a different arrangement of the aircraft seats **120a**, **220a**, **320a**, **420a** and by the at least partially different design of the aircraft seat devices **100a**, **200a**, **300a**, **400a**. The fifth aircraft seat device **500a**, the sixth aircraft seat device **600a**, the seventh aircraft seat device **700a** and the eighth aircraft seat device **800a** in the aircraft cabin section **26a** differ in at least one comfort category, wherein the aircraft seat devices **500a**, **600a**, **700a**, **800a** for the at least one comfort category each have a mutually different value which is caused by a different arrangement of the aircraft seats **520a**, **620a**, **720a**, **820a** and by the at least partially different design of the aircraft seat devices **500a**, **600a**, **700a**, **800a**.

(76) In principle, at least two aircraft seat devices of the first aircraft seat device **100a**, of the second aircraft seat device **200a**, of the third aircraft seat device **300a**, of the fourth aircraft seat device **400a**, of the fifth aircraft seat device **500a**, of the sixth aircraft seat device **600a**, of the seventh aircraft seat device **700a** and of the eighth aircraft seat device **800a**, but in particular not all of the aircraft seat devices, in the aircraft cabin section **26a** have to differ in at least one comfort category. In principle, the aircraft seat devices **100a**, **200a**, **300a**, **400a**, **500a**, **600a**, **700a**, **800a** do not have to differ from one another in all of the values, in particular for a plurality of comfort

categories.

(77) The at least one comfort category describes a living space.

(78) In the present case, a first comfort category is in the form of a maximum bed length of an aircraft seat in the lying position. The greater a value is for the maximum bed length, the higher is the comfort for a passenger. The value for the maximum bed length is in the form of one length. The second aircraft seat device **200a** has, for a maximum bed length of the second aircraft seat **220a**, a value which is greater than a value of the first aircraft seat device **100a** for a maximum bed length of the first aircraft seat **120a**. In the present case, the value of the second aircraft seat device **200a** for the maximum bed length of the second aircraft seat **220a** is 5% larger than the value of the first aircraft seat device **100a** for the maximum bed length of the first aircraft seat **120a**. The first aircraft seat device **100a** and the second aircraft seat device **200a** differ in their maximum bed lengths. The fourth aircraft seat device **400a** has, for a maximum bed length of the fourth aircraft seat **420a**, a value which is greater than a value of the third aircraft seat device **300a** for a maximum bed length of the third aircraft seat **320a**. In the present case, the value of the fourth aircraft seat device **400a** for the maximum bed length of the fourth aircraft seat **420a** is 5% greater than the value of the third aircraft seat device **300a** for the maximum bed length of the third aircraft seat **320a**. The third aircraft seat device **300a** and the fourth aircraft seat device **400a** differ in their maximum bed lengths.

(79) In the present case, a second comfort category is in the form of a minimum passage width in at least one region of an aircraft seat region. The passage width is in the form of a minimum width of the direct access in a region between the first aircraft cabin aisle **32a** or the second aircraft cabin aisle **34a** and a region which, as viewed in the sitting direction of the corresponding aircraft seat device, is arranged directly behind a seat bottom of an aircraft seat of said aircraft seat device. The greater a value is for the minimum passage width, the higher is the comfort for a passenger. The value for the minimum passage width in at least one region of an aircraft seat region is in the form of one length. The first aircraft seat device **100a** has, for a minimum passage width in at least one region of an aircraft seat region of the first aircraft seat device **100a**, a value which is greater than a value for a minimum passage width in at least one region of an aircraft seat region of the second aircraft seat device **200a**. The third aircraft seat device **300a** has, for a minimum passage width in at least one region of an aircraft seat region of the third aircraft seat device **300a**, a value which is greater than the value for the minimum passage width in the at least one region of the aircraft seat region of the first aircraft seat device **100a**. The fourth aircraft seat device **400a** has, for a minimum passage width in at least one region of an aircraft seat region of the fourth aircraft seat device **400a**, a value which is greater than the value for the minimum passage width in the at least one region of the aircraft seat region of the third aircraft seat device **300a**.

(80) In principle, at least one further comfort category can be in the form of a basic area of an aircraft seat device, in the form of a depositing surface of an aircraft seat device, in particular a console, in the form of a table surface of an aircraft seat device, in the form of, in particular minimum or maximum, arm freedom for a passenger, in particular a limiting maximum angle of movement starting from the sitting direction in the sitting position, in the form of an, in particular maximum, supporting surface of an aircraft seat for a passenger, in particular in the sitting position or in the lying position, in the form of an, in particular maximum, bed width of the aircraft seat in the lying position, and/or in the form of an, in particular maximum, foot space volume.

(81) In principle, the at least one comfort category can also describe a quality, a noise and/or an illumination. The quality can describe in particular a seat upholstery, for example a foam core or a spring core, or a contact material, for example fabric or leather. The noise can describe in particular shielding of the aircraft seat from ambient noises from the aircraft cabin. The illumination can describe in particular a number of illuminating means and a property of the illuminating means.

(82) In the first inner seat column **38a**, one of the further second aircraft seat devices **200'a** is arranged in a first seat row of the aircraft cabin section **26a**, as viewed counter to the flight

direction **24a** (FIG. 4). As viewed in the flight direction **24a**, one of the plurality of aircraft cabin modules **30a** is arranged in the central region **44a** directly behind the further second aircraft seat device **200'a** arranged in the first seat row of the aircraft cabin section **26a**. As a result, a higher degree of comfort can be achieved in the first seat row compared with the second aircraft seat device **200a** since more space is available in the first seat row. The further second aircraft seat device **200'a** arranged in the first seat row in the aircraft cabin section **26a** can in principle differ in at least one comfort category from at least one aircraft seat device of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a**. In the present case, the aircraft cabin module **30a** arranged in the central region **44a** can be designed as a front row monument. In principle, the aircraft cabin module **30a** can also be part of the further second aircraft seat device **200'a**.

(83) In the second inner seat column **40a**, one of the further sixth aircraft seat devices **600'a** is arranged in the first seat row of the aircraft cabin section **26a**, as viewed counter to the flight direction **24a** (FIG. 4). As viewed in the flight direction **24a**, the previously mentioned aircraft cabin module **30a** is arranged in the central region **44a** directly behind the further sixth aircraft seat device **600'a** arranged in the first seat row of the aircraft cabin section **26a**. The further sixth aircraft seat device **600'a** arranged in the first seat row in the aircraft cabin section **26a** can in principle differ in at least one comfort category from at least one aircraft seat device of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a**. In principle, the aircraft cabin module **30a** can also be part of the further sixth aircraft seat device **600'a**.

(84) In the first outer seat column **36a**, one of the further fifth aircraft seat devices **500'a** is arranged in the first seat row of the aircraft cabin section **26a**, as viewed counter to the flight direction **24a** (FIG. 4). As viewed in the flight direction **24a**, a further of the aircraft cabin modules **30a** is arranged directly behind the further fifth aircraft seat device **500'a**, arranged in the first seat row of the aircraft cabin section **26a**, in the first outer seat column **36a**. The further fifth aircraft seat device **500'a** arranged in the first seat row in the first seat column **36a** in the aircraft cabin section **26a** can in principle differ in at least one comfort category from at least one aircraft seat device of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a**. In principle, the further aircraft cabin module **30a** can also be part of the further sixth aircraft seat device **600'a**.

(85) In the second outer seat column **42a**, one of the further first aircraft seat devices **100'a** is arranged in the first seat row of the aircraft cabin section **26a**, as viewed counter to the flight direction **24a** (FIG. 4). As viewed in the flight direction **24a**, another of the aircraft cabin modules **30a** is arranged directly behind the further first aircraft seat device **100'a**, arranged in the first seat row of the aircraft cabin section **26a**, in the second outer seat column **42a**. The further first aircraft seat device **100'a** arranged in the first seat row in the second outer seat column **42a** in the aircraft cabin section **26a** can in principle differ in at least one comfort category from at least one aircraft seat device of the plurality of aircraft seat devices **100a, 200a, 300a, 400a, 500a, 600a, 700a, 800a**. In principle, the other aircraft cabin module **30a** can also be part of the further first aircraft seat device **100'a**.

(86) In principle, the aircraft seat arrangement **14a** which is illustrated in FIGS. 2 and 3 is not restricted to the number of aircraft seat devices shown. The aircraft seat arrangement **14a** can have fewer or more than the aircraft seat devices **100a, 100'a, 200a, 200'a, 300a, 300'a, 400a, 400'a, 500a, 500'a, 600a, 600'a, 700a, 700'a, 800a, 800'a** illustrated. In principle, it would also be conceivable for the aircraft seat arrangement **14a** shown in FIGS. 2 to 4 overall or partially, in particular at least one of the seat columns **36a, 38a, 40a, 42a**, to be arranged in the aircraft cabin **12a** in mirror form about an axis, wherein the axis is oriented perpendicularly to the aircraft cabin center axis **16a** and parallel to the aircraft cabin floor **22a**.

(87) FIGS. 5 to 10 show six further exemplary embodiments of the invention. The following descriptions and the drawings are restricted substantially to the differences between the exemplary

embodiments, wherein, with regard to components with identical designation, in particular with regard to components with the same reference signs, reference may basically also be made to the drawings and/or to the description of the other exemplary embodiments, in particular of FIGS. **1** to **4**. To distinguish between the exemplary embodiments, the alphabetic character **a** has been added as a suffix to the reference signs of the exemplary embodiment in FIGS. **1** to **4**. In the exemplary embodiments of FIGS. **5** to **10**, the alphabetic character **a** has been replaced by the alphabetic characters **b** to **g**.

(88) FIG. **5** shows an aircraft seat arrangement **14b** in a second exemplary embodiment. The aircraft seat arrangement **14b** is configured for use in an aircraft cabin **12b**, partially illustrated, of an aircraft. The aircraft cabin **12b** has an aircraft cabin center axis **16b**. The aircraft cabin center axis **16b** is in the form of an aircraft longitudinal axis. The aircraft cabin **12b** has two opposite aircraft cabin outer walls **18b**, **20b**. The aircraft cabin center axis **16b** is oriented parallel to an aircraft cabin floor **22b** of the aircraft cabin **12b**. In at least one operating state, the aircraft has a flight direction **24b**. In the present case, the flight direction **24b** is oriented in idealized form parallel to the aircraft cabin center axis **16b**. The aircraft cabin **12b** has an aircraft cabin section **26b** along the aircraft cabin center axis **16b**. In the present case, the aircraft cabin section **26b** is delimited by a plurality of aircraft cabin modules **30b**, illustrated schematically, along the aircraft cabin center axis **16b**. The aircraft cabin **12b** has a first aircraft cabin aisle **32b** and a second aircraft cabin aisle **34b** in the aircraft cabin section **26b**. The aircraft seat arrangement **14b** comprises a first outer seat column **36b**. The aircraft seat arrangement **14b** comprises a first inner seat column **38b**. The aircraft seat arrangement **14b** comprises a second inner seat column **40b**. The aircraft seat arrangement **14b** comprises a second outer seat column **42b**. In the present case, the first inner seat column **38b** is formed symmetrically with respect to the second inner seat column **40b** via the aircraft cabin center axis **16b**. In the present case, the first outer seat column **36b** is formed symmetrically with respect to the second outer seat column **42b** via the aircraft cabin center axis **16b**. The first inner seat column **38b** and the second inner seat column **40b** are arranged directly next to each other. The aircraft cabin **12b** has a central region **44b**.

(89) The aircraft seat arrangement **14b** comprises a plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** arranged in the aircraft cabin section **26b**. The plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** are designed to be different from one another. The aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** each have an aircraft seat. The aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** each have a console. The aircraft seat arrangement **14b** comprises a first aircraft seat device **100b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**. The first aircraft seat device **100b** has a sitting direction **110b**. The sitting direction **110b** of the first aircraft seat device **100b** corresponds to the flight direction **24b**. The first aircraft seat device **100b** has a first aircraft seat **120b**. The first aircraft seat device **100b** has a first console **130b**. The first aircraft seat device **100b** has direct access to the first aircraft cabin aisle **32b**. The aircraft seat arrangement **14b** comprises a second aircraft seat device **200b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**. The second aircraft seat device **200b** has a sitting direction **210b**. The sitting direction **210b** of the second aircraft seat device **200b** differs from the flight direction **24b**. The second aircraft seat device **200b** has a second aircraft seat **220b**. The second aircraft seat device **200b** has a second console **230b**. The second aircraft seat device **200b** has direct access to the first aircraft cabin aisle **32b**. The aircraft seat arrangement **14b** comprises a third aircraft seat device **300b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**. The third aircraft seat device **300b** has a sitting direction **310b**. The sitting direction **310b** of the third aircraft seat device **300b** corresponds to the flight direction **24b**. The third aircraft seat device **300b** has a third aircraft seat **320b**. The third aircraft seat device **300b** has a third console **330b**. The third aircraft seat device **300b** has direct access to the first aircraft cabin aisle **32b**. The first aircraft seat device **100b**, the second aircraft seat device **200b** and the third aircraft seat device **300b** are designed to be different from one

another. The aircraft seat arrangement **14b** comprises a fifth aircraft seat device **500b** of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b**. The fifth aircraft seat device **500b** is formed in mirror image with respect to the first aircraft seat device **100b** via an aircraft longitudinal axis, in particular via the aircraft cabin center axis **16b**. The fifth aircraft seat device **500b** has a sitting direction **510b**. The sitting direction **510b** of the fifth aircraft seat device **500b** corresponds to the flight direction **24b**.

(90) The fifth aircraft seat device **500b** has a fifth aircraft seat **520b**. The fifth aircraft seat device **500b** has a fifth console **530b**. The fifth aircraft seat device **500b** has direct access to the second aircraft cabin aisle **34b**. The aircraft seat arrangement **14b** comprises a sixth aircraft seat device **600b** of the plurality of aircraft seat devices **100b, 200b, 300b, 400b, 500b, 600b, 700b, 800b**. The sixth aircraft seat device **600b** is formed in mirror image with respect to the second aircraft seat device **200b** via an aircraft longitudinal axis, in particular via the aircraft cabin center axis **16b**. The sixth aircraft seat device **600b** has a sitting direction **610b**. The sitting direction **610b** of the sixth aircraft seat device **600b** differs from the flight direction **24b**. The sixth aircraft seat device **600b** has a sixth aircraft seat **620b**. The sixth aircraft seat device **600b** has a sixth console **630b**. The sixth aircraft seat device **600b** has direct access to the second aircraft cabin aisle **34b**. The aircraft seat arrangement **14b** comprises a seventh aircraft seat device **700b** of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b**. The seventh aircraft seat device **700b** is formed in mirror image with respect to the third aircraft seat device **300b** via an aircraft longitudinal axis, in particular via the aircraft cabin center axis **16b**. The seventh aircraft seat device **700b** has a sitting direction **710b**. The sitting direction **710b** of the seventh aircraft seat device **700b** corresponds to the flight direction **24b**. The seventh aircraft seat device **700b** has a seventh aircraft seat **720b**. The seventh aircraft seat device **700b** has a seventh console **730b**. The seventh aircraft seat device **700b** has direct access to the second aircraft cabin aisle **34b**. The fifth aircraft seat device **500b**, the sixth aircraft seat device **600b** and the seventh aircraft seat device **700b** are designed to be different from one another. The aircraft seats **120b, 220b, 320b, 520b, 620b, 720b** are each designed as a full-flat seat. The aircraft seats **120b, 220b, 320b, 520b, 620b, 720b** are each adjustable between a sitting position and a lying position. In the present case, the aircraft seat arrangement **14b** comprises six differently designed aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b** which are in each case present at least once in the aircraft seat arrangement **14b**. The first aircraft seat device **100b**, the second aircraft seat device **200b**, the third aircraft seat device **300b**, the fifth aircraft seat device **500b**, the sixth aircraft seat device **600b** and the seventh aircraft seat device **700b** are designed to be different from one another. In the present case, six aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b** designed to be different from one another are arranged in the aircraft cabin section **26b**. The aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b** each form an aircraft seat region. The aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b** have differently shaped and/or differently arranged components in the corresponding aircraft seat regions.

(91) In particular, an arrangement and an orientation of the aircraft seats **120b, 220b, 320b** in the respective aircraft seat regions differ for the first aircraft seat device **100b**, the second aircraft seat device **200b** and the third aircraft seat device **300b**. Furthermore, in particular an arrangement and an orientation of the aircraft seats **520b, 620b, 720b** in the respective aircraft seat regions differ for the fifth aircraft seat device **500b**, the sixth aircraft seat device **600b** and the seventh aircraft seat device **700b**. The first aircraft seat device **100b** and the fifth aircraft seat device **500b** are arranged directly next to each other. The second aircraft seat device **200b** and the sixth aircraft seat device **600b** are arranged directly next to each other. The third aircraft seat device **300b** and the seventh aircraft seat device **700b** are arranged directly next to each other.

(92) In the present case, the aircraft seat arrangement **14b** comprises a plurality of further first aircraft seat devices **100'b** which are formed at least substantially identically to the first aircraft seat device **100b**. The further first aircraft seat devices **100'b** are each arranged in the first inner seat column **38b** or in the second outer seat column **42b**. In the present case, the aircraft seat

arrangement **14b** comprises a plurality of further second aircraft seat devices **200'b** which are formed at least substantially identically to the second aircraft seat device **200b**. The further second aircraft seat devices **200'b** are each arranged in the first inner seat column **38b** or in the second outer seat column **42b**. In the present case, the aircraft seat arrangement **14b** comprises a plurality of further third aircraft seat devices **300'b** which are formed at least substantially identically to the third aircraft seat device **300b**. The further third aircraft seat devices **300'b** are each arranged in the first inner seat column **38b** or in the second outer seat column **42b**. In the present case, the aircraft seat arrangement **14b** comprises a plurality of further fifth aircraft seat devices **500'b** which are formed at least substantially identically to the fifth aircraft seat device **500b**. The further fifth aircraft seat devices **500'b** are each arranged in the second inner seat column **40b** or in the first outer seat column **36b**. In the present case, the aircraft seat arrangement **14b** comprises a plurality of further sixth aircraft seat devices **600'b** which are formed at least substantially identically to the sixth aircraft seat device **600b**. The further sixth aircraft seat devices **600'b** are each arranged in the second inner seat column **40b** or in the first outer seat column **36b**. In the present case, the aircraft seat arrangement **14b** comprises a plurality of further seventh aircraft seat devices **700'b** which are formed at least substantially identically to the seventh aircraft seat device **700b**. The further seventh aircraft seat devices **700'b** are each arranged in the second inner seat column **40b** or in the first outer seat column **36b**. For clarity reasons, only a selection of further aircraft seat devices **100'a**, **200'a**, **300'a**, **500'a**, **600'a**, **700'a** are provided with a reference sign in FIG. 5.

(93) In the aircraft cabin section **26b**, the sitting direction **110b** of the first aircraft seat device **100b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** in the first inner seat column **38b** is oriented at least substantially parallel to the aircraft cabin center axis **16b**. The first aircraft seat **120b** of the first aircraft seat device **100b** of the aircraft seat devices **100b**, **200b**, **300b** arranged in the first inner seat column **38b** in the aircraft cabin section **26b** is arranged on the aisle side. In the aircraft cabin section **26b**, the sitting direction **210b** of the second aircraft seat device **200b** of the plurality of aircraft seat devices **100b**, **200b**, **300b** in the first inner seat column **38b** is arranged in an angled manner at an angle of at least 18 degrees with respect to the aircraft cabin center axis **16b**. In the present case, in the first inner seat column **38b** in the aircraft cabin section **26b**, the sitting direction **210b** of the second aircraft seat device **200b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** is arranged in an angled manner at an angle of 30 degrees with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, the sitting direction **210b** of the second aircraft seat device **200b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** in the first inner seat column **38b** is directed away from the directly adjacent first aircraft cabin aisle **32b**. The second aircraft seat **220b** of the second aircraft seat device **200b** of the aircraft seat devices **100b**, **200b**, **300b** arranged in the first inner seat column **38b** in the aircraft cabin section **26b** is arranged on the aisle side. In the aircraft cabin section **26b**, the sitting direction **310b** of the third aircraft seat device **300b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** in the first inner seat column **38b** is oriented at least substantially parallel to the aircraft cabin center axis **16b**. The third aircraft seat **320b** of the third aircraft seat device **300b** of the aircraft seat devices **100b**, **200b**, **300b** arranged in the first inner seat column **38b** is arranged facing away from the aisle. The first aircraft seat device **100b** and the third aircraft seat device **300b** are spaced apart from each other by the second aircraft seat device **200b**. In the aircraft cabin section **26b**, the first aircraft seat device **100b** and the second aircraft seat device **200b** in the first inner seat column **38b** each have an aircraft seat **120b**, **220b** which is arranged on the aisle side, and the third aircraft seat device **300b**, which is arranged behind or in front of the two aircraft seat devices **100b**, **200b**, as viewed in the flight direction **24b**, has the aircraft seat **320b**, which is arranged facing away from the aisle. The aircraft seats **120b**, **320b** of the aircraft seat devices **100b**, **300b**, the sitting directions **110b**, **310b** of which are arranged at least substantially parallel to the aircraft cabin center axis **16b**, are at different distances from the first aircraft cabin aisle **32b**. In the aircraft cabin section **26b**, three aircraft seat devices of the

plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**, namely the first aircraft seat device **100b**, the second aircraft seat device **200b** and the third aircraft seat device **300b**, are arranged in the first inner seat column **38b**, wherein the sitting directions **110b**, **310b** of the first aircraft seat device **100b** and of the third aircraft seat device **300b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the sitting direction **210b** of the second aircraft seat device **200b** is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, the three aircraft seat devices of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**, namely the first aircraft seat device **100b**, the second aircraft seat device **200b** and the third aircraft seat device **300b**, are arranged directly one behind another in the first inner seat column **38b**, wherein the sitting directions **110b**, **310b** of the first aircraft seat device **100b** and of the third aircraft seat device **300b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the sitting direction **210b** of the second aircraft seat device **200b** is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, three aircraft seat devices of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**, namely at least one of the further third aircraft seat devices **300'b**, the first aircraft seat device **100b** and the second aircraft seat device **200b**, are arranged in the first inner seat column **38b**, wherein sitting directions of the first aircraft seat device **100b** and of the further third aircraft seat device **300'b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the sitting direction **210b** of the second aircraft seat device **200b** is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, the three aircraft seat devices of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**, namely at least one of the further third aircraft seat devices **300'b**, the first aircraft seat device **100b** and the second aircraft seat device **200b**, are arranged directly one behind another in the first inner seat column **38b**, wherein sitting directions of the first aircraft seat device **100b** and of the further third aircraft seat device **300'b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the sitting direction **210b** of the second aircraft seat device **200b** is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, three aircraft seat devices **100b**, **200b**, **300b**, which are designed to be different from one another and are arranged directly one behind another, of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** are arranged in the first inner seat column **38b**. The three aircraft seat devices **100b**, **200b**, **300b**, which are designed to be different from one another and are arranged in the first inner seat column **38b**, of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** are arranged directly consecutively in the flight direction **24b**. In the aircraft cabin section **26b**, the first aircraft seat device **100b**, the second aircraft seat device **200b** and the third aircraft seat device **300b** are arranged directly one behind another in the first inner seat column **38b**. In the first inner seat column **38b** in the aircraft cabin section **26b**, the first aircraft seat device **100b** is arranged directly behind the second aircraft seat device **200b**, as viewed in the flight direction **24b**. In the first inner seat column **38b** in the aircraft cabin section **26b**, the second aircraft seat device **200b** is arranged directly behind the third aircraft seat device **300b**, as viewed in the flight direction **24b**. In principle, the third aircraft seat device **300b** in the first inner seat column **38b** in the aircraft cabin section **26b** can be arranged directly behind the first aircraft seat device **100b**, as viewed in the flight direction **24b**.

(94) In the aircraft cabin section **26b**, the sitting direction **510b** of the fifth aircraft seat device **500b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** in the second inner seat column **40b** is oriented at least substantially parallel to the aircraft cabin center axis **16b**. The fifth aircraft seat **520b** of the fifth aircraft seat device **500b** of the aircraft seat devices **500b**, **600b**, **700b** arranged in the second inner seat column **40b** in the aircraft cabin section **26b** is arranged on the aisle side. In the aircraft cabin section **26b**, the sitting direction **610b** of the sixth aircraft seat device **600b** of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** is arranged in the second inner seat column **40b** in an angled manner at an angle of at least 18 degrees with

respect to the aircraft cabin center axis **16b**. In the present case, in the second inner seat column **40b** in the aircraft cabin section **26b**, the sitting direction **610b** of the sixth aircraft seat device **600b** of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b** is arranged in an angled manner at an angle of 30 degrees with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, the sitting direction **610b** of the sixth aircraft seat device **600b** of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b** in the second inner seat column **40b** is directed away from the directly adjacent second aircraft cabin aisle **34b**. The sixth aircraft seat **620b** of the sixth aircraft seat device **600b** of the aircraft seat devices **500b, 600b, 700b** arranged in the second inner seat column **40b** in the aircraft cabin section **26b** is arranged on the aisle side. In the aircraft cabin section **26b**, the sitting direction **710b** of the seventh aircraft seat device **700b** of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b** in the second inner seat column **40b** is oriented at least substantially parallel to the aircraft cabin center axis **16b**. The seventh aircraft seat **720b** of the seventh aircraft seat device **700b** of the aircraft seat devices **500b, 600b, 700b** arranged in the second inner seat column **40b** is arranged facing away from the aisle. The fifth aircraft seat device **500b** and the seventh aircraft seat device **700b** are spaced apart from each other by the sixth aircraft seat device **600b**. In the aircraft cabin section **26b**, the fifth aircraft seat device **500b** and the sixth aircraft seat device **600b** in the second inner seat column **40b** each have an aircraft seat **520b, 620b**, which is arranged on the aisle side, and the seventh aircraft seat device **700b**, which is arranged directly behind or in front of the two aircraft seat devices **500b, 600b**, as viewed in the flight direction **24b**, has the aircraft seat **720b**, which is arranged facing away from the aisle. The aircraft seats **520b, 720b** of the aircraft seat devices **500b, 700b**, the sitting directions **510b, 710b** of which are arranged at least substantially parallel to the aircraft cabin center axis **16b**, are at different distances from the second aircraft cabin aisle **34b**. In the aircraft cabin section **26b**, three aircraft seat devices of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b**, namely the fifth aircraft seat device **500b**, the sixth aircraft seat device **600b** and the seventh aircraft seat device **700b**, are arranged in the second inner seat column **40b**, wherein the sitting directions **510b, 710b** of the fifth aircraft seat device **500b** and of the seventh aircraft seat device **700b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the sitting direction **610b** of the sixth aircraft seat device **600b** is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, the three aircraft seat devices of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b**, namely the fifth aircraft seat device **500b**, the sixth aircraft seat device **600b** and the seventh aircraft seat device **700b**, are arranged directly one behind another in the second inner seat column **40b**, wherein the sitting directions **510b, 710b** of the fifth aircraft seat device **500b** and of the seventh aircraft seat device **700b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the sitting direction **610b** of the sixth aircraft seat device **600b** is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, three aircraft seat devices of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b**, namely one of the further seventh aircraft seat devices **700'b**, the fifth aircraft seat device **500b** and the sixth aircraft seat device **600b**, are arranged in the second inner seat column **40b**, wherein sitting directions of the fifth aircraft seat device **500b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the sitting direction **610b** of the sixth aircraft seat device **600b** is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, the three aircraft seat devices of the plurality of aircraft seat devices **100b, 200b, 300b, 500b, 600b, 700b**, namely one of the further seventh aircraft seat devices **700'b**, the fifth aircraft seat device **500b** and the sixth aircraft seat device **600b**, are arranged directly one behind another in the second inner seat column **40b**, wherein the sitting directions of the fifth aircraft seat device **500b** and of the further seventh aircraft seat device **700'b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the sitting direction of the sixth aircraft seat device **600b** is arranged in an angled manner with respect to the

aircraft cabin center axis **16b**. In the aircraft cabin section **26b**, three aircraft seat devices **500b**, **600b**, **700b**, which are designed to be different from one another and are arranged directly one behind another, of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** are arranged in the second inner seat column **40b**. The three aircraft seat devices **500b**, **600b**, **700b**, which are designed to be different from one another and are arranged in the second inner seat column **40b**, of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b** are arranged directly consecutively in the flight direction **24b**. In the aircraft cabin section **26b**, the fifth aircraft seat device **500b**, the sixth aircraft seat device **600b** and the seventh aircraft seat device **700b** are arranged directly one behind another in the second inner seat column **40b**. In the second inner seat column **40b** in the aircraft cabin section **26b**, the fifth aircraft seat device **500b** is arranged directly behind the sixth aircraft seat device **600b**, as viewed in the flight direction **24b**. In the second inner seat column **40b** in the aircraft cabin section **26b**, the sixth aircraft seat device **600b** is arranged directly behind the seventh aircraft seat device **700b**, as viewed in the flight direction **24b**. In principle, the seventh aircraft seat device **700b** in the second inner seat column **40b** in the aircraft cabin section **26b** can be arranged directly behind the fifth aircraft seat device **500b**, as viewed in the flight direction **24b**.

(95) In the aircraft cabin section **26b**, three aircraft seat devices **500'b**, **600'b**, **700'b**, which are designed to be different from one another and are arranged directly one behind another, of the plurality of further aircraft seat devices **100'b**, **200'b**, **300'b**, **500'b**, **600'b**, **700'b** are arranged in the first outer seat column **36b**. The three aircraft seat devices **500'b**, **600'b**, **700'b**, which are designed to be different from one another and are arranged in the first outer seat column **36b**, of the plurality of further aircraft seat devices **100'b**, **200'b**, **300'b**, **500'b**, **600'b**, **700'b** are arranged directly consecutively in the flight direction **24b**. In the present case, a further third aircraft seat device **300'b** is arranged in front of a further second aircraft seat device **200'b** in the second outer seat column **42b**, as viewed in the flight direction **24b**, wherein three additional further second aircraft seat devices **200'b** are arranged behind the further second aircraft seat device **200'b** in the second outer seat column **42b**, as viewed in the flight direction **24b**.

(96) In the aircraft cabin section **26b**, three aircraft seat devices **100'b**, **200'b**, **300'b**, which are designed to be different from one another and are arranged directly one behind another, of the plurality of further aircraft seat devices **100'b**, **200'b**, **300'b**, **500'b**, **600'b**, **700'b** are arranged in the second outer seat column **42b**. The three aircraft seat devices **100'b**, **200'b**, **300'b**, which are designed to be different from one another and are arranged in the second outer seat column **42b**, of the plurality of aircraft seat devices **100'b**, **200'b**, **300'b**, **500'b**, **600'b**, **700'b** are arranged directly consecutively in the flight direction **24b**. In the present case, a further seventh aircraft seat device **700'b** is arranged in front of a further sixth aircraft seat device **600'b** in the first outer seat column **36b**, as viewed in the flight direction **24b**, wherein three additional further sixth aircraft seat devices **600'b** are arranged behind the further sixth aircraft seat device **600'b** in the first outer seat column **36b**, as viewed in the flight direction **24b**.

(97) In principle, the previous descriptions of the first inner seat column **38b** are also applicable to the second outer seat column **42b**. In principle, the previous descriptions of the second inner seat column **40b** are also applicable to the first outer seat column **36b**.

(98) In the aircraft cabin section **26b**, two aircraft seat devices of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**, namely the third aircraft seat device **300b** and the seventh aircraft seat device **700b**, form a pair of seats **46b** in two seat columns arranged directly next to each other, namely the first inner seat column **38b** and the second inner seat column **40b**, wherein the sitting directions **310b**, **710b** of the two aircraft seat devices **300b**, **700b** are arranged at least substantially parallel to the aircraft cabin center axis **16b**, and the aircraft seats **320b**, **720b** of the two aircraft seat devices **300b**, **700b** are arranged facing away from the aisle, wherein at least two of the pairs of seats **46b** are arranged in the two seat columns **38b**, **40b** arranged directly next to each other.

(99) The aircraft seat arrangement **14b** has a first seat grouping **52b** of three aircraft seat devices arranged directly one behind another in the first inner seat column **38b** in the aircraft cabin section **26b**, namely the first aircraft seat device **100b**, the second aircraft seat device **200b** and the third aircraft seat device **300b**, which each have different sitting directions **110b**, **210b**, **310b** and the aircraft seats **120b**, **220b**, **320b** of which are arranged on the aisle side or facing away from the aisle. The sitting directions **110b**, **210b**, **310b** of the aircraft seat devices **100b**, **200b**, **300b** arranged directly one behind another are arranged within the first seat grouping **52b** in an alternating manner at least substantially parallel to and in an angled manner with respect to the aircraft cabin center axis **16b**. The first seat grouping **52b** forms a periodically repeatable sequence. A plurality of identical first seat groupings **52b** can be arranged directly one behind another along an aircraft longitudinal axis. Behind the first aircraft seat device **100b**, as viewed in the flight direction **24b**, the sitting direction **110b** of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**, there is arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**. In front of the first aircraft seat device **100b**, as viewed in the flight direction **24b**, the sitting direction **110b** of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**, there is arranged an aircraft seat device, the sitting direction of which is arranged in an angled manner with respect to the aircraft cabin center axis **16a**. In front of and behind the second aircraft seat device **200b**, as viewed in the flight direction **24b**, the sitting direction **210b** of which is arranged in an angled manner with respect to the aircraft cabin center axis **16b**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**. Behind the third aircraft seat device **300b**, as viewed in the flight direction **24b**, the sitting direction **310b** of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**, there is arranged an aircraft seat device, the sitting direction of which is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In front of the third aircraft seat device **300b**, as viewed in the flight direction **24b**, the sitting direction **310b** of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**, there is arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**.

(100) The aircraft seat arrangement **14b** has a second seat grouping **54b** of three aircraft seat devices arranged directly one behind another in the second inner seat column **40b** in the aircraft cabin section **26b**, namely the fifth aircraft seat device **500b**, the sixth aircraft seat device **600b** and the seventh aircraft seat device **700b**, which each have different sitting directions **510b**, **610b**, **710b** and the aircraft seats **520b**, **620b**, **720b** of which are arranged on the aisle side or facing away from the aisle. The sitting directions **510b**, **610b**, **710b** of the aircraft seat devices **500b**, **600b**, **700b** arranged directly one behind another are arranged within the second seat grouping **54b** in an alternating manner at least substantially parallel to and in an angled manner with respect to the aircraft cabin center axis **16b**. The second seat grouping **54b** forms a periodically repeatable sequence. A plurality of identical second seat groupings **54b** can be arranged directly one behind another along the aircraft cabin center axis **16b**. Behind the fifth aircraft seat device **500b**, as viewed in the flight direction **24b**, the sitting direction **510b** of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**, there is arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**. In front of the fifth aircraft seat device **500b**, as viewed in the flight direction **24b**, the sitting direction **510b** of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**, there is arranged an aircraft seat device, the sitting direction of which is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In front of and behind the sixth aircraft seat device **600b**, as viewed in the flight direction **24b**, the sitting direction **610b** of which is arranged in an angled manner with respect to the aircraft cabin center axis **16b**, there is in each case arranged an aircraft seat device, the sitting direction of which is arranged at least substantially

parallel to the aircraft cabin center axis **16b**. Behind the seventh aircraft seat device **700b**, as viewed in the flight direction **24b**, the sitting direction **710b** of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**, there is arranged an aircraft seat device, the sitting direction of which is arranged in an angled manner with respect to the aircraft cabin center axis **16b**. In front of the seventh aircraft seat device **700b**, as viewed in the flight direction **24b**, the sitting direction **710b** of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**, there is arranged an aircraft seat device, the sitting direction of which is arranged at least substantially parallel to the aircraft cabin center axis **16b**.

(101) The first aircraft seat device **100b**, the second aircraft seat device **200b** and the third aircraft seat device **300b** in the aircraft cabin section **26b** differ in at least one comfort category, wherein the aircraft seat devices **100b**, **200b**, **300b** for the at least one comfort category each have a different value from one another which is caused by a different arrangement of the aircraft seats **120b**, **220b**, **320b** and by the at least partially different design of the aircraft seat devices **100b**, **200b**, **300b**. The fifth aircraft seat device **500b**, the sixth aircraft seat device **600b** and the seventh aircraft seat device **700b** in the aircraft cabin section **26b** differ in at least one comfort category, wherein the aircraft seat devices **500b**, **600b**, **700b** for the at least one comfort category each have a value which is different from one another and is caused by a different arrangement of the aircraft seats **520b**, **620b**, **720b** and by the at least partially different design of the aircraft seat devices **500b**, **600b**, **700b**. The at least one comfort category describes a living space.

(102) In the first inner seat column **38b**, one of the further second aircraft seat devices **200'b** is arranged in a first seat row of the aircraft cabin section **26b**, as viewed counter to the flight direction **24b**. As viewed in the flight direction **24b**, a further aircraft cabin module can be arranged in the central region **44b** directly behind the further second aircraft seat device **200'b** arranged in the first seat row of the aircraft cabin section **26b**. The further aircraft cabin module can be designed here in particular as a front row monument. As a result, a higher degree of comfort can be achieved in the first seat row compared to the second aircraft seat device **200b** since more space is available in the first seat row. The further second aircraft seat device **200'b** which is arranged in the first seat row in the aircraft cabin section **26b** can in principle differ in at least one comfort category from at least one aircraft seat device of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**.

(103) In the second inner seat column **40b**, one of the further sixth aircraft seat devices **600'b** is arranged in the first seat row of the aircraft cabin section **26b**, as viewed counter to the flight direction **24b**. As viewed in the flight direction **24b**, a further aircraft cabin module can be arranged in the central region **44b** directly behind the further sixth aircraft seat device **600'b** arranged in the first seat row of the aircraft cabin section **26b**. The further sixth aircraft seat device **600'b** arranged in the first seat row in the aircraft cabin section **26b** can in principle differ in at least one comfort category from at least one aircraft seat device of the plurality of aircraft seat devices **100b**, **200b**, **300b**, **500b**, **600b**, **700b**.

(104) FIG. 6 shows an aircraft seat arrangement **14c** in a third exemplary embodiment. The aircraft seat arrangement **14c** is configured for use in an aircraft cabin **12c**, partially illustrated, of an aircraft. The aircraft cabin **12c** has an aircraft cabin center axis **16c**. The aircraft cabin center axis **16c** is in the form of an aircraft longitudinal axis. The aircraft cabin **12c** has two opposite aircraft cabin outer walls **18c**, **20c**. The aircraft cabin **12c** has an aircraft cabin floor **22c**. In at least one operating state, the aircraft has a flight direction **24c**. The aircraft cabin **12c** has an aircraft cabin section **26c** along the aircraft cabin center axis **16c**. In the present case, the aircraft cabin section **26c** is delimited by a plurality of aircraft cabin modules **30c**, illustrated schematically, along the aircraft cabin center axis **16c**. The aircraft cabin **12c** has a first aircraft cabin aisle **32c** and a second aircraft cabin aisle **34c** in the aircraft cabin section **26c**. The aircraft seat arrangement **14c** comprises a first outer seat column **36c**. The aircraft seat arrangement **14c** comprises a first inner seat column **38c**. The aircraft seat arrangement **14c** comprises a second inner seat column **40c**. The

aircraft seat arrangement **14c** comprises a second outer seat column **42c**. The aircraft cabin **12c** has a central region **44c**.

(105) The aircraft seat arrangement **14c** comprises a plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c** arranged in the aircraft cabin section **26c**. The plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c** are designed to be different from one another. In the present case, six aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c** which are designed to be different from one another are arranged in the aircraft cabin section **26c**. The aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c** each have an aircraft seat. The aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c** each have a console. The aircraft seat arrangement **14c** comprises a first aircraft seat device **100c** of the plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c**. The first aircraft seat device **100c** has a sitting direction **110c**. The first aircraft seat device **100c** has a first aircraft seat **120c**. The first aircraft seat device **100c** has a first console **130c**. The aircraft seat arrangement **14c** comprises a second aircraft seat device **200c** of the plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c**. The second aircraft seat device **200c** has a sitting direction **210c**. The second aircraft seat device **200c** has a second aircraft seat **220c**. The second aircraft seat device **200c** has a second console **230c**. The aircraft seat arrangement **14c** comprises a third aircraft seat device **300c** of the plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c**. The third aircraft seat device **300c** has a sitting direction **310c**. The third aircraft seat device **300c** has a third aircraft seat **320c**. The third aircraft seat device **300c** has a third console **330c**. The aircraft seat arrangement **14c** comprises a fifth aircraft seat device **500c** of the plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c**. The fifth aircraft seat device **500c** has a sitting direction **510c**. The fifth aircraft seat device **500c** has a fifth aircraft seat **520c**. The fifth aircraft seat device **500c** has a fifth console **530c**. The aircraft seat arrangement **14c** comprises a sixth aircraft seat device **600c** of the plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c**. The sixth aircraft seat device **600c** has a sitting direction **610c**. The sixth aircraft seat device **600c** has a sixth aircraft seat **620c**. The sixth aircraft seat device **600c** has a sixth console **630c**. The aircraft seat arrangement **14c** comprises a seventh aircraft seat device **700c** of the plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c**. The seventh aircraft seat device **700c** has a sitting direction **710c**. The seventh aircraft seat device **700c** has a seventh aircraft seat **720c**. The seventh aircraft seat device **700c** has a seventh console **730c**. The aircraft seat arrangement **14c** comprises a plurality of further first aircraft seat devices **100'c** which are formed at least substantially identically to the first aircraft seat device **100c**. The aircraft seat arrangement **14c** comprises a plurality of further second aircraft seat devices **200'c** which are formed at least substantially identically to the second aircraft seat device **200c**. The aircraft seat arrangement **14c** comprises a plurality of further third aircraft seat devices **300'c** which are formed at least substantially identically to the third aircraft seat device **300c**. The aircraft seat arrangement **14c** comprises a plurality of further fifth aircraft seat devices **500'c** which are formed at least substantially identically to the fifth aircraft seat device **500c**. The aircraft seat arrangement **14c** comprises a plurality of further sixth aircraft seat devices **600'c** which are formed at least substantially identically to the sixth aircraft seat device **600c**. The aircraft seat arrangement **14c** comprises a plurality of further seventh aircraft seat devices **700'c** which are formed at least substantially identically to the seventh aircraft seat device **700c**.

(106) In the aircraft cabin section **26c**, two aircraft seat devices of the plurality of aircraft seat devices **100c**, **200c**, **300c**, **500c**, **600c**, **700c**, namely the third aircraft seat device **300c** and the seventh aircraft seat device **700c**, form a pair of seats **46c** in two seat columns arranged directly next to each other, namely the first inner seat column **38c** and the second inner seat column **40c**, wherein the sitting directions **310c**, **710c** of the two aircraft seat devices **300c**, **700c** are arranged at least substantially parallel to the aircraft cabin center axis **16c**, and the aircraft seats **320c**, **720c** of the two aircraft seat devices **300c**, **700c** are arranged facing away from the aisle, wherein at least two of the pairs of seats **46c** are arranged in the two seat columns **38c**, **40c** arranged directly next to

each other. The aircraft seat arrangement **14c** has a first seat grouping **52c** of three aircraft seat devices arranged directly one behind another in the first inner seat column **38c** in the aircraft cabin section **26c**, namely the first aircraft seat device **100c**, the second aircraft seat device **200c** and the third aircraft seat device **300c**, which each have different sitting directions **110c**, **210c**, **310c** and the aircraft seats **120c**, **220c**, **320c** of which are arranged on the aisle side or facing away from the aisle. The aircraft seat arrangement **14c** has a second seat grouping **54c** of three aircraft seat devices arranged directly one behind another in the second inner seat column **40c** in the aircraft cabin section **26c**, namely the fifth aircraft seat device **500c**, the sixth aircraft seat device **600c** and the seventh aircraft seat device **700c**, which each have different sitting directions **510c**, **610c**, **710c** and the aircraft seats **520c**, **620c**, **720c** of which are arranged on the aisle side or facing away from the aisle.

(107) The first aircraft seat device **100c**, the second aircraft seat device **200c** and the third aircraft seat device **300c** in the aircraft cabin section **26c** differ in at least one comfort category, wherein the aircraft seat devices **100c**, **200c**, **300c** for the at least one comfort category each have a value which is different from one another and is caused by a different arrangement of the aircraft seats **120c**, **220c**, **320c** and by the at least partially different design of the aircraft seat devices **100c**, **200c**, **300c**. The fifth aircraft seat device **500c**, the sixth aircraft seat device **600c** and the seventh aircraft seat device **700c** in the aircraft cabin section **26c** differ in at least one comfort category, wherein the aircraft seat devices **500c**, **600c**, **700c** for the at least one comfort category in each case have a value which is different from one another and is caused by a different arrangement of the aircraft seats **520c**, **620c**, **720c** and by the at least partially different design of the aircraft seat devices **500c**, **600c**, **700c**.

(108) In contrast to the second exemplary embodiment, a further of the third aircraft seat devices **300'c** is arranged in the first inner seat column **38c**, as viewed in the flight direction **24c**, and a further of the seventh aircraft seat devices **700'c** is arranged in the second inner seat column **40c**, in a final seat row, as viewed counter to the flight direction **24c**, in the central region **44c** of the aircraft cabin section **26c**. In the first inner seat column **38c**, two aircraft seat devices are arranged directly behind the further third aircraft seat device **300'c**, as viewed in the flight direction **24c**, the sitting directions of which two aircraft seat devices are arranged at least substantially parallel to the aircraft cabin center axis **16c**. In the second inner seat column **40c**, two aircraft seat devices are arranged directly behind the further seventh aircraft seat device **700'c**, as viewed in the flight direction **24c**, the sitting directions of which are arranged at least substantially parallel to the aircraft cabin center axis **16c**.

(109) FIG. 7 shows an aircraft seat arrangement **14d** in a fourth exemplary embodiment. The aircraft seat arrangement **14d** is configured for use in an aircraft cabin **12d**, partially illustrated, of an aircraft. The aircraft cabin **12d** has an aircraft cabin center axis **16d**. The aircraft cabin center axis **16d** is in the form of an aircraft longitudinal axis. The aircraft cabin **12d** has two opposite aircraft cabin outer walls **18d**, **20d**. The aircraft cabin **12d** has an aircraft cabin floor **22d**. In at least one operating state, the aircraft has a flight direction **24d**. The aircraft cabin **12d** has an aircraft cabin section **26d** along the aircraft cabin center axis **16d**. In the present case, the aircraft cabin section **26d** is delimited by a plurality of aircraft cabin modules **30d**, illustrated schematically, along the aircraft cabin center axis **16d**. The aircraft cabin **12d** has a first aircraft cabin aisle **32d** and a second aircraft cabin aisle **34d** in the aircraft cabin section **26d**. The aircraft seat arrangement **14d** comprises a first outer seat column **36d**. The aircraft seat arrangement **14d** comprises a first inner seat column **38d**. The aircraft seat arrangement **14d** comprises a second inner seat column **40d**. The aircraft seat arrangement **14d** comprises a second outer seat column **42d**. The aircraft cabin **12d** has a central region **44d**.

(110) The aircraft seat arrangement **14d** comprises a plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d** arranged in the aircraft cabin section **26d**. The plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d** are designed to be different from one another. In the

present case, six aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d** which are designed to be different from one another are arranged in the aircraft cabin section **26d**. The aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d** each have an aircraft seat. The aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d** each have a console. The aircraft seat arrangement **14d** comprises a first aircraft seat device **100d** of the plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d**. The first aircraft seat device **100d** has a sitting direction **110d**. The first aircraft seat device **100d** has a first aircraft seat **120d**. The first aircraft seat device **100d** has a first console **130d**. The aircraft seat arrangement **14d** comprises a second aircraft seat device **200d** of the plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d**. The second aircraft seat device **200d** has a sitting direction **210d**. The second aircraft seat device **200d** has a second aircraft seat **220d**. The second aircraft seat device **200d** has a second console **230d**. The aircraft seat arrangement **14d** comprises a third aircraft seat device **300d** of the plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d**. The third aircraft seat device **300d** has a sitting direction **310d**. The third aircraft seat device **300d** has a third aircraft seat **320d**. The third aircraft seat device **300d** has a third console **330d**. The aircraft seat arrangement **14d** comprises a fifth aircraft seat device **500d** of the plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d**. The fifth aircraft seat device **500d** has a sitting direction **510d**. The fifth aircraft seat device **500d** has a fifth aircraft seat **520d**. The fifth aircraft seat device **500d** has a fifth console **530d**. The aircraft seat arrangement **14d** comprises a sixth aircraft seat device **600d** of the plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d**. The sixth aircraft seat device **600d** has a sitting direction **610d**. The sixth aircraft seat device **600d** has a sixth aircraft seat **620d**. The sixth aircraft seat device **600d** has a sixth console **630d**. The aircraft seat arrangement **14d** comprises a seventh aircraft seat device **700d** of the plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d**. The seventh aircraft seat device **700d** has a sitting direction **710d**. The seventh aircraft seat device **700d** has a seventh aircraft seat **720d**. The seventh aircraft seat device **700d** has a seventh console **730d**. The aircraft seat arrangement **14d** comprises a plurality of further first aircraft seat devices **100'd** which are formed at least substantially identically to the first aircraft seat device **100d**. The aircraft seat arrangement **14d** comprises a plurality of further second aircraft seat devices **200'd** which are formed at least substantially identically to the second aircraft seat device **200d**. The aircraft seat arrangement **14d** comprises a plurality of further third aircraft seat devices **300'd** which are formed at least substantially identically to the third aircraft seat device **300d**. The aircraft seat arrangement **14d** comprises a plurality of further fourth aircraft seat devices **400'd** which are formed at least substantially identically to the fourth aircraft seat device **400a** from the first exemplary embodiment. The aircraft seat arrangement **14d** comprises a plurality of further fifth aircraft seat devices **500'd** which are formed at least substantially identically to the fifth aircraft seat device **500d**. The aircraft seat arrangement **14d** comprises a plurality of further sixth aircraft seat devices **600'd** which are formed at least substantially identically to the sixth aircraft seat device **600d**. The aircraft seat arrangement **14d** comprises a plurality of further seventh aircraft seat devices **700'd** which are formed at least substantially identically to the seventh aircraft seat device **700d**. The aircraft seat arrangement **14d** comprises a plurality of further eighth aircraft seat devices **800'd** which are formed at least substantially identically to the eighth aircraft seat device **800a** from the first exemplary embodiment.

(111) In the aircraft cabin section **26d**, two aircraft seat devices of the plurality of aircraft seat devices **100d**, **200d**, **300d**, **500d**, **600d**, **700d**, namely the third aircraft seat device **300d** and the seventh aircraft seat device **700d**, form a pair of seats **46d** in two seat columns arranged directly next to each other, namely the first inner seat column **38d** and the second inner seat column **40d**, wherein the sitting directions **310d**, **710d** of the two aircraft seat devices **300d**, **700d** are arranged at least substantially parallel to the aircraft cabin center axis **16d**, and the aircraft seats **320d**, **720d** of the two aircraft seat devices **300d**, **700d** are arranged facing away from the aisle, wherein at least two of the pairs of seats **46d** are arranged in the two seat columns **38d**, **40d** which are arranged

directly next to each other. The aircraft seat arrangement **14d** has a first seat grouping **52d** of three aircraft seat devices arranged directly one behind another in the first inner seat column **38d** in the aircraft cabin section **26d**, namely the first aircraft seat device **100d**, the second aircraft seat device **200d** and the third aircraft seat device **300d**, which each have different sitting directions **110d**, **210d**, **310d** and the aircraft seats **120d**, **220d**, **320d** of which are arranged on the aisle side or facing away from the aisle. The aircraft seat arrangement **14d** has a second seat grouping **54d** of three aircraft seat devices arranged directly one behind another in the second inner seat column **40d** in the aircraft cabin section **26d**, namely the fifth aircraft seat device **500d**, the sixth aircraft seat device **600d** and the seventh aircraft seat device **700d**, which each have different sitting directions **510d**, **610d**, **710d** and the aircraft seats **520d**, **620d**, **720d** of which are arranged on the aisle side or facing away from the aisle.

(112) The first aircraft seat device **100d**, the second aircraft seat device **200d** and the third aircraft seat device **300d** in the aircraft cabin section **26d** differ in at least one comfort category, wherein the aircraft seat devices **100d**, **200d**, **300d** for the at least one comfort category in each case have a value which is different from one another and is caused by a different arrangement of the aircraft seats **120d**, **220d**, **320d** and by the at least partially different design of the aircraft seat devices **100d**, **200d**, **300d**. The fifth aircraft seat device **500d**, the sixth aircraft seat device **600d** and the seventh aircraft seat device **700d** in the aircraft cabin section **26d** differ in at least one comfort category, wherein the aircraft seat devices **500d**, **600d**, **700d** for the at least one comfort category in each case have a value which is different from one another and is caused by a different arrangement of the aircraft seats **520d**, **620d**, **720d** and by the at least partially different design of the aircraft seat devices **500d**, **600d**, **700d**.

(113) In contrast to the third exemplary embodiment, four aircraft seat devices **500'd**, **600'd**, **700'd**, **800'd**, which are designed to be different from one another, of the plurality of further aircraft seat devices **100'd**, **200'd**, **300'd**, **400'd**, **500'd**, **600'd**, **700'd**, **800'd** are arranged in the first outer seat column **36d** in the aircraft cabin section **26d**. A further fifth aircraft seat device **500'd**, a further seventh aircraft seat device **700'd** and a further eighth aircraft seat device **800'd** are arranged directly one behind another in the first outer seat column **36d**. In the first outer seat column **36d**, a further eighth aircraft seat device **800'd**, a further fifth aircraft seat device **500'd** and a further sixth aircraft seat device **600'd** are arranged directly behind one another. Between a further seventh aircraft seat device **700'd** and a further fifth aircraft seat device **500'd**, two further eighth aircraft seat devices **800'd** are arranged in the first outer seat column **36d**. Between the further fifth aircraft seat device **500'd** and a further seventh aircraft seat device **700'd**, two further sixth aircraft seat devices **600'd** are arranged in the first outer seat column **36d**.

(114) In contrast to the third exemplary embodiment, four aircraft seat devices **100'd**, **200'd**, **300'd**, **400'd**, which are designed to be different from one another, of the plurality of further aircraft seat devices **100'd**, **200'd**, **300'd**, **400'd**, **500'd**, **600'd**, **700'd**, **800'd** are arranged in the second outer seat column **42d** in the aircraft cabin section **26d**. A further first aircraft seat device **100'd**, a further third aircraft seat device **300'd** and a further fourth aircraft seat device **400'd** are arranged directly one behind another in the second outer seat column **42d**. A further fourth aircraft seat device **400'd**, a further first aircraft seat device **100'd** and a further second aircraft seat device **200'd** are arranged directly one behind another in the second outer seat column **42d**. Between a further third aircraft seat device **300'd** and a further first aircraft seat device **100'd**, two further fourth aircraft seat devices **400'd** are arranged in the second outer seat column **42d**. Between the further first aircraft seat device **100'd** and a further third aircraft seat device **300'd**, two further second aircraft seat devices **200'd** are arranged in the second outer seat column **42d**.

(115) FIG. 8 shows an aircraft seat arrangement **14e** in a fifth exemplary embodiment. The aircraft seat arrangement **14e** is configured for use in an aircraft cabin **12e**, partially illustrated, of an aircraft. The aircraft cabin **12e** has an aircraft cabin center axis **16e**. The aircraft cabin center axis **16e** is in the form of an aircraft longitudinal axis. The aircraft cabin **12e** has two opposite aircraft

cabin outer walls **18e, 20e**. In at least one operating state, the aircraft has a flight direction **24e**. The aircraft cabin **12e** has an aircraft cabin section **26e** along the aircraft cabin center axis **16e**. In the present case, the aircraft cabin section **26e** is delimited by a plurality of separating elements **28e** along the aircraft cabin center axis **16e**. The aircraft cabin **12e** has a first aircraft cabin aisle **32e** and a second aircraft cabin aisle **34e** in the aircraft cabin section **26d**. The aircraft seat arrangement **14e** comprises a first outer seat column **36e**. The aircraft seat arrangement **14e** comprises a first inner seat column **38e**. The aircraft seat arrangement **14e** comprises a second inner seat column **40e**. The aircraft seat arrangement **14e** comprises a second outer seat column **42e**. The aircraft cabin **12e** has a central region **44e**. The aircraft cabin **12e** comprises a first aircraft cabin side **56e** and a second aircraft cabin side **58e**.

(116) The aircraft seat arrangement **14e** comprises a plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e** arranged in the aircraft cabin section **26e**. The plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e** are designed to be different from one another. In the present case, seven aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**, which are designed to be different from one another, are arranged in the aircraft cabin section **26e**. The aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e** each have an aircraft seat. The aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e** each have a console. The aircraft seat arrangement **14e** comprises a first aircraft seat device **100e** of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**. The first aircraft seat device **100e** has a sitting direction **110e**. The first aircraft seat device **100e** has a first aircraft seat **120e**. The first aircraft seat device **100e** has a first console **130e**. The aircraft seat arrangement **14e** comprises a second aircraft seat device **200e** of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**. The second aircraft seat device **200e** has a sitting direction **210e**. The second aircraft seat device **200e** has a second aircraft seat **220e**. The second aircraft seat device **200e** has a second console **230e**. The aircraft seat arrangement **14e** comprises a third aircraft seat device **300e** of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**. The third aircraft seat device **300e** has a sitting direction **310e**. The third aircraft seat device **300e** has a third aircraft seat **320e**. The third aircraft seat device **300e** has a third console **330e**. The aircraft seat arrangement **14e** comprises a fifth aircraft seat device **500e** of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**. The fifth aircraft seat device **500e** has a sitting direction **510e**. The fifth aircraft seat device **500e** has a fifth aircraft seat **520e**. The fifth aircraft seat device **500e** has a fifth console **530e**. The aircraft seat arrangement **14e** comprises a sixth aircraft seat device **600e** of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**. The sixth aircraft seat device **600e** has a sitting direction **610e**. The sixth aircraft seat device **600e** has a sixth aircraft seat **620e**. The sixth aircraft seat device **600e** has a sixth console **630e**. The aircraft seat arrangement **14e** comprises a seventh aircraft seat device **700e** of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**. The seventh aircraft seat device **700e** has a sitting direction **710e**. The seventh aircraft seat device **700e** has a seventh aircraft seat **720e**. The seventh aircraft seat device **700e** has a seventh console **730e**. The aircraft seat arrangement **14e** comprises an eighth aircraft seat device **800e** of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**. The eighth aircraft seat device **800e** has a sitting direction **810e**. The eighth aircraft seat device **800e** has an eighth aircraft seat **820e**. The eighth aircraft seat device **800e** has an eighth console **830e**. The aircraft seat arrangement **14e** can comprise a plurality of further first aircraft seat devices which are formed at least substantially identically to the first aircraft seat device **100e**. The aircraft seat arrangement **14e** comprises a plurality of further second aircraft seat devices **200'e** which are formed at least substantially identically to the second aircraft seat device **200e**. The aircraft seat arrangement **14e** comprises at least one further third aircraft seat device **300'e** which is formed at least substantially identically to the third aircraft seat device **300e**. The aircraft seat arrangement **14e** can comprise a plurality of further fifth aircraft seat devices which are formed at least substantially identically to the fifth aircraft seat device **500e**. The aircraft seat arrangement

14e comprises a plurality of further sixth aircraft seat devices **600'e** which are formed at least substantially identically to the sixth aircraft seat device **600e**. The aircraft seat arrangement **14e** comprises at least one further seventh aircraft seat device **700'e** which is formed at least substantially identically to the seventh aircraft seat device **700e**. The aircraft seat arrangement **14e** can comprise a plurality of further eighth aircraft seat devices which are formed at least substantially identically to the eighth aircraft seat device **800e**.

(117) In contrast to the first exemplary embodiment, an arrangement of aircraft seat devices **200e**, **600e**, **800e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e** in the aircraft cabin section **26e** in the first outer seat column **36e** and the first inner seat column **38e** on the first aircraft cabin side **56e** is formed asymmetrically with respect to an arrangement of aircraft seat devices **100e**, **300e**, **500e**, **700e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e** in the second inner seat column **38e** and the second outer seat column **42e** on the second aircraft cabin side **58e**. The first aircraft cabin side **56e** is separated from the second aircraft cabin side **58e** by an imaginary aircraft cabin center plane which is oriented along the aircraft cabin center axis **16e** perpendicularly to an aircraft cabin floor **22e** of the aircraft cabin **12e**. An arrangement of aircraft seat devices **200e**, **200'e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e** in the first inner seat column **38e** on the first aircraft cabin side **56e** is formed asymmetrically, with reference to the aircraft cabin center axis **16e**, to an arrangement of aircraft seat devices **500e**, **700e**, **700'e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e** in the second inner seat column **38e** on the second aircraft cabin side **58e**. An arrangement of aircraft seat devices **500e**, **700e**, **700'e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e** in the second inner seat column **40e** on the second aircraft cabin side **58e** is formed symmetrically to an arrangement of aircraft seat devices **100e**, **300e**, **300'e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e** in the second outer seat column **42e** on the second aircraft cabin side **58e**.

(118) The first aircraft cabin side **56e** and the second aircraft cabin side **58e** each have precisely one of the aircraft cabin aisles **32e**, **34e**. The first aircraft cabin aisle **32e** is arranged on the first aircraft cabin side **56e**. The second aircraft cabin aisle **34e** is arranged on the second aircraft cabin side **58e**. In principle, it is conceivable for the aircraft cabin **12e** to have, in the aircraft cabin section **26e**, at least one partition along the aircraft cabin center axis **16e** that separates the first aircraft cabin side **56e** from the second aircraft cabin side **58e**. As a result, a private sphere in a large-capacity aircraft can advantageously be increased.

(119) There is an exclusive arrangement of aircraft seat devices **600e**, **800e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e**, the sitting directions **610e**, **810e** of which are arranged in an angled manner with respect to the aircraft cabin center axis **16e**, in the first outer seat column **36e**. There is an exclusive arrangement of aircraft seat devices **200e**, **200'e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e**, the sitting directions **210e** of which are arranged in an angled manner with respect to the aircraft cabin center axis **16e**, in the first inner seat column **38e**. There is an exclusive arrangement of aircraft seat devices **200e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e**, the aircraft seats **220e** of which are arranged on the aisle side, in the first inner seat column **38e**. The first outer seat column **36e** is formed partially in mirror image to the first inner seat column **38e** via the first aircraft cabin aisle **32e**.

(120) There is an exclusive arrangement of aircraft seat devices **500e**, **700e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e**, the sitting directions **510e**, **710e** of which are arranged at least substantially parallel to the aircraft cabin center axis **16e**, in the second inner seat column **40e**. There is an exclusive arrangement of aircraft seat devices **100e**, **300e** of the plurality of aircraft seat devices **100e**, **200e**, **300e**, **500e**, **600e**, **700e**, **800e**, the sitting directions **110e**, **310e** of which are arranged at least substantially parallel to the aircraft cabin center axis **16e**, in the second outer seat column **42e**. There is an exclusive arrangement of aircraft seat devices

500e, 700e of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**, the aircraft seats **220e, 520e** of which are arranged in an alternating manner on the aisle side or facing away from the aisle, in the second inner seat column **40e**. There is an exclusive arrangement of aircraft seat devices **100e, 300e** of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**, the aircraft seats **120e, 320e** of which are arranged in an alternating manner on the aisle side or facing away from the aisle, in the second outer seat column **42e**. The second outer seat column **42e** is formed in mirror image to the second inner seat column **40e** via the second aircraft cabin aisle **34e**.

(121) The aircraft seat arrangement **14e** comprises an interspace unit **60e**. The interspace unit **60e** is arranged in the first outer seat column **36e**. The interspace unit **60e** is arranged along an aircraft longitudinal axis between the sixth aircraft seat device **600e** and the eighth aircraft seat device **800e**. The interspace unit **60e** is configured to make functional use of a free space provided and/or produced between two aircraft seat devices. The interspace unit **60e** can be designed as a storage space for, for example, jackets, coats, blankets and/or amenity kits. Alternatively, the interspace unit **60e** can be designed as a storage space for items of hand luggage. The interspace unit **60e** can in principle also be designed as a bar, as a vending machine and/or as a presentation space for inflight shopping products. Furthermore, the interspace unit **60e** can be designed as a server cabinet which is connected electronically to at least some of the plurality of aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e** in the aircraft cabin section **26e**. In principle, the interspace unit **60e** can also be designed as a console or as a cabin monument.

(122) In the aircraft cabin section **26e**, the first aircraft seat device **100e**, the second aircraft seat device **200e**, the third aircraft seat device **300e**, the fifth aircraft seat device **500e**, the sixth aircraft seat device **600e**, the seventh aircraft seat device **700e** and the eighth aircraft seat device **800e** differ in at least one comfort category, wherein the aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e** for the at least one comfort category in each case have a value which is different from one another and is caused by a different arrangement of the aircraft seats **120e, 220e, 320e, 520e, 620e, 720e, 820e** and by the at least partially different design of the aircraft seat devices **100e, 200e, 300e, 500e, 600e, 700e, 800e**.

(123) The aircraft seat arrangement **14e** illustrated in FIG. 8 is in principle extendable by further aircraft seat devices **100'e, 200'e, 300'e, 500'e, 600'e, 700'e, 800'e**, as viewed in the flight direction **24e**.

(124) FIG. 9 shows an aircraft seat arrangement **14f** in a sixth exemplary embodiment. The aircraft seat arrangement **14f** is configured for use in an aircraft cabin **12f**, partially illustrated, of an aircraft. The aircraft cabin **12f** has an aircraft cabin center axis **16f**. The aircraft cabin center axis **16f** is in the form of an aircraft longitudinal axis. The aircraft cabin **12f** has two opposite aircraft cabin outer walls **18f, 20f**. In at least one operating state, the aircraft has a flight direction **24f**. The aircraft cabin **12f** has an aircraft cabin section **26f** along the aircraft cabin center axis **16f**. The aircraft cabin **12f** has a first aircraft cabin aisle **32f** and a second aircraft cabin aisle **34f** in the aircraft cabin section **26f**. The aircraft seat arrangement **14f** comprises a first outer seat column **36f**. The aircraft seat arrangement **14f** comprises a first inner seat column **38f**. The aircraft seat arrangement **14f** comprises a second inner seat column **40f**. The aircraft seat arrangement **14f** comprises a second outer seat column **42f**. The aircraft cabin **12f** has a central region **44f**. The aircraft cabin **12f** comprises a first aircraft cabin side **56f** and a second aircraft cabin side **58f**.

(125) The aircraft seat arrangement **14f** comprises a plurality of aircraft seat devices **100f, 300f, 400f, 500f, 700f** arranged in the aircraft cabin section **26f**. The plurality of aircraft seat devices **100f, 300f, 400f, 500f, 700f** are designed to be different from one another. The aircraft seat devices **100f, 300f, 400f, 500f, 700f** each have an aircraft seat. The aircraft seat devices **100f, 300f, 400f, 500f, 700f** each have a console. The aircraft seat arrangement **14f** comprises a first aircraft seat device **100f** of the plurality of aircraft seat devices **100f, 300f, 400f, 500f, 700f**. The first aircraft seat device **100f** has a sitting direction **110f**. The first aircraft seat device **100f** has a first aircraft

seat **120f**. The first aircraft seat device **100f** has a first console **130f**. The aircraft seat arrangement **14f** comprises a third aircraft seat device **300f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**. The third aircraft seat device **300f** has a sitting direction **310f**. The third aircraft seat device **300f** has a third aircraft seat **320f**. The third aircraft seat device **300f** has a third console **330f**. The aircraft seat arrangement **14f** comprises a fourth aircraft seat device **400f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**. The fourth aircraft seat device **400f** has a sitting direction **410f**. The fourth aircraft seat device **400f** has a fourth aircraft seat **420f**. The fourth aircraft seat device **400f** has a fourth console **430f**. The aircraft seat arrangement **14f** comprises a fifth aircraft seat device **500f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**. The fifth aircraft seat device **500f** has a sitting direction **510f**. The fifth aircraft seat device **500f** has a fifth aircraft seat **520f**. The fifth aircraft seat device **500f** has a fifth console **530f**. The aircraft seat arrangement **14f** comprises a seventh aircraft seat device **700f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**. The seventh aircraft seat device **700f** has a sitting direction **710f**. The seventh aircraft seat device **700f** has a seventh aircraft seat **720f**. The seventh aircraft seat device **700f** has a seventh console **730f**. The aircraft seat arrangement **14f** comprises at least one further first aircraft seat device **100'f** which is formed at least substantially identically to the first aircraft seat device **100f**. The aircraft seat arrangement **14f** can comprise a plurality of further third aircraft seat devices which are formed at least substantially identically to the third aircraft seat device **300f**. The aircraft seat arrangement **14f** comprises a plurality of further fourth aircraft seat devices **400'f** which are formed at least substantially identically to the fourth aircraft seat device **400f**. The aircraft seat arrangement **14f** comprises at least one further fifth aircraft seat device **500'f** which is formed at least substantially identically to the fifth aircraft seat device **500f**. The aircraft seat arrangement **14f** comprises a plurality of further seventh aircraft seat devices **700'f** which are formed at least substantially identically to the seventh aircraft seat device **700f**.

(126) In contrast to the fifth exemplary embodiment, the aircraft seat arrangement **14f** comprises a plurality of alternative aircraft seat devices **1000f**, **3000f**, **5000f**, **7000f** which are arranged in the aircraft cabin section **26f**. The aircraft seat arrangement **14f** comprises an alternative first aircraft seat device **1000f**. The alternative first aircraft seat device **1000f** has a sitting direction **1100f**. The sitting direction **1100f** of the alternative first aircraft seat device **1000f** is oriented counter to the flight direction **24f**. The sitting direction **1100f** of the alternative first aircraft seat device **1000f** is oriented at least substantially parallel to the aircraft cabin center axis **16f**. The alternative first aircraft seat device **1000f** has an alternative first aircraft seat **1200f**. The alternative first aircraft seat device **1000f** has an alternative first console **1300f**. The alternative first aircraft seat device **1000f** is formed in mirror image to the first aircraft seat device **100f** about an axis, wherein the axis is oriented perpendicularly to the aircraft cabin center axis **16f** and parallel to an aircraft cabin floor **22f** of the aircraft cabin **12f**. The aircraft seat arrangement **14f** can comprise at least one further alternative first aircraft seat device which is formed at least substantially identically to the alternative first aircraft seat device **1000f**. The aircraft seat arrangement **14f** comprises an alternative third aircraft seat device **3000f**. The alternative third aircraft seat device **3000f** has a sitting direction **3100f**. The sitting direction **3100f** of the alternative third aircraft seat device **3000f** is oriented counter to the flight direction **24f**. The sitting direction **3100f** of the alternative third aircraft seat device **3000f** is oriented at least substantially parallel to the aircraft cabin center axis **16f**. The alternative third aircraft seat device **3000f** has an alternative third aircraft seat **3200f**. The alternative third aircraft seat device **3000f** has an alternative third console **3300f**. The alternative third aircraft seat device **3000f** is formed in mirror image to the third aircraft seat device **300f** about an axis, wherein the axis is oriented perpendicularly to the aircraft cabin center axis **16f** and parallel to the aircraft cabin floor **22f**. The aircraft seat arrangement **14f** comprises a plurality of further alternative third aircraft seat devices **3000'f** which are formed at least substantially identically to the alternative third aircraft seat device **3000f**. The aircraft seat arrangement **14f** comprises an alternative fifth aircraft seat device **5000f**. The alternative fifth aircraft seat device **5000f** has a

sitting direction **5100f**. The sitting direction **5100f** of the alternative fifth aircraft seat device **5000f** is oriented counter to the flight direction **24f**. The sitting direction **5100f** of the alternative fifth aircraft seat device **5000f** is oriented at least substantially parallel to the aircraft cabin center axis **16f**. The alternative fifth aircraft seat device **5000f** has an alternative fifth aircraft seat **5200f**. The alternative fifth aircraft seat device **5000f** has an alternative fifth console **5300f**. The alternative fifth aircraft seat device **5000f** is formed in mirror image to the fifth aircraft seat device **500f** about an axis, wherein the axis is oriented perpendicularly to the aircraft cabin center axis **16f** and parallel to the aircraft cabin floor **22f**. The aircraft seat arrangement **14f** comprises a plurality of further alternative fifth aircraft seat devices **5000'f** which are formed at least substantially identically to the alternative fifth aircraft seat device **5000f**. The aircraft seat arrangement **14f** comprises an alternative seventh aircraft seat device **7000f**. The alternative seventh aircraft seat device **7000f** has a sitting direction **7100f**. The sitting direction **7100f** of the alternative seventh aircraft seat device **7000f** is oriented counter to the flight direction **24f**. The sitting direction **7100f** of the alternative seventh aircraft seat device **7000f** is oriented at least substantially parallel to the aircraft cabin center axis **16f**. The alternative seventh aircraft seat device **7000f** has an alternative seventh aircraft seat **7200f**. The alternative seventh aircraft seat device **7000f** has an alternative seventh console **7300f**. The alternative seventh aircraft seat device **7000f** is formed in mirror image to the seventh aircraft seat device **700f** about an axis, wherein the axis is oriented perpendicularly to the aircraft cabin center axis **16f** and parallel to the aircraft cabin floor **22f**. The aircraft seat arrangement **14f** comprises a plurality of further alternative seventh aircraft seat devices **7000'f** which are formed at least substantially identically to the alternative seventh aircraft seat device **7000f**. In contrast to the preceding exemplary embodiments, sitting directions **3100f**, **5100f**, **7100f** of some of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, **1000f**, **3000f**, **5000f**, **7000f** in the aircraft cabin section **26f** are oriented at least substantially in the opposite direction to the flight direction **24f**. In the present case, nine aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, **1000f**, **3000f**, **5000f**, **7000f** which are designed to be different from one another are arranged in the aircraft cabin section **26f**. (127) An arrangement of aircraft seat devices **100f**, **300f**, **3000f**, **700f**, **7000f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, **3000f**, **5000f**, **7000f** in the aircraft cabin section **26f** in the first outer seat column **36f** and the first inner seat column **38f** on the first aircraft cabin side **56f** is formed asymmetrically to an arrangement of aircraft seat devices **400f**, **500f**, **700f**, **5000f**, **7000f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, **3000f**, **5000f**, **7000f** in the second inner seat column **38f** and the second outer seat column **42f** on the second aircraft cabin side **58f**.

(128) There is an exclusive arrangement of aircraft seat devices **500f**, **700f**, **5000f**, **7000f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, the sitting directions **510f**, **710f**, **5100f**, **7100f** of which are arranged at least substantially parallel to the aircraft cabin center axis **16f**, in the first outer seat column **36f**. In the first outer seat column, the sitting directions of the seventh aircraft seat device **700f**, of the alternative fifth aircraft seat device **5000f**, of one of the further seventh aircraft seat devices **700'f**, of one of the further alternative fifth aircraft seat devices **5000'f** and one of the further alternative seventh aircraft seat devices **7000'f** are oriented along an aircraft longitudinal axis in an alternating manner in the flight direction **24f** and in the opposite direction to the flight direction **24f**.

(129) The aircraft seat arrangement **14f** comprises a plurality of additional consoles **62f**, **64f**, **66f**. In each case two foot spaces for two aircraft seat devices **1000f**, **3000f**, **500f**, **7000f**, **700f**, **5000f** arranged directly adjacent to the corresponding additional consoles **62f**, **64f**, **66f** are arranged in the additional consoles **62f**, **64f**, **66f**. The additional console **62f** is arranged in the first outer seat column **36f**, as viewed along an aircraft longitudinal axis, between the seventh aircraft seat device **700f** and the alternative fifth aircraft seat device **5000f**. The additional console **62f** spaces the seventh aircraft seat device **700f** apart from the alternative fifth aircraft seat device **5000f**. The sitting directions **710f**, **5100f** of the aircraft seat devices **700f**, **5000f**, which are spaced apart from

each other by the additional console **62f**, are oriented in an opposite direction to each other.

(130) The seventh aircraft seat device **700f**, the additional console **62f** and the alternative fifth aircraft seat device **5000f** form a seat grouping **68f** of the aircraft seat arrangement **14f** in the first outer seat column **36f**. The seat grouping **68f** has an at least substantially rectangular basic area. The seat grouping **68f** forms a periodically repeatable sequence. A plurality of identical seat groupings **68f** can be arranged directly one behind another along an aircraft longitudinal axis.

(131) In the first inner seat column **38f**, there is an exclusive arrangement of aircraft seat devices **100f**, **300f**, **1000f**, **3000f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, the sitting directions **110f**, **310f**, **1100f**, **3100f** of which are arranged at least substantially parallel to the aircraft cabin center axis **16f**. In the first inner seat column **38f**, there is an exclusive arrangement of aircraft seat devices **100f**, **300f**, **1000f**, **3000f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, the aircraft seats **120f**, **320f**, **1200f**, **3200f** of which are arranged in an alternating manner on the aisle side or facing away from the aisle. The first aircraft seat device **100f**, the third aircraft seat device **300f** and the further first aircraft seat device **100'f** are arranged directly one behind another. The third aircraft seat device **300f** spaces apart the first aircraft seat device **100f** from the further first aircraft seat device **100'f**. The additional console **64f** is arranged in the first inner seat column **38f**, as viewed along an aircraft longitudinal axis, between the first aircraft seat device **100f** and the alternative third aircraft seat device **3000f**. The additional console **64f** spaces apart the first aircraft seat device **100f** from the alternative third aircraft seat device **3000f**. The sitting directions **110f**, **3100f** of the aircraft seat devices **100f**, **3000f** which are spaced apart from each other by the additional console **64f** are oriented in an opposite direction to each other.

(132) In the second inner seat column **40f**, there is an exclusive arrangement of aircraft seat devices **500f**, **700'f**, **5000'f**, **7000f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, the sitting directions **510f**, **710f**, **5100f**, **7100f** of which are arranged at least substantially parallel to the aircraft cabin center axis **16f**. In the second inner seat column **40f**, there is an exclusive arrangement of aircraft seat devices **500f**, **700'f**, **5000'f**, **7000f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, the aircraft seats **520f**, **720f**, **5200f**, **7200f** of which are arranged in an alternating manner on the aisle side or facing away from the aisle.

(133) The fifth aircraft seat device **500f**, one of the further seventh aircraft seat devices **700'f** and the further fifth aircraft seat device **500'f** are arranged directly one behind another. The further seventh aircraft seat device **700'f** spaces apart the fifth aircraft seat device **500f** from the further fifth aircraft seat device **500'f**. The additional console **66f** is arranged in the second inner seat column **40f**, as viewed along an aircraft longitudinal axis, between the fifth aircraft seat device **500f** and the alternative seventh aircraft seat device **7000f**. The additional console **66f** spaces apart the fifth aircraft seat device **500f** from the alternative seventh aircraft seat device **7000f**. The sitting directions **510f**, **7100f** of the aircraft seat devices **500f**, **7000f** which are spaced apart from each other by the additional console **66f** are oriented in an opposite direction to each other. The first inner seat column **38f** is formed in mirror image to the second inner seat column **40f** via the aircraft cabin center axis **16f**.

(134) In the second outer seat column **42e**, there is an exclusive arrangement of aircraft seat devices **400f**, **400'f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, the aircraft seats **420f** of which are arranged facing away from the aisle. In the second outer seat column **42e**, there is an exclusive arrangement of aircraft seat devices **400f**, **400'f** of the plurality of aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, the sitting directions of which are arranged in an angled manner with respect to the aircraft cabin center axis **16f**.

(135) The aircraft seat arrangement **14f** illustrated in FIG. 9 is in principle extendable by further aircraft seat devices **100'f**, **300'f**, **400'f**, **500'f**, **700'f**, **3000'f**, **5000'f**, **7000'f**, as viewed in the flight direction **24f**.

(136) In the aircraft cabin section **26f**, the first aircraft seat device **100f**, the third aircraft seat device **300f**, the fourth aircraft seat device **400f**, the fifth aircraft seat device **500f**, the seventh

aircraft seat device **700f**, the alternative first aircraft seat device **1000f**, the alternative third aircraft seat device **3000f**, the alternative fifth aircraft seat device and the alternative seventh aircraft seat device **7000f** differ in at least one comfort category, wherein the aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, **1000f**, **3000f**, **5000f**, **7000f** for the at least one comfort category in each case have a different value from one another which is caused by a different arrangement of the aircraft seats **120f**, **320f**, **420f**, **520f**, **720f**, **1200f**, **3200f**, **5200f**, **7200f** and by the at least partially different design of the aircraft seat devices **100f**, **300f**, **400f**, **500f**, **700f**, **1000f**, **3000f**, **5000f**, **7000f**.

(137) In the present case, one comfort category is in the form of an aircraft seat orientation. A value for the aircraft seat orientation describes an angular deviation of the sitting direction from an aircraft longitudinal axis. The value for the aircraft seat device is in the form of an angle. The first aircraft seat device **100f**, the third aircraft seat device **300f**, the fifth aircraft seat device **500f**, the seventh aircraft seat device **700f**, the alternative first aircraft seat device **1000f**, the alternative third aircraft seat device **3000f**, the alternative fifth aircraft seat device **5000f** and the alternative seventh aircraft seat device **7000f** each have the same value for the aircraft seat orientation. For the aircraft seat orientation, the fourth aircraft seat device **400f** has a value which is greater than the value for the aircraft seat orientation of the first aircraft seat device **100f**. A further value for the aircraft seat orientation describes whether the sitting direction or a directional component of the sitting direction is directed in the flight direction **24f** or counter to the flight direction **24f**. The further value is in the form of “0” or “1” of a pair of values of a Boolean variable. The further value “0” corresponds to an orientation of the sitting direction or to a directional component of the sitting direction in the flight direction **24f**. The further value “1” corresponds to an orientation of the sitting direction or of a directional component of the sitting direction counter to the flight direction **24f**. In the present case, the first aircraft seat device **100f**, the third aircraft seat device **300f**, the fifth aircraft seat device **500f** and the seventh aircraft seat device **700f** each have a further value “0” for the aircraft seat orientation. The alternative first aircraft seat device **1000f**, the alternative third aircraft seat device **3000f**, the alternative fifth aircraft seat device **5000f** and the alternative seventh aircraft seat device **7000f** each have a further value “1” for the aircraft seat orientation.

(138) FIG. **10** shows an aircraft seat arrangement **14g** in a seventh exemplary embodiment. The aircraft seat arrangement **14g** is configured for use in an aircraft cabin **12g**, partially illustrated, of an aircraft. The aircraft cabin **12g** has an aircraft cabin center axis **16g**. The aircraft cabin center axis **16g** is in the form of an aircraft longitudinal axis. The aircraft cabin **12g** has two opposite aircraft cabin outer walls **18g**, **20g**. In at least one operating state, the aircraft has a flight direction **24g**. The aircraft cabin **12g** has an aircraft cabin section **26g** along the aircraft cabin center axis **16g**. The aircraft cabin **12g** has a first aircraft cabin aisle **32g** and a second aircraft cabin aisle **34g** in the aircraft cabin section **26g**. The aircraft seat arrangement **14g** comprises a first outer seat column **36g**. The aircraft seat arrangement **14g** comprises a first inner seat column **38g**. The aircraft seat arrangement **14g** comprises a second inner seat column **40g**. The aircraft seat arrangement **14g** comprises a second outer seat column **42g**. The aircraft cabin **12g** has a central region **44g**.

(139) The aircraft seat arrangement **14g** comprises a plurality of aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g** which are arranged in the aircraft cabin section **26g**. The plurality of aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g** are designed to be different from one another. The aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g** each have an aircraft seat. The aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g** each have a console. The aircraft seat arrangement **14g** comprises a first aircraft seat device **100g** of the plurality of aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g**. The first aircraft seat device **100g** has a sitting direction **110g**. The first aircraft seat device **100g** has a first aircraft seat **120g**. The first aircraft seat device **100g** has a first console **130g**. The aircraft seat arrangement **14g** comprises a second aircraft seat device **200g** of the plurality of aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g**. The second aircraft seat device **200g** has a sitting direction **210g**. The second aircraft seat device **200g** has a second aircraft

seat **220g**. The second aircraft seat device **200g** has a second console **230g**. The aircraft seat arrangement **14g** comprises a third aircraft seat device **300g** of the plurality of aircraft seat devices **100g, 200g, 300g, 400g, 500g, 600g, 700g, 800g**. The third aircraft seat device **300g** has a sitting direction **310g**. The third aircraft seat device **300g** has a third aircraft seat **320g**. The third aircraft seat device **300g** has a third console **330g**. The aircraft seat arrangement **14g** comprises a fourth aircraft seat device **400g** of the plurality of aircraft seat devices **100g, 200g, 300g, 400g, 500g, 600g, 700g, 800g**. The fourth aircraft seat device **400g** has a sitting direction **410g**. The fourth aircraft seat device **400g** has a fourth aircraft seat **420g**. The fourth aircraft seat device **400g** has a fourth console **430g**. The aircraft seat arrangement **14g** comprises a fifth aircraft seat device **500g** of the plurality of aircraft seat devices **100g, 200g, 300g, 400g, 500g, 600g, 700g, 800g**. The fifth aircraft seat device **500g** has a sitting direction **510g**. The fifth aircraft seat device **500g** has a fifth aircraft seat **520g**. The fifth aircraft seat device **500g** has a fifth console **530g**. The aircraft seat arrangement **14g** comprises a sixth aircraft seat device **600g** of the plurality of aircraft seat devices **100g, 200g, 300g, 400g, 500g, 600g, 700g, 800g**. The sixth aircraft seat device **600g** has a sitting direction **610g**. The sixth aircraft seat device **600g** has a sixth aircraft seat **620g**. The sixth aircraft seat device **600g** has a sixth console **630g**. The aircraft seat arrangement **14g** comprises a seventh aircraft seat device **700g** of the plurality of aircraft seat devices **100g, 200g, 300g, 400g, 500g, 600g, 700g, 800g**. The seventh aircraft seat device **700g** has a sitting direction **710g**. The seventh aircraft seat device **700g** has a seventh aircraft seat **720g**. The seventh aircraft seat device **700g** has a seventh console **730g**. The aircraft seat arrangement **14g** comprises an eighth aircraft seat device **800g** of the plurality of aircraft seat devices **100g, 200g, 300g, 400g, 500g, 600g, 700g, 800g**. The eighth aircraft seat device **800g** has a sitting direction **810g**. The eighth aircraft seat device **800g** has an eighth aircraft seat **820g**. The eighth aircraft seat device **800g** has an eighth console **830g**. (140) The aircraft seat arrangement **14g** comprises at least one further first aircraft seat device **100'g** which is formed at least substantially identically to the first aircraft seat device **100g**. The aircraft seat arrangement **14g** comprises a plurality of further second aircraft seat devices **200'g** which are formed at least substantially identically to the second aircraft seat device **200g**. The aircraft seat arrangement **14g** comprises a plurality of further third aircraft seat devices **300'g** which are formed at least substantially identically to the third aircraft seat device **300g**. The aircraft seat arrangement **14g** comprises at least one further fourth aircraft seat device **400'g** which is formed at least substantially identically to the fourth aircraft seat device **400g**. The aircraft seat arrangement **14g** comprises at least one further fifth aircraft seat device **500'g** which is formed at least substantially identically to the fifth aircraft seat device **500g**. The aircraft seat arrangement **14g** comprises a plurality of further sixth aircraft seat devices **600'g** which are formed at least substantially identically to the sixth aircraft seat device **600g**. The aircraft seat arrangement **14g** comprises a plurality of further seventh aircraft seat devices **700'g** which are formed at least substantially identically to the seventh aircraft seat device **700g**. The aircraft seat arrangement **14g** comprises at least one further eighth aircraft seat device **800'g** which is formed at least substantially identically to the eighth aircraft seat device **800g**.

(141) In contrast to the first exemplary embodiment, the aircraft seat arrangement **14g** comprises a plurality of alternative aircraft seat devices **4000g, 8000g** which are arranged in the aircraft cabin section **26g**. The aircraft seat arrangement **14g** comprises an alternative fourth aircraft seat device **4000g**. The alternative fourth aircraft seat device **4000g** has a sitting direction **4100g**. The sitting direction **4100g** of the alternative fourth aircraft seat device **4000g** has a directional component counter to the flight direction **24g**. The sitting direction **4100g** of the alternative fourth aircraft seat device **4000g** deviates from the flight direction **24g**. In the present case, the sitting direction **4100g** of the alternative fourth aircraft seat device **4000g** is oriented in an angled manner by 30 degrees with respect to the aircraft cabin center axis **16g**. The alternative fourth aircraft seat device **4000g** has an alternative fourth aircraft seat **4200g**. The alternative fourth aircraft seat device **4000g** has an alternative fourth console **4300g**. The alternative fourth aircraft seat device **4000g** is formed in

mirror image to the fourth aircraft seat device **400g** about an axis, wherein the axis is oriented perpendicularly to the aircraft cabin center axis **16g** and parallel to an aircraft cabin floor **22g** of the aircraft cabin **12g**. The aircraft seat arrangement **14g** comprises at least one further alternative fourth aircraft seat device **4000'g** which is formed at least substantially identically to the alternative fourth aircraft seat device **4000g**. The aircraft seat arrangement **14g** comprises an alternative eighth aircraft seat device **8000g**. The alternative eighth aircraft seat device **8000g** has a sitting direction **8100g**. The sitting direction **8100g** of the alternative eighth aircraft seat device **8000g** has a directional component counter to the flight direction **24g**. The sitting direction **8100g** of the alternative eighth aircraft seat device **8000g** deviates from the flight direction **24g**. In the present case, the sitting direction **8100g** of the alternative eighth aircraft seat device **8000g** is oriented in an angled manner by 30 degrees with respect to the aircraft cabin center axis **16g**. The alternative eighth aircraft seat device **8000g** has an alternative eighth aircraft seat **8200g**. The alternative eighth aircraft seat device **8000g** has an alternative eighth console **8300g**. The alternative eighth aircraft seat device **8000g** is formed in mirror image to the eighth aircraft seat device **800g** about an axis, wherein the axis is oriented perpendicularly to the aircraft cabin center axis **16g** and parallel to the aircraft cabin floor **22g**. The aircraft seat arrangement **14g** comprises at least one further alternative eighth aircraft seat device **8000'g** which is formed at least substantially identically to the alternative eighth aircraft seat device **8000g**.

(142) In the present case, the first inner seat column **38g** is formed symmetrically to the second inner seat column **40g** via the aircraft cabin center axis **16g**. In the present case, the first outer seat column **36g** is formed symmetrically to the second outer seat column **42g** via the aircraft cabin center axis **16g**. Sitting directions **4100g**, **8100g** of some of the plurality of aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g**, **4000g**, **8000g** are oriented in the aircraft cabin section **26g** at least substantially in the opposite direction to the flight direction **24g**. In the present case, ten aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g**, **4000g**, **8000g** which are designed to be different from one another are arranged in the aircraft cabin section **26g**.

(143) In the aircraft cabin section **26g**, four aircraft seat devices of the plurality of aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g**, **4000g**, **8000g**, namely at least the first aircraft seat device **100g**, the third aircraft seat device **300g**, the fourth aircraft seat device **400g** and the alternative fourth aircraft seat device **4000g**, are arranged in the first inner seat column **38g**. In contrast to the first exemplary embodiment, the second aircraft seat device **200a** from the first exemplary embodiment is replaced in the seventh exemplary embodiment by the alternative fourth aircraft seat device **4000g**. The aircraft seat arrangement **14g** comprises at least one additional console **62g**. In the first inner seat column **38g**, as viewed along an aircraft longitudinal axis, the additional console **62g** is arranged between the third aircraft seat device **300g** and the alternative fourth aircraft seat device **4000g**. The additional console **62g** spaces apart the third aircraft seat device **300g** from the alternative fourth aircraft seat device **4000g**. The sitting directions **310g**, **4100g** of the aircraft seat devices **300g**, **4000g** which are spaced apart from each other by the additional console **62g** are oriented in an opposite direction to each other. The aircraft seat arrangement **14g** has a first seat grouping **52g** of four aircraft seat devices arranged directly one behind another in the first inner seat column **38g** in the aircraft cabin section **26g**, namely the first aircraft seat device **100g**, the alternative fourth aircraft seat device **4000g**, the third aircraft seat device **300g** and the fourth aircraft seat device **400g**.

(144) In the aircraft cabin section **26g**, four aircraft seat devices of the plurality of aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g**, **4000g**, **8000g**, namely at least the fifth aircraft seat device **500g**, the seventh aircraft seat device **700g**, the eighth aircraft seat device **800g** and the alternative eighth aircraft seat device **8000g**, are arranged in the second inner seat column **40g**. In contrast to the first exemplary embodiment, the sixth aircraft seat device **600a** from the first exemplary embodiment is replaced in the seventh exemplary embodiment by the alternative eighth aircraft seat device **8000g**. The aircraft seat arrangement **14g** comprises at least one additional

console **64g**. The additional console **64g** is arranged in the second inner seat column **40g**, as viewed along an aircraft longitudinal axis, between the seventh aircraft seat device **700g** and the alternative eighth aircraft seat device **8000g**. The additional console **64g** spaces apart the seventh aircraft seat device **700g** from the alternative eighth aircraft seat device **8000g**. The sitting directions **710g**, **8100g** of the aircraft seat devices **700g**, **8000g** which are spaced apart from each other by the additional console **64g** are oriented in an opposite manner to each other. The aircraft seat arrangement **14g** has a second seat grouping **54g** of four aircraft seat devices arranged directly one behind another in the second inner seat column **40g** in the aircraft cabin section **26g**, namely the fifth aircraft seat device **500g**, the alternative eighth aircraft seat device **8000g**, the seventh aircraft seat device **700g** and the eighth aircraft seat device **800g**.

(145) In the aircraft cabin section **26g**, three aircraft seat devices differing in design, namely the further fifth aircraft seat device **500'g**, the sixth aircraft seat device **600g** and a further of the seventh aircraft seat devices **700'g**, are arranged in the first outer seat column **36g**. In the aircraft cabin section **26g**, the sixth aircraft seat device **600g**, the further seventh aircraft seat device **700'g** and the further fifth aircraft seat device **500'g** are arranged directly one behind another in the first outer seat column **36g**. In the first outer seat column **36g**, the further fifth aircraft seat device **500'g** and the sixth aircraft seat device **600g** are spaced apart from each other by the further seventh aircraft seat device **700'g**. In the aircraft cabin section **26g**, directly behind the sixth aircraft seat device **600g**, as viewed in the flight direction **24g**, a further of the sixth aircraft seat devices **600'g** is arranged.

(146) In the aircraft cabin section **26g**, three aircraft seat devices of differing design, namely the further first aircraft seat device **100'g**, the second aircraft seat device **200g** and a further of the third aircraft seat devices **300'g**, are arranged in the second outer seat column **42g**. In the aircraft cabin section **26g**, the second aircraft seat device **200g**, the further third aircraft seat device **300'g** and the further first aircraft seat device **100'g** are arranged directly one behind another in the second outer seat column **42g**. In the second outer seat column **42g**, the further first aircraft seat device **100'g** and the second aircraft seat device **200g** are spaced apart from each other by the further third aircraft seat device **300'g**. In the aircraft cabin section **26g**, directly behind the second aircraft seat device **200g**, as viewed in the flight direction **24g**, a further of the second aircraft seat devices **200'g** is arranged.

(147) In the aircraft cabin section **26g**, the first aircraft seat device **100g**, the second aircraft seat device **200g**, the third aircraft seat device **300g**, the fourth aircraft seat device **400g**, the fifth aircraft seat device **500g**, the sixth aircraft seat device **600g**, the seventh aircraft seat device **700g**, the eighth aircraft seat device **800g**, the alternative fourth aircraft seat device **4000g** and the alternative eighth aircraft seat device **8000g** differ in at least one comfort category, wherein the aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g**, **4000g**, **8000g** for the at least one comfort category in each case have a value which is different from one another and is caused by a different arrangement of the aircraft seats **120g**, **220g**, **320g**, **420g**, **520g**, **620g**, **720g**, **820g**, **4200g**, **8200g** and by the at least partially different design of the aircraft seat devices **100g**, **200g**, **300g**, **400g**, **500g**, **600g**, **700g**, **800g**, **4000g**, **8000g**.

Claims

1. An aircraft seat arrangement comprising a plurality of aircraft seat devices which are arranged in an aircraft cabin section and are designed to be at least partially different from one another and each have an aircraft seat which is designed as a full-flat seat, wherein the aircraft seat devices in the aircraft cabin section differ in at least one comfort category, wherein the aircraft seat devices for the at least one comfort category each have a mutually different value which is caused by a different arrangement of the aircraft seats and by the at least partially different design of the aircraft seat devices, wherein in one seat column in the aircraft cabin section at least three aircraft seat

devices of the plurality of aircraft seat devices are arranged in directly consecutive rows in a flight direction, the directly consecutive rows including a first row, a second row, and a third row, in the first row, a sitting direction of at least one of the at least three aircraft seat devices is arranged angled with respect to an aircraft longitudinal axis, in the second row and the third row, a sitting direction of at least two of the at least three aircraft seat devices is arranged substantially parallel to the aircraft longitudinal axis, a comfort category of the at least one of the at least three aircraft seat devices in the first row is configured to differ from a comfort category of the at least two of the at least three aircraft seat devices, wherein the comfort category in which the aircraft seat devices differ is one or more of living space size, bed width and/or length of a bed of the aircraft seat, delimited angle of movement from sitting position and/or lying position, maximum bed length in the lying position, and maximum foot space volume delimited by a console.

2. The aircraft seat arrangement as claimed in claim 1, wherein each of the plurality of aircraft seat devices in each case has a direct access to an aircraft cabin aisle.

3. The aircraft seat arrangement as claimed in claim 1, the comfort category further includes one or more of a base area, a foot space volume and/or a passage width, in at least one region.

4. The aircraft seat arrangement as claimed in claim 1, wherein in the first row the sitting direction of the at least one of the at least three aircraft seat devices is arranged angled with respect to the aircraft longitudinal axis, at an angle of at least 18 degrees.

5. The aircraft seat arrangement as claimed in claim 1, wherein in the aircraft cabin section, in the first row the sitting direction of the at least one of the at least three aircraft seat devices is directed away from a directly adjacent aircraft cabin aisle.

6. The aircraft seat arrangement as claimed in claim 1, wherein in the aircraft cabin section, in the first row the sitting direction of the at least one of the at least three aircraft seat devices is directed toward a directly adjacent aircraft cabin aisle.

7. The aircraft seat arrangement as claimed in claim 6, wherein an aircraft seat of an aircraft seat device of the aircraft seat devices which are arranged in the one seat column in the aircraft cabin section is arranged on an aisle side, wherein an aircraft seat of a further aircraft seat device of the aircraft seat devices which are arranged in the one seat column is arranged facing away from the aisle.

8. The aircraft seat arrangement as claimed in claim 6, further comprising at least one seat grouping of at least four aircraft seat devices of the plurality of aircraft seat devices, the at least four aircraft seat devices are arranged directly one behind another in the one seat column in the aircraft cabin section and each have different sitting directions and/or whose aircraft seats are arranged on an aisle side or facing away from the aisle.

9. The aircraft seat arrangement as claimed in claim 8, wherein in the one seat column in the aircraft cabin section, two aircraft seat devices of the plurality of aircraft seat devices each have an aircraft seat which is arranged on an aisle side, and two further aircraft seat devices of the plurality of aircraft seat devices which, as viewed in the flight direction, are arranged directly behind or in front of the two aircraft seat devices each have an aircraft seat which is arranged facing away from the aisle.

10. The aircraft seat arrangement as claimed in claim 8, wherein in the one seat column, the at least four aircraft seat devices are arranged directly one behind another, wherein one aircraft seat of one aircraft seat device of two aircraft seat devices of the at least four aircraft seat devices is arranged on an aisle side and a further aircraft seat of a further aircraft seat device of the two aircraft seat devices is arranged facing away from the aisle, and sitting directions of two further aircraft seat devices of the four aircraft seat devices including the at least one of the at least three aircraft seat devices are arranged in an angled manner with respect to the aircraft longitudinal axis, wherein one aircraft seat of one aircraft seat device of the two further aircraft seat devices is arranged on an aisle side and a further aircraft seat of a further aircraft seat device of the two further aircraft seat devices is arranged facing away from the aisle.

11. The aircraft seat arrangement as claimed in claim 8, wherein in the aircraft cabin section, two aircraft seat devices of the plurality of aircraft seat devices form a pair of seats in two seat columns which are arranged directly next to each other, wherein sitting directions of the two aircraft seat devices are arranged at least substantially parallel to the aircraft longitudinal axis, and aircraft seats of the two aircraft seat devices are arranged facing away from an aisle, wherein at least two of the pairs of seats are arranged in the two seat columns which are arranged directly next to each other.
 12. The aircraft seat arrangement as claimed in claim 8, wherein an arrangement of aircraft seat devices of the plurality of aircraft seat devices in the aircraft cabin section in at least one seat column on a first aircraft cabin side is formed asymmetrically to an arrangement of aircraft seat devices of the plurality of aircraft seat devices in at least one seat column on a second aircraft cabin side, wherein the first aircraft cabin side is separated from the second aircraft cabin side by an imaginary aircraft cabin center plane which is oriented along the aircraft longitudinal axis perpendicular to an aircraft cabin floor.
 13. The aircraft seat arrangement as claimed in claim 12, wherein in the at least one seat column on the first aircraft cabin side or the at least one seat column on the second aircraft cabin side, only such aircraft seat devices of the plurality of aircraft seat devices are arranged whose sitting directions are arranged in an angled manner with respect to the aircraft longitudinal axis.
 14. The aircraft seat arrangement as claimed in claim 12, wherein in the at least one seat column on the first aircraft cabin side or the at least one seat column on the second aircraft cabin side, only such aircraft seat devices of the plurality of aircraft seat devices are arranged whose sitting directions are arranged at least substantially parallel to the aircraft longitudinal axis.
 15. The aircraft seat arrangement as claimed in claim 12, wherein sitting directions in the aircraft cabin section are oriented at least substantially in an opposite direction to the flight direction.
 16. An aircraft seat device of an aircraft seat arrangement according to claim 1.
 17. An aircraft having an aircraft seat arrangement according to claim 1.
 18. The aircraft seat arrangement as claimed in claim 1, wherein the sitting directions of the at least three aircraft seat devices arranged in the directly consecutive rows further are oriented so as to face at least substantially in a same direction with respect to the flight direction.
 19. The aircraft seat arrangement as claimed in claim 1, wherein in the directly consecutive rows, four adjacent rows each having two aircraft seats are disposed along an aircraft cabin center axis of the aircraft cabin section, the four adjacent rows are arranged so that the two aircraft seats of the first row are each respectively placed directly adjacent to a respective aircraft cabin aisle and the sitting direction of the two aircraft seats of the first row is directed diagonally to the aircraft cabin center axis, the two aircraft seats of the second row are each located directly adjacent to each other and the sitting direction of the two aircraft seats of the second row is identical with the flight direction, the two aircraft seats of the third row are located directly adjacent to each other and the sitting direction of the two aircraft seats of the third row is each respectively directed diagonally to the adjacent respective aircraft cabin aisle, the two aircraft seats of a fourth row of the directly consecutive rows are each respectively placed directly adjacent to the respective aircraft cabin aisle and the sitting direction of the two aircraft seats of the fourth row is identical with the flight direction.
-