

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12416188
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Kim; Seung Wan et al.

Active hood hinge for vehicle

Abstract

An active hood hinge for a vehicle includes: a vehicle body bracket fixedly coupled to a vehicle body of a vehicle; a hood bracket fixedly coupled to a hood of the vehicle; an arm having a front end connected to the hood bracket, and a rear end connected to the vehicle body bracket; a lever connected to the arm; a locking pin having one side fixed to the lever and the other side protruding through the hood bracket and the arm; a locking bracket having one side fixed to the hood bracket and the other side coupled to the other side of the locking pin; and an actuator configured to push up the lever so that the locking bracket is damaged and the arm and the hood bracket are lifted when a frontal collision accident of the vehicle occurs.

Inventors:	Kim; Seung Wan (Daegu, KR), Kim; Dong Hyun (Daegu, KR)
Applicant:	PHA CO., LTD. (Daegu, KR)
Family ID:	1000008819610
Assignee:	PHA CO., LTD. (Daegu, KR)
Appl. No.:	18/496955
Filed:	October 30, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250137307 A1	May. 01, 2025

Publication Classification

Int. Cl.: E05D3/14 (20060101); B60R21/38 (20110101)

U.S. Cl.:

Field of Classification Search

CPC: B60R (21/38); B60R (21/34); E05D (3/145); E05D (3/14); E05D (3/06); E05Y (2900/536); B62D (25/12)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7552789	12/2008	Gust	180/69.24	E05D 3/145
2012/0084942	12/2011	Mehta	16/349	B60R 21/38
2014/0182962	12/2013	McIntyre, I	180/274	B60R 21/38
2015/0167369	12/2014	Hwang	16/233	E05D 7/1066
2016/0144822	12/2015	Kim	16/222	B60R 21/38
2017/0259776	12/2016	McLundie	N/A	B60R 21/38
2017/0282847	12/2016	Jenny	N/A	B60R 21/36
2017/0369028	12/2016	Patterson	N/A	E05D 11/08
2018/0141516	12/2017	Hwang	N/A	B60R 21/38
2019/0241150	12/2018	Fredriksson	N/A	B60R 21/38
2019/0375369	12/2018	Hufen	N/A	B60R 21/38
2020/0164831	12/2019	Wood	N/A	B62D 25/105
2020/0165851	12/2019	Page et al.	N/A	N/A
2020/0231113	12/2019	Weichsel	N/A	E05B 77/08
2021/0300295	12/2020	Sasaki	N/A	B60R 21/38
2022/0048462	12/2021	Boiger	N/A	B60R 21/38
2022/0136301	12/2021	Wood	16/295	B60R 21/38
2024/0253591	12/2023	McDonald	N/A	E05D 11/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102009040413	12/2010	DE	N/A
102015203516	12/2015	DE	N/A
1759937	12/2006	EP	N/A
2910872	12/2007	FR	N/A
10-1241017	12/2012	KR	N/A
10-1610945	12/2015	KR	N/A
2018-0004216	12/2017	KR	N/A

OTHER PUBLICATIONS

Extended European Search Report dated Apr. 8, 2024 in European Patent Application No. 23205732.3. cited by applicant

Primary Examiner: Morgan; Emily M

Attorney, Agent or Firm: AJU IP Global PLLC

Background/Summary

BACKGROUND

1. Field of the Invention

(1) The present disclosure relates to an active hood hinge for a vehicle, which relieves an impact on an upper body including a pedestrian's head by lifting a hood upon collision with the pedestrian.

2. Discussion of Related Art

(2) In general, hoods or bonnets in vehicles function to not only open and close an engine room but also block engine noises by shielding the engine room. The hood is coupled to a vehicle body above the engine room via a hood hinge, and the engine room is opened and closed as the hood rotates around the hood hinge.

(3) In the case of a traditional hood hinge, when a pedestrian collides with the front of the vehicle, the pedestrian's upper body including the pedestrian's head may hit the hood strongly, resulting in serious injury to the pedestrian. In recent years, an active hood hinge for alleviating an impact received by a pedestrian falling toward the hood has tended to be applied when the pedestrian collides with the front of the vehicle.

(4) The active hood hinge separates the hood from the engine and transmission positioned in the engine room by lifting the rear end of the hood when the pedestrian collides with the vehicle and falls toward the hood. Even when the pedestrian falls and collides with the lifted hood, the impact is absorbed as the hood is sufficiently bent, and the pedestrian's head does not collide strongly with the engine and transmission, so that it is possible to alleviate the pedestrian's impact and reduce the level of injury.

(5) However, there is a problem in that since the conventional active hood hinge is provided with a hook that is pressurized by a spring and a complex multi-bar link structure, the operation reliability is lowered and it is difficult to reduce the weight. In addition, there is also a problem in that the assembly productivity is lowered, and the manufacturing cost is increased.

(6) Background art for the present disclosure is disclosed in Korean Patent Registration Publication No. 10-1241017 (registered on Mar. 4, 2013, entitled HOOD HINGE DEVICE FOR REDUCING PEDESTRIAN'S INJURY).

SUMMARY OF THE INVENTION

(7) The present disclosure provides an active hood hinge for a vehicle, which can improve operation reliability, and reduce a weight and a size with a simple structure.

(8) The present disclosure provides an active hood hinge for a vehicle including: a vehicle body bracket fixedly coupled to a vehicle body of a vehicle; a hood bracket fixedly coupled to a hood of the vehicle; an arm having a front end connected to the hood bracket, and a rear end connected to the vehicle body bracket; a lever connected to the arm; a locking pin having one side fixed to the lever and the other side protruding through the hood bracket and the arm; a locking bracket having one side fixed to the hood bracket and the other side coupled to the other side of the locking pin; and an actuator configured to push up the lever so that the locking bracket is damaged and the hood bracket is lifted.

(9) The locking bracket may include: a body fixed to the hood bracket; and at least one finger protruding from the body to surround the locking pin.

(10) A notch, which is concavely recessed, may be formed at a boundary between the at least one finger and the body, and when the actuator pushes up the lever, the at least one finger may be transformed around the notch.

(11) A front end of the hood bracket may be connected to the front end of the arm, and when the actuator pushes up the lever, the hood bracket may rotate around the front end of the arm so that a rear end of the hood bracket is higher than the front end of the hood bracket.

- (12) The hood bracket may be fixedly coupled to a rear end of the hood, and when a front end of the hood is lifted in a state in which the actuator does not push up the lever, the hood bracket may move up so that a front end is higher than a rear end, and the arm may be fixed to the hood bracket and may move up so that the front end is higher than the rear end.
- (13) The active hood hinge for a vehicle according to the present disclosure may further include a rear end connection link including a lower end rotatably connected to a rear end of the vehicle body bracket, and an upper end rotatably connected to the rear end of the arm.
- (14) The hood bracket may be fixedly coupled to a rear end of the hood, and when a front end of the hood is lifted in a state in which the actuator does not push up the lever, the rear end connection link may rotate around the lower end of the rear end connection link so that the upper end of the rear end connection link moves from a position behind the lower end of the rear end connection link to a position in front of the lower end of the rear end connection link.
- (15) The active hood hinge for a vehicle may further include an intermediate connection link including a lower end rotatably connected between a front end and the rear end of the vehicle body bracket and an upper end rotatably connected between the front end and the rear end of the arm, and having a longer length than a length of the rear end connection link.
- (16) An active hood hinge for a vehicle according to the present disclosure has a simple structure in which a hood bracket is pushed up while a locking bracket coupled to a locking pin is damaged by a pressurizing force of an actuator, and does not have a hook that is pressurized by a spring or a multi-bar link structure.
- (17) Accordingly, it is possible to improve operation reliability in both cases in which a frontal collision accident of the vehicle occurs and does not occur, and it is easy to reduce the weight and size. In addition, it is possible to improve assembly productivity of the active hood hinge for a vehicle, and also reduce a manufacturing cost.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other objects, features and advantages of the present disclosure will become more apparent to those of ordinary skill in the art by describing in detail exemplary embodiments thereof with reference to the accompanying drawings, in which:
- (2) FIG. 1 is a perspective view showing an example of a vehicle to which an active hood hinge for a vehicle is applied;
- (3) FIGS. 2 and 3 are perspective views of an active hood hinge for a vehicle according to an embodiment of the present disclosure, FIG. 2 shows a state when a frontal collision accident does not occur viewed from a top front, and FIG. 3 shows a state when the frontal collision accident occurs viewed from a bottom back;
- (4) FIGS. 4 and 5 are front and back views of the active hood hinge for a vehicle according to the embodiment of the present disclosure, and views showing the state when the frontal collision accident does not occur; and
- (5) FIGS. 6 and 7 are front and back views of the active hood hinge for a vehicle according to the embodiment of the present disclosure, and views showing the state when the frontal collision accident occurs.

DETAILED DESCRIPTION OF EXEMPLARY EMBODIMENTS

- (6) Hereinafter, an active hood hinge for a vehicle according to an embodiment of the present disclosure will be described in detail with reference to the accompanying drawings. The terms used in this specification are terms used to appropriately express exemplary embodiments of the present disclosure, which may vary depending on the intention of a user or an operator, customs in the field to which the present disclosure pertains, and the like. Accordingly, the terms should be defined

based on the content throughout this specification.

(7) FIG. 1 is a perspective view showing an example of a vehicle to which an active hood hinge for a vehicle is applied, FIGS. 2 and 3 are perspective views of an active hood hinge for a vehicle according to an embodiment of the present disclosure, wherein FIG. 2 shows a state when a frontal collision accident does not occur viewed from a top front, and FIG. 3 shows a state when the frontal collision accident occurs viewed from a bottom back, FIGS. 4 and 5 are front and back views of the active hood hinge for a vehicle according to the embodiment of the present disclosure, and views showing the state when the frontal collision accident does not occur, and FIGS. 6 and 7 are front and back views of the active hood hinge for a vehicle according to the embodiment of the present disclosure, and views showing the state when the frontal collision accident occurs.

(8) Referring to FIG. 1, an active hood hinge 10 for a vehicle according to an embodiment of the present disclosure is installed between a hood 3 and a vehicle body 2 of a vehicle 1 and supports the hood 3 so that the hood 3 rotates with respect to the vehicle body 2 when an engine room of the vehicle 1 is open by opening the hood 3. In addition, the active hood hinge 10 for a vehicle protects a pedestrian by providing a buffer space, which may absorb an impact when an upper body including the pedestrian's head collides with the hood 3 by lifting a rear end 5 of the hood 3 in the event of a frontal collision accident in which a front end of the vehicle 1 collides with the pedestrian (not shown).

(9) The hood 3 functions as a cover configured to cover a top of the engine room. When the frontal collision accident occurs in a state in which the front end 4 of the hood 3 is caught on a latch 6, a sensor 7 installed on a bumper of the vehicle 1 detects the accident and transmits an accident occurrence signal to a controller 8. The controller 8 operates an actuator 60 (see FIGS. 2 to 7) by recognizing the occurrence of the frontal collision accident through the signal and transmitting a control signal. The rear end 5 of the hood 3 is lifted by an operation of the actuator 60, and the buffer space is formed between the engine and transmission, and the hood 3. A pair of active hood hinges 10 for a vehicle are installed in the vehicle 1, and specifically, are each installed at both ends of the vehicle 1 in a width direction.

(10) Referring to FIGS. 1 to 7 together, the active hood hinge 10 for a vehicle according to the embodiment of the present disclosure includes a vehicle body bracket 11, a hood bracket 20, an arm 30, a lever 40, a locking pin 71, a locking bracket 72, a rear end connection link 50, an intermediate connection link 55, and an actuator 60. The vehicle body bracket 11 is fixedly coupled to the vehicle body 2 under the rear end 5 of the hood 3. The vehicle body bracket 11 may be made of, for example, a steel material.

(11) The vehicle body bracket 11 includes, for example, a vehicle body fixing part 12 fixedly coupled to the vehicle body 2 using a bolt and a nut, and a wall part bent and protruding upward from the vehicle body fixing part 12. An actuator through hole 13 through which the actuator 60 passes is formed in the vehicle body fixing part 12. The hood bracket 20 may be made of, for example, a steel material, and is fixedly coupled to a lower surface of the rear end 5 of the hood 3. The hood bracket 20 includes a hood fixing part 21 fixedly coupled to the hood 3 using a bolt and a nut, and a wall part 24 bent and protruding downward from the hood fixing part 21.

(12) The arm 30 has a front end 31 connected to a front end 22 of the hood bracket 21, and a rear end 32 connected to the vehicle body bracket 11 by the rear end connection link 50. The arm 30 may be made of, for example, a steel material. The arm 30 includes an upper rib 34 and a lower rib 37 bent and protruding from a portion of an upper edge and a portion of a lower edge in a horizontal direction in order to increase a bending strength. In addition, an upper groove portion 35, which is recessed to be stepped, is provided at the upper edge of the arm 30 because the upper rib 34 does not extend. When the hood fixing part 21 of the hood bracket 20 is supported in contact with the upper groove portion 35, the upper rib 34 of the arm and the hood fixing part 21 do not have a stepped portion, so that a load of the hood 3 may be distributed and supported by the upper rib 34 of the arm 30 as well as the hood fixing part 21. The front end 22 of the hood bracket 20 and

the front end **31** of the arm **30** are connected to be rotatable with respect to each other by an arm pin **36** configured to thread and connect the front end **22** of the hood bracket **20** and the front end **31** of the arm **30**.

(13) The lever **40** is made of, for example, a steel material, and is connected to the arm **30** by a lever connection pin **42**. Specifically, the lever connection pin **42** threads and connects a part of the arm **30** closer to the front end **31** than the rear end **32** of the arm **30** and a lower end of the lever **40**. The lever **40** is rotatable with respect to the arm **30** around the lever connection pin **42**. The lever **40** includes a receiver **41** extending to protrude backward so as to cross an actuator axis (not shown) extending in a longitudinal direction of the actuator **60**.

(14) The actuator **60** pushes up the lever **40** so that the arm **30** and the hood bracket **20** are lifted as shown in FIGS. **3**, **6**, and **7** when the frontal collision accident of the vehicle **1** occurs. Specifically, the actuator **60** includes a cylinder **61** extending upward by passing through the actuator through hole **13** of the vehicle body bracket **11**, and a rod-shaped rod **63** inserted into an inside of the cylinder **61** so as to protrude upward from an upper end of the cylinder **61**. The cylinder **61** and the rod **63** may be made of, for example, a steel material. An explosive may be installed inside the cylinder **61**. When the explosive is detonated by a control signal of the controller **8**, the rod **63** rapidly moves up with a strong force by the explosive force, and the receiver **41** of the lever **40** positioned on a path where the rod **63** moves up is strongly lifted.

(15) The cylinder **61** may pass through the actuator fixing bracket **18** and may be fixedly coupled to the actuator fixing bracket **18**, and the front end and the rear end of the actuator fixing bracket **18** may be fixedly bonded to the vehicle body fixing part **12** of the vehicle body bracket **11**. With such a structure, the cylinder **61** of the actuator **60** may be fixed to the vehicle body bracket **11**.

(16) One side of the locking pin **71** is threaded and coupled to an upper end of the lever **40**, and the other side thereof passes through and protrudes from the arm **30** and the wall part **24** of the hood bracket **20**. The locking pin **71** may be made of, for example, a steel material. One side of the locking bracket **72** is fixed to the hood bracket **20** and the other side thereof is coupled to the other side of the locking pin **71**. Specifically, the locking bracket **72** includes a body **73** and a pair of fingers **74** protruding forward from the body **73**. The locking bracket **72** is coupled to the hood bracket **20** by a locking bracket coupling pin **77** configured to thread the wall part **24** of the hood bracket **20** and the body **73**.

(17) As shown in FIGS. **2** and **4**, when the rod **63** of the actuator **60** does not push up the lever **40**, the pair of fingers **74** surround an outer peripheral surface of the other side of the locking pin **71**. Accordingly, the hood bracket **20**, the arm **30**, and the lever **40** are connected so that the three members **20**, **30**, and **40** move together, and one of the three members **20**, **30**, and **40** may not move independently of the other two members.

(18) A pair of notches **75**, which are concavely recessed in an alphabetic V-shaped groove, are formed at a boundary between the pair of fingers **74** and the body **73**. When the rod **63** of the actuator **60** pushes up the receiver **41** of the lever **40**, as shown by the solid line in FIG. **6**, the pair of fingers **74** are transformed in directions separated from each other with respect to the pair of notches **75**. In other words, the locking bracket **72** is damaged. Accordingly, the locking pin **71** is separated from the locking bracket **72**, the arm **30** and the hood bracket **20** connected to the lever **40** by the locking pin **71** are lifted by a force at which the rod **63** of the actuator **60** pushes up the lever **40**, and the rear end **5** of the hood **3** fixedly supported by the hood bracket **20** is lifted.

(19) The rear end connection link **50** has a lower end rotatably connected to a rear end of the vehicle body bracket **11** and an upper end rotatably connected to the rear end **32** of the arm **30**. Specifically, the rear end connection link **50** is connected to the vehicle body bracket **11** rotatably around a first rear end link pin **51** by the first rear end link pin **51** configured to thread and connect the rear end of the wall part **15** of the vehicle body bracket **11** and the lower end of the rear end connection link **50**. In addition, the arm **30** is connected to the rear end connection link **50** rotatably around a second rear end link pin **52** by the second rear end link pin **52** configured to thread and

connect the rear end **32** of the arm **30** and the upper end of the rear end connection link **50**. The rear end connection link **50** may be made of, for example, a steel material.

(20) The intermediate connection link **55** has a lower end rotatably connected between a front end and the rear end of the vehicle body bracket **11** and an upper end rotatably connected between the front end **31** and the rear end **32** of the arm **30**. Specifically, the intermediate connection link **55** is connected to the vehicle body bracket **11** rotatably around a first intermediate link pin **56** by the first intermediate link pin **56** configured to thread and connect a portion between the front end and the rear end of the wall part **15** of the vehicle body bracket **11** and the lower end of the intermediate connection link **55**. In addition, the arm **30** is connected to the intermediate connection link **55** rotatably around a second intermediate link pin **57** by the second intermediate link pin **57** configured to thread and connect a portion between the front end **31** and the rear end **32** of the arm **30** and the upper end of the intermediate connection link **55**. A length of the intermediate connection link **55** is longer than a length of the rear end connection link **50**. The intermediate connection link **55** may be made of, for example, a steel material.

(21) In a state in which the frontal collision accident does not occur and the engine room of the vehicle **1** is not open, that is, a state in which the rod **63** of the actuator **60** does not push up the lever **40** and the front end **4** of the hood **3** is not lifted, the lever **40**, the arm **30**, and the hood bracket **20** do not move, and the locking bracket **72** is not damaged as shown by the solid lines in FIGS. **4** and **5**. At this time, the front end **31** of the arm **30** is positioned at a slightly lower height than the rear end **32**, and the front end **22** of the hood bracket **20** is also positioned at a slightly lower height than the rear end **23**. A position of the upper end of the rear end connection link **50**, specifically, a position **UP0** of the second rear end link pin **52** is positioned behind a position of the lower end of the rear end connection link **50**, specifically, a position of the first rear end link pin **51**.

(22) In a state in which the frontal collision accident does not occur but the engine room of the vehicle **1** is open, that is, a state in which the rod **63** of the actuator **60** does not push up the lever **40** but the front end **4** of the hood **3** is lifted, the lever **40**, the arm **30**, and the hood bracket **20** are connected to each other and move together because the locking bracket **72** is still not damaged as shown by the dashed-dotted lines in FIGS. **4** and **5**. In other words, the lever **40**, the arm **30**, and the hood bracket **20** are fixed relatively with respect to each other. In other words, the hood bracket **20** moves up so that the front end **22** is higher than the rear end **23**, and the arm **30** is also connected to the hood bracket **20** and moves up so that the front end **31** is higher than the rear end **32**.

(23) At this time, the arm **30** rotates around the upper end of the rear end connection link **50**, specifically, the second rear end link pin **52**, and rotates around the upper end of the intermediate connection link **55**, specifically, the second intermediate link pin **57**. At the same time, the rear end connection link **50** rotates around the lower end of the rear end connection link **50**, specifically, the first rear end link pin **51**, and the intermediate connection link **55** rotates around the lower end of the intermediate connection link **55**, specifically, the first intermediate link pin **56**. Accordingly, a position of the upper end of the rear end connection link **50**, that is, the second rear end link pin **52** moves from the position **UP0** behind a position **LP0** of the lower end of the rear end connection link **50**, that is, the first rear end link pin **51** to a position **UP1** in front of the position **LP0**. With this configuration, a driver may easily open and close the engine room by holding and lifting or moving the front end **4** of the hood **3** downward in an ergonomically comfortable posture.

(24) When the frontal collision accident occurs and the rod **63** of the actuator **60** pushes up the lever **40** with a strong impact, as shown in FIGS. **6** and **7**, a strong force and impact are transmitted to the locking bracket **72** through the locking pin **71** and thus the locking bracket **72** is damaged. Specifically, as shown by the solid line in FIG. **6**, the pair of fingers **74** may be transformed to be bent in a direction in which the pair of fingers **74** are separated from each other with respect to the pair of notches **75**, or in severe cases, at least one of the pair of fingers **74** may also be separately cut.

(25) In a state in which the coupling between the locking bracket **72** and the locking pin **71** is released, the force at which the rod **63** of the actuator **60** pushes up the lever **40** is transmitted to the arm **30** and the hood bracket **20** by the lever **40** and the locking pin **71** so that the arm **30** and the hood bracket **20** are lifted. The arm **30** moves up so that a height of the front end **31** and a height of the rear end **32** become substantially the same. At this time, the arm **30** rotates around the upper end of the rear end connection link **50**, specifically, the second rear end link pin **52**, and rotates around the upper end of the intermediate connection link **55**, specifically, the second intermediate link pin **57**. At the same time, the rear end connection link **50** rotates around the lower end of the rear end connection link **50**, specifically, the first rear end link pin **51**, and the intermediate connection link **55** rotates around the lower end of the intermediate connection link **55**, specifically, the first intermediate link pin **56**.

(26) However, rotation angles of the rear end connection link **50**, the intermediate connection link **55**, and the arm **30** are smaller than a rotation angle in a case in which the front end **4** of the hood **3** is lifted in the state in which the frontal collision accident does not occur. Accordingly, a position UP2 of the upper end of the rear end connection link **50**, that is, the second rear end link pin **52** moves forward from the position UP0 of the rear end link pin **52** in the case in which the frontal collision accident does not occur and the front end **5** of the hood **3** is not lifted, but is positioned behind the position UP1 of the rear end link pin **52** in the case in which the frontal collision accident does not occur and the front end **5** of the hood **3** is lifted to the maximum. In addition, the position UP2 of the rear end link pin **52** in the case in which the frontal collision accident occurs is still positioned behind the position LP0 of the first rear end link pin **51**.

(27) Meanwhile, when the rod **63** of the actuator **60** pushes up the lever **40**, the hood bracket **20** connected by the locking pin **71** rotates around the front end of the arm **30**, specifically, the arm pin **36**, so that the rear end **23** of the hood bracket **20** is higher than the front end **22** of the hood bracket **20**, and the hood fixing part **21** of the hood bracket **20** is spaced apart from the upper groove portion **35** of the arm **30**.

(28) The arm **30** is formed with a guide opening **33** extending in a direction centered on the lever connection pin **42** so that the lever **40** and the locking pin **71** may rotate around the lever connection pin **42** with respect to the arm **30** by the force at which the rod **63** of the actuator **60** pushes up the lever **40**. The locking pin **71** passes through the guide opening **33**.

(29) The wall part **24** of the hood bracket **20** is formed with a cam opening **25** through which the locking pin **71** passes. The cam opening **25** induces a rotation motion of the hood bracket **20** so that the rear end **23** of the hood bracket **20** is higher than the front end **22** thereof by the rotation of the hood bracket **20** around the arm pin **36** as the locking pin **71** rotates around the lever connection pin **42** with respect to the arm **30**.

(30) The above-described active hood hinge **10** for a vehicle has a simple structure in which the hood bracket **20** is pushed up as the locking bracket **73** coupled to the locking pin **71** is damaged by a pressurization force of the actuator **60** and does not have a hook that is pressurized by a spring or a multi-bar link structure. Accordingly, it is possible to improve operation reliability in both cases in which the frontal collision accident of the vehicle **1** occurs and does not occur, and it is easy to reduce the weight and the size. In addition, it is possible to improve the assembly productivity of the active hood hinge **10** for a vehicle, and also reduce the manufacturing cost.

(31) Although the present disclosure has been described with reference to one embodiment shown in the drawings, this is merely illustrative, and those skilled in the art to which the present technology pertains will understand that various modifications and equivalent other embodiments are possible.

Claims

1. An active hood hinge for a vehicle, comprising: a vehicle body bracket fixedly coupled to a vehicle body of a vehicle; a hood bracket fixedly coupled to a hood of the vehicle; an arm having a front end of the arm directly connected to the hood bracket, and a rear end of the arm indirectly connected to the vehicle body bracket via a rear end connection link; a lever connected to the arm; a locking pin having a first side of the locking pin fixed to the lever and a second side of the locking pin protruding through the hood bracket and the arm; a locking bracket having a first side of the locking bracket fixed to the hood bracket and a second side of the locking bracket coupled to the second side of the locking pin; and an actuator configured to push up the lever so that the locking pin is separated from the locking bracket and the hood bracket is lifted.
 2. The active hood hinge for the vehicle of claim 1, wherein the locking bracket includes: a body fixed to the hood bracket; and at least one finger protruding from the body to surround the locking pin.
 3. The active hood hinge for the vehicle of claim 2, wherein: the at least one finger comprises a pair of fingers, a notch, which is concavely recessed, is formed at a boundary between the pair of fingers and the body, and when the actuator pushes up the lever, the pair of fingers are transformed in directions separated from each other around the notch.
 4. The active hood hinge for the vehicle of claim 1, wherein: a front end of the hood bracket is connected to the front end of the arm, and when the actuator pushes up the lever, the hood bracket rotates around the front end of the arm so that a rear end of the hood bracket is higher than the front end of the hood bracket.
 5. The active hood hinge for the vehicle of claim 1, wherein the hood bracket is fixedly coupled to a rear end of the hood, and when a front end of the hood is lifted in a state in which the actuator does not push up the lever, the hood bracket moves up so that a front end of the hood bracket is higher than a rear end of the hood bracket, and the arm is fixed to the hood bracket and moves up so that the front end of the arm is higher than the rear end of the arm.
 6. The active hood hinge for the vehicle of claim 1, wherein the rear end connection link includes a lower end of the rear end connection link rotatably connected to a rear end of the vehicle body bracket, and an upper end of the rear end connection link rotatably connected to the rear end of the arm.
 7. The active hood hinge for the vehicle of claim 6, wherein the hood bracket is fixedly coupled to a rear end of the hood, and when a front end of the hood is lifted in a state in which the actuator does not push up the lever, the rear end connection link rotates around the lower end of the rear end connection link so that the upper end of the rear end connection link moves from a position behind the lower end of the rear end connection link to a position in front of the lower end of the rear end connection link.
 8. The active hood hinge for the vehicle of claim 6, further comprising an intermediate connection link including: a lower end of the intermediate connection link rotatable connected between a front end of the vehicle body bracket and the rear end of the vehicle body bracket, and an upper end of the intermediate connection link rotatably connected between the front end of the arm and the rear end of the arm and having a longer length than a length of the rear end connection link.
-