

# US Patent & Trademark Office

## Patent Public Search | Text View

---

|                      |                    |
|----------------------|--------------------|
| United States Patent | 12417479           |
| Kind Code            | B2                 |
| Date of Patent       | September 16, 2025 |
| Inventor(s)          | Yuki; Honami       |

---

### Recommendation device, system, method, and non-transitory computer-readable medium storing program

---

#### Abstract

A recommendation device includes: an acquisition unit configured to acquire a captured image; a personal authentication control unit configured to control to perform face authentication for a plurality of face regions detected from the captured image; a determination unit configured to determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; a specifying unit configured to specify an action in the group based on the point in a case where the group authentication has succeeded; an estimation unit configured to estimate a group attribute based on a personal attribute of each user belonging to the group; a selection unit configured to select recommendation information based on the group attribute and the action; and an output unit configured to output the selected recommendation information.

---

|                              |                                    |
|------------------------------|------------------------------------|
| <b>Inventors:</b>            | <b>Yuki; Honami (Tokyo, JP)</b>    |
| <b>Applicant:</b>            | <b>NEC Corporation (Tokyo, JP)</b> |
| <b>Family ID:</b>            | <b>1000008819684</b>               |
| <b>Assignee:</b>             | <b>NEC CORPORATION (Tokyo, JP)</b> |
| <b>Appl. No.:</b>            | <b>17/911724</b>                   |
| <b>Filed (or PCT Filed):</b> | <b>March 30, 2020</b>              |
| <b>PCT No.:</b>              | <b>PCT/JP2020/014463</b>           |
| <b>PCT Pub. No.:</b>         | <b>WO2021/199114</b>               |
| <b>PCT Pub. Date:</b>        | <b>October 07, 2021</b>            |

## Prior Publication Data

### Document Identifier

US 20230360101 A1

### Publication Date

Nov. 09, 2023

---

## Publication Classification

**Int. Cl.:** **G06K9/00** (20220101); **G06Q30/0601** (20230101); **G06V40/16** (20220101); **G06V40/50** (20220101)

**U.S. Cl.:**

**CPC** **G06Q30/0631** (20130101); **G06V40/171** (20220101); **G06V40/172** (20220101); **G06V40/50** (20220101);

## Field of Classification Search

**CPC:** G06V (40/172); G06V (10/764); G06V (10/774); G06V (10/82); G06V (40/168); G06V (40/175); G06V (40/103); G06V (40/171); G06V (40/174); G06V (40/50); G06F (16/9535); G06F (16/5838); G06F (16/51); G06F (18/214); G06F (18/24133); G06F (16/358); G06F (7/02); G06F (16/24578); G06F (16/532); G06F (16/70); G06F (16/9538); G06F (18/217); G06F (3/0482)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl.  | CPC          |
|--------------|-------------|---------------|-----------|--------------|
| 2009/0138805 | 12/2008     | Hildreth      | 715/745   | H04N 21/4755 |
| 2009/0167883 | 12/2008     | Nozaki        | 348/222.1 | H04N 1/2112  |
| 2021/0065260 | 12/2020     | Zheng         | N/A       | G06Q 30/0201 |

### FOREIGN PATENT DOCUMENTS

| Patent No.  | Application Date | Country | CPC |
|-------------|------------------|---------|-----|
| 2004-227158 | 12/2003          | JP      | N/A |
| 2012-208854 | 12/2011          | JP      | N/A |
| 2020-016696 | 12/2019          | JP      | N/A |

### OTHER PUBLICATIONS

International Search Report for PCT Application No. PCT/JP2020/014463, mailed on Jun. 23, 2020. cited by applicant

---

*Primary Examiner:* Liew; Alex Kok S

---

## Background/Summary

(1) This application is a National Stage Entry of PCT/JP2020/014463 filed on Mar. 30, 2020, the contents of all of which are incorporated herein by reference, in their entirety.

## TECHNICAL FIELD

(2) The present invention relates to a recommendation device, a system, a method, and a non-transitory computer-readable medium storing a program, and more particularly, to a recommendation device, a system, a method, and a non-transitory computer-readable medium storing a program for providing recommendation information to a user.

## BACKGROUND ART

(3) Patent Literature 1 discloses a technology of determining the number of persons and an attribute of a group from a captured image including a plurality of persons, selecting provision information to be provided according to the attribute of the group, and outputting the provision information.

## CITATION LIST

### Patent Literature

(4) Patent Literature 1: Japanese Unexamined Patent Application Publication No. 2004-227158

## SUMMARY OF INVENTION

### Technical Problem

(5) However, even in a case where group attributes are the same, effective recommendation information differs depending on actions of the groups. Therefore, the technology according to Patent Literature 1 has a problem that the accuracy of recommendation is insufficient.

(6) The present disclosure has been made to solve such a problem, and an object of the present disclosure is to provide a recommendation device, a system, a method, and a non-transitory computer-readable medium storing a program for providing appropriate recommendation information to a group.

### Solution to Problem

(7) A recommendation device according to the present disclosure includes: an acquisition unit configured to acquire a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; a personal authentication control unit configured to cause face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; a determination unit configured to determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; a specifying unit configured to specify an action in the group based on the point in a case where the group authentication has succeeded; an estimation unit configured to estimate a group attribute based on a personal attribute of each user belonging to the group; a selection unit configured to select recommendation information based on the group attribute and the action; and an output unit configured to output the selected recommendation information to a predetermined display terminal.

(8) A recommendation system according to the present disclosure includes: an imaging device configured to capture an image including a face region of a predetermined user; a recommendation device configured to be communicable with the imaging device; and an authentication device configured to store face feature information of the user and be communicable with the recommendation device, in which the recommendation device includes: an acquisition unit configured to acquire a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; a personal authentication control unit configured to cause the authentication device to perform face authentication for a plurality of face regions detected from the captured image; a determination unit configured to determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; a specifying unit configured to specify an action in the group based on the point in a case where the

group authentication has succeeded; an estimation unit configured to estimate a group attribute based on a personal attribute of each user belonging to the group; a selection unit configured to select recommendation information based on the group attribute and the action; and an output unit configured to output the selected recommendation information to a predetermined display terminal.

(9) A recommendation method according to the present disclosure performed by a computer includes: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; causing face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

(10) A non-transitory computer-readable medium according to the present disclosure records a program for performing: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; causing face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

(11) A recommendation device according to the present disclosure includes: an acquisition unit configured to acquire a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; an authentication unit configured to perform face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; a determination unit configured to determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; a specifying unit configured to specify an action in the group based on the point in a case where the group authentication has succeeded; an estimation unit configured to estimate a group attribute based on a personal attribute of each user belonging to the group; a selection unit configured to select recommendation information based on the group attribute and the action; and an output unit configured to output the selected recommendation information to a predetermined display terminal.

(12) A recommendation method according to the present disclosure performed by a computer includes: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; performing face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

(13) A non-transitory computer-readable medium according to the present disclosure records a program for performing: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; performing face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

#### Advantageous Effects of Invention

(14) According to the present disclosure, it is possible to provide the recommendation device, the system, the method, and the non-transitory computer-readable medium storing the program for providing appropriate recommendation information to a group.

---

## Description

### BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is a block diagram illustrating a configuration of a recommendation device according to a first example embodiment.
- (2) FIG. 2 is a flowchart illustrating a flow of a recommendation method according to the first example embodiment.
- (3) FIG. 3 is a block diagram illustrating a configuration of a recommendation device according to a second example embodiment.
- (4) FIG. 4 is a flowchart illustrating a flow of a recommendation method according to the second example embodiment.
- (5) FIG. 5 is a block diagram illustrating a configuration of a recommendation system according to a third example embodiment.
- (6) FIG. 6 is a block diagram illustrating a configuration of an authentication device.
- (7) FIG. 7 is a flowchart illustrating a flow of face feature information registration processing.
- (8) FIG. 8 is a flowchart illustrating a flow of face authentication processing.
- (9) FIG. 9 is a block diagram illustrating a configuration of a face authentication terminal.
- (10) FIG. 10 is a block diagram illustrating a configuration of a user terminal.
- (11) FIG. 11 is a block diagram illustrating a configuration of a recommendation device.
- (12) FIG. 12 is a flowchart illustrating a flow of recommendation processing.
- (13) FIG. 13 is a block diagram illustrating a configuration of a recommendation system according to a fourth example embodiment.
- (14) FIG. 14 is a block diagram illustrating a configuration of a recommendation device according to the fourth example embodiment.
- (15) FIG. 15 is a flowchart illustrating a flow of recommendation processing.
- (16) FIG. 16 is a diagram illustrating a recommendation information screen displayed on a display terminal.
- (17) FIG. 17 is a diagram illustrating a map displayed on the display terminal.
- (18) FIG. 18 is a diagram illustrating an action history displayed on the display terminal.

### EXAMPLE EMBODIMENT

(19) Hereinafter, example embodiments of the present disclosure will be described in detail with reference to the drawings. In the drawings, the same or corresponding elements are denoted by the same reference signs, and an overlapping description is omitted as necessary for clarity of

description.

#### First Example Embodiment

(20) FIG. 1 is a block diagram illustrating a configuration of a recommendation device **100** according to a first example embodiment. It is assumed that the recommendation device **100** may include at least an acquisition unit **112**, a personal authentication control unit **114**, a determination unit **115**, a specifying unit **116**, an estimation unit **117**, a selection unit **118**, and an output unit **119**, and may further include a storage unit **120**. The recommendation device **100** is connected to a network **500** (not illustrated). The network **500** may be a wired network or a wireless network. An authentication device **200**, a face authentication terminal **300**, a user terminal **400**, and the like (not illustrated) are connected to the network **500**.

(21) The storage unit **120** stores a set of identification information and personal attributes of a plurality of users as a group. Note that although the storage unit **120** is provided in the recommendation device **100** in the example illustrated in FIG. 1, the storage unit **120** may be provided outside the recommendation device **100**. The storage unit **120** may be provided in the authentication device **200**, for example. The acquisition unit **112** acquires a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point. The imaging device is, for example, the face authentication terminal **300** or the user terminal **400**. The personal authentication control unit **114** causes face authentication to be performed for a plurality of face regions detected from the captured image by using the authentication device **200** that stores face feature information of the plurality of users. In a case where the face authentication using each piece of face feature information of each user belonging to the group and any one of the plurality of detected face regions has succeeded, the determination unit **115** determines that group authentication has succeeded.

(22) In a case where the group authentication has succeeded, the specifying unit **116** specifies an action in the group based on the point. The estimation unit **117** estimates a group attribute based on the personal attribute of each user belonging to the group. The selection unit **118** selects recommendation information based on the group attribute and the action. The output unit **119** outputs the selected recommendation information to a predetermined display terminal. The display terminal is, for example, the face authentication terminal **300**, the user terminal **400**, a signage, or the like. The user terminal **400** is a communication terminal such as a smartphone carried by a user. The signage is a terminal installed on a street or the like, and displays, for example, “how about visiting ◦ ◦ next?” or the like when a user stands in front of the signage.

(23) FIG. 2 is a flowchart illustrating a flow of a recommendation method according to the first example embodiment. First, the storage unit **120** stores a set of identification information and personal attributes of a plurality of users as a group (Step **S101**). Next, the acquisition unit **112** acquires a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point (Step **S102**). Next, the personal authentication control unit **114** causes face authentication to be performed for a plurality of face regions detected from the captured image by using the authentication device **200** that stores face feature information of the plurality of users (Step **S103**). Once a face authentication request is received from the personal authentication control unit **114**, the authentication device **200** collates the face feature information included in the captured image with the face feature information registered in the authentication device **200**, and performs the face authentication by determining whether or not the authentication is successful based on whether or not the pieces of face feature information match each other. In a case where the face authentication has succeeded, the authentication device **200** includes, in the determination result, a user ID for which the authentication has succeeded, and transmits the determination result as a response to the recommendation device **100**.

(24) Next, in a case where the face authentication using each piece of face feature information of each user belonging to the group and any one of the plurality of detected face regions has succeeded, the determination unit **115** determines that group authentication has succeeded (Step

**S104**). Next, in a case where the group authentication has succeeded, the specifying unit **116** specifies an action in the group based on the point (Step **S105**). Next, the estimation unit **117** estimates a group attribute based on the personal attribute of each user belonging to the group (Step **S106**). Next, the selection unit **118** selects recommendation information based on the group attribute and the action (Step **S107**). Next, the output unit **119** outputs the selected recommendation information to a predetermined display terminal (Step **S108**). As described above, since the recommendation method according to the present example embodiment can present recommendation information based on a group attribute and an action, it is possible to provide appropriate recommendation information to a group.

(25) Note that the recommendation device **100** includes a processor, a memory, and a storage device as components not illustrated. Furthermore, the storage device stores a computer program in which processing of the recommendation method according to the present example embodiment is implemented. Then, the processor reads the computer program from the storage device into the memory, and executes the computer program. As a result, the processor implements the functions of the acquisition unit **112**, the personal authentication control unit **114**, the determination unit **115**, the specifying unit **116**, the estimation unit **117**, the selection unit **118**, and the output unit **119**.

(26) Alternatively, each of the storage unit **120**, the acquisition unit **112**, the personal authentication control unit **114**, the determination unit **115**, the specifying unit **116**, the estimation unit **117**, the selection unit **118**, and the output unit **119** may be implemented by dedicated hardware. In addition, some or all of the components of each device may be implemented by a general-purpose or dedicated circuitry, a processor, or the like, or a combination thereof. These may be implemented by a single chip or may be implemented by a plurality of chips connected via a bus. Some or all of the components of each device may be implemented by a combination of the above-described circuit or the like and a program. Furthermore, a central processing unit (CPU), a graphics processing unit (GPU), a field-programmable gate array (FPGA), or the like can be used as the processor.

(27) Furthermore, in a case where some or all of the components of the recommendation device **100** are implemented by a plurality of information processing devices, circuits, and the like, the plurality of information processing devices, circuits, and the like may be arranged in a centralized manner or in a distributed manner. For example, the information processing devices, the circuits, and the like may be implemented in a form in which each of them is connected via a communication network, such as a client server system or a cloud computing system. Furthermore, the function of the recommendation device **100** may be provided in a software as a service (SaaS) format.

### Second Example Embodiment

(28) A second example embodiment is a modification of the first example embodiment described above. The recommendation device **100** according to the first example embodiment performs face authentication by using the external authentication device **200**. On the other hand, a recommendation device **600** according to the present example embodiment performs face authentication inside the recommendation device **600**.

(29) FIG. **3** is a block diagram illustrating a configuration of the recommendation device **600** according to the second example embodiment. In the recommendation device **600**, the personal authentication control unit **114** in the configuration of the recommendation device **100** illustrated in FIG. **1** is replaced with an authentication unit **121**, and a face feature database (DB) (not illustrated) is further included. The face feature DB is a database that stores a user ID and face feature information in association with each other. For each component included in the recommendation device **600**, a description overlapping with that of the first example embodiment will be omitted as appropriate.

(30) The authentication unit **121** performs face authentication by using face feature information of a plurality of users stored in advance for a plurality of face regions detected from a captured image.

In the face authentication, the authentication unit **121** extracts a plurality of pieces of face feature information from the captured image, collates each piece of face feature information with the face feature information stored in the face feature DB, and determines whether or not the authentication is successful based on whether or not the pieces of face feature information match each other. The face feature DB stores face feature information of a plurality of registered users. The authentication unit **121** transmits, to the determination unit **115**, a result indicating the success or failure of the face authentication.

(31) FIG. **4** is a flowchart illustrating a flow of a recommendation method according to the second example embodiment. First, the storage unit **120** stores a set of identification information and personal attributes of a plurality of users as a group (Step **S201**). Next, the acquisition unit **112** acquires a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point (Step **S202**). Next, the authentication unit **121** performs face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance (Step **S203**). The authentication unit **121** extracts the face feature usage from the captured image, collates the face feature information included in the captured image with the face feature information registered in the face feature DB, and performs the face authentication by determining whether or not the authentication is successful based on whether or not the pieces of face feature information match each other.

(32) Next, in a case where the face authentication using each piece of face feature information of each user belonging to the group and any one of the plurality of detected face regions has succeeded, the determination unit **115** determines that group authentication has succeeded (Step **S204**). Next, in a case where the group authentication has succeeded, the specifying unit **116** specifies an action in the group based on the point (Step **S205**). Next, the estimation unit **117** estimates a group attribute based on the personal attribute of each user belonging to the group (Step **S206**). Next, the selection unit **118** selects recommendation information based on the group attribute and the action (Step **S207**). Next, the output unit **119** outputs the selected recommendation information to a predetermined display terminal (Step **S208**). The recommendation device according to the present example embodiment can achieve effects similar to the effects described in the first example embodiment.

### Third Example Embodiment

(33) A third example embodiment is a specific example of the first example embodiment described above. FIG. **5** is a block diagram illustrating a configuration of a recommendation system **700** according to the third example embodiment. The recommendation system **700** includes a recommendation device **100a**, an authentication device **200**, face authentication terminals **300** (**300X** and **300Y**), and a user terminal **400**. Each of the recommendation device **100a**, the authentication device **200**, the face authentication terminals **300** (**300X** and **300Y**), and the user terminal **400** is connected via a network **500**. Note that a description overlapping with the first example embodiment will be omitted as appropriate.

(34) The recommendation device **100a** is an information processing device that performs group authentication for a captured image obtained by imaging a plurality of persons, and in a case where the group authentication has succeeded, the recommendation device **100a** selects recommendation information based on an action and a group attribute of the group and outputs the recommendation information. The recommendation device **100a** is, for example, a server device implemented by a computer. The authentication device **200** is a device that performs face authentication. The authentication device **200** includes a face feature DB **210**. The face feature DB **210** is a face feature database that stores a user ID and face feature information of a corresponding user in association with each other. Note that the face feature DB **210** is an example of a face feature information storage unit.

(35) The face authentication terminal **300** is an information processing device that images a group visiting to each of points X and Y, transmits a group authentication request including a captured



image obtained by imaging a plurality of persons to the recommendation device **100a**, and receives and displays recommendation information in a case where the group authentication has succeeded. The face authentication terminal **300** is installed at each of the points X and Y. Specifically, the face authentication terminal **300X** is installed at the point X, and the face authentication terminal **300Y** is installed at the point Y. Hereinafter, it is assumed that a group of users exists at the point X as illustrated in FIG. 5. The group is an aggregate of a plurality of users. The user terminal **400** is an information processing device operated by a predetermined user. The user terminal **400** is, for example, a communication terminal such as a smartphone, a tablet, or a PC. The user terminal may perform processing similar to that of the face authentication terminal **300** or a part thereof.

(36) Next, a configuration of the authentication device **200** will be described in detail with reference to FIG. 6. FIG. 6 is a block diagram illustrating a configuration of the authentication device **200**. The authentication device **200** includes the face feature DB **210**, a face detection unit **220**, a feature point extraction unit **230**, a registration unit **240**, and an authentication unit **250**.

(37) The face feature DB **210** is a face feature database that stores a user ID and face feature information of a corresponding user in association with each other. The face detection unit **220** detects a face region included in a captured image and outputs the face region to the feature point extraction unit **230**. The feature point extraction unit **230** extracts a feature point from the face region detected by the face detection unit **220**, and outputs face feature information to the registration unit **240**. The face feature information is a set of extracted feature points.

(38) The registration unit **240** newly issues a user ID when registering the face feature information. The registration unit **240** registers the issued user ID and the face feature information extracted from the registered image in association with each other in the face feature DB **210**. The authentication unit **250** collates face feature information extracted from a face image with the face feature information in the face feature DB **210**. The authentication unit **250** determines that the face authentication has succeeded in a case where the pieces of face feature information match each other, and determines that the face authentication has failed in a case where the pieces of face feature information do not match each other. The authentication unit **250** transmits a result indicating the success or failure of the face authentication as a response to the recommendation device **100a**. Whether or not the pieces of face feature information match each other corresponds to the success or failure of the authentication. In addition, in a case where the face authentication has succeeded, the authentication unit **250** specifies a user ID associated with the face feature information for which the authentication has succeeded, and transmits an authentication result including the specified user ID and the fact that the authentication has succeeded to the recommendation device **100a**.

(39) An operation of the authentication device **200** when registering a user ID and face feature information in the face feature DB **210** will be described with reference to FIG. 7. FIG. 7 is a flowchart illustrating a flow of face feature information registration processing.

(40) When registering face feature information, a face information registration terminal (not illustrated) captures an image including a face of a user as a registration image, and transmits a face feature information registration request to the authentication device **200** via the network **500**. The face information registration terminal is, for example, an information processing device such as a personal computer, a smartphone, or a tablet terminal. The face information registration terminal is, for example, the user terminal **400**. The face feature information registration request includes the registration image. First, the authentication device **200** acquires the registration image included in the face feature information registration request from the face information registration terminal via the network **500** (Step S301).

(41) Next, the face detection unit **220** detects a face region included in the registration image (Step S302), and outputs the detected face region to the feature point extraction unit **230**. Next, the feature point extraction unit **230** extracts a feature point from the face region and outputs face feature information to the registration unit **240** (Step S303). Next, the registration unit **240** issues a

user ID corresponding to the output face feature information, and registers the user ID and the face feature information in association with each other in the face feature DB **210** (Step **S304**).

(42) An operation of the authentication device **200** when performing the face authentication will be described with reference to FIG. **8**. FIG. **8** is a flowchart illustrating a flow of face authentication processing. When performing the face authentication, the face authentication terminal **300** captures, as an authentication image, an image including a face of a user, and transmits a face authentication request to the recommendation device **100a** via the network **500**. The face authentication request includes the authentication image. First, the recommendation device **100a** transmits a face region or face feature information extracted from the authentication image to the authentication device **200**. The feature point extraction unit **230** acquires the face feature information by extracting the face feature information from the received face region or by receiving the face feature information (Step **S301**).

(43) Next, the authentication unit **250** collates the acquired face feature information with that in the face feature DB **210** (Step **S302**). In a case where the pieces of face feature information match each other (Yes in Step **S303**), the authentication unit **250** specifies a user ID of the user whose face feature information matches (Step **S304**), and transmits, as a response, the fact that the face authentication has succeeded and the specified user ID to the recommendation device **100a** (Step **S305**). In a case where there is no face feature information that matches with the acquired face feature information (No in Step **S303**), the authentication unit **250** transmits, as a response, the fact that the face authentication has failed to the recommendation device **100a** (Step **S306**). The authentication device **200** can estimate the age group and gender of the user based on the face feature information. In Step **S306**, the authentication unit **250** transmits, as a response, the estimated age group and gender to the recommendation device **100a**.

(44) Next, a configuration of the face authentication terminal **300** will be described in detail with reference to FIG. **9**. The face authentication terminal **300** includes an imaging device such as a camera, a display device, and a computer as hardware components. The face authentication terminal **300** is a device that requests for group authentication by face authentication. Examples of the face authentication terminal **300** include, but are not limited to, a terminal that performs payment by face authentication, a terminal that performs entrance control by face authentication, a digital signage that presents information according to face authentication, and the like.

(45) FIG. **9** is a block diagram illustrating a configuration of the face authentication terminal **300**. The face authentication terminal **300** includes a camera **310**, a storage unit **320**, a communication unit **330**, a display unit **340**, and a control unit **350**. The camera **310** is an imaging device that captures an image. The storage unit **320** is a storage device that stores a program for implementing each function of the face authentication terminal **300**. The communication unit **330** is a communication interface with the network **500**. The display unit **340** is a display device that displays a group authentication result, recommendation information, and the like to a user. The control unit **350** controls hardware included in the face authentication terminal **300**. The control unit **350** includes an imaging unit **352**, a registration unit **353**, an authentication unit **354**, and a payment unit **355**.

(46) The imaging unit **352** transmits an imaging request to the camera **310**. The camera **310** captures an image including a face of each user included in a group. The image captured by the camera **310** is used as the registration image and the authentication image. The registration unit **353** transmits the face feature information registration request to the authentication device **200** via the network **500**. The face feature information registration request includes the registration image captured by the camera **310**. The authentication unit **354** transmits the group authentication request to the recommendation device **100a** via the network **500**. The group authentication request includes the authentication image captured by the camera **310**. The authentication unit **354** receives a result indicating the success or failure of the group authentication from the recommendation device **100a**, and causes the display unit **340** to display the result.

(47) The payment unit **355** performs the payment processing in a case where the group authentication has succeeded. Note that the control unit **350** may include a recording unit (not illustrated) instead of the payment unit **355**. The recording unit records entrance and leaving of each user to and from a facility where the face authentication terminal **300** is installed in a case where the group authentication has succeeded.

(48) Next, a configuration of the user terminal **400** will be described in detail with reference to FIG. **10**. FIG. **10** is a block diagram illustrating a configuration of the user terminal **400**. The user terminal **400** includes a camera **410**, a storage unit **420**, a communication unit **430**, a display unit **440**, and a control unit **450**. The control unit **450** includes an imaging unit **452**, a registration unit **453**, an authentication unit **454**, and a payment unit **455**. Since the function of each component included in the user terminal **400** is similar to that of each component included in the face authentication terminal **300**, a description thereof will be omitted.

(49) The face authentication terminal **300** and the user terminal **400** have a function of transmitting the face feature information registration request and the group registration request. A flow of face feature information registration processing and group registration processing will be described below. Note that a case where the user terminal **400** performs the face feature information registration processing and the group registration processing will be described, but the face authentication terminal **300** may perform similar processing.

(50) First, the face feature information registration processing will be described. First, the imaging unit **452** controls the camera **410** to capture a registration image of a user. Next, the registration unit **453** transmits a face feature information registration request including a face region extracted from the registration image to the authentication device **200** via the network **500**. Finally, the registration unit **453** receives the face authentication result from the authentication device **200**. Note that the registration unit **453** may transmit a face information registration request including face feature information extracted from the registration image to the authentication device **200**.

(51) Next, the group registration processing will be described. First, the user terminal **400** individually performs the face information registration processing described above according to an operation of each user included in a group. Next, the user terminal **400** transmits a group registration request to the recommendation device **100a** according to an operation of an arbitrary user in the group, and registers the definition of the member belonging to the group.

(52) Next, a configuration of the recommendation device **100a** will be described in detail with reference to FIG. **11**. FIG. **11** is a block diagram illustrating a configuration of the recommendation device **100a**. The recommendation device **100a** includes a control unit **110**, a storage unit **120**, a memory **130**, and a communication unit **140**.

(53) The storage unit **120** is a storage device that stores group information **123**, a program **124**, history information **125**, a recommendation condition **126**, and recommendation information **127**. The group information **123** is information in which a user ID of each user included in a group is associated with a group ID **123a**. The group ID **123a** is identification information that enables identification of the group. The user ID is identification information that enables identification of the user, and is, for example, a name, a telephone number, an e-mail address, an arbitrary identification number, or the like. User IDs **123b** and **123c** are associated with attribute information **123d** and **123e**, respectively. That is, in the storage unit **120**, identification information of a plurality of users belonging to a group and personal attribute information of each user are associated with identification information of the group. Examples of the attribute information **123d** and **123e** include a gender, an age, a hobby, physical information, and the like, but are not limited thereto. Hereinafter, each of the attribute information **123d** and **123e** associated with each user ID may be referred to as a “personal attribute”. The program **124** is a computer program in which the recommendation processing according to the present example embodiment is implemented. The history information **125** is information in which a group ID **125a** and a point ID are associated with each other. The point ID is identification information of a point where the face authentication

terminal **300** is installed.

(54) The recommendation information **127** is associated with the recommendation condition **126**. The recommendation condition **126** is a combination of a group attribute and a point ID. The recommendation information **127** is information presented in a case where the associated recommendation condition **126** is satisfied. The recommendation information **127** is, for example, presentation information presented for guiding to a predetermined point, presentation information presented for guiding to a point different from the current point, or the like.

(55) The memory **130** is a storage region for temporarily storing processing contents of the control unit **110**, and is, for example, a volatile storage device such as a random access memory (RAM). The communication unit **140** is an interface that communicates with the outside of the recommendation device **100a**.

(56) The control unit **110** includes a registration unit **111**, an acquisition unit **112**, a region detection unit **113**, a personal authentication control unit **114**, a determination unit **115**, a specifying unit **116**, an estimation unit **117**, a selection unit **118**, and an output unit **119**. The control unit **110** is a control device that controls the operation of the recommendation device **100a**, and is, for example, a processor such as a CPU. The control unit **110** reads the program **124** from the storage unit **120** into the memory **130** and executes the program **124**. As a result, the control unit **110** implements the functions as the registration unit **111**, the acquisition unit **112**, the region detection unit **113**, the personal authentication control unit **114**, the determination unit **115**, the specifying unit **116**, the estimation unit **117**, the selection unit **118**, and the output unit **119**.

(57) The registration unit **111** receives the group registration request from the face authentication terminal **300** or the user terminal **400** via the network **500**. The registration unit **111** issues the group IDs **123a** corresponding to a plurality of user IDs included in the received group registration request. The registration unit **111** generates the group information **123** in which the user IDs **123b** and **123c** are associated with the issued group ID **123a**, and registers the group information **123** in the storage unit **120**.

(58) In a case where a group ID and one or more user IDs are included in the group registration request, the registration unit **111** may search the storage unit **120** for the group ID included in the received group registration request. In such a case, the registration unit **111** further associates the user ID included in the received group registration request with the found group ID, and updates the group information **123**. Note that the group registration processing is not limited thereto.

(59) The acquisition unit **112** acquires a captured image from the imaging device. Note that it is assumed that the captured image includes face regions of a plurality of persons. The region detection unit **113** detects a face region from the captured image. For example, the region detection unit **113** analyzes the captured image to recognize a plurality of face regions. In a case where a plurality of face regions have been specified, the personal authentication control unit **114** causes the authentication device **200** to perform face authentication using a set of face feature information for each specified face region.

(60) The determination unit **115** determines whether or not the group authentication is successful. In a case where the face authentication using each piece of face feature information of each user belonging to the group and any one of the plurality of detected face regions has succeeded, the determination unit **115** determines that group authentication has succeeded. In a case where the face authentication has succeeded for at least one of the users belonging to the group, and the face authentication has failed for the other users, the determination unit **115** determines whether or not the group authentication is successful based on the age group and gender of the user received from the authentication device **200**. In this case, the determination unit **115** collates the attribute information **123d** and **123e** associated with the group ID **123a** of the group to which the user whose face authentication has succeeded belongs with the age group and gender of each user received from the authentication device **200**, and determines whether or not the group authentication is successful based on whether or not the attribute information and the age group and gender match

each other. In a case where the group authentication has succeeded, the determination unit **115** registers, as the history information **125** in the storage unit **120**, the point ID of the point for which the group authentication has succeeded and in which the imaging device is installed.

(61) Note that, in a case where the face authentication has failed for at least one of the plurality of face regions, the determination unit **115** may extract the face feature information from the face region for which the face authentication has failed, and estimate the attribute information (for example, the age group and gender) of the user based on the extracted face feature information. In this case, the determination unit **115** may collate the estimated attribute information of the user with the attribute information **123d** and **123e** of other users associated with the group ID **123a** of the group to which the user whose face authentication has succeeded belongs, and determine that the group authentication has succeeded in a case where a certain number or more of pieces of the attribute information match. In other words, in a case where the face authentication of some users belonging to the group has succeeded and the face authentication of other users has failed, the determination unit **115** may estimate the personal attribute based on the face region for which the face authentication has failed. In this case, the determination unit **115** determines whether or not the group authentication is successful according to the degree of matching between the estimated personal attribute and the personal attribute of each user belonging to the group.

(62) For example, it is assumed that, in a case where face authentication is performed for a group including a couple and one child, pieces of face feature information of the couple (father and mother) are registered in advance and face feature information of the child is not registered. In a case where the face authentication is performed with a captured image including the faces of the family of three, the face authentication of the couple succeeds, but the face authentication of the child fails. At this time, the ages and genders of the couple are specified by the face authentication, and the age of the child is estimated based on the face feature information extracted from the captured image. Therefore, even in a case where the face feature information of the child is unregistered, the recommendation device **100a** can estimate that the group attribute of the group is a family of three.

(63) In addition, in a case where each face region for which the face authentication using the face feature information of each user belonging to the group has succeeded is within a predetermined range, the determination unit **115** may register the point ID of the point as the history information **125** in the storage unit **120**. That is, the determination unit **115** may authenticate only users close to each other to some extent as a group. For example, in a case where users who do not belong to a group unintentionally appear in the same frame, it is inappropriate to authenticate all users appearing in the captured image as one group. By authenticating only users close to each other to some extent as a group, the accuracy of the group authentication can be improved.

(64) In a case where the group authentication has succeeded, the specifying unit **116** specifies an action of the group. The specifying unit **116** specifies the action of the group by referring to the point ID **125b** registered as the history information **125** in the storage unit **120**. The estimation unit **117** estimates a group attribute based on the personal attribute of each user belonging to the group. The selection unit **118** selects recommendation information based on the group attribute estimated by the estimation unit **117** and the action specified by the specifying unit **116**. The output unit **119** outputs the recommendation information selected by the selection unit **118** to a predetermined display terminal. The display terminal is, for example, the face authentication terminal **300**, the user terminal **400**, a signage, or the like.

(65) Next, an operation of the recommendation device **100a** at the time of recommendation processing will be described with reference to FIG. **12**. FIG. **12** is a flowchart illustrating a flow of the recommendation processing. A case where a user ID of a user UA1, a user ID of a user UA2, and a user ID of a user UA3 are registered in association with each other as a group A in the storage unit **120** will be described.

(66) First, the acquisition unit **112** included in the recommendation device **100a** acquires a captured

image from the imaging device (Step S501). Next, the region detection unit **113** detects a plurality of face regions from the captured image (Step S502). Next, the personal authentication control unit **114** causes the authentication device **200** to perform the face authentication for each specified face region, and receives the face authentication result (Steps S503 to S506).

(67) After the face authentication is performed for all the face regions specified in Step S502, the determination unit **115** determines whether or not the face authentication has succeeded for all the users belonging to the group (Step S507). For example, in a case where the ID of the user UA1, the ID of the user UA2, and the ID of the user UA3 have been received as the face authentication result, the determination unit **115** determines that the face authentication has succeeded for all the users belonging to the group.

(68) In a case where the face authentication has succeeded for all the users belonging to the group (Yes in Step S507), the determination unit **115** registers, in the storage unit **120**, the point ID of the point for which the group authentication has succeeded and in which the imaging device is installed as the history information **125** associated with the group ID **125a** (Step S508). Next, the specifying unit **116** specifies an action of the group by referring to the point ID **125b** registered as the history information **125** in the storage unit **120** (Step S509). In a case where the face authentication has succeeded for all the users belonging to the group (Yes in Step S507), the estimation unit **117** estimates a group attribute based on a personal attribute of each user belonging to the group (Step S510).

(69) Next, the selection unit **118** selects recommendation information based on the group attribute estimated in Step S510 and the action specified in Step S509 (Step S511). Next, the output unit **119** outputs the recommendation information selected in Step S511 to a predetermined display terminal (Step S512).

(70) In a case where there is a user whose face authentication has failed among the users belonging to the group (No in Step S507), the determination unit **115** determines whether or not the face authentication has failed only for some of the users belonging to the group (Step S513). A state in which the face authentication has failed only for some of the users belonging to the group is a state in which the face authentication has succeeded for at least one of the users belonging to the group and the face authentication has failed for the other users. For example, in a case where the user ID of the user UA1 and the user ID of the user UA2 have been received as the face authentication result, and the user ID of the user UA3 is not received, the determination unit **115** determines that the face authentication has failed for only some of the users belonging to the group. For example, in a case where none of the ID of the user UA1, the ID of the user UA2, and the ID of the user UA3 has been received as the face authentication result, the determination unit **115** determines that the face authentication has failed for all the users belonging to the group.

(71) In a case where the face authentication of the user has failed, the authentication device **200** estimates the age group and gender of the user based on the face feature information, and transmits, as a response, the estimation result to the recommendation device **100a**. In a case where the face authentication has failed for only some of the users belonging to the group (Yes in Step S513), the determination unit **115** specifies the group ID **123a** including the user IDs **123b** and **123c** of the users whose face authentication has succeeded (Step S514). Next, the determination unit **115** collates the personal attribute associated with the group ID **123a** specified in Step S514 with the age group and gender of the user received from the authentication device **200** (Step S515).

(72) In a case where the personal attribute matches (Yes in Step S515), the recommendation device **100a** outputs recommendation information according to the procedures illustrated in Steps S508 to S512. In a case where the personal attribute does not match (No in Step S515), the output unit **119** outputs the fact that the face authentication has failed (Step S516). The output destination in Step S516 may be the user terminal **400** operated by the user whose face authentication has succeeded, or may be a display terminal that does not depend on the user, such as the face authentication terminal **300** or a signage.

(73) The determination unit **115** may specify a user whose face authentication has failed based on a difference between the user IDs **123b** and **123c** of all the users belonging to the group and the user ID of the user whose face authentication has succeeded. Then, the output unit **119** may output the fact that the face authentication has failed for a specific user to the user terminal **400** operated by the user. In addition, the output unit **119** may notify the user of the reason why the group authentication has failed. The reason why the group authentication has failed is, for example, that the user is away from other users belonging to the group, that the face authentication of the user has failed, and the like. Here, the determination unit **115** may notify the user of re-imaging guidance in such a way that the user approaches other users belonging to the group or faces the camera.

(74) In a case where the face authentication has failed for all the users belonging to the group (No in Step **S513**), the output unit **119** outputs the fact that the face authentication has failed (Step **S516**). The output destination in this case is, for example, a display terminal that does not depend on the user, such as the face authentication terminal **300** and a signage.

(75) Note that the output destination of the recommendation information in Step **S512** may be a display device installed at a point different from the point where the action of the group has been specified. Furthermore, the output of the recommendation information (Step **S512**) may be performed immediately after the recommendation information is selected (Step **S511**), or may be performed after a while. That is, a timing at which the recommendation information is output may deviate from a timing at which the recommendation information is selected. For example, it is assumed that a group visits a bowling alley and an image including faces is captured with a signage or the like installed in the bowling alley. At this time, the recommendation device **100a** causes the face authentication to be performed based on the captured image, and selects recommendation information based on a group attribute and an action of the group. When the face authentication is performed in a signage installed in a facility or on a road that the group visited next time, the recommendation device **100a** outputs the selected recommendation information to the signage. In this manner, the recommendation information may be output to a signage installed at a point different from the bowling alley.

(76) Hereinafter, specific examples of the recommendation condition **126** and the corresponding recommendation information **127** will be described. For example, in a case where the recommendation condition **126** is that “the group attribute indicates that only young people are included, and the point ID is an ID of a bowling alley”, the recommendation information **127** is “guidance information to an all-you-can-eat restaurant”. A group staying in a bowling alley is considered to have a meal after playing blowing. In addition, a group including only young people is considered to prefer an all-you-can-eat restaurant.

(77) In a case where the recommendation condition **126** is “the group attribute indicates that only females are included, and the point ID is an ID of a bookstore”, the recommendation information **127** is “guidance information to a predetermined cafe”. A group staying in a bookstore is considered to take a break after visiting the bookstore. In addition, a group including only females is considered to prefer a cafe as a rest place. In a case where the recommendation condition **126** is that “the group attribute indicates an elderly couple, and the point ID is an ID of a station”, the recommendation information **127** is “guidance information to a restaurant directly connected to the station”. A group staying in a station is considered to have a meal after visiting the station. In addition, a group of an elderly couple is considered to prefer a restaurant near the current location.

(78) In a case where the recommendation condition **126** is that “the group attribute indicates that only males are included, and the point ID is an ID of an automobile showroom”, the recommendation information **127** is “guidance information to a restaurant of a foreign car manufacturer”. A group staying in an automobile showroom is considered to take a break after visiting the automobile showroom. In addition, a group including only males and visiting an automobile showroom is considered to be an automobile lover. In a case where the recommendation condition **126** is that “the group attribute indicates a married couple with a child,

and the point ID is an ID of a park”, the recommendation information **127** is “guidance information to a cafe where a children's chair is provided around the park”. It is considered that a group staying in a park will enter a shop where drinks can be purchased. In addition, a group with children is considered to prefer a store in which a children's chair is provided.

(79) The recommendation information **127** of each specific example described above may be “presentation of a discount coupon usable in a store” or the like. Presenting the recommendation information **127** corresponding to a group satisfying the above-described recommendation condition **126** is presenting the recommendation information **127** matching the demand and preference of the group. Therefore, it is possible to increase the utilization rate of the presented recommendation information **127**.

#### Fourth Example Embodiment

(80) A fourth example embodiment is a modification of the third example embodiment described above. In the fourth example embodiment, the face authentication terminal **300** records an action history of a group. The action history is a history of actions performed by the group. Examples of the action history include a payment history for a product or the like, an entrance/leaving history for a facility, a participation history for an event, and the like. The action history may include information such as a time and place at which the user has performed the action.

(81) FIG. **13** is a block diagram illustrating a configuration of a recommendation system **900** according to the fourth example embodiment. In the recommendation system **900**, the recommendation device **100a** in the configuration of the recommendation system **700** illustrated in FIG. **5** is replaced with a recommendation device **800a**. For each component included in the recommendation system **900**, a description overlapping with that of the third example embodiment will be omitted as appropriate. FIG. **14** is a block diagram illustrating a configuration of the recommendation device according to the fourth example embodiment. The recommendation device **800a** is different from the recommendation device **100a** in that the history information **125** recorded in the storage unit **120** includes the action history. Since the other components are similar, a description thereof will be omitted as appropriate.

(82) In the present example embodiment, the face authentication terminal **300** also serves as an action history recording terminal. The action history recording terminal is a terminal that records an action history of a group. The action history is a history of actions performed by the group. Examples of the action history include a payment history for a product or the like, an entrance/leaving history for a facility, a participation history for an event, and the like. The action history may include information such as a time and place at which the group has performed the action. The action history is recorded as the history information **125** associated with the group ID **125a** in the storage unit **120**. In the present example embodiment, the recommendation condition **126** is a combination of at least one of the point ID or the action history, and the group attribute.

(83) Next, an operation of the recommendation device **800a** at the time of recommendation processing will be described with reference to FIG. **15**. FIG. **15** is a flowchart illustrating a flow of the recommendation processing. Note that, in the example illustrated in FIG. **15**, it is assumed that the face authentication terminal **300** performs the payment processing in a case where the face authentication has succeeded.

(84) The face authentication terminal **300** captures a captured image including face regions of a plurality of users, and transmits a group authentication request including the captured image to the recommendation device **800a**. The group authentication request includes a payment request. Once the group authentication request is received, the acquisition unit **112** included in the recommendation device **800a** acquires the captured image included in the group authentication request (Step **S601**). Next, the region detection unit **113** detects the plurality of face regions from the captured image (Step **S602**). Next, the personal authentication control unit **114** causes the authentication device **200** to perform the face authentication for each specified face region, and receives the face authentication result (Steps **S603** to **S606**). After the face authentication is



performed for all the face regions specified in Step S602, the determination unit **115** determines whether or not the face authentication has succeeded for all the users belonging to the group (Step S607).

(85) In a case where the face authentication has succeeded for all the users belonging to the group (Yes in Step S607), the output unit **119** transmits, as a response, an instruction for the payment processing to the face authentication terminal **300** (Step S608). Note that the instruction for the payment processing may include the user IDs **123b** and **123c** of the users who make payment. Once the instruction for the payment processing is received, the face authentication terminal **300** performs the payment processing and transmits, as a response, a payment history that is a result of the payment to the recommendation device **800a**. The payment history includes a group ID. The registration unit **111** acquires the payment history received from the face authentication terminal **300** and the group ID included in the payment history. The registration unit **111** registers the acquired payment history in association with the acquired group ID in the storage unit **120** (Step S609).

(86) Next, the specifying unit **116** specifies an action of the group by referring to the point ID **125b** registered as the history information **125** in the storage unit **120** and the payment history (Step S610). In a case where the face authentication has succeeded for all the users belonging to the group (Yes in Step S507), the estimation unit **117** estimates a group attribute based on a personal attribute of each user belonging to the group (Step S611).

(87) Next, the selection unit **118** selects the recommendation information **127** based on the group attribute estimated in Step S611 and the action specified in Step S610 (Step S612). Next, the output unit **119** outputs the recommendation information **127** selected in Step S612 to a predetermined display terminal (Step S613).

(88) In a case where there is a user whose face authentication has failed among the users belonging to the group (No in Step S607), the determination unit **115** determines whether or not the face authentication has failed only for some of the users belonging to the group (Step S614). In a case where the face authentication of the user has failed, the authentication device **200** estimates the age group and gender of the user based on the face feature information, and transmits, as a response, the estimation result to the recommendation device **100a**. In a case where the face authentication has failed for only some of the users belonging to the group (Yes in Step S614), the determination unit **115** specifies the group ID **123a** including the user IDs **123b** and **123c** of the users whose face authentication has succeeded (Step S615). Next, the determination unit **115** collates the personal attribute associated with the group ID **123a** specified in Step S615 with the age group and gender of the user received from the authentication device **200** (Step S616).

(89) In a case where the personal attribute matches (Yes in Step S616), the recommendation device **100a** outputs the recommendation information **127** according to the procedures illustrated in Steps S608 to S613. In a case where the personal attribute does not match (No in Step S616), the output unit **119** outputs the fact that the face authentication has failed (Step S617). The output destination in Step S617 may be the user terminal **400** operated by the user whose face authentication has succeeded, or may be a display terminal that does not depend on the user, such as the face authentication terminal **300** or a signage.

(90) In a case where the face authentication has failed for all the users belonging to the group (No in Step S615), the output unit **119** outputs the fact that the face authentication has failed (Step S617). The output destination in this case is, for example, a display terminal that does not depend on the user, such as the face authentication terminal **300** and a signage.

(91) Note that although FIG. 15 illustrates a case where the payment processing is performed in a case where the face authentication has succeeded, processing such as recording of an entrance/leaving history and recording of a participation history may be performed in a case where the face authentication has succeeded. The face authentication terminal **300** can include, in the group authentication request, a request for registration of the action history such as the

entrance/leaving history and the participation history, similarly to the payment request. In addition, the face authentication terminal **300** may perform payment without depending on the face authentication. In this case, the group authentication request including the payment history is transmitted to the recommendation device **800a**. The registration unit **111** registers the payment history included in the group authentication request in the storage unit **120**. Examples of a method of making payment without depending on the face authentication include a method of making payment by using a credit card and a method of making payment by using electronic money.

(92) In the above example, the face authentication terminal **300** transmits the group authentication request including the payment request. However, the face authentication terminal **300** may transmit the payment request before transmitting the group authentication request. In this case, for example, the face authentication terminal **300** captures an image including a face of a payment target person at the time of payment, and transmits the payment request including the captured image to the recommendation device **800a**. The recommendation device **800a** extracts face feature information of the payment target person and causes the authentication device **200** to perform the face authentication. The face authentication terminal **300** receives the face authentication result from the recommendation device **800a**, and performs the payment processing in a case where the face authentication has succeeded. The face authentication terminal **300** transmits the group authentication request after transmitting the payment history to the recommendation device **800a**.

(93) FIG. **16** is a view illustrating the recommendation information **127** displayed on the display terminal. FIG. **16** illustrates a case where the recommendation information **127** is displayed on the user terminal **400**. As illustrated in FIG. **16**, the user terminal **400** displays the recommendation information **127** received in Step **S613** on a screen. Note that, in Step **S613**, the output unit **119** may transmit the action history of the group to the display terminal in addition to the recommendation information **127**.

(94) FIG. **17** is a view illustrating a map displayed as the action history on the display terminal. As illustrated in FIG. **17**, the user terminal **400** may display the action history of the group received in Step **S613** on the map. FIG. **18** is a view illustrating the action history displayed on the display terminal. As illustrated in FIG. **18**, the user terminal **400** may display the action history received in Step **S613** in time series. Note that FIGS. **17** and **18** illustrate the payment history as an example of the action history.

(95) FIGS. **17** and **18** illustrate a case where only the action history of the group is displayed on the display terminal, but the recommendation information **127** may be displayed on the display terminal in addition to the action history. The recommendation information **127** may include store information, an address of the store, route guidance from the current location of the group to the store, and the like. The route guidance may include a distance from the current location of the group to the store, a required time, and the like. Further, a plurality of pieces of recommendation information **127** may be displayed on the display terminal. In a case where a plurality of pieces of recommendation information **127** are displayed, details of each piece of recommendation information **127**, route guidance, and the like may be simultaneously displayed. Each user belonging to the group can examine the details of each piece of recommendation information **127**, route guidance, and the like, and compare the pieces of recommendation information **127** with each other.

(96) Hereinafter, specific examples of the recommendation condition **126** and the corresponding recommendation information **127** will be described. For example, in a case where the recommendation condition **126** is that “the group attribute indicates that only young people are included, and the action history is payment for food and drink”, the recommendation information **127** is “guidance information to a karaoke”. A group having finished eating and drinking is considered to go to an entertainment facility where the group can have fun later. In addition, a group including only young people is considered to prefer a karaoke as an entertaining facility. In a case where the recommendation condition **126** is that “the group attribute indicates that only young

people are included, and the action history is payment for bowling”, the recommendation information **127** is “guidance information to an all-you-can-eat restaurant”. A group having played bowling is considered to have a meal after playing bowling. In addition, a group including only young people is considered to prefer an all-you-can-eat restaurant.

(97) In a case where the recommendation condition **126** is that “the group attribute indicates that only females are included, and the action history is a travel book purchase history”, the recommendation information **127** is “guidance information to a predetermined cafe”. A group having purchased a travel book is considered to visit a store or the like where the group can have a conversation in order to make a travel plan later. In addition, it is considered that a group including only females prefers a cafe as a place where they can talk. In a case where the recommendation condition **126** is that “the group attribute indicates that only high school students are included, and the action history is a payment history for a photo sticker”, the recommendation information **127** is “guidance information to a snack bar”. A group having taken a photo sticker is considered to have a snack after taking the photo sticker. In addition, A group including only high school students is considered to prefer a snack that they can eat on the go.

(98) The recommendation information **127** of each specific example described above may be “presentation of a discount coupon usable in a store” or the like. Presenting the recommendation information **127** corresponding to a group satisfying the above-described recommendation condition **126** is presenting the recommendation information **127** further matching the demand and preference of the group. Therefore, it is possible to further increase the utilization rate of the presented recommendation information **127**.

(99) Since the recommendation device according to the present example embodiment can present the recommendation information **127** by using the action history, it is possible to provide the recommendation information **127** more appropriate for a group. Furthermore, the recommendation device according to the present example embodiment can achieve effects similar to the effects described in the first to third example embodiments.

#### Fifth Example Embodiment

(100) A fifth example embodiment is a modification of the first to fourth example embodiments described above. In the recommendation systems **700** and **900** according to the first to fourth example embodiments, the recommendation information **127** is specified based on a visit to one point or an action history at the point. On the other hand, in the fifth example embodiment, the recommendation information **127** is specified based on visits to a plurality of points or an action history at each point.

(101) In the present example embodiment, as illustrated in FIGS. **5** and **13**, imaging devices such as the face authentication terminal **300** are installed at a plurality of points, and the group visits two or more points among the plurality of points. When visiting each point, the face authentication terminal **300** installed at the point performs the group authentication by the face authentication for the group. Every time the group authentication succeeds, the registration unit **111** registers the point ID of the point where the authentication has succeeded in association with the group ID **125a** of the group in the storage unit **120**. In a case where two or more point IDs **125b** are registered in the history information **125** of the group, the specifying unit **116** specifies all the actions at each point. The selection unit **118** selects the recommendation information **127** based on a set of the group attribute and the action.

(102) Hereinafter, specific examples of the recommendation condition **126** and the corresponding recommendation information **127** will be described. For example, in a case where the recommendation condition **126** is that “the group attribute indicates that only young people are included, and the action history is payment for bowling and food and drink”, the recommendation information **127** is “guidance information to an aquarium”. A group having finished eating and drinking is considered to go to a facility where the group can have fun later. In addition, a group having already visited a bowling alley is considered to prefer a facility where the group can enjoy

activities other than sports. In a case where the recommendation condition **126** is that “the group attribute indicates that only females are included, and the action history is a payment history for a predetermined number or more of products”, the recommendation information **127** is “guidance information to a cafe where many baggage can be placed”. A group including only females who have purchased a product is considered to visit a cafe to take a break after the purchase. In addition, a group having purchased a large amount of baggage is considered to prefer a store having a large space for putting baggage.

(103) Since the recommendation system according to the present example embodiment can specify recommendation information based on a plurality of actions, it is possible to provide recommendation information more appropriate for a group. Furthermore, the recommendation device according to the present example embodiment can achieve effects similar to the effects described in the first to fifth example embodiments.

(104) Note that, although the hardware configuration has been described in the above-described example embodiments, the present disclosure is not limited thereto. According to the present disclosure, arbitrary processing can also be implemented by causing a CPU to execute a computer program.

(105) In the above example, the program may be stored using various types of non-transitory computer-readable media and supplied to a computer. The non-transitory computer-readable media include various types of tangible storage media. Examples of the non-transitory computer-readable medium include a magnetic recording medium (for example, a flexible disk, a magnetic tape, or a hard disk drive), an optical magnetic recording medium (for example, a magneto-optical disk), a compact disc-read only memory (CD-ROM), a CD-R, a CD-R/W, a digital versatile disc (DVD), and a semiconductor memory such as a mask ROM, a programmable ROM (PROM), an erasable PROM (EPROM), a flash ROM, or a random access memory (RAM). In addition, the program may be supplied to the computer by various types of transitory computer-readable media. Examples of the transitory computer-readable medium include an electric signal, an optical signal, and electromagnetic waves. The transitory computer-readable medium can provide the program to the computer via a wired communication line such as electric wires and optical fibers or a wireless communication line.

(106) Note that the present disclosure is not limited to the above example embodiments, and can be appropriately changed without departing from the gist. Furthermore, the present disclosure may be implemented by appropriately combining the respective example embodiments.

(107) The whole or part of the example embodiments disclosed above can be described as, but not limited to, the following Supplementary Notes.

(108) (Supplementary Note A1)

(109) A recommendation device including: an acquisition unit configured to acquire a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; a personal authentication control unit configured to cause face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; a determination unit configured to determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; a specifying unit configured to specify an action in the group based on the point in a case where the group authentication has succeeded; an estimation unit configured to estimate a group attribute based on a personal attribute of each user belonging to the group; a selection unit configured to select recommendation information based on the group attribute and the action; and an output unit configured to output the selected recommendation information to a predetermined display terminal.

(Supplementary Note A2)

(110) The recommendation device according to Note A1, in which the specifying unit specifies the

action based on an action history of at least one person in the group at the point in a case where the group authentication has succeeded.

(111) (Supplementary Note A3)

(112) The recommendation device according to Supplementary Note A2, in which the captured image is an image captured when payment is made by at least one person in the group at the point, the action history is a payment history at the point, and the specifying unit specifies the action based on the payment history in a case where the group authentication has succeeded.

(Supplementary Note A4)

(113) The recommendation device according to Supplementary Note A3, in which the payment history is a history of payment made in a case where the face authentication has succeeded.

(114) (Supplementary Note A5)

(115) The recommendation device according to any one of Supplementary Notes A1 to A4, in which the imaging device is installed at each of a plurality of different points, the recommendation device further includes a registration unit configured to register the point in association with the group in a case where the group authentication has succeeded, the specifying unit specifies, in a case where two or more points are associated with the group, a set of the actions at the respective points, and the selection unit selects the recommendation information based on a set of the group attribute and the action.

(Supplementary Note A6)

(116) The recommendation device according to any one of Supplementary Notes A1 to A5, in which the determination unit estimates, in a case where the face authentication has succeeded for some users belonging to the group and the face authentication has failed for other users, a personal attribute based on a face region for which the face authentication has failed, and determines whether or not the group authentication is successful according to a degree of matching between the estimated personal attribute and the personal attribute of each user belonging to the group.

(117) (Supplementary Note A7)

(118) The recommendation device according to any one of Supplementary Notes A1 to A6, further including a storage unit configured to store a set of identification information of the plurality of users and the personal attribute as the group.

(119) (Supplementary Note B1)

(120) A recommendation system including: an imaging device configured to capture an image including a face region of a predetermined user; a recommendation device configured to be communicable with the imaging device; and an authentication device configured to store face feature information of the user and be communicable with the recommendation device, in which the recommendation device includes: an acquisition unit configured to acquire a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; a personal authentication control unit configured to cause the authentication device to perform face authentication for a plurality of face regions detected from the captured image; a determination unit configured to determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; a specifying unit configured to specify an action in the group based on the point in a case where the group authentication has succeeded; an estimation unit configured to estimate a group attribute based on a personal attribute of each user belonging to the group; a selection unit configured to select recommendation information based on the group attribute and the action; and an output unit configured to output the selected recommendation information to a predetermined display terminal.

(Supplementary Note B2)

(121) The recommendation system according to Note B1, in which the specifying unit specifies the action based on an action history of at least one person in the group at the point in a case where the group authentication has succeeded.

(122) (Supplementary Note C1)

(123) A recommendation method performed by a computer, the recommendation method including: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; causing face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

(Supplementary Note D1)

(124) A non-transitory computer-readable medium storing a recommendation program that causes a computer to perform: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; causing face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

(Supplementary Note E1)

(125) A recommendation device including: an acquisition unit configured to acquire a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; an authentication unit configured to perform face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; a determination unit configured to determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; a specifying unit configured to specify an action in the group based on the point in a case where the group authentication has succeeded; an estimation unit configured to estimate a group attribute based on a personal attribute of each user belonging to the group; a selection unit configured to select recommendation information based on the group attribute and the action; and an output unit configured to output the selected recommendation information to a predetermined display terminal.

(Supplementary Note E2)

(126) The recommendation device according to Note E1, in which the specifying unit specifies the action based on an action history of at least one person in the group at the point in a case where the group authentication has succeeded.

(127) (Supplementary Note F1)

(128) A recommendation method performed by a computer, the recommendation method including: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; performing face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal

attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

(Supplementary Note G1)

(129) A non-transitory computer-readable medium storing a recommendation program that causes a computer to perform: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point; performing face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as a group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

(130) Although the present invention has been described with reference to the example embodiments (and examples), the present invention is not limited to the above example embodiments (and examples). Various modifications that can be understood by those skilled in the art can be made to the configuration and details of the present invention within the scope of the present invention.

#### REFERENCE SIGNS LIST

(131) **100, 100a, 600, 800a** RECOMMENDATION DEVICE **700, 900** RECOMMENDATION SYSTEM **110** CONTROL UNIT **111** REGISTRATION UNIT **112** ACQUISITION UNIT **113** REGION DETECTION UNIT **114** PERSONAL AUTHENTICATION CONTROL UNIT **115** DETERMINATION UNIT **116** SPECIFYING UNIT **117** ESTIMATION UNIT **118** SELECTION UNIT **119** OUTPUT UNIT **120** STORAGE UNIT **123** GROUP INFORMATION **123a** GROUP ID **123b, 123c** USER ID **123d, 123e** ATTRIBUTE INFORMATION **124** PROGRAM **125** HISTORY INFORMATION **125a** GROUP ID **125b** POINT ID **126** RECOMMENDATION CONDITION **127** RECOMMENDATION INFORMATION **121** AUTHENTICATION UNIT **130** MEMORY **140** COMMUNICATION UNIT **200** AUTHENTICATION DEVICE **210** FACE FEATURE DB **220** FACE DETECTION UNIT **230** FEATURE POINT EXTRACTION UNIT **240** REGISTRATION UNIT **250** AUTHENTICATION UNIT **300(300X, 300Y)** FACE AUTHENTICATION TERMINAL **310** CAMERA **320** STORAGE UNIT **330** COMMUNICATION UNIT **340** DISPLAY UNIT **350** CONTROL UNIT **352** IMAGING UNIT **353** REGISTRATION UNIT **354** AUTHENTICATION UNIT **355** PAYMENT UNIT **400** USER TERMINAL **410** CAMERA **420** STORAGE UNIT **430** COMMUNICATION UNIT **440** DISPLAY UNIT **450** CONTROL UNIT **451** IMAGING UNIT **452** IMAGING UNIT **453** REGISTRATION UNIT **454** AUTHENTICATION UNIT **455** PAYMENT UNIT **500** NETWORK

#### Claims

1. A recommendation device comprising: at least one memory acquiring storing instructions and at least one processor configured to execute the instructions to; acquire a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point and captured in a case where payment is made by at least one person in a group at the point; cause face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as the group and any one of the plurality of detected face regions has succeeded; specify an action in the group based on a payment history of at least one person in the

group at the point in a case where the group authentication has succeeded; estimate a group attribute based on a personal attribute of each user belonging to the group; select recommendation information based on the group attribute and the action; and output the selected recommendation information to a predetermined display terminal.

2. The recommendation device according to claim 1, wherein the payment history is a history of payment made in a case where the face authentication has succeeded.

3. The recommendation device according to claim 1, wherein the imaging device is installed at each of a plurality of different points, the at least one processor is further configured to execute the instructions to; register the point in association with the group in a case where the group authentication has succeeded, specify, in a case where two or more points are associated with the group, a set of the actions at the respective points, and select the recommendation information based on a set of the group attribute and the action.

4. The recommendation device according to claim 1, wherein the at least one processor is further configured to execute the instructions to estimate, in a case where the face authentication has succeeded for some users belonging to the group and the face authentication has failed for other users, a personal attribute based on a face region for which the face authentication has failed, and determines whether or not the group authentication is successful according to a degree of matching between the estimated personal attribute and the personal attribute of each user belonging to the group.

5. The recommendation device according to claim 1, wherein the at least one memory is configured to store a set of identification information of the plurality of users and the personal attribute as the group.

6. A recommendation system comprising: an imaging device configured to capture an image including a face region of a predetermined user; a recommendation device configured to be communicable with the imaging device; and an authentication device configured to store face feature information of the user and be communicable with the recommendation device, wherein the recommendation device includes: acquisition means for acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point and captured in a case where payment is made by at least one person in a group at the point; personal authentication control means for causing the authentication device to perform face authentication for a plurality of face regions detected from the captured image; determination means for determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as the group and any one of the plurality of detected face regions has succeeded; specifying means for specifying an action in the group based on a payment history of at least one person in the group at the point in a case where the group authentication has succeeded; estimation means for estimating a group attribute based on a personal attribute of each user belonging to the group; selection means for selecting recommendation information based on the group attribute and the action; and output means for outputting the selected recommendation information to a predetermined display terminal.

7. A recommendation method performed by a computer, the recommendation method comprising: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point and captured in a case where payment is made by at least one person in a group at the point; causing face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as the group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on a payment history of at least one person in the group at the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the



action; and outputting the selected recommendation information to a predetermined display terminal.

8. A non-transitory computer-readable medium storing a recommendation program that causes a computer to perform: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point and captured in a case where payment is made by at least one person in a group at the point; causing face authentication to be performed for a plurality of face regions detected from the captured image by using an authentication device that stores face feature information of a plurality of users; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as the group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on a payment history of at least one person in the group at the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

9. A recommendation device comprising: at least one memory acquiring storing instructions and at least one processor configured to execute the instructions to; acquire a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point and captured in a case where payment is made by at least one person in a group at the point; perform face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; determine that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as the group and any one of the plurality of detected face regions has succeeded; specify an action in the group based on a payment history of at least one person in the group at the point in a case where the group authentication has succeeded; estimate a group attribute based on a personal attribute of each user belonging to the group; select recommendation information based on the group attribute and the action; and output the selected recommendation information to a predetermined display terminal.

10. A recommendation method performed by a computer, the recommendation method comprising: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point and captured in a case where payment is made by at least one person in a group at the point; performing face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as the group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on a payment history of at least one person in the group at the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

11. A non-transitory computer-readable medium storing a recommendation program that causes a computer to perform: acquiring a captured image obtained by imaging a plurality of persons by an imaging device installed at a predetermined point and captured in a case where payment is made by at least one person in a group at the point; performing face authentication for a plurality of face regions detected from the captured image by using face feature information of a plurality of users stored in advance; determining that group authentication has succeeded in a case where face authentication using at least one of the plurality of users registered as the group and any one of the plurality of detected face regions has succeeded; specifying an action in the group based on a payment history of at least one person in the group at the point in a case where the group authentication has succeeded; estimating a group attribute based on a personal attribute of each user

belonging to the group; selecting recommendation information based on the group attribute and the action; and outputting the selected recommendation information to a predetermined display terminal.

---