

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250279747

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

KINNEY; James Tyler et al.

Extendable Solar Assembly for Vehicle

Abstract

An extendable solar assembly for removably attaching to a vehicle is disclosed herein. The extendable solar assembly may comprise a housing securely affixed to a vehicle during use and a set of solar panels configured to be stacked within the housing when the extendable solar assembly is in the retracted position. The extendable solar assembly further comprises lateral arms and/or tracks configured to support the set of solar panels and cause the set of solar panels to extend and retract as the extendable solar assembly extends from a retracted position to an extended position. The set of solar panels and each of the lateral arms and/or tracks are all retracted within the housing when the extendable solar assembly is in the retracted position. The extendable solar assembly comprises a self-contained, standalone unit configured to be removed and attached to another structure.

Inventors: KINNEY; James Tyler (Arvada, CO), McMILLAN; David Thomas (Broomfield, CO), MAYER; Kevin Paul (Boulder, CO)

Applicant: Carefree/Scott Fetzer Company (Broomfield, CO)

Family ID: 95154849

Assignee: Carefree/Scott Fetzer Company (Broomfield, CO)

Appl. No.: 19/070182

Filed: March 04, 2025

Related U.S. Application Data

us-provisional-application US 63561010 20240304

Publication Classification

Int. Cl.: H02S30/20 (20140101); H02S20/30 (20140101)

Background/Summary

RELATED APPLICATIONS [0001] This application claims priority to U.S. Provisional Patent Application No. 63/561,010 filed Mar. 4, 2024, the content of which is hereby incorporated herein by reference in its entirety.

FIELD OF THE DISCLOSURE

[0002] The present invention relates to an extendable solar assembly and method of making same and, more particularly, an extendable solar assembly that provides power to vehicle.

BACKGROUND OF THE INVENTION

[0003] Persons traveling in vehicles across long distances often require power during stationary periods. However, utilizing that power can drain batteries and cause vehicles to fail. Further, green energy is beneficial for the environment, and solar power is a good source of green energy. Additionally, certain types of vehicles may have unique power requirements (e.g., for refrigeration of medical supplies, such as vaccines). It is also typical for certain vehicles to only travel at night and rest during the day, creating unique issues when it comes to maintaining their cargo. Solutions for generating power using green energy when a vehicle is stopped to power appliances, devices, or utilities exist, but these solutions have numerous drawbacks. Indeed, it is common for persons traveling in recreational vehicles to set up solar panels when stopped to generate electricity. However, such solar panels can be cumbersome to set up, take down, and store. Additionally, these solar panels are often set up on the ground, potentially taking up valuable space near the vehicle, presenting a safety hazard for those in the vicinity, while also exposing the solar panels themselves to risk of damage from moving bodies, vehicles, and other equipment. Accordingly, there is a need for improved solutions for generating power from renewable sources when a vehicle is stopped to power appliances, devices, or utilities that may be easily installed on a vehicle and selectively utilized regardless of space or time constraints.

SUMMARY OF THE INVENTION

[0004] Aspects of this disclosure relate to an extendable solar assembly for a vehicle or other structure. In various embodiments, the extendable solar assembly comprises a housing securely affixed to a structure during use, a set of arms attached to the housing and configured to support a lead rail of the extendable solar assembly as the extendable solar assembly extends from a retracted position to an extended position, at least one track coupled to the housing and the lead rail and configured to extend and retract as the extendable solar assembly extends from the retracted position to the extended position, and a set of solar panels coupled to the at least one track that are configured to be stacked within the housing when the extendable solar assembly is in the retracted position. In various embodiments, the structure may comprise an exterior surface of a vehicle. In various embodiments, each of the set of arms, the at least one track, and the set of solar panels are all retracted within the housing when the extendable solar assembly is in the retracted position. In some embodiments, at least one solar panel of the set of solar panels remains exposed, is able to gather sunlight to generate electricity, and comprises a top surface of the extendable solar assembly when the set of solar panels are stacked within the housing (i.e., when the extendable solar assembly is in the retracted position). In some embodiments, the topmost solar panel when the solar panels are stacked within the housing may comprise a curved solar panel (e.g., to increase solar incidence). In some embodiments, each of the set of solar panels are stacked face up within the housing when the extendable solar assembly is in the retracted position. In other embodiments,

each solar panel of the set of solar panels is stacked in an alternating manner relative to at least one adjacent solar panel of the set of solar panels within the housing when the extendable solar assembly is in the retracted position. In various embodiments, the extendable solar assembly comprises a self-contained, standalone unit configured to be removed and attached to another structure.

[0005] In various embodiments, the at least one track may comprise a first track and a second track, wherein the set of solar panels are coupled to both the first track and the second track. In some embodiments, the set of solar panels may be coupled to the at least one track via progressively taller risers. In some embodiments, the at least one track may comprise an angled track. In some embodiments, the at least one track may comprise a stackable track including a series of stackable links, each pivotably movable with respect to an adjacent stackable link.

[0006] In various embodiments, the extendable solar assembly may comprise one or more actuators connected to at least the lead rail and configured to cause the extendable solar assembly to extend from the retracted position to the extended position. In some such embodiments, the one or more actuators may be retracted within the housing when the extendable solar assembly is in the retracted position. In some embodiments, the set of arms themselves may comprise actuated arms configured to cause the extendable solar assembly to move between the retracted position and the extended position. In some embodiments, the extendable solar assembly may comprise a motor configured to manipulate a strap or a cable to cause extendable solar assembly to move between the retracted position and the extended position.

[0007] Another aspect of this disclosure relates to an extendable solar assembly comprising a housing securely affixed to a structure during use, a set of sliding arms configured to extend outwardly when the extendable solar assembly extends from a retracted position to an extended position and collapse when the extendable solar assembly retracts from the extended position to the retracted position, and a set of solar panels that are coupled to the set of sliding arms, wherein the solar panels are configured to be stacked within the housing when the extendable solar assembly is in the retracted position. In such an embodiment of an extendable solar assembly described herein, a lead rail may be absent or entirely decorative. Instead, in some embodiments, the set of solar panels may be extended and retracted using the set of slidable lateral arms. In various embodiments, the set of sliding arms include two sliding arms, each configured to support an outside edge of the set of solar panels. In various embodiments, the set of sliding arms are configured to retract within the housing when the extendable solar assembly is in the retracted position. In various embodiments, when the set of solar panels are stacked within the housing when the extendable solar assembly is in the retracted position, at least one solar panel of the set of solar panels may remain exposed, is able to gather sunlight to generate electricity, and comprises a top surface of the extendable solar assembly. In various embodiments, the extendable solar assembly comprises a self-contained, standalone unit configured to be removed and attached to another structure.

[0008] These and other objects, functions, and characteristics of the systems and/or methods disclosed herein, as well as the methods of operation and functions of the related elements of structure and the combination thereof, will become more apparent upon consideration of the following description and the appended claims with reference to the accompanying drawings, all of which form a part of this specification, wherein like reference numerals designate corresponding parts in the various figures. It is to be expressly understood, however, that the drawings are for the purpose of illustration and description only and are not intended as a definition of the limits of the invention. As used in the specification and in the claims, the singular form of “a”, “an”, and “the” include plural referents unless the context clearly dictates otherwise.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The present invention is illustrated by way of example and not limited in the accompanying figures in which like reference numerals indicate similar elements and in which:

[0010] FIG. **1** depicts a top perspective view of an example extendable solar assembly in an extended position, according to one or more aspects described herein;

[0011] FIG. **2** depicts a bottom perspective view of an example extendable solar assembly in an extended position, according to one or more aspects described herein;

[0012] FIG. **3** depicts a front elevation view of an example extendable solar assembly, according to one or more aspects described herein;

[0013] FIG. **4** depicts a side view of an example embodiment of an extendable solar assembly in an extended position, according to one or more aspects described herein;

[0014] FIG. **5** depicts a side view of another example embodiment of an extendable solar assembly in an extended position, according to one or more aspects described herein;

[0015] FIG. **6** depicts a side view of a portion of an example stackable track of an extendable solar assembly including a stackable/link function, according to one or more aspects described herein;

[0016] FIG. **7** depicts a side view of an example embodiment of an extendable solar assembly having a stackable track in an extended position, according to one or more aspects described herein;

[0017] FIG. **8** depicts a cross-sectional view of an example extendable solar assembly having a stackable track in a retracted position, according to one or more aspects described herein;

[0018] FIG. **9** depicts top cross-sectional views of an example extendable solar assembly having an angled actuator in an extended and retracted position, according to one or more aspects described herein;

[0019] FIG. **10** depicts top cross-sectional views of an example extendable solar assembly having perpendicular actuators in an extended and retracted position, according to one or more aspects described herein;

[0020] FIG. **11** depicts top cross-sectional views of an example extendable solar assembly having actuated lateral arms in an extended and retracted position, according to one or more aspects described herein;

[0021] FIG. **12** depicts top cross-sectional views of an example extendable solar assembly having spring-loaded lateral arms in an extended and retracted position, according to one or more aspects described herein;

[0022] FIG. **13** depicts top cross-sectional views of an example extendable solar assembly having a scissor mechanism in an extended and retracted position, according to one or more aspects described herein;

[0023] FIG. **14** depicts side cross-sectional views of an example extendable solar assembly having a drawer slider mechanism in an extended and retracted position, according to one or more aspects described herein; and

[0024] FIG. **15** depict perspective views of an example extendable solar assembly installed on a vehicle, according to one or more aspects described herein.

[0025] These drawings are provided for purposes of illustration only and merely depict typical or example embodiments. These drawings are provided to facilitate the reader's understanding and shall not be considered limiting of the breadth, scope, or applicability of the disclosure. For clarity and ease of illustration, these drawings are not necessarily drawn to scale.

DETAILED DESCRIPTION

[0026] In the following description of various examples of the invention, reference is made to the accompanying drawings, which form a part hereof, and in which are shown by way of illustration various example structures, systems, and steps in which aspects of the invention may be practiced. These aspects are indicative, however, of but a few of the various ways in which the principles of

the invention may be employed and the present invention is intended to include all such aspects and their equivalents. It is to be understood that other specific arrangements of parts, structures, example devices, systems, and steps may be utilized, and structural and functional modifications may be made without departing from the scope of the present invention. Also, while the terms “top,” “bottom,” “front,” “back,” “side,” and the like may be used in this specification to describe various example functions and elements of the invention, these terms are used herein as a matter of convenience, e.g., based on the example orientations shown in the figures. Nothing in this specification should be construed as requiring a specific three-dimensional orientation of structures in order to fall within the scope of this invention.

[0027] The invention described herein relates to an extendable solar assembly that can be installed on a structure (such as an exterior surface of a vehicle). In various embodiments, the extendable solar assembly comprises a housing securely affixed to the structure during use and a set of solar panels configured to be stacked within the housing when the extendable solar assembly is in the retracted position. In some embodiments, the extendable solar assembly may comprise a set of arms attached to the housing and a track, wherein the set of arms are configured to support a lead rail as the extendable solar assembly extends from a retracted position to an extended position, and the track is coupled to the housing and the lead rail and is configured to extend and retract as the lead rail extends, causing the set of solar panels to extend and retract. In other embodiments, the extendable solar assembly may instead further include a set of sliding arms configured to extend outwardly when moving to an extended position and collapse when moving to the retracted position, causing the set of solar panels to do the same. In either respect, the extendable solar assembly comprises a self-contained, standalone unit configured to be removed and attached to another structure.

[0028] In various embodiments, the extendable solar assembly described herein may be couplable to a residence, vehicle, or other structure. For example, an extendable solar assembly, as disclosed herein, may be coupled to, securely attached/affixed, and/or removably secured to a residence, vehicle, or other structure. For ease of understanding and illustration, extendable solar assembly **200** is described and depicted herein as coupled (or otherwise attachable) to a vehicle **10** as a non-limiting example. For example, extendable solar assembly **200** may be coupled to an exterior surface of a car, truck, bus, camping car, trailer, recreational vehicle, or any other type of vehicle or wheeled object. However, it is to be understood that extendable solar assembly **200** may similarly be coupled (or otherwise attachable) to a residence or other moving or stationary structure aside from vehicle **10**.

[0029] FIG. 1 and FIG. 2 depict various views of extendable solar assembly **200** in an extended position, according to one or more aspects described herein. For example, FIG. 1 depicts a top perspective view of extendable solar assembly **200** in an extended position, and FIG. 2 depicts a bottom perspective view of extendable solar assembly **200** in an extended position. In various embodiments, extendable solar assembly **200** may include a support structure **210** configured to support a set of solar panels **102-110**. In various embodiments, support structure **210** may comprise a lead rail **212**, one or more lateral arms (e.g., first and second lateral arms **214**, **216** or sliding arms **214**, **216**), a housing **218**, and/or one or more other components. As depicted, for example, in FIG. 2 and FIG. 15, the one or more lateral arms of extendable solar assembly may comprise a first lateral arm **214** and a second lateral arm **216** (or a set of sliding arms **214**, **216**) that extend away from housing **218** as extendable solar assembly **200** extends from a retracted position to an extended position. However, in some embodiments, extendable solar assembly **200** may include only a single lateral arm or more than two lateral arms. In various embodiments, housing **218** may comprise a cassette or a box in which some or all of the components of extendable solar assembly **200** are housed when extendable solar assembly **200** is in a retracted position. In various embodiments, housing **218** may be coupled, securely affixed, removably attached, and/or otherwise connected to a structure (e.g., vehicle **10**). Together, the one or more components of extendable

solar assembly **200** may form an awning canopy with the set of solar panels **102-110** defining a top surface of the awning canopy.

[0030] In various embodiments, the one or more lateral arms of extendable solar assembly **200** may comprise a set of arms configured to support the set of solar panels **102-110** as extendable solar assembly **200** extends from a retracted position to an extended position. In various embodiments, the one or more lateral arms may be connected, at least at one end, to housing **218**, and are configured to extend as extendable solar assembly **200** moves between a retracted and extended position. In some embodiments (for example, as depicted in FIG. 2), the one or more lateral arms of extendable solar assembly **200** may comprise a first lateral arm **214** and a second lateral arm **216** configured to support the set of solar panels **102-110** from below as extendable solar assembly **200** extends from a retracted position to an extended position. In some embodiments, first and second lateral arms **214**, **216** may be configured to support lead rail **212** when extendable solar assembly **200** is not in a retract position (e.g., when extending and when in an extended position). In other embodiments (for example, as depicted in FIG. 15 and described further herein), the one or more lateral arms of extendable solar assembly **200** may comprise a set of sliding arms **214**, **216** that each support an outside edge of the set of solar panels **102-110**.

[0031] In some embodiments, the one or more lateral arms (e.g., first and second lateral arms **214**, **216**) may comprise a proximal arm (positioned closer to housing **218** when in an extended position) and a distal arm (positioned further from housing **218** when in an extended position) pivotally joined together at an arm elbow. For example, the one or more lateral arms may comprise arms each having a proximal first arm and a distal second arm pivotally joined together at an arm elbow as described in U.S. Patent Application No. 10,316,522, entitled “Residential Awning Canopy Assembly,” filed Jul. 25, 2018, the content of which is hereby incorporated by reference herein in its entirety. In some embodiments, the proximal and distal arms may rotate with respect to each other at the arm elbows such that each proximal arm may be closer to being axially aligned with its respective distal arm when extendable solar assembly **200** is in an extended position. In such embodiments, each set of proximal and distal arms may be substantially parallel and adjacent to each other when extendable solar assembly **200** is in a retracted (or stowed) position.

[0032] In various embodiments, the one or more lateral arms of support structure **210** may provide vertically sound structural stability to one or more solar panels mounted on the extendable solar assembly **200**. In some embodiments (for example, as depicted in FIG. 2), first and second lateral arms **214**, **216** of support structure **210** may be spaced apart from one another to provide appropriate structural support for one or more solar panels across the support structure **210**. For example, first and second lateral arms **214**, **216** may be spaced apart from one another to ensure good distribution of the load (i.e., one or more solar panels **102-110**) of extendable solar assembly **200** while minimizing shear and tensile stress caused by weight of one or more solar panels **102-110** within support structure **210**.

[0033] In various embodiments, extendable solar assembly **200** may include a lead rail **212**. For example, as depicted in FIG. 2, extendable solar assembly **200** may include a lead rail **212** that is supported by the one or more lateral arms of support structure **210** (e.g., first and second lateral arms **214**, **216**) when extendable solar assembly **200** is in an extended position. In some embodiments, lead rail **212** may be coupled to a track **112** at a first end **102a** of extendable solar assembly **200** when extendable solar assembly **200** is in an extended position. In some embodiments, lead rail **212** may be coupled to a second track **114** in the same manner. For example, when second track **114** exists, second track **114** may include a mirror image of track **112**. In some embodiments, track **112** may also be attached to housing **218** at a second end **102b** of extendable solar assembly **200** when extendable solar assembly **200** is in an extended position. In various embodiments, the track **112** may be extended responsive to the lead rail **212** being extended away from the housing **218** and retracted responsive to the lead rail being retracted toward housing **218**. In some embodiments, lead rail **212** may be propelled and retracted to move extendable solar

assembly **200** between an extended and retracted position. For example, in some embodiments, lead rail **212** may be propelled and retracted to move extendable solar assembly **200** between an extended and retracted position via the one or more lateral arms (e.g., first and second lateral arms **214**, **216**) and/or via the one or more tracks (e.g., track **112** and/or track **114**). In other embodiments, lead rail **212** may be purely decorative. For example, in FIG. **15** (described further herein), lead rail **212** (not shown) may simply comprise a front edge of extendable solar assembly **200**. In some such embodiments, however, lead rail **212** may also protect a front edge of extendable solar assembly **200** and/or provide rigidity or otherwise support a front, long edge of extendable solar assembly **200**.

[0034] In various embodiments, extendable solar assembly **200** may include a set of solar panels **102-110**. As depicted in FIG. **2**, for example, extendable solar assembly **200** may include a first, second, third, fourth, and fifth solar panel **102**, **104**, **106**, **108**, **110**. While depicted and described herein as including a set of five solar panels (solar panels **102**, **104**, **106**, **108**, **110**), it is to be understood that any number of solar panels may be used. Indeed, it would be appreciated by one having ordinary skill in the art that more or less than five solar panels are contemplated. For example, in some embodiments, extendable solar assembly **200** may include two solar panels, while, in other embodiments, extendable solar assembly **200** may include six or more solar panels.

[0035] In various embodiments, the set of solar panels **102-110** may be coupled to one or more tracks (e.g., track **112**) of extendable solar assembly **200**. In some embodiments, the one or more tracks of extendable solar assembly **200** (e.g., track **112** and/or second track **114**) may be made of light weight material such as aluminum, plastic, ceramics, or the like. In some embodiments, extendable solar assembly **200** may include a track **112** that extends along a first lateral edge of extendable solar assembly **200** and/or solar panels **102-110**. In some such embodiments, extendable solar assembly **200** may also include a second track **114** that extends along a second lateral edge of the extendable solar assembly **200** and/or solar panels **102-110**. In such embodiments, the second lateral edge may be opposite the first lateral edge, and each of the first lateral edge and the second lateral edge may extend between a first end **102a** and a second end **102b** of extendable solar assembly **200** (e.g., between lead rail **212** and housing **218** when extendable solar assembly **200** is in an extended position).

[0036] In various embodiments, when extendable solar assembly **200** is in a retracted (or stowed) position, the set of solar panels **102-110** may be stacked (one on top of the other) within housing **218**. In some embodiments, when retracting the set of solar panels (i.e., when moving from an extended position to a retracted position), the set of solar panels **102-110** may be retracted by first stacking (or vertically aligning) the solar panels furthest from housing **218**. In other embodiments, when retracting the set of solar panels (i.e., when moving from an extended position to a retracted position), the set of solar panels **102-110** may be retracted by first stacking (or vertically aligning) the solar panels closest to housing **218**. For example, and referring to FIG. **1** and FIG. **2**, when retracting the set of solar panels **102-110** by first stacking (or vertically aligning) the solar panels furthest from housing **218**, fifth solar panel **110** (i.e., or the solar panel from housing **218**) may first be retracted to be vertically aligned with fourth solar panel **108**. Responsive to fourth solar panel **108** being vertically aligned with fifth solar panel **110**, the stacked fourth and fifth solar panels **108**, **110** may be retracted to be vertically aligned with third solar panel **106** as extendable solar assembly **200** continues to retract. Responsive to the third solar panel **106** being vertically aligned with the fourth and fifth solar panels **108**, **110**, the stacked third, fourth and fifth solar panels **106**, **108**, **110** may be retracted to be vertically aligned with second solar panel **104** as extendable solar assembly **200** continues to retract. Responsive to the second solar panel **104** being vertically aligned with the third, fourth and fifth solar panels **106**, **108**, **110**, the stacked second, third, fourth and fifth solar panels **104**, **106**, **108**, **110** may be retracted to be vertically aligned with the first solar panel **102** as extendable solar assembly continues **200** to retract (until extendable solar assembly **200** is fully retracted).

[0037] As another example, and referring to FIG. 1 and FIG. 2, when retracting the set of solar panels **102-110** by first stacking (or vertically aligning) the solar panels closest to housing **218**, second solar panel **104** (i.e., or the solar panel from housing **218**) may first be retracted to be vertically aligned with first solar panel **102**. Responsive to first solar panel **102** being vertically aligned with second solar panel **104**, third solar panel **106** may be retracted to be vertically aligned with the stacked first and second solar panels **102, 104** as extendable solar assembly **200** continues to retract. Responsive to the third solar panel **106** being vertically aligned with the first and second solar panels **102, 104**, the fourth solar panel **108** may be retracted to be vertically aligned with the stacked first, second, and third solar panels **102, 104, 106** as extendable solar assembly **200** continues to retract. Responsive to the fourth solar panel **108** being vertically aligned with the first, second, and third solar panels **102, 104, 106**, the fifth solar panel **110** may be retracted to be vertically aligned with the first, second, third, and fourth solar panels **102, 104, 106, 108** as extendable solar assembly continues **200** to retract (until extendable solar assembly **200** is fully retracted).

[0038] In some embodiments, the set of solar panels **102-110** may be retracted one at a time (or concurrently) as described in each of the foregoing examples. In other embodiments, the set of solar panels **102-110** may all be retracted simultaneously. For example, in some embodiments, the set of solar panels **102-110** may be retracted such that each of the set of solar panels **102-110** becomes vertically aligned with another solar panel at the same time (i.e., when all of the solar panels are aligned in the retracted position). In some embodiments, the solar panel furthest from housing **218** when extendable solar assembly is in an extended position (e.g., solar panel **110**) may comprise a top (or uppermost) solar panel when extendable solar assembly **200** is in a retracted position. In other embodiments, the solar panel furthest from housing **218** when extendable solar assembly is in an extended position (e.g., solar panel **110**) may comprise a bottom (or lowermost) solar panel when extendable solar assembly **200** is in a retracted position. In such embodiments, the solar panel closest to housing **218** when extendable solar assembly is in an extended position (e.g., solar panel **102**) would comprise the top (or uppermost) solar panel when extendable solar assembly **200** is in a retracted position. For example, as depicted in FIG. 3, a solar panel closest to housing **218** when extendable solar assembly is in an extended position (e.g., solar panel **102**) may comprise a top solar panel when extendable solar assembly **200** is in a retracted position. In this way, a top solar panel (e.g., solar panel **102**) (or a top set of solar panels) may remain exposed and is able to gather sunlight to generate electricity (or power) when extendable solar assembly **200** is in a retracted position. For example, as described further herein, extendable solar assembly **200** may operate in a low-power mode, or a lower power state, compared to the operation of extendable solar assembly **200** when the extendable solar assembly **200** in an extended position. Such a low-power mode may still have use for long term storage and trickle charging batteries, for example. In some embodiments, a top solar panel when extendable solar assembly **200** is in a retracted position may be curved to increase solar incidence, both when extendable solar assembly **200** is in a retracted position and when extendable solar assembly **200** is in an extended position. In some embodiments, the top solar panel and/or one or more other solar panels of the set of solar panels included in extendable solar assembly **200** may be curved to increase solar incidence. For example, in some embodiments, a subset of the set of solar panels included in extendable solar assembly **200** that are exposed when extendable solar assembly **200** is in a retracted position may each be curved to increase solar incidence.

[0039] In various embodiments, the set of solar panels **102-110** may be configured to generate electricity from solar energy (or sunlight). In some embodiments, the set of solar panels **102-110** may be connected to a solar cable that transmits energy to a battery, an electrical box of a vehicle **10** (or other structure to which extendable solar assembly **200** is attached), an electrical grid, or a battery connected to an electrical box of a vehicle **10** (or other structure to which extendable solar assembly **200** is attached).

[0040] In various embodiments, some or all of the components of extendable solar assembly **200** may be included or encompassed within housing **218** when extendable solar assembly **200** is in a retracted position. For example, in some embodiments, the set of solar panels **102-110**, the one or more lateral arms, and/or one or more other components of extendable solar assembly **200** may be included or encompassed within a cavity formed by housing **218** when extendable solar assembly is in a retracted position. In some embodiments, all of the components of extendable solar assembly **200** are included or encompassed within a cavity formed by housing **218** when extendable solar assembly is in a retracted position. For example, in some embodiments, each of the set of solar panels **102-110**, one or more lateral arms, one or more tracks (described herein), and any other components of a given embodiment of extendable solar assembly **200** may included or encompassed within a cavity formed by housing **218** when extendable solar assembly is in a retracted position. In various embodiments, at least the one or more lateral arms may be stowed (or otherwise included) within housing **218** (in addition to at least the set of solar panels **102-110**) when extendable solar assembly **200** is in a retracted position. For example, first and second lateral arms **214**, **216** may fold together to be stowed within the housing **218**. In some embodiments, housing **218** may be attachable (removably attached) to a wall or other mounting surface. For example, housing **218** may be attached to a vehicle **10** (e.g., a mobile home, truck, bus, or other vehicle) or other structure. In some embodiments, a front cap may encapsulate/cover an opening defined in housing **218**, and thus retain first and second lateral arms **214**, **216**, one or more solar panels **102-110**, and/or one or more other components of extendable solar assembly **200** when extendable solar assembly is in a retracted position.

[0041] In some embodiments, housing **218** may be completely enclosed when extendable solar assembly **200** is in a retracted position. In this way, extendable solar assembly **200** may comprise a self-contained, standalone unit that may be removed and attached to another vehicle. Additional, extendable solar assembly **200**, when completely enclosed, may provide added protection to the various components, for example, when vehicle **10** is moving. In other embodiments, one or more sides of housing **218** may be left open. For example, in some embodiments, a topmost solar panel (e.g., either solar panel **102** or solar panel **110**) or a subset of the solar panels included in extendable solar assembly **200** may remain exposed by residing on or forming a top surface of housing **218** when extendable solar assembly **200** is in a retracted position. In some embodiments, when in a retracted position, extendable solar assembly **200** may operate in a low-power mode (or lower power state), in which just a single exposed solar panel (or a subset of the set of one or more solar panels **102-110**) may be used to generate power (or electricity) from solar energy (or sunlight). For example, low-power mode may be used when a vehicle is moving (i.e., when the extendable solar assembly **200** may not be fully extended). When additional power is needed (or when vehicle **10** is parked), extendable solar assembly **200** may be extended to use each of the set of solar panels provided.

[0042] In various embodiments, the set of solar panels **102-110** may be coupled to a track **112** and/or a second track **114** along first and second (lateral) arms **214**, **216** perpendicular to a longitudinal axis (or x-axis) of the housing **218** at an appropriate manner. In some embodiments, the set of solar panels may be coupled to one or more tracks via one or more progressively taller risers **116**. For example, as depicted in FIG. 4, the set of solar panels **102-110** may be coupled to the track **112** (and/or second track **114** (not shown)) via one or more progressively taller risers **116**. In such embodiments, solar panel **110** may be coupled to the lowest, or with no riser, so that solar panel **110** may be located underneath the adjacent solar panel, when retracted. In some embodiments, the set of solar panels may be coupled to one or more angled tracks. For example, as depicted in FIG. 5, the set of solar panels **102-110** may be coupled to an angled track **112** (and/or an angled second track **114** (not shown)). In such embodiments, angled track **112** may be a linear track with an appropriate angle θ , in order to be at a relative height that is greater than a relative height that the angled track is coupled to the lead rail. In various embodiments, extendable solar

assembly **200** may be extended and retracted between the open (or extended) position (when extendable solar assembly **200** is in use) and the closed (or retracted) position (when extendable solar assembly **200** is not in use) manually.

[0043] In some embodiments, the set of solar panels **102-110** may be coupled to one or more stackable tracks. For example, as depicted in FIGS. **6-8**, a set of solar panels **102-110** may be coupled to a stackable track **112** (and/or a stackable second track **114** (not shown)). In various embodiments, for example, as depicted in FIG. **7**, stackable track **112** may include a series of stackable links **130**, each supporting one or more solar panels of the set of solar panels **102-110**. In some embodiments, at least one solar panel (e.g., solar panel **102**) may remain positioned atop housing **218**. When retracted, and as depicted in FIG. **8**, the stackable track **112** (and the set of solar panels **102-110**, **120**) may be folded (or stacked) and retracted within housing **218**. In such embodiments, extendable solar assembly **200** may include an housing **218** removably attached to a mounting surface of a vehicle **10** or other structure (not shown), a track **112** removably attached to an opening of the housing **218** and configured to extend and retract between an extended position and a retracted position, a set of arms (e.g., first lateral arm **214** (not shown) and second lateral arm **216**) configured to be slidably movable with respect to the housing **218** between the extended position and the retracted position to provide structural stability, and a set of solar panels **102-110** that are coupled to (or otherwise securely attached to) track **112**. In some such embodiments, the set of solar panels **102-110** are extendable using a stackable/link function **132**.

[0044] FIG. **6** depicts a cross-sectional view of a stackable track **112** of extendable solar assembly including a stackable/link function **132**, according to one or more aspects described herein. In various embodiments, stackable track **112** may include stackable/link function **132**. In various embodiments, stackable/link function **132** may comprise a first portion **132a** (i.e., an inserting portion) and a second portion **132b** (i.e., a receiving portion) that may operate using a ratchet mechanism engaging first portion **132a** with second portion **132b**. In such embodiments, first portion **132a** of stackable/link function **132** may be mated to and received within an opening **132c** of second portion **132b** (or receiving portion). Such a ratchet mechanism may allow first portion **132a** (or inserting portion) to be operatively coupled with second portion **132b** of stackable/link function **132**, wherein the ratchet mechanism positions the first portion relative to the second portion in a removably attaching (securing or fastening) manner. In various embodiments, the first portion **132a** and second portion **132b** may be removably attachable relative to one another, such that extendable solar assembly **200** may move between a retracted position and an extended position.

[0045] As depicted in FIG. **6** (and FIG. **7**), as the extendable solar assembly **200** is retracted, each of the stackable links **130**, in series, may push upward (as depicted as “U”) until the stackable link **130** uncouples from the proceeding stackable link **130**, and stacks over the proceeding stackable link **130**. As the extendable solar assembly **200** is extended, each of the stackable links **130**, in series, may slide (e.g., pushes to left as depicted as “L”) toward a succeeding stackable link **130**, until the stackable link **130** couples to the succeeding stackable link **130**, and becomes substantially linear with the succeeding stackable link **130**. In some embodiments, the solar panels **102-110** may be attached, and positioned substantially parallel, to an elongated surface of stackable link **130**. Accordingly, solar panels **102-110** may extend and retract as stackable track **112** is extended and retracted, as described above.

[0046] FIG. **7** depicts a cross-sectional view of extendable solar assembly **200** having a stackable track **112** in an extended position, according to one or more aspects described herein. In various embodiments, extendable solar assembly **200** may include a set of solar panels **102**, **104**, **106**, **108**, **110** coupled to stackable links **130a**, **130b**, **130c**, **130d**, **130e**. In some embodiments, the stackable links **130a**, **130b**, **130c**, **130d**, **130e** may, using stackable/link function **132**, extend away from housing **218** to lead rail **212** along first lateral arm **214** (not shown) and/or second lateral arm **216** perpendicular to a longitudinal axis (or x-axis) of housing **218**. In various embodiments, stackable

links **130a**, **130b**, **130c**, **130d**, **130e** may be pivotably movable with respect to one another (and housing **218**) between an open (or extended) position (i.e., when the extendable solar assembly is in use, as depicted in FIG. 7) and a closed (or retracted) position (i.e., when the extendable solar assembly is not in use, as depicted in FIG. 8), as described herein.

[0047] FIG. 8 depicts a cross-sectional view of extendable solar assembly **200** having a stackable track **112** in a retracted position, according to one or more aspects described herein. In various embodiments, when extendable solar assembly **200** is not in use, stackable track **112** may allow extendable solar assembly **200** to be stackable, collapsible, or reduced in length, so that the extendable solar assembly **200** may be stored back within the housing **218** (for example, as depicted in FIG. 8).

[0048] In various embodiments, extendable solar assembly **200** may include any suitable number of solar panels or stackable links **130**. For example, as depicted in FIG. 7, extendable solar assembly **200** may include five stackable links **130**. In some embodiments, the stackable links **130** may be of equal length. In other embodiments, the stackable links **130** may be of different lengths. A stackable link **130** may be operatively coupled with another, wherein stackable/link function **132** of stackable link **130** pivotably positions the first portion of a first stackable link **130** relative to a second portion of a second stackable link **130**. In some embodiments, the number of stackable links **130** used may be determined based on a coverage area when the extendable solar assembly is in use and/or a number of solar panels included in extendable solar assembly **200**.

[0049] In various embodiments, stackable link **130** may be of any appropriate shape, size, type, or configuration, such that extendable solar assembly **200** may extend at an appropriate length when extendable solar assembly **200** is in a fully extended position. By way of a non-limiting example, the stackable link **130** may extend away from housing **218** to lead rail **212** along one or more lateral arms perpendicular to a longitudinal axis (or x-axis) of the housing **218** at an appropriate width.

[0050] In various embodiments, and by way of a non-limiting example, extendable solar assembly **200** may be any suitable length along a vehicle **10** or other structure. For example, extendable solar assembly **200** may be 5-20 feet in length (measured by the length of a mounting surface running along a vehicle **10** or other structure). By way of non-limiting example, extendable solar assembly **200** may be 10, 15, or 20 feet long. In various embodiments, when in an extended position, extendable solar assembly **200** may project from a vehicle **10** or other structure 3-6 feet. By way of non-limiting example, extendable solar assembly **200** may project 4 feet from a vehicle **10** or other structure to which extendable solar assembly **200** is attached (i.e., from first end **102a** to second end **102b**). It would be appreciated by one having ordinary skill in the art that extendable solar assembly may measure less than 5 feet in length and more than 20 feet in length. It would also be appreciated by one having ordinary skill in the art that extendable solar assembly **200** may project less than 3 feet and more than 6 feet from a vehicle when in an extended position.

[0051] Advantageously, the extendable solar assembly **200** provides power to the vehicle **10** or other structure to which extendable solar assembly **200** is coupled. For example, extendable solar assembly **200** may provide power to recreational vehicles when stationary, allowing users full enjoyment of electrical devices without worrying about reduced battery power.

[0052] In some embodiments, extendable solar assembly **200** may be secured in the closed/retracted position (or in the open position) via a biasing component. In various embodiments, the biasing component may comprise a spring. For example, the biasing component may comprise a torsion spring or any other suitable type of spring. In various embodiments, the extendable solar assembly **200** may include a locking portion configured to receive any appropriate biasing or locking components. In some embodiments, the biasing component may be adjusted to maintain a predetermined maximum and/or minimum length of the extendable solar assembly **200**.

[0053] FIGS. 9-14 depict various views of alternative configurations (or mechanisms) for extending and retracting extendable solar assembly **200** between an extended (E) and retracted (R)

position. For the purposes of illustration, the alternative configurations of FIGS. **9-14** are each depicted without a set of solar panels **102-110**. However, it would be understood by a person of ordinary skill in the art that each of the alternative configurations of FIGS. **9-14** would include a set of solar panels **102-110**, a housing **218**, and/or one or more other components of extendable solar assembly **200**, as described herein.

[0054] FIG. **9** depicts top cross-sectional views of extendable solar assembly **200** having an angled actuator **215** in an extended and retracted position, according to one or more aspects described herein. In various embodiments, extendable solar assembly **200** may include an actuator **215**. For example, actuator **215** may comprise a gas spring actuator, an electronic actuator, and/or any other type of suitable actuator now known or future developed. In some embodiments, extendable solar assembly **200** may include an actuator **215** instead of or in addition to one or more lateral arms (e.g., first and second lateral arms **214**, **216**) and/or one or more tracks (e.g., track **112** and second track **114**). In some embodiments, as depicted in FIG. **9**, extendable solar assembly **200** may include an actuator **215** that is angled and connected directly to lead rail **212** and a fixed base **219**. For example, the fixed base **219** may comprise, be included within, or located adjacent to housing **218**. In some embodiments, angled actuator **215** may be slidably movable (i.e., angularly) with respect to fixed base **219**, such that a lead rail **212** may move between an extended position (E) and a retracted position (R) as actuator **215** extends and an angle between angled actuator **215** and fixed base **219** increases. When extendable solar assembly **200** is in a retracted position, angled actuator **215** may be included or encompassed within a cavity formed by housing **218**.

[0055] FIG. **10** depicts top cross-sectional views of extendable solar assembly **200** having perpendicular actuators **215** in an extended and retracted position, according to one or more aspects described herein. In some embodiments, extendable solar assembly **200** may include one or more actuator **215** that are perpendicular and directly connected to a lead rail **212** and fixed base **219**. In such embodiments, extension of perpendicular actuator(s) **215** may cause lead rail **212** (and, accordingly, a set of solar panels **102-110**) to move between a retracted and extended position. Similarly, retraction of perpendicular actuator(s) **215** may cause lead rail **212** (and, accordingly, a set of solar panels **102-110**) to move between an extended and retracted position. In some embodiments, when extendable solar assembly **200** is in a retracted position, perpendicular actuator(s) **215** may be included or encompassed within a cavity formed by housing **218**. In other embodiments, when extendable solar assembly **200** is in a retracted position, perpendicular actuator(s) **215** may be positioned outside a cavity formed by housing **218**. For example, in some embodiments, perpendicular actuator(s) **215** may be integrated in a roof rack or any other roof components.

[0056] FIG. **11** depicts top cross-sectional views of extendable solar assembly **200** having actuated lateral arms **214**, **216** in an extended and retracted position, according to one or more aspects described herein. In some embodiments, as depicted in FIG. **11**, lateral arms **214**, **216** of extendable solar assembly **200** may each include an actuator **215**. For example, slidably movable actuators **215** may be configured to cause lateral arms **214**, **216** to extend and propel lead rail **212** away from housing **218**. Actuators **215** may similarly be used to cause lead rail to retract toward housing **218**, thus enabling movement of lateral arms **214**, **216** to control the movement of lead rail **212** and, in turn, the set of solar panels **102-110**.

[0057] FIG. **12** depicts top cross-sectional views of extendable solar assembly **200** having spring-loaded lateral arms **214**, **216** in an extended and retracted position, according to one or more aspects described herein. In some embodiments, as depicted in FIG. **12**, extendable solar assembly **200** may include a strap **217** connected to a motor M. For example, strap **217** may be connected to lead rail **212**, and motor M may be configured to pull strap **217** towards fixed base **219** to pull lead rail **212** towards housing **218**. Accordingly, motor M may be configured to pull strap **217** to pull extendable solar assembly **200** into a retracted position. In such embodiments, lateral arms **214**, **216** may be spring-loaded and configured to cause lead rail **212** to extend away from housing **218**

when tension in strap **217** is released, thereby causing extendable solar assembly **200** to move into an extended position. In such an embodiment, lateral arms **214**, **216** may comprise conventional box awning arms. In such an embodiment, strap **217** may replace a canopy as in a traditional awning.

[0058] FIG. **13** depicts top cross-sectional views of extendable solar assembly **200** having a scissor mechanism in an extended and retracted position, according to one or more aspects described herein. In some embodiments, as depicted in FIG. **13**, extendable solar assembly **200** may include a scissor mechanism **221**. In some embodiments, extendable solar assembly **200** may include a scissor mechanism **221** instead of or in addition to one or more lateral arms (e.g., first and second lateral arms **214**, **216**) and/or one or more tracks (e.g., track **112** and second track **114**). In some embodiments, scissor mechanism **221** may be connected (or pinned) to lead rail **212** and fixed base **219** at connecting points **222a**, **222b**, and arms of scissor mechanism **221** may also be connected (or pinned) to each other at connecting point **222c**. In such embodiments, the arms of scissor mechanism **221** may be configured to pivot relative to one another at connecting point **222c**. In some embodiments, scissor mechanism **221** may also be connected to each of lead rail **212** and fixed base at additional points having rollers **223a**, **223b**. In such embodiments, extendable solar assembly **200** may be configured to cause scissor mechanism **221** to move at rollers **223a**, **223b**, thereby causing lead rail **212** to extend and retract with respect to fixed base **219**. In some embodiments, the scissor mechanism **221** may be slidably movable (i.e., similar to slides in vertical arms) with respect to a fixed base **219**, such that a lead rail **212** may move (or position) between an extended position (E) and a retracted position (R). In some embodiments, extendable solar assembly **200** may include one or more multiple scissor mechanisms. In some embodiments, scissor mechanism **221** may include a threaded rod at fixed base **219** that is connected to rollers **223a**, **223b**. In some embodiments, scissor mechanism **221** may include an actuator **215** (not shown) connected to linkages **224a**, **224b** (similar to latitude arm gas springs). In some embodiments, scissor mechanism **221** may include an actuator **215** (not shown) connected between fixed base and linkages **224a**, **224b**. In some embodiments, scissor mechanism **221** may include a strap connected to lead rail **212** that may be pulled to retract lead rail **212** (as rollers **223a**, **223b** move away from connecting points **222a**, **222b**) and spring loaded arms that cause lead rail **212** to be extended away housing **218** (thereby pushing extendable solar assembly **200** into an extended position).

[0059] FIG. **14** depicts side cross-sectional views of extendable solar assembly **200** having a drawer slider mechanism in an extended and retracted position, according to one or more aspects described herein. In some embodiments, as depicted in FIG. **14**, extendable solar assembly **200** may include a drawer slider **230** with cables **232**, **234** (or links). For example, cables **232**, **234** may be connected to a motor M and may be slidably movable, such that the plates **236** may move between an extended position (E) and a retracted position (R). In some embodiments, a first cable **232** may be pulled by motor M to retract extendable solar assembly **200** into a retracted position (R), and a second cable **234** may be pulled by motor M to extend the plates **236** to cause extendable solar assembly **200** to move into an extended position (E). As depicted in FIG. **14**, an extendable solar assembly **200** having a drawer slider **230** may include three plates **236** (or links) for simplicity, but more drawers (or links) may be added. In some embodiments, drawer slider **230** with cables **232**, **234** may be of any appropriate number of drawers, shape, size, type, and/or configuration, such that extendable solar assembly **200** may extend to an appropriate length when in a fully extended position.

[0060] FIG. **15** depicts perspective views of extendable solar assembly **200** installed on a vehicle **10**, according to one or more aspects described herein. In some embodiments, extendable solar assembly **200** may include a set of solar panels **102-110**, one or more slidable lateral arms (e.g., slidable lateral arms **214**, **216**), a housing **218**, and/or one or more other components. Together, the one or more components of extendable solar assembly **200** may form an awning canopy with the

set of solar panels **102-110** defining a top surface of the awning canopy. In some embodiments, extendable solar assembly **200** may also include one or more plates **236** extending between the slidable lateral arms **214, 216**, each configured to support at least one solar panel of the set of solar panels **102-110**. In various embodiments, the one or more slidable lateral arms are configured to support the one or more solar panels **102-110**. In some embodiments, the one or more slidable lateral arms may comprise two slidable lateral arms, such as slidable lateral arms **214, 216** depicted in FIG. **15**. In some such embodiments, slidable lateral arms **214, 216** may be configured to each support an outside edge of the one or more solar panels **102-110**. In some embodiments, the one or more slidable lateral arms are configured to support an outside edge and/or support (or form) an inside support for the set of one or more solar panels. In various embodiments, the one or more slidable lateral arms (e.g., slidable lateral arms **214, 216**) are configured to extend outwardly when extendable solar assembly **200** extends from the retracted position to the extended position and collapse such that they may be stored (or included within) a cavity formed by housing **218** when extendable solar assembly **200** retracts from an extended position to a retracted position. In various embodiments, the set of solar panels may be manually moved between an extended position and a retracted position. In other embodiments, one or more techniques described herein (e.g., with respect to FIGS. **9-14**) may be used to extend or retract lead rail **212** to cause extendable solar assembly **200** to move between an extended and retracted position. For example, actuators, a motor with straps or cables, a scissor mechanism, a drawer slide mechanism, and/or one or more other techniques may be used with the embodiment depicted in FIG. **15**. In some embodiments, one or more techniques described herein (e.g., with respect to FIGS. **9-14**) for extending or retracting a lead rail **212** may similarly be used to extend or retract one or more solar panels of the set of solar panels (i.e., without using lead rail **212**) and thus move extendable solar assembly **200** between an extended and retracted position. Indeed, in some instances of the embodiment depicted in FIG. **15**, lead rail **212** may be absent or entirely decorative. Instead, the set of solar panels **102-110** may be extended and retracted using the one or more slidable lateral arms (e.g., slidable lateral arms **214, 216**). Additionally, in some instances of the embodiment depicted in FIG. **15**, slidable lateral arms **214, 216** may obviate the need for a track, instead serving to also guide the set of solar panels **102-110**, in addition to supporting the set of solar panels **102-110** as the extendable solar assembly **200** moves between an extended and retracted position.

[0061] In various embodiments, the set of solar panels may be extendable in a cascading manner to improve performance/efficiency without requiring additional space to house or position the solar panels. In various embodiments, extendable solar assembly **200** may enable a set of solar panels **102-110** to be either stacked on top of each other (when in a retracted position) or projected outward in a side-by-side configuration to form an array (when in an extend position). In various embodiments, when in a retracted position, each solar panel of the set of solar panels may be stacked face up (i.e., with photovoltaic cells or surface configured to gather or receive sunlight facing up). In this manner, the set of solar panels may retract, from an extended position to a retracted position, into housing **218** like a deck of cards. In other embodiments, when in a retracted position, the set of solar panels may be stacked in an alternating manner such that, for example, a given solar panel is stacked face up, a next adjacent solar panel is stacked face down, the next adjacent solar panel is stacked face up, and so on. For example, in some embodiments, each solar panel of the set of solar panels may be connected via a hinge or other mechanism such that the solar panels fold at the hinge to stack on top of one another in an inverted (or alternating) manner when extendable solar assembly **200** is in a retracted position. In this manner, the set of solar panels may fold up when retracting, from an extended position to a retracted position, like a map until the set of solar panels are stacked and stowed in a retracted position (e.g., within a cavity defined by housing **218**). In some embodiments when the set of solar panels are stacked in an alternating manner, a topmost solar panel (or set of solar panels) that is exposed when extendable solar assembly **200** is in a retracted position may be stacked facing upward to gather (or receive) sunlight

(e.g., in a low-power mode, as described herein). In other embodiments when the set of solar panels are stacked in an alternating manner, a topmost solar panel (or set of solar panels) defining a top surface of the extendable solar assembly **200** when extendable solar assembly is in a retracted position may be stacked face down to protect the topmost solar panel (or set of solar panels) from the elements (e.g., debris, hail, and/or other potential harmful objects or aspects of the environment) when extendable solar assembly **200** is in a retracted position (and potentially not in use).

[0062] It is to be understood that the invention is not limited in its application to the details of construction and the arrangement of the components set forth herein. The invention is capable of other embodiments and of being practiced or being carried out in various ways. Variations and modifications of the foregoing are within the scope of the present invention. It should be understood that the invention disclosed and defined herein extends to all alternative combinations of two or more of the individual features mentioned or evident from the text and/or drawings. All of these different combinations constitute various alternative aspects of the present invention. The embodiments described herein explain the best modes known for practicing the invention and will enable others skilled in the art to utilize the invention.

[0063] While the preferred embodiments of the invention have been shown and described, it will be apparent to those skilled in the art that changes and modifications may be made therein without departing from the spirit of the invention, the scope of which is defined by this description.

[0064] Reference in this specification to “one implementation”, “an implementation”, “some implementations”, “various implementations”, “certain implementations”, “other implementations”, “one series of implementations”, or the like means that a particular feature, design, structure, or characteristic described in connection with the implementation is included in at least one implementation of the disclosure. The appearances of, for example, the phrase “in one implementation” or “in an implementation” in various places in the specification are not necessarily all referring to the same implementation, nor are separate or alternative implementations mutually exclusive of other implementations. Moreover, whether or not there is express reference to an “implementation” or the like, various features are described, which may be variously combined and included in some implementations, but also variously omitted in other implementations. Similarly, various features are described that may be preferences or requirements for some implementations, but not other implementations.

[0065] The language used herein has been principally selected for readability and instructional purposes, and it may not have been selected to delineate or circumscribe the inventive subject matter. Other implementations, uses and advantages of the invention will be apparent to those skilled in the art from consideration of the specification and practice of the invention disclosed herein. The specification should be considered exemplary only, and the scope of the invention is accordingly intended to be limited only by the following claims.

Claims

1. An extendable solar assembly comprising: a housing securely affixed to a structure during use; a set of arms attached to the housing and configured to support a lead rail of the extendable solar assembly as the extendable solar assembly extends from a retracted position to an extended position; at least one track coupled to the housing and the lead rail and configured to extend and retract as the extendable solar assembly extends from the retracted position to the extended position; and a set of solar panels coupled to the at least one track, wherein the solar panels are configured to be stacked within the housing when the extendable solar assembly is in the retracted position.
2. The extendable solar assembly of claim 1, wherein the structure comprises an exterior surface of a vehicle.

3. The extendable solar assembly of claim 1, the at least one track comprising a first track and a second track, wherein the set of solar panels are coupled to the first track and the second track.
4. The extendable solar assembly of claim 1, wherein each of the set of arms, the at least one track, and the set of solar panels are retracted within the housing when the extendable solar assembly is in the retracted position.
5. The extendable solar assembly of claim 1, wherein when the set of solar panels are stacked within the housing when the extendable solar assembly is in the retracted position, at least one solar panel of the set of solar panels remains exposed, is able to gather sunlight to generate electricity, and comprises a top surface of the extendable solar assembly.
6. The extendable solar assembly of claim 1, wherein the extendable solar assembly comprises a self-contained, standalone unit configured to be removed and attached to another structure.
7. The extendable solar assembly of claim 1, wherein the set of solar panels are coupled to the at least one track via progressively taller risers.
8. The extendable solar assembly of claim 1, wherein the at least one track comprises an angled track.
9. The extendable solar assembly of claim 1, wherein the at least one track comprises a stackable track including a series of stackable links, each pivotably movable with respect to an adjacent stackable link.
10. The extendable solar assembly of claim 1, further comprising one or more actuators connected to at least the lead rail and configured to cause the extendable solar assembly to extend from the retracted position to the extended position.
11. The extendable solar assembly of claim 10, wherein the one or more actuators are retracted within the housing when the extendable solar assembly is in the retracted position.
12. The extendable solar assembly of claim 1, wherein the set of arms comprise actuated arms configured to cause the extendable solar assembly to move between the retracted position and the extended position.
13. The extendable solar assembly of claim 1, further comprising a motor configured to manipulate a strap or a cable to cause extendable solar assembly to move between the retracted position and the extended position.
14. The extendable solar assembly of claim 1, wherein a topmost solar panel of the set of solar panels when the set of solar panels are stacked within the housing comprises a curved solar panel.
15. The extendable solar assembly of claim 1, wherein each of the set of solar panels are stacked face up within the housing when the extendable solar assembly is in the retracted position.
16. The extendable solar assembly of claim 1, wherein each solar panel of the set of solar panels is stacked in an alternating manner relative to at least one adjacent solar panel of the set of solar panels within the housing when the extendable solar assembly is in the retracted position.
17. An extendable solar assembly comprising: a housing securely affixed to a structure during use; and a set of sliding arms configured to extend outwardly when the extendable solar assembly extends from a retracted position to an extended position and collapse when the extendable solar assembly retracts from the extended position to the retracted position; and a set of solar panels that are coupled to the set of sliding arms, wherein the solar panels are configured to be stacked within the housing when the extendable solar assembly is in the retracted position.
18. The extendable solar assembly of claim 17, wherein the structure comprises an exterior surface of a vehicle.
19. The extendable solar assembly of claim 17, wherein the set of sliding arms include two sliding arms, each configured to support an outside edge of the set of solar panels.
20. The extendable solar assembly of claim 17, wherein the set of sliding arms are retracted within the housing when the extendable solar assembly is in the retracted position.
21. The extendable solar assembly of claim 17, wherein when the set of solar panels are stacked within the housing when the extendable solar assembly is in the retracted position, at least one solar

panel of the set of solar panels remains exposed, is able to gather sunlight to generate electricity, and comprises a top surface of the extendable solar assembly.

22. The extendable solar assembly of claim 17, wherein the extendable solar assembly comprises a self-contained, standalone unit configured to be removed and attached to another structure.
