

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275772

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Krasniak; Carolyn M. et al.

BONE PUNCH INSTRUMENT

Abstract

A medical device configured to form one or more holes within a bone of a patient may include a handle assembly including a housing, a lever rotatably coupled to the housing, and a sheath extending distally from the housing, the handle assembly including a spring biasing the lever toward an initial or intermediate position; and a bone punch including an elongate shaft, a head at a proximal end of the elongate shaft, and a piercing tip at a distal end of the elongate shaft configured to be driven into the bone. The elongate shaft may be slidably disposed within the sheath in a first position when the lever is in the initial or intermediate position. Translation of the bone punch distally within the sheath from the first position to a second position may cause a distal end of the lever to rotate away from the housing to an extended position.

Inventors: Krasniak; Carolyn M. (Melrose, MA), Pierce; Cori G. (Salem, NH), Falco; Kevin M. (Chelmsford, MA), Barnes; Jeffrey L. (Medford, MA)

Applicant: Smith & Nephew, Inc. (Memphis, TN); Smith & Nephew Orthopaedics AG (Zug, CH); Smith & Nephew Asia Pacific Pte. Limited (N/A, N/A)

Family ID: 75539913

Assignee: Smith & Nephew, Inc. (Memphis, TN); Smith & Nephew Orthopaedics AG (Zug, CH); Smith & Nephew Asia Pacific Pte. Limited (N/A, omitted)

Appl. No.: 19/177931

Filed: April 14, 2025

Related U.S. Application Data

parent US continuation 17899253 20220830 parent-grant-document US 12295591 child US 19177931

parent US continuation PCT/US2021/023011 20210318 PENDING child US 17899253

us-provisional-application US 62991993 20200319

us-provisional-application US 63091107 20201013

Publication Classification

Int. Cl.: A61B17/16 (20060101); A61B17/06 (20060101)

U.S. Cl.:

CPC A61B17/1604 (20130101); A61B17/06066 (20130101);

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 17/899,253, filed Aug. 30, 2022, which is a continuation of International Application No. PCT/US2021/023011, filed Mar. 18, 2021, which claims the benefit of and priority to U.S. Provisional Patent Application Ser. No. 62/991,993, filed on Mar. 19, 2020, and U.S. Provisional Patent Application Ser. No. 63/091,107, filed on Oct. 13, 2020, the disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

[0002] The present disclosure pertains generally to medical devices, and methods for manufacturing and/or using medical devices. More particularly, the present disclosure pertains to devices for making an aperture in bone within patients, and methods for manufacturing and using such devices.

BACKGROUND

[0003] Injuries may require the placement of anchors and/or implants into the bone(s) of a patient to repair. In one example, injuries to tendons may be treated by affixing a tendon repair implant to one or more bones associated with an articulating joint, such as the glenohumeral joint. Such affixation may use an anchor member, such as a staple, or other securement element inserted at least partially into bone, and in some cases, inserted at least partially into holes formed in the bone to receive the anchor member, staple, or other securement element. Formation of these holes and subsequent removal of a tool for doing so may be difficult due to the cortical elasticity of the bone. Of the known medical devices, and methods of manufacturing and using those devices, each has certain advantages and disadvantages. There is an ongoing need for improved and/or alternative medical devices and methods of making and using such devices.

SUMMARY

[0004] In one example, a medical device configured to form one or more holes within a bone of a patient may comprise a handle assembly including a housing, a lever rotatably coupled to the housing between an initial position and an extended position, and a sheath extending distally from the housing; and a bone punch including an elongate shaft, a head at a proximal end of the elongate shaft, and a piercing tip at a distal end of the elongate shaft, wherein the piercing tip is configured to be driven into the bone. The elongate shaft may be slidably disposed within the sheath in a first position when the lever is in the initial position. Translation of the bone punch distally within the sheath from the first position to a second position may cause a distal end of the lever to rotate away from the housing to the extended position.

[0005] In addition or alternatively to any example disclosed herein, the head of the bone punch is releasably engaged with the housing in the first position.

[0006] In addition or alternatively to any example disclosed herein, a distal surface of the head of the bone punch engages a proximal surface of the housing in the second position.

[0007] In addition or alternatively to any example disclosed herein, less than 40% of the piercing tip extends distally of the sheath in the first position.

[0008] In addition or alternatively to any example disclosed herein, translation of the bone punch distally within the sheath from the first position to the second position causes the distal end of the lever to rotate away from a longitudinal axis of the bone punch.

[0009] In addition or alternatively to any example disclosed herein, a distal end of the sheath is configured to be disposed adjacent a surface of the bone. A rotational position of the lever relative to the housing may indicate a depth of the piercing tip within the bone.

[0010] In addition or alternatively to any example disclosed herein, rotation of the lever from the extended position toward the initial position generates proximal translation of the bone punch to extract the piercing tip from the bone.

[0011] In addition or alternatively to any example disclosed herein, the handle assembly includes a spring biasing the lever toward the initial position.

[0012] In a second example, a medical device configured to form one or more holes within a bone of a patient may comprise: a handle assembly including a housing, a lever rotatably coupled to the housing between an initial position and an extended position, and a sheath extending distally from the housing; and a bone punch including an elongate shaft, a head at a proximal end of the elongate shaft, and a piercing tip at a distal end of the elongate shaft, wherein the piercing tip is configured to be driven into the bone. The elongate shaft may be slidably disposed within the sheath in a first position when the lever is in the initial position. The handle assembly may include a linkage disposed within the housing. The head of the bone punch may engage the linkage in the first position and distal translation of the bone punch from the first position to a second position may cause the linkage to rotate a distal end of the lever away from the housing to the extended position.

[0013] In addition or alternatively to any example disclosed herein, the linkage includes an ejector block slidably disposed within the housing.

[0014] In addition or alternatively to any example disclosed herein, the linkage further includes a distal link pivotably engaged with the housing at a distal pivot point and a middle link pivotably engaged with the ejector block at a proximal pivot point.

[0015] In addition or alternatively to any example disclosed herein, the distal link is pivotably engaged with the middle link at an intermediate pivot point between the distal pivot point and the proximal pivot point.

[0016] In addition or alternatively to any example disclosed herein, the distal link includes a cam surface configured to engage the lever.

[0017] In addition or alternatively to any example disclosed herein, distal translation of the head of the bone punch from the first position to the second position translates the ejector block distally within the housing.

[0018] In addition or alternatively to any example disclosed herein, rotation of the lever toward a longitudinal axis of the bone punch when the bone punch is in the second position actuates the linkage to translate the head of the bone punch proximally to extract the piercing tip from the bone.

[0019] In addition or alternatively to any example disclosed herein, the handle assembly includes a spring biasing the lever toward the initial position.

[0020] In a third example, a medical device configured to form one or more holes within a bone of a patient may comprise: a handle assembly including a housing, a lever rotatably coupled to the housing between an initial position and an extended position, and a sheath extending distally from the housing; and a bone punch including an elongate shaft having gear teeth extending outwardly therefrom, a head at a proximal end of the elongate shaft, and a piercing tip at a distal end of the elongate shaft, wherein the piercing tip is configured to be driven into the bone. The elongate shaft may be slidably disposed within the sheath in a first position when the lever is in the initial position. The handle assembly may include a plurality of gears disposed within the housing, at least one of the plurality of gears being configured to engage with the gear teeth of the elongate shaft. The head of the bone punch may be spaced away from a proximal surface of the housing in the first position and distal translation of the bone punch from the first position to a second position may

cause the plurality of gears to rotate a distal end of the lever away from the housing to the extended position.

[0021] In addition or alternatively to any example disclosed herein, in the initial position, the lever is engaged with an outer surface of the housing.

[0022] In addition or alternatively to any example disclosed herein, in the initial position, the lever extends toward a distal end of the sheath generally parallel to a longitudinal axis of the sheath.

[0023] In addition or alternatively to any example disclosed herein, in the extended position, the lever extends toward a distal end of the sheath at an oblique angle to the sheath.

[0024] In addition or alternatively to any example disclosed herein, in the second position, a distal surface of the head of the bone punch is engaged with a proximal surface of the housing.

[0025] In addition or alternatively to any example disclosed herein, the plurality of gears includes a first gear configured to engage the gear teeth of the elongate shaft, a second gear fixedly secured to the lever, and a third gear engaged with both the first gear and the second gear.

[0026] In a fourth example, a medical device configured to form one or more holes within a bone of a patient may comprise: a handle assembly including a housing, a lever rotatably coupled to the housing between an initial position and an extended position, and a sheath extending distally from the housing; and a bone punch including an elongate shaft, a head at a proximal end of the elongate shaft, and a piercing tip at a distal end of the elongate shaft, wherein the piercing tip is configured to be driven into the bone. The elongate shaft may be slidably disposed within the sheath in a first position when the lever is in the initial position. The handle assembly may include a linkage disposed within the housing, the linkage including an ejector block slidably disposed within the housing. The head of the bone punch may be releasably coupled to the ejector block in the first position, and distal translation of the bone punch from the first position to a second position may cause the linkage to rotate a distal end of the lever away from the housing to the extended position.

[0027] In addition or alternatively to any example disclosed herein, the head of the bone punch is magnetically coupled to the ejector block.

[0028] In addition or alternatively to any example disclosed herein, the head of the bone punch includes one or more magnets disposed therein and the ejector block includes a magnetic material disposed therein opposite the one or more magnets.

[0029] In addition or alternatively to any example disclosed herein, the ejector block includes one or more magnets disposed therein and the head of the bone punch includes a magnetic material disposed therein opposite the one or more magnets.

[0030] In addition or alternatively to any example disclosed herein, the head of the bone punch includes one or more magnets disposed therein and the ejector block includes one or more magnets disposed therein opposite the one or more magnets disposed in the head of the bone punch.

[0031] In addition or alternatively to any example disclosed herein, distal translation of the head of the bone punch from the first position to the second position translates the ejector block distally within the housing.

[0032] In addition or alternatively to any example disclosed herein, rotation of the lever from the extended position toward a longitudinal axis of the bone punch when the bone punch is in the second position generates proximal translation of the bone punch to extract the piercing tip from the bone.

[0033] In addition or alternatively to any example disclosed herein, at least a portion of the head of the bone punch is configured to pass through an opening in a wall of the housing as the bone punch is translated from the first position to the second position.

[0034] The above summary of some embodiments, aspects, and/or examples is not intended to describe each disclosed embodiment or every implementation of the present disclosure. The figures and the detailed description which follows more particularly exemplify these embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0035] The disclosure may be more completely understood in consideration of the following detailed description in connection with the accompanying drawings, in which:

[0036] FIG. 1 is a stylized anterior view of a shoulder including a humerus and a scapula;

[0037] FIG. 2 is a stylized anterior view of a shoulder depicting the head of the humerus shown mating with the glenoid fossa of the scapula at a glenohumeral joint and a sheet-like material is affixed to the tendon;

[0038] FIG. 3 is a perspective view illustrating aspects of an example bone punch;

[0039] FIG. 4 is a side view illustrating aspects of an example medical device;

[0040] FIG. 5 illustrates aspects of the medical device of FIG. 4 with the lever in an initial or intermediate position;

[0041] FIG. 6 illustrates aspects of the medical device of FIG. 4 with the lever in an extended position;

[0042] FIG. 7 is a detailed view illustrating aspects of the medical device of FIG. 4 with the lever in the extended position of FIG. 6;

[0043] FIGS. 8-10 are perspective views illustrating aspects of the medical device of FIG. 4 with the lever in the extended position of FIG. 6;

[0044] FIG. 11 illustrates aspects of the medical device of FIG. 4 with the lever in a disengagement position;

[0045] FIG. 12 is a partial cross-sectional view depicting the medical device of FIG. 4 and the bone punch of FIG. 3 disposed at an implant site after the bone punch has been driven into bone at the implant site;

[0046] FIG. 13 is a partial cross-sectional view depicting the medical device of FIG. 4 and the bone punch of FIG. 3 disposed at an implant site after the bone punch has been driven into and removed from bone at the implant site;

[0047] FIG. 14 is a perspective view of an example bone staple inserter;

[0048] FIG. 15 is a perspective view of an example bone staple;

[0049] FIG. 16 is a side view illustrating aspects of an example medical device;

[0050] FIG. 17 illustrates aspects of the medical device of FIG. 16 with the lever in an initial position;

[0051] FIG. 18 illustrates aspects of the medical device of FIG. 16 with the lever in an extended position;

[0052] FIG. 19 is a perspective view illustrating aspects of an example bone punch;

[0053] FIG. 19A is a view of the head of the bone punch taken along line 19A-19A of FIG. 19;

[0054] FIG. 20 is a side view illustrating aspects of an example medical device;

[0055] FIG. 21 illustrates aspects of the medical device of FIG. 20 with the lever in an initial or intermediate position;

[0056] FIG. 22 illustrates aspects of the medical device of FIG. 20 with the lever in an extended position;

[0057] FIG. 23 is a detailed view illustrating aspects of the medical device of FIG. 20 with the lever in the extended position of FIG. 22;

[0058] FIG. 24 illustrates aspects of the medical device of FIG. 20 with the lever in a disengagement position; and

[0059] FIG. 25 illustrates selected aspects of an example configuration of the medical device of FIG. 20;

[0060] FIG. 26 illustrates selected aspects of an example configuration of the medical device of FIG. 20; and

[0061] FIG. 27 illustrates selected aspects of an example configuration of the medical device of FIG. 20.

[0062] While aspects of the disclosure are amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in detail. It should be understood, however, that the intention is not to limit aspects of the disclosure to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the disclosure.

DETAILED DESCRIPTION

[0063] The following description should be read with reference to the drawings, which are not necessarily to scale, wherein like reference numerals indicate like elements throughout the several views. The detailed description and drawings are intended to illustrate but not limit the claimed invention. Those skilled in the art will recognize that the various elements described and/or shown may be arranged in various combinations and configurations without departing from the scope of the disclosure. The detailed description and drawings illustrate example embodiments of the claimed invention. However, in the interest of clarity and ease of understanding, while every feature and/or element may not be shown in each drawing, the feature(s) and/or element(s) may be understood to be present regardless, unless otherwise specified.

[0064] For the following defined terms, these definitions shall be applied, unless a different definition is given in the claims or elsewhere in this specification.

[0065] All numeric values are herein assumed to be modified by the term “about,” whether or not explicitly indicated. The term “about”, in the context of numeric values, generally refers to a range of numbers that one of skill in the art would consider equivalent to the recited value (e.g., having the same function or result). In many instances, the term “about” may include numbers that are rounded to the nearest significant figure. Other uses of the term “about” (e.g., in a context other than numeric values) may be assumed to have their ordinary and customary definition(s), as understood from and consistent with the context of the specification, unless otherwise specified.

[0066] The recitation of numerical ranges by endpoints includes all numbers within that range, including the endpoints (e.g., 1 to 5 includes 1, 1.5, 2, 2.75, 3, 3.80, 4, and 5).

[0067] Although some suitable dimensions, ranges, and/or values pertaining to various components, features and/or specifications are disclosed, one of skill in the art, incited by the present disclosure, would understand desired dimensions, ranges, and/or values may deviate from those expressly disclosed.

[0068] As used in this specification and the appended claims, the singular forms “a”, “an”, and “the” include plural referents unless the content clearly dictates otherwise. As used in this specification and the appended claims, the term “or” is generally employed in its sense including “and/or” unless the content clearly dictates otherwise. It is to be noted that in order to facilitate understanding, certain features of the disclosure may be described in the singular, even though those features may be plural or recurring within the disclosed embodiment(s). Each instance of the features may include and/or be encompassed by the singular disclosure(s), unless expressly stated to the contrary. For simplicity and clarity purposes, not all elements of the disclosed invention are necessarily shown in each figure or discussed in detail below. However, it will be understood that the following discussion may apply equally to any and/or all of the components for which there are more than one, unless explicitly stated to the contrary. Additionally, not all instances of some elements or features may be shown in each figure for clarity.

[0069] Relative terms such as “proximal”, “distal”, “advance”, “retract”, variants thereof, and the like, may be generally considered with respect to the positioning, direction, and/or operation of various elements relative to a user/operator/manipulator of the device, wherein “proximal” and “retract” indicate or refer to closer to or toward the user and “distal” and “advance” indicate or refer to farther from or away from the user. In some instances, the terms “proximal” and “distal” may be arbitrarily assigned in an effort to facilitate understanding of the disclosure, and such

instances will be readily apparent to the skilled artisan. Other relative terms, such as “upstream”, “downstream”, “inflow”, and “outflow” refer to a direction of fluid flow within a lumen, such as a body lumen, a blood vessel, or within a device. Still other relative terms, such as “axial”, “circumferential”, “longitudinal”, “lateral”, “radial”, etc. and/or variants thereof generally refer to direction and/or orientation relative to a central longitudinal axis of the disclosed structure or device.

[0070] The term “extent” may be understood to mean a greatest measurement of a stated or identified dimension, unless the extent or dimension in question is preceded by or identified as a “minimum”, which may be understood to mean a smallest measurement of the stated or identified dimension. For example, “outer extent” may be understood to mean an outer dimension, “radial extent” may be understood to mean a radial dimension, “longitudinal extent” may be understood to mean a longitudinal dimension, etc. Each instance of an “extent” may be different (e.g., axial, longitudinal, lateral, radial, circumferential, etc.) and will be apparent to the skilled person from the context of the individual usage. Generally, an “extent” may be considered a greatest possible dimension measured according to the intended usage, while a “minimum extent” may be considered a smallest possible dimension measured according to the intended usage. In some instances, an “extent” may generally be measured orthogonally within a plane and/or cross-section, but may be, as will be apparent from the particular context, measured differently—such as, but not limited to, angularly, radially, circumferentially (e.g., along an arc), etc.

[0071] The terms “monolithic” and “unitary” shall generally refer to an element or elements made from or consisting of a single structure or base unit/element. A monolithic and/or unitary element shall exclude structure and/or features made by assembling or otherwise joining multiple discrete structures or elements together, particularly where those discrete structures or elements remain individually identifiable.

[0072] It is noted that references in the specification to “an embodiment”, “some embodiments”, “other embodiments”, etc., indicate that the embodiment(s) described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it would be within the knowledge of one skilled in the art to implement the particular feature, structure, or characteristic in connection with other embodiments, whether or not explicitly described, unless clearly stated to the contrary. That is, the various individual elements described below, even if not explicitly shown in a particular combination, are nevertheless contemplated as being combinable or arrangeable with each other to form other additional embodiments or to complement and/or enrich the described embodiment(s), as would be understood by one of ordinary skill in the art.

[0073] For the purpose of clarity, certain identifying numerical nomenclature (e.g., first, second, third, fourth, etc.) may be used throughout the description and/or claims to name and/or differentiate between various described and/or claimed features. It is to be understood that the numerical nomenclature is not intended to be limiting and is exemplary only. In some embodiments, alterations of and deviations from previously used numerical nomenclature may be made in the interest of brevity and clarity. That is, a feature identified as a “first” element may later be referred to as a “second” element, a “third” element, etc. or may be omitted entirely, and/or a different feature may be referred to as the “first” element. The meaning and/or designation in each instance will be apparent to the skilled practitioner.

[0074] The figures generally illustrate selected components and/or arrangements of medical devices or instruments. It should be noted that in any given figure, some features of the medical devices or instruments may not be shown, or may be shown schematically, for simplicity. Additional details regarding some of the elements of the medical devices or instruments may be illustrated in other figures in greater detail. It is to be noted that in order to facilitate understanding,

certain features of the disclosure may be described in the singular, even though those features may be plural or recurring within the disclosed embodiment(s). Each instance of the features may include and/or be encompassed by the singular disclosure(s), unless expressly stated to the contrary. For example, a reference to features or elements may be equally referred to all instances and quantities beyond one of said feature or element. As such, it will be understood that the following discussion may apply equally to any and/or all of the elements for which there are more than one within the medical devices or instruments, unless explicitly stated to the contrary. Additionally, not all instances of some elements or features may be shown in each figure for clarity.

[0075] FIG. 1 is a stylized anterior view of a patient 20 illustrating one example area that may benefit from the disclosed invention. For purposes of illustration, a shoulder 22 of patient 20 is shown in partial cross-section in FIG. 1. The shoulder 22 includes a humerus 14 and a scapula 12. In FIG. 1, a head 24 of the humerus 14 can be seen mating with a glenoid fossa of the scapula 12 at a glenohumeral joint. With reference to FIG. 1, it will be appreciated that the glenoid fossa comprises a shallow depression in the scapula 12. Movement of the humerus 14 relative to the scapula 12 is controlled by a number of muscles including: the deltoid, the supraspinatus, the infraspinatus, the subscapularis, and the teres minor. For purposes of illustration, only the supraspinatus 26 is shown in FIG. 1.

[0076] In FIG. 1, a distal tendon 28 of the supraspinatus 26 meets the humerus 14 at an insertion point. The scapula 12 of the shoulder 22 includes an acromion 32. In FIG. 1, a subacromial bursa 34 is shown extending between the acromion 32 of the scapula 12 and the head 24 of the humerus 14. The subacromial bursa 34 is shown overlaying the supraspinatus 26 as well as the distal tendon 28 and a portion of the humerus 14. The subacromial bursa 34 is one of the hundreds of bursae found the human body. Each bursa comprises a fluid filled sac. The presence of these bursae in the body reduces friction between bodily tissues.

[0077] The exemplary staples or fasteners described herein may be used to affix tendon repair implants to various target tissues in one example use of the disclosed medical device(s). The shoulder 22 depicted in FIG. 1 is one example where a tendon repair implant may be affixed to one or more bones associated with an articulating joint, such as the glenohumeral joint. Additionally, the tendon repair implant may be affixed to one or more tendons to be treated. In some cases, the tendons to be treated may be torn, partially torn, have internal micro-tears, be untorn, and/or be thinned due to age, injury or overuse.

[0078] FIG. 2 is a stylized anterior view of the shoulder 22 including the humerus 14 and the scapula 12. In FIG. 2, the head 24 of the humerus 14 is shown mating with the glenoid fossa of the scapula 12 at the glenohumeral joint. The supraspinatus 26 is also shown in FIG. 2. This muscle, along with others, controls the movement of the humerus 14 relative to the scapula 12. The distal tendon 28 of the supraspinatus 26 meets the humerus 14 at an insertion point 30.

[0079] As depicted in FIG. 2, the distal tendon 28 may include a first damaged portion 36. A number of loose tendon fibers 40 in the first damaged portion 36 are visible in FIG. 2. The first damaged portion 36 includes a first tear 42 extending partially through the distal tendon 28. The first tear 42 may therefore be referred to as a partial thickness tear. In FIG. 2, the first tear 42 begins on the side of the distal tendon 28 facing the subacromial bursa (e.g., FIG. 1) and ends midway through the distal tendon 28. Accordingly, the first tear 42 may be referred to as a bursal side tear.

[0080] In FIG. 2, the distal tendon 28 also includes a second damaged portion 38 located near insertion point 30. As illustrated, the second damaged portion 38 of the distal tendon 28 has become frayed and a number of loose tendon fibers 40 are visible. The second damaged portion 38 of the distal tendon 28 includes a second tear 44. The second tear 44 begins on the side of the distal tendon 28 facing the center of the head 24 of the humerus 14. Accordingly, the second damaged portion 38 may be referred to as an articular side tear.

[0081] FIG. 2 illustrates a sheet-like implant 50 has been placed over the bursal side of the distal

tendon **28**. The sheet-like implant **50** may be affixed to the distal tendon **28** by a plurality of tendon staples **51**. The sheet-like implant **50** may be affixed to the humerus **14** by one or more bone staples **100**, or other similar and/or suitable bone anchors. The sheet-like implant **50** extends over the insertion point **30**, the first tear **42**, and the second tear **44**. Some methods in accordance with this disclosure may include placing a tendon repair implant on the bursal side of a tendon regardless of whether the tears being treated are on the bursal side, the articular side, or within the tendon. In some cases, the exact location and nature of the tears being treated may be unknown. In some cases, the tendon repair implant may be applied to the bursal side of the tendon to treat shoulder pain that is most likely caused by one or more partial thickness tears in the tendon.

[0082] In some embodiments, a medical device may be used to form one or more holes within a bone (e.g., the humerus **14**) of a patient to facilitate placement of the one or more bone staples **100** and/or to secure the sheet-like implant **50** to the bone. In some embodiments, the medical device (e.g., FIG. **4**) may include a bone punch **270** including an elongate shaft **274**, a head **276** disposed at a proximal end of the elongate shaft **274**, and a piercing tip **272** disposed at a distal end **275** of the elongate shaft **274**, as shown in FIG. **3** for example. In some embodiments, the bone punch **270** and/or the piercing tip **272** may include a plurality of piercing tips, two or more piercing tips, a pair of piercing tips, etc. extending distally from the distal end **275** of the elongate shaft **274**. The piercing tip **272** may be configured to be driven into the bone (e.g., the humerus **14**). In some embodiments, the piercing tip **272** may be a spike, a prong, a spear, or other suitable shape. As such, the piercing tip **272** may include a sharpened distal end and/or a tapered distal portion configured to engage and/or penetrate bone.

[0083] In some embodiments, the head **276** of the bone punch **270** may include a plurality of connecting members **278**. Each of the plurality of connecting members **278** may include an outwardly extending protrusion **279**. In some embodiments, the plurality of connecting members **278** may be fixedly attached to opposing sides of the head **276**. The plurality of connecting members **278** may extend from the head **276** distally toward the distal end **275** of the elongate shaft **274**. The plurality of connecting members **278** may extend laterally outward from the head **276** at an oblique angle to a longitudinal axis of the bone punch **270** and/or the elongate shaft **274**. In some embodiments, the plurality of connecting members **278** may be biased laterally outward from the head **276**. Additional details regarding the plurality of connecting members **278** and their use will become apparent from the discussion herein.

[0084] In some embodiments, the head **276** may include one or more lateral projections. In some embodiments, the one or more lateral projections may be disposed between the plurality of connecting members **278** and/or between a proximal end of the head **276** and a distal end of the head **276**. The one or more lateral projections may each and/or collectively define a distal surface **277** of the head **276**. The distal surface **277** may be a distally facing surface and does not necessarily need to be a distalmost surface of the head **276**. For example, the distal surface **277** may be disposed between the proximal end of the head **276** and the distal end of the head **276**.

[0085] In some embodiments, the proximal end of the elongate shaft **274** may extend into the head **276** of the bone punch **270**. In some embodiments, the proximal end of the elongate shaft **274** may be fixedly attached to the head **276**. In some embodiments, the elongate shaft **274** may be monolithically formed with the head **276**, such as by casting, molding, or machining, for example. Other configurations are also contemplated. Similarly, a proximal end of the piercing tip **272** may extend into the distal end **275** of the elongate shaft **274**. The proximal end of the piercing tip **272** may be fixedly attached to the elongate shaft **274**. In some embodiments, the piercing tip **272** may be monolithically formed with the elongate shaft **274**, such as by casting, molding, or machining, for example. Other configurations are also contemplated. Some examples of suitable but non-limiting materials for the bone punch **270** and/or elements or components thereof are described below.

[0086] FIG. **4** illustrates aspects of a medical device configured to form one or more holes within a

bone of a patient in a side view. The medical device may comprise a handle assembly **200** including a housing **207**, a lever **205** rotatably coupled to the housing **207**, and a sheath **203** extending distally from the housing **207**. In at least some embodiments, a proximal end of the sheath **203** may be fixedly attached to the housing **207**. The sheath **203** may extend into and/or within the housing **207**, such that the proximal end of the sheath **203** is disposed within a distal portion of the housing **207**, and the sheath **203** extends within the housing **207** and distally from a distal end of the housing **207**. Some examples of suitable but non-limiting materials for the housing **207**, the lever **205**, the sheath **203**, and/or elements or components thereof are described below.

[0087] The housing **207** may be formed as a multi-piece structure including a first housing portion **207A**, seen in FIG. **4**, and a second housing portion **207B**, not visible in FIG. **4**. For the purpose of illustration herein, one of the first housing portion **207A** or the second housing portion **207B** may be hidden from view in the figures to permit viewing of internal components and/or features thereof. The first housing portion **207A** and the second housing portion **207B** may be assembled together to form the housing **207**. In the illustrated example(s), fasteners such as screws and nuts may be used to assemble the housing **207**. However, other assembly and/or attachment means may also be used, including but not limited to snap fit, friction fit, pins, rivets, etc. In some embodiments, once the housing **207** is assembled, such assembly may be considered and/or made permanent using any known suitable means, such as but not limited to adhesives, welding, etc.

[0088] The medical device may include the bone punch **270** described herein. The bone punch **270** may be disposed within and/or extend through the sheath **203**. The head **276** of the bone punch **270** may be releasably engaged with the housing **207** in a first position, as shown in FIGS. **4-5**. The piercing tip **272** may be positioned proximate a distal end of the sheath **203** in the first position. In some embodiments, the piercing tip **272** may be disposed within the distal end of the sheath **203** in the first position. In some embodiments, a portion of the piercing tip **272** may extend distally of the distal end of the sheath **203** in the first position to aid in positioning the medical device at a treatment site (e.g., to engage a surface of the bone). In some embodiments, less than 50% of the piercing tip **272** extends distally of the distal end of the sheath **203** in the first position. In some embodiments, less than 40% of the piercing tip **272** extends distally of the distal end of the sheath **203** in the first position. In some embodiments, less than 30% of the piercing tip **272** extends distally of the distal end of the sheath **203** in the first position. In some embodiments, less than 20% of the piercing tip **272** extends distally of the distal end of the sheath **203** in the first position. In some embodiments, less than 10% of the piercing tip **272** extends distally of the distal end of the sheath **203** in the first position. In some embodiments, less than 5% of the piercing tip **272** extends distally of the distal end of the sheath **203** in the first position.

[0089] FIG. **5** illustrates the medical device with the first housing portion **207A** of the handle assembly **200** removed and the second housing portion **207B** visible. The housing **207** may include a leg **210** extending laterally from a distal portion thereof. In some embodiments, the leg **210** may be disposed at and/or extend laterally from the distal end of the housing **207**. The lever **205** may be rotatably and/or pivotably coupled to the housing **207** about an axis of rotation. The handle assembly **200** may include a spring **211** biasing the lever **205** toward an initial position, such as an intermediate position. In at least some embodiments, the spring **211** may include a coiled portion disposed about and/or coaxial with the axis of rotation of the lever **205**.

[0090] In FIG. **5**, the lever **205** is shown disposed in the initial or intermediate position. In at least some embodiments, from the initial or intermediate position, the lever **205** may be configured to rotate a distal end **209** of the lever **205** toward or away from the housing **207**. In the initial or intermediate position, the distal end **209** of the lever **205** may be substantially aligned with and/or disposed within a free end of the leg **210**. In the initial or intermediate position, the lever **205** may extend distally toward a distal end of the sheath **203** and/or the handle assembly **200** at a first angle relative to a longitudinal axis of the sheath **203**. For example, the first angle may be less than about 15 degrees, less than about 10 degrees, less than about 5 degrees, about 0 degrees, or another small,

oblique angle. In some embodiments, in the initial or intermediate position, the lever **205** may extend toward the distal end of the sheath **203** generally parallel to a longitudinal axis of the sheath **203**.

[0091] In FIG. 5, the bone punch **270** is shown disposed in the first position. The elongate shaft **274** of the bone punch **270** is slidably disposed within the sheath **203** of the handle assembly **200** when the lever **205** is in the initial or intermediate position. The head **276** of the bone punch **270** may be releasably engaged with the housing **207** of the handle assembly **200** in the first position and/or when the lever **205** is in the initial or intermediate position. For example, the plurality of connecting members **278** and the outwardly extending protrusion(s) **279** thereof may engage a wall of the housing **207** defining a proximal surface **208** of the housing **207**. In some embodiments, the proximal surface **208** may be a proximally facing surface of the housing **207** at and/or proximate a proximal end of the housing **207**. In some embodiments, the proximal surface **208** may be a proximalmost surface of the housing **207**.

[0092] In the first position, the outwardly extending protrusion(s) **279** may extend laterally outward from the head **276** and/or the longitudinal axis of the bone punch **270** and/or the elongate shaft **274** beyond a perimeter of an opening in the wall of the housing **207** within which the head **276** is disposed. The outwardly extending protrusion(s) **279** may prevent the head **276** and/or the bone punch **270** from being removed from the housing **207** until the plurality of connecting members **278** are squeezed, urged, actuated, or otherwise moved inward toward the head **276**, and/or the longitudinal axis of the bone punch **270** and/or the elongate shaft **274**, to disengage the outwardly extending protrusion(s) **279** from the wall of the housing **207** by translating the outwardly extending protrusion(s) **279** inward until the outwardly extending protrusion(s) **279** are disposed within and/or inward of the perimeter of the opening. Doing so will permit the plurality of connecting members **278** and the outwardly extending protrusion(s) **279** to pass through the opening in the wall of the housing **207**. In the first position, the one or more lateral projections of the head **276** and/or the distal surface **277** of the head **276** may be spaced apart proximally from the proximal surface **208** of the wall of the housing **207**.

[0093] In some embodiments, the handle assembly **200** may include a linkage **220** disposed within the housing **207**. The linkage **220** will be described in more detail with respect to FIGS. 7-10. As may be seen in FIG. 5, the head **276** of the bone punch **270** may engage the linkage **220** in the first position. The linkage **220** may be pivotably engaged with and/or coupled to the housing **207**. The linkage **220** may include a plurality of elements that are movable and/or pivotable relative to each other. Translation of the bone punch **270** distally within the sheath **203**, and/or translation of the head **276** of the bone punch **270** distally relative to the housing **207**, from the first position to a second position distal of the first position may cause the linkage **220** to rotate the distal end **209** of the lever **205** away from the housing **207** and/or away from the longitudinal axis of the bone punch **270** and/or the elongate shaft **274** to an extended position, as shown in FIG. 6. In the extended position, the lever **205** may extend toward a distal end of the sheath **203** and/or the handle assembly **200** at a second angle relative to the longitudinal axis of the sheath **203**. In some embodiments, the second angle may be an oblique angle. The second angle may be greater than the first angle.

[0094] As shown in FIG. 6, the distal surface **277** of the head **276** of the bone punch **270** may engage and/or abut the proximal surface **208** of the housing **207** in the second position. In the second position, the outwardly extending protrusion(s) **279** may be spaced apart distally from the wall of the housing **207** defining the proximal surface **208**. However, the outwardly extending protrusion(s) **279** may still extend laterally outward from the head **276** and/or the longitudinal axis of the bone punch **270** and/or the elongate shaft **274** beyond the perimeter of the opening in the wall of the housing **207** within which the head **276** is disposed, thus preventing inadvertent removal of the bone punch **270** from the handle assembly **200**.

[0095] In the second position, the piercing tip **272** may be extended from the distal end of the

sheath **203** as the elongate shaft **274** is translated distally within the sheath **203**. The distal end of the sheath **203** may be configured to be disposed adjacent a surface of the bone. As the bone punch **270** is translated distally to the second position, the piercing tip **272** may be driven into the bone to form one or more holes in the bone. There may be a direct or indirect correlation between a rotational position of the lever **205** relative to the housing **207** and a depth of the piercing tip **272** within the bone. As the lever **205** rotates farther away from the housing **207** and/or as an angle between the lever **205** and the longitudinal axis of the sheath **203** and/or the bone punch **270** increases, the piercing tip **272** may be extended farther distally from the distal end of the sheath **203** and/or may be driven farther into the bone. A user of the medical device and/or the handle assembly **200** may be able to use the rotational position of the lever **205** relative to the housing **207** and/or the longitudinal axis of the sheath **203** and/or the bone punch **270** to indicate the depth of the piercing tip **272** within the bone, thereby providing a visual cue to the user about the status of the procedure.

[0096] Thereafter, rotation of the lever **205** from the extended position (e.g., FIG. **6**) toward the initial or intermediate position (e.g., FIG. **5**) may generate proximal force on the bone punch **270** sufficient to overcome cortical elasticity of the bone (which is “squeezing” or “pinching” the piercing tip **272**) to extract the piercing tip **272** from the bone. Accordingly, rotation of the lever **205** from the extended position (e.g., FIG. **6**) toward the initial or intermediate position (e.g., FIG. **5**) may generate proximal translation of the bone punch **270** to thereby extract the piercing tip **272** from the bone, leaving the one or more holes formed in the bone. The linkage **220** may provide a mechanical advantage in generating the force necessary to extract the piercing tip **272** from the bone, thereby reducing the force that the user needs to exert on the lever **205**. Rotating the lever **205** from the extended position to the initial or intermediate position may translate the bone punch **270** from the second position back to the first position. Thereafter, the bone punch **270** may be removed from the handle assembly **200** if desired, or the medical device may be removed from the treatment site.

[0097] FIG. **7** is a detailed view of a portion of the medical device of FIG. **6**, wherein the bone punch **270** is disposed in the second position and the lever **205** is disposed in the extended position. The linkage **220** may include an ejector block **221** slidably disposed within the housing **207**. The ejector block **221** may include one or more pins **229** configured to engage the housing **207** and/or configured to slide longitudinally and/or axially within a channel formed in the housing **207**. In some embodiments, the ejector block **221** may be configured to slide longitudinally and/or axially within a channel formed in the housing **207**. In some embodiments, the ejector block **221** may be configured to slide parallel to the longitudinal axis of the sheath **203** and/or the longitudinal axis of the bone punch **270** and/or the elongate shaft **274**. In some embodiments, the sheath **203** may extend through and/or may pass through the ejector block **221**. As such, the ejector block **221** may be slidably disposed about the sheath **203**. Since the elongate shaft **274** may be slidably disposed within the sheath **203**, the elongate shaft **274** may also extend through the ejector block **221**. The head **276** of the bone punch **270** may be configured to engage the ejector block **221** in the first position. During distal translation of the bone punch **270** from the first position to the second position, the head **276** of the bone punch **270** may push, urge, or otherwise translate the ejector block **221** distally within the housing **207**, thereby actuating the linkage **220** and causing the linkage **220** to rotate the distal end **209** of the lever **205** away from the housing **207** to the extended position.

[0098] In at least some embodiments, the linkage **220** may further include a distal link **222** pivotably engaged with the housing **207** at a distal pivot point **223**, and a middle link **224** pivotably engaged with the ejector block **221** at a proximal pivot point **225**. In some embodiments, the middle link **224** may include a first middle link **224A** and a second middle link **224B** (not shown). In some embodiments, a proximal portion of the distal link **222** may be disposed between the first middle link **224A** and the second middle link **224B**. In some embodiments, a distal portion of the

distal link **222** may comprise a pair of opposing legs extending on opposite sides of the sheath **203**. One leg of the pair of opposing legs may be configured to engage the first housing portion **207A**, and one leg (e.g., the opposite leg) of the pair of opposing legs may be configured to engage the second housing portion **207B**.

[0099] The distal link **222** may be pivotably engaged with the middle link **224** at an intermediate pivot point **226** between the distal pivot point **223** and the proximal pivot point **225**. The distal pivot point **223** may be axially and/or longitudinally fixed relative to the housing **207**. As such, when the head **276** of the bone punch **270** is translated distally to slide the ejector block **221** distally within the housing **207**, a proximal end of the distal link **222** and a distal end of the middle link **224** may be translated laterally relative to the longitudinal axis of the sheath **203**, the bone punch **270**, and/or the elongate shaft **274** by pivoting relative to each other at the intermediate pivot point **226** as a proximal end of the middle link **224** is translated distally and/or longitudinally toward a distal end of the distal link **222** and/or the distal pivot point **223**. In some embodiments, the proximal pivot point **225**, the intermediate pivot point **226**, and/or the distal pivot point **223** may include and/or be defined by one or more pins, shafts, or other elements. Some examples of suitable but non-limiting materials for the ejector block **221**, the distal link **222**, the middle link **224**, and/or elements or components thereof are described below.

[0100] The distal link **222** may include a cam surface **227** configured to engage a corresponding surface of the lever **205**, wherein the corresponding surface of the lever **205** faces toward the housing **207**, the distal link **222**, and/or the longitudinal axis of the sheath **203**, the bone punch **270**, and/or the elongate shaft **274**. In some embodiments, the cam surface **227** may be a curved surface. In some embodiments, the cam surface **227** may be a convex surface. In some embodiments, the corresponding surface of the lever **205** may be a curved surface. In some embodiments, the corresponding surface of the lever **205** may be a convex surface. In some embodiments, the corresponding surface of the lever **205** may be a concave surface. In some embodiments, the corresponding surface of the lever **205** may be a complex and/or an irregular surface having both concave and convex portions. Other configurations are also contemplated.

[0101] As discussed above, the handle assembly **200** may include a spring **211** disposed within the housing **207**. The spring **211** may include a first arm portion **211A** extending proximally from the coiled portion and configured to engage the housing **207**. In at least some embodiments, the first arm portion **211A** may be configured to engage the first housing portion **207A** (not shown). The spring **211** may include a second arm portion **211B** extending distally from the coiled portion and configured to engage the lever **205**. For example, the lever **205** may include a slot formed therein configured to receive the second arm portion **211B**. In another example, the lever **205** may include one or more apertures **206** configured to receive the second arm portion **211B**, as seen in FIG. **8**.

[0102] FIGS. **8-10** are perspective views of the medical device and the handle assembly **200** described herein. FIGS. **8-10** are shown from different angles and with different elements of the handle assembly **200** hidden from view show additional features and/or to facilitate understanding of the various interactions between components. For example, in some embodiments, the pair of opposing legs of the distal link **222** may include a first leg **222A** and a second leg **222B**.

[0103] In some embodiments, the first housing portion **207A** may include a slot **202** configured to receive the first arm portion **211A** of the spring **211**, as seen in FIG. **9**. Other configurations for securing the first arm portion **211A** relative to the first housing portion **207A**, and/or preventing relative movement therebetween, are also contemplated. As discussed above, the middle link **224** may include a first middle link **224A** (not shown) and a second middle link **224B**, shown in FIG. **9**. The first middle link **224A** and the second middle link **224B** may be similar in form, size, and/or shape.

[0104] In some embodiments, the handle assembly **200** may include a second spring **213**, shown in FIG. **10**, may include a coiled portion, a first arm portion **213A** extending proximally from the coiled portion, and a second arm portion **213B** extending distally from the coiled portion. In some

embodiments, the second middle link **224B** (not shown) may include a slot formed therein facing and/or opening inwardly and/or toward the proximal portion of the distal link **222**. The slot formed in the second middle link **224B** may be configured to receive the first arm portion **213A** of the second spring **213**. The distal link **222** may include a slot **230** formed in the second leg **222B** of the pair of opposing legs of the distal link **222**, wherein the slot **230** faces and/or opens outwardly and/or toward the second middle link **224B**. The slot **230** may be configured to receive the second arm portion **213B** of the second spring **213**. In some embodiments, at least a portion of the coiled portion of the second spring **213** may be received and/or recessed in the proximal portion of the distal link **222**.

[0105] It will be easily understood that rotation of the lever **205** toward the housing **207** and/or the longitudinal axis of the sheath **203**, the bone punch **270**, and/or the elongate shaft **274** (e.g., toward the initial or intermediate position) when the bone punch **270** is in the second position may actuate the linkage **220** to translate the head **276** of the bone punch **270** proximally to retract the piercing tip **272** into the sheath **203** and/or to extract the piercing tip **272** from the bone of the patient. The corresponding surface of the lever **205** may exert a force upon the cam surface **227** of the distal link **222**, thereby urging and/or translating the proximal portion of the distal link **222** laterally toward the longitudinal axis of the sheath **203**, the bone punch **270**, and/or the elongate shaft **274**, thereby resulting in corresponding movement of the middle link **224** and proximal translation of the ejector block **221** within the housing **207** until the outwardly extending protrusion(s) **279** re-engage the wall of the housing **207**. When the outwardly extending protrusion(s) **279** are engaged with the wall of the housing **207**, the lever **205** is in the initial or intermediate position and is prevented from rotating inward past the initial or intermediate position and/or closer to the housing **207** than the initial or intermediate position until the outwardly extending protrusion(s) **279** are disengaged from the wall of the housing **207** by squeezing, urging, actuating, or otherwise moving the plurality of connecting members **278** inward toward the head **276**, and/or the longitudinal axis of the bone punch **270** and/or the elongate shaft **274**. Once the outwardly extending protrusion(s) **279** are disengaged from the wall of the housing **207**, the lever **205** may be rotated toward the housing **207** and/or the longitudinal axis of the sheath **203**, the bone punch **270**, and/or the elongate shaft **274** toward a disengagement position, shown in FIG. **11**, to aid in ejecting the bone punch **270** from the handle assembly **200**.

[0106] The spring **211** may be biased toward the initial or intermediate position of the lever **205**. As such, if the lever **205** is rotated away from the initial or intermediate position, the spring **211** may be stressed and may exert a force on the lever **205** to return the lever **205** to the initial or intermediate position. The initial or intermediate position of the lever **205** may be considered a “home” position for the spring **211**. Similarly, the second spring **213** may be biased toward the disengagement position of the lever **205**. As such, if the lever **205** is rotated away from the disengagement position, the second spring **213** may be stressed and may exert a force on the linkage **220** to return the lever **205** to the disengagement position. The disengagement position of the lever **205**, and the corresponding positioning of the linkage **220**, may be considered a “home” position for the second spring **213**. The spring **211** may be configured to exert a greater force on the lever **205** than the second spring **213** is configured to exert on the linkage **220**. Effectively, the spring **211** is “stronger” than the second spring **213** and the force exerted by the spring **211** may override the force exerted by the second spring **213**. This relationship may also require less force to be applied to the lever **205** to rotate the lever **205** from the extended position toward the initial or intermediate position and/or the disengagement position than to rotate the lever **205** from the initial or intermediate position to the extended position. In other instances, the handle assembly **200** may be configured such that the second spring **213** may be configured to exert a greater force on the lever than the spring **211**. If all external forces are removed from the handle assembly **200**, the lever **205** will be biased toward and/or will return to the initial or intermediate position. If the bone punch **270** is not present within the handle assembly **200**, the lever **205** will be biased toward

and/or will return to the initial or intermediate position.

[0107] In use, the distal end of the sheath **203** may be configured to be positioned adjacent and/or against the surface of a bone of the patient. As discussed herein, the medical device may be configured to form one or more holes within the bone. In some embodiments, the distal end of the sheath **203** may be positioned directly against the surface of the bone. In some embodiments, the distal end of the sheath **203** may be positioned against a sheet-like implant **50** that is positioned directly against the surface of the bone, as shown in FIG. **12** for example, so that the one or more holes may also be formed in the sheet-like implant **50**. As such, the presence of the sheet-like implant **50** as positioned in FIG. **12** may be considered optional.

[0108] After positioning the piercing tip **272** against the surface of the bone, the user may apply distal force to the head **276** of the bone punch **270**, such as with a mallet or other tool, to drive the piercing tip **272** into the bone, as seen in FIG. **12**. In some embodiments, the sheath **203** may optionally include position retention members **204** extending distally therefrom, wherein the position retention members **204** are configured to extend into the one or more holes formed in the bone as the piercing tip **272** is driven distally into the bone. Next, as the lever **205** is rotated toward the housing **207** to extract the piercing tip **272** from the bone, the position retention members **204** may remain positioned within the one or more holes to maintain the position of the sheath **203** and/or the handle assembly **200** relative to the one or more holes, as seen in FIG. **13**.

[0109] In some embodiments, after disengaging the bone punch **270** from the housing **207** and/or after removing the bone punch **270** from the handle assembly **200**, the user may insert a staple delivery insert **600**, as depicted in FIG. **14**, into the sheath **203** of the handle assembly **200**. The staple delivery insert **600** may be comprised of a shaft **602**, a proximal head **604**, and a distal end **606**. The staple delivery insert **600** may have arms **608** connected to the distal end **606** which may retain a bone staple, such as a bone staple **100**, shown and described in more detail with respect to FIG. **15**. In some examples, the arms **608** may be designed to be received into the cavities **128A**, **128B** of the bone staple **100** and retain the bone staple **100** with friction. Once the staple delivery insert **600** is received within the sheath **203**, the user may then apply force to the proximal end of the staple delivery insert **600**. The applied force may drive the arms **610** of the staple delivery insert **600**, along with the bone staple **100**, into the one or more holes formed in the bone. Natural movement of tissue and/or the bone, and/or a pullout force applied to the bridge of the bone staple **100**, may act to secure the bone staple **100** within the bone.

[0110] The user may then remove the staple delivery insert **600** from handle assembly **200**. The bone may impart a holding force on the bone staple **100** sufficient to overcome the friction force between the arms **608** of the staple delivery insert **600** and the bone staple **100** such that the staple delivery insert **600** may be removed from the bone while the bone staple **100** remains in the bone. Finally, the user may then retract the handle assembly **200** from the patient and finish the procedure.

[0111] FIG. **15** illustrates an example bone staple **100** that may be used with the medical device(s) described herein. Although the various parts of the exemplary bone staple **100** are depicted in relative proportion to other parts of the bone staple **100**, other configurations in size and orientation of the various parts are also contemplated in other examples. A number of reference directions are illustrated using arrows in FIG. **15** to assist in understanding the details of the bone staple **100**. The illustrated directions include: proximal direction P, distal direction D, first laterally outward direction LOA, second laterally outward direction LOB, first laterally inward direction LIA, and second laterally inward direction LIB.

[0112] In some examples, the bone staple **100** comprises a first arm **102A**, a second arm **102B**, and a bridge **104**. The bridge **104** may abut, or extend from or adjacent to, a proximal end of the first arm **102A** to a proximal end of the second arm **102B**. First arm **102A** may include a first trunk **106A**, with the first trunk **106A** generally having a greater width than the rest of the first arm **102A** as depicted in FIG. **15**. In some examples, the first arm **102A** may also include a non-trunk portion

105A. The length of the first trunk **106A** relative to the overall length of the first arm **102A** can vary in different examples. For instance, the first trunk **106A** can extend for the entire length of the first arm **102A** such that the bridge **104** abuts with or is adjacent to the first trunk **106A**. In other examples, the first arm **102A** may not include the first trunk **106A**. That is, the first arm **102A** may not have a portion with a greater width than the rest of the first arm **102A**. In such examples, the first arm **102A** may still have the non-trunk portion **105A**.

[0113] Similarly, the second arm **102B** may include a second trunk **106B**, with the second trunk **106B** generally having a greater width than the rest of the second arm **102B**. Additionally, the second trunk **106B** may extend for at least a portion of the second arm **102B**. A distal portion of the second arm **102B** may abut a proximal end of the second trunk **106B** and in some embodiments, the second arm **102B** may further include a non-trunk portion similar to the non-trunk portion **105A**. As with the first trunk **106A**, the second trunk **106B** may extend along the second arm **102B** for varying lengths. Additionally, in some examples, the second arm **102B** may not have a portion with a greater width than the rest of the second arm **102B**. In FIG. 15, the first trunk **106A** and the second trunk **106B** are shown extending distally from a proximal portion of the first arm **102A** and the second arm **102B**, respectively.

[0114] In the example of FIG. 15, the first trunk **106A** has a lateral extent, or cross-sectional area, that is larger than a lateral extent of the non-trunk portion **105A** of the first arm **102A** and the bridge **104**. The bone staple **100** may include a first change in lateral stiffness **108A** disposed where the distal end of the non-trunk portion **105A** of the first arm **102A** abuts the first trunk **106A**. As depicted, the change in stiffness is abrupt, but can be gradual in alternative examples—such as through a gradual change in lateral extent between the first trunk **106A** and the non-trunk portion **105A**. In an example where the first trunk **106A** extends for the full length of the first arm **102A**, the change in stiffness may occur where the first trunk **106A** abuts the bridge **104**. With reference to the example of FIG. 15, it will be appreciated that the first trunk **106A** is mounted eccentrically to the first arm **102A** and the second trunk **106B** is mounted eccentrically to the second arm **102B**. As with the first trunk **106A**, the second trunk **106B** has a lateral extent, or cross-sectional area that is larger than a lateral extent of the non-trunk portion **105B** of the second arm **102B** and the bridge **104**. The bone staple **100** may include a second change in lateral stiffness **108B** where the distal end of the non-trunk portion **105B** of the second arm **102B** abuts the second trunk **106B**. Similarly to the first arm **102A**, in some examples, the change in stiffness may be abrupt or gradual. If the second trunk **106B** extends for the entire length of the second arm **102B**, the change in stiffness may occur at the abutment with the bridge **104**. In additional examples where there may be no change in lateral extent between the first and second trunks **106A**, **106B** and the first and second arms **102A**, **102B**, respectively, a change in stiffness may be accomplished by the use of different materials for the first and second trunks **106A**, **106B** and the first and second arms **102A**, **102B**.

[0115] Some examples of the bone staple **100** may include at least a first projection **122A** and a second projection **122B** on the first trunk **106A**, and a third projection **122C** and a fourth projection **122D** on the second trunk **106B**. The first and third projections **122A**, **122C** on the first and second trunks **106A**, **106B**, respectively, may further include a first proximal surface **124A** and a third proximal surface **124C**, respectively, each extending away from its respective trunk in a first direction, such as out and away from each opposite trunk **106A**, **106B**. The first direction may be a direction such that the first and third proximal surfaces **124A**, **124C** will engage with tissue or bone after the trunk is inserted therein and by natural movement of the tissue or bone. In some examples, a pullout force may be applied to the bridge **104** to further engage the first and third proximal surfaces **124A**, **124C** with the bone or tissue. The natural movement of the bone or tissue or the pullout force creates a first moment centered on the area of reduced stiffness adjacent each trunk, tending to rotate each trunk thereabout. The rotation of each trunk may further provide a greater holding force of the bone staple **100** in bone or tissue. The second projection **122B** and the fourth projection **122D** on the first and second trunks **106A**, **106B**, respectively, may include a second

proximal surface **124B** and a fourth proximal surface **124D**, respectively, extending away from its respective trunk in a second direction, different from the first direction, such as inward, toward the opposite trunk. For example, the second direction may be selected such that the second and fourth proximal surfaces **124B**, **124D** will engage tissue or bone after each trunk is inserted therein and by natural movement of the tissue or bone. In some examples, a pullout force may be applied to the bridge **104**. A slit or area of reduced cross section in each trunk adjacent the second and fourth projections **122B**, **122D** provide an area of weakness so that a second moment is applied to the trunk in response to natural movement of the tissue or bone and/or to a pullout force on the bridge **104**. This moment causes rotation of the trunk about the area of weakness and increases the holding force of the bone staple **100**.

[0116] As illustrated in the example of the bone staple **100** in FIG. **15**, the first trunk **106A** includes the first projection **122A** disposed at an outer side of the first trunk **106A** and the second projection **122B** disposed at an inner side of the first trunk **106A**. The first projection **122A** includes the first proximal surface **124A** extending away from the first trunk **106A** in the first direction. With reference to FIG. **15**, it will be appreciated that the first direction has an outward lateral component and a proximal component so that the first proximal surface **124A** extends outwardly and proximally away from the first trunk **106A**. For example, the first direction may be selected such that the first proximal surface **124A** will engage tissue or bone proximate the outer side of the first trunk **106A** after being inserted therein so that a first moment is applied to the first trunk **106A** in response to natural movement of the tissue or bone and/or to a pullout force on the bridge **104**. The moment centers on the arm portion of lesser stiffness adjacent the first projection **122A**.

[0117] In the example of FIG. **15**, the first trunk **106A** includes a first localized area of weakness **120A** disposed proximate the second projection **122B**. The second projection **122B** includes the second proximal surface **124B** extending away from the first trunk **106A** in a second direction. The second direction is selected such that the second proximal surface **124B** will engage tissue or bone proximate the inner side of the first trunk **106A** when inserted therein so that a second moment is applied to the first trunk **106A** in response to natural movement of the tissue or bone and/or a pullout force on the bridge **104**. The moment centers around the first localized area of weakness **120A**. The second moment has a direction that is generally opposite a direction of the first moment. It will be appreciated that the second direction has an inward lateral component and a proximal component so that the second proximal surface **124B** extends inwardly and proximally away from the first trunk **106A**. In other examples, the first arm **102A** may not include the second projection **122B**. In such examples, only a first moment may be applied to the first trunk **106A** in response to natural movement of the tissue or bone and/or a pullout force on the bridge **104**.

[0118] The second trunk **106B** includes the third projection **122C** disposed at an outer side of the second trunk **106B** and the fourth projection **122D** disposed at an inner side of the second trunk **106B**. In the example of FIG. **15**, the third projection **122C** includes a third proximal surface **124C** extending away from second trunk **106B** in a third direction. With reference to FIG. **15**, it will be appreciated that the third direction has an outward lateral component and a proximal component so that the third proximal surface **124C** extends outwardly and proximally away from the second trunk **106B**. The third direction is selected such that the third proximal surface **124C** will engage tissue or bone proximate the outer side of the second trunk **106B** when inserted therein so that a third moment is applied to the second trunk **106B** in response to natural movement of the tissue or bone and/or a pullout force on bridge **104**.

[0119] In the example of FIG. **15**, the second trunk **106B** includes a second localized area of weakness **120B** disposed proximate the fourth projection **122D**. The fourth projection **122D** includes a fourth proximal surface **124D** extending away from the second trunk **106B** in a fourth direction. In the example of FIG. **15**, the fourth direction is selected such that the second proximal surface **124B** will engage tissue or bone proximate the inner side of the second trunk **106B** when inserted therein so that a fourth moment is applied to the second trunk **106B** in response to natural

movement of the tissue or bone and/or a pullout force on the bridge **104**. The fourth moment has a direction that is generally opposite a direction of the third moment. It will be appreciated that the fourth direction has an inward lateral component and a proximal component so that the fourth proximal surface **124D** extends inwardly and proximally away from the second trunk **106B**. In other examples, the second arm **102B** may not include the fourth projection **122D**. In such examples, only a first moment may be applied to the second trunk **106B** in response to natural movement of the tissue or bone and/or a pullout force on the bridge **104**.

[0120] In some embodiments, the bone staple **100** includes proximal projections that extend away from or outward from the bridge **104**, while the distal projections extend inward or toward the center of the bridge **104**. This creates generally opposing forces in response to tension on the bridge **104** which, in combination with areas of weakness or reduced lateral extent, substantially increases the holding force of the bone staple **100** in bone as the different portions of the trunks tend to rotate in opposite directions and apply force to an opposing wall in the hole in the bone in which the bone staple **100** is positioned. It is however, understood that other configurations of the projections are possible. In some examples, only two projections are included and they extend in different directions to cause different force responses as tension is applied to the bridge **104**. Additional examples may include varying numbers of projections which produce one or more moments in each of the first and second arms **102A**, **102B**.

[0121] In some examples, each projection of the bone staple **100** may be clefted to form a plurality of points for greater retention in tissue or bone. In the example of FIG. **15**, the first projection **122A** of the first trunk **106A** defines a first notch **126A** that divides the first projection **122A** into a first sub-projection and a second sub-projection. The second projection **122B** of the second trunk **106B** defines a second notch **126B**. In the example of FIG. **15**, the second notch **126B** divides the second projection **122B** into a first sub-projection and a second sub-projection. The third projection **122C** of the second trunk **106B** defines a third notch **126C** that divides the third projection **122C** into a first sub-projection and a second sub-projection. The fourth projection **122D** of the second trunk **106B** defines a fourth notch **126D** that divides the fourth projection **122D** into a first sub-projection and a second sub-projection.

[0122] With continued reference to FIG. **15**, the first trunk **106A** defines a first cavity **128A** and the second trunk **106B** defines a second cavity **128B**. The first cavity **128A** extends into the first trunk **106A** and the second cavity **128B** extends into the second trunk **106B**. The first and second cavities **128A**, **128B** are sized to cooperate with the staple delivery insert **600** for holding and inserting the staple into tissue or bone. In summary, the staple delivery insert **600** includes longitudinally extending stakes that fit within the first and second cavities **128A**, **128B** to hold the bone staple **100** and push it into position in the tissue or bone as the stake abuts a portion of its respective trunk. In some examples, the cavities may extend through a portion of the length of each trunk and the distal end of the bone staple **100** is closed. Alternatively, the first cavity **128A** and the second cavity **128B** may extend through the entire length of the first trunk **106A** and the second trunk **106B**, respectively, or other portions of the bone staple **100** in some examples. In some embodiments, the first cavity **128A** and the second cavity **128B** each have a generally rectangular or square cross-sectional shape to cooperate with a similarly shaped cross-section on the staple delivery insert **600**. However, the first cavity **128A** and the second cavity **128B** may have various cross-sectional shapes to cooperate with alternative staple delivery insert designs without deviating from the spirit and scope of the present disclosure.

[0123] FIG. **16** illustrates an alternative medical device that may be used to form one or more holes within a bone (e.g., the humerus **14**) of a patient to facilitate placement of the one or more bone staples **100** and/or to secure the sheet-like implant **50** to the bone. In some embodiments, the medical device may include a bone punch **370** including an elongate shaft **374** having gear teeth **375** (e.g., FIGS. **17-18**) extending outwardly therefrom, a head **376** disposed at a proximal end of the elongate shaft **374**, and a piercing tip **372** disposed at a distal end of the elongate shaft **374**, and

may be formed similarly to the bone punch **270** shown in FIG. 3 for example. In some embodiments, the bone punch **370** and/or the piercing tip **372** may include a plurality of piercing tips, two or more piercing tips, a pair of piercing tips, etc. extending distally from the distal end of the elongate shaft **374**. The piercing tip **372** may be configured to be driven into the bone (e.g., the humerus **14**). In some embodiments, the piercing tip **372** may be a spike, a prong, a spear, or other suitable shape. As such, the piercing tip **372** may include a sharpened distal end and/or a tapered distal portion configured to engage and/or penetrate bone.

[0124] While a simpler version of the bone punch **370**, and in particular the head **376**, is illustrated in FIGS. **16-18**, it is contemplated that the bone punch **370** may include some, many, and/or all of the same features shown for the bone punch **270** disclosed herein. For example, while not explicitly shown, in some embodiments, the head **376** of the bone punch **370** may include a plurality of connecting members, and each of the plurality of connecting members may include an outwardly extending protrusion, as in the bone punch **270** disclosed herein. In some embodiments, the plurality of connecting members may be fixedly attached to opposing sides of the head **376**. The plurality of connecting members may extend from the head **376** distally toward the distal end of the elongate shaft **374**. The plurality of connecting members may extend laterally outward from the head **376** at an oblique angle to a longitudinal axis of the bone punch **370** and/or the elongate shaft **374**. In some embodiments, the plurality of connecting members may be biased laterally outward from the head **376**. The bone punch **370** may function similarly to the bone punch **270** where similar elements are provided.

[0125] The head **376** of the bone punch **370** may include and/or define a distal surface **377**. The distal surface **377** may be a distally facing surface and does not necessarily need to be a distalmost surface of the head **376**. For example, the distal surface **377** may be disposed between a proximal end of the head **376** and the distal end of the head **376**. In some embodiments, the head **376** may include one or more lateral projections. In some embodiments, the one or more lateral projections may be disposed between the plurality of connecting members and/or between the proximal end of the head **376** and the distal end of the head **376**. In some embodiments, the one or more lateral projections may each and/or collectively define the distal surface **377** of the head **376**.

[0126] In some embodiments, the proximal end of the elongate shaft **374** may extend into the head **376** of the bone punch **370**. In some embodiments, the proximal end of the elongate shaft **374** may be fixedly attached to the head **376**. In some embodiments, the elongate shaft **374** may be monolithically formed with the head **376**, such as by casting, molding, or machining, for example. Other configurations are also contemplated. Similarly, a proximal end of the piercing tip **372** may extend into the distal end of the elongate shaft **374**. The proximal end of the piercing tip **372** may be fixedly attached to the elongate shaft **374**. In some embodiments, the piercing tip **372** may be monolithically formed with the elongate shaft **374**, such as by casting, molding, or machining, for example. Other configurations are also contemplated. Some examples of suitable but non-limiting materials for the bone punch **370** and/or elements or components thereof are described below.

[0127] The medical device of FIG. **16** may comprise a handle assembly **300** including a housing **307**, a lever **305** rotatably coupled to the housing **307**, and a sheath **303** extending distally from the housing **307**. In at least some embodiments, a proximal end of the sheath **303** may be fixedly attached to the housing **307**. The sheath **303** may extend into and/or within the housing **307**, such that the proximal end of the sheath **303** is disposed within a distal portion of the housing **307**, and the sheath **303** extends within the housing **307** and distally from a distal end of the housing **307**. Some examples of suitable but non-limiting materials for the housing **307**, the lever **305**, the sheath **303**, and/or elements or components thereof are described below.

[0128] The housing **307** may be formed as a multi-piece structure including a first housing portion **307A**, seen in FIG. **16**, and a second housing portion **307B**, not visible in FIG. **16**. For the purpose of illustration herein, one of the first housing portion **307A** or the second housing portion **307B** may be hidden from view in the figures to permit viewing of internal components and/or features

thereof. The first housing portion **307A** and the second housing portion **307B** may be assembled together to form the housing **307**. In the illustrated example(s), fasteners such as screws and nuts may be used to assemble the housing **307**. However, other assembly and/or attachment means may also be used, including but not limited to snap fit, friction fit, pins, rivets, etc. In some embodiments, once the housing **307** is assembled, such assembly may be considered and/or made permanent using any known suitable means, such as but not limited to adhesives, welding, etc.

[0129] The medical device may include the bone punch **370** described herein. The bone punch **370** may be disposed within and/or extend through the sheath **303**. The elongate shaft **374** may be slidably disposed within the sheath **303** in a first position when the lever **305** is in an initial position, seen in FIG. **16** for example. In some embodiments, the head **376** of the bone punch **370** may be releasably engaged with the housing **307**, as described herein. In some embodiments, the head **376** of the bone punch **370** may be spaced away from a proximal surface **308** of the housing **307** in the first position. The piercing tip **372** may be positioned proximate a distal end of the sheath **303** in the first position. In some embodiments, the piercing tip **372** may be disposed within the distal end of the sheath **303** in the first position. In some embodiments, a portion of the piercing tip **372** may extend distally of the distal end of the sheath **303** in the first position to aid in positioning the medical device at a treatment site (e.g., to engage a surface of the bone). In some embodiments, less than 10% of the piercing tip **372** extends distally of the distal end of the sheath **303** in the first position. In some embodiments, less than 5% of the piercing tip **372** extends distally of the distal end of the sheath **303** in the first position.

[0130] FIG. **17** illustrates the medical device with the first housing portion **307A** of the handle assembly **300** removed and the second housing portion **307B** visible. The housing **307** may include a leg extending laterally from a distal portion thereof. In some embodiments, the leg may be disposed at and/or extend laterally from the distal end of the housing **307**. The lever **305** may be rotatably and/or pivotably coupled to the housing **307** about an axis of rotation. In some embodiments, the handle assembly **300** may include a spring biasing the lever **305** toward the initial position.

[0131] In FIG. **17**, the lever **305** is shown disposed in the initial position. In the initial position, the lever **305** may be engaged with an outer surface of the housing **307**. In the initial position, the distal end **309** of the lever **305** may be substantially aligned with and/or disposed within a free end of the leg. In the initial position, the lever **305** may extend distally toward a distal end of the sheath **303** and/or the handle assembly **300** at a first angle relative to a longitudinal axis of the sheath **303**. For example, the first angle may be less than about 15 degrees, less than about 10 degrees, less than about 5 degrees, about 0 degrees, or another small, oblique angle. In some embodiments, in the initial position, the lever **305** may extend toward the distal end of the sheath **303** generally parallel to a longitudinal axis of the sheath **303**. In at least some embodiments, from the initial position, the lever **305** may be configured to rotate a distal end **309** of the lever **305** toward or away from the housing **307**.

[0132] In FIG. **17**, the bone punch **370** is shown disposed in the first position. The elongate shaft **374** of the bone punch **370** is slidably disposed within the sheath **303** of the handle assembly **300** when the lever **305** is in the initial position. The distal surface **377** of the head **376** of the bone punch **370** may be spaced apart from the proximal surface **308** of the housing **307** of the handle assembly **300** in the first position and/or when the lever **305** is in the initial position. In some embodiments, the head **376** of the bone punch **370** may be releasably engaged with the housing **307** of the handle assembly **300** in the first position and/or when the lever **305** is in the initial position. For example, a plurality of connecting members and outwardly extending protrusion(s) thereof may engage a wall of the housing **307** defining the proximal surface **308** of the housing **307**. In some embodiments, the proximal surface **308** may be a proximally facing surface of the housing **307** at and/or proximate a proximal end of the housing **307**. In some embodiments, the proximal surface **308** may be a proximalmost surface of the housing **307**.

[0133] In the first position, the outwardly extending protrusion(s) may extend laterally outward from the head **376** and/or the longitudinal axis of the bone punch **370** and/or the elongate shaft **374** beyond a perimeter of an opening in the wall of the housing **307** within which the head **376** is disposed. Where provided, the outwardly extending protrusion(s) may prevent the head **376** and/or the bone punch **370** from being removed from the housing **307** until the plurality of connecting members are squeezed, urged, actuated, or otherwise moved inward toward the head **376**, and/or the longitudinal axis of the bone punch **370** and/or the elongate shaft **374**, to disengage the outwardly extending protrusion(s) from the wall of the housing **307** by translating the outwardly extending protrusion(s) inward until the outwardly extending protrusion(s) are disposed within and/or inward of the perimeter of the opening. Doing so will permit the plurality of connecting members and the outwardly extending protrusion(s) to pass through the opening in the wall of the housing **307**. In the first position, the distal surface **377** of the head **376** may be spaced apart proximally from the proximal surface **308** of the wall of the housing **307**.

[0134] As seen in FIG. **17**, the bone punch **370** may include an elongate shaft **374** having gear teeth **375** extending outwardly therefrom. The gear teeth **375** may be disposed between a distal end of the elongate shaft **374** and the head **376**. In some embodiments, the gear teeth **375** may be spaced apart from the head **376**. In some embodiments, the elongate shaft **374** may include a spine **373** extending radially outward from the elongate shaft **374**, wherein the spine **373** is circumferentially and/or axially aligned with the gear teeth **375**. In some embodiments, the spine **373** spaces the head **376** from the gear teeth **375**. In some embodiments, the gear teeth **375** may be formed from and/or cut out of the spine **373** by removing material from the spine **373** to form the gear teeth **375**. In some embodiments, the spine **373** and the gear teeth **375** may be monolithically formed together.

[0135] The spine **373** and the gear teeth **375** may be fixedly attached to the elongate shaft **374**. In some embodiments, the spine **373** and/or the gear teeth **375** may be formed with the elongate shaft **374** as a single monolithic structure.

[0136] In some embodiments, the sheath **303** may include a slot **304** formed therein and/or through a side wall of the sheath **303** to accommodate the gear teeth **375** and/or the spine **373**. The slot **304** may extend longitudinally from the proximal end of the sheath **303** in a distal direction along a proximal portion of the sheath **303**. In some embodiments, the slot **304** may be oriented to face toward the lever **305**.

[0137] In some embodiments, the handle assembly **300** may include a plurality of gears **380** disposed within the housing **307**. At least one of the plurality of gears **380** may be configured to engage with the gear teeth **375** of the elongate shaft **374**. As may be seen in FIG. **17**, the gear teeth **375** of the bone punch **370** may engage at least one of the plurality of gears **380** in the first position. The plurality of gears **380** may be rotatably engaged with and/or coupled to the housing **307**. The plurality of gears **380** may include a first gear **382** configured to engage the gear teeth **375** of the elongate shaft **374**, a second gear **384** fixedly secured to the lever **305**, and a third gear rotatably engaged with both the first gear **382** and the second gear **384**. Other configurations are also contemplated.

[0138] Translation of the bone punch **370** distally within the sheath **303**, and/or translation of the head **376** of the bone punch **370** distally relative to the housing **307**, from the first position to a second position distal of the first position may cause the plurality of gears **380** to rotate the distal end **309** of the lever **305** away from the housing **307** and/or away from the longitudinal axis of the bone punch **370** and/or the elongate shaft **374** to an extended position, as shown in FIG. **18**. In the extended position, the lever **305** may extend toward a distal end of the sheath **303** and/or the handle assembly **300** at a second angle relative to the longitudinal axis of the sheath **303**. In some embodiments, the second angle may be an oblique angle. The second angle may be greater than the first angle.

[0139] As shown in FIG. **18**, the distal surface **377** of the head **376** of the bone punch **370** may engage and/or abut the proximal surface **308** of the housing **307** in the second position. In the

second position, the outwardly extending protrusion(s), where provided, may be spaced apart distally from the wall of the housing **307** defining the proximal surface **308**. In such cases, the outwardly extending protrusion(s) may extend laterally outward from the head **376** and/or the longitudinal axis of the bone punch **370** and/or the elongate shaft **374** beyond the perimeter of the opening in the wall of the housing **307** within which the head **376** is disposed, thus preventing inadvertent removal of the bone punch **370** from the handle assembly **300**.

[0140] In the second position, the piercing tip **372** may be extended from the distal end of the sheath **303** as the elongate shaft **374** is translated distally within the sheath **303**. The distal end of the sheath **303** may be configured to be disposed adjacent a surface of the bone, similar to the discussion above with respect to the sheath **203** and FIG. **12**. As the bone punch **370** is translated distally to the second position, the piercing tip **372** may be driven into the bone to form one or more holes in the bone. There may be a direct or indirect correlation between a rotational position of the lever **305** relative to the housing **307** and a depth of the piercing tip **372** within the bone. As the lever **305** rotates farther away from the housing **307** and/or as an angle between the lever **305** and the longitudinal axis of the sheath **303** and/or the bone punch **370** increases, the piercing tip **372** may be extended farther distally from the distal end of the sheath **303** and/or may be driven farther into the bone. A user of the medical device and/or the handle assembly **300** may be able to use the rotational position of the lever **305** relative to the housing **307** and/or the longitudinal axis of the sheath **303** and/or the bone punch **370** to indicate the depth of the piercing tip **372** within the bone, thereby providing a visual cue to the user about the status of the procedure.

[0141] Thereafter, rotation of the lever **305** from the extended position (e.g., FIG. **18**) toward the initial position (e.g., FIG. **17**) may generate proximal force on the bone punch **370** sufficient to overcome cortical elasticity of the bone (which is “squeezing” or “pinching” the piercing tip **372**) to extract the piercing tip **372** from the bone. Accordingly, rotation of the lever **305** from the extended position (e.g., FIG. **18**) toward the initial position (e.g., FIG. **17**) may generate proximal translation of the bone punch **370** to thereby extract the piercing tip **372** from the bone, leaving the one or more holes formed in the bone. The plurality of gears **380** may provide a mechanical advantage in generating the force necessary to extract the piercing tip **372** from the bone, thereby reducing the force that the user needs to exert on the lever **305**. Rotating the lever **305** from the extended position to the initial position may translate the bone punch **370** from the second position back to the first position. Thereafter, the bone punch **370** may be removed from the handle assembly **300** if desired, or the medical device may be removed from the treatment site.

[0142] In use, the distal end of the sheath **303** may be configured to be positioned adjacent and/or against the surface of a bone of the patient. As discussed herein, the medical device may be configured to form one or more holes within the bone. In some embodiments, the distal end of the sheath **303** may be positioned directly against the surface of the bone. In some embodiments, the distal end of the sheath **303** may be positioned against a sheet-like implant **50** that is positioned directly against the surface of the bone, similar to the sheath **203** shown in FIG. **12** for example, so that the one or more holes may also be formed in the sheet-like implant **50**. As such, the presence of the sheet-like implant **50** may be considered optional.

[0143] After positioning the piercing tip **372** against the surface of the bone, the user may apply distal force to the head **376** of the bone punch **370**, such as with a mallet or other tool, to drive the piercing tip **372** into the bone. In some embodiments, the sheath **303** may optionally include position retention members (e.g., position retention members **204** as seen in FIG. **12**) extending distally therefrom, wherein the position retention members are configured to extend into the one or more holes formed in the bone as the piercing tip **372** is driven distally into the bone. Next, as the lever **305** is rotated toward the housing **307** to extract the piercing tip **372** from the bone, the position retention members may remain positioned within the one or more holes to maintain the position of the sheath **303** and/or the handle assembly **300** relative to the one or more holes, similar to the configuration shown in FIG. **13** for example.

[0144] In some embodiments, after disengaging the bone punch **370** from the housing **307** and/or after removing the bone punch **370** from the handle assembly **300**, the user may insert a staple delivery insert **600**, as depicted in FIG. **14**, into the sheath **303** of the handle assembly **300**. The staple delivery insert **600** may be comprised of a shaft **602**, a proximal head **604**, and a distal end **606**. The staple delivery insert **600** may have arms **608** connected to the distal end **606** which may retain a bone staple, such as a bone staple **100**, shown and described herein with respect to FIG. **15**. In some examples, the arms **608** may be designed to be received into the cavities **128A**, **128B** of the bone staple **100** and retain the bone staple **100** with friction. Once the staple delivery insert **600** is received within the sheath **303**, the user may then apply force to the proximal end of the staple delivery insert **600**. The applied force may drive the arms **610** of the staple delivery insert **600**, along with the bone staple **100**, into the one or more holes formed in the bone. Natural movement of tissue and/or the bone, and/or a pullout force applied to the bridge of the bone staple **100**, may act to secure the bone staple **100** within the bone.

[0145] The user may then remove the staple delivery insert **600** from handle assembly **300**. The bone may impart a holding force on the bone staple **100** sufficient to overcome the friction force between the arms **608** of the staple delivery insert **600** and the bone staple **100** such that the staple delivery insert **600** may be removed from the bone while the bone staple **100** remains in the bone. Finally, the user may then retract the handle assembly **300** from the patient and finish the procedure.

[0146] FIG. **19** illustrates an alternative configuration of a bone punch **470** that may be used with an alternative medical device **400** (e.g., FIG. **20**), described in more detail below. The bone punch **470** may include an elongate shaft **474**, a head **476** disposed at a proximal end of the elongate shaft **474**, and a piercing tip **472** disposed at a distal end **475** of the elongate shaft **474**, as shown in FIG. **19** for example. In some embodiments, the bone punch **470** and/or the piercing tip **472** may include a plurality of piercing tips, two or more piercing tips, a pair of piercing tips, etc. extending distally from the distal end **475** of the elongate shaft **474**. The piercing tip **472** may be configured to be driven into the bone (e.g., the humerus **14**). In some embodiments, the piercing tip **472** may be a spike, a prong, a spear, or other suitable shape. As such, the piercing tip **472** may include a sharpened distal end and/or a tapered distal portion configured to engage and/or penetrate bone.

[0147] In some embodiments, the head **476** may include one or more lateral projections. In some embodiments, the one or more lateral projections may be disposed between a proximal end of the head **476** and a distal end of the head **476**. The one or more lateral projections may each and/or collectively define a distal surface **477** of the head **476**. The distal surface **477** may be a distally facing surface and does not necessarily need to be a distalmost surface of the head **476**. For example, the distal surface **477** may be disposed between the proximal end of the head **476** and the distal end of the head **476**. In at least some embodiments, the head **476** of the bone punch **470** may include one or more magnets **473** disposed therein. In some embodiments, the one or more magnets **473**, described in more detail herein, may be fixedly attached to the head **476** using one or more of a variety of attachment means, such as but not limited to, adhesives, interference fit, friction fit, welding, co-molding, injection molding, etc. In some embodiments, the one or more magnets **473** may be embedded within the head **476**. In some embodiments, at least a portion of the one or more magnets **473** may be exposed to an exterior of the head **476**, such as exposed at a distally facing surface of the head **476**. In some embodiments, the one or more magnets **473** may be completely embedded within the head **476** such that none of the one or more magnets **473** is exposed to the exterior of the head **476**.

[0148] As shown in FIG. **19A**, the head **476** may include a plurality of magnets **473** equidistantly spaced from the central longitudinal axis of the bone punch **470** such that the magnets are symmetrically arranged about the central longitudinal axis. Thus, the magnets may be arranged in the same orientation from the central longitudinal axis when the head **476** of the bone punch **470** is in any one of a plurality or rotational orientations. For example, the head **476** may include a first

magnet **473** and a second magnet **473** diametrically opposite the first magnet **473**, such that the first magnet **473** is in a first position and the second magnet **473** is in a second position when the head **476** of the bone punch **470** is in a first rotational orientation about the central longitudinal axis, and the first magnet **473** is in the second position and the second magnet **473** is in the first position when the head **476** of the bone punch **470** is in a second rotational orientation about the central longitudinal axis. The first rotational orientation may be **180** degrees from the second orientation, for example.

[0149] In some embodiments, the proximal end of the elongate shaft **474** may extend into the head **476** of the bone punch **470**. In some embodiments, the proximal end of the elongate shaft **474** may be fixedly attached to the head **476**. In some embodiments, the elongate shaft **474** may be monolithically formed with the head **476**, such as by casting, molding, or machining, for example. Other configurations are also contemplated. Similarly, a proximal end of the piercing tip **472** may extend into the distal end **475** of the elongate shaft **474**. The proximal end of the piercing tip **472** may be fixedly attached to the elongate shaft **474**. In some embodiments, the piercing tip **472** may be monolithically formed with the elongate shaft **474**, such as by casting, molding, or machining, for example. Other configurations are also contemplated. Some examples of suitable but non-limiting materials for the bone punch **470** and/or elements or components thereof are described below.

[0150] FIG. **20** illustrates aspects of the alternative medical device configured to form one or more holes within a bone of a patient in a side view. The medical device may comprise a handle assembly **400** including a housing **407**, a lever **405** rotatably coupled to the housing **407**, and a sheath **403** extending distally from the housing **407**. In at least some embodiments, a proximal end of the sheath **403** may be fixedly attached to the housing **407**. The sheath **403** may extend into and/or within the housing **407**, such that the proximal end of the sheath **403** is disposed within the housing **407**, and the sheath **403** extends distally from a distal end of the housing **407**. Some examples of suitable but non-limiting materials for the housing **407**, the lever **405**, the sheath **403**, and/or elements or components thereof are described below.

[0151] The housing **407** may be formed as a multi-piece structure including a first housing portion **407A**, seen in FIG. **20**, and a second housing portion **407B**, not visible in FIG. **20**. For the purpose of illustration herein, one of the first housing portion **407A** or the second housing portion **407B** may be hidden from view in the figures to permit viewing of internal components and/or features thereof. The first housing portion **407A** and the second housing portion **407B** may be assembled together to form the housing **407**. In the illustrated example(s), fasteners such as screws and nuts may be used to assemble the housing **407**. However, other assembly and/or attachment means may also be used, including but not limited to snap fit, friction fit, pins, rivets, etc. In some embodiments, once the housing **407** is assembled, such assembly may be considered and/or made permanent using any known suitable means, such as but not limited to adhesives, welding, etc.

[0152] The medical device may include the bone punch **470** described herein. In some embodiments, the medical device may include the bone punch **270** and/or the bone punch **370** described herein instead of the bone punch **470**. The description related to the medical device **400** will be limited to the bone punch **470** for brevity, but it will be understood that other configurations are both possible and contemplated. The bone punch **470** may be disposed within and/or extend through the sheath **403**. The head **476** of the bone punch **470** may be releasably engaged with the housing **407** in a first position, as shown in FIGS. **20-21**. The piercing tip **472** may be positioned proximate a distal end of the sheath **403** in the first position. In some embodiments, the piercing tip **472** may be disposed within the distal end of the sheath **403** in the first position. In some embodiments, a portion of the piercing tip **472** may extend distally of the distal end of the sheath **403** in the first position to aid in positioning the medical device at a treatment site (e.g., to engage a surface of the bone). In some embodiments, less than 50% of the piercing tip **472** extends distally of the distal end of the sheath **403** in the first position. In some embodiments, less than 40% of the

piercing tip **472** extends distally of the distal end of the sheath **403** in the first position. In some embodiments, less than 30% of the piercing tip **472** extends distally of the distal end of the sheath **403** in the first position. In some embodiments, less than 20% of the piercing tip **472** extends distally of the distal end of the sheath **403** in the first position. In some embodiments, less than 10% of the piercing tip **472** extends distally of the distal end of the sheath **403** in the first position. In some embodiments, less than 5% of the piercing tip **472** extends distally of the distal end of the sheath **403** in the first position.

[0153] FIG. **21** illustrates the medical device with the first housing portion **407A** of the handle assembly **400** removed and the second housing portion **407B** visible. The lever **405** may be rotatably and/or pivotably coupled to the housing **407** about an axis of rotation. The handle assembly **400** may include a spring **411** biasing the lever **405** toward an initial position, such as an intermediate position. In at least some embodiments, the spring **411** may include a coiled portion disposed about and/or coaxial with the axis of rotation of the lever **405**.

[0154] In FIG. **21**, the lever **405** is shown disposed in the initial or intermediate position. In at least some embodiments, from the initial or intermediate position, the lever **405** may be configured to rotate a distal end **409** of the lever **405** toward or away from the housing **407**. In the initial or intermediate position, the lever **405** may extend distally toward a distal end of the sheath **403** and/or the handle assembly **400** at a first angle relative to a longitudinal axis of the sheath **403**. For example, the first angle may be less than about 15 degrees, less than about 10 degrees, less than about 5 degrees, about 0 degrees, or another small, oblique angle. In some embodiments, in the initial or intermediate position, the lever **405** may extend toward the distal end of the sheath **403** generally parallel to a longitudinal axis of the sheath **403**.

[0155] In FIG. **21**, the bone punch **470** is shown disposed in the first position. The elongate shaft **474** of the bone punch **470** is slidably disposed within the sheath **403** of the handle assembly **400** when the lever **405** is in the initial or intermediate position. In some embodiments, at least a portion of the head **476** may be configured to engage and/or pass through a wall of the housing **407** defining a proximal surface **408** of the housing **407**. In some embodiments, the proximal surface **408** may be a proximally facing surface of the housing **407** at and/or proximate a proximal end of the housing **407**. In some embodiments, the proximal surface **408** may be a proximalmost surface of the housing **407**. In the first position, the distal surface **477** of the head **476** may be spaced apart proximally from a proximal surface **408** of the wall of the housing **407**.

[0156] In some embodiments, the handle assembly **400** may include a linkage **420** disposed within the housing **407**. The linkage **420** is similar in form and function to the linkage **220**, except as specifically noted herein, and will be described in more detail with respect to FIG. **23**. Some additional and/or functional details related to the linkage **420** may be discerned from the linkage **220** described with respect to FIGS. **8-10**. As may be seen in FIG. **21**, the head **476** of the bone punch **470** may engage the linkage **420** in the first position. The linkage **420** may be pivotably engaged with and/or coupled to the housing **407**. The linkage **420** may include a plurality of elements that are movable and/or pivotable relative to each other. Translation of the bone punch **470** distally within the sheath **403**, and/or translation of the head **476** of the bone punch **470** distally relative to the housing **407**, from the first position to a second position distal of the first position may cause the linkage **420** to rotate the distal end **409** of the lever **405** away from the housing **407** and/or away from the longitudinal axis of the bone punch **470** and/or the elongate shaft **474** to an extended position, as shown in FIG. **22**. In the extended position, the lever **405** may extend toward a distal end of the sheath **403** and/or the handle assembly **400** at a second angle relative to the longitudinal axis of the sheath **403**. In some embodiments, the second angle may be an oblique angle. The second angle may be greater than the first angle.

[0157] As shown in FIG. **22**, at least a portion of the head **476** of the bone punch **470** may be configured to pass through the opening in the wall and/or the proximal surface **408** of the housing **407** as the bone punch **470** is translated from the first position to the second position. In some

embodiments, the distal surface **477** of the head **476** of the bone punch **470** may engage and/or abut the proximal surface **408** of the housing **407** in the second position. In the second position, the piercing tip **472** may be extended from the distal end of the sheath **403** as the elongate shaft **474** is translated distally within the sheath **403**. The distal end of the sheath **403** may be configured to be disposed adjacent a surface of the bone. As the bone punch **470** is translated distally to the second position, the piercing tip **472** may be driven into the bone to form one or more holes in the bone. There may be a direct or indirect correlation between a rotational position of the lever **405** relative to the housing **407** and a depth of the piercing tip **472** within the bone. As the lever **405** rotates farther away from the housing **407** and/or as an angle between the lever **405** and the longitudinal axis of the sheath **403** and/or the bone punch **470** increases, the piercing tip **472** may be extended farther distally from the distal end of the sheath **403** and/or may be driven farther into the bone. A user of the medical device and/or the handle assembly **400** may be able to use the rotational position of the lever **405** relative to the housing **407** and/or the longitudinal axis of the sheath **403** and/or the bone punch **470** to indicate the depth of the piercing tip **472** within the bone, thereby providing a visual cue to the user about the status of the procedure.

[0158] Thereafter, rotation of the lever **405** from the extended position (e.g., FIG. 22) toward the initial or intermediate position (e.g., FIG. 21) may generate proximal force on the bone punch **470** sufficient to overcome cortical elasticity of the bone (which is “squeezing” or “pinching” the piercing tip **472**) to extract the piercing tip **472** from the bone. Accordingly, rotation of the lever **405** from the extended position (e.g., FIG. 22) toward the initial or intermediate position (e.g., FIG. 21) may generate proximal translation of the bone punch **470** to thereby extract the piercing tip **472** from the bone, leaving the one or more holes formed in the bone. The linkage **420** may provide a mechanical advantage in generating the force necessary to extract the piercing tip **472** from the bone, thereby reducing the force that the user needs to exert on the lever **405**. Rotating the lever **405** from the extended position to the initial or intermediate position may translate the bone punch **470** from the second position back to the first position. Thereafter, the bone punch **470** may be removed from the handle assembly **400** if desired, or the medical device may be removed from the treatment site.

[0159] FIG. 23 is a detailed view of a portion of the medical device of FIG. 22, wherein the bone punch **470** is disposed in the second position and the lever **405** is disposed in the extended position. The linkage **420** may include an ejector block **421** slidably disposed within the housing **407**. The ejector block **421** may include one or more pins **429** configured to engage the housing **407** and/or configured to slide longitudinally and/or axially within a channel formed in the housing **407**. In some embodiments, the ejector block **421** may be configured to slide longitudinally and/or axially within a channel formed in the housing **407**. In some embodiments, the ejector block **421** may be configured to slide parallel to the longitudinal axis of the sheath **403** and/or the longitudinal axis of the bone punch **470** and/or the elongate shaft **474**. In some embodiments, the sheath **403** may extend through and/or may pass through the ejector block **421**. As such, the ejector block **421** may be slidably disposed about the sheath **403**. Since the elongate shaft **474** may be slidably disposed within the sheath **403**, the elongate shaft **474** may also extend through the ejector block **421**. The head **476** of the bone punch **470** may be releasably coupled to the ejector block **421** in the first position (e.g., FIG. 21) and/or when the lever **405** is in the initial or intermediate position. During distal translation of the bone punch **470** from the first position to the second position (e.g., FIG. 22), the head **476** of the bone punch **470** may push, urge, or otherwise translate the ejector block **421** distally within the housing **407**, while remaining releasably coupled to the ejector block **421**, thereby actuating the linkage **420** and causing the linkage **420** to rotate the distal end **409** of the lever **405** away from the housing **407** to the extended position.

[0160] In at least some embodiments, the ejector block **421** may include one or more magnets **419** disposed therein. In some embodiments, the one or more magnets **419**, described in more detail herein, may be fixedly attached to the ejector block **421** using one or more of a variety of

attachment means, such as but not limited to, adhesives, interference fit, friction fit, welding, co-molding, injection molding, etc. In some embodiments, the one or more magnets **419** may be embedded within the ejector block **421**. In some embodiments, at least a portion of the one or more magnets **419** may be exposed to an exterior of the ejector block **421**, such as exposed at a proximally facing surface of the ejector block **421** facing or juxtaposed with a distally facing surface of the head **476**. In some embodiments, the one or more magnets **419** may be completely embedded within the ejector block **421** such that none of the one or more magnets **419** is exposed to the exterior of the ejector block **421**.

[0161] In some embodiments, the head **476** of the bone punch **470** may be magnetically coupled to the ejector block **421**. As discussed herein, in some embodiments, the head **476** of the bone punch **470** may include one or more magnets **473** disposed therein and the ejector block **421** may include one or more magnets **419** disposed therein. The one or more magnets **473** of the head **476** of the bone punch **470** may be opposite polarity to the one or more magnets **419** of the ejector block **421**, so as to exert an attractive magnetic force on each other to releasably couple the head **476** of the bone punch **470** to the ejector block **421**.

[0162] In some embodiments, the one or more magnets **419** in the ejector block **421** may instead be a magnetic material (e.g., a ferrous metal, etc.). As such, the head **476** of the bone punch **470** may include one or more magnets **473** disposed therein and the ejector block **421** may include the magnetic material disposed therein opposite the one or more magnets **473** of the head **476** so as to exert an attractive magnetic force on each other to releasably couple the head **476** of the bone punch **470** to the ejector block **421**.

[0163] In some embodiments, the one or more magnets **473** in the head **476** of the bone punch **470** may instead be a magnetic material (e.g., a ferrous metal or other material that is magnetically attracted to a magnet, etc.). As such, the ejector block **421** may include one or more magnets **419** disposed therein and the head **476** of the bone punch **470** may include the magnetic material disposed therein opposite the one or more magnets **419** of the ejector block **421** so as to exert an attractive magnetic force on each other to releasably couple the head **476** of the bone punch **470** to the ejector block **421**.

[0164] In at least some embodiments, the linkage **420** may further include a distal link **422** pivotably engaged with the housing **407** at a distal pivot point **423**, and a middle link **424** pivotably engaged with the ejector block **421** at a proximal pivot point **425**. In some embodiments, the middle link **424** may include a first middle link **424A** and a second middle link **424B** (not shown). In some embodiments, a proximal portion of the distal link **422** may be disposed between the first middle link **424A** and the second middle link **424B**. In some embodiments, a distal portion of the distal link **422** may comprise a pair of opposing legs extending on opposite sides of the sheath **403**. One leg of the pair of opposing legs may be configured to engage the first housing portion **407A**, and one leg (e.g., the opposite leg) of the pair of opposing legs may be configured to engage the second housing portion **407B**.

[0165] The distal link **422** may be pivotably engaged with the middle link **424** at an intermediate pivot point **426** between the distal pivot point **423** and the proximal pivot point **425**. The distal pivot point **423** may be axially and/or longitudinally fixed relative to the housing **407**. As such, when the head **476** of the bone punch **470** is translated distally to slide the ejector block **421** distally within the housing **407**, a proximal end of the distal link **422** and a distal end of the middle link **424** may be translated laterally relative to the longitudinal axis of the sheath **403**, the bone punch **470**, and/or the elongate shaft **474** by pivoting relative to each other at the intermediate pivot point **426** as a proximal end of the middle link **424** is translated distally and/or longitudinally toward a distal end of the distal link **422** and/or the distal pivot point **423**. In some embodiments, the proximal pivot point **425**, the intermediate pivot point **426**, and/or the distal pivot point **423** may include and/or be defined by one or more pins, shafts, or other elements. Some examples of suitable but non-limiting materials for the ejector block **421**, the distal link **422**, the middle link

424, and/or elements or components thereof are described below.

[0166] The distal link **422** may include a cam surface **427** configured to engage a corresponding surface of the lever **405**, wherein the corresponding surface of the lever **405** faces toward the housing **407**, the distal link **422**, and/or the longitudinal axis of the sheath **403**, the bone punch **470**, and/or the elongate shaft **474**. In some embodiments, the cam surface **427** may be a curved surface. In some embodiments, the cam surface **427** may be a convex surface. In some embodiments, the corresponding surface of the lever **405** may be a curved surface. In some embodiments, the corresponding surface of the lever **405** may be a convex surface. In some embodiments, the corresponding surface of the lever **405** may be a concave surface. In some embodiments, the corresponding surface of the lever **405** may be a complex and/or an irregular surface having both concave and convex portions. Other configurations are also contemplated.

[0167] As discussed above, the handle assembly **400** may include a spring **411** disposed within the housing **407**. The spring **411** may include a first arm portion **411A** extending proximally from the coiled portion and configured to engage the housing **407**. In at least some embodiments, the first arm portion **411A** may be configured to engage the first housing portion **407A** (not shown). The spring **411** may include a second arm portion **411B** extending distally from the coiled portion and configured to engage the lever **405**. For example, the lever **405** may include a slot formed therein configured to receive the second arm portion **411B**. As mentioned above, the spring **411** and the lever **405** may function similar to and/or the same as the spring **211** and the lever **205** described with respect to FIGS. **8-10**.

[0168] In some embodiments, the lever **405** may be rotated toward the housing **407** and/or the longitudinal axis of the sheath **403**, the bone punch **470**, and/or the elongate shaft **474** toward a disengagement position, shown in FIG. **24**, to aid in ejecting the bone punch **470** from the handle assembly **400**. However, it will be appreciated that moving and/or translating the lever **405** toward and/or to the disengagement position is not strictly necessary to eject the bone punch **470** from the handle assembly **400**. In at least some embodiments, after the piercing tip **472** has been extracted from the bone, sufficient manual retraction force may be applied to the head **476** of the bone punch **470** to overcome the magnetic force coupling the head **476** of the bone punch **470** to the ejector block **421** and thereby separate the head **476** of the bone punch **470** from the ejector block **421**, thus permitting removal of the bone punch **470** from the handle assembly **400**.

[0169] FIG. **25** illustrates an example configuration of the housing **407**, wherein the housing **407** may include and/or may be formed as a multi-piece structure including a first housing portion **407A** and a second housing portion **407B** as described herein. For the purpose of illustration, the second housing portion **407B** is rotated about the axis X-X to permit viewing of internal components and/or features of the housing **407** and external features of the lever **405**. In the illustrated example, the lever **405** may include a protrusion **440** extending laterally from the lever **405** on a left side of the lever **405**, as viewed proximally to distally. In some embodiments, the protrusion **440** may be and/or may include a spring-loaded ball plunger disposed within a cavity formed in the lever **405**, wherein a ball of the spring-loaded ball plunger is biased toward an extended position in which the ball protrudes laterally from an outside surface of the lever **405**.

[0170] The second housing portion **407B** may include a receiving feature **442** configured to align with and/or receive the ball of the protrusion **440** therein when the lever **405** is disposed in the initial and/or intermediate position. In the illustrated example, the receiving feature **442** includes an annular shoulder **444** extending inward from the second housing portion **407B**, wherein the annular shoulder **444** defines a central aperture **446** configured to receive the ball of the protrusion **440** when the lever **405** is disposed in the initial and/or intermediate position, thereby aiding in maintaining the lever **405** in the initial and/or intermediate position by preventing free and/or accidental movement of the lever **405** away from the initial and/or intermediate position. In some embodiments, when the lever **405** is disposed in the extended position, a position of the ball of the protrusion **440** is shifted in a direction away from the longitudinal axis of the sheath **403** and the

ball of the protrusion **440** extends outside of and/or alongside the annular shoulder **444** of the receiving feature **442** above the receiving feature **442** (as viewed from the side) on an opposite side of the receiving feature **442** relative to the longitudinal axis of the sheath **403**, thereby aiding in maintaining the lever **405** in the extended position by preventing free and/or accidental movement of the lever **405** away from the extended position. In some embodiments, when the lever **405** is disposed in the disengagement position, the position of the ball of the protrusion **440** is shifted in a direction toward the longitudinal axis of the sheath **403** and the ball of the protrusion **440** extends outside of and/or alongside the annular shoulder **444** of the receiving feature **442** above the receiving feature **442** (as viewed from the side) on a same side of the receiving feature **442** as the longitudinal axis of the sheath **403**, thereby aiding in maintaining the lever **405** in the disengagement position by preventing free and/or accidental movement of the lever **405** away from the disengagement position. It will be appreciated that application of a sufficient force to the lever **405** may overcome any resistance to movement provided by the ball of the protrusion **440** being engaged with the receiving feature **442** such that the lever **405** may be selectively and intentionally moved between the above-referenced positions (e.g., the initial and/or intermediate position, the extended position, and the disengagement position).

[0171] FIG. **26** illustrates an example configuration of the housing **407**, wherein the housing **407** may include and/or may be formed as a multi-piece structure including a first housing portion **407A** and a second housing portion **407B** as described herein. For the purpose of illustration, the second housing portion **407B** is rotated about the axis X-X to permit viewing of internal components and/or features of the housing **407** and external features of the lever **405**. In the illustrated example, the lever **405** may include a protrusion **450** extending laterally from the lever **405** on a right side of the lever **405**, as viewed proximally to distally. In some embodiments, the protrusion **450** may be and/or may include a fixed projection that protrudes laterally from an outside surface of the lever **405**.

[0172] The first housing portion **407A** may include a receiving feature **452** configured to align with and/or receive the protrusion **450** therein. In at least some embodiments, the receiving feature **452** may include a plurality of recesses including a first recess **452a**, a second recess **452b**, and a third recess **452c**. Fewer and/or additional recesses and/or other configurations are also contemplated. In the illustrated example, the receiving feature **452** includes a proximal shoulder **454A** and a distal shoulder **454B** extending inward from the first housing portion **407A**, wherein the proximal shoulder **454A** and the distal shoulder **454B** collectively define the first recess **452a**, the second recess **452b**, and the third recess **452c**, which recesses are configured to receive the protrusion **450** in the initial and/or intermediate position, the extended position, and the disengagement position, respectively. The receiving feature **452** and/or the plurality of recesses may be configured to aid in maintaining the lever **405** in one or more of the above-referenced positions (e.g., the initial and/or intermediate position, the extended position, and the disengagement position) by substantially preventing free and/or accidental movement of the lever **405**.

[0173] In some embodiments, when the lever **405** is positioned in the initial and/or intermediate position, a portion of the protrusion **450** is disposed within and engaged with the first recess **452a**, thereby aiding in maintaining the lever **405** in the initial and/or intermediate position by preventing free and/or accidental movement of the lever **405** away from the initial and/or intermediate position. In some embodiments, when the lever **405** is disposed in the extended position, the position of the protrusion **450** is shifted in a direction away from the longitudinal axis of the sheath **403** and the protrusion **450** is disposed within and engaged with the second recess **452b**, thereby aiding in maintaining the lever **405** in the extended position by preventing free and/or accidental movement of the lever **405** away from the extended position. In some embodiments, when the lever **405** is disposed in the disengagement position, the position of the protrusion **450** is shifted in a direction toward the longitudinal axis of the sheath **403** and the protrusion **450** is disposed within and/or engaged with the third recess **452c**, thereby aiding in maintaining the lever **405** in the

disengagement position by preventing free and/or accidental movement of the lever **405** away from the disengagement position. It will be appreciated that application of a sufficient force to the lever **405** may overcome any resistance to movement provided by the protrusion **450** being engaged with the receiving feature **452** and/or the first recess **452a**, the second recess **452b**, and/or the third recess **452c**, such that the lever **405** may be selectively and intentionally moved between the above-referenced positions (e.g., the initial and/or intermediate position, the extended position, and the disengagement position).

[0174] FIG. **27** illustrates an example configuration of the housing **407**, wherein the housing **407** may include and/or may be formed as a multi-piece structure including a first housing portion **407A** and a second housing portion **407B** as described herein. For the purpose of illustration, the first housing portion **407A** is rotated about the axis X-X to permit viewing of internal components and/or features of the housing **407** and external features of the lever **405**. In the illustrated example, the lever **405** may include a polymeric washer **460** disposed over and/or around a protrusion **462** extending laterally from the lever **405** on a right side of the lever **405**, as viewed proximally to distally. In some embodiments, the polymeric washer **460** may be disposed over and/or around a protrusion extending laterally from the lever **405** on a left side of the lever **405**, as viewed proximally to distally. In some embodiments, polymeric washers **460** may be disposed over and/or around protrusions extending laterally from the lever **405** on both the left and right sides of the lever **405**. The protrusion **462** (or protrusions) may correspond to and/or may be aligned and/or coaxial with a pivot axis of the lever **405** relative to the housing **407**. In some embodiments, the polymeric washer **460** may be formed from and/or may include a material having a high coefficient of friction with respect to the housing **407** and/or the lever **405**. For example, the polymeric washer **460** may be formed from a rubber material, a urethane material, a silicone material, or another material that will increase friction between the lever **405** and the housing **407** as the lever **405** is rotated about the pivot axis compared to when the polymeric washer **460** is absent (e.g., not present).

[0175] The first housing portion **407A** and/or the second housing portion **407B** may each include a receiving feature **464** configured to receive the protrusion **462**. In the illustrated example, the receiving feature **464** includes an annular shoulder **466** extending inward from the second housing portion **407B**, wherein the annular shoulder **466** defines a central aperture **468** configured to receive the protrusion **462**. The polymeric washer **460** may be configured to matingly and/or frictionally engage both the lever **405** and the annular shoulder **466** when the protrusion **462** is disposed within the central aperture **468**. In some embodiments, the polymeric washer **460** may be sandwiched, compressed, and/or pinched between the lever **405** and the housing **407** (e.g., the first housing portion **407A** and/or the second housing portion **407B**). Such a configuration will increase friction between the lever **405** and the housing **407**. As such, when the lever **405** is disposed in the initial and/or intermediate position, the polymeric washer **460** may aid in maintaining the lever **405** in the initial and/or intermediate position by preventing free and/or accidental movement of the lever **405** away from the initial and/or intermediate position. In some embodiments, when the lever **405** is disposed in the extended position, the polymeric washer **460** may aid in maintaining the lever **405** in the extended position by preventing free and/or accidental movement of the lever **405** away from the extended position. In some embodiments, when the lever **405** is disposed in the disengagement position, the polymeric washer **460** may aid in maintaining the lever **405** in the disengagement position by preventing free and/or accidental movement of the lever **405** away from the disengagement position. The materials that can be used for the various components of the medical device(s) and the various elements thereof disclosed herein may include those commonly associated with medical devices. For simplicity purposes, the following discussion refers to the apparatus. However, this is not intended to limit the devices and methods described herein, as the discussion may be applied to other elements, members, components, or devices disclosed herein, such as, but not limited to, the medical device, the housing assembly, the bone punch, the bone

staple, and/or elements or components thereof.

[0176] In some embodiments, the apparatus, and/or components thereof, may be made from a metal, metal alloy, polymer (some examples of which are disclosed below), a metal-polymer composite, ceramics, combinations thereof, and the like, or other suitable material.

[0177] Some examples of suitable polymers may include polytetrafluoroethylene (PTFE), ethylene tetrafluoroethylene (ETFE), fluorinated ethylene propylene (FEP), polyoxymethylene (POM, for example, DELRIN® available from DuPont), polyether block ester, polyurethane (for example, Polyurethane 85A), polypropylene (PP), polyvinylchloride (PVC), polyether-ester (for example, ARNITEL® available from DSM Engineering Plastics), ether or ester based copolymers (for example, butylene/poly (alkylene ether) phthalate and/or other polyester elastomers such as HYTREL® available from DuPont), polyamide (for example, DURETHAN® available from Bayer or CRISTAMID® available from Elf Atochem), elastomeric polyamides, block polyamide/ethers, polyether block amide (PEBA, for example available under the trade name PEBAX®), ethylene vinyl acetate copolymers (EVA), silicones, polyethylene (PE), MARLEX® high-density polyethylene, MARLEX® low-density polyethylene, linear low density polyethylene (for example REXELL®), polyester, polybutylene terephthalate (PBT), polyethylene terephthalate (PET), polytrimethylene terephthalate, polyethylene naphthalate (PEN), polyetheretherketone (PEEK), polyimide (PI), polyetherimide (PEI), polyphenylene sulfide (PPS), polyphenylene oxide (PPO), poly paraphenylene terephthalamide (for example, KEVLAR®), polysulfone, nylon, nylon-12 (such as GRILAMID® available from EMS American Grilon), perfluoro (propyl vinyl ether) (PFA), ethylene vinyl alcohol, polyolefin, polystyrene, epoxy, polyvinylidene chloride (PVdC), poly (styrene-b-isobutylene-b-styrene) (for example, SIBS and/or SIBS 50A), polycarbonates, polyurethane silicone copolymers (for example, ElastEon® from Aortech Biomaterials or ChronoSil® from AdvanSource Biomaterials), biocompatible polymers, other suitable materials, or mixtures, combinations, copolymers thereof, polymer/metal composites, and the like. In some embodiments the sheath can be blended with a liquid crystal polymer (LCP). For example, the mixture can contain up to about 6 percent LCP.

[0178] Some examples of suitable metals and metal alloys include stainless steel, such as 304V, 304L, and 316LV stainless steel; mild steel; nickel-titanium alloy such as linear-elastic and/or super-elastic nitinol; other nickel alloys such as nickel-chromium-molybdenum alloys (e.g., UNS: N06625 such as INCONEL® 625, UNS: N06022 such as HASTELLOY® C-22®, UNS: N10276 such as HASTELLOY® C276®, other HASTELLOY® alloys, and the like), nickel-copper alloys (e.g., UNS: N04400 such as MONEL® 400, NICKELVAC® 400, NICORROS® 400, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R30035 such as MP35-N® and the like), nickel-molybdenum alloys (e.g., UNS: N10665 such as HASTELLOY® ALLOY B2®), other nickel-chromium alloys, other nickel-molybdenum alloys, other nickel-cobalt alloys, other nickel-iron alloys, other nickel-copper alloys, other nickel-tungsten or tungsten alloys, and the like; cobalt-chromium alloys; cobalt-chromium-molybdenum alloys (e.g., UNS: R30003 such as ELGILOY®, PHYNOX®, and the like); platinum enriched stainless steel; titanium; platinum; palladium; gold; combinations thereof; or any other suitable material.

[0179] In at least some embodiments, portions or all of the apparatus, and/or components thereof, may also be doped with, made of, or otherwise include a radiopaque material. Radiopaque materials are understood to be materials capable of producing a relatively bright image on a fluoroscopy screen or another imaging technique during a medical procedure. This relatively bright image aids the user of the apparatus in determining its location. Some examples of radiopaque materials can include, but are not limited to, gold, platinum, palladium, tantalum, tungsten alloy, polymer material loaded with a radiopaque filler, and the like. Additionally, other radiopaque marker bands and/or coils may also be incorporated into the design of the apparatus to achieve the same result.

[0180] In some embodiments, a degree of Magnetic Resonance Imaging (MRI) compatibility is

imparted into the apparatus and/or other elements disclosed herein. For example, the apparatus, and/or components or portions thereof, may be made of a material that does not substantially distort the image and create substantial artifacts (e.g., gaps in the image). Certain ferromagnetic materials, for example, may not be suitable because they may create artifacts in an MRI image. The apparatus, or portions thereof, may also be made from a material that the MRI machine can image. Some materials that exhibit these characteristics include, for example, tungsten, cobalt-chromium-molybdenum alloys (e.g., UNS: R30003 such as ELGILOY®, PHYNEX®, and the like), nickel-cobalt-chromium-molybdenum alloys (e.g., UNS: R30035 such as MP35-N® and the like), nitinol, and the like, and others.

[0181] In some embodiments, the apparatus and/or other elements disclosed herein may include and/or be treated with a suitable therapeutic agent. Some examples of suitable therapeutic agents may include anti-thrombogenic agents (such as heparin, heparin derivatives, urokinase, and PPACK (dextrophenylalanine proline arginine chloromethylketone)); anti-proliferative agents (such as enoxaparin, angiostatin, monoclonal antibodies capable of blocking smooth muscle cell proliferation, hirudin, and acetylsalicylic acid); anti-inflammatory agents (such as dexamethasone, prednisolone, corticosterone, budesonide, estrogen, sulfasalazine, and mesalamine); antineoplastic/antiproliferative/anti-mitotic agents (such as paclitaxel, 5-fluorouracil, cisplatin, vinblastine, vincristine, epothilones, endostatin, angiostatin and thymidine kinase inhibitors); anesthetic agents (such as lidocaine, bupivacaine, and ropivacaine); anti-coagulants (such as D-Phe-Pro-Arg chloromethyl ketone, an RGD peptide-containing compound, heparin, anti-thrombin compounds, platelet receptor antagonists, anti-thrombin antibodies, anti-platelet receptor antibodies, aspirin, prostaglandin inhibitors, platelet inhibitors, and tick antiplatelet peptides); vascular cell growth promoters (such as growth factor inhibitors, growth factor receptor antagonists, transcriptional activators, and translational promoters); vascular cell growth inhibitors (such as growth factor inhibitors, growth factor receptor antagonists, transcriptional repressors, translational repressors, replication inhibitors, inhibitory antibodies, antibodies directed against growth factors, bifunctional molecules consisting of a growth factor and a cytotoxin, bifunctional molecules consisting of an antibody and a cytotoxin); cholesterol-lowering agents; vasodilating agents; and agents which interfere with endogenous vasoactive mechanisms.

[0182] It should be understood that this disclosure is, in many respects, only illustrative. Changes may be made in details, particularly in matters of shape, size, and arrangement of steps without exceeding the scope of the invention. This may include, to the extent that it is appropriate, the use of any of the features of one example embodiment being used in other embodiments. The invention's scope is, of course, defined in the language in which the appended claims are expressed.

Claims

1. A medical device configured to form one or more holes within a bone of a patient, comprising: a handle assembly including a housing, a lever rotatably coupled to the housing between an initial position and an extended position, and a sheath extending distally from the housing; and a bone punch including an elongate shaft, a head at a proximal end of the elongate shaft, and a piercing tip at a distal end of the elongate shaft, wherein the piercing tip is configured to be driven into the bone; wherein the elongate shaft is slidably disposed within the sheath in a first position when the lever is in the initial position; wherein the handle assembly includes a linkage disposed within the housing, the linkage including an ejector block slidably disposed within the housing; wherein the head of the bone punch is magnetically coupled to the ejector block in the first position.
2. The medical device of claim 1, wherein distal translation of the bone punch from the first position toward a second position causes the linkage to rotate a distal end of the lever away from the housing to the extended position.
3. The medical device of claim 2, wherein rotation of the lever from the extended position toward a

longitudinal axis of the bone punch when the bone punch is in the second position generates proximal translation of the bone punch to extract the piercing tip from the bone.

4. The medical device of claim 2, wherein distal translation of the head of the bone punch from the first position to the second position translates the ejector block distally within the housing.
 5. The medical device of claim 2, wherein a rotational position of the lever relative to the housing indicates a distance the piercing tip has been translated distally.
 6. The medical device of claim 2, wherein distal translation of the bone punch from the first position toward the second position shortens an axial distance between a proximalmost pivot point of the linkage and a distalmost pivot point of the linkage.
 7. The medical device of claim 1, wherein the head of the bone punch includes one or more magnets disposed therein and the ejector block includes a magnetic material disposed therein opposite the one or more magnets.
 8. The medical device of claim 1, wherein the ejector block includes one or more magnets disposed therein and the head of the bone punch includes a magnetic material disposed therein opposite the one or more magnets.
 9. The medical device of claim 1, wherein the head of the bone punch includes one or more magnets disposed therein and the ejector block includes one or more magnets disposed therein opposite the one or more magnets disposed in the head of the bone punch.
 10. The medical device of claim 1, wherein the head of the bone punch includes one or more magnets fixedly attached thereto and the ejector block includes a magnetic material disposed opposite the one or more magnets.
 11. The medical device of claim 10, wherein the one or more magnets is exposed to an exterior of the head of the bone punch.
 12. The medical device of claim 1, wherein the ejector block includes one or more magnets fixedly attached thereto and the head of the bone punch includes a magnetic material disposed opposite the one or more magnets.
 13. The medical device of claim 12, wherein the one or more magnets is exposed to an exterior of the head of the bone punch.
 14. The medical device of claim 1, wherein the head of the bone punch includes one or more magnets fixedly attached thereto and the ejector block includes one or more magnets fixedly attached thereto opposite the one or more magnets disposed in the head of the bone punch.
 15. The medical device of claim 14, wherein the one or more magnets of the head of the bone punch is exposed to an exterior of the head of the bone punch.
 16. The medical device of claim 14, wherein the one or more magnets of the ejector block is exposed to an exterior of the ejector block.
 17. The medical device of claim 1, wherein the head of the bone punch includes a plurality of magnets equidistantly spaced from a central longitudinal axis of the bone punch.
 18. The medical device of claim 17, wherein the plurality of magnets is symmetrically arranged around the central longitudinal axis of the bone punch.
 19. The medical device of claim 18, wherein the plurality of magnets is arranged in diametrically opposed pairs.
 20. The medical device of claim 1, wherein the head of the bone punch is releasably coupled to the ejector block in the first position.
-