

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280161

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Nonnenmacher; Jorg et al.

SYSTEMS AND METHODS FOR CONTENT ITEM RECOGNITION AND ADAPTIVE PACKET TRANSMISSION

Abstract

Systems, methods, and machine-readable media for audio/video recognition and adaptive packet transmission are disclosed. A first content item that includes audio content and video content may be received and processed to detect a set of one or more video characteristics and/or a set of one or more audio characteristics that may be analyzed to identify the first content item as corresponding to a service provider system. The first content item may be transferred for display with an endpoint media device. At least one electronic signal may be received and processed, the at least one electronic signal indicative of execution of at least one operation of a set of one or more operations relating to one or more images of the first content item consequent to the display of the first content with the endpoint media device.

Inventors: Nonnenmacher; Jorg (Plascassier, FR), Carney Landow; Kate Megan (Denver, CO)

Applicant: DISH Network L.L.C. (Englewood, CO)

Family ID: 75491442

Appl. No.: 19/063055

Filed: February 25, 2025

Related U.S. Application Data

parent US continuation 18298846 20230411 parent-grant-document US 12262071 child US 19063055

parent US continuation 16655102 20191016 parent-grant-document US 11638049 child US 18298846

Publication Classification

Int. Cl.: H04N21/238 (20110101); H04N21/233 (20110101); H04N21/234 (20110101)

U.S. Cl.:

CPC H04N21/238 (20130101); H04N21/233 (20130101); H04N21/23418 (20130101);

Background/Summary

CROSS REFERENCES TO RELATED APPLICATION [0001] This application is a continuation of U.S. patent application Ser. No. 18/298,846, filed on Apr. 11, 2023, which is a continuation of U.S. patent application Ser. No. 16/655,102, filed on Oct. 16, 2019, now U.S. Pat. No. 11,638,049, issued on Apr. 25, 2023, the disclosures of which are hereby incorporated by reference in their entireties for all purposes.

TECHNICAL FIELD

[0002] This disclosure generally relates to content delivery, and more particularly to systems and methods for content item recognition and adaptive packet transmission.

BACKGROUND

[0003] The evolution of wireless networks and content distribution platforms may present a number of challenges and problems for content delivery within packet streams per Internet Protocol (IP), the ATSC (Advanced Television Systems Committee) 3.0 standard, or a like protocol. Such modes of content delivery may not be linear, in contrast to traditional television delivery, for example. And, still, there are needs for deeper integration with endpoint devices in a broadcast environment. Content viewers are in need of better viewer experiences and more tailored service offerings.

[0004] Thus, there is a need for systems and methods that address such problems. This and other needs are addressed by the present disclosure.

BRIEF SUMMARY

[0005] Certain embodiments of the present disclosure relate generally to content delivery, and more particularly to systems and methods for content item recognition and adaptive packet transmission.

[0006] In one aspect, a method for audio/video recognition and adaptive packet transmission is disclosed. The method may include one or a combination of the following. A first content item that includes audio content and video content may be received by a processing system including one or more processing devices. The first content item may be processed by the processing system to detect a set of one or more video characteristics of the video content and/or a set of one or more audio characteristics of the audio content. The set of one or more video characteristics of the video content and/or the set of one or more audio characteristics of the audio content may be analyzed by the processing system to identify the first content item as corresponding to a service provider system. The first content item may be transferred by the processing system for display with an endpoint media device. At least one electronic signal may be processed by the processing system, the at least one electronic signal received by the processing system that is indicative of execution of at least one operation of a set of one or more operations relating to one or more images of the first content item consequent to the display of the first content with the endpoint media device. The at least one electronic signal may be mapped by the processing system to the content item based at least in part on identifying the set of one or more operations as facilitated by the first content item. Responsive to the mapping of the at least one electronic signal to the first content item, a second content item may be identified by the processing system as being particularized to the first content item. The second content item may be transferred by the processing system so that the second content item is accessible with the endpoint media device.

[0007] In another aspect, a system to facilitate audio/video recognition and adaptive packet transmission is disclosed. The system may include one or more processing devices, and memory communicatively coupled with and readable by the one or more processing devices and having stored therein processor-readable instructions which, when executed by the one or more processing devices, cause the one or more processing devices to perform one or a combination of the following. A first content item that includes audio content and video content may be received. The first content item may be processed to detect a set of one or more video characteristics of the video content and/or a set of one or more audio characteristics of the audio content. The set of one or more video characteristics of the video content and/or the set of one or more audio characteristics of the audio content may be analyzed to identify the first content item as corresponding to a service provider system. The first content item may be transferred for display with an endpoint media device. At least one electronic signal may be processed, the at least one electronic signal received by the processing system that is indicative of execution of at least one operation of a set of one or more operations relating to one or more images of the first content item consequent to the display of the first content with the endpoint media device. The at least one electronic signal may be mapped to the content item based at least in part on identifying the set of one or more operations as facilitated by the first content item. Responsive to the mapping of the at least one electronic signal to the first content item, a second content item may be identified as being particularized to the first content item. The second content item may be transferred so that the second content item is accessible with the endpoint media device.

[0008] In yet another aspect, one or more non-transitory, machine-readable media are disclosed. The one or more non-transitory, machine-readable media may have machine-readable instructions thereon which, when executed by one or more processing devices, cause the one or more processing devices to perform one or a combination of the following. A first content item that includes audio content and video content may be received. The first content item may be processed to detect a set of one or more video characteristics of the video content and/or a set of one or more audio characteristics of the audio content. The set of one or more video characteristics of the video content and/or the set of one or more audio characteristics of the audio content may be analyzed to identify the first content item as corresponding to a service provider system. The first content item may be transferred for display with an endpoint media device. At least one electronic signal may be processed, the at least one electronic signal received by the processing system that is indicative of execution of at least one operation of a set of one or more operations relating to one or more images of the first content item consequent to the display of the first content with the endpoint media device. The at least one electronic signal may be mapped to the content item based at least in part on identifying the set of one or more operations as facilitated by the first content item. Responsive to the mapping of the at least one electronic signal to the first content item, a second content item may be identified as being particularized to the first content item. The second content item may be transferred so that the second content item is accessible with the endpoint media device.

[0009] In various embodiments, the processing system and/or the one or more processing devices may be remote from the endpoint media device, and the transferring the content item for display with the endpoint media device may include transmitting the content item via one or more networks to endpoint media device. In various embodiments, the endpoint media device may include at least part of the processing system and/or the one or more processing devices. The transferring the content item for display with the endpoint media device may include outputting the content item for display with a display device included in the endpoint media device and/or communicatively coupled to the endpoint media device.

[0010] In various embodiments, a set of observation data corresponding to indications of detected operations associated with the endpoint media device and mapped to a set of one or more content items may be aggregated based at least in part on the processing the at least one electronic signal.

The set of one or more content items may include the first content item. The identifying the second content item as being particularized to the first content item may be based at least in part on the set of observation data.

[0011] In various embodiments, the processing the first content item to detect the set of one or more video characteristics of the video content of the first content item may include recognizing text represented by one or more images of the video content. The set of one or more video characteristics of the video content may include at least a portion of the recognized text. The analyzing the set of one or more video characteristics of the video content to identify the first content item as corresponding to the service provider system may be based at least in part on the at least the portion of the recognized text.

[0012] In various embodiments, the recognizing the text represented by the one or more images of the video content may include recognizing a uniform resource identifier, and the recognized text may include the uniform resource identifier. In various embodiments, the processing the first content item to detect the set of one or more audio characteristics of the audio content of the first content item may include recognizing dialogue from the audio content. The set of one or more audio characteristics of the audio content may include at least a portion of the recognized dialogue. The analyzing the set of one or more audio characteristics of the audio content to identify the first content item as corresponding to the service provider system may be based at least in part on the at least the portion of the recognized dialogue.

[0013] Further areas of applicability of the present disclosure will become apparent from the detailed description provided hereinafter. It should be understood that the detailed description and specific examples, while indicating various embodiments, are intended for purposes of illustration only and are not intended to necessarily limit the scope of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] A further understanding of the nature and advantages of various embodiments may be realized by reference to the following figures. In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

[0015] FIG. 1 illustrates a content distribution system, in accordance with disclosed embodiments of the present disclosure.

[0016] FIG. 2 further illustrates a content distribution system, in accordance with disclosed embodiments of the present disclosure.

[0017] FIG. 3 illustrates a diagram of an adaptive content composite system, in accordance with disclosed embodiments of the present disclosure.

[0018] FIG. 4 illustrates a composite build engine, in accordance with disclosed embodiments of the present disclosure.

[0019] FIG. 5 illustrates certain aspects of subsystem data flow, in accordance with disclosed embodiments of the present disclosure.

[0020] FIG. 6 illustrates a receiver that makes use of, interacts with, and/or at least partially includes the content composite subsystem, in accordance with disclosed embodiments of the present disclosure.

[0021] FIG. 7 illustrates a system including one non-limiting example of a computing device configured to make use of, interact with, and/or at least partially include the content composite

subsystem, in accordance with disclosed embodiments of the present disclosure.

[0022] FIG. 8 illustrates a computer system, in accordance with disclosed embodiments of the present disclosure.

DETAILED DESCRIPTION

[0023] The ensuing description provides preferred exemplary embodiment(s) only, and is not intended to limit the scope, applicability or configuration of the disclosure. Rather, the ensuing description of the preferred exemplary embodiment(s) will provide those skilled in the art with an enabling description for implementing a preferred exemplary embodiment of the disclosure. It should be understood that various changes may be made in the function and arrangement of elements without departing from the spirit and scope of the disclosure as set forth in the appended claims.

[0024] Specific details are given in the following description to provide a thorough understanding of the embodiments. However, it will be understood by one of ordinary skill in the art that the embodiments may be practiced without these specific details. For example, circuits may be shown in block diagrams in order not to obscure the embodiments in unnecessary detail. In other instances, well-known circuits, processes, algorithms, structures, and techniques may be shown without unnecessary detail in order to avoid obscuring the embodiments.

[0025] Also, it is noted that the embodiments may be described as a process which is depicted as a flowchart, a flow diagram, a data flow diagram, a structure diagram, or a block diagram. Although a flowchart may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process is terminated when its operations are completed but could have additional steps not included in the figure. A process may correspond to a method, a function, a procedure, a subroutine, a subprogram, etc. When a process corresponds to a function, its termination corresponds to a return of the function to the calling function or the main function.

[0026] Various embodiments will now be discussed in greater detail with reference to the accompanying figures, beginning with FIG. 1.

[0027] FIG. 1 illustrates a content distribution system **100**, in accordance with disclosed embodiments of the present disclosure. For brevity, system **100** is depicted in a simplified and conceptual form, and may generally include more or fewer systems, devices, networks, and/or other components as desired. Further, the number and types of features or elements incorporated within the system **100** may or may not be implementation-specific, and at least some of the aspects of the system **100** may be similar to a cable television distribution system, an IPTV (Internet Protocol Television) content distribution system, and/or another type of media or content distribution system.

[0028] In general, the system **100** may include a plurality of networks **120** that can be used for bi-directional communication paths for data transfer between components of system **100**. Disclosed embodiments may transmit and receive data, including video content, via the networks **120** using any suitable protocol(s), as is disclosed in co-pending U.S. patent application Ser. No. 16/383,300, filed Apr. 12, 2019, the disclosure of which application is incorporated by reference herein in its entirety for all purposes, as if fully set forth herein. The networks **120** may be or include one or more next-generation networks (e.g., 5G wireless networks and beyond). Further, the plurality of networks **120** may correspond to a hybrid network architecture with any number of terrestrial and/or non-terrestrial networks and/or network features, for example, cable, satellite, wireless/cellular, or Internet systems, or the like, utilizing various transport technologies and/or protocols, such as radio frequency (RF), optical, satellite, coaxial cable, Ethernet, cellular, twisted pair, other wired and wireless technologies, and the like. In various instances, the networks **120** may be implemented with, without limitation, satellite communication with a plurality of orbiting (e.g., geosynchronous) satellites, a variety of wireless network technologies such as 5G, 4G, LTE (Long-Term Evolution), 3G, GSM (Global System for Mobile Communications), another type of

wireless network (e.g., a network operating under Bluetooth®, any of the Institute of Electrical and Electronics (IEEE) 802.11 suite of protocols, and/or any other wireless protocol), a wireless local area network (WLAN), a HAN (Home Area Network) network, another type of cellular network, the Internet, a wide area network (WAN), a local area network (LAN) such as one based on Ethernet, Token-Ring and/or the like, such as through etc., a gateway, and/or any other appropriate architecture or system that facilitates the wireless and/or hardwired packet-based communications of signals, data, and/or message in accordance with embodiments disclosed herein. In various embodiments, the networks **120** and its various components may be implemented using hardware, software, and communications media such wires, optical fibers, microwaves, radio waves, and other electromagnetic and/or optical carriers; and/or any combination of the foregoing and/or the like. In some embodiments, the networks **120** may include a telephone network that may be circuit switched, package switched, or partially circuit switched and partially package switched. For example, the telephone network may partially use the Internet to carry phone calls (e.g., through VoIP). In various instances, the networks **120** may transmit data using any suitable communication protocol(s), such as TCP/IP (Transmission Control Protocol/Internet protocol), SNA (systems network architecture), IPX (Internet packet exchange), UDP, AppleTalk, and/or the like.

[0029] The system **100** may include one or more content provider systems **102**, one or more other data source systems **103**, and media devices including adaptive routers **110** and various endpoint devices **116**. Many embodiments may include a large number of content provider systems **102**, data source systems **103**, and/or such media devices. The one or more content provider systems **102** may include one or more television service provider systems. The content provider systems **102** may distribute broadcast video content to the endpoint devices **116** via one or more networks of the networks **120** and the adaptive routers **110**. For example, a content provider system **102** may be configured to stream, via the networks **120**, television channels, on-demand programming, movies, other shows, television programs or portions of television programs following and/or during a live broadcast of the television programs, announcement content and commercials, programming information (e.g., table data, electronic programming guide (EPG) content, etc.), and/or other services to endpoint devices **116** via satellite, 5G, 4G, and/or LTE wireless communication protocols and network components, in accordance with embodiments disclosed herein.

[0030] A content provider system **102** with satellite transmitter equipment, satellite uplink, and/or other network routing equipment that may, for example, be operated by a television service provider. The content provider system **102** may receive feeds of one or more television channels from various sources. Such television channels may include multiple television channels that contain the same content (but may be in different formats, such as high-definition and standard-definition). To distribute such video content to endpoint devices **116**, feeds of the video content may be relayed to the adaptive routers **110** and the endpoint devices **116** via one or more satellites in the form of transponder streams or transmitted to the adaptive routers **110** and the endpoint devices **116**.

[0031] The data source systems **103** may correspond to any suitable sources of data such as one or more computer systems, databases, websites, portals, any repositories of data in any suitable form, server systems, other endpoint devices like endpoint devices **116** but functioning as data sources, and/or the like. In some instances, the data source systems **103** may include one or more mobile computing device locator services that provide information regarding the location of one or more of the endpoint devices **116** and/or the the adaptive routers **110**. In various instances, the data source systems **103** may provide various details relating to IP addresses, cellular tower identification and location data, mobile device triangulation data, LAN identification data, Wi-Fi identification data, access point identification and location data, and/or the like data that facilitates location of one or more of the endpoint devices **116** and/or the adaptive routers **110**.

[0032] In various embodiments, the data from one or more of the data source systems **103** may be retrieved and/or received by a television service provider system **102** via one or more data

acquisition interfaces through network(s) **120** and/or through any other suitable means of transferring data. In various embodiments, the television service provider system **102** the data source systems **103** could use any suitable means for direct communication. In various embodiments, the television service provider system **102** may actively gather and/or pull from one or more of the data source systems **103**. Additionally or alternatively, the television service provider system **102** may wait for updates from one or more of the data source systems **103**. The data collected (location data, IP address, etc.) may be curated so that only the data necessary for the transaction is collected. The one or more data acquisition interfaces may include one or more application programming interfaces (APIs) that define protocols and routines for interfacing with the data source systems **103**. The APIs may specify application programming interface (API) calls to/from data source systems **103**. In some embodiments, the APIs may include a plug-in to integrate with an application of a data source systems **103**. The data acquisition interfaces, in some embodiments, could use a number of API translation profiles configured to allow interface with the one or more additional applications of the data sources to access data (e.g., a database or other data store) of the data source systems **103**. The API translation profiles may translate the protocols and routines of the data source systems **103** to integrate at least temporarily with the system and allow communication with the system by way of API calls.

[0033] FIG. 2 illustrates a content distribution system **200**, in accordance with disclosed embodiments of the present disclosure. In various embodiments, the system **200** may correspond to an example system that may encompass all or part of the content distribution system **100** and that illustrates certain features of disclosed embodiments. Again, for brevity, system **200** is depicted in a simplified and conceptual form, and may generally include more or fewer systems, devices, networks, and/or other components as desired. Further, the number and types of features or elements incorporated within the system **200** may or may not be implementation-specific, and at least some of the aspects of the system **200** may be similar to a cable television distribution system, an IPTV (Internet Protocol Television) content distribution system, and/or any other type of media or content distribution system.

[0034] The system **200** may include content provider system **102-1**, satellite uplink **104**, a plurality of orbiting (e.g., geosynchronous) satellites **106**, satellite receiver **108**, one or more computing devices **116a-d**, one or more television receivers **116e**, one or more content sources **112** (e.g., online content sources), and service provider systems **103-1**. In various embodiments, one or a combination of the one or more computing devices **116a-d**, one or more television receivers **116e**, and/or one or more display devices **160** may correspond to endpoint media devices **116**.

[0035] The content provider system **102-1** and satellite transmitter equipment (which may include the satellite uplink **104**) may be operated by a television service provider. A television service provider may distribute television channels, on-demand programming, programming information, and/or other services to users via satellite. The content provider system **102-1** may receive feeds of one or more television channels from various sources. Such television channels may include multiple television channels that contain the same content (but may be in different formats, such as high-definition and standard-definition). To distribute such television channels to users, feeds of the television channels may be relayed to user equipment via one or a combination of the networks **120** and/or via one or more satellites in the form of transponder streams. Satellite transmitter equipment may be used to transmit a feed of one or more television channels from the content provider system **102-1** to one or more satellites **106**. While a single content provider system **102-1** and satellite uplink **104** are illustrated as part of the television distribution system **200**, it should be understood that multiple instances of transmitter equipment may be used, possibly scattered geographically to communicate with satellites **106**. Such multiple instances of satellite transmitting equipment may communicate with the same or with different satellites **106**.

[0036] The television receivers **116e**, as described throughout, may generally be any type of television receiver (such as an STB (set-top box), for example) configured to decode signals

received for output and presentation via a display device **160**. In another example, television receiver **116e** (which may include another remote television receiver **116e**) may be integrated as part of or into a television, a DVR, a computing device, such as a tablet computing device, or any other computing system or device, as well as variations thereof. In some embodiments, a television receiver **116e** may be a component that is added into the display device **160**, such as in the form of an expansion card. A television receiver **116e** and network **120** together with television receivers **116e** and/or one or more computing devices **116**, may form at least a portion of a particular home computing network, and may each be respectively configured such as to enable communications in accordance with any particular communication protocol(s) and/or standard(s) including, for example, TCP/IP (Transmission Control Protocol/Internet Protocol), DLNA/DTCP-IP (Digital Living Network Alliance/Digital Transmission Copy Protection over Internet Protocol), HDMI/HDCP (High-Definition Multimedia Interface/High-Bandwidth Digital Content Protection), etc. While only a limited number of television receivers **116e**, display devices **160**, computing devices **116**, etc. are illustrated, it should be understood that multiple (e.g., tens, thousands, millions) instances of such equipment, corresponding to various users in various geolocations, may be included the system **200**.

[0037] In various embodiments, broadcast television programs may be delivered to television receivers, including a television receiver **116e**, via one or a combination of the networks **120** and/or via satellite according to a schedule. On-demand content may also be delivered to a television receiver **116e** via one or a combination of the networks **120** and/or via satellite. Satellites **106** may be configured to receive uplink signals **122** from satellite uplink **104**. In this example, uplink signals **122** may contain one or more transponder streams of particular data or content, such as particular television channels, each of which may be supplied by content provider system **102-1**. For example, each of uplink signals **122** may contain various media content such as HD (High Definition) television channels, SD (Standard Definition) television channels, on-demand programming, programming information (e.g., table data), and/or any other content in the form of at least one transponder stream, and in accordance with an allotted carrier frequency and bandwidth. In this example, different media content may be carried using different satellites of satellites **106**. Further, different media content may be carried using different transponders of a particular satellite (e.g., satellite **106-1**); thus, such media content may be transmitted at different frequencies and/or different frequency ranges. For example, a first television channel and a second television channel may be carried on a first carrier frequency over a first transponder (as part of a single transponder stream) of satellite **106-1**, and a third, fourth, and fifth television channel may be carried on a second carrier frequency (as part of another transponder stream) over a transponder of satellite **106-3**, or, the third, fourth, and fifth television channel may be carried on a second carrier frequency over a second transponder of satellite **106-1**, etc.

[0038] The satellites **106** may be further configured to relay uplink signals **122** to the satellite receiver **108** as downlink signals **124**. Similar to the uplink signals **122**, each of the downlink signals **124** may contain one or more transponder streams of particular data or content, such as various encoded and/or at least partially scrambled television channels, on-demand programming, etc., in accordance with an allotted carrier frequency and bandwidth. The satellite receiver **108**, which may include a satellite dish, a low noise block (LNB), and/or other components, may be provided for use to receive television channels, such as on a subscription basis, distributed by the content provider system **102-1** via the satellites **106**. For example, the satellite receiver **108** may be configured to receive particular transponder streams as downlink signals **124**, from one or more of the satellites **106**. Based at least in part on the characteristics of a given television receiver **116e** and/or satellite receiver **108**, it may only be possible to capture transponder streams from a limited number of transponders of the satellites **106** concurrently. For example, a tuner of the television receiver **116e** may only be able to tune to a single transponder stream from a transponder of a single satellite, such as the satellite **106-1**, at a time.

[0039] The television receiver **116e**, which may be communicatively coupled to the satellite receiver **108**, may subsequently select, via a tuner, decode, and relay television programming to a television for display thereon. Broadcast television programming or content may be presented “live,” or from a recording as previously stored on, by, or at the television receiver **116e**. For example, an HD channel may be output to a television by the television receiver **116e** in accordance with the HDMI/HDCP content protection technologies. Other embodiments are possible. For example, in some embodiments, an HD channel may be output to a television in accordance with the MoCA® (Multimedia over Coax Alliance) home entertainment networking standard. Other embodiments are possible.

[0040] The television receiver **116e** may select via tuner, decode, and relay particular transponder streams to one or more of television receivers **116e**, which may in turn relay particular transponder streams to one or more display devices **160**. For example, the satellite receiver **108** and the television receiver **116e** may, respectively, be configured to receive, decode, and relay at least one television channel to a television by way of a television receiver **116e**. Similar to the above example, a television channel may generally be presented “live,” or from a recording as previously stored by the television receiver **116e**, and may be output to the display device **160** by way of the television receiver **116e** in accordance with a particular content protection technology and/or networking standard. Other embodiments are possible.

[0041] In various embodiments, the content resources may be used to provide the television receiver **116e** with content (e.g., television programming). The content resources may be used to retrieve television programs or portions of television programs following and/or during a live broadcast of the television programs. The content resources may include the content provider system **102-1**, the service provider systems **103-1**, the online content sources **112**, one or more other television receivers **116e**, and/or the like.

[0042] The content provider system **102-1**, which may distribute broadcast television programming to the television receivers **116e** via a satellite-based television programming distribution arrangement (or some other form of television programming distribution arrangement, such as a cable-based network, fiber-based network, or IP-based network), may use an alternate communication path, such as via the network **120**, to provide television programming to the television receivers **116e**. The television receivers **116e** may be permitted to request various television programs or portions of television programs from the content provider system **102-1** via the network **120**. For instance, the content provider system **102-1** may be permitted to transmit a portion of a television program or an entire television program during and/or after a time at which the television program was broadcast live by the television service provider via a satellite-based television programming distribution arrangement.

[0043] In some embodiments, the content provider system **102-1** may provide a television program via on-demand content. On-demand content may be included in a user's subscription or may be provided on a per-request basis. Such on-demand content may be provided via the satellite-based distribution arrangement and/or via the network **120**. On-demand content provided via the satellite-based distribution arrangement may be stored locally by the television receiver **116e** to allow on-demand access. On-demand content may also be retrieved via the network **120** from the content provider system **102-1**.

[0044] The computing devices **116a-d** represent various computerized devices that may or may not be associated with a user of the television receiver **116e** and that may be configured to facilitate various adaptive content features disclosed in various embodiments herein. As indicated by **116a**, the computing devices **116a-d** may include a laptop computer, a desktop computer, a home server, or another similar form of computerized device. As indicated by **116b** and **116c**, the computing devices **116a-d** may include a cellular phone and/or smartphone, a tablet computer, or another similar form of mobile device. As indicated by **116d**, the computing devices **116a-d** may include smart glasses or another similar form of wearable computing device.

[0045] In various embodiments, the television receiver **116e** may be provided with access credentials that allow access to content stored and/or accessible through one or more of the computing devices **116a-d**. Likewise, in various embodiments, one or more of the computing devices **116a-d** may be provided with access credentials that allow access to content stored and/or accessible through the television receiver **116e** and/or account associated therewith and/or associated with an application installed on the one or more of the computing devices **116a-d**. It should be understood that computing devices **116a-d** are exemplary in nature. Content may be accessible through a lesser or greater number of computerized devices associated with a user of the television receiver **116e**.

[0046] In some embodiments, the online content sources **112** may represent content resources through which content may be retrieved by the endpoint media devices **116** via the network **120**. Content available through the online content sources **112** may be available for free and not require subscription (a username and/or password may or may not be necessary). Each of the online content sources **112** may represent different websites available via the Internet. For example, some content may be legally made available for free (such as television programming provided by government-funded sources, e.g., the BBC or Hulu®). Periodically, the endpoint media devices **116** may poll online content sources **112** to determine which content is available and/or which content is scheduled to be available in the future. In some embodiments, the endpoint media devices **116** may poll online content sources **112** regarding the availability of at least a portion of a specific show.

[0047] The service provider systems **103-1** may correspond to one or more data sources **112** that are any suitable source of data to facilitate embodiments disclosed further herein. In various embodiments, the service provider systems **103-1** may include one or more computer systems, a database, a website, a portal, any repository of data in any suitable form, a server system, and/or the like. With some embodiments, the data sources **112** may include one or more mobile computing device locator services that provide information regarding the location of one or more computing devices **116a-d**. With some embodiments, the data sources **112** may provide various details relating to IP addresses, cellular tower identification and location data, mobile device triangulation data, LAN identification data, Wi-Fi identification data, access point identification and location data, and/or the like data that facilitates location of one or more computing devices **116a-d**. With some embodiments, the data sources **112** may provide demographic data about an area encompassing the location of one or more computing devices **116a-d**, as well as identity information, user profile information, usage information, account information, and/or the like about users and viewers associated with the computing device **116a-d**.

[0048] In various embodiments, the data from the one or more data sources **112** may be retrieved and/or received by the content provider system **102-1** and/or the subsystem(s) **111** via one or more data acquisition interfaces through network(s) **120** and/or through any other suitable means of transferring data. In various embodiments, the content provider system **102-1** and/or the subsystem(s) **111** and the data sources **112** could use any suitable means for direct communication. The one or more data acquisition interfaces may include one or more application programming interfaces (APIs) that define protocols and routines for interfacing with the data sources **112**. The APIs may specify application programming interface (API) calls to/from service provider systems **103-1**. In some embodiments, the APIs may include a plug-in to integrate with an application of a service provider system **103-1**. The data acquisition interfaces, in some embodiments, could use a number of API translation profiles configured to allow interface with the one or more additional applications of the data sources to access data (e.g., a database or other data store) of the data sources **112**. The API translation profiles may translate the protocols and routines of the service provider system **103-1** to integrate at least temporarily with the system and allow communication with the system by way of API calls. Data, as referenced herein, may correspond to any one or combination of raw data, unstructured data, structured data, information, and/or content which may

include media content, text, documents, files, instructions, code, executable files, images, video, audio, and/or any other suitable content suitable for embodiments of the present disclosure.

[0049] Although FIG. 2 illustrates an example that includes a satellite-based television channel distribution system, it should be understood that at least some of the aspects of such a system may be similar to a cable television distribution system, an IPTV content distribution system, and/or any other type of media or content distribution system. For example, in a cable television system, rather than using satellite transponders, multiple RF channels on a cable may be used to transmit streams of television channels. As such, aspects detailed herein may be applicable to cable television distribution systems.

[0050] Further, the content provider system **102-1** may include one or more content server systems configured to stream television programming, including televised events such as sports events, to the computing devices **116** via the network **120**. When the streaming content servers stream content to the computing devices **116**, the stream content may be processed and displayed by the computing devices **116** using one or more applications installed on the computing devices **116**. Some such streaming services may require a subscription and may require user authentication, e.g., with a username and/or password which may or may not be associated with an account map to the television receiver **116e**. Accordingly, the streaming services may make a television program available for streaming or download during the live broadcast of the television program.

[0051] The television receiver **116e** may be able to retrieve at least a portion of a television program through other television receivers **116e**, which can function as content resources. Similarly, the television receiver **116e** may be able to cast at least a portion of a television program through other television receivers **116e** and/or to computing devices **116**. For instance, a Slingbox® (or other form of media streaming device) functioning in concert with a television receiver **116e** may permit television programs to be captured and streamed over the network **120**. In some embodiments, the television receivers **116e** may have such media streaming capabilities integrated. In some embodiments, the television receivers **116e** may cast programming content to the computing devices **116** via wireless signals. For example, the programming content from the television receiver **116e** may be indirectly transmitted via a local network (e.g., via Wi-Fi) or directly transmitted to the computing device **116** via a casting device integrated with the television receiver **116e** or coupled to the television receiver **116e** (e.g., via a dongle). In some embodiments, the programming content may be cast to the computing device **116** via a wired connection (e.g., via one or more of HDMI, USB, lightning connector, etc.). Some embodiments of the television receivers **116e** may provide for simulcasting such that the same programming that is being displayed on the display device **160** is being displayed on one or more of the computing devices **116** simultaneously or substantially simultaneously.

[0052] A user may be able to obtain at least a portion of a television program via the television receivers **116e**, which may be associated with other users or with the same user. For instance, the user may have multiple television receivers **116e** at different locations. Periodically, the television receiver **116e** may poll the other television receivers **116e** to determine which television programs are available and/or which television programs are scheduled to be available in the future. In some embodiments, the television receiver **116e** may poll the television receivers **116e** regarding the availability of at least a portion of a specific television program.

[0053] Thus, while network configuration data may be broadcast repeatedly via satellite to television receivers **116e**, it should be understood that a similar arrangement may be used in cable-based television programming broadcast networks to broadcast network configuration. For any of the various type of network, various other forms of data may be transmitted via an Internet-based network **120** connection rather than using the television service provider's proprietary network. For instance, EPG data may be transmitted to television receivers via the network **120** (e.g., Internet) connection. As another example, firmware and/or software updates may be transmitted on demand to a television receiver via the Internet rather than the television receiver receiving the update via

the television programming broadcast network.

[0054] The content provider system **102-1** may include one or more adaptable content item **176** repositories and/or particular content item **177** repositories. The content provider system **102-1** may store adaptable content items **176** and/or particular content item **177** in the one or more repositories. The one or more repositories may be implemented in various ways. For example, one or more data processing systems may store adaptable content items. One or more relational or object-oriented databases, or flat files on one or more computers or networked storage devices, may store adaptable content items. In some embodiments, a centralized system stores adaptable content items; alternatively, a distributed/cloud system, network-based system, such as being implemented with a peer-to-peer network, or Internet, may store adaptable content items.

[0055] Adaptable content items **176** and/or particularized content items **177** may correspond to any one or combination of raw data, unstructured data, structured data, information, and/or content which may include media content, text, documents, files, instructions, code, executable files, images, video, audio, audio video, and/or any other suitable content suitable for embodiments of the present disclosure. For example, the content items **176** may be adaptable content items that may correspond to visual and/or audiovisual announcements with graphical and/or audio components particularized to certain types of products and/or services. In some embodiments, the announcements may correspond to commercials to be presented during commercial breaks of television programming, such as televised events. In some instances, the content items **176** may be sourced by one or more of the service provider systems **103-1**.

[0056] In some embodiments, the adaptable content items **176** may correspond to video and/or audio video file structures with one or more transition points, hooks, frames, windows, and/or the like for merging with one or more particularized content items, content items **177**, particularized to certain products and/or services. As disclosed herein, the adaptable content items **176** may be merged, blended, joined, overlaid, customized, and/or the like in any suitable manner with other particularized content items **177** in order to create electronic content composites **180** particularized to certain types of products and/or services. In various embodiments, as further disclosed herein, the adaptable content items **176** and/or the other content items **177** may be formatted, rescaled, cropped, image characteristic (e.g., color, brightness, transparency, opaqueness, contrast, etc.) adjusted, and/or otherwise prepared to facilitate the merging, blending, joining, overlaying, customizing, and/or the like and presentation by endpoint media devices **116** as disclosed herein.

[0057] In various embodiments, the particularized content items **177** may correspond to content that is particularized to certain types of products and/or services and that, in various embodiments, may be sourced by one or combination of the system **102**, one or more of the service provider systems **103-1**, and/or the endpoint media device **116** (e.g., in instances where personalization data that may form at least part of a particularized content item **177**). In various embodiments, the service provider systems **103-1** may correspond to one or more sources of data and/or services corresponding to the adaptable content items **176** and/or the particularized content items **177**, and particularized content items **177** may correspond to the specific data and/or services sourced by a specific service provider system **103-1**. For example, the data may correspond particular digital content that is redeemable to discount product(s) and/or service(s) (i.e., a redeemable content item, such as an e-coupon), matrix code such as a QR code, trailer, movie content, and/or the like. In some embodiments, particularized content items **177** may include personalized content that is particular to one or more viewers. In some embodiments, the personalized content may be separate from the particularized content items **177**. As disclosed above, the adaptable content items **176** and/or the content items **177** may correspond to any one or combination of raw data, unstructured data, structured data, information, and/or content which may include media content, text, documents, files, instructions, code, executable files, images, video, audio, audio video, and/or any other suitable content suitable for embodiments of the present disclosure.

[0058] In various embodiments, content items **176** and/or **177** may be actively gathered and/or

pulled from one or more data sources **112**, for example, by accessing a repository and/or by “crawling” various repositories. Additionally or alternatively, the content provider system **102-1** and/or the subsystem(s) **111** may wait for updates from one or a combination of the content source systems **112**. Content items **176** and/or **177** pulled and/or pushed from the one or more data sources **112** may be transformed, and the transformed content items **176** and/or **177** and/or other data generated based thereon may be made available by the content provider system **102-1** and/or the subsystem(s) **111** for use by the subsystem(s) **111** in conjunction with content composites **180**. [0059] In some embodiments, the content provider system **102-1** may provide the adaptable content items **176** and, in some embodiments, the particularized content items **177**, to the endpoint media device **116** as part of a data transfer that is sent through the satellite **106**. For example, in some embodiments, the television receiver **116e** may receive a downlinked satellite signal that includes the data for adaptable content items **176** and/or particularized content items **177** transferred on a designated line in the vertical blanking interval (VBI) or other portion of the broadcast service transmission that does not interfere with other transmitted content. Additionally or alternatively, the content provider system **102-1** may provide adaptable content items **176** and/or particularized content items **177** to the television receiver **116e** via the one or more data networks **120**. In some embodiments, the content provider system **102-1** may store the adaptable content items **176** and/or particularized content items **177** in an adaptable content item **176** repository and/or a particularized content items **177** repository included in or otherwise accessible to the content provider system **102-1**. In some embodiments, the television receiver **116e** may store the adaptable content items **176** and/or particularized content items **177** in an adaptable content item **176** repository and/or a particularized content items **177** repository included in the television receiver **116e** or otherwise local to the television receiver **116e**. Consequently, the television receiver **116e** may use one or more of the adaptable content items **176** and one or more of the particularized content items **177** in accordance with embodiments disclosed herein. In some embodiments, additionally or alternatively to providing the adaptable content items **176** and/or particularized content items **177**, the content provider system **102-1** may provide content composites **180** to the television receiver **116e** through such means.

[0060] The content provider system **102-1** may include a content composite subsystem **111** in whole or in part. The extent to which the media devices **116** may be configured to provide features of the subsystem **111** (e.g., by way of software updates and communications from the system **102-1**) may depend on the processing power and storage capabilities of a given device **116**. The system **102-1** may communicate with a given device **116** to pull specifications and current device capability information from the device **116**. Based on such communications, the system **102-1** may the extent to which the device **116** can be configured to provide features of the subsystem **111** and may operate accordingly. For example, the system **102-1** may push one or more software packages to the device **116** to configure the device **116** to provide a set of one or more features of the subsystem **111**. In instances where the device **116** lacks sufficient processing and/or storage capabilities, the subsystem **111** may operate on the system **102-1**. As one example with respect to many features disclosed herein, the filtering of composites **180** may be performed on the backend at system **102-1** when the device **116** lacks sufficient resources to perform the filtering itself. Further, in some embodiments, additionally or alternatively, one or more of the endpoint media devices **116** may include a content composite subsystem **111** whole or in part. In some embodiments, additionally or alternatively, one or more service provider systems **103-1** may include a content composite subsystem **111** in whole or in part. The content composite subsystem **111** may be configured to facilitate various content adaptation features in accordance with various embodiments disclosed herein.

[0061] The system **102** with the content composite subsystem **111** may be configured to perform one or more methods for facilitating adaptive content items for delivery in a packet stream, such as methods for containerizing and adapting content items, as disclosed herein. In various

embodiments, part or all of the method may be performed while an endpoint media device **116** is receiving programming content and/or is outputting programming content for display. In various embodiments, at least part of the method may be performed in advance of the programming content and, thus, may be performed while is scheduled to output programming content but before the programming content is broadcast to endpoint media devices **116** and/or before the programming content output by an endpoint media device **116** for display. In various embodiments, one or more media devices (e.g., the devices **116a-e** and/or the system **102-1**) may perform all or part of the method, with a single media device or multiple media devices performing the method.

[0062] In various instances, a media device may receive and process an electronic communication from a user interface, the electronic communication corresponding to an indicator of content. For example, the indicator may correspond to a selection corresponding to a televised event, may correspond to an initialization/powering up of the device **116**, a channel and/or stream selection such as a selection to tune to a channel that is streaming the televised event or that is scheduled the stream the event, an application selection such as a selection to download or otherwise stream the televised event which may be by way of an application device, a selection to view and/or record a particular televised event, and/or the like.

[0063] The media device may receive first content corresponding to the programming content and may output the content for display with a display device **160** and/or with a display component of a device **116**. The first content may be determined to correspond to a televised event as including the televised event, as preceding the televised event, and/or as being delivered within a temporal proximity to the televised event. This may include identifying one or more specifications of the programming content from the programming content; metadata associated with the programming content; EPG or other schedule data received by the device **116** from the content provider system **102-1** and mapping such data to the programming content, channel, and/or current or upcoming time/time period; and/or the like. Some embodiments may further include identifying the programming content as likely be viewed by a particular viewer based at least in part on viewer pattern data, even though the viewer has not yet made a selection to view and/or record the programming content. For example, as disclosed herein, the pattern data may indicate a preference for a particular type of programming content. The subsystem **111** may determine that the programming content corresponds to the preference and that temporal specifications for the programming content satisfy one or more temporal thresholds. In some instances, the subsystem **111** may determine that the programming content is currently ongoing and available for viewing on another channel, stream, or other viewing options that the viewer has not yet selected. Likewise, in some instances, the subsystem **111** may determine that the programming content is scheduled to be available within a suitable time for threshold (e.g., a number of minutes, hours, days, weeks, and/or the like) for viewing on the same channel, stream, or other viewing option that the viewer has selected or on a different channel, stream, or other viewing option that the viewer has not yet selected.

[0064] One or more content composites **180** may be created to facilitate delivery of the composite **180** and display of one or more content items **176** (in some instances, as modified with particular items **177**) in conjunction with the televised event or other type of audiovisual content (movies, shows, etc.). One or more indicators of one or more state changes with respect to the content (e.g., event that is televised, show, etc.) may be detected. The one or more state changes may include upcoming state changes, such as commercial breaks upcoming within a time threshold (e.g., a number of seconds and/or minutes). In some embodiments, the one or more content composites **180** may be created and/or delivered consequent to the detecting the one or more state changes. In some embodiments, the one or more content items **176** may be adapted with one or more particular items **177** consequent to the detecting the one or more state changes.

[0065] In some embodiments, the creating the content composite **180** and/or the adaptation of the one or more content items **176** with one or more particular items **177** may be a function of a current

geolocation of the endpoint media device **116**, with a set of rules mapped to the current geolocation and specifying geo-specific criteria for creating content composites **180**, selecting content items **176** and particularized content items **177**, adapting the content items **176** with particularized content items **177**, and provisioning the content items **176** and particularized content items **177**. The current geolocation of the media device may be determined at a time when the first content is being output for display. With the content composite **180** created and, in some instances, the one or more content items **176** adapted, the one or more content items **176** corresponding to the programming content may be output for display, e.g., during the commercial break, where the content items **176** and particularized content items **177** are selected based at least in part on location metadata mapped to the content items **176** and particularized content items **177** specifying location indicia for the content items **176** and particularized content items **177**. Some sets of rules may specify a threshold distance, and the content items **176** and particularized content items **177** may be selected when a distance between the current geolocation of the endpoint media device **116** and the location indicia for the content items **176** and particularized content items **177** satisfies the distance threshold. Some sets of rules may specify that only certain types of particularized content items **177** may be selected when the distance threshold is not satisfied (e.g., promo codes but not e-coupons).

[0066] Disclosed embodiments may confirm and verify that a content item **176** (in some instances, as modified with one or more particular content items **177**, such as a redeemable content item, matrix code such as a QR code, particularization data, etc.) was transmitted to an endpoint media device **116**. Disclosed embodiments may confirm and verify that the modified or unmodified content item **176** was presented with a display device at the endpoint media device **116** (which display device may be integrated with the endpoint media device **116** or otherwise communicatively coupled to the endpoint media device **116**). Disclosed embodiments may confirm and verify to what extent the modified or unmodified content item **176** was presented (in full or to a lesser extent). Disclosed embodiments may confirm and verify that the modified or unmodified content item **176** was shown to an intended end user if and when utilizing encryption and/or an encryption flag. Disclosed embodiments may confirm and verify detection of one or more operations executed consequent to the presentation (e.g., scanning a matrix code, loading a redeemable content item and/or another particularized content item **177** into mobile app such as a digital wallet of the endpoint media device **116**, utilizing the particularized content items **177** such as to order a product and/or service, etc.) and metrics of the operations (e.g., time of execution). Such confirmations may take the form of return channel notifications from the endpoint device **116** to the system **102**, which may contribute to the observation data **229** and feedback loop features disclosed further herein. In addition to such communications from endpoint devices **116**, the system **102** may receive pushed and/or pulled notifications from one or more service provider systems **103** that indicate when particularized content items **177** have been used by the endpoint devices **116** with respect to the systems **103** (e.g., to a system **103**, uploading at least a portion of a content item **177**; communicating at least a portion of a content item **177** such as code, accessing using a URL of a content item **177**; transferring, presenting, or otherwise providing an image capture of a content item **177**; and/or the like). Such notifications may also contribute to the observation data **229** and feedback loop features.

[0067] FIG. 3 illustrates a functional diagram of an adaptive content composite system **300**, in accordance with disclosed embodiments of the present disclosure. In various embodiments, the content composite system **300** may be included in whole or in part in the content provider system **102-1** and/or an endpoint media device **116**. In some embodiments, the content composite system **300** may be separate from, and provide content to, the content provider system **102-1**. In some embodiments, the content composite system **300** may be included in the end-user system and may be included in the television receiver **116e** and/or one or more of the computing devices **116**. In some embodiments, various features of the content composite system **300** may be distributed

between the television receiver **116e** and upstream of the television receiver **116e**. Likewise, in some embodiments, various features of the content composite system **300** may be distributed between one or more of the computing devices **116** and upstream of the one or more computing devices **116**. While not all components of the adaptive content composite system **300** are shown, the system **200** may include one or a combination of such components.

[0068] As depicted, the content composite system **300** includes a content composite subsystem **111**. The content composite subsystem **111** may include or otherwise correspond to an audiovisual control engine that, as with disclosed embodiments of the other engines, may include instructions retained in processor-readable media and to be executed by one or more processors. The content composite subsystem **111** may be communicatively coupled with interface components and communication channels (e.g., of the television receiver **116e** and/or the computing device **116**, which may take various forms in various embodiments as disclosed herein) configured to receive programming content **202**, which may correspond to televised sporting events, movies, television programs, portions thereof, etc. In various embodiments, the programming content **202** may include audiovisual content broadcast and/or otherwise transmitted by the content provider system **102-1** and/or one or more other service providers **103-1**. The programming content **202** may include various components, including without limitation, one or more video tracks, audio tracks, audio video tracks, metadata tracks, close captioning information, and/or the like. In some embodiments, the content composite system **300** may retain received programming content **202** in content storage **222**. The content storage **222** may include any suitable form of storage media, such as any suitable form disclosed herein.

[0069] The content composite subsystem **111** may be further configured to receive adaptable content items **176** and particularized content items **177**. The content composite subsystem **111** may include a harvesting engine **236** configured to aggregate adaptable content items **176**, particularized content items **177**, and/or programming content **202** in order to facilitate content splicing features disclosed herein. The content composite subsystem **111** may include a matching engine **238**, which, in various embodiments, may be configured to analyze, classify, categorize, characterize, tag, and/or annotate adaptable content items **176**, particularized content items **177**, and/or programming content **202**.

[0070] The content composite subsystem **111** may include a content splicing engine **242**. In some embodiments, the content splicing engine **242** may include a multiplexer. In various embodiments, the multiplexer may create a digital stream of data packets containing the video, audio, and, in some embodiments, the metadata to output the programming content **202**, adaptable content items **176**, and/or the composites **180** created with selected adaptable content items **176**. In various embodiments, the content splicing engine **242** may be implemented at the receiver **116e**, the device **116**, and/or the service provider system **102-1**.

[0071] In some embodiments where the content splicing engine **242** is implemented at the service provider system **102-1**, the multiplexed data stream may be transmitted via the one or more networks **124** for provisioning to computing devices **116** or via a particular transponder stream via a transponder of a satellite for provisioning to receivers **116e**. The multiplexer may create a digital stream of data packets containing the video, audio, and entitlement control messages (ECMs), to be transmitted on the transponder data stream. The data stream, which includes video and/or audio data packets that are not scrambled, may be passed to a scrambling engine, which may use a control word to scramble video or audio present in a data packet. Some audio and video packets may also pass through with no scrambling, if desired by the content provider system **102-1**. A control word generator may generate the control word that is used by a scrambling engine to scramble the video or audio present in the data packet. Control words generated by the control word generator may be passed to a security system, which may be operated by the television service provider or by a third-party security provider. The control words generated by control word generator may be used by security system to generate an ECM. Each ECM may indicate two

control words. The control words indicated may be the current control word being used to scramble video and audio, and the control word that will next be used to scramble video and audio. The security system may output an ECM to the multiplexer for transmission to subscribers' set-top boxes. Each data packet, whether it contains audio, video, an ECM, or some other form of data, may be associated with a particular PID. This PID may be used by the set-top box in combination with a networking information table to determine which television channel the data contained within the data packet corresponds. Accordingly, the transponder data streams may contain scrambled video packet stream and audio packet stream and also an encrypted ECM packet stream which contains the control words necessary to descramble the scrambled video and audio packets.

[0072] In some embodiments, the harvesting engine **236** may be configured to receive, pull, process, buffer, organize, rank, and/or store adaptable content items **176**, particularized content items **177**, and/or programming content **202**. In various embodiments, the content provider system **102-1**, the television receiver **116e**, and/or the computing device **116** may include one or more applications to facilitate the subsystem **111** analyzing and consolidating data feeds and/or event updates received from various data sources **112**. As an example, data feeds and/or event updates may include, but are not limited to, updates (real-time and/or otherwise) and/or continuous data streams received from one or more data sources **112**, which may include real-time events related to promotions, redeemable content items, special offerings, discounts, sports event information, Twitter® feeds, Instagram® posts, Facebook® updates, Amazon® updates, and/or the like.

[0073] As disclosed above, the adaptable content items **176** may be particularized to certain products and/or services. In some embodiments, the adaptable content items **176** may correspond to commercials to be presented during commercial breaks of the programming content **202**. In various embodiments, the content items **176** may include audiovisual content broadcast and/or otherwise transmitted by the content provider system **102-1**. In some embodiments, adaptable content items **176** may be pushed by the content provider system **102-1** to the subsystem **111**. In addition or in alternative, adaptable content items **176** may be pulled by the subsystem **111** (e.g., by the harvesting engine **236**) from the content provider system **102-1**.

[0074] The particularized content items **177** may correspond to content that is particularized to certain types of products and/or services and that is sourced by one or more of the service provider systems **103-1**. In various embodiments, the service provider systems **103-1** may correspond to one or more sources of data, products, and/or services corresponding to the adaptable content items **176**, and particularized content items **177** may correspond to the specific data and/or services sourced by a specific service provider system **103-1** for one or more specific products and/or services. As disclosed above, the adaptable content items **176** and/or the content items **177** may correspond to any one or combination of raw data, unstructured data, structured data, information, and/or content which may include media content, text, documents, files, instructions, code, executable files, images, video, audio, audio video, and/or any other suitable content suitable for embodiments of the present disclosure.

[0075] In various embodiments, sets of one or more adaptable content items **176** and/or sets of one or more content items **177** may be transmitted to the subsystem **111** in batches. For example, sets of one or more adaptable content items **176** and/or sets of one or more content items **177** may be transmitted to the subsystem **111** on a periodic or otherwise scheduled basis. The subsystem **111** may store the adaptable content items **176** locally and, subsequently select one or more of the adaptable content items **176** when needed for presentation during an upcoming break in the programming content **202** and/or when needed for presentation during the programming content **202** based at least in part on the subsystem **111** determining specifications of the programming content **202**, a temporal progression in the programming content **202** (e.g., the fourth quarter, the second round, etc.), a state change in the event (e.g., a score change, one team or competitor leading or falling behind, etc.), and/or the like.

[0076] In various embodiments, sets of one or more adaptable content items **176** and/or sets of one

or more content items **177** may be transmitted to the subsystem **111** on an as-needed basis when the subsystem **111** is receiving programming content **202** corresponding to a certain type (e.g., a televised sporting event), is scheduled to receive such programming content **202**, is predicted to receive programming content **202** based at least in part on a detected viewing pattern of past viewing of previous programming content **202** (e.g., of a certain type of event, at certain times, on certain days, etc.), and/or is predicted to receive programming content **202** based at least in part on a detected pattern of past viewer responses to content composites for previous programming content **202** of that type. Additionally or alternatively, in some embodiments, sets of one or more adaptable content items **176** and/or sets of one or more content items **177** may be selected (e.g., the service provider system **102-1**) as tailored for particular event viewing habits, ordering patterns, and inferred interests of viewers.

[0077] In various embodiments, sets of one or more adaptable content items **176** may be selected (e.g., by the service provider system **102-1**) for particular time periods and may be transmitted to the subsystem **111** with an assignment (e.g., by way of tag data or other metadata) for the designated time period. Additionally or alternatively, in some embodiments, sets of one or more adaptable content items **176** may be selected (e.g., by the service provider system **102-1**) for particular channels and/or television programs and may be transmitted to the subsystem **111** with an assignment (e.g., by way of tag data or other metadata) for the designated channels, shows, movies, and/or television programs. The transmission of the sets of one or more adaptable content items **176** may be in response to the subsystem **111** pulling the sets of one or more adaptable content items **176** from the service provider system **102-1**. For example, the subsystem **111** may pull adaptable content items **176** based at least in part on detecting programming content **202** currently being viewed via a television receiver **116e** or computing device **116**, detecting programming content **202** scheduled to be viewed or recorded, predicting programming content **202** of interest to a viewer based on detected viewing patterns and/or patterns of interacting with content items **176**, **177**, determining upcoming programming content **202** based on electronic programming guide information received, and/or the like.

[0078] In a similar manner, sets of one or more content items **177** may be pulled from or pushed by one or more service provider systems **103-1**, in various embodiments using one or more of the various methods disclosed, to the subsystem **111** directly or indirectly (e.g., by way of the content provider system **102-1**, which may then transmit the content items **177** to the subsystem **111**) for particular time periods, with assignments for designated channels, shows, movies, and/or television programs. For example, in conjunction with the selection of sets of one or more adaptable content items **176**, sets of one or more content items **177** that match the one or more adaptable content items **176** may be pulled from one or more service provider systems **103-1**. In various examples, the matching may be based at least in part on specifications of the event, a temporal progression in the event (e.g., the fourth quarter, the second round, etc.), a state change in the event (e.g., a score change, one team or competitor leading or falling behind, etc.), and/or the like.

[0079] The subsystem **111** may use the rules **218** to adaptively control content composite creation, the delivery of such content, and interactions with such content. The categorization **212** of the harvested regulations and updated regulations may be used to create various sets of rules **218** governing the creation and provisioning of particularized content composites **180**. The various sets of rules **218** may govern the creation and provisioning of particularized content composites **180** as a function of a location of a particular receiver **116e** and/or device **116**. Hence, different sets of rules **218** may apply to different locations. Further, various sets of rules **218** may provide for various types of restrictions and/or specifications on creating and/or provisioning content composites **180**. In addition to geolocation restrictions/specifications, the various types of restrictions and/or specifications may include time restrictions, such as limits on a time of day when content composites **180** may be presented, limits on time in advance particular event (e.g., days, hours, etc.) and/or portion thereof ahead of which content composites **180** may be presented,

and the like. Additionally or alternatively, the various types of restrictions and/or specifications may include restrictions on and/or specifications of types of content (e.g., ratings for different audience designations, content designations, etc.) for which content composites **180** may or may not be presented and the manner in which content composites **180** may be presented for the different types of programs and/or viewers (e.g., adult-directed ads may not be presented during children-directed shows and/or to viewers identified as children). Thus, provisioning of content composites **180** may be further differentiated according to show type and/or viewer type, with time, place, and/or manner restrictions/specifications contingent on show type and/or viewer type. Restrictions on and/or specifications of the manner in which content composites **180** may be presented may include differentiating types of devices (e.g., smart phone versus laptop computer, laptop computer versus television receiver, etc.) which will display the content composites **180**. [0080] To facilitate geo-discrimination to differentiate which sets of rules **218** apply to a given content provisioning instance with respect to a program and which content items **176**, **177** to select and present as a function of the current device **116** location, disclosed embodiments may provide for capturing and analyzing location data **179** for the device **116** to determine a current location of the device **116**. The current location of the device **116** may also be used to identify, by a system **102**, **103** and/or an application of the device **116**, when a content item **177** stored by the device **116** (e.g., in a digital wallet) is applicable based at least in part on location metadata of the content item **177** that specifies a product/service provider location that is within a threshold distance from the current location. The threshold distance may be specified by the location metadata, user preferences, application settings, and/or the system **102**, **103**. In instances where the threshold is satisfied, one or more push notifications may be transmitted from one of the systems **102**, **103** to the endpoint media device **116**; the application of the endpoint media device **116** may be invoked, awakened, opened, otherwise activated; and/or the application may pop up a notification on a display of the endpoint media device **116** to alert the user to the content item **177** and the proximate provider location.

[0081] Location data **179** may also be captured to facilitate geo-sensitive adaptive content splicing adaptive content splicing with respect to content **202** corresponding to a televised event as a function of a location detected for the device **116** that receives the content and is to cause display of content composites **180** in conjunction with the content. In various embodiments, the matching engine **238** may include a location correlation engine that may correlate location data **179** to a set of one or more zip codes (or other postal codes) and a corresponding rule set identifier for a set of one or more rules **218** mapped to the set of one or more zip codes (or other postal codes) via identifiers keyed with one or more tables and/or indexes.

[0082] In various embodiments, location data may be determined by television receivers **116e** and/or devices **116**, and such data may be sent to the system **102-1**. The television receivers **116e** and/or devices **116** may, in some embodiments, have location detection capabilities based at least in part on location data provided by way of device GPS capabilities, Wi-Fi, cellular, other access points, subscriber/account information, and/or the like techniques for determining a current location of the respective receiver **116e** and/or device **116**, and corresponding location data **179** may be transmitted to the system **102-1**. In some embodiments, the system **102-1** may gather the location data **179**. In some embodiments, where the location data **179** does not explicitly indicate a geolocation, the system **102-1** may determine geo-locations by cross-referencing subscriber/account identifiers with stored geolocation data associated with subscribers/accounts.

[0083] Additionally, in some embodiments, the receiver **116e** and/or device **116** may be capable of communicating with a Global Positioning System (GPS) in order to determine to location of the respective receiver **116e** and/or device **116**. The antenna may be a GPS receiver or otherwise include a GPS receiver. In various embodiments, communication with the receiver **116e** and/or device **116** may be conducted with a single antenna configured for multiple purposes (e.g., cellular, transactions, GPS, etc.), or with further interfaces (e.g., three, four, or more separate interfaces). In

some embodiments, an application installed on the receiver **116e** and/or device **116** may cooperate with the system **102-1** to facilitate tracking of locations of the receiver **116e** and/or device **116**. For example, the receiver **116e** and/or device **116** may transmit location data **179** to any suitable backend system component. The location data **179** may be a combination of data based on one or a combination of GPS, Wi-Fi, cellular, device sensor(s) such as a barometric sensor or accelerometer, RFID device signals, and/or other techniques for determining a current location of the receiver **116e** and/or device **116**.

[0084] The receiver **116e** and/or device **116** may access the one or more networks **120** through one or more wireless links to one or more access points. The access points may be of any suitable type or types. For example, an access point may be a cellular base station, an access point for wireless local area network (e.g., a Wi-Fi access point), an access point for wireless personal area network (e.g., a Bluetooth access point), etc. The access point may connect the receiver **116e** and/or device **116** to the one or more networks **120**, which may include the Internet, an intranet, a local area network, a public switched telephone network (PSTN), private communication networks, etc. In some embodiments, access point(s) may be used in obtaining location data **179** for the receiver **116e** and/or device **116**.

[0085] FIG. **4** is a simplified illustration of a composite build engine **240**, in accordance with disclosed embodiments of the present disclosure. In various embodiments, the composite build engine **240** may be included in the subsystem **111** or may be separate from the subsystem **111**. The composite build engine **240** may, in some embodiments, be included in the content provider system **102-1**. Having processed an adaptable content item **176**, the subsystem **111** may create one or more content composites **180** that may include the adaptable content item **176**.

[0086] To create the content composites **180**, disclosed embodiments may provide the content item **176** with containerization objects **182** that each containerize a set of data as a persistent object in time. Each containerization object **182** may be configured to function in a broadcast environment while facilitating the various features disclosed herein. For example, among other things, the containerization object **182** may create the ability for the disclosed deeper integration with endpoint devices **116** in a broadcast environment. With the containerization object **182**, the content composites **180** may allow the content item **176** to be treated as an object wrapped with an identity and with one or more layers of encryption. As disclosed herein, the one or more layers of encryption provided with various embodiments may correspond to encryption at one or more software layers, as distinguishable from hardware encryption of a device **116**. The various embodiments of one or more layers of encryption may allow for encryption of one or a combination of return channel communications, data regarding endpoint device **116** operations that contribute to observation data **229**, content items **176**, content items **177**, composites **180**, and/or components thereof, which may particularly include encryption of personalization and transactional data, which may provide for DRM, and which may ensure end user privacy.

[0087] The composite build engine **240** may configure the containerization object **182** to include a container flag **184**. The container flag **184** may include one or more parameters that indicate one or more containerization specifications **186**. The container flag **184** may be thin and may indicate other components packetized in the containerization object **182**. For example, in various embodiments, container flag **184** may include indicia of one or a combination of: an identifier of the content item **176** in the container, boundaries of the set of one or more audio and/or video packets that form the content item **176**, access and reference to one or more other containerization specifications **186**, access and reference to other metadata **188**, and/or the like. The content item identifier may correspond to a field with parameters that identifies the content item **176**.

[0088] Further, the composite build engine **240** may configure the containerization object **182** to include the containerization specifications **186** to facilitate performance of a set of one or more operations by the one or more endpoint media devices **116** with respect to the content item **176** consequent to the one or more endpoint devices **116** receiving the content composite **180**. In

various embodiments, the containerization specifications **186** may include one or a combination of instructions, metadata, personalization content or instructions to fetch personalization content, and/or the like to specify and facilitate performance of the set of one or more operations by an endpoint media device **116**. In some embodiments, the containerization specifications **186** may include a particularized content item **177** or instructions to fetch a particularized content item **177**. [0089] Accordingly, the content composite **180** may include the content item **176** and the containerization object **182**. Further, in various embodiments, the content composite **180** may include a particularized content item **177** at the time the content composite **180** is transmitted to one or more endpoint media devices **116**, separate from or grafted into the content item **176** such that the content item **176** is an adapted content item **176** adapted with the particularized content item **177**. In some embodiments, the content composite **180** may not include a particularized content item **177** at the time the content composite **180** is transmitted to one or more endpoint media devices **116**. In such instances, the particularized content item **177** may be fetched per the containerization specifications **186** from the system **102, 200**, another data source **103**, or from storage of the endpoint media device **116**, and may be used by an endpoint media device **116** to adapt the content item **176**. The containerization specifications **186** may include instructions and build specifications according to which the endpoint media device **116** may merge the pulled/retrieved particularized content item **177** with the content item **176**. As part of the instructions and build specifications, the containerization specifications **186** may specify that the particularized content item **177** (e.g., a particular redeemable content item, matrix code such as a QR code, trailer, movie content, and/or the like) contain one or more date and/or time attributes (e.g., a time stamp) indicate of one or a combination of when the item was created, when the item is to be output by the endpoint media device **116** for display, when the item is stored by the endpoint media device **116** (e.g., in a digital wallet), and/or the like. In some embodiments, the one or more date and/or time attributes may be stored with the metadata **188**.

[0090] In various embodiments, the content composite **180** may further include personalization content personalized to the end user of the endpoint media device **116** at the time the content composite **180** is transmitted to one or more endpoint media devices **116**, separate from or grafted into the content item **176** such that the content item **176** is an adapted content item **176** adapted with the personalization content. In some embodiments, the content composite **180** may not include personalization content at the time the content composite **180** is transmitted to one or more endpoint media devices **116**. In such instances, the personalization content may be fetched per the containerization specifications **186** from the system **102, 200**, another data source **103**, or from storage of the endpoint media device **116**, and may be used by an endpoint media device **116** to adapt the content item **176** according to instructions and build specifications of the containerization specifications **186**.

[0091] The subsystem **111** may transmit the content composite **180** to one or more endpoint media devices **116**, and, in some embodiments, may broadcast the content composite **180** to a plurality of endpoint media devices **116**. The subsystem **111** may transmit the content composite **180** in accordance with composite transmission specifications. The composite transmission specifications may at least partially specify transmission parameters that govern transmission of the containerization object **182** in a data stream with the set of one or more audio and/or video packets in audio and/or video streams corresponding to the content item **176**.

[0092] The content item **176** may correspond to a specific unit within the content stream. The specific unit in the content stream may correspond to a section of the video stream that includes the set of one or more audio and/or video packets for the content item **176**. The composite transmission specifications may specify how the containerization object **182** should be transmitted in the data stream with the content item **176**, how many instances of the containerization object **182** should be created and transmitted, how should some instances of the containerization object **182** be time/place shifted in advance of the packets corresponding to the content item **176**, and/or the like.

Thus, the composite transmission specifications may provide for one or more instances of the containerization object **182** particularized for the individual content item **176** to be transmitted within the data stream of the content stream, with the content item **176** transmitted in the audio and/or video stream(s). Accordingly, a number of instances of the containerization object **182** with the content item identifier, as specified by the composite transmission specifications, may be embedded in a section of the data stream that indicates the content item **176**. Not only may the containerization object **182** with the container flag **184** be carried as a data stream with the audio video content stream, flagging the content item **176**, it may also be replicated and encoded in a carousel manner per the composite transmission specifications to facilitate pick-up mid-stream of the content item **176**, and/or in advance of the content item **176** in the stream to facilitate forward identification of the upcoming content item **176**.

[0093] The container flag **184** and its indicia may be encrypted and transmitted to the endpoint media device(s) **116** in the encrypted state with the content composite **180**. Additionally or alternatively, the containerization specifications **186** may be encrypted and transmitted to the endpoint media device(s) **116** in the encrypted state with the content composite **180**. Accordingly, disclosed embodiments may add an encrypted container flag **184** to the content item **176**.

[0094] In various embodiments, the encrypted container flag **184** may govern access by the endpoint media device **116** to one or more other components of the content composite **180**. Consequent to delivery of the content composite **180** to the endpoint media device **116**, the endpoint media device **116** may decrypt the encrypted container flag **184**. Once the endpoint media device **116** decrypts the container flag **184**, the endpoint media device **116** may have access to, for example, the metadata of the content composite **180**, such as the instructions of the containerization specifications **186**, other containerization specifications **186**, and/or the other metadata **188**.

[0095] The container flag **184** may include indicia that identifies the state and extent of one or more layers of encryption of the content composite **180**. One or more of the components of the content composite **180** may be encrypted. The encryption may include a lightweight, point-to-point encryption for specific components of the content composite **180**, which may be advantageous to avoid bogging down processing in view of relatively heavier processing needs for video of content items **176** and generally shorter durations of content items **176**.

[0096] The indicia may flag one or more objects and/or containers for the specific unit(s) within the content stream without the entire data stream being encrypted. The subsystem **111** may all or part of content composite **180** contingent on the extent of the personalization of the content composite **180**. For example, when the content composite **180** is transmitted with personalization content, the personalization content may be encrypted. As one example out of many possibilities, when a content item **176** is adapted with a list of items to acquire prepared for an identified viewer, at least the portion of data corresponding to the list may be encrypted, whereas the balance of the content item **176** that is not personalized may not be encrypted. Accordingly, a partially customized content composite **180** and/or content item **176** may only be partially encrypted. However, a highly customized content composite **180** and/or content item **176** may be entirely or substantially entirely encrypted, commensurate with the extent of the customization for the identified viewer. For example, if the content item **176** is due to an identified viewer selection (say, a prior procurement, such as the viewer having obtained access permissions to a movie or other particular content), then, after scraping an ID that a viewer has allowed such, the content composite **180** and/or content item **176** (which, for example, may be directed to opening up 1-to-1 connection to access a digital ticket, access to a digital copy of the content, bonus content, a content item that requires tracking such as a redeemable content item for a pay-per-view, etc.) may be entirely or substantially entirely encrypted. Such content may be highly customized and may include watermarking. One or more particularized content items **177**, for example, may include watermarks for merging with content items **176** as disclosed herein.

[0097] The content composites **180** may provide for advantages with greater layers within a content

stream more based around computer language. In some embodiments, various options for content items **176** may be broadcasted, with only a subset of the content items **176** being presented by particular endpoint media devices **116**. The indicia of the container flags **184** of the content composites **180** may allow for filtering the content composites **180** according to attributes of the endpoint media device **116** and/or the endpoint viewer so the matching content composite **180** is presented to the identified viewer/viewer type, pursuant to the differentiated interaction with mobile app, etc. For example, flag indicia may include layer flag indicia that indicates this content item is for unlocked devices or only locked devices. One layer may allow for identifying different types of the endpoint media devices **116** that differ in capabilities, which, in some embodiments, may be determining based at least in part on pulling information (e.g., device specifications) from the particular endpoint media device **116**. Such device type identification may further allow for selectively providing a type of endpoint media device **116** with different types of content items **176** and different content attributes as a function of the device type. For example, such selective provisioning may include filtering content items **176** based at least in part on the differences in frame rate of the content items **176** as a function of the endpoint media device type and/or capabilities. Different content items **176** may be filtered for different endpoint media device **116** (e.g., content items **176** with frame rates associated with fast-changing content may not be mapped to devices with lesser capabilities). As another example, such selective provisioning may include filtering content items **176** based at least in part on the differences in how the content items **176** are compressed as a function of the endpoint media device type and/or capabilities.

[0098] One layer may allow for determining endpoint media device **116** authentication. The endpoint media device **116** authentication may be dependent on discovery processes that the determine what is on the device that can be used to sufficiently authenticate the endpoint media device **116**. For example, the discovery processes may determine and utilize a SIM card of a mobile device, television receiver with a smartcard, and/or similar identification that can be used to authenticate to set up account. Having determined that the endpoint media device **116** and/or the endpoint has potential to have an account, another layer may allow for search and authentication operations to try to find an account associated with the endpoint media device **116** and/or the endpoint and then authenticate against services related as part of a subscriber account.

[0099] Another layer may allow for filtering one or a combination of the content composite **180**, the content item **176**, the particularized content item **177**, and/or the personalization content based at least in part on the authentication and identification of the endpoint viewer. For example, such filtering may include selecting and presenting the content composite **180**, the content item **176**, the particularized content item **177**, and/or the personalization content that correspond to one or more demographics of the identified viewer (e.g., age, marital status, children, pets, renter, homeowner, etc.) and/or viewer type (e.g., flag indicia of NC-17, MA, or another rating so an endpoint device with parental specifications would be provided with appropriate content items). As another example, such filtering may include selecting and presenting the content composite **180**, the content item **176**, the particularized content item **177**, and/or the personalization content that correspond to identified past actions mapped to the endpoint and/or endpoint media device **116**. This can result in such differences as presenting content that is directed to, say, “get video subscription service X” versus “because you have video subscription service X, . . . Y.” Another layer may allow for creating a backchannel to facilitate communications, ordering, secure video delivery, and/or the like disclosed herein.

[0100] In some embodiments, the container flag **184** and/or containerization specifications **186** may prompt the endpoint media device **116** to execute the instructions to perform at least one operation of the set of one or more operations facilitated by the containerization object **182**. In some embodiments, APIs may be used to instruct the endpoint media device **116** as to what to do with the container flag **184** and/or containerization specifications **186**. In some embodiments, the container flag **184** and/or containerization specifications **186** may allow for invoking, waking up,

opening, and/or otherwise activating an application of the endpoint media device **116** responsive to the decryption of the container flag **184** and/or containerization specifications **186**, in some instances, when the application is offline and/or otherwise not online with respect to the system **102, 200**, and/or another system **103**.

[0101] For example, the container flag **184** and/or containerization specifications **186** may include a read flag that triggers one or more return channel communications. The corresponding instructions may instruct the endpoint media device **116** to report to the system **102, 200**, and/or another system **103** with one or more return channel communications one or a combination of: that the content item **176** was received by the endpoint media device **116**; that the content item **176** was presented with a display device at the endpoint media device **116**; to what extent the content item **176** was presented (in full or to what lesser extent in percentage or another suitable metric); that the content item **176** was shown to an intended endpoint user, detection of one or more operations executed consequent to the presentation (e.g., scanning a matrix code, loading a redeemable content item and/or particularization content into a mobile app such as a digital wallet of the endpoint media device **116**, utilizing the particular content items **177** such as to order a product and/or service, etc.) and metrics of the operations (e.g., time of execution); and/or the like. Further, the return channel communications may include one or a combination of: indicia of a particular endpoint user and/or type of endpoint user using the endpoint media device **116** within a time period before and/or when at least part of a content item **176** is/was output for display; indicia of endpoint media device **116** capabilities (e.g., device specifications); indicia of authentication bases such as a SIM card of a mobile device, television receiver with a smartcard, and/or similar identification that can be used to authenticate to set up account; and/or the like.

[0102] The return channel communications may contribute to the observation data **229** and feedback loop features disclosed further herein. The containerization specifications **186** may instruct the endpoint media device **116** to report back upon occurrence of each state change and/or to report back per a reporting schedule (e.g., just prior to closure of an application, at end of day, at the end of another reporting period, etc.). In various embodiments, the container flag **184** and/or containerization specifications **186** may include one or more encrypted messages, hashes, and/or the like that each indicate one or more of the above reporting events. Accordingly, the instructions may specify that each return channel notification include a corresponding encrypted message, hash, code, and/or the like, which the system **102, 200**, and/or another system **103** may process to verify the respective reporting event and metrics thereof.

[0103] In instances where the system **102** may receive pushed and/or pulled notifications from one or more service provider systems **103** that indicate when particularized content items **177** have been used by the endpoint devices **116** with respect to the systems **103** (e.g., to a system **103**, uploading at least a portion of a content item **177**; communicating at least a portion of a content item **177** such as code, accessing using a URL of a content item **177**; transferring, presenting, or otherwise providing an image capture of a content item **177**; and/or the like), the notifications may contain indicia of one or a combination of the content item **177**, the endpoint device **116**, the user associated with the endpoint device **116**, a location associated with the use of the content item **177**, date and/or time associated with the use of the content item **177**, and/or the like. Having received such indicia from a service provider system **103**, the subsystem **111** (e.g., the matching engine **238**) may correlate the indicia to records stored in a database **222** with identifiers of one or a combination of the content item **177**, the endpoint device **116**, the user and/or account associated with the endpoint device **116**, a location associated with the user, account, and/or endpoint device **116**, and/or date and/or time associated with the delivery and/or presentation of the content item **177**. The identified correlations may contribute to the observation data **229** and feedback loop features.

[0104] In some embodiments, where the content item **176** is not already adapted with the particularized content item **177**, the set of one or more operations may include identifying the

particularized content item **177** and adapting the content item **176** with the particularized content item **177**. When the particularized content item **177** is not included in the content composite **180** when the content composite **180** is received by the endpoint media device **116**, the set of one or more operations may include pulling the particularized content item **177** from the system **102, 200**, another data source **103** per the containerization specifications **186**. In some embodiments, the particularized content item(s) **177** may be transmitted separately from the system **102, 200** and/or another data source **103** prior to the delivery of the content composite **180** such that the endpoint media device **116** stores the particularized content item(s) **177** locally. In such instances, the set of one or more operations may include retrieving the matching particularized content item **177** from storage of the endpoint media device **116** per the containerization specifications **186**. Further, in some embodiments, when the particularized content item **177** is not transmitted with the content item **176**, the containerization specifications **186** may specify first checking local storage of the endpoint media device **116** for the matching particularized content item **177** and only pulling the particularized content item **177** from the system **102, 200** and/or another data source **103** when the particularized content item **177** is not available from the local storage.

[0105] Similarly, the set of one or more operations may include identifying the personalized content that is particular to one or more viewers and adapting the content item **176** with the personalized content. As disclosed herein, in some embodiments, the particularized content item **177** may include personalized content. In such instances, the adapting of the content item **176** with the particularized content item **177** may include adapting of the content item **176** with personalized content. Additionally or alternatively, personalized content may be separate from the particularized content item **177**. Hence, where the content item **176** is not already adapted with the personalized content, the personalized content may be included in the content composite **180** when the content composite **180** is received by the endpoint media device **116**. When the personalized content is not included in the content composite **180** when the content composite **180** is received by the endpoint media device **116**, the set of one or more operations may include retrieving/pulling the personalized content from one or a combination of local storage of the endpoint media device **116**, the system **102, 200**, and/or another data source **103** per the containerization specifications **186**. The containerization specifications **186** may specify first checking local storage of the endpoint media device **116** for the matching personalized content and then pulling the personalized content from the system **102, 200** and/or another data source **103** when at least some of the personalized content is not available (or when sufficient personalized content of one or more specified types is not available) from the local storage or when supplemental personalized content is identified as requested per the containerization specifications **186**.

[0106] To facilitate the content composite **180**, the composite build engine **240** may include a metadata handler **208** that may generate metadata (e.g., one or more tags) corresponding to identifiers, attributes, characteristics, and/or categories of programming content **202**, adaptable content items **176**, and/or particularized content items **177**. In some embodiments, the composite build engine **240** may assign packet identifiers to identify data of the content that is to be transmitted as part of a data stream to an endpoint media device **116** and that is to be associated with one or more tags. Data transmitted as part of a data stream to an endpoint media device **116** may be packetized and assigned packet identifiers. A particular packet identifier may be associated with data packets related to tags for particular segments of programming content **202**, adaptable content items **176**, and/or particularized content items **177**.

[0107] The content matching engine **238** may identify a televised event in the programming content **202** and may identify one or more corresponding identifiers, attributes, characteristics, and/or categories of programming content **202**, adaptable content items **176**, and/or particularized content items **177** of one or more adaptable content items **176** and/or one or more particularized content items **177**. Based at least in part on such identification, the composite build engine **240** may create metadata, which, in some embodiments, may correspond to tag data.

[0108] Tag data may include an indication of a period of time (or other measure of time, e.g., a number of frames), a start frame, an end frame, and/or the like. Tag data may include or otherwise be associated with a tag identifier and may include event, attribute, characteristic, and/or category identifiers. For example, the metadata for the televised event may identify the particular event. The metadata may further identify one or more attributes of the particular event (e.g., any suitable identifier for the participating entities, the location of an event, and/or the like). In some embodiments, at least a portion of the metadata augmentation may be performed at the content provider system **102-1** such that one or more tagged composite components may be provided to an endpoint media device **116**. Subsequently, the endpoint media device **116** may identify composite components, for example, by processing the metadata.

[0109] The metadata for adaptable content items **176** may, for example, identify the adaptable content items **176** as being adaptable with any suitable identifier, such as a flag, field value, etc. Additionally or alternatively, the metadata for the adaptable content items **176** may identify that the adaptable content items **176** are designated for a certain event or category of events with any suitable identifier. The metadata for the adaptable content items **176** may further identify one or more attributes of the particular event (e.g., any suitable identifier for associated entities, location, a temporal attribute such as a time of an event, and/or the like). Additionally or alternatively, the metadata for the adaptable content items **176** may identify transition points, hooks, frames, windows, other portions designated for overlays, and/or the like for merging with content items **177** such that content from the content items **177** is merged at the transition points, hooks, frames, windows, other portions designated for overlays, and/or the like.

[0110] In some embodiments, metadata-augmented adaptable content items **176** may be provided by the service provider system **102-1** to the endpoint media devices **116**, after which the endpoint media devices **116**, each having at least a portion of the content composite subsystems **111**, may process and use the metadata to facilitate matching adaptable content items **176** with corresponding programming content **202**. Likewise, the endpoint media devices **116** may process and use the metadata to facilitate matching adaptable content items **176** with corresponding content items **177**. Thus, the metadata may facilitate the endpoint media devices **116** appropriately providing corresponding content composites **180** for display with appropriate placement with respect to televised events, shows, etc. at commercial breaks and/or during presentation of the televised events, shows, etc.

[0111] In a similar manner, metadata for particularized content items **177** may, for example, identify an identifier of the particular event, show, etc. The metadata for the content items **177** may further identify fields and content for one or more attributes, such as URLs and hyperlinks to platforms and websites and/or sites for further information, ordering, and/or the like. In some embodiments, at least a portion of the metadata augmentation may be performed at the service provider system **102-1** and/or the service provider system **103-1** with respect to the particularized content items **177**. Subsequently, the content composite subsystem(s) **111** and/or endpoint media devices **116** may process and use the metadata to facilitate matching adaptable content items **176** with corresponding content items **177**. In some embodiments, the devices **116**, having at least a portion of the content composite subsystem **111**, may process the particularized content items **177** in the form in which they are received (e.g., directly from a service provider **103-1**) and, based on such processing, may match content items **176** with corresponding content items **177**.

[0112] Referring again more particularly to FIG. 3, the matching engine **238** may be configured to match content items **176** to segments of programming content **202** based at least in part on metadata at a service provider system **102-1** side or at a device **116**, in accordance with various embodiments. For example, metadata may be extracted when or before a given segment of programming content **202** is to be output for display and before a transition point. In some embodiments, the matching engine **238** may read the metadata mapped to the segment and perform a search of the repositories **222** for one or more content items **176** that have metadata matching the

extracted metadata with respect to one or more of event identification, event category identification, and/or temporal identification, with the highest preference given to the content item **176** that has metadata most closely matching the metadata of the previous segment. Alternatively, the matching engine **238** may read the metadata mapped to the segment and pull one or more adaptable content items **176** from the service provider system **102-1**. In so doing, the subsystem **111** may transmit at least a portion of the metadata of the programming content **202** to the service provider system **102-1** in order to facilitate matching the extracted metadata with one or more content items **176** with respect to one or more of event identification, event category identification, and/or temporal identification. Some embodiments may include the subsystem **111** configured to perform a search of the repositories **222** for one or more content items **176** that have metadata matching the extracted metadata in addition to pulling one or more adaptable content items **176** from the service provider system **102-1**. For example, the subsystem **111** may first perform a search of the repositories **222** for any matching content items **176** and then only pull one or more content items **176** from the service provider system **102-1** when no adaptable content items **176** are found in the search of the repositories **222** that match the extracted metadata with a sufficient match score that indicates a level of correlation satisfying a correlation threshold. Accordingly, certain embodiments may facilitate matching of content items **176** to segments of programming content **202** based at least in part on metadata.

[0113] In a similar manner, the matching engine **238** may be configured to match particularized content items **177** to one or more of content items **176**, segments of programming content **202**, and/or provider systems **103** at a service provider system **102-1** side or at a device **116**, in accordance with various embodiments. For example, in some embodiments, the matching of one or more particularized content items **177** may be based at least in part on metadata. The metadata may be extracted and read when or before a given content item **176** and/or a given segment of programming content **202-1** is to be output for display, and, before a transition point, may be mapped to the content item **176** or the segment. In some embodiments, the matching of one or more particularized content items **177** may be based at least in part on identified characteristics of a given content item **176** and/or a given segment of programming content **202**. The matching engine **238** may take the identified characteristics of a given content item **176** and/or a given segment of programming content **202** as cues to retrieve one or more content items **177** and/or one or more corresponding adaptable content items **176** and for the content splicing engine **242** to output one or more content composites **180** for presentation. The timing of the presentation may be after the segment of programming content **202** (e.g., at a commercial break), during the segment of programming content **202** (e.g., as an overlay, in a side window/frame, etc.) to match the identified characteristics of the programming content **202**, or after the presentation of a first composite **180** (e.g., when one or more content items **177** and/or one or more corresponding adaptable content items **176** are selected for presentation as a subsequent composite **180** or for separate provisioning to the device **116** in accordance with various embodiments disclosed herein such as transferring to an account accessible by a user of the endpoint media device **116**).

[0114] In various embodiments, the characteristic identification may include one or a combination of text recognition, image recognition, and/or audio recognition. For example, the matching engine **238** may recognize text from the metadata of content items **176** and/or programming content **202**. As some possible examples out of many possibilities, the matching engine **238** may recognize indicia of uniform resource identifiers (e.g., URLs), identifiers of provider systems **103**, and/or the like from the metadata (which may include closed captioning information) that the matching engine **238** may map to provider systems **103**. To facilitate image recognition, some embodiments of the content composite subsystem **111** (e.g., by way of the matching engine **238**) may be configured to detect one or more color characteristics in content items **176** and/or programming content **202**, which may include any suitable color characteristic that may be measured to recognize alpha and/or numerical portions of the images and/or objects in the images. From such portions and/or objects,

the matching engine **238** may recognize uniform resource identifiers (e.g., URLs, web addresses, etc.), phone numbers, identifiers of provider systems **103**, logos, products, graphics displayed with streaming tickers or overlays typically positioned and/or scrolling across a portion of the display area, and/or the like which the matching engine **238** may map to provider systems **103**. The matching engine **238** may include an image analyzer and handling module to facilitate that detection. By way of example, the matching engine **238** may detect one or more color characteristics in programming content **202** by way of any one or combination of pixel identification, detecting color component values, detecting color codes, and/or the like.

[0115] To facilitate audio recognition, the content composite subsystem **111** (e.g., by way of the matching engine **238**) may be configured to detect one or more audio characteristics in content items **176** and/or programming content **202**. The matching engine **238** may include an audio analyzer and handling module to facilitate that detection. By way of example, the matching engine **238** may detect one or more audio characteristics in content items **176** and/or programming content **202** by way of any one or combination of analyzing audio, applying voice recognition, acoustic spectrum analysis, analyzing the audio tracks metadata track, comparison to acoustic profiles for types of content, and/or the like. Some embodiments of the content composite subsystem **111** may store acoustic profiles mapped to types of content items **176** and/or programming content **202** and corresponding provider systems **103** in the repository **222**. Each acoustic profile may specify one or more selected values of acoustic metrics as distinctive markings and/or acoustic categories **214** (e.g., songs, musical scores, jingles, voice characteristics, and/or the like) as characteristics of the types of content items **176** and/or programming content **202** and corresponding provider systems **103**.

[0116] As another example, the subsystem **111** may recognize one or more keywords from dialogue that the matching engine **238** may map to provider systems **103**. The matching engine **238** may identify one or more keywords and/or expressions in the dialogue as a dialogue impression for the purposes of characterizing the sample and identifying content items **176** and/or programming content **202** and corresponding provider systems **103**. The matching engine **238** may compile the keywords and/or expressions of the sample and retain the keywords and/or expressions and corresponding provider systems **103** in the dialogue impression. In some cases, the matching engine **238** may correlate the dialogue impression to one or more dialogue categories **212** for similar dialogue impressions and corresponding provider systems **103**. In various embodiments, the correlation may be based at least in part on matching selected keywords and/or expressions to identical and/or similar keywords and/or expressions specified for certain dialogue categories **212** and corresponding provider systems **103**. The dialogue categories **212** may include categorizations of concept, keyword, expression, and/or the like mapped to corresponding provider systems **103**. Based at least in part on the dialogue impression, the matching engine **238** may create a dialogue profile for content items **176** and/or programming content **202** and corresponding provider systems **103**. The dialogue profile may be retained in any suitable form, such as a file, a list, etc. The content composite subsystem **111** may store dialogue profiles mapped to content items **176** and/or programming content **202** and corresponding provider systems **103** in the repository **222**. Each dialogue profile may specify one or more selected keywords and/or expressions as distinctive markings and/or dialogue categories **212** as characteristics of the content items **176** and/or programming content **202** and corresponding provider systems **103**.

[0117] To facilitate the matching, the matching engine **238** may perform correlation based at least in part on the text recognition, image recognition, and/or audio recognition and text, image, and/or audio categories **212**. By way of example, the correlation rules **218** may include correlation criteria that could include keywords identified by any one or combination of words, word stems, phrase, word groupings, and/or like keyword information. The correlation criteria could include weightings assigned to dialogue specifications. Hence, within each dialogue bucket, a keyword could be assigned a weight according to its significance. More significant keywords could be assigned a

greater weight than stop words. Such buckets could be implemented in any suitable manner, including lists, tables, matrices, and/or the like. And within a bucket, characteristics and/or keywords could be organized in a rank order and/or any hierarchical structure according to weight. Some embodiments may have characteristics and/or keywords organized according to decision tree, with contingencies so that only certain combinations of characteristics and/or keywords may be considered. For example, certain characteristics and/or keywords could only have significance if used in conjunction with other characteristics and/or keywords, and/or not in conjunction with others. Similar correlation criteria may be used for acoustic impressions.

[0118] In some embodiments, the matching engine **238** may employ a scoring system to quantify correlations with a numerical expression, for example, a match score, with higher scores being assigned to higher correlations. Higher scores may be assigned for greater extents of matching. By way of example with respect to dialogue, a match of three dialogue cues or dialogue categories may be assigned a higher score than a match of only one top dialogue cue and/or dialogue category. As another example, an exact match of words, expressions, and/or dialogue categories may be assigned a higher score than a complimentary match (e.g., where absent an exact match, a word, expression, and/or dialogue category is defined as a complement to another a word, expression, and/or dialogue category).

[0119] Some embodiments may sample only portions of content items **176** and/or programming content **202** to derive the characteristics of the content items **176** and/or programming content **202**. For example, the sampling may be relegated to only the last X seconds of audio and/or video of a content item **176**. As another example, the sampling may be relegated to only I-frames of a content item **176**. Accordingly, the sampling may facilitate composite **180** creation and presentation so that the composite **180** may be dynamically inserted in the content stream or otherwise provisioned within a short time and with minimized processing resources.

[0120] In some embodiments, with a system **103** identified based at least in part on identified the metadata and/or characteristics, the matching engine **238** may and perform a search of the repositories **222** for one or more content items **177** that have metadata that maps to provider systems **103**. In such cases where the repositories **222** are searched for one or more content items **177**, the one or more content items **177** may have been previously transmitted to the subsystem **111** directly from one or more service provider systems **103-1** or indirectly from one or more service provider systems **103-1** by way of the service provider system **102-1**. Such content items **177** may include temporal identification indicating a time for which content corresponding to the content item **177** remains in effect. For example, each content item **177** may comprise content for which an expiration is specified (e.g., with one or more of time, date, duration, etc.). Accordingly, the matching engine **238** may perform a staleness check by examining the metadata of any such content items **177** retrieved from the repositories **222** to determine whether the content items **177** have expired with respect to the current time and date.

[0121] Additionally or alternatively, the subsystem **111** may pull one or more content items **177** from the service provider system **102-1** and/or one or more service provider systems **103-1**. In so doing, the subsystem **111** may transmit at least a portion of the metadata of the programming content **202** to the service provider system **102-1** and/or one or more service provider systems **103-1** in order to facilitate matching the extracted metadata with one or more content items **177** with respect to one or more of event identification, event category identification, and/or temporal identification. Consequently, the service provider system **102-1** and/or one or more service provider systems **103-1** may transmit one or more matching content items **177** to the subsystem **111**. Additionally or alternatively, in some embodiments, the subsystem **111** first obtain one or more matching adaptable content items **176**, then read metadata from the one or more matching adaptable content items **176**, and transmit at least a portion of the metadata to the service provider system **102-1** and/or one or more service provider systems **103-1** in order to facilitate matching the metadata with one or more content items **177**.

[0122] Some embodiments may include the subsystem **111** being configured to perform a search of the repositories **222** for one or more content items **177** that have metadata matching the metadata of one or both of adaptable content items **176** and the segment of programming content **202** in addition to pulling one or more content items **177** from the service provider systems **102-1** and/or **103-1**. For example, the subsystem **111** may first perform a search of the repositories **222** for any matching content items **177** and then only pull one or more content items **177** from the service provider systems **102-1** and/or **103-1** when no non-expired content items **177** are found in the search of the repositories **222** that match the metadata with a sufficient match score that indicates a level of correlation satisfying a correlation threshold. In some embodiments, the subsystem **111** may first attempt to pull one or more content items **177** from the service provider system **102-1** and, in the case that no matching non-expired content items **177** are successfully pulled from the service provider system **102-1** within a time threshold after the initial request, then pull one or more content items **177** from one or more service provider systems **103-1**. Likewise, the subsystem **111** may attempt to pull one or more content items **177** from a first set of one or more service provider systems **103-1** and, in the case that no matching content items **177** are successfully pulled from the first set of one or more service provider system **103-1** within a time threshold after the initial request, then pull one or more content items **177** from a second set of one or more service provider systems **103-1**. In some embodiments, the subsystem **111** may implement all three of the aforementioned stages of pulling content items **177** from the service provider system **102-1**, then the first set of one or more service provider systems **103-1**, and then a second set of one or more service provider systems **103-1**. In such embodiments, the time thresholds may be different for each stage, e.g., decreasing or increasing in time. Additionally, the size of the selected sets of service provider systems **103-1** may be different for each stage, e.g., decreasing or increasing in size. Accordingly, various embodiments may facilitate matching of particularized content items **177** to segments of programming content **202** and/or adaptable content items **176** based at least in part on metadata.

[0123] In some embodiments, the subsystem **111** may receive pushed and/or pulled notifications from one or more service provider systems **103** that indicate when content items **176** have been used by the endpoint devices **116** with respect to the systems **103**. Such notifications may include indicia of events such as: uploading at least a portion of a content item **176**; communicating at least a portion of a content item **176** such as a code, accessing using a URL of a content item **176**; transferring, presenting, or otherwise providing an image capture of a content item **176**; and/or the like). However, when such a notification does not identify the particular endpoint device **116** or the user thereof, the subsystem **111** (e.g., the matching engine **238**) may correlate the notification to a particular endpoint device **116** or user. Based at least in part on correlation rules **218**, the matching engine **238** may match an identifier of the content item **176** received from the system **103** (e.g., the notification may include an identifier of the content item **176**, along with indicia of the corresponding event) to stored records for the identified content item **176**. The stored records for the identified content item **176** may be included in observation data **229** disclosed herein. For example, the matching engine **238** may match the identifier of the content item **176** to records of temporal data. The temporal data may, for example, include one or more date and/or time attributes (e.g., a time stamp) indicative of when the identified content item **176** was broadcasted or otherwise transmitted. The matching may be further based at least in part on location indicia if the notification from the system **103** includes indicia of a location of the event involving the content item **176** (e.g., indicia of a geolocation of site corresponding to the system **103**, IP address of the endpoint device **116**, type of device **116**, and/or the like). As disclosed herein, the subsystem **111** may track delivery locations to which content items **176** are transmitted. The matching engine **238** may match the identifier of the content item **176** to records of location data corresponding to the tracked delivery locations.

[0124] The correlation may include matching the identifier of the content item **176** and potentially

the location indicia with the stored temporal data and potentially the stored location data to identify one or more matching endpoint devices **116** and/or users, with the highest preference given to the endpoint device **116** and/or user mapped to the most closely matching temporal and/or location data. In instances where a set of matching endpoint devices **116** and/or users identified, the set may be ranked according to correlation such that the strongest matching endpoint device **116** and/or user is ranked highest. In various embodiments, one or more of the matching endpoint devices **116** and/or users identified may be selected for composite **180** and/or particularized content item **176** provisioning according to the ranked order. Hence, one or more composites **180** may be created and provisioned to the one or more of the matching endpoint devices **116** and/or users in accordance with embodiments disclosed herein. For example, the one or more composites **180** and/or particularized content item **176** may be created/selected as relating to the content item **176** and/or system **103** with the biasing **181** of composites **180** disclosed herein.

[0125] The matching engine **238** may take the identified characteristics of a given segment of programming content **202** as cues to retrieve one or more corresponding adaptable content items **176** and one or more content items **177** for the content splicing engine **242** to output one or more content composites **180** for presentation after the segment of programming content **202** (e.g., at a commercial break) or during the segment of programming content **202** (e.g., as an overlay, in a side window/frame, etc.) to match the identified characteristics of the programming content **202**. According to some embodiments, the matching engine **238** may employ one or more artificial intelligence algorithms to identify characteristic patterns in the programming content **202** which may correspond to triggers for intra-event creation of composites **180** for presentation at an upcoming break or during the event.

[0126] As one example case out of many possibilities, say a state change in a televised event of programming content **202** occurs (e.g., a score change, one team or competitor leading or falling behind, a takedown, a foul, etc.) and/or temporal progression marker (e.g., the fourth quarter, the second round, etc.) is reached. The subsystem **111** may detect the state change and, in response, initiate creation of composites **180** for presentation at an upcoming break or during the event. Accordingly, the dialogue may trigger composite **180** creation and presentation so that the composite **180** may be dynamically inserted in the content stream within a short time (e.g., substantially, seconds, within a minute, with environments, etc.) after the state change. In various embodiments, the subsystem **111** may detect the state change the way of keyword recognition of a dialogue from an announcer (e.g., detecting words such as touchdown, goal, takedown, foul, minutes on the clock, etc.), sudden changes in crowd noise, and/or image recognition (e.g., detecting graphics displayed with a televised event such as a scoreboard, streaming tickers or overlays typically positioned and/or scrolling across a portion of the display area, etc.).

[0127] To facilitate audio recognition, the content composite subsystem **111** (e.g., by way of the matching engine **238**) may be configured to detect one or more audio characteristics in adaptable programming content **202**. In some embodiments, the matching engine **238** may include an audio analyzer and handling module to facilitate that detection. By way of example, the matching engine **238** may detect one or more audio characteristics in programming content **202** by way of any one or combination of analyzing closed captioning information, analyzing audio, applying voice recognition, acoustic spectrum analysis, comparison to acoustic profiles for types of events, and/or the like.

[0128] Some embodiments of the content composite subsystem **111** may store acoustic profiles mapped to types of programming content **202** and corresponding state changes in the processed content repository. Each acoustic profile may specify one or more selected values of acoustic metrics as distinctive markings and/or acoustic categories **214** as characteristics of the types of programming content **202** and corresponding state changes. In various embodiments, the matching engine **238** may analyze the audio tracks metadata track, and/or close captioning information to identify dialogue as distinctive markings of state changes. The matching engine **238** may identify

one or more keywords and/or expressions in the dialogue as a dialogue impression for the purposes of characterizing the sample and identifying state changes. The matching engine **238** may compile the keywords and/or expressions of the sample and retain the keywords and/or expressions and corresponding state changes in the dialogue impression. In some cases, the matching engine **238** may correlate the dialogue impression to one or more dialogue categories **212** for similar dialogue impressions and corresponding state changes. In various embodiments, the correlation may be based at least in part on matching selected keywords and/or expressions to identical and/or similar keywords and/or expressions specified for certain dialogue categories **212**. The dialogue categories **212** may include categorizations of concept, keyword, expression, and/or the like mapped to corresponding state changes.

[0129] Based at least in part on the dialogue impression, the matching engine **238** may create a dialogue profile for a given segment and/or type of programming content **202** and corresponding state changes. The dialogue profile may be retained in any suitable form, such as a file, a list, etc. The content composite subsystem **111** may store dialogue profiles mapped to segments of programming content **202** and corresponding state changes in the processed content repository. Each dialogue profile may specify one or more selected keywords and/or expressions as distinctive markings and/or dialogue categories **212** as characteristics of the segment and/or type of programming content **202** and corresponding state changes.

[0130] To facilitate image recognition, some embodiments of the content composite subsystem **111** (e.g., by way of the matching engine **238**) may be configured to detect one or more color characteristics in programming content **202**, which may include any suitable color characteristic that may be measured recognize alphanumeric images corresponding to such state changes. In some embodiments, the matching engine **238** may include an image analyzer and handling module to facilitate that detection. By way of example, the matching engine **238** may detect one or more color characteristics in programming content **202** by way of any one or combination of pixel identification, detecting color component values, detecting color codes, and/or the like. Some embodiments may sample only portions of images, such as only part of a frame (which could, for example, be specified by identification of pixel coordinates and ranges thereof to define areas of interest). Some embodiments may sample only a central portion of a frame. Other embodiments may only sample a non-central portion, such as a border portion of a frame. Some embodiments may start with one portion of a frame and only sample to until a state change is recognized.

[0131] The matching engine **238** may perform correlation based at least in part on correlation rules **218**. The matching engine **238** may correlate segments of programming content **202** to state changes based at least in part on one or a combination of such characteristics. In some embodiments, the correlation may be based at least in part on the color profiles, acoustic profiles, and/or dialogue profiles of types and/or segments of programming content **202**. In some embodiments, the correlation may be based at least in part on color, dialogue, and/or acoustic categories **212**.

[0132] The correlation rules **218** may include correlation criteria that could include keywords identified by any one or combination of words, word stems, phrase, word groupings, and/or like keyword information. The correlation criteria could include weightings assigned to dialogue specifications. Hence, within each dialogue bucket, a keyword could be assigned a weight according to its significance. By way of example, more significant keywords could be assigned a greater weight than stop words. Such buckets could be implemented in any suitable manner, including lists, tables, matrices, and/or the like. And within a bucket, characteristics and/or keywords could be organized in a rank order and/or any hierarchical structure according to weight. Some embodiments may have characteristics and/or keywords organized according to decision tree, with contingencies so that only certain combinations of characteristics and/or keywords may be considered. For example, certain characteristics and/or keywords could only have significance if used in conjunction with other keywords, and/or not in conjunction with others.

[0133] In some embodiments, the matching engine **238** may employ a scoring system to quantify correlations with a numerical expression, for example, a match score, with higher scores being assigned to higher correlations of segments of programming content **202** with state changes. Higher scores may be assigned for greater extents of matching. For example, a match of three dialogue cues or dialogue categories may be assigned a higher score than a match of only one top dialogue cue and/or dialogue category. As another example, an exact match of words, expressions, and/or dialogue categories may be assigned a higher score than a complimentary match (e.g., where absent an exact match, a word, expression, and/or dialogue category is defined as a complement to another a word, expression, and/or dialogue category).

[0134] Further, the matching engine **238** may correlate the state changes to corresponding adaptable content items **176** that the subsystem **111** has stored locally to identify one or more of which that are particularized to some extent to the types of state changes detected. In some embodiments, a set of adaptable content items **176** may be ranked according to correlation such that the strongest matching content item **176** is ranked highest, and the ranked set may be selected for composite **180** creation in the ranked order consequent to the matched segment of programming content **202**.

[0135] As disclosed herein, the subsystem **111** may determine that the programming content **202** corresponds to a televised content segment for which content composite **180** creation is an option. The subsystem **111** may detect a location corresponding to the computing device **116** and the receiver **111**, and may determine from rules **218** whether the provisioning of content composites **180** of certain type are prohibited for the location. In the case where the subsystem **111** determines that there is no prohibition for the location, the subsystem **111** may determine a set of the rules **218** that govern timing restrictions and specifications, event type restrictions and specifications, place and manner restrictions and specifications, and types of adaptations of the adaptable content items **176** with the particularized content items **177** to create the composites **180**. Various sets of rules **218** may provide for various types of adaptations of the adaptable content items **176** with the particularized content items **177**, and the subsystem **111** may determine which set of rules **218** apply to a given receiver **116e** and/or device **116** as a function of the location of the receiver **116e** and/or device **116**.

[0136] The place and manner restrictions and specifications of the rules **218** may govern how and when composites are provisioned with respect to programming content **202** (e.g., as a commercial, as a real-time pop-up, as a real-time overlay, as an inset frame, a sliding and swipable overlay, and/or like), which may be a function of the type of program, type of end user (e.g., demographics), history and patterns of user input and selections, and/or the type of end-user device. For example, a set of rules **218** may specify that composites **180** may only be provided during commercial breaks of program. Another set of rules **218** may specify that composites **180** may be provided as overlays, frames, and/or pop-ups during the televised event.

[0137] The rules **218** may require the user opt in and request particularized content items **177**. Accordingly, one or more user-selectable options may be presented to the user via the receiver **116e** and/or device **116** to allow presentation of particularized content items **177** and/or options to request particularized content items **177**. Such user-selectable options may be provided with composites **180** that are presented and during commercial breaks. Likewise, one or more user-selectable options may be presented to the user via the receiver **116e** and/or device **116** to prohibit provisioning of particularized content items **177** and/or options to request particularized content items **177**. Upon user selection of such prohibition, the subsystem **111** may present alternative content items in lieu of particularized content items **177** and/or options to request particularized content items **177** during commercial breaks, such as content items **176** without particularized content items **177** and/or options to request particularized content items **177** and/or other content items. Consequent to a user opting in, prohibiting, and/or requesting particularized content items **177**, one or more communications may be transmitted to the system **102** to indicate the user

selection(s). The system **102** may update an account associated with the user and/or endpoint media device **116** accordingly, for example, with storage of user preferences and credits/awards for user interactions with respect to content items **177**.

[0138] In some embodiments, during a period of time when a content item **176** is being presented with a display of the endpoint device **116** (e.g., with a commercial), a user-selectable option may be presented to allow for user selection to request one or more particularized content items **177** corresponding to the content item **176**. In some embodiments, a request for one or more particularized content items **177** corresponding to the content item **176** may be made by way of one or more buttons on a remote control associated with a television receiver **116e** that are configured for selection of a displayed user-selectable option or otherwise to request a particularized content item **177** corresponding to the content item **176** being output by the television receiver **116e** for display. In addition or in alternative, one or more user-selectable options may be available during the time period for on-screen selection via a remote control and a selection function (e.g., an on-screen selector such as a hovering indicator of any suitable form) and/or one or more buttons on television receiver **116e** that allows a user to interact with television receiver **116e**. In some embodiments, an indication of the user-selectable option associated with a content item **176** represented on-screen could be presented to indicate that the user may select an option to obtain further information.

[0139] Additionally or alternatively, in some embodiments, a selection of a user-selectable option and/or another type of request may be made orally by user and recognized with a voice recognition device integrated with the remote control or integrated with or otherwise communicatively coupled to the endpoint media device **116**. For example, the voice recognition device may correspond to a smart speaker with virtual assistant. Thus, a user may user opt in and request particularized content items **177** via voice recognition.

[0140] Particularized content items **177** may be provisioned to endpoint media devices **116** in one or a combination of ways. In some embodiments, particularized content items **177** may be integrated and displayed with the adaptable content item **176**. Such presentations of the particularized content items **177** may be captured by an endpoint media device **116** via scanning with a scanner, taking a photo with a camera, saving a screenshot, and/or the like. Additionally or alternatively, particularized content items **177** may transferred to an account accessible by the user of the endpoint media device **116**. Additionally or alternatively, particularized content items **177** may be provisioned to a device **116** by way of one or combination of application installed on the device **116**, communications from a receiver **116e**, communications from the service provider system **102-1**, a near field communication interface (e.g., contactless interface, Bluetooth, optical interface, etc.), wireless communications interfaces capable of communicating through a cellular data network, or through Wi-Fi, such as with a wireless local area network (WLAN), and/or the network **120**. By way of example, a composite **180** may be presented via a television receiver **116e** on a display **160** with one or more user-selectable options that allow redirection of composites **180** and/or particularized content items **177** to a secondary device **116** consequent to user selection. Further, one or more user-selectable options may be presented to the user via the receiver **116e** and/or device **116** to allow content composite **180** and/or particularized content item **177** provisioning to a secondary device **116** concurrently with the presentation of the televised content segment.

[0141] The user-selectable options presented with the composite **180** may allow for taking actions, such as selecting one or more URLs, hyperlinks, click-to-call, and/or voice-activate-to-call options to one or more platforms, websites, and/or sites for further information, ordering, requesting, and/or accessing products and/or services. As disclosed herein, the user-selectable options may include one or more options to transition provisioning of one or more composites **180** to a secondary device **116** and/or to request notifications from the one or more platforms, websites, and/or sites be sent to the secondary device **116** so that the secondary device **116** may be used to interact with the

platforms and sites via an application installed on the secondary device **116**. In that way, a user may interact with the one or more platforms and sites via the secondary device **116** while viewing the televised event on a primary display associated with a receiver **116e** and/or primary device **116**. [0142] According to one option, the secondary device **116** may receive the same content, including composites **180** as commercial segments and/or overlays, being displayed on the display device **160** with simulcasting to the secondary device **116** so that the secondary device **116** need only display the augmented content. According to another option, the television receiver **116e** may provide the programming content to the display device **160**, and the secondary device **116** may receive the programming content and splice composites **180** into the content displayed with the device **116**. In various embodiments, the device **116** may receive the composites **180** for splicing from the receiver **116e**, may receive the composites **180** for splicing from the service provider system **102-1**, and/or may receive adaptable content items **176** and content items **177** from the receiver **116e** and/or the system **102-1** in order that the device **116** may create provision composites **180** therefrom. In some modes of operation, the television receiver **116e** may present alternative content items with the display device **160** in lieu of content composites **180**, while the content composites may be shunted to the secondary device **116**. Thus, the secondary device **116** may receive composites **180** that would otherwise be displayed on the display device **160**. In some embodiments and options, the receiver **116e** may not cast to the televised event, but the device **116** may present composites **180** without the televised event. For example, according to some options, an application for the device **116** may be downloaded, installed, and initiated to facilitate content provisioning on the device **116** and interaction with one or a combination of the receiver **116e**, system **102-1**, and/or one or more systems **103-1**. Accordingly, various embodiments may provide various user-selectable options for transitioning from just viewing a televised event to displaying and interacting with composites **180** and service provider systems **103-1** via a secondary device **116**, while a televised event corresponding to the composites **180** is being displayed on another device such as display device **160** the receiver **116e**.

[0143] In accordance with the geo-specific rules **218**, the subsystem **111** may detect a trigger for composite **180** creation that corresponds to a need for presentation of one or more composites **180** during an upcoming break in the programming content **202** corresponding to an event and/or during the presentation programming content **202** corresponding to the event. Detecting a trigger may include determining timing specifications of the event and a temporal progression in the event (e.g., the fourth quarter, the second round, etc.), detecting a state change in the event (e.g., a score change, one team or competitor leading or falling behind, etc.), and/or the like. In various embodiments, a trigger may correspond to the matching engine **238** processing the metadata associated with programming content **202** and/or processing the audio and/or video content of the programming content **202** to identify an upcoming break in the programming content **202**. This may include processing the metadata to identify flags or other indicators of the timing specifications of a commercial break. Additionally or alternatively, this may include the audio recognition, video recognition, and/or closed captioning recognition disclosed above to identify timing specifications, temporal progression, and/or state changes as triggers for composite **180** creation.

[0144] When the subsystem **111** detects a trigger, the subsystem **111** may receive and/or select from one or more adaptable content items **176** provided by the system **102-1** as matching particular segments of the televised content segment and one or more content items **177** to generate and output for display, utilizing the content splicing engine **242**, one or more composites **180** to display as a commercial during a programming break after a particular segment or as an intra-program overlay, frame, window, pop-up, and/or the like presented concurrently with the televised event. For example, a content item **177** may include text, one or more images, links, URLs, buttons, other user interface elements, and/or the like which the content splicing engine **242** may aggregate, process, format, crop, rescale, and/or otherwise prepare and include in composites **180** for insertion

into the content stream for output with the programming content **202** and/or during breaks of the programming content **202**. Thus, the content splicing engine **242** may identify content portions for augmentation by processing the content item **177**, reading the content item **177** or certain portions thereof, and determine portions for augmentation in video segments. In some embodiments, portions of images and/or frames of the adaptable content item **176** may be overwritten with captured content from the content item **177**.

[0145] The content splicing engine **242** may identify one or more portions of adaptable content item **176** to be augmented based at least in part on content item **177**, which may, in various embodiments, be identified by image analysis and/or analysis of tag data that defines one or more areas within frames that correspond to certain portions represented within the frames for augmentation. As disclosed herein, such tag data could define the area of interest in any suitable way in various embodiments which could be by way of any one or combination of mattes, masks, pixel identification (which could, for example, include identification of pixel coordinates and ranges thereof to define areas of interest), pixel color component characteristics such as color component values, overlays, and/or the like, allowing for correlation to the area to be augmented in any suitable way. In some embodiments, a processor (such as a main processor, a core processor, digital signal processor, and/or like) may take a definition of the augmentation area with respect to one or more reference frames and may perform auto-correlation of related images in a video stream to identify/define the augmentation areas in other frames of the video sequence that represent the portion to be augmented. Image characteristics (e.g., color, brightness, etc.) of the area of interest with respect to the reference frame(s) could be measured, quantified, and/or otherwise identified, and matched with measured image characteristics of the other frames to define the area to be augmented in multiple frames in an image-changing sequence. Accordingly, certain embodiments may allow for handling the complexity of multiple on-screen options by differentiating particular areas in dynamic, image-changing content.

[0146] As illustrated by FIG. 3, the content processing subsystem **111** may include a learning engine **239** that may be an analysis engine that employs machine learning. The learning engine **239** may further employ deep learning. Accordingly, the learning engine **239** may facilitate machine learning or, more specifically, deep learning, to facilitate creation, development, and/or use of viewer pattern data **216**. As disclosed herein, the subsystem **111** may determine a program, show, etc. that the viewer actually is viewing, is about to view (e.g., the televised event is scheduled to play on the channel that the viewer is currently viewing), or is likely to view as determined with the learning engine **239**. The subsystem **111** may push information indicating the televised event to one or more service provider systems **102-1** and/or **103-1**. In some embodiments, the service provider system **102-1** may select one or more adaptable content items **176** matching the televised content segment for transfer to the subsystem **111** which, as disclosed herein, may be a part of the content provider system **102** and/or may be part of the receiver **116e** and/or devices **116**. The subsystem **111** may select from the one or more adaptable content items **176** as matching particular segments of the televised segment and, utilizing a content splicing engine **242** in some embodiments, may output one or more corresponding content composites **180** for display after the particular segments and/or simultaneously with the particular segments.

[0147] In various embodiments, one or more of the service provider systems **102-1**, **103-1** may select one or more particularized content items **177** matching the televised event for transfer to the subsystem **111**. In some embodiments, one or more of the service provider systems **102-1**, **103-1** may select a set of one or more particularized content items **177** for transfer (e.g., based on recency of information updates corresponding to the content items **177**) for transfer to the subsystem **111**, and the subsystem **111** may determine which content items **177** from the set match the televised content segment. As disclosed above, the content composite subsystem **111** may include a matching engine **238** that may include logic to implement and/or otherwise facilitate any taxonomy, classification, categorization, correlation, mapping, qualification, scoring, organization, and/or the

like features disclosed herein.

[0148] FIG. 5 illustrates certain aspects of the AI-based subsystem data flow **500**, in accordance with various embodiments of the present disclosure. The content processing subsystem **111** may be configured to gather observation data **229**, which may be specific to one or more particular identified users and/or may be generally related to particular endpoint media devices **116**. The observation data **229** may be gathered from one or more devices **116**, aggregated, consolidated, and transformed into viewer pattern profiles that include personalized pattern data **216**.

[0149] In embodiments where the learning engine **239** is included in an endpoint media device **116**, the device **116** may be a self-observer that may additionally gather additional observation data **229**. In various embodiments, the data from the one or more devices **116** may be retrieved and/or received by the content processing subsystem **111** via one or more data acquisition interfaces, which may include interfaces of the content processing subsystem **111**, the one or more endpoint media devices **116**, and/or the like-through network(s) **120** in various embodiments, through any suitable means for direct communication, and/or through any other suitable means of transferring data. According to various embodiments where the subsystem **111** is included in a service provider system **102-1**, observation data **229** may be actively gathered and/or pulled from the one or more endpoint media devices **116**.

[0150] As disclosed herein, in various embodiments, the one or more data acquisition interfaces may include one or more APIs that define protocols and routines for interfacing with the one or more endpoint media devices **116** and which may specify API calls to/from one or more endpoint media devices **116**. In various embodiments, the APIs may include a plug-in to integrate with an application of one or more endpoint media devices **116**. The API translation profiles may translate the protocols and routines of the data source component and/or system to integrate at least temporarily with the system and allow one-way communication to the system **102-1** and/or two-way communication with system **102-1** in various embodiments by way of API calls.

[0151] Some embodiments of the subsystem **111** may aggregate observation data **229** to derive device identification data **504**, device operations **506**, temporal data **508**, and/or contextual data **510**. The device identification data **504** may include any suitable data for identifying and tracking particular receivers **116e** and devices **116**; associated accounts, subscribers, and viewers; and/or the like disclosed herein. The device operations data **506** may include any suitable data for identifying and tracking device operations and interactions as those disclosed herein. The contextual data **510** may include metrics and patterns of viewer interactions/responses pursuant to provisioning of content composites **180** and service provider system **103-1** biasing **181**. For example, viewer responses to content composites **180** provisioning may include indications of whether the viewer selected a user-selectable options provided with composites **180**, the types of such selections, and/or types of consequent interactions with service provider systems **103-1**. For example, the metrics and patterns may take into account whether the viewer opted out of content composites **180**, whether the viewer selected links of composites **180** to interact with the platforms and sites of one or more service provider systems **103-1**, whether the viewer selected options to redirect content composites **180** and/or notifications from service provider systems **103-1** to a secondary device **116**, which options and/or service provider systems **103-1** the viewer selected, whether the viewer used redeemable content items, QR codes, etc. and the types of the viewer's orders, purchases, and other interactions with service provider systems **103-1**, and/or the like. The temporal data **508** may include metrics such as any information to facilitate detection, recognition, and differentiation of one or combination of temporal factors correlated or which the content processing subsystem **111** correlates to other observation data **229** such as device identification data **504**, contextual data **510**, and/or the like. For example, the temporal data **508** may include time of day information, time of week information, time of year information, holiday information, etc. when the viewer made selections, orders, purchases, redemptions of redeemable content items, offers, promo codes, etc.; and/or the like.

[0152] The learning engine **239** may map one or a combination of the various extra-composite metrics of the observation data **229** to the metrics of the particular composites **180** provided to a particular viewer. Based at least in part on taking into account such observation data **229** as part of a feedback loop, the learning engine **239** may employ an ongoing learning mode to develop personalized pattern data **216** for particular viewers or content receivers/devices generally, and to confirm, correct, and/or refine determinations made for personalized pattern data **216** for particular viewers or content receivers/devices generally. The content processing subsystem **111** may be configured to employ machine learning to process the observation data **229** and the content items **180** and to derive and develop the personalized pattern data **216**. The content processing subsystem **111** may be configured to employ deep learning to process the observation data **229** and the content items **180** and to derive and develop the personalized pattern data **216**. The learning engine **239** may be configured to perform any one or combination of features directed to matching or otherwise correlating the observation data **229**—such as the device identification data **504**, the device operation identification data **506**, the temporal data **508**, the contextual data **510**, descriptive information of the content items **180**, and/or the like—with intra-content metrics of the content items **180**. The learning engine **239** may include logic to implement and/or otherwise facilitate any taxonomy, classification, categorization, correlation, mapping, qualification, scoring, organization, and/or the like features disclosed herein. In some embodiments, the learning engine **239** may include the matching engine **238**.

[0153] The learning engine **239** may include a reasoning module to make logical inferences from a set of the detected and differentiated data to infer one or more patterns of activity for particular viewers and/or receivers/devices generally. A pattern-based reasoner could be employed to use various statistical techniques in analyzing the data in order to infer personalized pattern data **216** from the observation data **229**. A transitive reasoner may be employed to infer relationships from a set of relationships related to the observation data **229**. In various embodiments, the system automatically establishes and develops the personalized pattern data **216**. However, the personalized pattern data **216** may be set up and/or tailored by users. With various embodiments, the personalized pattern data **216** may be automatically established and developed by the system.

[0154] The feedback could be used for training the system to heuristically adapt conclusions, profiles, correlations, attributes, triggers, patterns, and/or the like to learn particular viewers and adapt content composite **180** provisioning to particular viewers, which may include requesting, searching for, and/or selecting particular types of adaptable content items **176** and/or content items **177** (e.g., which may be based at least in part on the metadata features disclosed herein) for content composite **180** creation. For example, the learning engine **239** may learn that a particular viewer tends to interact with content composites **180** that are directed to only certain types of products and/or services. Such interaction object type differentiation may be on the macro level, such as recognizing that a viewer tends to interact more with composites **180** directed to certain types of products, services, and/or offers and not other types of products, services, and/or offers. Additionally, the learning engine **239** may learn that a particular viewer tends to interact with particular content composites **180** and/or types only after the particular content composite **180** and/or type has been presented to the viewer X number of times. In some instances, the detection of a particular content item **176** having been presented to the viewer X number of times (e.g., an absolute threshold number of times and/or a relative threshold to presentations to other viewers such as a top percentile of presentations relative to other viewers) may trigger the subsystem **111** provisioning a related particularized content item **177** to the viewer. Accordingly, the subsystem **111** may bias content composites **180** provisioning toward the types of products and/or services that tend to elicit viewer interaction, and decrease composite **180** provisioning frequency or cease provisioning for other types.

[0155] Further, the learning engine **239** may learn that a particular viewer tends to interact with content composites **180** that are directed to only types of products, services, and/or offers within a

particular category. Accordingly, the subsystem **111** may likewise bias content composites **180** provisioning toward such types of products, services, and/or offers and decrease or cease provisioning with respect to other types. Further, viewer interaction differentiation may be on the micro level, such as recognizing that a viewer tends to interact more with composites **180** directed to certain types of offers, redeemable content items, promotions, etc. Accordingly, the subsystem **111** may likewise bias content composites **180** provisioning toward such types and decrease or cease provisioning with respect to other types.

[0156] Further, in situations where a pattern of more micro-level interactions detected for particular viewer, the subsystem **111** biasing **181** of composites **180** may include serial provisioning of composites **180** in a serial drill-down manner such that the first composites **180** provisioned may be directed to a more macro-level outcome and one or more composites **180** subsequently provisioned may be directed to more micro-level outcomes in accordance with the detected pattern. Thus, disclosed embodiments may provide for serial matching of composites **180** with respect to one another in order to provision the composites **180** with a trend that matches the detected pattern. As one possible example out of many, when viewer interaction with macro-level composite **180** directed to a macro-level product and/or service (e.g., a vehicle) results in a macro-level outcome by the viewer (e.g., an purchase, order, etc. of the vehicle), the biasing **181** may include ceasing provisioning of repeats and variations of the macro-level composite **180** to the viewer and may further include subsequently provisioning more micro-level content composites **180** directed to more micro-level outcomes (e.g., complementary products/services, such as warranties, accessories, etc.).

[0157] As part of such learning and adaptation processes, the subsystem **111** may bias composite **180** provisioning toward use of content items **177** from certain service provider systems **103-1** over other service provider systems **103-1**. The learning engine **239** may perform correlation based at least in part on correlation rules that govern correlation of the personalized pattern data **216** to content items **177** and corresponding sources of the content items **177** based at least in part on metrics and availabilities of the content items **177** from the particular source systems **103-1**. In various embodiments, the correlation may be based at least in part on the profiles of the service provider systems **103-1**. In analyzing content items **177** received for particular service provider systems **103-1**, the subsystem **111** may identify patterns of types of content items **177** and mapped which types of content items **177** are provided by which service provider systems **103-1**. Based at least in part on such mapping, the subsystem **111** may prioritize use of content items **177** from particular service provider systems **103-1** where the content items **177** are of viewers directed to the types of interactions that match interaction patterns of a particular viewer.

[0158] Further, such biasing **181** of content items **177** from one or more systems **103-1** may include prioritizing attempts to pull content items **177** from one or more systems **103-1** based at least in part on speed and responsiveness of systems **103-1**. The subsystem **111** may aggregate and develop service provider system metrics based at least in part on the speed and responsiveness of systems **103-1** demonstrated with previous attempts to pull one or more content items **177** within one or more historical time windows (e.g., previous day, five days, week, month, year, etc.). The service provider systems **103-1** may be scored based at least in part on the metrics, and an individual scores may be utilized in identifying preferential biasing **181** an attempt to pull content items **177** from respective systems **103-1**. For example, the subsystem **111** may attempt to pull one or more content items **177** from a first set of one or more service provider systems **103-1** that has the highest score based on previous performance with respect to speed, timeliness, and a matching content item **177**. In the case that no matching content items **177** are successfully pulled from the first set of one or more service provider system **103-1** within a time threshold after the initial request, then the subsystem **111** may pull one or more content items **177** from a second set of one or more service provider systems **103-1** that have lower scores. Such serial stages attempt to pull content items **177** may be continued with additional sets of lower scored systems **103-1**. The time

thresholds may be different for each stage (e.g., decreasing or increasing in time) and the size of the selected sets of service provider systems **103-1** may be different for each stage (e.g., decreasing or increasing in size). In cases where multiple such stages are necessary, the subsystem **111** may subsequently adjust metrics for the systems **103-1**, taking into account the performance demonstrated with such stages of attempt to pull objects **177**.

[0159] FIG. **6** illustrates a receiver **600** that makes use of, interacts with, and/or at least partially includes the subsystem **111**, in accordance with disclosed embodiments of the present disclosure. Certain embodiments of the receiver **600** may include set top boxes (STBs), television receivers, and over-the-top receivers. In some embodiments, the receiver **600** may correspond to the television receiver **116e**. In various embodiments, in addition to being in the form of a STB, a receiver may be incorporated as part of another device, such as a television or other form of display device, such as a computer, smartphone, tablet, or other handheld portable electronic device. For example, a television may have an integrated receiver (which does not involve an external STB being coupled with the television). One or a combination of the content harvesting engine **236-1**, the content matching engine **238-1**, learning engine **239-1**, content composite build engine **240-1**, and/or content splicing engine **242-1** may be provided in conjunction with content harvesting module **236-2**, the content matching module **238-2**, content augmentation module **240-2**, and/or content splicing module **242-2** to implement various functionalities of the content composite subsystem **111** into the receiver **600**.

[0160] The receiver **600** may represent receiver **116e** of FIG. **1** and may be in the form of a STB that communicates with a display device such as a television. The receiver **600** may be incorporated as part of a television, such as the display device **160** of FIG. **1** or television **600** of FIG. **6**, etc. The receiver **600** may include: processors **610** (which may include control processor **610-1**, tuning management processor **610-2**, and possibly additional processors), tuners **615**, network interface **620**, non-transitory computer-readable storage medium **625**, electronic programming guide (EPG) database **630**, networking information table (NIT) **640**, digital video recorder (DVR) database **645**, on-demand programming **627**, content store **222-3**, user interface **650**, decryption device **660**, decoder module **633**, interface **635**, and/or descrambling engine **665**. In other embodiments of receiver **600**, fewer or greater numbers of components may be present. It should be understood that the various components of receiver **600** may be implemented using hardware, firmware, software, and/or some combination thereof. Functionality of components may be combined; for example, functions of descrambling engine **665** may be performed by tuning management processor **610-2**. Further, functionality of components may be spread among additional components; for example, PID filters **655** may be handled by separate hardware from program map table **657**. The receiver **600** may be in data communication with service providers, such as by way of network interface **620**.

[0161] The processors **610** may include those configured to perform processes such as tuning to a particular channel, accessing and displaying EPG information from the EPG database **630**, and/or receiving and processing input from a user. For example, the processors **610** may include one or more processors dedicated to decoding video signals from a particular format, such as MPEG, for output and display on a television and for performing decryption, if required. It should be understood that the functions performed by various modules of FIG. **6** may be performed using one or more processors. As such, for example, functions of the descrambling engine **665** may be performed by the control processor **610-1**.

[0162] The control processor **610-1** may communicate with tuning management processor **610-2**. The control processor **610-1** may control the recording of television channels based at least in part on timers stored in the DVR database **645**. The control processor **610-1** may also provide commands to the tuning management processor **610-2** when recording of a television channel is to cease. In addition to providing commands relating to the recording of television channels, the control processor **610-1** may provide commands to the tuning management processor **610-2** that

indicate television channels to be output to the decoder module **633** for output to a display device. The control processor **610-1** may also communicate with the network interface **620** and the user interface **650**. The control processor **610-1** may handle incoming data from network interface **620**, including network transport streams received from over-the-top service providers. The control processor **610-1** may handle incoming data from the network interface **620**, including network transport streams received from the user interface **650**, which may include user input received by way of one or more human interface devices. Additionally, the control processor **610-1** may be configured to output data via the network interface **620**. The control processor **610** may also be configured to perform image and audio analysis, such as to identify contextual aspects present in an audio or video stream, for example facial recognition or voice recognition.

[0163] The tuners **615** may include one or more tuners used to tune to transponders that include broadcasts of one or more television channels that may be received from a satellite or cable system, for example. In the illustrated embodiment of receiver **600**, three tuners are present (tuner **615-1**, tuner **615-2**, and tuner **615-3**). In other embodiments, two or more than three tuners may be present, such as four, six, or eight tuners. Each tuner contained in the tuners **615** may be capable of receiving and processing a single transponder stream from a satellite transponder at a given time, for example. As such, a single tuner may tune to a single transponder stream at a given time. If the tuners **615** include multiple tuners, one tuner may be used to tune to a television channel on a first transponder stream for display using a television, while another tuner may be used to tune to a television channel on a second transponder for recording and viewing at some other time. If multiple television channels transmitted on the same transponder stream are desired, a single tuner of the tuners **615** may be used to receive the signal containing the multiple television channels for presentation and/or recording. The tuners **615** may receive commands from the tuning management processor **610-2**. Such commands may instruct the tuners **615** which frequencies are to be used for tuning.

[0164] The network interface **620** may be used to communicate via an alternate communication channel with a television service provider, if such communication channel is available. The primary communication channel may be via satellite (which may be unidirectional to the receiver **600**) and the alternate communication channel (which may be bidirectional) may be via a network, such as the Internet. Referring back to FIG. 1, receiver **116e** may be able to communicate with content provider system **102-1** via a network **120**, such as the Internet. This communication may be bidirectional: data may be transmitted from the receiver **116e** to the content provider system **102-1** and from the content provider system **102-1** to the receiver **116e**. Referring back to FIG. 6, the network interface **620** may be configured to communicate via one or more networks, such as the Internet, to communicate with content provider system **102-1** of FIG. 1. Other information may be transmitted and/or received via the network interface **620** such as adaptable content items **176**, content items **177**, metadata, and/or the like as disclosed herein.

[0165] The storage medium **625** may represent one or more non-transitory computer-readable storage mediums. The storage medium **625** may include memory and/or a hard drive. The storage medium **625** may be used to store information received from one or more satellites and/or information received via the network interface **620**. The storage medium **625** may store information related to the EPG database **630**, augmentation module **632** and related preferences, other non-video/audio data **631**, DVR database **645**, commercial database **646**, and/or on-demand programming **627**. Recorded television programs may be stored using the storage medium **625** as part of the DVR database **645**. The storage medium **625** may be partitioned or otherwise divided (such as into folders) such that predefined amounts of the storage medium **625** are devoted to storage of television programs recorded due to user-defined timers and stored television programs recorded due to provider-defined timers.

[0166] The EPG database **630** may store information related to television channels and the timing of programs appearing on such television channels. The EPG database **630** may be stored using the

storage medium **625**, which may be a hard drive. Information from the EPG database **630** may be used to inform users of what television channels or programs are popular and/or provide recommendations to the user. Information from the EPG database **630** may provide the user with a visual interface displayed by a television that allows a user to browse and select television channels and/or television programs for viewing and/or recording. Information used to populate the EPG database **630** may be received via the network interface **620** and/or via satellites, such as the satellite **106** of FIG. **1** via the tuners **615**. For instance, updates to the EPG database **630** may be received periodically via satellite. The EPG database **630** may serve as an interface for a user to control DVR functions of the receiver **600**, and/or to enable viewing and/or recording of multiple television channels simultaneously. Information from EPG database **630** may be output as a video stream to a display device. A particular user may issue commands indicating that an EPG interface be presented. A user issuing a command that an EPG be displayed may constitute a change command. In some embodiments, content composites **180** may be created and presented in conjunction with the EPG. For example, content composites **180** could pertain to televised events indicated in the EPG. Hence, content composite **180** features may extend to EPG views in some embodiments.

[0167] The network information table (NIT) **640** may store information used by the receiver **600** to access various television channels. The NIT **640** may be stored locally by a processor, such as the tuning management processor **610-2** and/or by the storage medium **625**. Information used to populate the NIT **640** may be received via satellite (or cable) through the tuners **615**, may be received via the network interface **620**, such as from the television service provider. As such, information present in the NIT **640** may be periodically updated. In some embodiments, NIT **640** may be locally-stored by the receiver **600** using the storage medium **625**. Generally, the NIT **640** may store information about a service provider network, such as a satellite-based service provider network. Information that may be present in the NIT **640** may include: television channel numbers, satellite identifiers (which may be used to ensure different satellites are tuned to for reception of desired television channels), frequency identifiers, transponder identifiers for various television channels, antenna identifiers (which may be used to ensure different antennas are tuned to for reception of desired television channels), radio frequency identifiers, and/or subchannel identifiers for various television channels. In some embodiments, the NIT **640** may contain additional data or additional tables may be stored by the receiver. For example, while specific audio PIDs and video PIDs may not be present in the NIT **640**, a channel identifier may be present within the NIT **640** which may be used to look up the audio PIDs and video PIDs in another table, such as a program map table (PMT). In some embodiments, a PID associated with the data for the PMT is indicated in a separate table, program association table (PAT), which is not illustrated in FIG. **6**. A PAT may be stored by the receiver in a similar manner to the NIT. For example, a PMT may store information on audio PIDs, and/or video PIDs. A PMT stores data on ECM (entitlement control message) PIDs for television channels that are transmitted on a transponder stream, transport stream, or digital broadcast. If, for a first television channel, multiple television channels are to be tuned to, the NIT **640** and/or the PMT **657** may indicate a second television channel that is to be tuned to when a first channel is tuned to; this may allow for switching to output of the second television channel for different commercials, for example.

[0168] A table, such as the NIT, PAT, or PMT may store indications of PIDs that are related to supplemental audio content for individual channels or other forms of content. For instance, each television channel may be associated with a different supplemental audio PID. If supplemental audio content is to be transmitted for a given television channel, packets containing the supplemental audio are transmitted to the receiver having its associated supplemental audio content PID. This PID could be distinct from any of the audio programs of the television programming (e.g., the first audio program, second audio program (SAP), actual descriptive audio). In some embodiments, supplemental audio content is transmitted using the same transponder stream as the

television channel or content to which the supplemental audio content corresponds. In some embodiments, a single supplemental audio PID is used to identify supplemental audio for multiple television channels, such as all the television channels on a given transponder. A second identifier present within the supplemental audio data may be used to distinguish for which television channel the supplemental audio data corresponds.

[0169] Based at least in part on information in the NIT, it may be possible to determine the proper satellite and transponder to which to tune for a particular television channel, or to determine the proper antenna and frequency to which to tune to for a particular television channel. In some embodiments, the NIT may list a particular frequency to which to tune for a particular television channel. Once tuned to the proper satellite/transponder/antenna/frequency, the PMT PID may be used to retrieve a program map table that indicates the PIDs for audio and video streams of television channels transmitted by that transponder.

[0170] While a large portion of storage space of the storage medium **625** may be devoted to storage of television programming, a portion may be devoted to storage of non-audio/video data, such as the EPG database **630** and other non-video/audio data **631**. This “other” data may permit the receiver **600** to function properly. In some embodiments, at least ten gigabytes are allocated to such other data. For example, if the NIT **640** is stored by the storage medium **625**, it may be part of the other non-video/audio data **631**.

[0171] The decoder module **633** may serve to convert encoded video and audio into a format suitable for output to a display device. For instance, the decoder module **633** may receive MPEG video and audio from the storage medium **625**, the network interface **620**, or the descrambling engine **665** to be output to a television. MPEG video and audio from the storage medium **625** may have been recorded to the DVR database **645** as part of a previously recorded television program. The decoder module **633** may convert the MPEG video and audio into a format appropriate to be displayed by a television or other form of display device and audio into a format appropriate to be output from speakers, respectively. The decoder module **633** may have the ability to convert a finite number of television channel streams received from the storage medium **625**, the network interface **620**, or the descrambling engine **665** simultaneously. For instance, each of the decoders **634** within the decoder module **633** may be able to only decode a single television channel at a time.

[0172] While a television channel is being decoded by a decoder of the decoders **634**, the television channel is not necessarily output to a display device via the television interface **635**. For instance, a television channel may be decoded but not output to allow for seamless or near-seamless switching to the television channel when output is desired. For example, if a second television channel is to be output for presentation during commercial breaks on a first television channel, the second television channel and the first television channel may each be continuously decoded by different decoders of the decoder module **633** to allow for fast switching between the channels. Without a television channel being continuously decoded, fast switching may be difficult due at least in part to the format in which the channel is encoded. For instance, for MPEG encoding, it may be necessary to first decode an I-frame before certain subsequent (or earlier) received frames may be properly decoded. The output of the decoder, which is provided to the television interface **635**, may be controlled by the control processor **610-1**, or some other processor. While the decoder module **633** is illustrated as having three decoders **634** (decoder **634-1**, decoder **634-2**, and decoder **634-3**), in other embodiments, a greater or fewer number of decoders may be present in the receiver **600**.

[0173] The television interface **635** may serve to output a signal to a television (or another form of display device) in a proper format for display of video and playback of audio. As such, the television interface **635** may output one or more television channels, stored television programming from the storage medium **625** (e.g., television programs from the DVR database **645**, television programs from on-demand programming **627** and/or information from the EPG database **630**) to a television for presentation.

[0174] Digital Video Recorder (DVR) functionality may permit a television channel to be recorded

for a period of time. DVR functionality of the receiver **600** may be managed by the control processor **610-1**. The control processor **610-1** may coordinate the television channel, start time, and stop time of when recording of a television channel is to occur. In various embodiments, adaptable content items **176** could be selected and inserted into the presentation stream prior to recording, during recording, and/or upon playback of the recording. The DVR database **645** may store information related to the recording of television channels. The DVR database **645** may store timers that are used by the control processor **610-1** to determine when a television channel should be tuned to and its programs recorded to the DVR database **645** of storage medium **625**. In some embodiments, a limited amount of the storage medium **625** may be devoted to the DVR database **645**. Timers may be set by the television service provider and/or one or more users of the receiver **600**.

[0175] User profiles may also be stored in the storage medium **645** and may include stored user preferences that may be inferred by the television receiver **600** based at least in part on viewing history. The television receiver **600** may communicate user profile information to the service system(s) **102-1**, **103-1** to request adaptable content items **176** and content items **177** tailored to the inferred user preferences to provision composites **180** in accordance with certain embodiments disclosed herein. The user profiles may include profiles for multiple users or may include a single profile for the television receiver in general. In some embodiments, the user profiles may include preferences for customized content presentation adjustments disclosed herein. The preferences could include customized viewing interests, such as programming content, announcement content, product content, and/or the like that corresponds to augmented content selections relating to recognized actors and/or products. The user profiles may further include user feedback, via user-selectable options, received from the user regarding customizations. The feedback data may be used to refine the customizations for particular viewers and types of content customizations.

[0176] The on-demand programming **627** may represent additional television programming stored by the storage medium **625**. The on-demand programming **627** may include television programming that was not recorded to the storage medium **625** via a timer (either user- or provider-defined). Rather, on-demand programming is programming provided to the receiver directly for storage by the receiver and for later presentation to one or more users. In various embodiments, adaptable content items **176** could be selected and inserted into the presentation stream prior to or upon playback of the recording.

[0177] The user interface **650** may include a remote control (physically separate from the receiver **600**) and/or one or more buttons on the receiver **600** that allow a user to interact with the receiver **600**. The user interface **650** may be used to select a television channel for viewing, view information from the EPG database **630**, and/or program a timer stored to DVR database **645**, wherein the timer is used to control the DVR functionality of the control processor **610-1**. The user interface **650** may also be used to transmit commands to the receiver **600** and make user selections to customize user preferences, make selections with respect to content items **176**, **177**, and content composites **180**.

[0178] Referring back to the tuners **615**, television channels received via satellite (or cable) may contain at least some scrambled data. Packets of audio and video may be scrambled to prevent unauthorized users (e.g., nonsubscribers) from receiving television programming without paying the television service provider. When a tuner of the tuners **615** is receiving data from a particular transponder of a satellite, the transponder stream may be a series of data packets corresponding to multiple television channels. Each data packet may contain a packet identifier (PID), which, in combination with the NIT **640** and/or the PMT **657**, may be determined to be associated with a particular television channel. Particular data packets, referred to as entitlement control messages (ECMs), may be periodically transmitted. ECMs may be associated with another PID and may be encrypted; the receiver **600** may use the decryption device **660** to decrypt ECMs. Decryption of an ECM may only be possible if the user has authorization to access the particular television channel

associated with the ECM. When an ECM is determined to correspond to a television channel being stored and/or displayed, the ECM may be provided to the decryption device **660** for decryption. [0179] The decryption device **660** may be a removable or non-removable smart card. When the decryption device **660** receives an encrypted ECM, the decryption device **660** may decrypt the ECM to obtain some number of control words. In some embodiments, from each ECM received by the decryption device **660**, two control words are obtained. In some embodiments, when the decryption device **660** receives an ECM, it compares the ECM to the previously received ECM. If the two ECMs match, the second ECM is not decrypted because the same control words would be obtained. In other embodiments, each ECM received by the decryption device **660** is decrypted; however, if a second ECM matches a first ECM, the outputted control words will match; thus, effectively, the second ECM does not affect the control words output by the decryption device **660**. The decryption device **660** may be permanently part of the receiver **600** or may be configured to be inserted and removed from the receiver **600**. In some embodiments, the control processor **610-1**, the tuning management processor **610-2**, or other hardware may be able to determine that a received ECM has not changed from the previous iteration, and therefore not provide the repeated ECM to the smart card, since the same control word(s) will be obtained.

[0180] The tuning management processor **610-2** may be in communication with the tuners **615** and the control processor **610-1**. The tuning management processor **610-2** may be configured to receive commands from the control processor **610-1**. Such commands may indicate when to start/stop recording a television channel and/or when to start/stop causing a television channel to be output to a television. The tuning management processor **610-2** may control the tuners **615**. From the tuners **615**, the tuning management processor **610-2** may receive transponder streams of packetized data. From the network interface **620**, the tuning management processor **610-2** may receive network transport stream of packetized data. As previously detailed, some or all of these packets may include a PID that identifies the content of the packet.

[0181] The tuning management processor **610-2** may be configured to create one or more PID filters **655** that sort packets received from the tuners **615** and/or the network interface **620** based at least in part on the PIDs. When a tuner is initially tuned to a particular frequency (e.g., to a particular transponder of a satellite), a PID filter may be created based at least in part on the PMT data. The PID created, based at least in part on the PMT data packets, may be known because it is stored as part of the NIT **640** or another table, such as a program association table (PAT). From the PMT data packets, PMT may be constructed by the tuning management processor **610-2**.

[0182] The PID filters **655** may be configured to filter data packets based at least in part on PIDs. In some embodiments, the PID filters **655** are created and executed by the tuning management processor **610-2**. For each television channel to be output for presentation or recorded, a separate PID filter may be configured. In other embodiments, separate hardware may be used to create and execute such PID filters. Depending on a television channel selected for recording/viewing, a PID filter may be created to filter: (1) the video packets associated with the television channel; (2) the audio packets associated with the television channel; and (3), if enabled, supplemental audio content for use in conjunction with interactive content. The PMT **657** may store the particular assignments of PIDs for individual television channels. For example, if a transponder data stream includes multiple television channels, data packets corresponding to a television channel that is not desired to be stored or displayed by the user may be ignored by the PID filters **655** and not routed to the descrambling engine **665**, the decryption device **660**, or the control processor **610-1**. As such, only data packets corresponding to the one or more television channels desired to be stored and/or displayed may be filtered and passed to either the descrambling engine **665** or the decryption device **660**; other data packets may be ignored. For each television channel, a stream of video packets, a stream of audio packets (one or both of the audio programs), a stream of supplemental audio content, and/or a stream of ECM packets may be present, each stream identified by a PID. In some embodiments, a common ECM stream may be used for multiple television channels.

Additional data packets corresponding to other information, such as updates to the NIT **640**, may be appropriately routed by the PID filters **655**. At a given time, one or multiple PID filters may be executed by the tuning management processor **610-2**.

[0183] The descrambling engine **665** may use the control words output by the decryption device **660** in order to descramble video and/or audio corresponding to television channels for storage and/or presentation. Video and/or audio data contained in the transponder data stream received by the tuners **615** may be scrambled. Video and/or audio data may be descrambled by the descrambling engine **665** using a particular control word. Which control word output by the decryption device **660** to be used for successful descrambling may be indicated by a scramble control identifier present within the data packet containing the scrambled video or audio. Descrambled video and/or audio may be output by the descrambling engine **665** to the storage medium **625** for storage (in the DVR database **645**) and/or to the decoder module **633** for output to a television or other presentation equipment via the television interface **635**.

[0184] For simplicity, the receiver **600** of FIG. **6** has been reduced to a block diagram; commonly known parts, such as a power supply, have been omitted. Further, some routing between the various modules of the receiver **600** has been illustrated. Such illustrations are for exemplary purposes only. The state of two modules not being directly or indirectly connected does not indicate the modules cannot communicate. Rather, connections between modules of the receiver **600** are intended only to indicate possible common data routing. It should be understood that the modules of the receiver **600** may be combined into a fewer number of modules or divided into a greater number of modules.

[0185] Further, the components of the television receiver **600** may be part of another device, such as built into a television. The television receiver **600** may include one or more instances of various computerized components, such as disclosed in relation to computer systems disclosed further herein. While the television receiver **600** has been illustrated as a satellite receiver, it is to be appreciated that techniques below may be implemented in other types of television receiving devices, such as cable receivers, terrestrial receivers, IPTV receivers or the like. In some embodiments, the television receiver **600** may be configured as a hybrid receiving device, capable of receiving content from disparate communication networks, such as satellite and terrestrial television broadcasts. In some embodiments, the tuners may be in the form of network interfaces capable of receiving content from designated network locations.

[0186] FIG. **7** is a block diagram of a system **700** including one non-limiting example of a computing device **116** configured to make use of, interact with, and/or at least partially include the subsystem **111**, in accordance with disclosed embodiments of the present disclosure. The computing device **116** may be a portable device suitable for sending and receiving information to/from the receiver **116e** and over a network to/from remote data sources (e.g., service providers **103-1** and online content sources **112**) in accordance with embodiments described herein. For example, in various embodiments, the computing device **116** may correspond to one or more of computing devices **116a**, **116b**, **116c**, **116d** depicted in FIG. **2**.

[0187] In some embodiments, the computing device **116** may be provided with an application **751**, which may, in some embodiments, correspond to a mobile application configured to run on the computing device **116** to facilitate various embodiments of this disclosure. For example without limitation, the mobile application **751** may transform the computing device **116** into an adaptive content splicing device to facilitate features of various embodiments disclosed herein. In various embodiments, the mobile application **751** may allow the device **116** to be configured to provide one or a combination of the content harvesting engine **236-1**, the content matching engine **238-1**, learning engine **239-1**, composite build engine **240-1**, and/or content splicing engine **242-1** may be provided in conjunction with the content harvesting module **236-2**, the content matching module **238-2**, composite build module **240-2**, and/or content splicing module **242-2** to implement various functionalities of the content composite subsystem **111** into the device **116**.

[0188] In various embodiments, the application **751** can be any suitable computer program that can be installed and run on the computing device **116**, and, in some embodiments, the application **751** may not be a mobile app but may be another type of application, set of applications, and/or other executable code configured to facilitate embodiments disclosed herein. The application **751** may be provided in any suitable way. For non-limiting example, the application **751** may be made available from a website, an application store, the service provider **102-1**, etc. for download to the computing device **116**; alternatively, it may be pre-installed on the computing device **116**.

[0189] In various embodiments, the computing device **116** configured with the application **751** may provide one or more display screens that may each include one or more user interface elements. A user interface may include any text, image, and/or device that can be displayed on a display screen for providing information to a user and/or for receiving user input. A user interface may include one or more widgets, text, text boxes, text fields, tables, grids, charts, hyperlinks, buttons, lists, combo boxes, checkboxes, radio buttons, and/or the like. As shown in FIG. 7, the computing device **116** includes a display **720** and input elements **732** to allow a user to input information into the computing device **116**. By way of example without limitation, the input elements **732** may include one or more of a keypad, a trackball, a touchscreen, a touchpad, a pointing device, a microphone, a voice recognition device, or any other appropriate mechanism for the user to provide input.

[0190] In various embodiments, the computing device **116** may pull content items **176**, content items **177**, and/or composites **180** from the receiver **116e** and/or from systems **102-1** and/or **103-1** via the network **120** in order to facilitate the content composites **180** to a user of the computing device **116** through the application **751**. The application **751** can include a utility that communicates with the receiver **116e** and/or from online data sources via the network **120** to control downloading, displaying, caching, and/or other operations concerning the handling of content items **176**, content items **177**, and/or composites **180**. The application **751** and the computing device **116** may cooperate with the receiver **116e** to facilitate tracking of (and customizations of user profiles and other features disclosed herein based at least in part on) user selections in response to content items displayed through the one or more additional applications.

[0191] The user selection of a user-selectable option corresponding to the application **751** may involve any one or combination of various user inputs. The user selection may be in the form of a keyboard/keypad input, a touch pad input, a track ball input, a mouse input, a voice command, etc. For example, the content item may be selected by the user by pointing and clicking on a content item. As another example, a content item may be selected by an appropriate tap or movement applied to a touch screen or pad of the computing device **116**.

[0192] The computing device **116** includes a memory **734** communicatively coupled to a processor **736** (e.g., a microprocessor) for processing the functions of the computing device **116**. The computing device **116** may include at least one antenna **738** for wireless data transfer to communicate through a cellular network, a wireless provider network, and/or a mobile operator network, such as GSM, for example without limitation, to send and receive Short Message Service (SMS) messages or Unstructured Supplementary Service Data (USSD) messages. The computing device **116** may also include a microphone **740** to allow a user to transmit voice communication through the computing device **116**, and a speaker **742** to allow the user to hear voice communication. The antenna **738** may include a cellular antenna (e.g., for sending and receiving cellular voice and data communication, such as through a network such as a 3G, 4G, or 5G network). In addition, the computing device **116** may include one or more interfaces in addition to the antenna **738**, e.g., a wireless interface coupled to an antenna.

[0193] The communications interfaces **744** can provide a near field communication interface (e.g., contactless interface, Bluetooth, optical interface, infrared interface, etc.) and/or wireless communications interfaces capable of communicating through a cellular network, such as GSM, or through Wi-Fi, such as with a wireless local area network (WLAN). Accordingly, the computing device **116** may be capable of transmitting and receiving information wirelessly through both short

range, radio frequency (RF), cellular, and Wi-Fi connections. The computing device **116** may access the network **108** through a wireless link to an access point. For example, a computing device **116** may access the network **108** through one or more access points **706**. The access points **706** may be of any suitable type or types. For example, an access point **706** may be a cellular base station, an access point for wireless local area network (e.g., a Wi-Fi access point), an access point for wireless personal area network (e.g., a Bluetooth access point), etc. The access point **706** may connect the computing device **116** to the network **108**, which may include the Internet, an intranet, a local area network, private communication networks, etc. In some embodiments, the communications interfaces **744** may allow computing device **116** to receive programming content cast from the television receiver. For example, the programming content from the television receiver may be indirectly transmitted via a local network (e.g., via Wi-Fi) or directly transmitted to the computing device via a casting device integrated with the television receiver or coupled to the television receiver (e.g., via a dongle). As another example, the television receiver may cast programming content to the computing device via a wired connection (e.g., via one or more of HDMI, USB, lightning connector, etc.). Some embodiments may provide for simulcasting such that the same programming that is being displayed on the display device is being displayed on the computing device **116** simultaneously or substantially simultaneously.

[0194] The computing device **116** can also include at least one computer-readable medium **746** coupled to the processor **736**, which stores application programs and other computer code instructions for operating the device, such as an operating system (OS) **748**. In some embodiments, the application **751** may be stored in the memory **734** and/or computer-readable media **746**. Again, the example of computing device **116** is non-limiting. Other devices, such as those disclosed herein, may be used.

[0195] The mobile computing device **736** can additionally include an integrated camera **754**, capable of capturing images and/or video, and output elements **752**. In certain embodiments, the mobile computing device **736** may include a non-transitory computer-readable storage medium, e.g., memory **734**, for storing images captured with the camera **754**. In alternative embodiments, the mobile computing device **736** receives image data from an image capture device that is not integrated with the mobile computing device **736** (e.g., from the receiver **116e** and/or the online content sources **112**).

[0196] In some embodiments, the computer-readable medium **746** can also include an image-processing engine **746(a)**. The image-processing engine **746(a)** can perform image processing of images captured by the camera **754** to perform recognition of programming content **202** in accordance with embodiments disclosed herein. The image-processing engine **746(a)** may analyze the images and generate accessible interface elements using the identified and/or analyzed images. With some embodiments, the image-processing engine **746(a)** is separate from the application **751**. In other embodiments, the application **751** may include the image-processing engine **746(a)**. In some embodiments, the computing device **116** provides the captured images to the receiver **116e**, and the receiver **116e** performs the image processing and analysis. In some embodiments, the computing device **116** provides the captured images to the service provider **102-1**, and the service provider performs the image processing and analysis.

[0197] It will be apparent to those skilled in the art that substantial variations may be made in accordance with specific requirements. For example, customized hardware might also be used, and/or particular elements might be implemented in hardware, software (including portable software, such as applets, etc.), or both. Further, connection to other computing devices such as network input/output devices may be employed.

[0198] A computer system as illustrated in FIG. **8** may be incorporated as part of the previously described computerized devices, such as a television receiver **116e**, device(s) **116**, and/or content provider system **102-1**. FIG. **8** provides a schematic illustration of one embodiment of a computer system **800** that can perform various steps of the methods provided by various embodiments. It

should be noted that FIG. 8 is meant only to provide a generalized illustration of various components, any or all of which may be utilized as appropriate. FIG. 8, therefore, broadly illustrates how individual system elements may be implemented in a relatively separated or relatively more integrated manner.

[0199] The computer system **800** is shown comprising hardware elements that can be electrically coupled via a bus **805** (or may otherwise be in communication, as appropriate). The hardware elements may include one or more processors **810**, including without limitation one or more general-purpose processors and/or one or more special-purpose processors (such as digital signal processing chips, graphics acceleration processors, video decoders, and/or the like); one or more input devices **815**, which can include without limitation a mouse, a keyboard, remote control, and/or the like; and one or more output devices **820**, which can include without limitation a display device, a printer, and/or the like.

[0200] The computer system **800** may further include (and/or be in communication with) one or more non-transitory storage devices **825**, which can comprise, without limitation, local and/or network accessible storage, and/or can include, without limitation, a disk drive, a drive array, an optical storage device, a solid-state storage device, such as a random access memory (“RAM”), and/or a read-only memory (“ROM”), which can be programmable, flash-updateable and/or the like. Such storage devices may be configured to implement any appropriate data stores, including without limitation, various file systems, database structures, and/or the like.

[0201] The computer system **800** might also include a communications subsystem **830**, which can include without limitation a modem, a network card (wireless or wired), an infrared communication device, a wireless communication device, and/or a chipset (such as a Bluetooth™ device, an 802.11 device, a Wi-Fi device, a WiMAX device, cellular communication device, etc.), and/or the like. The communications subsystem **830** may permit data to be exchanged with a network (such as the network described below, to name one example), other computer systems, and/or any other devices described herein. In many embodiments, the computer system **800** will further comprise a working memory **835**, which can include a RAM or ROM device, as described above.

[0202] The computer system **800** also can comprise software elements, shown as being currently located within the working memory **835**, including an operating system **840**, device drivers, executable libraries, and/or other code, such as one or more application programs **845**, which may comprise computer programs provided by various embodiments, and/or may be designed to implement methods, and/or configure systems, provided by other embodiments, as described herein. Merely by way of example, one or more procedures described with respect to the method(s) discussed above might be implemented as code and/or instructions executable by a computer (and/or a processor within a computer); in an aspect, then, such code and/or instructions can be used to configure and/or adapt a general purpose computer (or other device) to perform one or more operations in accordance with the described methods.

[0203] A set of these instructions and/or code might be stored on a non-transitory computer-readable storage medium, such as the non-transitory storage device(s) **825** described above. In some cases, the storage medium might be incorporated within a computer system, such as computer system **800**. In other embodiments, the storage medium might be separate from a computer system (e.g., a removable medium, such as a compact disc), and/or provided in an installation package, such that the storage medium can be used to program, configure, and/or adapt a general purpose computer with the instructions/code stored thereon. These instructions might take the form of executable code, which is executable by the computer system **800** and/or might take the form of source and/or installable code, which, upon compilation and/or installation on the computer system **800** (e.g., using any of a variety of generally available compilers, installation programs, compression/decompression utilities, etc.), then takes the form of executable code.

[0204] As mentioned above, in one aspect, some embodiments may employ a computer system (such as the computer system **800**) to perform methods in accordance with various embodiments of

the invention. According to a set of embodiments, some or all of the procedures of such methods are performed by the computer system **800** in response to processor **810** executing one or more sequences of one or more instructions (which might be incorporated into the operating system **840** and/or other code, such as an application program **845**) contained in the working memory **835**. Such instructions may be read into the working memory **835** from another computer-readable medium, such as one or more of the non-transitory storage device(s) **825**. Merely by way of example, execution of the sequences of instructions contained in the working memory **835** might cause the processor(s) **810** to perform one or more procedures of the methods described herein.

[0205] The terms “machine-readable medium,” “machine-readable media,” “computer-readable storage medium,” “computer-readable storage media,” “computer-readable medium,” “computer-readable media,” “processor-readable medium,” “processor-readable media,” and/or like terms as used herein, refer to any medium that participates in providing data that causes a machine to operate in a specific fashion. These mediums may be non-transitory. In an embodiment implemented using the computer system **800**, various computer-readable media might be involved in providing instructions/code to processor(s) **810** for execution and/or might be used to store and/or carry such instructions/code. In many implementations, a computer-readable medium is a physical and/or tangible storage medium. Such a medium may take the form of a non-volatile media or volatile media. Non-volatile media include, for example, optical and/or magnetic disks, such as the non-transitory storage device(s) **825**. Volatile media include, without limitation, dynamic memory, such as the working memory **835**.

[0206] Common forms of physical and/or tangible computer-readable media include, for example, a floppy disk, a flexible disk, hard disk, magnetic tape, or any other magnetic medium, a CD-ROM, any other optical medium, any other physical medium with patterns of marks, a RAM, a PROM, EPROM, a FLASH-EPROM, any other memory chip or cartridge, or any other medium from which a computer can read instructions and/or code.

[0207] Various forms of computer-readable media may be involved in carrying one or more sequences of one or more instructions to the processor(s) **810** for execution. Merely by way of example, the instructions may initially be carried on a magnetic disk and/or optical disc of a remote computer. A remote computer might load the instructions into its dynamic memory and send the instructions as signals over a transmission medium to be received and/or executed by the computer system **800**.

[0208] The communications subsystem **830** (and/or components thereof) generally will receive signals, and the bus **805** then might carry the signals (and/or the data, instructions, etc. carried by the signals) to the working memory **835**, from which the processor(s) **810** retrieves and executes the instructions. The instructions received by the working memory **835** may optionally be stored on a non-transitory storage device **825** either before or after execution by the processor(s) **810**.

[0209] It should further be understood that the components of computer system **800** can be distributed across a network. For example, some processing may be performed in one location using a first processor while other processing may be performed by another processor remote from the first processor. Other components of computer system **800** may be similarly distributed. As such, computer system **800** may be interpreted as a distributed computing system that performs processing in multiple locations. In some instances, computer system **800** may be interpreted as a single computing device, such as a distinct laptop, desktop computer, or the like, depending on the context.

[0210] The methods, systems, and devices discussed above are examples. Various configurations may omit, substitute, or add various procedures or components as appropriate. For instance, in alternative configurations, the methods may be performed in an order different from that described, and/or various stages may be added, omitted, and/or combined. Also, features described with respect to certain configurations may be combined in various other configurations. Different aspects and elements of the configurations may be combined in a similar manner. Also, technology

evolves and, thus, many of the elements are examples and do not limit the scope of the disclosure or claims.

[0211] Specific details are given in the description to provide a thorough understanding of example configurations (including implementations). However, configurations may be practiced without these specific details. For example, well-known circuits, processes, algorithms, structures, and techniques have been shown without unnecessary detail in order to avoid obscuring the configurations. This description provides example configurations only, and does not limit the scope, applicability, or configurations of the claims. Rather, the preceding description of the configurations will provide those skilled in the art with an enabling description for implementing described techniques. Various changes may be made in the function and arrangement of elements without departing from the spirit or scope of the disclosure.

[0212] Also, configurations may be described as a process which is depicted as a flow diagram or block diagram. Although each may describe the operations as a sequential process, many of the operations can be performed in parallel or concurrently. In addition, the order of the operations may be rearranged. A process may have additional steps not included in the figure. Furthermore, examples of the methods may be implemented by hardware, software, firmware, middleware, microcode, hardware description languages, or any combination thereof. When implemented in software, firmware, middleware, or microcode, the program code or code segments to perform the necessary tasks may be stored in a non-transitory computer-readable medium such as a storage medium. Processors may perform the described tasks.

[0213] Having described several example configurations, various modifications, alternative constructions, and equivalents may be used without departing from the spirit of the disclosure. For example, the above elements may be components of a larger system, wherein other rules may take precedence over or otherwise modify the application of the invention. Also, a number of steps may be undertaken before, during, or after the above elements are considered.

[0214] Furthermore, the example embodiments described herein may be implemented as logical operations in a computing device in a networked computing system environment. The logical operations may be implemented as: (i) a sequence of computer implemented instructions, steps, or program modules running on a computing device; and (ii) interconnected logic or hardware modules running within a computing device.

[0215] Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the specific features or acts described above. Rather, the specific features and acts described above are disclosed as example forms of implementing the claims.

[0216] Also, the terms in the claims have their plain, ordinary meaning unless otherwise explicitly and clearly defined by the patentee. The indefinite articles “a” or “an,” as used in the claims, are defined herein to mean one or more than one of the element that the particular article introduces; and subsequent use of the definite article “the” is not intended to negate that meaning. Furthermore, the use of ordinal number terms, such as “first,” “second,” etc., to clarify different elements in the claims is not intended to impart a particular position in a series, or any other sequential character or order, to the elements to which the ordinal number terms have been applied.

Claims

1. (canceled)

2. A system comprising: one or more processing devices; and memory communicatively coupled with and readable by the one or more processing devices and having stored therein processor-readable instructions which, when executed by the one or more processing devices, cause the system to perform operations comprising: receiving a first content item that comprises audio content and video content; transferring the first content item for display with an endpoint media

device; processing at least one electronic signal received by the system that is indicative of execution of at least one operation of a set of one or more operations relating to the first content item consequent to the display of the first content item with the endpoint media device; mapping the at least one electronic signal to the first content item and a service provider system, where the set of one or more operations corresponds to interaction with a service provider system; and biasing, based at least in part on the mapping, subsequent provisioning of one or more content items toward content items associated with the service provider system, where the biasing the subsequent provisioning of the one or more content items comprises: identifying, based at least in part on the mapping, a second content item as being associated with the service provider system; and transferring the second content item so that the second content item is accessible with the endpoint media device.

3. The system as recited in claim 2, where the set of one or more operations corresponds to initiating an interactive process based at least in part on one or more selections of one or more user-selectable options presented by the first content item.

4. The system as recited in claim 2, where the set of one or more operations corresponds to initiating an interactive process to redeem a redeemable content item, use a matrix code, use a promotional code, and/or order or purchase a product or a service that is not audiovisual content based at least in part on one or more user selections of one or more user-selectable options presented by the first content item.

5. The system as recited in claim 2, where the biasing is further based at least in part on identifying a pattern of interacting with content items associated with the service provider system.

6. The system as recited in claim 2, where the identifying the second content item comprises selecting the second content item from a plurality of content items associated with a plurality of service providers systems.

7. The system as recited in claim 2, where the biasing the subsequent provisioning of the one or more content items corresponds to prioritizing use of the one or more content items over content items associated with one or more other service provider systems.

8. The system as recited in claim 7, where the prioritizing use of the one or more content items over content items comprises prioritizing one or more attempts to pull the one or more content items from the service provider system.

9. A method comprising: receiving, by a processing system comprising one or more processing devices, a first content item that comprises audio content and video content; transferring, by the processing system, the first content item for display with an endpoint media device; processing, by the processing system, at least one electronic signal received by the system that is indicative of execution of at least one operation of a set of one or more operations relating to the first content item consequent to the display of the first content item with the endpoint media device; mapping, by the processing system, the at least one electronic signal to the first content item and a service provider system, where the set of one or more operations corresponds to interaction with a service provider system; and biasing, by the processing system and based at least in part on the mapping, subsequent provisioning of one or more content items toward content items associated with the service provider system, where the biasing the subsequent provisioning of the one or more content items comprises: identifying, based at least in part on the mapping, a second content item as being associated with the service provider system; and transferring the second content item so that the second content item is accessible with the endpoint media device.

10. The method as recited in claim 9, where the set of one or more operations corresponds to initiating an interactive process based at least in part on one or more selections of one or more user-selectable options presented by the first content item.

11. The method as recited in claim 9, where the set of one or more operations corresponds to initiating an interactive process to redeem a redeemable content item, use a matrix code, use a promotional code, and/or order or purchase a product or a service that is not audiovisual content

based at least in part on one or more user selections of one or more user-selectable options presented by the first content item.

12. The method as recited in claim 9, where the biasing is further based at least in part on identifying a pattern of interacting with content items associated with the service provider system.

13. The method as recited in claim 9, where the identifying the second content item comprises selecting the second content item from a plurality of content items associated with a plurality of service providers systems.

14. The method as recited in claim 9, where the biasing the subsequent provisioning of the one or more content items corresponds to prioritizing use of the one or more content items over content items associated with one or more other service provider systems.

15. The method as recited in claim 14, where the prioritizing use of the one or more content items over content items comprises prioritizing one or more attempts to pull the one or more content items from the service provider system.

16. One or more non-transitory, machine-readable media having machine-readable instructions thereon which, when executed by one or more processing devices, cause a system to perform operations comprising: receiving a first content item that comprises audio content and video content; transferring the first content item for display with an endpoint media device; processing at least one electronic signal received by the system that is indicative of execution of at least one operation of a set of one or more operations relating to the first content item consequent to the display of the first content item with the endpoint media device; mapping the at least one electronic signal to the first content item and a service provider system, where the set of one or more operations corresponds to interaction with a service provider system; and biasing, based at least in part on the mapping, subsequent provisioning of one or more content items toward content items associated with the service provider system, where the biasing the subsequent provisioning of the one or more content items comprises: identifying, based at least in part on the mapping, a second content item as being associated with the service provider system; and transferring the second content item so that the second content item is accessible with the endpoint media device.

17. The one or more non-transitory, machine-readable media as recited in claim 16, where the set of one or more operations corresponds to initiating an interactive process based at least in part on one or more selections of one or more user-selectable options presented by the first content item.

18. The one or more non-transitory, machine-readable media as recited in claim 16, where the set of one or more operations corresponds to initiating an interactive process to redeem a redeemable content item, use a matrix code, use a promotional code, and/or order or purchase a product or a service that is not audiovisual content based at least in part on one or more user selections of one or more user-selectable options presented by the first content item.

19. The one or more non-transitory, machine-readable media as recited in claim 16, where the biasing is further based at least in part on identifying a pattern of interacting with content items associated with the service provider system.

20. The one or more non-transitory, machine-readable media as recited in claim 16, where the identifying the second content item comprises selecting the second content item from a plurality of content items associated with a plurality of service providers systems.

21. The one or more non-transitory, machine-readable media as recited in claim 16, where the biasing the subsequent provisioning of the one or more content items corresponds to prioritizing use of the one or more content items over content items associated with one or more other service provider systems.
