

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280375

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

CHAI; Li et al.

METHOD AND DEVICE FOR SCHEDULING AND INFORMATION TRANSMISSION, RELATED APPARATUS, AND STORAGE MEDIUM

Abstract

Disclosed are a method and device for scheduling and transmission, a terminal, a communication node, and a storage medium. The method includes: a first communication node acquires clock information; and sends m types of clock information to a terminal on the basis of the acquired clock information, where m is greater than or equal to 1.

Inventors: CHAI; Li (Beijing, CN), WU; Min (Beijing, CN)

Applicant: CHINA MOBILE COMMUNICATION CO., LTD RESEARCH INSTITUTE (Beijing, CN); CHINA MOBILE COMMUNICATIONS GROUP CO., LTD. (Beijing, CN)

Family ID: 72966701

Appl. No.: 19/213090

Filed: May 20, 2025

Foreign Application Priority Data

CN 201910364283.0

Apr. 30, 2019

Related U.S. Application Data

parent US division 17607119 20211028 parent-grant-document US 12349084 WO division PCT/CN2020/087052 20200426 child US 19213090

Publication Classification

Int. Cl.: H04W56/00 (20090101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This is a divisional application of U.S. patent application Ser. No. 17/607,119, filed on Oct. 28, 2021, which is a national phase application of International Application No. PCT/CN2020/087052, filed on Apr. 26, 2020, which is based upon and claims priority to Chinese Patent Application No. 201910364283.0, filed on Apr. 30, 2019. The disclosures of U.S. patent application Ser. No. 17/607,119, International Application No. PCT/CN2020/087052, and Chinese Patent Application No. 201910364283.0 are hereby incorporated by reference in their entireties.

TECHNICAL FIELD

[0002] The disclosure relates to the field of wireless communications, and in particular to a scheduling and information transmission method and apparatus, a related device, and a storage medium.

BACKGROUND

[0003] In order to promote the development of the Industrial Internet of Things (IIoT), a Time Sensitive Network (TSN) is created to establish a “general” time sensitive mechanism for Ethernet protocols to ensure the time certainty of network data transmission.

[0004] When a TSN service passes through a mobile communication network, how to select a logical channel to ensure the utilization ratio of radio resource resources and the performance of User Equipment (UE) running services is an urgent problem to be solved.

SUMMARY

[0005] To solve the related technical problems, embodiments of the disclosure provide a scheduling and information transmission method and apparatus, a related device, and a storage medium.

[0006] A technical solution in the embodiments of the disclosure is implemented as follows.

[0007] The embodiments of the disclosure provide an information transmission method, which is applied to a first communication node, and may include the following operations.

[0008] Clock information is acquired.

[0009] m types of clock information are sent to a terminal based on the acquired clock information, where m is greater than or equal to 1.

[0010] In the above solution, the operation that the clock information is acquired may include at least one of the following: [0011] clock information is acquired from a core network; [0012] clock information is acquired from an adjacent communication node; [0013] clock information sent by the terminal is received; [0014] capability information reported by the terminal is received, the capability information indicating clock related capability supported by the terminal; or [0015] clock information is acquired from a specific network system.

[0016] In the above solution, the capability information includes at least one of the following:

[0017] a clock type supported by the terminal; or [0018] at least one of synchronization precision information or synchronization granularity information supported by the terminal.

[0019] In the above solution, the clock information sent by the terminal includes: clock information of a system to which the terminal is being connected.

[0020] In the above solution, the clock information includes at least one of the following: [0021] time information of Universal Time Coordinated (UTC); [0022] an offset between the UTC and GPS; [0023] information about a relationship between Daylight Saving Time (DST) and local time; [0024] an offset between the UTC and the local time; [0025] an offset between the UTC and a

specific network; [0026] a mapping relationship between the UTC and a System Frame Number (SFN); [0027] indication information about whether the clock is a master clock; [0028] level information of the clock; [0029] information about an offset with respect to a reference time of a specific clock type; [0030] synchronization precision information of the clock; [0031] synchronization granularity information of the clock; [0032] synchronization inaccuracy information; [0033] type information of the clock; [0034] reference time information; [0035] position relationship indication information of the reference time information and a received signaling; or [0036] time update period information of the clock.

[0037] In the above solution, the reference time information includes at least one of the following: [0038] reference system radio frame information; [0039] reference subframe information; [0040] reference slot information; and [0041] reference time symbol information.

[0042] The embodiments of the disclosure also provide an information transmission method. The method is applied to a terminal, and may include the following operations.

[0043] At least one of capability information or clock information is sent to a first communication node. The capability information indicates clock related capability supported by the terminal.

[0044] m types of clock information sent by the first communication node are received, where m is greater than or equal to 1.

[0045] In the above solution, the capability information includes at least one of the following:

[0046] a clock type supported by the terminal; or [0047] at least one of synchronization precision information or synchronization granularity information supported by the terminal.

[0048] In the above solution, the sent clock information includes clock information of a system to which the terminal is being connected.

[0049] In the above solution, the clock information includes at least one of the following: [0050] time information of UTC; [0051] an offset between the UTC and GPS; [0052] information about a relationship between DST and local time; [0053] an offset between the UTC and the local time; [0054] an offset between the UTC and a specific network; [0055] a mapping relationship between the UTC and an SFN; [0056] indication information about whether the clock is the master clock; [0057] level information of the clock; [0058] information about an offset with respect to a reference time of a specific clock type; [0059] synchronization precision information of the clock; [0060] synchronization granularity information of the clock; [0061] synchronization inaccuracy information; [0062] type information of the clock; [0063] reference time information; [0064] position relationship indication information of the reference time information and a received signaling; or [0065] time update period information of the clock.

[0066] In the above solution, the reference time information includes at least one of the following: [0067] reference system radio frame information; [0068] reference subframe information; [0069] reference slot information; or [0070] reference time symbol information.

[0071] The embodiments of the disclosure also provide a scheduling method. The method is applied to a terminal, and may include the following operations.

[0072] First information sent by the first communication node is received, the first information including at least one granted radio resource.

[0073] Time information of an on duration and a suspended duration of at least one granted radio resource is acquired.

[0074] At least one granted radio resource is selected for at least one logical channel.

[0075] At least one of specific logical channel data or signaling is sent or received on an available resource indicated by the time information of the on duration of the granted radio resource.

[0076] In the above solution, the operation that at least one granted radio resource is selected for at least one logical channel may include the following actions.

[0077] At least one granted radio resource is selected for at least one logical channel based on at least one of the following information: [0078] time information of a service corresponding to the at least one logical channel; a logical channel selection result of a data packet cached by the at least

one logical channel; or fourth information representing at least one corresponding granted radio resource configured by each logical channel and/or a Radio Network Temporary Identifier (RNTI) configured by at least one logical channel; and [0079] sending or reception of at least one of data or signaling on a resource indicated by the time information of the suspended duration of the granted radio resource is stopped.

[0080] In the above solution, when the time information of the on duration and the suspended duration of each granted radio resource is acquired, the method may include the following operation.

[0081] The time information of the on duration and the time information of the suspended duration of the corresponding granted radio resource that is configured through Radio Resource Control (RRC) dedicated signaling is received.

[0082] The embodiments of the disclosure also provide an information transmission method. The method is applied to a first communication node, and may include the following operation.

[0083] Time information of an on duration and time information of a suspended duration of a corresponding granted radio resource is configured for a terminal through RRC dedicated signaling.

[0084] The embodiments of the disclosure also provide a scheduling method. The method is applied to a terminal, and may include the following operations.

[0085] Configuration information of at least one set of configured grant that a first communication node configures for a used traffic pattern is received.

[0086] An offset sent by the first communication node is received.

[0087] An offset of a configured grant resource is updated with the received offset.

[0088] In the above solution, the operation that the offset sent by the first communication node is received may include the following action.

[0089] The offset sent by the first communication node is received through Downlink Control Information (DCI).

[0090] The embodiments of the disclosure also provide a scheduling method. The method is applied to a first communication node, and may include the following operations.

[0091] A traffic pattern used by the terminal is acquired.

[0092] At least one set of configured grant for the used traffic pattern is configured for the terminal.

[0093] An offset is sent to the terminal, the sent offset being used for the terminal to update an offset of a configured grant resource.

[0094] In the above solution, the operation that the traffic pattern used by the terminal is acquired may include one of the following: [0095] the traffic pattern used by the terminal is acquired from the core network; and [0096] the traffic pattern used by the terminal is acquired from the terminal.

[0097] In the above solution, the operation that the offset is sent to the terminal may include the following action.

[0098] The offset is sent to the terminal through DCI.

[0099] The embodiments of the disclosure also provide a scheduling method. The method is applied to a terminal, and may include the following operations.

[0100] Time information of a service corresponding to at least one logical channel is determined.

[0101] First information sent by a first communication node is received, the first information including a granted radio resource.

[0102] At least one logical channel is selected for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.

[0103] In the above solution, the operation that the at least one logical channel is selected for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel may include the following action.

[0104] When a priority of a first logical channel corresponding to a first data packet is lower than that of a second logical channel corresponding to a second data packet, and a time characteristic of the granted radio resource matches better with a time characteristic represented by time information corresponding to the first logical channel, the first data packet corresponding to the first logical channel is preferentially scheduled with the granted radio resource; [0105] or, when the priority of the first logical channel corresponding to the first data packet is the same as that of the second logical channel corresponding to the second data packet, and the time characteristic of the granted radio resource matches better with the time characteristic represented by the time information corresponding to the first logical channel, the first data packet corresponding to the first logical channel is preferentially scheduled with the granted radio resource.

[0106] In the above solution, the operation that the at least one logical channel is selected for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel may include the following action.

[0107] A data packet corresponding to at least one specific logical channel and preferentially scheduled with the granted radio resource is determined according to a first weight and third information.

[0108] The first weight is a predefined weight or a weight of a matching degree, indicated by the first communication node, between time characteristic of the granted radio resource and time characteristic represented by the time information corresponding to the corresponding logical channel.

[0109] The third information includes at least one of the following information: [0110] a priority of logical information; [0111] a subcarrier spacing; or [0112] a duration of a Physical Uplink Shared Channel (PUSCH).

[0113] In the above solution, the granted radio resource includes at least one of the following: [0114] a dynamically scheduled granted radio resource; [0115] a Configured Grant (CG) radio resource; or [0116] a semi-persistent scheduling (SPS) radio resource.

[0117] In the above solution, the time information of the service corresponding to the logical channel includes at least one of the following: [0118] clock information of the service corresponding to the logical channel; or [0119] time characteristic information of the service corresponding to the logical channel.

[0120] In the above solution, the time characteristic information includes at least one of the following: [0121] sending time information of a data packet; [0122] arrival time information of the data packet; [0123] sending period information of the data packet; [0124] sending duration information of the data packet in a period; [0125] length information of the data packet; [0126] duration information of the data packet residing in a cache; [0127] survival time information of the data packet; [0128] sending state information of the first n data packets of the data packet, where n is a positive integer; [0129] a delay requirement of the data packet; [0130] a value of k in Hybrid Automatic Repeat Request (HARQ) timing of the data packet; [0131] a reliability requirement of the data packet; [0132] an RNTI for scheduling and matching of the data packet; or [0133] a transmit power requirement of the data packet.

[0134] In the above solution, when the time information of the service corresponding to each logical channel is determined, the method includes at least one of the following operations.

[0135] The time information of the service corresponding to the corresponding logical channel is received from the first communication node.

[0136] The time information of the service corresponding to the corresponding logical channel is determined according to the learned time characteristic information of the service corresponding to the logical channel.

[0137] In the above solution, the time information of the service corresponding to the corresponding logical channel is received from the first communication node through one of the

following signaling: [0138] DCI of a Uplink (UL) grant; [0139] DCI of Downlink (DL) scheduling; [0140] RRC signaling carrying grand information of UL configuration; [0141] signaling carrying SPS information of DL configuration; [0142] RRC signaling carrying configuration information of the logical channel; and [0143] RRC signaling carrying absolute time information.

[0144] In the above solution, the operation that the time information of the service corresponding to the at least one logical channel is determined may include the following action.

[0145] Second information is received through one of the following signaling: [0146] DCI of a UL grant; [0147] DCI of DL scheduling; [0148] RRC signaling carrying grand information of UL configuration; [0149] a signaling carrying SPS information of DL configuration; [0150] RRC signaling carrying configuration information of the logical channel; and [0151] RRC signaling carrying absolute time information; [0152] The time information of the service corresponding to the logical channel is determined by using the second information.

[0153] The second information represents at least one of the following: [0154] an indicated resource is aligned with a specific clock boundary or has a minimum offset from the specific clock boundary; or [0155] a period of the indicated resource has a multiple relationship with a period of the specific clock, or an offset of a period value of the indicated resource is the minimum.

[0156] In the above solution, the method may further include the following operation.

[0157] The time information of the service corresponding to at least one logical channel is updated.

[0158] In the above solution, when the time information of the service corresponding to the logical channel is updated, the method may include the following operations.

[0159] Updated time-related information sent by the first communication node is received.

[0160] The time information of the service corresponding to the corresponding logical channel is updated by using the received updated time-related information.

[0161] In the above solution, the updated time-related information sent by the first communication node is received through one of the following signaling: [0162] tRRC signaling; and [0163] a Media Access Control (MAC) Control Element (CE).

[0164] In the above solution, the time-related information includes at least one of the following: [0165] clock information; or [0166] a delta value of an offset between the time in the previous clock information and reference time.

[0167] In the above solution, the time information of the service corresponding to the logical channel includes at least one of the following: [0168] time information of UTC; [0169] an offset between the UTC and GPS; [0170] information about the relationship between DST and local time; [0171] an offset between the UTC and the local time; [0172] an offset between the UTC and a specific network; [0173] a mapping relationship between the UTC and an SFN; [0174] indication information about whether the clock is a master clock; [0175] level information of the clock; [0176] information about an offset with respect to reference time of a specific clock type; [0177] synchronization precision information of the clock; [0178] synchronization granularity information of the clock; [0179] synchronization inaccuracy information; [0180] type information of the clock; [0181] reference time information; [0182] the position relationship indication information of the reference time information and a received signaling; or [0183] time update period information of the clock.

[0184] In the above solution, the reference time information includes at least one of the following: [0185] reference system radio frame information; [0186] reference subframe information; [0187] reference slot information; or [0188] reference time symbol information.

[0189] The embodiments of the disclosure also provide an information transmission method. The method is applied to a first communication node, and may include one of the following operations.

[0190] Time information of a service corresponding to a corresponding logical channel is sent to a terminal.

[0191] Second information is sent to the terminal. The second information represents at least one of

the following: [0192] an indicated resource is aligned with a specific clock boundary or has the minimum offset from the specific clock boundary; or [0193] a period of the indicated resource has a multiple relationship with a period of a specific clock, or an offset of the period value of the indicated resource is the minimum.

[0194] In the above solution, the corresponding information is sent through one of the following signaling: [0195] DCI of a UL grant; [0196] DCI of DL scheduling; [0197] RRC signaling carrying grand information of UL configuration; [0198] a signaling carrying SPS information of DL configuration; [0199] RRC signaling carrying configuration information of the logical channel; and [0200] RRC signaling carrying absolute time information.

[0201] In the above solution, the method may further include the following operation.

[0202] Updated time-related information is sent to the terminal.

[0203] The embodiments of the present disclosure also provide an information transmission apparatus, which may include a second acquiring unit and a third sending unit.

[0204] The second acquiring unit is configured to acquire clock information.

[0205] The third sending unit is configured to send m types of clock information to the terminal based on the acquired clock information, where m is greater than or equal to 1.

[0206] The embodiments of the present disclosure also provide an information transmission apparatus, which may include a fourth sending unit and a fourth receiving unit.

[0207] The fourth sending unit is configured to send at least one of capability information or clock information to a first communication node, the capability information indicating clock related capability supported by the terminal; and [0208] The fourth receiving unit is configured to receive m types of clock information sent by the first communication node, where m is greater than or equal to 1.

[0209] The embodiments of the present disclosure also provide a scheduling apparatus, which may include a second receiving unit, an acquiring unit, a second determining unit and a transmitting unit.

[0210] The second receiving unit is configured to receive first information sent by a first communication node, the first information including at least one granted radio resource.

[0211] The acquiring unit is configured to acquire time information of an on duration and a suspended duration of the at least one granted radio resource.

[0212] The second determining unit is configured to select at least one granted radio resource for at least one logical channel.

[0213] The transmitting unit is configured to send or receive at least one of specific logical channel data or signaling on an available resource indicated by the time information of the on duration of the granted radio resource.

[0214] In the above solution, the transmitting unit is further configured to stop sending or receiving at least one of data or signaling on a resource indicated by the time information of the suspended duration of the granted radio resource.

[0215] The embodiments of the disclosure also provide an information transmission apparatus, which may include a second sending unit.

[0216] The second sending unit is configured to configure time information of an on duration and time information of a suspended duration of the corresponding granted radio resource for a terminal through RRC dedicated signaling.

[0217] The embodiments of the present disclosure also provide a scheduling apparatus, which may include a third receiving unit and a processing unit.

[0218] The third receiving unit is configured to receive configuration information of at least one set of configured grant that a first communication node configures for a used traffic pattern, and receive an offset sent by the first communication node.

[0219] The processing unit is configured to update an offset of the configured grant resource with the received offset.

[0220] The embodiments of the present disclosure also provide a scheduling method, which may include a first acquiring unit, a configuring unit and an updating unit.

[0221] The first acquiring unit is configured to acquire a traffic pattern used by the terminal.

[0222] The configuring unit is configured to configure for the terminal at least one set of configured grant for the used traffic pattern.

[0223] The updating unit is configured to send an offset to the terminal, the sent offset being used for the terminal to update an offset of the configured grant resource.

[0224] The embodiments of the present disclosure also provide a scheduling apparatus, which may include a first determining unit, a first receiving unit and a first selecting unit.

[0225] The first determining unit is configured to determine time information of a service corresponding to at least one logical channel.

[0226] The first receiving unit is configured to receive first information sent by a first communication node, the first information including a granted radio resource.

[0227] The first selecting unit is configured to select at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.

[0228] In the above solution, the first determining unit is further configured to update the time information of the service corresponding to the at least one logical channel.

[0229] The embodiments of the disclosure also provide an information transmission apparatus, which may include a first sending unit.

[0230] The first sending unit is configured to: [0231] send time information of a service corresponding to a corresponding logical channel to a terminal; or, [0232] send second information to the terminal. The second information represents at least one of the following: [0233] an indicated resource is aligned with a specific clock boundary or has the minimum offset from the specific clock boundary; or [0234] a period of the indicated resource has a multiple relationship with a period of a specific clock, or an offset of a period value of the indicated resource is the minimum.

[0235] The embodiments of the disclosure also provide a terminal, which may include a first communication interface and a first processor.

[0236] The first communication interface is configured to receive configuration information of at least one set of configured grant that a first communication node configures for a used traffic pattern, and receive an offset sent by the first communication node. The first processor is configured to update an offset of the configured grant resource with the received offset.

[0237] Or, [0238] the first communication interface is configured to send at least one of capability information or clock information to the first communication node, the capability information indicating clock related capability supported by the terminal, and receive m types of clock information sent by the first communication node, where m is greater than or equal to 1.

[0239] The embodiments of the disclosure also provide a communication node, which may include a second communication interface and a second processor.

[0240] The second processor is configured to acquire a traffic pattern used by a terminal, and configure for the terminal at least one set of configured grant for the used traffic pattern through the second communication interface; the second communication interface is configured to send an offset to the terminal, the sent offset being used for the terminal to update an offset of a configured grant resource.

[0241] Or, [0242] the second communication interface is configured to acquire clock information, and send m types of clock information to the terminal based on the acquired clock information, where m is greater than or equal to 1.

[0243] The embodiments of the present disclosure also provide a terminal, which may include a first processor and a first communication interface.

[0244] The first processor is configured to determine time information of a service corresponding to at least one logical channel.

[0245] The first communication interface is configured to receive first information sent by a first communication node, the first information including a granted radio resource.

[0246] The first processor is further configured to select at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.

[0247] In the above solution, the first processor is further configured to update the time information of the service corresponding to at least one logical channel.

[0248] The embodiments of the disclosure also provide a communication node, which may include a second processor and a second communication interface.

[0249] The second communication interface is configured to: send time information of a service corresponding to a corresponding logical channel to a terminal under control of the second processor; [0250] or, send second information to the terminal under the control of the second processor. The second information represents at least one of the following: [0251] an indicated resource is aligned with a specific clock boundary or has the minimum offset from the specific clock boundary; or [0252] a period of the indicated resource has a multiple relationship with a period of the specific clock, or an offset of a period value of the indicated resource is the minimum.

[0253] The embodiments of the present disclosure also provide a terminal, which may include a first communication interface and a first processor.

[0254] The first communication interface is configured to receive first information sent by a first communication node, the first information including at least one granted radio resource.

[0255] The first processor is configured to acquire time information of an on duration and a suspended duration of the at least one granted radio resource, and select at least one granted radio resource for at least one logical channel.

[0256] The first communication interface is further configured to send or receive at least one of specific logical channel data or signaling on an available resource indicated by the time information of the on duration of the granted radio resource.

[0257] In the above solution, the first communication interface is further configured to stop sending or receiving at least one of data or signaling on the resource indicated by the time information of the suspended duration of the granted radio resource.

[0258] The embodiments of the disclosure also provide a communication node, which may include a second processor and a second communication interface.

[0259] The second processor is configured to configure, by using the second communication interface, time information of an on duration and time information of a suspended duration of the corresponding granted radio resource for the terminal through RRC dedicated signaling.

[0260] The embodiments of the disclosure also provide a terminal, which may include a first processor and a first memory configured to store a computer program capable of running in the processor.

[0261] The first processor is configured to, when running the computer program, execute the operations of any method for the terminal side.

[0262] The embodiments of the disclosure also provide a communication node, which may include a second processor and a second memory configured to store a computer program capable of running in the processor.

[0263] The second processor is configured to, when running the computer program, execute the operations of any method for the first communication node side.

[0264] The embodiments of the disclosure also provide a storage medium having a computer program stored thereon. When executed by the processor, the computer program implements the operations of any method for the terminal side, or implements the operations of any method for the first communication node side.

[0265] With the scheduling and information transmission method and apparatus, the related device and the storage medium provided by the embodiments of the disclosure, the terminal determines

the time information of the service corresponding to at least one logical channel, receives the first information sent by the first communication node, the first information including the granted radio resource, and selects at least one logical channel for the granted radio resource based on the time information of the service corresponding to at least one logical channel in combination with the configuration parameters of at least one logical channel. The logical channel is selected by using the time information of the service, which improves the accuracy of logical channel selection, and fully ensures the utilization ratio of radio resources and the performance of a terminal running services.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0266] FIG. 1 is a flowchart of a scheduling method according to an embodiment of the disclosure.

[0267] FIG. 2 is a flowchart of another scheduling method according to an embodiment of the disclosure.

[0268] FIG. 3 is a schematic diagram of a scheduling process according to an embodiment of the disclosure.

[0269] FIG. 4 is a structural schematic diagram of a scheduling apparatus according to an embodiment of the disclosure.

[0270] FIG. 5 is a structural schematic diagram of another scheduling apparatus according to an embodiment of the disclosure.

[0271] FIG. 6 is a structural schematic diagram of a terminal according to an embodiment of the disclosure.

[0272] FIG. 7 is a structural schematic diagram of a communication node according to an embodiment of the disclosure.

DETAILED DESCRIPTION

[0273] The disclosure is further described below in combination with the accompanying drawings and embodiments.

[0274] In the related art, a TSN supports real-time control and synchronization, for example, between sport applications and robots, through the Ethernet. The TSN may also support other data communications common in manufacturing applications, which promotes convergence between Information Technology (IT) and Operation Technology (OT). The TSN will bring a world of smarter, virtually-connected devices and infrastructure. Although a plurality of data collected by an industrial sensor and a control system in the IIoT is not time-sensitive, there is a mass of mission-critical, time-sensitive data that must be transmitted and shared within the strict range of delay and reliability. For a general clock used for transmission time scheduling, delay regulation, reserved bandwidth and redundancy configuration, such a requirement for the TSN enables the TSN to ensure the precision of time synchronization and thus support the synchronization of multiple data streams.

[0275] When a TSN service does not pass through a network cables, but through a fifth generation mobile communication technology (5G) system, the 5G system is connected with multiple TSNs, each TSN system has its own clock, and the 5G system also has a clock based on the Global Navigation Satellite System (GNSS). Timing of a wireless network for mobile communications mostly relies on the clock based on the GNSS, so a base station can only obtain the clock based on the GNSS, but not a clock of the TSN, and cannot schedule the TSN service based on the clock of the TSN. Thus, the utilization ratio of radio resources and the performance of UE running services cannot be ensured. The GNSS refers to all satellite navigation systems, including the global, regional and enhanced satellite navigation systems, such as the Global Positioning System (GPS) of the United States and the Beidou navigation satellite system of China, and related augmentation

systems, such as the Wide Area Augmentation System (WAAS) of the United States, the European Geostationary Navigation Overlay System (EGNOS) of Europe and the Multi-functional Satellite Augmentation System (MSAS) of Japan, and also covers other satellite navigation systems being built and to be built in future.

[0276] Based on this, in the embodiments of the disclosure, when selecting a logical channel, a terminal considers both a service characteristic and corresponding reference time information to make the time information corresponding to the service become a reference element for resource selection.

[0277] With the solution of the embodiments of the disclosure, the terminal uses time information of a service to select a logical channel, which improves the accuracy of logical channel selection and fully ensures the utilization ratio of radio resources and the performance of the terminal running services.

[0278] The embodiments of the disclosure provide a scheduling method, which is applied to a terminal. As shown in FIG. 1, the method may include the following operations.

[0279] In **101**, time information of a service corresponding to at least one logical channel is determined.

[0280] In **102**, first information sent by a first communication node is received.

[0281] The first information includes a granted radio resource.

[0282] In **103**, at least one logical channel is selected for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.

[0283] The time information of the service corresponding to the logical channel may include at least one of the following information: [0284] clock information of the service corresponding to the logical channel; or [0285] time characteristic information of the service corresponding to the logical channel.

[0286] The time characteristic information includes at least one of the following: [0287] sending time information of a data packet; [0288] arrival time information of the data packet; [0289] sending period information of the data packet; [0290] sending duration information of the data packet in a period; [0291] length information of the data packet; [0292] duration information of the data packet residing in a cache; [0293] survival time information of the data packet; [0294] sending state information of the first n data packets of the data packet, where n is a positive integer; [0295] a delay requirement of the data packet; [0296] a value of k in HARQ timing of the data packet; [0297] a reliability requirement of the data packet; [0298] an RNTI for scheduling and matching of the data packet; or [0299] a transmit power requirement of the data packet.

[0300] The survival time information of the data packet refers to that if the P th data packet received by a base station is wrong, and the correct $(P+1)$ th data packet is not received within the survival time, the connection is considered to be unavailable.

[0301] The sending state information includes at least one of the following: [0302] HARQ feedback information (ACK or NACK); [0303] feedback information (ACK or NACK) of an Automatic Repeat Request (ARQ) in a Radio Link Control (RLC) layer; or [0304] information regarding whether a discard timer of a Packet Data Convergence Protocol (PDCP) corresponding to the first n data packets expires.

[0305] k in the HARQ timing indicates a delay between reception of a downlink (DL) grant and reception of DL data, a delay between reception of the DL data and reception of the corresponding HARQ feedback, a delay between sending of an uplink (UL) grant and sending of UL data, or a delay between reception of the HARQ feedback and UL retransmission. In practical applications, k_0 and k_1 are used for representing different delays.

[0306] The reliability requirement of the data packet refers to that a packet error rate is lower than a certain threshold.

[0307] In an embodiment, when the time information of the service corresponding to each logical

channel is determined, the method may include at least one of the following operations.

[0308] The time information of the service corresponding to the corresponding logical channel is received from the first communication node.

[0309] The time information of the service corresponding to the corresponding logical channel is determined according to the learned time characteristic information of the service corresponding to the logical channel.

[0310] The learned time characteristic information of the service corresponding to the logical channel may refer to the time characteristic information of the service corresponding to the logical channel learned according to historical time characteristic information of a service corresponding to a logical channel.

[0311] In practical applications, the terminal may receive the time information of the service corresponding to the corresponding logical channel from the first communication node through one of the following signaling: [0312] DCI of an uplink grant; [0313] DCI of DL scheduling; [0314] RRC signaling carrying grand information of UL configuration; [0315] a signaling carrying semi-persistent scheduling (SPS) information of DL configuration; [0316] RRC signaling carrying configuration information of the logical channel; and [0317] RRC signaling carrying absolute time information.

[0318] The DCI of UL grant is used for scheduling a UL resource; correspondingly, the DCI of DL scheduling is used for scheduling a DL resource.

[0319] The first communication node may directly send the time information of the service corresponding to the corresponding logical channel to the terminal, that is, the terminal may directly obtain the time information of the service corresponding to the corresponding logical channel. In practical applications, the terminal may also implicitly determine the time information of the service corresponding to the corresponding logical channel according to the information sent by the first communication node.

[0320] Based on this, in an embodiment, the operation that the time information of the service corresponding to at least one logical channel is determined may include the following actions.

[0321] Second information is received. The second information represents at least one of the following: an indicated resource is aligned with a specific clock boundary or has a minimum offset from the specific clock boundary; or, the period of the indicated resource has a multiple relationship with the period of the specific clock, or an offset of a period value of the indicated resource is the minimum.

[0322] The time information of the service corresponding to the logical channel is determined by using the second information.

[0323] That is, the second information implicitly indicates the time information of the service corresponding to the corresponding logical channel.

[0324] In practical applications, the terminal may receive the second information through one of the following signaling: [0325] DCI of a UL grant; [0326] DCI of DL scheduling; [0327] RRC signaling carrying grand information of UL configuration; [0328] a signaling carrying SPS information of DL configuration; [0329] RRC signaling carrying configuration information of the logical channel; and [0330] RRC signaling carrying absolute time information.

[0331] In practical applications, the time information of the service corresponding to the corresponding logical channel may be updated.

[0332] Based on this, in an embodiment, the method may further include the following operation.

[0333] The time information of the service corresponding to at least one logical channel is updated.

[0334] In practical applications, the process of updating the time information may be triggered by the first communication node or the terminal.

[0335] The time information of the service corresponding to at least one logical channel may be updated according to time-related information sent by the first communication node.

[0336] Based on this, in an embodiment, when the time information of the service corresponding to

the logical channel is updated, the method may include the following operations.

[0337] Updated time-related information sent by the first communication node is received.

[0338] The time information of the service corresponding to the corresponding logical channel is updated by using the received updated time-related information.

[0339] In practical applications, the updated time-related information sent by the first communication node may be received through one of the following signaling: RRC signaling or a media access control (MAC) control element (CE).

[0340] In an embodiment, the time-related information may include at least one of the following: clock information or a delta value of an offset between the previous clock information and reference time.

[0341] The delta value may also be understood as an offset value.

[0342] In practical applications, the time information of the service corresponding to the logical channel includes at least one of the following: [0343] time information of Universal Time Coordinated (UTC); [0344] an offset between the UTC and GPS; [0345] information about a relationship between Daylight Saving Time (DST) and local time; [0346] an offset between the UTC and the local time; [0347] an offset between the UTC and a specific network (for example, the TSN); [0348] a mapping relationship between the UTC and a System Frame Number (SFN); [0349] indication information about whether the clock is a master clock; [0350] level information of the clock; [0351] information about the offset between the time information of the service corresponding to the logical channel and reference time of a specific clock type; [0352] synchronization precision information of the clock; [0353] synchronization granularity information of the clock; [0354] synchronization inaccuracy information; [0355] type information of the clock; [0356] reference time information; [0357] position relationship indication information of the reference time information and the received signaling; or [0358] time update period information of the clock.

[0359] For the level information of the clock, the closer the clock is to the master clock, the lower the level and the higher the precision.

[0360] The reference time information includes at least one of the following: [0361] reference system radio frame information; [0362] reference subframe information; [0363] reference slot information; or [0364] reference time symbol information.

[0365] The position relationship indication information of the reference time information and the received signaling carrying the time-related information refers to that the reference information precedes or follows the received signaling carrying the time-related information.

[0366] In practical applications, the first communication node may send the clock information by separately sending information of each clock domain, or sending the common part of the clock information of multiple clock domains and the differential information of each clock domain.

[0367] In practical applications, the granted radio resource may include at least one of the following: [0368] a dynamically scheduled granted radio resource; [0369] a configured grant (CG) radio resource; or [0370] an SPS radio resource.

[0371] In practical applications, the first communication node may be a base station, a core network element, or an adaptive functional body of a core network and a perimeter network, etc.

[0372] In an embodiment, the specific implementation of the operation in **103** may include one of the following.

[0373] When a priority of a first logical channel corresponding to a first data packet is lower than that of a second logical channel corresponding to a second data packet, and a time characteristic of the granted radio resource matches better with a time characteristic represented by the time information corresponding to the first logical channel, the first data packet corresponding to the first logical channel is preferentially scheduled by using the granted radio resource.

[0374] When the priority of the first logical channel corresponding to the first data packet is the same as that of the second logical channel corresponding to the second data packet, and the time

characteristic of the granted radio resource matches better with the time characteristic represented by the time information corresponding to the first logical channel, the first data packet corresponding to the first logical channel is preferentially scheduled by using the granted radio resource.

[0375] In practical applications, when the priority of the first logical channel corresponding to the first data packet is higher than that of the second logical channel corresponding to the second data packet, and the time characteristic of the granted radio resource matches better with the time characteristic represented by the time information corresponding to the first logical channel, the first data packet corresponding to the first logical channel is preferentially scheduled by using the granted radio resource.

[0376] From another perspective, the specific implementation of the operation in **103** may also include the following.

[0377] A data packet corresponding to at least one logical channel and preferentially scheduled with the granted radio resource is determined according to a first weight and third information.

[0378] The first weight is a predefined weight or a weight of a matching degree, indicated by the first communication node, between the time characteristic of the granted radio resource and the time characteristic represented by the time information corresponding to the corresponding logical channel.

[0379] The third information includes at least one of the following information: [0380] a priority of logical information; [0381] a subcarrier spacing; and [0382] a duration of a Physical Uplink Shared Channel (PUSCH).

[0383] In the above process, the operation for the first communication node side includes one of the following.

[0384] The time information of the service corresponding to the corresponding logical channel is sent to the terminal.

[0385] The second information is sent to the terminal. The second information represents at least one of the following: an indicated resource is aligned with a specific clock boundary or has a minimum offset from the specific clock boundary; or, the period of the indicated resource has a multiple relationship with the period of the specific clock, or the offset of the period value of the indicated resource is the minimum.

[0386] In an embodiment, the corresponding information is sent through one of the following signaling: [0387] DCI of a UL grant; [0388] DCI of DL scheduling; [0389] RRC signaling carrying grand information of UL configuration; [0390] a signaling carrying SPS information of DL configuration; [0391] RRC signaling carrying configuration information of the logical channel; and [0392] RRC signaling carrying absolute time information.

[0393] In an embodiment, the method may further include the following operation.

[0394] The updated time-related information is sent to the terminal.

[0395] In the above scheduling process, when the granted radio resource is SPS or CG radio resource, the granted radio resources has the time of on duration and the time of suspended duration, so it is needed to consider the time information of the on duration and the suspended duration of the SPS or CG radio resource in the scheduling process.

[0396] Based on this, as shown in FIG. 2, an implementation mode of scheduling may include the following operations.

[0397] In **201**, first information sent by the first communication node is received.

[0398] The first information includes at least one granted radio resource.

[0399] In **202**, time information of an on duration and a suspended duration of the at least one granted radio resource is acquired.

[0400] In **203**, at least one granted radio resource is selected for at least one logical channel.

[0401] In **204**, at least one of specific logical channel data or signaling is sent or received on an available resource indicated by the time information of the on duration of the granted radio

resource.

[0402] In practical applications, the specific implementation of the operation in **202** may include the following operation.

[0403] The time information of the on duration and the time information of the suspended duration of the corresponding granted radio resource configured through RRC dedicated signaling is received.

[0404] The specific implementation of the operation in **203** may include the following operation.

[0405] At least one granted radio resource is selected for the at least one logical channel based on at least one of the following information: [0406] time information of the service corresponding to the at least one logical channel; [0407] a logical channel selection result of the data packet cached by the at least one logical channel; or [0408] fourth information.

[0409] The fourth information represents at least one corresponding granted radio resource configured by each logical channel and/or a Radio Network Temporary Identifier (RNTI) configured by the at least one logical channel.

[0410] It is to be noted that the specific process of determining and updating the time information of the service corresponding to at least one logical channel has been described in detail above and will not be repeated here.

[0411] In **204**, sending or reception of at least one of data or signaling on a resource indicated by the time information of the suspended duration of the granted radio resource is stopped.

[0412] In this way, the operation of the first communication node may include the following action.

[0413] The time information of the on duration and the time information of the suspended duration of the corresponding granted radio resource is configured for the terminal through the RRC dedicated signaling.

[0414] Another manner of scheduling is that: the terminal receives fifth information sent by the first communication node. The fifth information is the updated offset information of the granted SPS or CG radio resource.

[0415] The start position of the granted SPS or CG radio resource is updated using the fifth information.

[0416] When the period value in the time information of the service corresponding to the logical channel does not match the period value of the existing 5G network, for example, the period value in the time information of the service corresponding to the logical channel is not an integer divisor of the cycle period, namely 10240 ms, of a radio frame, after several SPS or CG periods (e.g., after the SFN warps around), a sending opportunity calculated based on the existing resources, namely the offset value, is inconsistent with the actual time point at which a service packet needs to be sent. The problem may be solved by updating the start position of the SPS or CG radio resource.

[0417] The fifth information sent by the first communication node is received through one of the following signaling: RRC signaling, an MAC CE or DCI.

[0418] In this way, the operation of the first communication node may include the following action.

[0419] The fifth information is sent to the terminal.

[0420] In an embodiment, the fifth information is sent to the terminal through one of the following signaling: RRC signaling, an MAC CE or DCI.

[0421] Based on the above scheduling solution, the embodiments of the disclosure also provide a scheduling method, which is applied to a terminal, and may include the following operations.

[0422] Configuration information of at least one set of configured grant that the first communication node configures for a used traffic pattern is received.

[0423] An offset sent by the first communication node is received.

[0424] An offset of a configured grant resource is updated with the received offset.

[0425] In an embodiment, the operation that the offset sent by the first communication node is received may include the following action.

[0426] The offset sent by the first communication node is received through DCI.

[0427] In practical applications, the configuration information of at least one set of configured grant that the first communication node configures for the used traffic pattern may be received through the RRC signaling. The configuration information includes the offset information of the configured grant resource.

[0428] Correspondingly, the embodiments of the disclosure also provide a scheduling method, which is applied to a first communication node. The method may include the following operations.

[0429] A traffic pattern used by the terminal is acquired.

[0430] For the used traffic pattern, at least one set of configured grant is configured for the terminal.

[0431] An offset is sent to the terminal, the offset sent being used for the terminal to update an offset of the configured grant resource.

[0432] In an embodiment, the operation that the traffic pattern used by the terminal is acquired may include one of the following: [0433] the traffic pattern used by the terminal is acquired from a core network; and [0434] the traffic pattern used by the terminal is acquired from the terminal.

[0435] In an embodiment, the operation that the offset is sent to the terminal may include the following action.

[0436] The offset is sent to the terminal through the DCI.

[0437] The embodiments of the disclosure provide an information transmission method, which is applied to a first communication node. The method may include the following operations.

[0438] Clock information is acquired.

[0439] m types of clock information are sent to a terminal based on the acquired clock information. m is greater than or equal to 1.

[0440] In an embodiment, the operation that the clock information is acquired may include at least one of the following: [0441] the clock information is acquired from a core network; [0442] the clock information is acquired from an adjacent communication node; [0443] the clock information sent by the terminal is received; [0444] capability information reported by the terminal is received, the capability information indicating clock related capability supported by the terminal; or [0445] the clock information is acquired from a specific network system (for example, the TSN system).

[0446] In an embodiment, the capability information includes at least one of the following: [0447] the clock type supported by the terminal; or [0448] at least one of the synchronization precision information or the synchronization granularity information supported by the terminal.

[0449] In an embodiment, the clock information sent by the terminal includes clock information of a system to which the terminal is being connected.

[0450] In an embodiment, the clock information includes at least one of the following: [0451] time information of the UTC; [0452] an offset between the UTC and the GPS; [0453] information about the relationship between the DST and the local time; [0454] an offset between the UTC and the local time; [0455] an offset between the UTC and the specific network; [0456] a mapping relationship between the UTC and the SFN; [0457] indication information about whether the clock is the master clock; [0458] level information of the clock; [0459] information about an offset between the clock information and the reference time of the specific clock type; [0460] synchronization precision information of the clock; [0461] synchronization granularity information of the clock; [0462] synchronization inaccuracy information; [0463] type information of the clock; [0464] reference time information; [0465] position relationship indication information of the reference time information and the received signaling; or [0466] time update period information of the clock.

[0467] In an embodiment, the reference time information includes at least one of the following:

[0468] reference system radio frame information; [0469] reference subframe information; [0470] reference slot information; or [0471] reference time symbol information.

[0472] Correspondingly, the embodiments of the disclosure also provide an information transmission method. The method is applied to a terminal, and may include the following

operations.

[0473] At least one of capability information or clock information is sent to the first communication node. The capability information indicates the clock related capability supported by the terminal.

[0474] The m types of clock information sent by the first communication node are received, where m is greater than or equal to 1.

[0475] With the solution provided by the embodiments of the disclosure, the terminal determines the time information of the service corresponding to at least one logical channel, receives the first information sent by the first communication node, the first information including the granted radio resource, and selects at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel in combination with configuration parameters of the at least one logical channel. The logical channel is selected by using the time information of the service, which improves the accuracy of logical channel selection, and fully ensures the utilization ratio of radio resources and the performance of the terminal running services.

[0476] The disclosure is further described below in combination with application embodiments.

First Application Embodiment

[0477] In the application embodiment, the service is TSN service.

[0478] The process of selecting a logical channel in the application embodiment includes the following operations.

[0479] At the first step, after acquiring clock information of a TSN system, a base station broadcasts n (n being greater than or equal to 1) types of clock information through a system message.

[0480] In practical applications, the base station may receive the clock information of the TSN system sent by the core network and the adjacent base station, and may also directly obtain the clock information from the TSN system. The base station may also receive the clock information of the TSN system sent by UE 1.

[0481] The n types of clock information broadcast include, for example, the clock information of the TSN system 1, the clock information of the TSN system 2, the clock information of the TSN system 3 with a precision k , the clock information of the TSN system 3 with a precision 1, the clock information of the TSN system 3 with a precision z , the clock information obtained from the GNSS, the clock information of the GNSS with a precision m , and the clock information of the GNSS with a precision h .

[0482] At the second step, the UE2 reports capability information.

[0483] The capability information reported by the UE2 carries information about the clock type, synchronization precision and/or synchronization granularity supported by the UE2.

[0484] In practical applications, the UE 1 and the UE 2 may be the same UE or different UEs.

[0485] At the third step, a base station system sends m (m being greater than or equal to 1) types of clock information through an RRC dedicated message.

[0486] The m types of clock information may be determined as needed, and for example, include: the clock information of the TSN system 1, the clock information of the TSN system 2, the clock information of the TSN system 3 with a precision k , the clock information of the TSN system 3 with a precision 1, the clock information obtained from the GNSS, and the clock information obtained from the GNSS with a precision m .

[0487] The clock information may include at least one of the following information: [0488] time information of UTC; [0489] an offset between the UTC and the GPS ((number of leap seconds offset between GPS Time and UTC); [0490] information about a relationship between DST and local time (if and how the DST is applied to obtain the local time); [0491] an offset between the UTC and the local time; [0492] an offset between the UTC and the TSN; [0493] a mapping relationship between the UTC and the SFN; [0494] indication information about whether the clock

is the master clock; [0495] level information of the clock; [0496] the information about the offset between the clock information and a reference time of a specific clock type, the specific clock type may be a master clock or a currently applied clock or a clock type configured through signaling; [0497] synchronization precision information of the clock; [0498] synchronization granularity information of the clock; [0499] synchronization inaccuracy information (inaccuracy indication); [0500] type information of the clock, for example, the GNSS or the TSN; or [0501] time update period information of the clock.

[0502] When using the resource of the SPS or CG, the UE 2 applies the corresponding clock of the SPS or CG configuration as the reference time.

[0503] The synchronization inaccuracy information indicates an inaccuracy range of time reference information. For example, if the inaccuracy indication is $3\ \mu\text{s}$ (microseconds) and the time of the time reference information is k , then the UE 2 considers that the current time is $(k-3\ \mu\text{s}, k+3\ \mu\text{s})$.

[0504] At the same time, when configuring the logical channel, the base station configures one or more clock information types to indicate the clock types, such as a logistics network of TSN, the Internet of Vehicles, a GPS network, and a power network of TSN. That is, the RRC dedicated signaling is RRC signaling carrying the configuration information of the logical channel.

[0505] At the fourth step, the UE 2 receives and applies the configuration information of these clocks and services.

[0506] In practical applications, the UE 2 may acquire the clock information from a system message broadcast by the base station, and may also acquire the clock information from the RRC dedicated message sent by the base station, that is, the UE 2 may directly acquire the time information (clock information of the service corresponding to the logical channel) such as the corresponding time point from the system message or the dedicated message. In addition, in practical applications, the UE 2 may also acquire the clock information through one of the following signaling: [0507] DCI of a UL grant; [0508] DCI of DL scheduling; [0509] RRC signaling carrying the grand information of the UL configuration; [0510] a signaling carrying SPS information of the DL configuration; [0511] RRC signaling carrying the configuration information of the logical channel; and

[0512] RRC signaling carrying the absolute time information.

[0513] In addition, in practical applications, the UE 2 may also receive the second information through one of the following signaling: [0514] DCI of the UL grant; [0515] DCI of the DL scheduling; [0516] RRC signaling carrying the grand information of the UL configuration; [0517] a signaling carrying the SPS information of the DL configuration; and [0518] RRC signaling carrying the absolute time information.

[0519] The second information represents at least one of the following: [0520] an indicated resource is aligned with a specific clock boundary or has the minimum offset from the specific clock boundary; or [0521] the period of the indicated resource has a multiple relationship with the period of the specific clock, or a offset of the period value of the indicated resource is the minimum.

[0522] The time information of the service corresponding to the logical channel is determined using the second information, that is, the clock information of the service corresponding to the logical channel is implicitly inferred.

[0523] For example, the UE 2 implicitly infers the clock information of the service corresponding to the logical channel based on a certain clock the boundary of which is aligned with or has the minimum offset from the resource indicated by the UL grant.

[0524] In the process of multiplexing UL information, when performing the logical channel selection, the UE 2 not only considers the configuration parameters of logical information (such as the priority and numerology), but also considers the time information. That is, when there are data packets corresponding to one or more logical channels that newly arrive or need to be retransmitted in the cache of the UE 2, the UE 2 also needs to consider the clock information in addition to the

priority and numerology of logical information during choosing to send the data packets on the resource of the UL grant or the SPS/CG. For example, when the priority of the logical channel 1 corresponding to the data packet 1 is lower than that of the logical channel 2 corresponding to the data packet 2, because the clock information indicated in DCI signaling is consistent with the clock information corresponding to the logical channel 1, the data packet 1 corresponding to the logical channel 1 is preferentially scheduled with this resource. For another example, when the priority of the logical channel 1 corresponding to the data packet 1 is the same as that of the logical channel 2 corresponding to the data packet 2, because the location of resource information in time indicated by the DCI signaling or SPS/CG is closer to the location of arrival time of the data packet 1 of the logical channel 1 (relative to the data packet 2), the data packet 1 corresponding to the logical channel 1 is preferentially scheduled with this resource.

Second Application Embodiment

[0525] In the application embodiment, the service is the TSN service.

[0526] The process of the present embodiment is basically the same as the process of selecting a logical channel in the first application embodiment. Different from the first application embodiment, the UE 2 directly obtains a reference time type from the RRC message (system message and/or dedicated message), and then calculates the information such as the corresponding time point or the like according to the offset information (namely the second information) between the reference time in the message and the reference time of a specific clock type, that is, acquires the clock information of the service corresponding to the logical channel. That is, the time information of the service corresponding to the logical channel is determined using the second information, that is, the clock information of the service corresponding to the logical channel is implicitly inferred.

[0527] The UE 2 may also receive the second information through one of the following signaling:

[0528] DCI of a UL grant; [0529] DCI of DL scheduling; [0530] RRC signaling carrying grand information of the UL configuration; [0531] a signaling carrying SPS information of the DL configuration; and [0532] RRC signaling carrying absolute time information; [0533] The second information represents at least one of the following: [0534] an indicated resource is aligned with a specific clock boundary or has the minimum offset from the specific clock boundary; or [0535] the period of the indicated resource has a multiple relationship with the period of the specific clock, or the offset of the period value of the indicated resource is the minimum.

[0536] For example, the UE 2 implicitly infers the clock information of the service corresponding to the logical channel based on a certain clock the boundary of which is aligned with or has the minimum offset from the resource indicated by the UL grant.

Third Application Embodiment

[0537] In the application embodiment, the service is the TSN service.

[0538] In the application embodiment, the process of updating the clock information is described based on the first application embodiment and the second application embodiment.

[0539] There is a timer at each of the base station side and the UE side, and the duration of the timer is time update period information of the clock. When the timer expires, the base station or UE triggers the process of updating the clock information, and the base station sends the updated time-related information to the UE.

[0540] The time-related information may include the updated clock information and/or the delta value of an offset between the time of the previous clock information and reference time of a specific clock type.

[0541] In practical applications, the time-related information may be sent to the UE through the RRC signaling or the MAC CE.

[0542] In practical applications, when the timer does not expire, the base station or the UE may also trigger the process of updating the clock information in advance, and the base station sends the updated time-related information to the UE, for example, in a scenario with a low delay

requirement of UE.

Fourth Application Embodiment

[0543] In the application embodiment, the process that the UE uses the resource of the SPS or CG configuration to transmit data is described based on the first embodiment to the third embodiment.

[0544] When SPS/CG information is configured, the following operations may be included.

[0545] At the first step, the base station obtains a TSN traffic pattern from the core network or the UE, and configures one or more sets of configured grant for the UE through the RRC dedicated messages to support the corresponding TSN traffic pattern. The configuration information of the configured grant includes at least one of the following information: [0546] a period; [0547] an offset from SFN=0 in time domain; [0548] a start symbol number in the time domain, a duration of available resources and a PUSCH mapping type; [0549] resources allocated in frequency domain; [0550] a Modulation and Coding Scheme (MCS) and a transport block size; [0551] the time or symbol number of the on duration of the configured grant (namely the time information of the on duration); or [0552] the time or symbol number of the suspended duration of the configured grant (namely the time information of the suspended duration).

[0553] At the second step, the UE receives and applies the configuration information of the configured grant.

[0554] Specifically, the UE directly obtains information such as the time (or symbol number) of the on duration and the time (or the symbol number) of the suspended duration of the configured grant from the RRC dedicated message. The time of the on duration and the time of the suspended duration form a configured grant cycle, as shown in FIG. 3.

[0555] As shown in FIG. 3, within the time (or symbol number) of the on duration of the configured grant, the UE may send data to be transmitted on time-frequency resources that the base station reserves for the configured grant. Within the time (or symbol number) of the suspended duration of the configured grant, the base station does not reserve the time-frequency resources for the configured grant, and the UE cannot use the time-frequency resources for the configured grant within the time. The configured grant may be reactivated or deactivated through the RRC dedicated signaling within both the time (symbol number) of the on duration and the time (symbol number) of the suspended duration of the configured grant. Of course, the UE may select, in a suspended state, the resource(s) of another configured grant to send the data to be transmitted.

Fifth Application Embodiment

[0556] In the application embodiment, the process that the UE uses the resource of the SPS or CG configuration to transmit data is described based on the first embodiment to the third embodiment.

[0557] When the SPS/CG information is configured, the following operations may be included.

[0558] At the first step, the base station obtains the TSN traffic pattern from the core network or the UE, and configures one or more sets of configured grant for the UE through the RRC dedicated message to support the corresponding TSN traffic pattern. The configuration information of the configured grant includes at least one of the following information: [0559] a period; [0560] an offset from SFN=0 in time domain; [0561] a start symbol number in the time domain, a duration of available resources and a PUSCH mapping type; [0562] resources allocated in frequency domain; [0563] an MCS and a transport block size; [0564] the time or symbol number of the on duration of the configured grant (namely the time information of the on duration); or [0565] the time or symbol number of the suspended duration of the configured grant (namely the time information of the suspended duration).

[0566] Then, the base station updates the offset information of configured grant resource through DCI of a Physical Downlink Control Channel (PDCCH).

[0567] The problem that the period value in the time information of the service corresponding to the logical channel does not match the period value of the existing 5G network may be solved by updating the start position of the SPS or CG radio resource.

[0568] In practical applications, the base station may update the offset information of configured

grant resource through the DCI of the PDCCH.

[0569] In order to implement the method for the terminal side of the embodiments of the disclosure, the embodiments of the disclosure provide a scheduling apparatus, which is arranged on the terminal. As shown in FIG. 4, the apparatus may include a first determining unit **41**, a first receiving unit **42** and a first selecting unit **43**.

[0570] The first determining unit **41** is configured to determine time information of a service corresponding to at least one logical channel.

[0571] The first receiving unit **42** is configured to receive first information sent by a first communication node. The first information includes a granted radio resource.

[0572] The first selecting unit **43** is configured to select at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.

[0573] In an embodiment, the first determining unit **41** is further configured to update the time information of the service corresponding to the at least one logical channel.

[0574] In practical applications, the first determining unit **41** may be implemented by a processor in the scheduling apparatus in combination with a communication interface. The first receiving unit **42** may be implemented by the communication interface in the scheduling apparatus. The first selecting unit **43** may be implemented by the processor in the scheduling apparatus.

[0575] In order to implement the method for the first communication node of the embodiments of the disclosure, the embodiments of the disclosure provide an information transmission apparatus, which is arranged on the communication node. The apparatus may include a first sending unit.

[0576] The first sending unit is configured to: send time information of a service corresponding to a corresponding logical channel to a terminal; or, send second information to the terminal.

[0577] The second information represents at least one of the following: [0578] an indicated resource is aligned with a specific clock boundary or has the minimum offset from the specific clock boundary; or [0579] a period of the indicated resource has a multiple relationship with a period of the specific clock, or an offset of the period value of the indicated resource is the minimum.

[0580] In practical applications, the first sending unit may be implemented by a processor in the information transmission apparatus in combination with a communication interface.

[0581] In order to implement the method for the terminal side of the embodiments of the disclosure, the embodiments of the disclosure provide a scheduling apparatus, which is arranged on the terminal. As shown in FIG. 5, the apparatus may include a second receiving unit **51**, an acquiring unit **52**, a second determining unit **53** and a transmitting unit **54**.

[0582] The second receiving unit **51** is configured to receive first information sent by a first communication node, the first information including at least one granted radio resource.

[0583] The acquiring unit **52** is configured to acquire time information of an on duration and a suspended duration of the at least one granted radio resource.

[0584] The second determining unit **53** is configured to select at least one granted radio resource for at least one logical channel.

[0585] The transmitting unit **54** is configured to send or receive at least one of specific logical channel data or signaling on the available resource indicated by the time information of the on duration of the granted radio resource.

[0586] In an embodiment, the second determining unit **53** is configured to select at least one granted radio resource for at least one logical channel based on at least one of the following information: [0587] time information of a service corresponding to the at least one logical channel; a logical channel selection result of a data packet cached by the at least one logical channel; or the fourth information.

[0588] The fourth information represents at least one corresponding granted radio resource configured by each logical channel and/or RNTI configured by the at least one logical channel.

[0589] The transmitting unit **54** is further configured to stop sending or receiving at least one of data or signaling on the resource indicated by the time information of the suspended duration of the granted radio resource.

[0590] In practical applications, the second receiving unit **51** may be implemented by a communication interface in the scheduling apparatus. The acquiring unit **51** and the transmitting unit **54** may be implemented by a processor in the scheduling apparatus in combination with the communication interface. The second determining unit may be implemented by the processor in the scheduling apparatus.

[0591] In order to implement the method for the first communication node side, the embodiments of the disclosure provide an information transmission apparatus, which is arranged on the first communication node. The apparatus may include a second sending unit.

[0592] The second sending unit is configured to configure time information of an on duration and time information of a suspended duration of the corresponding granted radio resource for a terminal through RRC dedicated signaling.

[0593] In practical applications, the second sending unit may be implemented by a processor in the information transmission apparatus in combination with a communication interface.

[0594] In order to implement the method of the embodiments of the disclosure, the embodiments of the disclosure also provide a scheduling apparatus, which is arranged on the terminal. The apparatus may include a third receiving unit and a processing unit.

[0595] The third receiving unit is configured to receive configuration information of at least one set of configured grant that a first communication node configures for a used traffic pattern, and receive an offset sent by the first communication node.

[0596] The processing unit is configured to update the offset of the configured grant resource with the received offset.

[0597] In an embodiment, the third receiving unit is configured to receive the offset sent by the first communication node through DCI.

[0598] In practical applications, the third receiving unit may be implemented by a communication interface in the scheduling apparatus, and the processing unit may be implemented by a processor in the scheduling apparatus.

[0599] In order to implement the method of the embodiments of the disclosure, the embodiments of the disclosure also provide a scheduling method, which is arranged on the first communication node. The apparatus may include a first acquiring unit, a configuring unit and an updating unit.

[0600] The first acquiring unit is configured to acquire a traffic pattern used by a terminal.

[0601] The configuring unit is configured to configure for the terminal at least one set of configured grant for the used traffic pattern.

[0602] The updating unit is configured to send an offset to the terminal. The sent offset is used for the terminal to update an offset of the configured grant resource.

[0603] In an embodiment, the first acquiring unit is configured to perform one of the following operations: [0604] acquiring the traffic pattern used by the terminal from the core network; or [0605] acquiring the traffic pattern used by the terminal from the terminal.

[0606] In an embodiment, the updating unit is configured to: [0607] send the offset to the terminal through DCI.

[0608] In practical applications, the first acquiring unit and the updating unit may be implemented by the communication interface in the scheduling apparatus, and the configuring unit may be implemented by the communication interface in the scheduling apparatus in combination with a processor.

[0609] In order to implement the method of the embodiments of the disclosure, the embodiments of the disclosure also provide an information transmission apparatus, which is arranged on a first communication node. The apparatus may include a second acquiring unit and a third sending unit.

[0610] The second acquiring unit is configured to acquire clock information.

[0611] The third sending unit is configured to send m types of clock information to a terminal based on the acquired clock information, where m is greater than or equal to 1.

[0612] In an embodiment, the second acquiring unit is configured to perform at least one of the following operations: [0613] acquiring the clock information from a core network; [0614] acquiring the clock information from an adjacent communication node; or [0615] receiving the clock information sent by the terminal; [0616] receiving capability information reported by the terminal, the capability information indicating clock related capability supported by the terminal; or [0617] acquiring the clock information from a specific network system.

[0618] In practical applications, the second acquiring unit may be implemented by a communication interface in the information transmission apparatus, and the third sending unit may be implemented by the communication interface in the information transmission apparatus in combination with a processor.

[0619] In order to implement the method of the embodiments of the disclosure, the embodiments of the disclosure also provide an information transmission apparatus, which is arranged on a terminal. The apparatus may include a fourth sending unit and a fourth receiving unit.

[0620] The fourth sending unit is configured to send at least one of capability information or clock information to a first communication node, the capability information indicating clock related capability supported by the terminal.

[0621] The fourth receiving unit is configured to receive m types of clock information sent by the first communication node, where m is greater than or equal to 1.

[0622] In practical applications, the fourth sending unit and the fourth receiving unit may be implemented by the communication interface in the information transmission apparatus.

[0623] It is to be noted that when the scheduling apparatus provided by the embodiments performs the scheduling processing, the apparatus is illustrated only by the division of program modules mentioned above. In practical applications, the above processing may be assigned to different program modules to complete as needed, that is, the internal structure of the apparatus is divided into different program modules to complete all or part of the processing described above. In addition, the scheduling apparatus provided in the embodiments belongs to the same concept as the scheduling method embodiments, and details about a specific implementation process thereof refer to the method embodiments, which will not be elaborated herein. Correspondingly, when the information transmission apparatus provided by the embodiments performs information transmission, the apparatus is illustrated only by the division of program modules mentioned above. In practical applications, the above processing may be assigned to different program modules to complete as needed, that is, the internal structure of the apparatus is divided into different program modules to complete all or part of the processing described above. In addition, the information transmission apparatus provided in the embodiments belongs to the same concept as the information transmission method embodiments, and details about a specific implementation process thereof refer to the method embodiments, which will not be elaborated herein.

[0624] Based on hardware implementation of the above program modules, for implementing the method for the terminal side in the embodiments of the disclosure, the embodiments of the disclosure provide a terminal. As shown in FIG. 6, the terminal **60** includes a first communication interface **61**, a first processor **62** and a first memory **63**.

[0625] The first communication interface **61** may perform information interaction with a first communication node.

[0626] The first processor **62** is connected with the first communication interface **61** to implement information interaction with the first communication node, and is configured to run a computer program to execute the method provided in one or more technical solutions for the terminal side. The computer program is stored in the first memory **63**.

[0627] Specifically, when the process shown in FIG. 1 is implemented, the first processor **62** is configured to determine time information of a service corresponding to at least one logical channel.

[0628] The first communication interface **61** is configured to receive first information sent by the first communication node, the first information including a granted radio resource.

[0629] The first processor **62** is further configured to select at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.

[0630] In an embodiment, the first processor **62** is further configured to update the time information of the service corresponding to the at least one logical channel.

[0631] When the process shown in FIG. 2 is implemented, the first communication interface **61** is configured to receive first information sent by the first communication node, the first information including at least one granted radio resource.

[0632] The first processor **62** is configured to acquire time information of an on duration and a suspended duration of the at least one granted radio resource, and select at least one granted radio resource for at least one logical channel.

[0633] The first communication interface **61** is further configured to send or receive at least one of specific logical channel data or signaling on the available resource indicated by the time information of the on duration of the granted radio resource.

[0634] In an embodiment, the first processor **62** is configured to select at least one granted radio resource for at least one logical channel based on at least one of the following information: [0635] time information of a service corresponding to the at least one logical channel; a logical channel selection result of a data packet cached by the at least one logical channel; or the fourth information.

[0636] The fourth information represents at least one corresponding granted radio resource configured by each logical channel and/or RNTI configured by the at least one logical channel.

[0637] The first communication interface **61** is further configured to stop sending or receiving at least one of data or signaling on the resource indicated by the time information of the suspended duration of the granted radio resource.

[0638] In the embodiments of the disclosure, the first communication interface **61** is configured to receive configuration information of at least one set of configured grant that the first communication node configures for the used traffic pattern, and receive an offset sent by the first communication node. The first processor **62** is configured to update the offset of the configured grant resource with the received offset.

[0639] Or, [0640] the first communication interface **61** is configured to send at least one of capability information or clock information to the first communication node, the capability information indicating clock related capability supported by the terminal, and receive m types of clock information sent by the first communication node, where m is greater than or equal to 1.

[0641] In an embodiment, the first communication interface **61** is configured to receive the offset sent by the first communication node through DCI.

[0642] It is to be noted that the specific processing of the first processor **62** and the first communication interface **61** may be understood with reference to the above method.

[0643] In practical applications, various components in the terminal **60** are coupled together through a bus system **64**. It may be understood that the bus system **64** is configured to implement connection communication between these components. The bus system **64** includes a data bus and further includes a power bus, a control bus and a state signal bus. However, for clear description, various buses in FIG. 6 are marked as the bus system **64**.

[0644] The first memory **63** in the embodiments of the disclosure is configured to store various types of data to support the operations of the terminal **60**. Examples of the data include any computer program operated in the terminal **60**.

[0645] The method disclosed in the embodiments of the disclosure may be applied to the first processor **62** or implemented by the first processor **62**. The first processor **62** may be an integrated circuit chip with a signal processing capability. In an implementation process, the operations of the

method may be accomplished by an integrated logic circuit of hardware in the first processor **62** or an instruction in a software form. The first processor **62** may be a universal processor, a Digital Signal Processor (DSP) or another Programmable Logic Device (PLD), a discrete gate or transistor logic device, a discrete hardware component, etc. The first processor **62** may implement or execute each method, operation and logical block diagram disclosed in the embodiments of the disclosure. The universal processor may be a microprocessor, any conventional processor or the like. The operations of the method disclosed in combination with the embodiments of the disclosure may be directly embodied to be executed and completed by a hardware decoding processor or executed and completed by a combination of hardware and software modules in the decoding processor. The software module may be located in a storage medium, and the storage medium is located in the first memory **63**. The first processor **62** reads information in the first memory **63** and completes the operations of the method in combination with hardware.

[0646] In an exemplary embodiment, the terminal **60** may be implemented by one or more Application Specific Integrated Circuits (ASICs), DSPs, Programmable Logic Devices (PLDs), Complex Programmable Logic Devices (CPLDs), Field-Programmable Gate Array (FPGAs), universal processors, controllers, Micro Controller Units (MCUs), microprocessors, or other electronic components, and is configured to execute the above methods.

[0647] Based on the hardware implementation of each program module, for implementing the method for the first communication node side in the embodiments of the disclosure, the embodiments of the disclosure provide a communication node. As shown in FIG. 7, the communication node **70** includes a second communication interface **71**, a second processor **72** and a second memory **73**.

[0648] The second communication interface **71** may perform information interaction with a network device.

[0649] The second processor **72** is connected with the second communication interface **71** to implement information interaction with a terminal, and is configured to run a computer program to execute the method provided in one or more technical solutions for the first communication node side. The computer program is stored in the second memory **73**.

[0650] Specifically, when the process shown in FIG. 1 is implemented, the second communication interface **71** is configured to send time information of a service corresponding to a corresponding logical channel to a terminal under control of the second processor **72**; or, send second information to the terminal under the control of the second processor.

[0651] The second information represents at least one of the following: [0652] an indicated resource is aligned with a specific clock boundary or has the minimum offset from the specific clock boundary; or [0653] the period of the indicated resource has a multiple relationship with the period of the specific clock, or the offset of the period value of the indicated resource is the minimum.

[0654] When the process shown in FIG. 2 is implemented, the second processor **72** is configured to configure, by using the second communication interface **71**, time information of an on duration and time information of a suspended duration of the corresponding granted radio resource for the terminal through RRC dedicated signaling.

[0655] In the embodiments of the disclosure, the second processor **72** is configured to acquire a traffic pattern used by the terminal, and configure for the terminal at least one set of configured grant for the used traffic pattern through the second communication interface **71**.

[0656] The second communication interface **71** is configured to send the offset to the terminal. The sent offset is used for the terminal to update the offset of the configured grant resource.

[0657] Or, the second communication interface **71** is configured to acquire clock information, and send m types of clock information to the terminal based on the acquired clock information, where m is greater than or equal to 1.

[0658] In an embodiment, the second communication interface **71** is configured to perform one of

the following operations: [0659] acquiring the traffic pattern used by the terminal from the core network; or [0660] acquiring the traffic pattern used by the terminal from the terminal.

[0661] In an embodiment, the second communication interface **71** is configured to send the offset to the terminal through DCI.

[0662] In an embodiment, the second communication interface **71** is configured to perform at least one of the following operations: [0663] acquiring the clock information from the core network; [0664] acquiring the clock information from an adjacent communication node; [0665] receiving the clock information sent by the terminal; [0666] receiving capability information reported by the terminal, the capability information indicating clock related capability supported by the terminal; or [0667] acquiring the clock information from the specific network system.

[0668] It is to be noted that the specific processing of the second processor **71** and the second communication interface **71** may be understood with reference to the above method.

[0669] In practical applications, various components in the communication node **70** are coupled through the bus system **74**. It may be understood that the bus system **74** is configured to implement connection communication between these components. The bus system **74** includes a data bus and further includes a power bus, a control bus and a state signal bus. However, for clear description, various buses in FIG. **7** are marked as the bus system **74**.

[0670] The second memory **73** in the embodiments of the disclosure is configured to store various types of data to support the operations of the communication node **70**. Examples of the data include any computer program operated on the communication node **70**.

[0671] The method disclosed in the embodiments of the disclosure may be applied to the second processor **72** or implemented by the second processor **72**. The second processor **72** may be an integrated circuit chip with a signal processing capability. In an implementation process, the operations of the method may be accomplished by an integrated logic circuit of hardware in the second processor **72** or an instruction in a software form. The second processor **72** may be a universal processor, a DSP or other PLD, a discrete gate or transistor logic device, a discrete hardware component, etc. The second processor **72** may implement or execute each method, operation and logical block diagram disclosed in the embodiments of the disclosure. The universal processor may be a microprocessor, any conventional processor or the like. The operations of the method disclosed in combination with the embodiments of the disclosure may be directly embodied to be executed and completed by a hardware decoding processor or executed and completed by a combination of hardware and software modules in the decoding processor. The software module may be located in a storage medium, and the storage medium is located in the second memory **73**. The second processor **72** reads information in the second memory **73** and completes the operations of the method in combination with hardware.

[0672] In an exemplary embodiment, the communication node **70** may be implemented by one or more ASICs, DSPs, PLDs, CPLDs, FPGAs, universal processors, controllers, MCUs, microprocessors, or other electronic components, and is configured to execute the above methods.

[0673] It is to be understood that the each of memories (the first memory **63** and the second memory **73**) in the embodiments of the disclosure may be a volatile memory or a nonvolatile memory, or may include both the volatile and nonvolatile memories. The nonvolatile memory may be a Read Only Memory (ROM), a Programmable Read-Only Memory (PROM), an Erasable Programmable Read-Only Memory (EPROM), an Electrically Erasable Programmable Read-Only Memory (EEPROM), a Ferromagnetic Random Access Memory (FRAM), a flash memory, a magnetic surface memory, an optical disc, or a Compact Disc Read-Only Memory (CD-ROM). The magnetic surface memory may be a disk memory or a tape memory. The volatile memory may be a Random Access Memory (RAM), and is used as an external high-speed cache. It is exemplarily but unlimitedly described that RAMs in various forms may be adopted, such as a Static Random Access Memory (SRAM), a Synchronous Static Random Access Memory (SSRAM), a Dynamic Random Access Memory (DRAM), a Synchronous Dynamic Random Access Memory (SDRAM),

a Double Data Rate Synchronous Dynamic Random Access Memory (DDRSDRAM), an Enhanced Synchronous Dynamic Random Access Memory (ESDRAM), a SyncLink Dynamic Random Access Memory (SLDRAM) and a Direct Rambus Random Access Memory (DRRAM). The memory described in the embodiments of the disclosure is intended to include, but not limited to, memories of these and any other proper types.

[0674] In an exemplary embodiment, the embodiments of the disclosure also provide a storage medium, namely a computer storage medium, specifically a computer-readable storage medium, which includes, for example, the first memory **63** storing a computer program. The computer program may be executed by the first processor **62** of the terminal **60** to complete the operations of the method for the terminal side. For another example, the storage medium includes the second memory **73** storing a computer program. The computer program may be executed by the second processor **72** of the communication node **70** to complete the operations of the method for the first communication node side. The computer-readable storage medium may be a memory such as an FRAM, a ROM, a PROM, an EPROM, an EEPROM, a flash memory, a magnetic surface memory, an optical disc, or a CD-ROM.

[0675] It is to be noted that terms “first”, “second” and the like are adopted to distinguish similar objects and not intended to describe a specific sequence or order.

[0676] In addition, the technical solutions recorded in the embodiments of the disclosure may be freely combined without conflicts.

[0677] The above is only the preferred embodiments of the disclosure and not intended to limit the protection scope of the disclosure.

Claims

1. A scheduling method, applied to a terminal, comprising: determining time information of a service corresponding to at least one logical channel; receiving first information sent by a first communication node, the first information comprising a granted radio resource; and selecting at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.
2. The method of claim 1, wherein selecting at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel comprises: when a priority of a first logical channel corresponding to a first data packet is lower than that of a second logical channel corresponding to a second data packet, and a time characteristic of the granted radio resource matches better with a time characteristic represented by time information corresponding to the first logical channel, preferentially scheduling the first data packet corresponding to the first logical channel with the granted radio resource; or, when the priority of the first logical channel corresponding to the first data packet is the same as that of the second logical channel corresponding to the second data packet, and the time characteristic of the granted radio resource matches better with the time characteristic represented by the time information corresponding to the first logical channel, preferentially scheduling the first data packet corresponding to the first logical channel with the granted radio resource.
3. The method of claim 1, wherein selecting at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel comprises: determining, according to a first weight and third information, a data packet corresponding to at least one logical channel and preferentially scheduled with the granted radio resource; wherein, the first weight is a predefined weight or a weight of a matching degree, indicated by the first communication node, between time characteristic of the granted radio resource and time characteristic represented by the

time information corresponding to the corresponding logical channel; the third information comprises at least one of the following: a priority of logical information; a subcarrier spacing; or a duration of a Physical Uplink Shared Channel (PUSCH).

4. The method of claim 1, wherein the granted radio resource comprises at least one of the following: a dynamically scheduled granted radio resource; a Configured Granted (CG) radio resource; or a semi-persistent scheduling (SPS) radio resource.

5. The method of claim 1, wherein the time information of the service corresponding to the logical channel comprises at least one of the following: clock information of the service corresponding to the logical channel; or time characteristic information of the service corresponding to the logical channel.

6. The method of claim 5, wherein the time characteristic information comprises at least one of the following: sending time information of a data packet; arrival time information of the data packet; sending period information of the data packet; sending duration information of the data packet in a period; length information of the data packet; duration information of the data packet residing in a cache; survival time information of the data packet; sending state information of a first n data packets of the data packet, n being a positive integer; a delay requirement of the data packet; a value of k in Hybrid Automatic Repeat Request (HARQ) timing of the data packet; a reliability requirement of the data packet; a Radio Network Temporary Identifier (RNTI) for scheduling and matching of the data packet; or a transmit power requirement of the data packet.

7. The method of claim 1, wherein when the time information of the service corresponding to each logical channel is determined, the method comprises at least one of the following: receiving time information of the service corresponding to the corresponding logical channel from the first communication node; or determining the time information of the service corresponding to the corresponding logical channel according to learned time characteristic information of the service corresponding to the logical channel.

8. The method of claim 7, wherein receiving the time information of the service corresponding to the corresponding logical channel from the first communication node through one of the following signaling: Downlink Control Information (DCI) of an Uplink (UL) grant; DCI of Downlink (DL) scheduling; Radio Resource Control (RRC) signaling carrying grand information of UL configuration; a signaling carrying semi-persistent scheduling (SPS) information of DL configuration; RRC signaling carrying configuration information of the logical channel; and RRC signaling carrying absolute time information.

9. The method of claim 1, wherein determining the time information of the service corresponding to the at least one logical channel comprises: receiving second information through one of the following: DCI of a UL grant; DCI of DL scheduling; RRC signaling carrying grand information of UL configuration; a signaling carrying SPS information of DL configuration; RRC signaling carrying configuration information of the logical channel; and RRC signaling carrying absolute time information; and determining the time information of the service corresponding to the logical channel by using the second information; wherein the second information represents at least one of the following: an indicated resource is aligned with a specific clock boundary or has a minimum offset from the specific clock boundary; and a period of the indicated resource has a multiple relationship with a period of the specific clock, or an offset of a period value of the indicated resource is the minimum.

10. The method of claim 1, further comprising: updating the time information of the service corresponding to at least one logical channel.

11. The method of claim 1, wherein the time information of the service corresponding to the logical channel comprises at least one of the following: time information of Universal Time Coordinated (UTC); an offset between the UTC and Global Positioning System (GPS); information about a relationship between Daylight Saving Time (DST) and local time; an offset between the UTC and the local time; an offset between the UTC and a specific network; a mapping relationship between

the UTC and a System Frame Number (SFN); indication information about whether a clock is a master clock; level information of the clock; information about an offset with respect to reference time of a specific clock type; synchronization precision information of the clock; synchronization granularity information of the clock; synchronization inaccuracy information; type information of the clock; reference time information; position relationship indication information of the reference time information and a received signaling; or, time update period information of the clock.

12. The method of claim 11, wherein the reference time information comprises at least one of the following: reference system radio frame information; reference subframe information; reference slot information; or reference time symbol information.

13. A terminal, comprising: a first processor, configured to determine time information of a service corresponding to at least one logical channel; and a first communication interface, configured to receive first information sent by a first communication node, the first information comprising a granted radio resource; wherein the first processor is further configured to select at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.

14. The terminal of claim 13, wherein the first processor is further configured to: when a priority of a first logical channel corresponding to a first data packet is lower than that of a second logical channel corresponding to a second data packet, and a time characteristic of the granted radio resource matches better with a time characteristic represented by time information corresponding to the first logical channel, preferentially schedule the first data packet corresponding to the first logical channel with the granted radio resource; or, when the priority of the first logical channel corresponding to the first data packet is the same as that of the second logical channel corresponding to the second data packet, and the time characteristic of the granted radio resource matches better with the time characteristic represented by the time information corresponding to the first logical channel, preferentially schedule the first data packet corresponding to the first logical channel with the granted radio resource.

15. The terminal of claim 13, wherein the first processor is further configured to: determine, according to a first weight and third information, a data packet corresponding to at least one logical channel and preferentially scheduled with the granted radio resource; wherein, the first weight is a predefined weight or a weight of a matching degree, indicated by the first communication node, between time characteristic of the granted radio resource and time characteristic represented by the time information corresponding to the corresponding logical channel; the third information comprises at least one of the following: a priority of logical information; a subcarrier spacing; or a duration of a Physical Uplink Shared Channel (PUSCH).

16. The terminal of claim 13, wherein the granted radio resource comprises at least one of the following: a dynamically scheduled granted radio resource; a Configured Granted (CG) radio resource; or a semi-persistent scheduling (SPS) radio resource.

17. The terminal of claim 13, wherein the time information of the service corresponding to the logical channel comprises at least one of the following: clock information of the service corresponding to the logical channel; or time characteristic information of the service corresponding to the logical channel.

18. The terminal of claim 17, wherein the time characteristic information comprises at least one of the following: sending time information of a data packet; arrival time information of the data packet; sending period information of the data packet; sending duration information of the data packet in a period; length information of the data packet; duration information of the data packet residing in a cache; survival time information of the data packet; sending state information of a first n data packets of the data packet, n being a positive integer; a delay requirement of the data packet; a value of k in Hybrid Automatic Repeat Request (HARQ) timing of the data packet; a reliability requirement of the data packet; a Radio Network Temporary Identifier (RNTI) for scheduling and matching of the data packet; or a transmit power requirement of the data packet.

19. The terminal of claim 13, wherein when the time information of the service corresponding to each logical channel is determined, at least one of: the first communication interface is further configured to receive time information of the service corresponding to the corresponding logical channel from the first communication node; or the first processor is further configured to determine the time information of the service corresponding to the corresponding logical channel according to learned time characteristic information of the service corresponding to the logical channel.

20. A non-transitory storage medium, having stored a computer program thereon, wherein the computer program, when executed by a processor of a terminal, implements a scheduling method, comprising: determining time information of a service corresponding to at least one logical channel; receiving first information sent by a first communication node, the first information comprising a granted radio resource; and selecting at least one logical channel for the granted radio resource based on the time information of the service corresponding to the at least one logical channel and configuration parameters of the at least one logical channel.
