

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403380
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kuo; Eric

Systems for protecting and repositioning teeth

Abstract

Systems for protecting and repositioning teeth are provided. In some embodiments, a system includes a tooth repositioning appliance and a covering guard. The tooth repositioning appliance can have a plurality of tooth-receiving cavities shaped to reposition teeth of a patient. The covering guard, when worn by the patient and coupled with the tooth repositioning appliance, can provide protection against impact-induced injuries. The covering guard can have a guard segment that covers at least a portion of the tooth repositioning appliance. A combination of the covering guard and the tooth repositioning appliance can include an occlusal portion disposed between a plurality of upper and lower teeth when worn by the patient. The occlusal portion can have a compliance selected to provide impact absorption during an impact forcing the lower teeth into the upper teeth.

Inventors:	Kuo; Eric (San Jose, CA)
Applicant:	Align Technology, Inc. (San Jose, CA)
Family ID:	42111466
Assignee:	Align Technology, Inc. (San Jose, CA)
Appl. No.:	18/475906
Filed:	September 27, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240024757 A1	Jan. 25, 2024

Related U.S. Application Data

division parent-doc US 15788529 20171019 US 11806602 child-doc US 18475906
division parent-doc US 12277191 20081124 ABANDONED child-doc US 15788529

Publication Classification

Int. Cl.: A61F5/00 (20060101); A61C7/08 (20060101); A61F5/56 (20060101); A63B71/08 (20060101)

U.S. Cl.:

CPC A63B71/085 (20130101); A61C7/08 (20130101); A61F5/566 (20130101); A63B2071/088 (20130101)

Field of Classification Search

CPC: A61C (5/90); A61C (5/14); A61C (7/08); A61C (7/36); A61C (7/00); A61C (2005/563); A63B (71/085); A63B (2071/086); A63B (2071/088); A61F (5/56); A61F (5/566); A61F (2005/563)

USPC: 128/848; 128/859; 128/861; 128/862; 433/5-8; 433/24

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
4755139	12/1987	Abbatte	433/6	A61C 7/08
5082007	12/1991	Adell	128/862	A63B 71/085
5293880	12/1993	Levitt	128/862	A63B 71/085
5499633	12/1995	Fenton	128/859	A61F 5/566
5536169	12/1995	Yousefian	433/6	A61C 5/007
5820368	12/1997	Wolk	N/A	N/A
6241518	12/2000	Sullivan	433/140	A61F 5/566
6386864	12/2001	Kuo	N/A	N/A
6450807	12/2001	Chishti et al.	N/A	N/A
6454565	12/2001	Phan et al.	N/A	N/A
6471511	12/2001	Chishti et al.	N/A	N/A
6607382	12/2002	Kuo et al.	N/A	N/A
6783604	12/2003	Tricca	N/A	N/A
6790035	12/2003	Tricca et al.	N/A	N/A
6814574	12/2003	Abolfathi et al.	N/A	N/A
6830450	12/2003	Knopp et al.	N/A	N/A
6947038	12/2004	Anh et al.	N/A	N/A
7074039	12/2005	Kopelman et al.	N/A	N/A
7104792	12/2005	Taub et al.	N/A	N/A
7121825	12/2005	Chishti et al.	N/A	N/A
7160107	12/2006	Kopelman et al.	N/A	N/A
7192273	12/2006	McSurdy, Jr.	N/A	N/A
7347688	12/2007	Kopelman et al.	N/A	N/A
7354270	12/2007	Abolfathi et al.	N/A	N/A
7448514	12/2007	Wen	N/A	N/A
7481121	12/2008	Cao	N/A	N/A
7543511	12/2008	Kimura et al.	N/A	N/A

7553157	12/2008	Abolfathi et al.	N/A	N/A
7600999	12/2008	Knopp	N/A	N/A
7658610	12/2009	Knopp	N/A	N/A
7766658	12/2009	Tricca et al.	N/A	N/A
7771195	12/2009	Knopp et al.	N/A	N/A
7854609	12/2009	Chen et al.	N/A	N/A
7871269	12/2010	Wu et al.	N/A	N/A
7878801	12/2010	Abolfathi et al.	N/A	N/A
7878805	12/2010	Moss et al.	N/A	N/A
7883334	12/2010	Li et al.	N/A	N/A
7914283	12/2010	Kuo	N/A	N/A
7947508	12/2010	Tricca et al.	N/A	N/A
8152518	12/2011	Kuo	N/A	N/A
8172569	12/2011	Matty et al.	N/A	N/A
8235715	12/2011	Kuo	N/A	N/A
8292617	12/2011	Brandt et al.	N/A	N/A
8337199	12/2011	Wen	N/A	N/A
8401686	12/2012	Moss et al.	N/A	N/A
8517726	12/2012	Kakavand et al.	N/A	N/A
8562337	12/2012	Kuo et al.	N/A	N/A
8641414	12/2013	Borovinskih et al.	N/A	N/A
8684729	12/2013	Wen	N/A	N/A
8708697	12/2013	Li et al.	N/A	N/A
8758009	12/2013	Chen et al.	N/A	N/A
8771149	12/2013	Rahman et al.	N/A	N/A
8899976	12/2013	Chen et al.	N/A	N/A
8899977	12/2013	Cao et al.	N/A	N/A
8936463	12/2014	Mason et al.	N/A	N/A
8936464	12/2014	Kopelman	N/A	N/A
9022781	12/2014	Kuo et al.	N/A	N/A
9119691	12/2014	Namiranian et al.	N/A	N/A
9161823	12/2014	Morton et al.	N/A	N/A
9241774	12/2015	Li et al.	N/A	N/A
9326831	12/2015	Cheang	N/A	N/A
9433476	12/2015	Khardekar et al.	N/A	N/A
9610141	12/2016	Kopelman et al.	N/A	N/A
9655691	12/2016	Li et al.	N/A	N/A
9675427	12/2016	Kopelman	N/A	N/A
9700385	12/2016	Webber	N/A	N/A
9744001	12/2016	Choi et al.	N/A	N/A
9844424	12/2016	Wu et al.	N/A	N/A
10045835	12/2017	Boronkay et al.	N/A	N/A
10111730	12/2017	Webber et al.	N/A	N/A
10150244	12/2017	Sato et al.	N/A	N/A
10201409	12/2018	Mason et al.	N/A	N/A
10213277	12/2018	Webber et al.	N/A	N/A
10299894	12/2018	Tanugula et al.	N/A	N/A
10363116	12/2018	Boronkay	N/A	N/A
10383705	12/2018	Shanjani et al.	N/A	N/A
D865180	12/2018	Bauer et al.	N/A	N/A

10449016	12/2018	Kimura et al.	N/A	N/A
10463452	12/2018	Matov et al.	N/A	N/A
10470847	12/2018	Shanjani et al.	N/A	N/A
10492888	12/2018	Chen et al.	N/A	N/A
10517701	12/2018	Boronkay	N/A	N/A
10537406	12/2019	Wu et al.	N/A	N/A
10537463	12/2019	Kopelman	N/A	N/A
10548700	12/2019	Fernie	N/A	N/A
10555792	12/2019	Kopelman et al.	N/A	N/A
10588776	12/2019	Cam et al.	N/A	N/A
10613515	12/2019	Cramer et al.	N/A	N/A
10639134	12/2019	Shanjani et al.	N/A	N/A
10743964	12/2019	Wu et al.	N/A	N/A
10758323	12/2019	Kopelman	N/A	N/A
10781274	12/2019	Liska et al.	N/A	N/A
10813720	12/2019	Grove et al.	N/A	N/A
10874483	12/2019	Boronkay	N/A	N/A
10881487	12/2020	Cam et al.	N/A	N/A
10912629	12/2020	Tanugula et al.	N/A	N/A
10959810	12/2020	Li et al.	N/A	N/A
10993783	12/2020	Wu et al.	N/A	N/A
11026768	12/2020	Moss et al.	N/A	N/A
11026831	12/2020	Kuo	N/A	N/A
11045282	12/2020	Kopelman et al.	N/A	N/A
11045283	12/2020	Riley et al.	N/A	N/A
11103330	12/2020	Webber et al.	N/A	N/A
11123156	12/2020	Cam et al.	N/A	N/A
11154382	12/2020	Kopelman et al.	N/A	N/A
11166788	12/2020	Webber	N/A	N/A
11174338	12/2020	Liska et al.	N/A	N/A
11219506	12/2021	Shanjani et al.	N/A	N/A
11259896	12/2021	Matov et al.	N/A	N/A
11273011	12/2021	Shanjani et al.	N/A	N/A
11278375	12/2021	Wang et al.	N/A	N/A
11318667	12/2021	Mojdeh et al.	N/A	N/A
11331166	12/2021	Morton et al.	N/A	N/A
11344385	12/2021	Morton et al.	N/A	N/A
11376101	12/2021	Sato et al.	N/A	N/A
11419702	12/2021	Sato et al.	N/A	N/A
11419710	12/2021	Mason et al.	N/A	N/A
11471253	12/2021	Venkatasanthanam et al.	N/A	N/A
11497586	12/2021	Kopelman	N/A	N/A
11504214	12/2021	Wu et al.	N/A	N/A
11523881	12/2021	Wang et al.	N/A	N/A
11534268	12/2021	Li et al.	N/A	N/A
11534974	12/2021	O'Leary et al.	N/A	N/A
11554000	12/2022	Webber	N/A	N/A
11564777	12/2022	Kopelman et al.	N/A	N/A
11571278	12/2022	Kopelman et al.	N/A	N/A
11571279	12/2022	Wang et al.	N/A	N/A

11576750	12/2022	Kopelman et al.	N/A	N/A
11576752	12/2022	Morton et al.	N/A	N/A
11589955	12/2022	Medvinskaya et al.	N/A	N/A
11596502	12/2022	Webber et al.	N/A	N/A
11602414	12/2022	Sato et al.	N/A	N/A
11642194	12/2022	Boronkay et al.	N/A	N/A
11642198	12/2022	Kopelman et al.	N/A	N/A
11666415	12/2022	Wang et al.	N/A	N/A
11701203	12/2022	Makarenkova et al.	N/A	N/A
11737857	12/2022	Derakhshan et al.	N/A	N/A
11779243	12/2022	Li et al.	N/A	N/A
11779437	12/2022	Cam et al.	N/A	N/A
11793606	12/2022	Cam et al.	N/A	N/A
2002/0192617	12/2001	Phan et al.	N/A	N/A
2003/0224312	12/2002	Bergersen	433/6	A61C 7/08
2004/0166462	12/2003	Phan et al.	N/A	N/A
2004/0166463	12/2003	Wen et al.	N/A	N/A
2005/0003318	12/2004	Choi	433/24	A61C 7/08
2005/0014105	12/2004	Abolfathi et al.	N/A	N/A
2005/0186524	12/2004	Abolfathi et al.	N/A	N/A
2005/0244768	12/2004	Taub et al.	N/A	N/A
2006/0019218	12/2005	Kuo	N/A	N/A
2006/0078841	12/2005	Desimone et al.	N/A	N/A
2006/0115782	12/2005	Li et al.	N/A	N/A
2006/0115785	12/2005	Li et al.	N/A	N/A
2006/0199142	12/2005	Liu et al.	N/A	N/A
2006/0234179	12/2005	Wen et al.	N/A	N/A
2007/0065768	12/2006	Nadav	433/18	A61C 7/08
2007/0084472	12/2006	Berghash	128/861	A63B 71/085
2008/0118882	12/2007	Su	N/A	N/A
2008/0160473	12/2007	Li et al.	N/A	N/A
2008/0286716	12/2007	Sherwood	N/A	N/A
2008/0286717	12/2007	Sherwood	N/A	N/A
2009/0272387	12/2008	Spencer	128/848	A61F 5/566
2009/0280450	12/2008	Kuo	N/A	N/A
2010/0055635	12/2009	Kakavand	N/A	N/A
2011/0269092	12/2010	Kuo et al.	N/A	N/A
2013/0244195	12/2012	Farrell	433/24	A61C 7/08
2014/0067334	12/2013	Kuo	N/A	N/A
2016/0193014	12/2015	Morton et al.	N/A	N/A
2017/0007359	12/2016	Kopelman et al.	N/A	N/A
2017/0135793	12/2016	Webber et al.	N/A	N/A
2018/0360567	12/2017	Xue et al.	N/A	N/A
2019/0046297	12/2018	Kopelman et al.	N/A	N/A
2019/0099129	12/2018	Kopelman et al.	N/A	N/A
2019/0262101	12/2018	Shanjani et al.	N/A	N/A
2019/0298494	12/2018	Webber et al.	N/A	N/A
2020/0155276	12/2019	Cam et al.	N/A	N/A
2020/0188062	12/2019	Kopelman et al.	N/A	N/A
2021/0147672	12/2020	Cole et al.	N/A	N/A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) The application is a divisional of U.S. patent application Ser. No. 15/788,529, filed Oct. 19, 2017, now U.S. Pat. No. 11,806,602, issued Nov. 7, 2023, which is a divisional of U.S. patent application Ser. No. 12/277,191, filed Nov. 24, 2008, each of which is incorporated by reference in its entirety.

BACKGROUND

(1) The present invention relates generally to the field of orthodontics, and more particularly to dental positioning appliances and mouth guards that provide protection against impact-induced injuries during a course of orthodontic treatment, as well as related methods and systems.

(2) An objective of orthodontics is to move a patient's teeth to positions where function and/or aesthetics are optimized. Traditionally, appliances such as braces are applied to a patient's teeth by a treating practitioner and the set of braces exerts continual force on the teeth and gradually urges them toward their intended positions. Over time and with a series of clinical visits and adjustments to the braces, the practitioner adjusts the appliances to move the teeth toward their final destination.

(3) More recently, alternatives to conventional orthodontic treatment with traditional affixed appliances (e.g., braces) have become available. For example, systems including a series of preformed appliances/aligners have become commercially available from Align Technology, Inc., Santa Clara, Calif., under the tradename Invisalign® System. The Invisalign® System is described in numerous patents and patent applications assigned to Align Technology, Inc. including, for example in U.S. Pat. Nos. 6,450,807, and 5,975,893, as well as on the company's website, which is accessible on the World Wide Web (see, e.g., the url "www.invisalign.com"). The Invisalign® System includes designing and/or fabricating multiple, and sometimes all, of the aligners to be worn by the patient before the aligners are administered to the patient and used to reposition the teeth (e.g., at the outset of treatment). Often, designing and planning a customized treatment for a patient makes use of computer-based 3-dimensional planning/design tools, such as Treat™ from Align Technology, Inc. The design of the aligners can rely on computer modeling of a series of planned successive tooth arrangements, and the individual aligners are designed to be worn over the teeth and elastically reposition the teeth to each of the planned tooth arrangements.

(4) While recently developed orthodontic treatment technologies, such as those described above, represent a considerable advancement in the field of orthodontics, additional advancements remain of interest. For example, certain individuals may engage in a sporting activity during their orthodontic treatment. In many sports, especially in contact sports such as football, a player typically wears a mouth guard so as to protect the player against impact-induced injuries, including concussion. As such, there is a need for innovative products that provide an orthodontic patient with protection against impact-induced injuries.

BRIEF SUMMARY

(5) The present disclosure provides protective positioning appliances, accommodating mouth guards, and covering guards that provide an orthodontic patient with protection against impact-induced injuries, and related systems and methods. The disclosed protective appliances, accommodating mouth guards, and covering guards provide the ability to have a patient's teeth protected while undergoing orthodontic treatment, such with the Invisalign® System. Mouth guards are often used by players of contact sports, such as football.

(6) For a fuller understanding of the nature and advantages of the present invention, reference should be made to the ensuing detailed description and accompanying drawings. Other aspects, objects and advantages of the invention will be apparent from the drawings and detailed description that follows.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 illustrates a jaw together with an incremental positioning appliance.
- (2) FIG. 2 illustrates a jaw together with a protective incremental positioning appliance according to an embodiment of the present invention.
- (3) FIG. 3 illustrates a jaw together with a protective incremental positioning appliance according to another embodiment of the present invention.
- (4) FIGS. 4A and 4B are cross-sectional illustrations of teeth received within protective incremental positioning appliances according to embodiments of the present invention.
- (5) FIG. 5 illustrates a fabrication process that can be used to create upper arch and lower arch protective incremental positioning appliances, accommodating mouth guards, covering guards, and/or accommodating covering guards that have complementary coupling features according to embodiments of the present invention.
- (6) FIGS. 6A and 6B are cross-sectional illustrations of teeth received within accommodating mouth guards according to embodiments of the present invention.
- (7) FIG. 7 is a cross-sectional diagram illustrating the accommodation of a single tooth along a path of intermediate stages according to embodiments of the present invention.
- (8) FIGS. 8A and 8B are cross-sectional illustrations of teeth received within incremental positioning appliances that are coupled with covering guards in accordance with embodiments of the present invention.
- (9) FIGS. 9A and 9B are cross-sectional illustrations of teeth received within incremental positioning appliances that are coupled with accommodating covering guards in accordance with embodiments of the present invention.
- (10) FIG. 10 is a simplified block diagram illustrating a system of accommodating mouth guards in accordance with embodiments of the present invention.
- (11) FIG. 11 is a simplified block diagram illustrating a system of accommodating covering guards in accordance with embodiments of the present invention.
- (12) FIGS. 12 and 13 are simplified block diagrams illustrating methods for fabricating protective incremental positioning appliances according to embodiments of the present invention.
- (13) FIGS. 14 and 15 are simplified block diagrams illustrating methods for fabricating accommodating mouth guards according to embodiments of the present invention.
- (14) FIG. 16 diagrammatically illustrates a system according to an embodiment of the present invention.

DETAILED DESCRIPTION

- (15) Protective repositioning appliances, accommodating mouth guards, covering guards and accommodating covering guards are provided that protect an orthodontic patient against impact-induced injuries, as well as related systems and methods. In the absence of adequate protection, players of certain contact sports, such as football, may be exposed to a significant risk of impact-induced injuries. The presently disclosed appliances, guards, systems and methods provide a means by which an orthodontic patient can be protected against oral-related impact induced injuries during a course of orthodontic treatment.
- (16) A protective repositioning appliance can be configured to reposition a patient's teeth while protecting the patient against impact-induced injuries. Such a protective repositioning appliance

can include teeth receiving cavities that are shaped to resiliently reposition a patient's teeth from a first arrangement towards a second arrangement. A protective repositioning appliance can be further configured to have a shape or material selected to provide protection against impact-induced injury.

(17) An accommodating mouth guard can be configured to protect an orthodontic patient's teeth during a portion of a course of orthodontic treatment, during which the patient's teeth are repositioned from a first arrangement towards a second arrangement. An accommodating mouth guard can include teeth receiving cavities that are shaped to accommodate a range of positions of the patient's teeth. A system of accommodating mouth guards can be used to provide protection during multiple stages of orthodontic treatment, where during each stage a patient's teeth are repositioned by some amount.

(18) A covering guard can be configured to couple with at least a portion of a tooth repositioning appliance. The combination of the covering guard and the tooth repositioning appliance can serve to protect the orthodontic patient against impact-induced injuries. An accommodating covering guard can be configured to couple with a sequence of tooth repositioning appliances.

(19) Tooth Repositioning Appliances

(20) FIG. 1 provides an appropriate starting point in a discussion of the present invention with respect to tooth repositioning appliances designed to apply repositioning forces to teeth. A tooth repositioning appliance **10** can be worn by a patient in order to achieve an incremental repositioning of individual teeth in the jaw **11**. The appliance can include a shell (e.g., polymeric shell) having teeth-receiving cavities that receive and resiliently reposition the teeth. In one embodiment, a polymeric appliance can be formed from a known thin sheet of suitable elastomeric polymeric material, such a 0.03 inch thermal forming dental material by Tru-Tain Plastics, Rochester, Minn. An appliance can fit over all teeth present in an upper or lower jaw, or less than all of the teeth. In some cases, only certain teeth received by an appliance will be repositioned by the appliance while other teeth can provide a base or anchor region for holding the appliance in place as it applies force against the tooth or teeth targeted for repositioning. In some cases, many or most, and even all, of the teeth will be repositioned at some point during treatment. Teeth that are moved can also serve as a base or anchor for holding the appliance as it is worn by the patient. Typically, no wires or other means will be provided for holding an appliance in place over the teeth. In some cases, however, it may be desirable or necessary to provide individual anchors on teeth with corresponding receptacles or apertures in the appliance so that the appliance can apply a selected force on the tooth. Exemplary appliances, including those utilized in the Invisalign® System, are described in numerous patents and patent applications assigned to Align Technology, Inc. including, for example in U.S. Pat. Nos. 6,450,807, and 5,975,893, as well as on the company's website, which is accessible on the World Wide Web (see, e.g., the url “www.invisalign.com”).

(21) An appliance can be designed and/or provided as part of a set or plurality of appliances. In such an embodiment, each appliance may be configured so a tooth-receiving cavity has a geometry corresponding to an intermediate or final tooth arrangement intended for the appliance. The patient's teeth can be progressively repositioned from an initial tooth arrangement to a target tooth arrangement by placing a series of incremental position adjustment appliances over the patient's teeth. A target tooth arrangement can be a planned final tooth arrangement selected for the patient's teeth at the end of all planned orthodontic treatment. Alternatively, a target arrangement can be one of many intermediate arrangements for the patient's teeth during the course of orthodontic treatment, which may include where surgery is recommended, where inter-proximal reduction (IPR) is appropriate, where a progress check is scheduled, where anchor placement is best, where palatal expansion is desirable, etc. As such, it is understood that a target tooth arrangement can be any planned resulting arrangement for the patient's teeth that follows one or more incremental repositioning stages. Likewise, an initial tooth arrangement can be any initial arrangement for the patient's teeth that is followed by one or more incremental repositioning stages. The adjustment

appliances can be generated all at the same stage or in sets or batches, e.g., at the beginning of a stage of the treatment, and the patient wears each appliance until the pressure of each appliance on the teeth can no longer be felt or has resulted in the maximum amount of expressed tooth movement for that given stage. A plurality of different appliances (e.g., set) can be designed and even fabricated prior to the patient wearing any appliance of the plurality. After wearing an appliance for an appropriate period of time, the patient replaces the current appliance with the next appliance in the series until no more appliances remain. The appliances are generally not affixed to the teeth and the patient may place and replace the appliances at any time during the procedure (e.g., patient-removable appliances). The final appliance or several appliances in the series may have a geometry or geometries selected to overcorrect the tooth arrangement, i.e., have a geometry which would (if fully achieved) move individual teeth beyond the tooth arrangement which has been selected as the “final.” Such over-correction may be desirable in order to offset potential relapse after the repositioning method has been terminated, i.e., to permit movement of individual teeth back toward their pre-corrected positions. Over-correction may also be beneficial to speed the rate of correction, i.e., by having an appliance with a geometry that is positioned beyond a desired intermediate or final position, the individual teeth will be shifted toward the position at a greater rate. In such cases, the use of an appliance can be terminated before the teeth reach the positions defined by the appliance.

(22) Protective Repositioning Appliances

(23) Protective dental appliances are provided that reposition a patient's teeth and provide protection against impact-induced injuries. A protective appliance can include teeth receiving cavities shaped to receive and reposition a patient's teeth. A protective appliance can have a shape or material selected to provide protection against impact-induced injury.

(24) Referring now to FIG. 2, an embodiment of a protective repositioning appliance **20** is shown. Similar to the tooth repositioning appliance **10** shown in FIG. 1, the protective repositioning appliance **20** includes teeth receiving cavities (hidden from view in FIG. 2) shaped to receive and resiliently reposition a patient's teeth. In the embodiment shown, the protective appliance **20** includes an optional u-shaped tray **22** for receiving the patient's opposite jaw teeth when the patient bites down. The u-shaped tray **22** can be defined in part by an occlusal-pad portion **24**, which can be configured so as to exhibit an impact-absorbing compliance during an impact that forces the lower teeth into the upper teeth. The amount of compliance can be influenced by the elasticity and thickness of material used in the occlusal-pad portion. The amount of compliance can also be influenced by the span coverage of the occlusal-pad portion. Additionally, the optional u-shaped tray is partially defined by buccal wall **26** and lingual wall **28**. The buccal wall **26** and lingual wall **28** can serve to laterally couple a plurality of a patient's upper and lower jaw teeth so as to help protect against lateral impact-induced injuries by distributing localized lateral impacts to surrounding tissues.

(25) A protective repositioning appliance **20** can come in a range of variations. For example, an appliance **20** can also be adapted to permit better air flow and breathing while the patient bites down. In the embodiment shown, a plurality of traverse air passages **30** are provided so as to permit the flow of air between buccal and lingual sides of the appliance **20**. A variety of other configurations can also be used to facilitate mouth breathing. For example, one or more regions of the buccal wall **26**, the lingual wall **28**, and/or the occlusal-pad portion **24** can be modified so as to provide air passages across the appliance **20**. A protective repositioning appliance **20** can also include provisions for the attachment of a connecting leash, such as the leash tab **32** shown. A connecting leash can be used to couple the appliance with the patient so that it will not get misplaced, such as by attaching the connecting leash to a football helmet or the like. A variety of other configurations may be used to provide for the attachment of a connecting leash, such as loops, sockets, or the like.

(26) An appliance can also include a selected color or ornamental design. For example, an

appliance can include embedded colors and/or logos, such as for a team or a sponsor. As another example, an appliance can be made with camouflage color for military use. An appliance can also be labeled with personal information, such as the name of the owner, or the number of the owner's athletic jersey.

(27) An appliance can be multi-laminate in composition, such that the different layers of the appliance confer different physical properties. For example, an outer layer can be softer for greater impact protection and an inner layer can be made of harder material for better adaptation to the teeth. An appliance can be tri-laminate, with an outer layer being hard for durability, a middle layer being softer for impact absorption, and an inner layer being hard for better adaptation and retention.

(28) FIG. 3 illustrates another protective repositioning appliance **40**, in accordance with an embodiment. Appliance **40** includes a plurality of teeth receiving cavities **42** for the patient's upper and lower teeth. Appliance **40** can be configured to be an integral unit, or can be configured to include an upper component **44** and a lower component **46**, each of which can include teeth receiving cavities **42**. Where separate upper and lower components are used, they can be configured with complementary interfacing surfaces (not shown in FIG. 3). These complementary interfacing surfaces can serve to laterally couple a plurality of a patient's upper and lower teeth, thereby helping to distribute localized lateral impacts to surrounding tissues. These complementary surfaces can also provide for snap-fit coupling between the upper component **44** and the lower component **46**. Appliance **40** can also be adapted to facilitate mouth breathing while the patient is biting down, such as by the traverse air passages **48** shown. Additionally, an appliance **40** can be adapted to facilitate mouth breathing in a variety of different ways, such as discussed above with reference to FIG. 2.

(29) FIGS. 4A and 4B are cross-sectional illustrations of embodiments of protective repositioning appliances. FIG. 4A illustrates a cross-section of an appliance **50** having lower-teeth receiving cavities. The appliance can include an occlusal-pad portion **52** and an optional u-shaped tray **54** for receiving the patient's upper teeth. As discussed above with reference to FIG. 2, the occlusal-pad portion **52** can be configured to exhibit an impact absorbing compliance so as to reduce peak forces transmitted between the patient's jaws during an impact that forces the lower teeth into the upper teeth, or vice-versa. The optional u-shaped tray **54** can be configured to provide coupling between a plurality of the patient's upper and lower teeth, so as to distribute localized lateral impact forces to surrounding tissues thereby reducing the level of localized impact forces felt by local tissues. The appliance **50** of FIG. 4A can be used to protect a patient against impact-induced injuries while simultaneously subjecting the patient's lower teeth to resilient repositioning forces. An analogous, but opposite, appliance can be used for to reposition the patient's upper teeth while providing protection against impact-induced injuries. The appliance **60** of FIG. 4B includes an upper component **62** having teeth receiving cavities for the patient's upper teeth **64**, and a lower component **66** having teeth receiving cavities for the patient's lower teeth **68**.

(30) The upper and lower components can be configured with complementary shaped interfacing surfaces, such as the snap-fit surfaces **70** shown. These complementary-shaped surfaces can provide for lateral coupling between a plurality of the patient's upper and lower teeth, thereby enhancing the distribution of localized lateral impact forces to surrounding tissues. Various complementary shaped interfacing surfaces can be used. For example, FIG. 5 illustrates a fabrication process that can be used to create upper arch and lower arch protective incremental positioning appliances, accommodating mouth guards, covering guards, and/or accommodating covering guards that have complementary coupling features. Thin sheets **72**, **74** of a suitable elastomeric polymeric material can be configured with complementary coupling features, such as ribs on sheet **72** and grooves on sheet **74**, or any other complementary shaped features. Sheet **72** can be formed over a positive mold **76** to form an upper arch component **80** having complementary shaped features disposed on its outer surface. Likewise, sheet **74** can be formed over a positive mold **78** to form a lower arch component **82** having complementary shaped features disposed on its

outer surface. When worn by a patient, one or more upper arch component features **84** can interface with one or more lower arch component features **86** so as to provide the above discussed lateral coupling. Components **80**, **82** can be a protective incremental positioning appliance, an accommodating mouth guard, a covering guard, or an accommodating covering guard.

(31) Accommodating Mouth Guards

(32) Accommodating mouth guards are provided that can be used during a portion of a course of orthodontic treatment. An accommodating mouth guard can accommodate a range of positions of the patient's teeth. An accommodating mouth guard may or may not supply any repositioning forces to a patient's teeth. Instead, an accommodating mouth guard can be used in place of a tooth positioning appliance during a sporting activity.

(33) Accommodating mouth guards are provided that can be used during a course of orthodontic treatment. An accommodating mouth guard can include teeth receiving cavities shaped to accommodate a patient's teeth in a first and a second arrangement. An accommodating mouth guard can have a shape or material selected to provide protection against impact-induced injury.

(34) FIGS. **6A** and **6B** are cross-sectional illustrations of embodiments of accommodating mouth guards. FIG. **6A** illustrates a cross-section of an accommodating mouth guard **100** having lower-teeth receiving cavities. Accommodation of a range of positions of the patient's teeth can be provided in a number of ways. For example, as shown in FIG. **6A**, the teeth receiving cavities can be configured with additional volume selected to accommodate the range of positions. This additional volume provides a cavity of sufficient dimensions to accommodate a tooth in any of the range of positions along the path of possible tooth positions from the initial point to the end point (i.e., the tooth's swept volume). As another example, the appliance cavity walls can include sufficient compliance so as to be able to deflect a sufficient amount to accept the tooth in any of the range of positions. A combination of additional volume and cavity wall compliance can also be used. As such, it is understood that a tooth receiving cavity can be shaped to accommodate a range of positions for the tooth in a variety of ways, including those discussed above. Additionally, an accommodating mouth guard can include features similar to features of a protective repositioning appliance, such as the occlusal-pad portion **102** and the optional u-shaped tray **104** as shown, and as discussed above with reference to FIG. **4A**. Similarly, the accommodating mouth guard **100** of FIG. **6A** can be likewise configured for a patient's upper teeth.

(35) Accommodating mouth guards can also be advantageously configured to selectively provide accommodation only for teeth that are being repositioned during a stage of orthodontic treatment. During orthodontic treatment using repositioning appliances, an appliance, or even a series of appliances, may be used to reposition a subset of the patient's teeth. The remaining teeth may not be repositioned during the stage of treatment. The teeth receiving cavities for non-repositioned teeth can be configured without accommodation, thereby providing for a more secure coupling with the non-moving teeth. This more secure coupling can provide for a more secure coupling between the accommodating mouth guard and the patient's teeth in general.

(36) The accommodating mouth guard **110** of FIG. **6B** includes an upper component **112** having teeth receiving cavities for the patient's upper teeth **114**, and a lower component **116** having teeth receiving cavities for the patient's lower teeth **118**. As discussed above with reference to FIG. **6A**, these teeth receiving cavities can be configured to accommodate a range of positions for any subset of teeth that are being repositioned during a stage of orthodontic treatment, and omit accommodation for any subset of teeth that are not being repositioned during the stage of treatment. Similarly, the upper and lower component can be configured with complementary-shaped interfacing surfaces, such as the snap-fit surfaces **120** shown. These complementary-shaped surfaces can provide for a level of lateral coupling between a plurality of the patient's upper and lower teeth, thereby enhancing the distribution of localized lateral impact forces to surrounding tissues.

(37) FIG. **7** is a simplified cross-sectional diagram of the cavity walls **121** of an accommodating

mouth guard and received teeth **122**, **123**, **124** that illustrates the accommodation of a single tooth **123** along a path of movement. As can be seen, the cavity walls **121** that surround tooth **123** are configured to accommodate the entire path of the tooth **123** (i.e., the swept volume) for a sequence of positions **125**, **126**, **127**. Such accommodation can also be incorporated into an accommodating covering guard.

(38) Accommodating mouth guards may also be designed to accommodate orthodontic treatment that is being performed using fixed wire and bracket braces. The accommodation in the mouth guard would allow the mouth guard to fit around both the braces and the archwire, and enable a range of tooth movements to take place for the given time period for which the guard is applicable. The braces treatment plan can be digitally planned out in advance, so that an accommodating mouth guard can be designed to work for a specific portion of the treatment plan.

(39) Covering Guards

(40) Covering guards are provided that can be coupled with a tooth repositioning appliance so as to provide protection against impact-induced injuries. A covering guard can include a guard segment that covers at least a portion of an appliance. In some embodiments, the covering guard includes at least one snap-fit feature for coupling the guard segment with the tooth repositioning appliance. The combination of a guard segment and an appliance can have a shape or material selected to provide protection against impact-induced injury. In some embodiments, the covering guard has a multi-laminate material.

(41) Covering guards are provided that can be used in combination with a repositioning appliance so as to provide protection against impact-induced injury. FIG. **8A** is a cross-sectional illustration of a covering guard **130** in accordance with an embodiment. As shown, a covering guard can be coupled with a basic repositioning appliance **132**. A covering guard can be coupled with a repositioning appliance **132** in a variety of ways. For example, the covering guard **130** shown includes repositioning appliance receiving cavities that provide an interface with the underlying repositioning appliance **132**. A covering guard can include a variety of features similar to features discussed above, such as an optional u-shaped tray **134** for receiving teeth from the opposing arch, and an occlusal-pad portion **136**. As discussed above, the optional u-shaped tray **134** can provide for lateral coupling between a plurality of the patient's upper and lower teeth, thereby helping to distribute localized lateral impact forces to surrounding tissues. The occlusal-pad portion **136** can be configured to provide an impact-absorbing compliance so as to reduce peak forces transmitted between the patient's arches during an impact that forces the arches together. This reduction of peak transmitted forces can help to reduce the occurrence of impact-induced injuries, such as damage to teeth or concussion.

(42) FIG. **8B** is a cross-sectional illustration of a covering guard **140** in accordance with an embodiment. The covering guard **140** includes an upper component **146** adapted to couple with an upper-arch appliance **142**, and a lower component **148** adapted to couple with a lower-arch appliance **144**. As discussed above, a variety of ways can be used to couple the upper and lower components with an underlying repositioning appliance. In the embodiment shown, the upper and lower components have appliance receiving cavities that provide an interface with the underlying repositioning appliance. The upper and lower component can be configured with complementary-shaped interfacing surfaces, such as the snap-fit surfaces **150** shown. Complementary-shaped interfacing surfaces can provide for lateral coupling between a plurality of the patient's upper and lower teeth, thereby enhancing the distribution of localized lateral impact forces to surrounding tissues.

(43) Accommodating Covering Guards

(44) Accommodating covering guards are provided that combine characteristics of an accommodating mouth guard and a covering guard. As such, an accommodating covering guard can be configured to interface with a series of underlying repositioning appliances. FIGS. **9A** and **9B** illustrate embodiments of accommodating covering guards **160**, **170**. Because these

accommodating guards share characteristics with the accommodating mouth guards and covering guards discussed above, the above discussion applies and will not be repeated here.

(45) Protective Systems

(46) Systems are provided that provide protection against impact-induced injuries during a multi-stage orthodontic treatment. An orthodontic treatment stage can include a series of appliances shaped to reposition a patient's teeth from an arrangement to a subsequent arrangement. A system can include a first accommodating mouth guard for use during a first treatment stage, and a second accommodating mouth guard for use during a second treatment stage. An accommodating mouth guard can include teeth receiving cavities shaped to accommodate a range of positions of a patient's teeth. An accommodating mouth guard can have a shape or material selected to provide protection against impact-induced injury. A system can include a first accommodating covering guard for use during a first treatment stage, and a second accommodating covering guard for use during a second treatment stage. An accommodating covering guard can be configured to interface with a series of repositioning appliances.

(47) A series of two or more of the above discussed protective repositioning appliances, accommodating mouth guards, covering guards, or accommodating covering guards can be used to form a protective system. In the case of protective repositioning appliances or covering guards, the period of use of a particular protective repositioning appliance or covering guard can be generally equivalent to the period of use of an analogous or associated basic repositioning appliance. In the case of accommodating mouth guards or accommodating covering guards, the period of use can be greater than the period of use of an analogous or associated basic repositioning appliance. The period of use for accommodating mouth guards or accommodating covering guards will typically depend on the range of positions accounted for, and the rate that the teeth are being repositioned.

(48) FIG. 10 diagrammatically illustrates a system **180** of accommodating mouth guards. The system can include a first accommodating mouth guard **182** that is worn during a first treatment stage during which the patient's teeth are repositioned from a first arrangement to a second arrangement. The system can include a second accommodating mouth guard **184** that is worn during a second treatment stage during which the patient's teeth are repositioned from the second arrangement to a third arrangement. The system can also include additional accommodating mouth guards, such as an Nth accommodating mouth guard **186**. Similarly, FIG. 11 diagrammatically illustrates an analogous system **190** of accommodating covering guards **192**, **194**, and **196**.

(49) Fabrication Methods

(50) FIG. 12 diagrammatically illustrates a method **200** that can be used to fabricate of a protective positioning appliance. In step **202**, digital models of teeth-receiving cavities are obtained. These cavities are shaped so that when incorporated into a protective repositioning appliance the appliance exerts resilient forces to the patient's teeth so as to reposition the patient's teeth over time. In step **204**, the digital models are used to fabricate a positive mold. The positive mold can be fabricated using a variety of approaches, such as by way of a rapid prototyping machine such as a stereo lithography or digital light projector machine, or also via computer numerical control (CNC) milling. An exemplary rapid prototyping machine is available from 3D System, Valencia, Calif. or EnvisionTEC, Gladbeck, Germany. The rapid prototyping machine can selectively harden a liquid or other non-hardened resin into a three-dimensional structure which can be separated from the remaining non-hardened resin, washed, and used as a positive mold for the appliance. Where such a fabrication method is used, a digital model that includes a negative representation of the teeth-receiving cavities can be prepared from which the positive mold can be fabricated. In step **206**, the appliance is fabricated by forming material over the positive mold.

(51) FIG. 13 diagrammatically illustrates a method **210** that can be used to fabricate of a protective positioning appliance having an upper component with upper-teeth receiving cavities, and having a lower component with lower-teeth receiving cavities. In step **212**, digital models of the teeth receiving cavities are received. In step **214**, an upper-positive mold can be fabricated using the

digital models for the upper-teeth receiving cavities as discussed above. In step **216**, an upper component is fabricated using the upper-positive mold. In step **218**, a lower-positive mold can be fabricated using the digital models for the lower-teeth receiving cavities as discussed above. In step **220**, a lower component is fabricated using the lower positive mold. In step **222**, the appliance is fabricated using the upper and lower components.

(52) FIG. **14** diagrammatically illustrates a method **230** that can be used to fabricate an accommodating mouth guard. In step **232**, digital models of teeth in an initial arrangement are obtained. In step **234**, digital models of teeth in a subsequent arrangement are obtained. The initial arrangement and the subsequent arrangements can be the starting and the ending arrangements for which accommodation is to be provided. In step **236**, the digital models are combined so as to generate an accommodation model that includes geometry that accommodates the positions of the teeth as they move from the initial arrangement to the subsequent arrangement. Intermediate arrangements between the initial arrangement and the subsequent arrangement can also be used in the generation of the accommodation model so as to more accurately accommodate for intermediate positions of the patient's teeth. A "swept volume" representing the spatial path of each tooth from the beginning to the end within the series can be built in so that the appliance will not interfere with the tooth movement planned during the tooth movement interval for which the guard is designed to accommodate. In step **238**, a positive mold is fabricated by using the accommodation model. The positive mold can be fabricated in a variety of ways, such as by using a rapid prototyping machine as discussed above. In step **240**, the accommodating mouth guard is fabricated using the positive mold.

(53) FIG. **15** diagrammatically illustrates a method **250** that can be used to fabricate of an accommodating mouth guard having an upper component with upper-teeth receiving cavities and a lower component with lower-teeth receiving cavities. In step **252**, digital models of teeth in an initial arrangement are obtained. In step **254**, digital models of teeth in a subsequent arrangement are obtained. In step **256**, the digital models are used to generate an accommodation model that includes geometry that accommodates the positions of the teeth as they move from the initial arrangement to the subsequent arrangement. As discussed above, one or more intermediate arrangements can also be used in the formation of the accommodation model so as to more accurately account for intermediate positions of the teeth. In step **258**, an upper-positive mold is fabricated by using the accommodation model. In step **260**, an upper component is fabricated by using the upper-positive mold. In step **262**, a lower-positive mold is fabricated by using the accommodation model. In step **264**, a lower component is fabricated by using the lower-positive mold. In step **266**, the mouth guard is fabricated from the upper and lower components.

(54) FIG. **16** is a simplified block diagram of a data processing system **300** embodying the present invention. Data processing system **300** typically includes at least one processor **302** which communicates with a number of peripheral devices via bus subsystem **304**. These peripheral devices typically include a storage subsystem **306** (memory subsystem **308** and file storage subsystem **314**), a set of user interface input and output devices **318**, and an interface to outside networks **316**, including the public switched telephone network. This interface is shown schematically as "Modems and Network Interface" block **316**, and is coupled to corresponding interface devices in other data processing systems via communication network interface **324**. Data processing system **300** could be a terminal or a low-end personal computer or a high-end personal computer, workstation or mainframe.

(55) The user interface input devices typically include a keyboard and may further include a pointing device and a scanner. The pointing device may be an indirect pointing device such as a mouse, trackball, touchpad, or graphics tablet, or a direct pointing device such as a touch screen incorporated into the display. Other types of user interface input devices, such as voice recognition systems, are also possible.

(56) User interface output devices typically include a printer and a display subsystem, which

includes a display controller and a display device coupled to the controller. The display device may be a cathode ray tube (CRT), a flat-panel device such as a liquid crystal display (LCD), or a projection device. The display subsystem may also provide non-visual display such as audio output.

(57) Storage subsystem **306** maintains the basic programming and data constructs that provide the functionality of the present invention. The software modules discussed above are typically stored in storage subsystem **306**. Storage subsystem **306** typically comprises memory subsystem **308** and file storage subsystem **314**.

(58) Memory subsystem **308** typically includes a number of memories including a main random access memory (RAM) **310** for storage of instructions and data during program execution and a read only memory (ROM) **312** in which fixed instructions are stored. In the case of Macintosh-compatible personal computers the ROM would include portions of the operating system; in the case of IBM-compatible personal computers, this would include the BIOS (basic input/output system).

(59) File storage subsystem **314** provides persistent (non-volatile) storage for program and data files, and typically includes at least one hard disk drive and at least one disk drive (with associated removable media). There may also be other devices such as a CD-ROM drive and optical drives (all with their associated removable media). Additionally, the system may include drives of the type with removable media cartridges. The removable media cartridges may, for example be hard disk cartridges, such as those marketed by Syquest and others, and flexible disk cartridges, such as those marketed by Iomega. One or more of the drives may be located at a remote location, such as in a server on a local area network or at a site on the Internet's World Wide Web.

(60) In this context, the term "bus subsystem" is used generically so as to include any mechanism for letting the various components and subsystems communicate with each other as intended. With the exception of the input devices and the display, the other components need not be at the same physical location. Thus, for example, portions of the file storage system could be connected via various local-area or wide-area network media, including telephone lines. Similarly, the input devices and display need not be at the same location as the processor, although it is anticipated that the present invention will most often be implemented in the context of PCs and workstations.

(61) Bus subsystem **304** is shown schematically as a single bus, but a typical system has a number of buses such as a local bus and one or more expansion buses (e.g., ADB, SCSI, ISA, EISA, MCA, NuBus, or PCI), as well as serial and parallel ports. Network connections are usually established through a device such as a network adapter on one of these expansion buses or a modem on a serial port. The client computer may be a desktop system or a portable system.

(62) Scanner **320** is responsible for scanning casts of the patient's teeth obtained either from the patient or from an orthodontist and providing the scanned digital data set information to data processing system **300** for further processing. In a distributed environment, scanner **320** may be located at a remote location and communicate scanned digital data set information to data processing system **300** via network interface **324**.

(63) Fabrication machine **322** can encompass a range of fabrication machines and methods used to fabricate positive molds, protective positioning appliances, accommodating mouth guards, or covering guards based on data set information received from data processing system **300**. In a distributed environment, fabrication machine **322** may be located at a remote location and receive data set information from data processing system **300** via network interface **324**.

(64) It is understood that the examples and embodiments described herein are for illustrative purposes and that various modifications or changes in light thereof will be suggested to persons skilled in the art and are to be included within the spirit and purview of this application and the scope of the appended claims. Numerous different combinations are possible, and such combinations are considered to be part of the present invention.

Claims

1. A system comprising: an aligner having a polymeric shell comprising a plurality of tooth-receiving cavities shaped to reposition teeth of a patient, wherein the polymeric shell is shaped to cover an occlusal surface of the patient's teeth when the aligner is worn by the patient; and a covering guard for providing protection against impact-induced injuries when coupled with the aligner and when worn by the patient, the covering guard comprising a guard segment shaped to cover at least a portion of the aligner, a combination of the guard segment and the aligner shaped to provide protection against impact-induced injury, wherein the combination comprises an occlusal portion disposed between a plurality of upper and lower teeth when the combination is worn by the patient, the occlusal portion having a compliance selected to provide impact absorption during an impact forcing the lower teeth into the upper teeth, and wherein the covering guard is configured to be removably coupled to the aligner.
2. The system of claim 1, wherein the guard segment is adapted to interface with a sequence of aligners.
3. The system of claim 1, wherein the guard segment comprises a u-shaped portion for receiving a plurality of teeth not received within the aligner.
4. The system of claim 1, wherein the covering guard further comprises a leash tab.
5. The system of claim 1, wherein the covering guard is adapted to facilitate mouth breathing while the patient bites down.
6. The system of claim 1, wherein the covering guard further comprises a multi-laminate material.
7. The system of claim 1, wherein the covering guard further comprises at least one snap-fit feature for coupling the guard segment with the aligner.
8. The system of claim 1, wherein the covering guard further comprises a selected color or ornamental design.
9. The system of claim 1, wherein the covering guard further comprises an upper component for covering an upper arch aligner and a lower component for covering a lower arch aligner.
10. The system of claim 9, wherein the upper component and the lower component comprise complementary coupling features.
11. The system of claim 10, wherein the complementary coupling features comprise snap-fit features.
12. The system of claim 10, wherein the complementary coupling features comprise a plurality of ribs and a plurality of grooves.
13. The system of claim 9, wherein the covering guard further comprises an integral component comprising the upper component and the lower component.
14. A system for protecting a patient during an orthodontic treatment, the system comprising: an aligner having a polymeric shell comprising a plurality of tooth-receiving cavities shaped to reposition teeth of a patient's jaw from a first arrangement toward a second arrangement, wherein the polymeric shell is shaped to cover an occlusal surface of the teeth when the aligner is worn by the patient; and a mouth guard shaped to protect the teeth, the mouth guard comprising: a plurality of cavities shaped to receive the teeth during the orthodontic treatment and accommodate the aligner when worn on the teeth, and an occlusal portion connected to the plurality of cavities, wherein the occlusal portion is shaped to reduce impact forces on the teeth, wherein the mouth guard is configured to be removably coupled to the aligner.
15. The system of claim 14, further comprising: a second mouth guard shaped to protect a second plurality of teeth on a second jaw of the patient, the second mouth guard comprising: a second plurality of cavities shaped to receive the second teeth; and a second occlusal portion connected to the second plurality of cavities.
16. The system of claim 14, wherein the mouth guard does not apply repositioning forces to the

teeth.

17. The system of claim 14, wherein the occlusal portion comprises one or more interfacing surfaces.

18. The system of claim 17, wherein the one or more interfacing surfaces are configured to interface with second teeth on an opposite jaw of the patient.

19. The system of claim 17, wherein the one or more interfacing surfaces are configured to interface with a second mouth guard.

20. The system of claim 14, wherein the impact forces comprise forces transmitted between a first dental arch and a second dental arch of the patient.

21. The system of claim 14, wherein the mouth guard comprises a multi-laminate material comprising a hard outer layer, a soft middle layer, and a hard inner layer.

22. The system of claim 14, wherein the plurality of cavities comprises an accommodation envelope providing a swept volume that accommodates the aligner.

23. The system of claim 22, wherein the swept volume accommodates at least one tooth of the teeth along a spatial path from a first location of the at least one tooth in the first arrangement to a second location of the at least one tooth in the second arrangement.
