

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405567
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Ueno; Takahito et al.

Process cartridge, electrophotographic image forming apparatus, and electrophotographic photosensitive drum unit

Abstract

A cartridge includes a photosensitive drum having a rotational axis about which the photosensitive drum is rotatable. The cartridge also includes a developing roller having a rotational axis about which the developing roller is rotatable. A developing frame rotatably supports the developing roller. A drum flange is connected to an end of the photosensitive drum, with the drum flange including an inner surface facing the rotational axis of the photosensitive drum and a hollow portion inside of the drum flange. A casing including a bearing member rotatably supports the photosensitive drum.

Inventors: Ueno; Takahito (Mishima, JP), Miyabe; Shigeo (Numazu, JP), Morioka; Masanari (Numazu, JP), Hisano; Masato (Susono, JP)

Applicant: CANON KABUSHIKI KAISHA (Tokyo, JP)

Family ID: 39906671

Assignee: Canon Kabushiki Kaisha (Tokyo, JP)

Appl. No.: 18/785232

Filed: July 26, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240419122 A1	Dec. 19, 2024

Foreign Application Priority Data

JP	2006-346190	Dec. 22, 2006
JP	2007-042665	Feb. 22, 2007
JP	2007-330303	Dec. 21, 2007

Related U.S. Application Data

continuation parent-doc US 11964518 20071226 US 8280278 20121002 child-doc US 13570671
division parent-doc US 18201265 20230524 PENDING child-doc US 18785232
division parent-doc US 17528299 20211117 US 11720054 20230808 child-doc US 18201265
division parent-doc US 17104379 20201125 US 11237517 20220201 child-doc US 17528299
division parent-doc US 16815477 20200311 US 10877433 20201229 child-doc US 17104379
division parent-doc US 16421683 20190524 US 10671018 20200602 child-doc US 16815477
division parent-doc US 16113422 20180827 US 10539923 20200121 child-doc US 16421683
division parent-doc US 15171291 20160602 US 10551793 20200204 child-doc US 16113422
division parent-doc US 14068149 20131031 US 9678471 20170613 child-doc US 15171291
division parent-doc US 13570671 20120809 US 8630564 20140114 child-doc US 14068149

Publication Classification

Int. Cl.: G03G21/18 (20060101); G03G15/00 (20060101); G03G21/16 (20060101)

U.S. Cl.:

CPC G03G21/1842 (20130101); G03G15/751 (20130101); G03G15/757 (20130101);
G03G21/1647 (20130101); G03G21/1814 (20130101); G03G21/1817 (20130101);
G03G21/1821 (20130101); G03G21/185 (20130101); G03G21/1853 (20130101);
G03G21/1857 (20130101); G03G21/186 (20130101); G03G2221/1657 (20130101)

Field of Classification Search

CPC: G03G (21/1842); G03G (21/1647); G03G (21/1821); G03G (21/1857); G03G (21/186);
G03G (21/1803)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
899913	12/1907	Shaw	N/A	N/A
2292676	12/1941	Thiry	N/A	N/A
2300514	12/1941	Mallman	N/A	N/A
3381497	12/1967	Allen	N/A	N/A
3390546	12/1967	Jewell	N/A	N/A
3406534	12/1967	Chapper	N/A	N/A
3490841	12/1969	Celry, Jr. et al.	N/A	N/A
3512375	12/1969	Madarasz et al.	N/A	N/A
3537275	12/1969	Smith	N/A	N/A
3747368	12/1972	Morin	N/A	N/A
3815380	12/1973	Esmay	N/A	N/A
3818380	12/1973	Tyre	N/A	N/A
3922883	12/1974	Bevacqua	N/A	N/A
3996821	12/1975	Murray	N/A	N/A
4065941	12/1977	Aoki	N/A	N/A

4106611	12/1977	Suzuki et al.	N/A	N/A
4167321	12/1978	Miyashita et al.	N/A	N/A
4320429	12/1981	Knerich et al.	N/A	N/A
4433767	12/1983	Thor	N/A	N/A
4439257	12/1983	Sato et al.	N/A	N/A
4451117	12/1983	Goode'	N/A	N/A
4457738	12/1983	Gross et al.	N/A	N/A
4607734	12/1985	Watashi et al.	N/A	N/A
4692127	12/1986	Wagner	N/A	N/A
4753626	12/1987	Hazebrook et al.	N/A	N/A
4829335	12/1988	Kanemitsu et al.	N/A	N/A
4833502	12/1988	Azuma	N/A	N/A
4835565	12/1988	Nagatsuna et al.	N/A	N/A
4839690	12/1988	Onoda et al.	N/A	N/A
4873549	12/1988	Tada et al.	N/A	N/A
4941862	12/1989	Hazenbrook et al.	N/A	N/A
5009446	12/1990	Davis	N/A	N/A
5019867	12/1990	Yamakawa et al.	N/A	N/A
5023660	12/1990	Ebata et al.	N/A	N/A
5106224	12/1991	van Gelderen	N/A	N/A
5128715	12/1991	Furyama et al.	N/A	N/A
5132728	12/1991	Suzaki et al.	N/A	N/A
5168319	12/1991	Kimura et al.	N/A	N/A
5177854	12/1992	Herbert, Jr. et al.	N/A	N/A
5210574	12/1992	Kita	N/A	N/A
5247847	12/1992	Gu	N/A	N/A
5277659	12/1993	Cornay	N/A	N/A
5290203	12/1993	Krude	N/A	N/A
5331373	12/1993	Nomura et al.	N/A	N/A
5452056	12/1994	Nomura et al.	N/A	N/A
5463446	12/1994	Watanabe et al.	N/A	N/A
5562357	12/1995	Sandell	N/A	N/A
5579085	12/1995	Miyabe et al.	N/A	N/A
5583618	12/1995	Takeuchi et al.	N/A	N/A
5583630	12/1995	Kimura et al.	N/A	N/A
5585889	12/1995	Shishido et al.	N/A	N/A
5640650	12/1996	Watanabe et al.	N/A	N/A
5738586	12/1997	Arriaga	N/A	N/A
5740500	12/1997	Hashimoto	N/A	N/A
5749028	12/1997	Damji et al.	N/A	N/A
5766081	12/1997	Desmarais	N/A	N/A
5809380	12/1997	Katakabe et al.	N/A	N/A
5815782	12/1997	Yokomori et al.	N/A	N/A
5839028	12/1997	Nomura et al.	N/A	N/A
5845175	12/1997	Kumar et al.	N/A	N/A
5848334	12/1997	Kamola	N/A	N/A
5855519	12/1998	Kadota	N/A	N/A
5878309	12/1998	Normura et al.	N/A	N/A
5878310	12/1998	Noda et al.	N/A	N/A
5878492	12/1998	Gleasant et al.	N/A	N/A

5903802	12/1998	Watanabe et al.	N/A	N/A
5903803	12/1998	Kawai et al.	N/A	N/A
5907750	12/1998	Yamada et al.	N/A	N/A
5920753	12/1998	Sasaki et al.	N/A	N/A
5926666	12/1998	Miura et al.	N/A	N/A
5926672	12/1998	Nishibata et al.	N/A	N/A
5930562	12/1998	Noda et al.	N/A	N/A
5943529	12/1998	Miyabe et al.	N/A	N/A
5946531	12/1998	Miura et al.	N/A	N/A
5950047	12/1998	Miyabe et al.	N/A	N/A
5953562	12/1998	Kawaguchi et al.	N/A	N/A
5966567	12/1998	Matsuzaki et al.	N/A	N/A
5983055	12/1998	Bito et al.	N/A	N/A
5987287	12/1998	Huang	N/A	N/A
5991571	12/1998	Yamada et al.	N/A	N/A
5993101	12/1998	Kohno et al.	N/A	N/A
6011942	12/1999	Taniguchi et al.	N/A	N/A
6029027	12/1999	Yokomori et al.	N/A	N/A
6029031	12/1999	Yokomori et al.	N/A	N/A
6032002	12/1999	Yokomori et al.	N/A	N/A
6032008	12/1999	Kolodziej	N/A	N/A
6036369	12/1999	Ichiyama	N/A	N/A
6041203	12/1999	Suzuki et al.	N/A	N/A
6058280	12/1999	Kumar et al.	N/A	N/A
6061535	12/1999	Yokomori et al.	N/A	N/A
6064843	12/1999	Isobe et al.	N/A	N/A
6070028	12/1999	Odagawa et al.	N/A	N/A
6072968	12/1999	Nomura et al.	N/A	N/A
6081676	12/1999	Inomata	N/A	N/A
6074304	12/1999	Olbrich et al.	N/A	N/A
6101350	12/1999	Suzuki et al.	N/A	N/A
6115569	12/1999	Akutsu	N/A	N/A
6118962	12/1999	Casper et al.	N/A	N/A
6128452	12/1999	Miyabe et al.	N/A	N/A
6137970	12/1999	Sasago	N/A	N/A
6152826	12/1999	Profeta et al.	N/A	N/A
6154623	12/1999	Suzuki et al.	N/A	N/A
6167219	12/1999	Miyamoto et al.	N/A	N/A
6169865	12/2000	Miyabe et al.	N/A	N/A
6173140	12/2000	Suzuki et al.	N/A	N/A
6173145	12/2000	Chadani et al.	N/A	N/A
6175705	12/2000	Harada et al.	N/A	N/A
6198891	12/2000	Ishida et al.	N/A	N/A
6208818	12/2000	Noda	N/A	N/A
6215969	12/2000	Namura et al.	N/A	N/A
6226476	12/2000	Miyabe et al.	N/A	N/A
6226478	12/2000	Watanabe et al.	N/A	N/A
6235383	12/2000	Hong et al.	N/A	N/A
6240266	12/2000	Watanabe et al.	N/A	N/A
6249663	12/2000	Alzawa et al.	N/A	N/A

6257798	12/2000	Wormsbaecher	N/A	N/A
6256467	12/2000	Yokomori et al.	N/A	N/A
6282390	12/2000	Miyabe et al.	N/A	N/A
6282395	12/2000	Nittani et al.	N/A	N/A
6301458	12/2000	Mori et al.	N/A	N/A
6317572	12/2000	Miyabe et al.	N/A	N/A
6336012	12/2001	Noda et al.	N/A	N/A
6336017	12/2001	Miyamoto et al.	N/A	N/A
6336018	12/2001	Kawai et al.	N/A	N/A
6343192	12/2001	Miyabe et al.	N/A	N/A
6438347	12/2001	Nittani et al.	N/A	N/A
6349191	12/2001	Willis	N/A	N/A
6351620	12/2001	Miyabe et al.	N/A	N/A
6366748	12/2001	Takeuchi et al.	N/A	N/A
6381430	12/2001	Yokomori et al.	N/A	N/A
6385416	12/2001	Horikawa et al.	N/A	N/A
6385420	12/2001	Morioka	N/A	N/A
6397029	12/2001	Portig	N/A	N/A
6400914	12/2001	Noda et al.	N/A	N/A
6415121	12/2001	Suzuki et al.	N/A	N/A
6418296	12/2001	Aizawa et al.	N/A	N/A
6452826	12/2001	Kim et al.	N/A	N/A
6463242	12/2001	Kojima et al.	N/A	N/A
6473578	12/2001	Miyabe et al.	N/A	N/A
6473580	12/2001	Inomata	N/A	N/A
6490426	12/2001	Zaman	N/A	N/A
6501926	12/2001	Watanabe et al.	N/A	N/A
6517439	12/2002	Sears	N/A	N/A
6519431	12/2002	Toba et al.	N/A	N/A
6542706	12/2002	Toba et al.	N/A	N/A
6546220	12/2002	Asakura et al.	N/A	N/A
6549736	12/2002	Miyabe et al.	N/A	N/A
6549738	12/2002	Otani et al.	N/A	N/A
6556799	12/2002	Saito	N/A	N/A
6572480	12/2002	Huang	N/A	N/A
6574446	12/2002	Kitayama	N/A	N/A
6577831	12/2002	Kojima et al.	N/A	N/A
6587660	12/2002	Ueno et al.	N/A	N/A
6603939	12/2002	Toba et al.	N/A	N/A
6608980	12/2002	Murayama et al.	N/A	N/A
6654580	12/2002	Yamaguchi et al.	N/A	N/A
6671473	12/2002	Miyabe	N/A	N/A
6678488	12/2003	Toba et al.	N/A	N/A
6699550	12/2003	Suzuki et al.	N/A	N/A
6704522	12/2003	Sasago et al.	N/A	N/A
6708010	12/2003	Miyabe et al.	N/A	N/A
6714746	12/2003	Morioka et al.	N/A	N/A
6714752	12/2003	Ueno et al.	N/A	N/A
6725004	12/2003	Ahn et al.	N/A	N/A
6768890	12/2003	Cho et al.	N/A	N/A

6795666	12/2003	Miyabe et al.	N/A	N/A
6823153	12/2003	Ueno et al.	N/A	N/A
6823160	12/2003	Okabe	N/A	N/A
6827206	12/2003	Brase	N/A	N/A
6829455	12/2003	Yasumoto et al.	N/A	N/A
6834175	12/2003	Marayama et al.	N/A	N/A
6836629	12/2003	Miyabe et al.	N/A	N/A
6898391	12/2004	Numagami et al.	N/A	N/A
6898399	12/2004	Morioka et al.	N/A	N/A
6912365	12/2004	Ueno et al.	N/A	N/A
6931226	12/2004	Chadani et al.	N/A	N/A
6934485	12/2004	Miyabe et al.	N/A	N/A
6937832	12/2004	Sato et al.	N/A	N/A
6947677	12/2004	Uyama et al.	N/A	N/A
6950621	12/2004	Himes	N/A	N/A
6954600	12/2004	Fujita et al.	N/A	N/A
6954601	12/2004	Numagami et al.	N/A	N/A
6963706	12/2004	Morioka et al.	N/A	N/A
6968141	12/2004	Fujita et al.	N/A	N/A
6968144	12/2004	Mizoguchi	N/A	N/A
6968146	12/2004	Fujita et al.	N/A	N/A
6970668	12/2004	Ueno et al.	N/A	N/A
6978099	12/2004	Ueno et al.	N/A	N/A
6980758	12/2004	Murayama et al.	N/A	N/A
7003247	12/2005	Koishi et al.	N/A	N/A
7016626	12/2005	Yokomori et al.	N/A	N/A
7020410	12/2005	Zogg et al.	N/A	N/A
7024131	12/2005	Komatsu et al.	N/A	N/A
7035573	12/2005	Yamaguchi et al.	N/A	N/A
6984012	12/2005	Asauchi	N/A	N/A
7062200	12/2005	Ueno et al.	N/A	N/A
7079783	12/2005	Yokoi	N/A	N/A
7079787	12/2005	Ogino et al.	N/A	N/A
7092658	12/2005	Yasumoto et al.	N/A	N/A
7121205	12/2005	Ono et al.	N/A	N/A
7127192	12/2005	Batori et al.	N/A	N/A
7136604	12/2005	Chadani et al.	N/A	N/A
7139502	12/2005	Koishi et al.	N/A	N/A
7147457	12/2005	Iten	N/A	N/A
7149457	12/2005	Miyabe et al.	N/A	N/A
7155141	12/2005	Sato et al.	N/A	N/A
7158735	12/2006	Murayama et al.	N/A	N/A
7158736	12/2006	Sato et al.	N/A	N/A
7164875	12/2006	Miyabe et al.	N/A	N/A
7174122	12/2006	Fujita et al.	N/A	N/A
7184690	12/2006	Ueno et al.	N/A	N/A
7200349	12/2006	Sato et al.	N/A	N/A
7209682	12/2006	Numagami et al.	N/A	N/A
7212768	12/2006	Numagami et al.	N/A	N/A
7212773	12/2006	Sudo et al.	N/A	N/A

7224925	12/2006	Sato et al.	N/A	N/A
7228090	12/2006	Toso et al.	N/A	N/A
7236722	12/2006	Portig	N/A	N/A
7242890	12/2006	Yokota	N/A	N/A
7242893	12/2006	Murakami et al.	N/A	N/A
7248810	12/2006	Miyabe et al.	N/A	N/A
7289752	12/2006	Yamazaki et al.	N/A	N/A
7315710	12/2007	Ueno et al.	N/A	N/A
7349657	12/2007	Sato et al.	N/A	N/A
7366443	12/2007	Ohashi et al.	N/A	N/A
7366445	12/2007	Hoashi et al.	N/A	N/A
7366452	12/2007	Fujita et al.	N/A	N/A
7403733	12/2007	Watanabe et al.	N/A	N/A
7421235	12/2007	Choi	N/A	N/A
7424244	12/2007	Williams et al.	N/A	N/A
7424247	12/2007	Iwasaki	N/A	N/A
7433622	12/2007	Chadani et al.	N/A	N/A
7433628	12/2007	Kweon et al.	N/A	N/A
7491161	12/2008	Taguchi	N/A	N/A
7509075	12/2008	Hayakawa	N/A	N/A
7526228	12/2008	Shiraki	N/A	N/A
7529507	12/2008	Ohashi et al.	N/A	N/A
7537410	12/2008	Parisi et al.	N/A	N/A
7603059	12/2008	Marumoto	N/A	N/A
7623811	12/2008	Sato	N/A	N/A
7630667	12/2008	Huang et al.	N/A	N/A
7651436	12/2009	Sugitani	N/A	N/A
7672611	12/2009	Nakaya	N/A	N/A
7684729	12/2009	Goda	N/A	N/A
7720405	12/2009	Okabe	N/A	N/A
7756443	12/2009	Okabe et al.	N/A	N/A
7817938	12/2009	Igarashi	N/A	N/A
7869735	12/2010	Hattori	N/A	N/A
7899364	12/2010	Chadani et al.	N/A	N/A
7942426	12/2010	Peters	N/A	N/A
7953330	12/2010	Ishikawa	N/A	N/A
7979008	12/2010	Kim et al.	N/A	N/A
8249485	12/2011	Horikawa	399/111	G03G 21/185
8417154	12/2012	Nieda	N/A	N/A
8467701	12/2012	Kikuchi	399/262	G03G 15/0194
8676090	12/2013	Ueno et al.	N/A	N/A
8682215	12/2013	Ueno et al.	N/A	N/A
8688008	12/2013	Norioka et al.	N/A	N/A
8731438	12/2013	Okabe	N/A	N/A
9026006	12/2014	Kawai	N/A	N/A
9880518	12/2017	Wen et al.	N/A	N/A
10571850	12/2019	Matsuoka et al.	N/A	N/A
2001/0041079	12/2000	Michlin et al.	N/A	N/A

2001/0041080	12/2000	Higeta et al.	N/A	N/A
2002/0018666	12/2001	Noda et al.	N/A	N/A
2002/0025191	12/2001	Kitayama	N/A	N/A
2002/0034398	12/2001	Higeta et al.	N/A	N/A
2002/0044794	12/2001	Nishiuwatoko et al.	N/A	N/A
2002/0057928	12/2001	Yasumoto et al.	N/A	N/A
2002/0110385	12/2001	Terada et al.	N/A	N/A
2002/0110388	12/2001	Yokomori et al.	N/A	N/A
2003/0049051	12/2002	Takahashi et al.	N/A	N/A
2003/0059233	12/2002	Jang et al.	N/A	N/A
2003/0123904	12/2002	Maeshima et al.	N/A	N/A
2003/0138270	12/2002	Matsuoka	N/A	N/A
2003/0156848	12/2002	Kawai et al.	N/A	N/A
2003/0235429	12/2002	Sato et al.	N/A	N/A
2004/0013446	12/2003	Morioka et al.	N/A	N/A
2004/0037590	12/2003	Morioka et al.	N/A	N/A
2004/0086300	12/2003	Kawai et al.	N/A	N/A
2004/0131370	12/2003	Yamauchi	N/A	N/A
2004/0136746	12/2003	Komatsu et al.	N/A	N/A
2004/0179862	12/2003	Ono et al.	N/A	N/A
2004/0190937	12/2003	Mercer et al.	N/A	N/A
2005/0031374	12/2004	Nagashima et al.	N/A	N/A
2005/0105936	12/2004	Morioka et al.	N/A	N/A
2005/0111881	12/2004	Arimitsu et al.	N/A	N/A
2005/0111882	12/2004	Sudo et al.	N/A	N/A
2005/0117934	12/2004	Murayama et al.	N/A	N/A
2005/0143179	12/2004	Delaney et al.	N/A	N/A
2005/0191092	12/2004	Toso et al.	N/A	N/A
2005/0254858	12/2004	Numagami et al.	N/A	N/A
2005/0281586	12/2004	Ohashi et al.	N/A	N/A
2005/0286931	12/2004	Kim et al.	N/A	N/A
2006/0002735	12/2005	Tamaru et al.	N/A	N/A
2006/0008289	12/2005	Sato et al.	N/A	N/A
2006/0029435	12/2005	Kasai et al.	N/A	N/A
2006/0034637	12/2005	Kim et al.	N/A	N/A
2006/0051133	12/2005	Koishi et al.	N/A	N/A
2006/0056878	12/2005	Okabe et al.	N/A	N/A
2006/0062488	12/2005	Smeijers	N/A	N/A
2006/0067737	12/2005	Yamazaki et al.	N/A	N/A
2006/0093398	12/2005	Hayakawa	N/A	N/A
2006/0140648	12/2005	Takegawa	N/A	N/A
2006/0140672	12/2005	Taguchi	N/A	N/A
2006/0146371	12/2005	Hoashi et al.	N/A	N/A
2006/0182465	12/2005	Funamoto et al.	N/A	N/A
2006/0228127	12/2005	Miyabe et al.	N/A	N/A
2006/0240896	12/2005	Ohashi et al.	N/A	N/A
2006/0257164	12/2005	Hoshi et al.	N/A	N/A
2006/0269318	12/2005	Ueno et al.	N/A	N/A
2007/0042826	12/2006	Furusawa	N/A	N/A
2007/0065183	12/2006	Tomita	N/A	N/A

2007/0104510	12/2006	Kawai et al.	N/A	N/A
2007/0110478	12/2006	Numagami et al.	N/A	N/A
2007/0122188	12/2006	Igarashi	N/A	N/A
2007/0196131	12/2006	Sato	N/A	N/A
2007/0237545	12/2006	Cho et al.	N/A	N/A
2007/0264048	12/2006	Kuroda	N/A	N/A
2008/0025757	12/2007	Sato et al.	N/A	N/A
2008/0102966	12/2007	Gleasant	N/A	N/A
2008/0138113	12/2007	Murrell et al.	N/A	N/A
2008/0138114	12/2007	Chadani et al.	N/A	N/A
2008/0152388	12/2007	Ueno et al.	N/A	N/A
2008/0159773	12/2007	Murayama et al.	N/A	N/A
2008/0199212	12/2007	Tsui et al.	N/A	N/A
2008/0240796	12/2007	Morioka et al.	N/A	N/A
2008/0260428	12/2007	Ueno et al.	N/A	N/A
2009/0196655	12/2008	Takigawa et al.	N/A	N/A
2009/0317132	12/2008	Asanuma et al.	N/A	N/A
2009/0317134	12/2008	Miyabe et al.	N/A	N/A
2009/0317135	12/2008	Miyabe et al.	N/A	N/A
2010/0054778	12/2009	Adachi et al.	N/A	N/A
2010/0054823	12/2009	Takasaka et al.	N/A	N/A
2010/0142991	12/2009	Holmes et al.	N/A	N/A
2010/0239311	12/2009	Kikuchi	399/111	G03G 15/1605
2011/0038649	12/2010	Miyabe et al.	N/A	N/A
2011/0091239	12/2010	Ueno et al.	N/A	N/A
2011/0299882	12/2010	Tanaami	399/110	G03G 15/326
2012/0275824	12/2011	Gu et al.	N/A	N/A
2013/0136492	12/2012	Xu	N/A	N/A
2013/0302066	12/2012	Kawai	N/A	N/A
2014/0270845	12/2013	Kawakami et al.	N/A	N/A
2015/0177683	12/2014	Gu et al.	N/A	N/A
2015/0331386	12/2014	Tanaami	399/110	G03G 21/1666
2016/0154376	12/2015	Xiao et al.	N/A	N/A
2017/0219985	12/2016	Iljima et al.	N/A	N/A
2019/0227481	12/2018	Chadani	N/A	G03G 21/1821
2019/0286048	12/2018	Fukuma	N/A	G03G 21/1619
2020/0150580	12/2019	Matsumoto	N/A	G03G 21/1647

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1179559	12/1997	CN	N/A
1205459	12/1998	CN	N/A
1346077	12/2001	CN	N/A

1158583	12/2003	CN	N/A
1696839	12/2004	CN	N/A
1763638	12/2005	CN	N/A
1851282	12/2005	CN	N/A
1851282	12/2005	CN	N/A
0511203	12/1991	EP	N/A
0 827 049	12/1997	EP	N/A
0 886 075	12/1997	EP	N/A
1178370	12/2001	EP	N/A
1199610	12/2001	EP	N/A
2003-202727	12/2002	EP	N/A
1628165	12/2005	EP	N/A
1791034	12/2006	EP	N/A
1 207 437	12/2021	EP	N/A
2141520	12/1983	GB	N/A
57-153844	12/1981	JP	N/A
S59228281	12/1983	JP	N/A
60-249729	12/1984	JP	N/A
S60249729	12/1984	JP	N/A
61-092967	12/1985	JP	N/A
1-164818	12/1988	JP	N/A
H03125166	12/1990	JP	N/A
4-119363	12/1991	JP	N/A
H04-119363	12/1991	JP	N/A
4-240870	12/1991	JP	N/A
H04240870	12/1991	JP	N/A
U05-019658	12/1992	JP	N/A
U05-030857	12/1992	JP	N/A
H05172152	12/1992	JP	N/A
5-341589	12/1992	JP	N/A
H07217655	12/1994	JP	N/A
H07217665	12/1994	JP	N/A
H07-295461	12/1994	JP	N/A
8-030168	12/1995	JP	N/A
H09160274	12/1996	JP	N/A
H09177807	12/1996	JP	N/A
H09230654	12/1996	JP	N/A
63-004252	12/1997	JP	N/A
U53-115630	12/1997	JP	N/A
11-15265	12/1998	JP	N/A
11-325097	12/1998	JP	N/A
H11325097	12/1998	JP	N/A
2000-075660	12/1999	JP	N/A
2000075732	12/1999	JP	N/A
2000-120715	12/1999	JP	N/A
2000-132040	12/1999	JP	N/A
2000-137360	12/1999	JP	N/A
2000170783	12/1999	JP	N/A
2000257646	12/1999	JP	N/A
2000280348	12/1999	JP	N/A

2001-083753	12/2000	JP	N/A
2001194954	12/2000	JP	N/A
2002-031153	12/2001	JP	N/A
2002-48148	12/2001	JP	N/A
2002-048148	12/2001	JP	N/A
2002217574	12/2001	JP	N/A
2002-250435	12/2001	JP	N/A
2003-162137	12/2002	JP	N/A
2003-202727	12/2002	JP	N/A
2003247535	12/2002	JP	N/A
2004-45603	12/2003	JP	N/A
2004045603	12/2003	JP	N/A
2004-85593	12/2003	JP	N/A
2004144240	12/2003	JP	N/A
2004198822	12/2003	JP	N/A
2004-233876	12/2003	JP	N/A
2004246058	12/2003	JP	N/A
2004251401	12/2003	JP	N/A
2004-361719	12/2003	JP	N/A
2005076734	12/2004	JP	N/A
2005164684	12/2004	JP	N/A
2005-299788	12/2004	JP	N/A
2005-300846	12/2004	JP	N/A
2005296235	12/2004	JP	N/A
3728104	12/2004	JP	N/A
2009-0000661	12/2005	JP	N/A
2006039364	12/2005	JP	N/A
2006-072160	12/2005	JP	N/A
2006084935	12/2005	JP	N/A
2006106681	12/2005	JP	N/A
2006133436	12/2005	JP	N/A
2006139230	12/2005	JP	N/A
2006163232	12/2005	JP	N/A
2007032794	12/2006	JP	N/A
2007-52185	12/2006	JP	N/A
2007069868	12/2006	JP	N/A
2007121774	12/2006	JP	N/A
2007-218403	12/2006	JP	N/A
2007-218403	12/2006	JP	N/A
2007-240007	12/2006	JP	N/A
2007-303615	12/2006	JP	N/A
2009-104101	12/2008	JP	N/A
2009300516	12/2008	JP	N/A
100270224	12/1999	KR	N/A
10-2006-0000661	12/2005	KR	N/A
20090044054	12/2008	KR	N/A
2003123803	12/2004	RU	N/A
2266553	12/2004	RU	N/A
2 289 835	12/2005	RU	N/A
2006014821	12/2005	WO	N/A

OTHER PUBLICATIONS

Smith Corona 5H Series Personal Word Processors Service Manuel, dated Sep. 1989. cited by applicant

John W. Weigl, "Electrophotography", 16 Angew. Chem. Int. Ed. Engl., 374-392 (Jun. 1977). cited by applicant

Kawamoto, "Vibration Induced in Driving Mechanism of Photoconductor Drum in Color Laser Printer", 48 Jour. of Image Sci. and Tech., 306-311 (Jul./Aug. 2004). cited by applicant

Knight et al., "Robust Control for Carriage Drum Printer", Control Applications, Proceedings of the Third IEEE International Conference on Control and Applications, 971-976 (Aug. 1994). cited by applicant

Pai et al., "Physics of Electrophotography", 65 Reviews of Mod. Physics, 163-211 (Jan. 1993). cited by applicant

Respondents' Ninestar Corporation, Ninestar Image Tech Limited, Ninestar Technology Company, Ltd., and Apex Mictrotech Ltd.'s Response to Canon's Interrogatory Nos. 20-30 in ITC Investigation No. 337-TA-1106, dated May 7, 2018 (including claim charts asserting invalidity of claims of U.S. Pat. Nos. 9,874,846; 9,869,960; 9,857,765; 9,836,021; 9,746,826). cited by applicant

Respondents' Ninestar Corporation, Ninestar Image Tech Limited, Ninestar Technology Company, Ltd., and Apex Mictrotech Ltd.'s Supplemental Response to Canon's Interrogatory Nos. 21 in ITC Investigation No. 337-TA-1106, dated May 25, 2018 (including claim charts asserting invalidity of claims of U.S. Pat. Nos. 9,874,846; 9,869,960; 9,857,765; 9,836,021; 9,746,826). cited by applicant

Respondents' Ninestar Corporation, Ninestar Image Tech Limited, Ninestar Technology Company, Ltd., and Apex Mictrotech Ltd.'s Second Supplemental Response to Canon's Interrogatory Nos. 21 in ITC Investigation No. 337-TA-1106, dated Jun. 22, 2018 (including claim charts asserting invalidity of claims of U.S. Pat. Nos. 9,874,846; 9,869,960; 9,857,765; 9,836,021; 9,746,826). cited by applicant

Respondents' Ninestar Corporation, Ninestar Image Tech Limited, Ninestar Technology Company, Ltd., and Apex Mictrotech Ltd.'s Third Supplemental Response to Canon's Interrogatory Nos. 21 in ITC Investigation No. 337-TA-1106, dated Jul. 11, 2018 (including claim charts asserting invalidity of claims of U.S. Pat. Nos. 9,874,846; 9,869,960; 9,857,765; 9,836,021; 9,746,826). cited by applicant

Respondents' Ninestar Corporation, Ninestar Image Tech Limited, Ninestar Technology Company, Ltd., and Apex Mictrotech Ltd.'s Fourth Supplemental Response to Canon's Interrogatory Nos. 21 in ITC Investigation No. 337-TA-1106, dated Aug. 13, 2018 (including claim charts asserting invalidity of claims of U.S. Pat. Nos. 9,874,846; 9,869,960; 9,857,765; 9,836,021; 9,746,826). cited by applicant

Respondent's Notice of Prior Art in ITC Investigation No. 337-TA-1106, dated Sep. 4, 2018. cited by applicant

Initial Expert Report of Alexander J. Solcum, Ph.D., on invalidity of U.S. Pat. Nos. 9,746,826; U.S. Pat. No. 9,836,021; U.S. Pat. No. 9,857,765; U.S. Pat. No. 9,869,960; and U.S. Pat. No. 9,874,846, in ITC Investigation No. 337-TA-1106, dated Oct. 1, 2018 (redacted). cited by applicant

Canon's Initial Markman Brief in ITC Investigation No. 337-TA-1106, dated Jul. 26, 2018. cited by applicant

Respondents' Initial Markman Brief in ITC Investigation No. 337-TA-1106, dated Jul. 26, 2018. cited by applicant

Commission Investigative Staff's Opening Markman Brief in ITC Investigation No. 337-TA-1106, dated Jul. 27, 2018. cited by applicant

Canon's Rebuttal Markman Brief in ITC Investigation No. 337-TA-1106, dated Aug. 16, 2018. cited by applicant

Respondents' Rebuttal Markman Brief in ITC Investigation No. 337-TA-1106, dated Aug. 16, 2018.

cited by applicant

Commission Investigative Staff's Rebuttal Markman Brief in ITC Investigation No. 337-TA-1106, dated Aug. 16, 2018. cited by applicant

The Ninestar Respondent's Contingent Motion for Summary Determination of Invalidity for Failure to Satisfy the Written Description Requirement in ITC Investigation No. 337-TA-1106, dated Nov. 28, 2018. cited by applicant

Reply Memorandum of Points and Authorities in Support of the Ninestar Respondents' Contingent Motion for Summary Determination of Invalidity for Failure to Satisfy the Written Description Requirement (Motion 1106-022) in ITC Investigation No. 337-TA-1106, dated Dec. 13, 2018. cited by applicant

Markman Order and Order Addressing Motions for Summary Determination and Prehearing Briefs in ITC Investigation No. 337-TA-1106, dated Feb. 28, 2019. cited by applicant

Transcript of Nov. 9, 2018 Deposition of Alexander H. Slocumb, Ph.D. in ITC Investigation No. 337-TA-1106 (redacted). cited by applicant

Transcript of Nov. 1, 2018 Deposition of Richard A. Lux, Ph.D. in ITC Investigation No. 337-TA-1106 (redacted). cited by applicant

Initial Expert Report of Richard A. Lux, Ph.D. in ITC Investigation No. 337-TA-1106, dated Oct. 1, 2018 (redacted). cited by applicant

Contingent Direct Witness Statement of Richard A. Lux, Ph.D. Pursuant to Order No. 34 in ITC Investigation No. 337-TA-1106. cited by applicant

Direct Witness Statement of Richard A. Lux, Ph.D. in ITC Investigation No. 337-TA-1106 (redacted). cited by applicant

Rebuttal Witness Statement of Richard A. Lux, Ph.D. in ITC Investigation No. 337-TA-1106. cited by applicant

Rebuttal Report of Richard A. Lux, Ph.D. in ITC Investigation No. 337-TA-1106, dated Oct. 24, 2018. cited by applicant

Rebuttal Witness Statement of Alexander Slocum to the Witness Statement of Shigeo Miyabe (CX-0018C) and the Witness Statements of Richard Lux (CX-0161C and CX-0162) in ITC Investigation No. 337-TA-1106. cited by applicant

Witness Statement of Alexander Slocum in ITC Investigation No. 337-TA-1106 (redacted). cited by applicant

An Anti-Backlash Two-Part Shaft Coupling with Interlocking Elastically Averaged Teeth, Balasubramaniam et al., 26 J. of Int. Societies for Precision Eng. and Nanotech., 314-330 (2002). cited by applicant

Design of Three-Groove Kinematic Couplings, Alexander H. Slocum (1992). cited by applicant
FUNdaMENTALS of Design, Alexander H. Solcum (2008). cited by applicant

McGraw Hill Series in Mechanical Engineering: Design of Machinery, Norton, pp. 22-23 (2001). cited by applicant

Physics of Electrophotography, Damodar et al., pp. 163-211 (1993). cited by applicant

Jul. 30, 2019 Office Action in Vietnamese Patent Application No. 1-2009-01264 (with English translation). cited by applicant

Jul. 22, 2019 Examination Report in Indian Patent Application No. 201648003029 (with English translation). cited by applicant

International Search Report and Written Opinion of the International Searching Authority dated Dec. 25, 2007, in International Application No. PCT/JP2007/075364. cited by applicant

Singapore Search Report and Written in Singapore Application No. 900903015-6, issued Jan. 5, 2010. cited by applicant

Japanese Office Action dated Mar. 16, 2010, in counterpart Japanese Application No. 2007-330303. cited by applicant

Office Action in Taiwanese Patent Application No. 096149780, mailed Jun. 11, 2012 (with English

translation). cited by applicant
Decision on Grant in Russian Patent Application No. 2009128196/(039172), mailed Apr. 18, 2012 (with English translation). cited by applicant
Notice of Allowance in Korean Patent Application No. 10-2009-7022510, mailed May 3, 2011. cited by applicant
Notice of Acceptance in Australian Patent Application No. 200739163, dated Feb. 3, 2012. cited by applicant
Official Communication in Canadian Patent Application No. 2,670,502, dated Nov. 10, 2011. cited by applicant
Office Action in Japanese Patent Application No. 2007-330304, dated Nov. 22, 2011, with English translation. cited by applicant
Office Action in Indonesia Patent Application No. W-002000901748, dated Mar. 30, 2011 (with partial translation). cited by applicant
Official Communication in Korean Patent Application No. 10-2009-7022510, issued Aug. 8, 2011. cited by applicant
English Translation of Jan. 17, 2011 Office Action in Korean Patent Application No. 10-2009-7015430. cited by applicant
Office Action in Korean Patent Application No. 10-2009-7015474, dated Jan. 17, 2011, with English translation. cited by applicant
Office Action in Korean Patent Application No. 10-2009-7022191, dated Feb. 17, 2011. cited by applicant
English translation of Japanese Laid-open Patent Application Hei No. 1-164818. cited by applicant
Office Action in Chinese Patent Application No. 207780047584.6, dated Nov. 1, 2010, with English translation. cited by applicant
Office Action in Korean Patent Application No. 10-2009-7015430, dated Nov. 17, 2011. cited by applicant
Australian Search Report and Written Opinion, dated Nov. 24, 2009, which was enclosed with an Invitation to Respond to Written Opinion dated Dec. 22, 2009, in Singapore Application No. 200903732-6. cited by applicant
English-language translation of Japanese Patent Document No. 11-15265 A. cited by applicant
English-language translation of Japanese Patent Document No. 2003-202727 A. cited by applicant
International Search Report and Written Opinion in PCT/JP2008/056259, dated Jun. 16, 2008. cited by applicant
Singapore Search Report and Written Opinion in Singapore Application No. 200903005-7, issued Jan. 5, 2010. cited by applicant
International Search Report and Written Opinion of the International Searching Authority dated Apr. 11, 2008, in International Application No. PCT/JP2007/075366. cited by applicant
Office Action in Russian Patent Application No. 2009128196, dated Nov. 3, 2010, with English translation. cited by applicant
Singapore Search Report and Written Opinion in Singapore Application No. 200903015-6, issued Jan. 5, 2010. cited by applicant
Notice of Allowance in Korean Patent Application No. 10-2009-7015430, mailed Aug. 6, 2012. cited by applicant
Official Communication in European Patent Application No. 07 860 559.9, mailed Jul. 17, 2012. cited by applicant
Office Action in Korean Patent Application No. 10-2012-7000630, mailed Jan. 29, 2013. cited by applicant
Office Action in Korean Patent Application No. 10-2012-7000629, mailed Jan. 29, 2013. cited by applicant
Office Action in Taiwanese Patent Application No. 098135943, dated Jul. 17, 2013, with English

translation. cited by applicant

Notice of Acceptance in Australian Patent Application No. 2012200109, mailed Apr. 16, 2014.

cited by applicant

Notice of Allowance in Australian Patent Application No. 2015203129, mailed Jun. 28, 2016. cited by applicant

Apr. 20, 2016 Office Action in German Patent Application No. 11 2007 003 045.3. cited by applicant

Jan. 19, 2016 Office Action in Brazilian Patent Application No. BR122015008873-9 (with partial translation). cited by applicant

Jan. 19, 2016 Office Action in Brazilian Patent Application No. BR122015008874-7 (with partial translation). cited by applicant

Notice of Allowance in Korean Patent Application No. 10-2014-7013438, dated Apr. 14, 2015. cited by applicant

Notice of Allowance in Korean Patent Application No. 10-2014-7013436, dated Apr. 14, 2015. cited by applicant

Office Action in Taiwanese Patent Application No. 102102866, mailed Jul. 13, 2015 (with English translation). cited by applicant

Office Action in Taiwanese Patent Application No. 102102869, mailed Jul. 13, 2015 (with English translation). cited by applicant

Office Action in Malaysian Patent Application No. PI 20092602, dated Jul. 15, 2015. cited by applicant

Office Action in Chinese Patent Application No. 201310224833.1, dated Feb. 28, 2015 (with English translation). cited by applicant

Office Action in Indian Patent Application No. 3622/CHENP/2009, dated Dec. 17, 2014. cited by applicant

Office Action in Chinese Patent Application No. 201310224834.6, dated Feb. 2, 2015 (with English translation). cited by applicant

Office Action in Brazilian Patent Application No. PI 0720506.6, dated Feb. 3, 2015 (with English translation). cited by applicant

Office Action in Chinese Patent Application No. 20130223491.1, dated Nov. 3, 2014 (with English translation). cited by applicant

Office Action in Chinese Patent Application No. 201301224820.4, dated Nov. 3, 2014. cited by applicant

Decision on Russian Patent Application No. 2012130722, dated Sep. 16, 2014 (with English translation). cited by applicant

ITC Investigation No. 337-TA-918—Canon's Proposed Claim Constructions, dated Sep. 15, 2014. cited by applicant

ITC Investigation No. 337-TA-918—The Ninestar Respondents' Supplemental Objections and Responses to Complainants' Interrogatory Nos. 32-43, 45-47, and 49-51, dated Sep. 19, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Respondents' Notice of Prior Art, dated Sep. 26, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Canon's Supplemental Proposed Claim Constructions, dated Oct. 10, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Canon's Objections and Supplemental Responses to ILG's Interrogatory Nos. 1, 5, 7, 10, 12, 43, 47, 60-65, 85, 87, and 120 to Complainants, dated Oct. 17, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Respondent International Laser Group, Inc.'s Oct. 17, 2014 Supplemental Responses to Complainants Canon, Inc., Canon U.S.A., Inc. and Canon Virginia, Inc.'s Interrogatories (Nos. 33-46, 49, 58), dated Oct. 17, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Initial Expert Report of Charles M. Curley Regarding Invalidity of Certain Claims of U.S. Pat. Nos. 8,280,278; 8,630,564; 8,682,215; and 8,688,008, dated Oct. 21, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Initial Expert Report of Richard A. Lux, Ph.D., dated Oct. 17, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Expert Report of Dr. Alexander Slocum on the Invalidity of the Asserted Claims of Canon's Patents, dated Oct. 20, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Supplemental Joint Chart Regarding Claim Construction, dated Oct. 23, 2014. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 8,280,278, dated Oct. 27, 2014. cited by applicant

Declaration of Charles M. Curley in Support of Petition for Inter Partes Review of U.S. Pat. No. 8,280,278, dated Oct. 9, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Rebuttal Expert Report of Richard A. Lux, Ph.D., dated Nov. 7, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Rebuttal Expert Report of Alexander Slocum, dated Nov. 7, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Deposition of Richard A. Lux, Ph.D. (vol. 1), dated Nov. 11, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Deposition of Richard A. Lux, Ph. D. (vol. 2), dated Nov. 12, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Deposition of Alexander Henry Slocum, Ph.D., dated Nov. 14, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Deposition of Charles Michael Curley, dated Dec. 3, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Canon's Prehearing Brief (redacted), dated Dec. 22, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Commission Investigative Staff's Combined Prehearing Brief and Prehearing Statement (redacted), dated Jan. 14, 2015. cited by applicant

ITC Investigation No. 337-TA-918—Pre-hearing Statement and Brief of Respondents International Laser Group, the Ninestar Respondents, and Katun Corp. (redacted), dated Dec. 22, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Direct Witness Statement of Charles M. Curley, dated Dec. 22, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Witness Statement of Alexander Slocum, dated Dec. 21, 2014. cited by applicant

ITC Investigation No. 337-TA-918—Rebuttal Witness Statement of Richard A. Lux, Ph.D., dated Jan. 9, 2015. cited by applicant

ITC Investigation No. 337-TA-918—Initial Determination Granting Complainants' Motion for Summary Determination of Violations by the Defaulting Respondents and Non-participating Respondents and Recommended Determination on Remedy and Bonding (public version), dated May 12, 2015. cited by applicant

Corrected Petition in IPR2015-00508 (Inter Partes Review of U.S. Pat. No. 8,688,008), dated Jan. 22, 2015. cited by applicant

Expert Declaration of Charles M. Curley in IPR 2015-00508 (Inter Partes Review of U.S. Pat. No. 8,688,008) dated Dec. 31, 2014. cited by applicant

Office Action in Chinese Patent Application No. 201310224839.9, dated Sep. 12, 2014 (with English translation). cited by applicant

Notice of Allowance in Korean Patent Application No. 10-2012-700629, dated Jul. 30, 2014. cited by applicant

Notice of Allowance in Korean Patent Application No. 10-2012-700730, dated Jul. 30, 2014. cited

applicant
Nov. 3, 2021 Extended Search Report in European Patent Application No. 21 189 623.8. cited by applicant
Jul. 22, 2021 Notice of Allowance in Taiwanese Patent Application No. 10906076.1. cited by applicant
May 7, 2021 Notice of Acceptance in Australian Patent Application No. 2019236605. cited by applicant
Jun. 16, 2022 Office Action in Taiwan Patent Application No. 110138994. cited by applicant
Oct. 28, 2021 Office Action in Malaysian Patent Application No. PI 2018000519. cited by applicant
Oct. 28, 2021 Office Action in Malaysian Patent Application No. PI 2018000515. cited by applicant
Jun. 8, 2022 Decision to Grant in Russian Patent Application No. 2021131857 (with English translation). cited by applicant
Dec. 22, 2022 Notice of Acceptance in Australian Patent Application No. 2021203403. cited by applicant
Oct. 20, 2021 Office Action in Malaysian Patent Application No. PI 2018000513. cited by applicant
Oct. 20, 2021 Office Action in Malaysian Patent Application No. PI 2018000511. cited by applicant
May 29, 2023 Office Action in Indian Patent Application No. 201648003029. cited by applicant
Decision to Grant in Russian Patent Application No. 2018115941, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115943, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115945, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115947, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115949, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115952, dated Mar. 26, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115955, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115957, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115958, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115959, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115961, dated Mar. 6, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115962, dated Feb. 14, 2019 (with English translation). cited by applicant
Decision to Grant in Russian Patent Application No. 2018115964, dated Feb. 14, 2019 (with English translation). cited by applicant
May 21, 2020 Decision to Grant in Russian Patent Application No. 2020102902 (with English translation). cited by applicant
Apr. 20, 2020 Judgment by the United States Court of Appeals for the Federal Circuit in Appeal

from United States International Trade Commission Investigation No. 337-TA-1106. cited by applicant
Notice of Acceptance dated Dec. 10, 2020 in counterpart Russian Application 2020124264/28, together with English translation thereof. cited by applicant
Aug. 30, 2021 Office Action in Indian Patent Application No. 201648035034. cited by applicant

Primary Examiner: Gray; Francis C

Attorney, Agent or Firm: Venable LLP

Background/Summary

FIELD OF THE INVENTION AND RELATED ART

(1) The present invention relates to a process cartridge, an electrophotographic image forming apparatus to which the process cartridge is detachably mountable, and an electrophotographic photosensitive drum unit.

(2) Examples of the electrophotographic image forming apparatus include an electrophotographic copying machine, an electrophotographic printer (a laser beam printer, an LED printer, and so on), and the like.

(3) The process cartridge is prepared by integrally assembling an electrophotographic photosensitive member and process means acting on the electrophotographic photosensitive member into a unit (cartridge) and is mounted to and demounted from a main assembly of the electrophotographic image forming apparatus. For example, the process cartridge is prepared by integrally assembling the electrophotographic photosensitive member and at least one of a developing means, a charging means, and a cleaning means as the process means into a cartridge. Accordingly, examples of the process cartridge include a process cartridge prepared by integrally assembling the electrophotographic photosensitive member and three process means consisting of the developing means, the charging means, and the cleaning means into a cartridge; a process cartridge prepared by integrally assembling the electrophotographic photosensitive member and the charging means as the process means into a cartridge; and a process cartridge prepared by integrally assembling the electrophotographic photosensitive member and two process means consisting of the charging means and the cleaning means.

(4) The process cartridge is detachably mountable to an apparatus main assembly by a user by himself (herself). Accordingly, maintenance of the apparatus can be performed by the user by himself without relying on a service person. As a result, operability of the maintenance of the electrophotographic image forming apparatus.

(5) In a conventional process cartridge, the following constitution for receiving a rotational driving force, for rotating a drum shaped electrophotographic photosensitive member (hereinafter referred to as a "photosensitive drum"), from an apparatus main assembly is known.

(6) On a main assembly side, a rotatable member for transmitting a driving force of a motor and a non circular twisted hole, which is provided at a center portion of the rotatable member and has a cross section integrally rotatable with the rotatable member and provided with a plurality of corners, are provided.

(7) On a process cartridge side, a non circular twisted projection, which is provided at one of longitudinal ends of a photosensitive drum and has a cross section provided with a plurality of corners, is provided.

(8) When the rotatable member is rotated in an engaged state between the projection and the hole in the case where the process cartridge is mounted to the apparatus main assembly, a rotational force

of the rotatable member is transmitted to the photosensitive drum in a state in which an attraction force toward the hole is exerted on the projection. As a result, the rotational force for rotating the photosensitive drum is transmitted from the apparatus main assembly to the photosensitive drum (U.S. Pat. No. 5,903,803).

(9) Further, a method in which a photosensitive drum is rotated by engaging a gear fixed to the photosensitive drum constituting a process cartridge has been known (U.S. Pat. No. 4,829,335).

(10) However, in the conventional constitution described in U.S. Pat. No. 5,903,803, the rotatable member is required to be moved in a horizontal direction when the process cartridge is mounted to or demounted from the main assembly by being moved in a direction substantially perpendicular to an axial line of the rotatable member. That is, the rotatable member is required to be horizontally moved by an opening and closing operation of a main assembly cover provided to the apparatus main assembly. By the opening operation of the main assembly cover, the hole is moved apart from the projection. On the other hand, by the closing operation of the main assembly cover, the hole is moved toward the projection so as to be engaged with the projection.

(11) Accordingly, in the conventional process cartridge, a constitution for moving the rotatable member in a rotational axis direction by the opening and closing operation of the main assembly cover is required to be provided to the main assembly.

(12) In the constitution described in U.S. Pat. No. 4,829,335, without moving the driving gear provided to the main assembly along the axial line direction thereof, the cartridge can be mounted to and demounted from the main assembly by being moved in a direction substantially perpendicular to the axial line. However, in this constitution a driving connection portion between the main assembly and the cartridge is an engaging portion between gears, so that it is difficult to prevent rotation non uniformity of the photosensitive drum.

SUMMARY OF THE INVENTION

(13) A principal object of the present invention is to provide a process cartridge, a photosensitive drum unit used in the process cartridge, and an electrophotographic image forming apparatus to which the process cartridge is detachably mountable, capable of solving the above described problems of the conventional process cartridges.

(14) Another object of the present invention is to provide a process cartridge capable of smoothly rotating a photosensitive drum by being mounted to a main assembly provided with no mechanism for moving a main assembly side coupling member, in its axial line direction, for transmitting a rotational force to the photosensitive drum by an opening and closing operation of a main assembly cover. A further object of the present invention is to provide a photosensitive drum unit used in the process cartridge and an electrophotographic image forming apparatus to which the process cartridge is mountable and from which the process cartridge is demountable.

(15) A further object of the present invention is to provide a process cartridge demountable from a main assembly of an electrophotographic image forming apparatus provided with a driving shaft in a direction perpendicular to an axial line of the driving shaft. A further object of the present invention is to provide a photosensitive drum unit used in the process cartridge and an electrophotographic image forming apparatus to which the process cartridge is detachably mountable.

(16) A further object of the present invention is to provide a process cartridge mountable to a main assembly of an electrophotographic image forming apparatus provided with a driving shaft in a direction substantially perpendicular to an axial line of the driving shaft. A further object of the present invention is to provide a photosensitive drum unit used in the process cartridge and an electrophotographic image forming apparatus to which the process cartridge is detachably mountable.

(17) A further object of the present invention is to provide a process cartridge mountable to and demountable from a main assembly of an electrophotographic image forming apparatus provided with a driving shaft in a direction substantially perpendicular to an axial line of the driving shaft. A

further object of the present invention is to provide a photosensitive drum unit used in the process cartridge and an electrophotographic image forming apparatus to which the process cartridge is detachably mountable.

(18) A further object of the present invention is to provide a process cartridge which compatibly realized that the process cartridge is demountable from a main assembly provided with a driving shaft in a direction substantially perpendicular to an axial line of the driving shaft and is capable of smoothly rotating the photosensitive drum. A further object of the present invention is to provide a photosensitive drum unit used in the process cartridge and an electrophotographic image forming apparatus to which the process cartridge is detachably mountable.

(19) A further object of the present invention is to provide a process cartridge which compatibly realizes that the process cartridge is mountable to a main assembly provided with a driving shaft in a direction substantially perpendicular to an axial line of the driving shaft and is capable of smoothly rotating the photosensitive drum. A further object of the present invention is to provide a photosensitive drum unit used in the process cartridge and an electrophotographic image forming apparatus to which the process cartridge is detachably mountable.

(20) A further object of the present invention is to provide a process cartridge which compatibly realizes that the process cartridge is mountable to and demountable from a main assembly provided with a driving shaft in a direction substantially perpendicular to an axial line of the driving shaft and is capable of smoothly rotating the photosensitive drum. A further object of the present invention is to provide a photosensitive drum unit used in the process cartridge and an electrophotographic image forming apparatus to which the process cartridge is detachably mountable.

(21) According to the present invention, there is provided a process cartridge which can be demounted from a main assembly of an electrophotographic image forming apparatus provided with the drive shaft in a direction substantially perpendicular to an axis of a drive shaft

(22) According to the present invention, there is provided a photosensitive drum unit usable with the process cartridge and an electrophotographic image forming apparatus to which the process cartridge is detachably mountable

(23) According to the present invention, there is provided a process cartridge mountable, in a direction substantially perpendicular to an axis of a drive shaft, to a main assembly of an electrophotographic image forming device provided with the drive shaft

(24) According to the present invention, there is provided a photosensitive drum unit usable with the process cartridge and an electrophotographic image forming apparatus with the detachably mountable process cartridge

(25) According to the present invention, there is provided a process cartridge which can be mounted and dismounted, in a direction substantially perpendicular to an axis of a drive shaft, to a main assembly of an electrophotographic image forming apparatus provided with the drive shaft

(26) According to the present invention, there is provided a photosensitive drum unit usable with the process cartridge and an electrophotographic image forming apparatus relative to which the process cartridge can be mounted and demounted

(27) According to the present invention, a process cartridge is mounted to a main assembly which is not provided with a mechanism for moving a main assembly side drum coupling member for transmitting a rotational force to a photosensitive drum to an axial direction, and can rotate the photosensitive drum smoothly

(28) According to the present invention, a process cartridge can be demounted in a direction substantially perpendicular to an axis of a drive shaft provided in a main assembly, and simultaneously, the smooth rotation of a photosensitive drum can be carried out

(29) According to the present invention, a process cartridge can be mounted in a direction substantially perpendicular to an axis of a drive shaft provided in a main assembly, and simultaneously, the smooth rotation of a photosensitive drum can be carried out

(30) According to the present invention, a process cartridge is mountable and dismountable in a direction substantially perpendicular to an axis of a drive shaft provided in a main assembly, and simultaneously, the smooth rotation of a photosensitive drum can be carried out.

(31) These and other objects, features, and advantages of the present invention will become more apparent upon consideration of the following description of the preferred embodiments of the present invention, taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a sectional side elevation of a cartridge according to an embodiment of the present invention.
- (2) FIG. 2 is a perspective view of the cartridge according to the embodiment of the present invention.
- (3) FIG. 3 is a perspective view of the cartridge according to the embodiment of the present invention.
- (4) FIG. 4 is a sectional side elevation of an apparatus main assembly according to the embodiment of the present invention.
- (5) FIG. 5 is a perspective view and a longitudinal sectional view of a drum flange (drum shaft) according to the embodiment of the present invention.
- (6) FIG. 6 is a perspective view of a photosensitive drum according to the embodiment of the present invention.
- (7) FIG. 7 is longitudinal sectional views of the photosensitive drum according to the embodiment of the present invention.
- (8) FIG. 8 is perspective views and a longitudinal sectional view of a coupling according to the embodiment of the present invention.
- (9) FIG. 9 is perspective views of a drum bearing member according to the embodiment of the present invention.
- (10) FIG. 10 is detailed views of a side surface of the cartridge according to the embodiment of the present invention.
- (11) FIG. 11 is exploded perspective views and longitudinal sectional views of the coupling and the bearing member according to the embodiment of the present invention.
- (12) FIG. 12 is a longitudinal sectional view after the assembling of the cartridge according to the embodiment of the present invention.
- (13) FIG. 13 is a longitudinal sectional view after the assembling of the cartridge according to the embodiment of the present invention.
- (14) FIG. 14 is a longitudinal sectional view of the cartridge according to the embodiment of the present invention.
- (15) FIG. 15 is perspective views which illustrate a combined state of the drum shaft and the coupling.
- (16) FIG. 16 is perspective views which illustrate an inclined state of the coupling.
- (17) FIG. 17 is perspective views and a longitudinal sectional view of a driving structure of the apparatus main assembly according to the embodiment of the present invention.
- (18) FIG. 18 is a perspective view of a cartridge set portion of the apparatus main assembly according to the embodiment of the present invention.
- (19) FIG. 19 is a perspective view of the cartridge set portion of the apparatus main assembly according to the embodiment of the present invention.
- (20) FIG. 20 is sectional views which illustrate a process of the mounting of the cartridge to the apparatus main assembly according to the embodiment of the present invention.

(21) FIG. 21 is perspective views which illustrate a process of the engagement between the drive shaft and the coupling according to the embodiment of the present invention.

(22) FIG. 22 is perspective views which illustrate a process of the engagement between the drive shaft and the coupling according to the embodiment of the present invention.

(23) FIG. 23 is perspective views which illustrate the coupling of the apparatus main assembly and the coupling of the cartridge according to the embodiment of the present invention.

(24) FIG. 24 is an exploded perspective view which illustrates the drive shaft, the driving gear, the coupling, and the drum shaft according to the embodiment of the present invention.

(25) FIG. 25 is perspective views which illustrate a process of the disengagement of the coupling from the drive shaft according to the embodiment of the present invention.

(26) FIG. 26 is perspective views which illustrate the coupling and the drum shaft according to the embodiment of the present invention.

(27) FIG. 27 is perspective views which illustrate the drum shaft according to the embodiment of the present invention.

(28) FIG. 28 is perspective views which illustrate a drive shaft and a driving gear according to the embodiment of the present invention.

(29) FIG. 29 is perspective views which illustrate the coupling according to the embodiment of the present invention, and side views.

(30) FIG. 30 is exploded perspective views which illustrate the drum shaft, the drive shaft, and the coupling according to the embodiment of the present invention.

(31) FIG. 31 shows a side view and a longitudinal section of the side surface of the cartridge according to the embodiment of the present invention.

(32) FIG. 32 is a perspective view and a view, as seen from the device of the cartridge set portion of the apparatus main assembly, according to the embodiment of the present invention.

(33) FIG. 33 is longitudinal sectional views which illustrate a dismounting process from the apparatus main assembly of the cartridge according to the embodiment of the present invention.

(34) FIG. 34 is longitudinal sectional views which illustrate a mounting process to the apparatus main assembly of the cartridge according to the embodiment of the present invention.

(35) FIG. 35 is perspective views which illustrate phase control means for a drive shaft according to a second embodiment of the present invention.

(36) FIG. 36 is perspective views which illustrate a mounting operation of a cartridge according to the embodiment of the present invention.

(37) FIG. 37 is perspective views of a coupling according to the embodiment of the present invention.

(38) FIG. 38 is top plan views of a mounted state of the cartridge as seen in a mounting direction according to the embodiment of the present invention.

(39) FIG. 39 is perspective views which illustrate a drive stop state of the process cartridge (photosensitive drum) according to the embodiment of the present invention.

(40) FIG. 40 is longitudinal sectional views and perspective views which illustrate a dismounting operation of the process cartridge according to the embodiment of the present invention.

(41) FIG. 41 is a sectional view which illustrates the state where a door provided in an apparatus main assembly is opened according to a third embodiment of the present invention.

(42) FIG. 42 is a perspective view which illustrates a mounting guide of a driving side of the apparatus main assembly according to the embodiment of the present invention.

(43) FIG. 43 is a side view of the driving side of the cartridge according to the embodiment of the present invention.

(44) FIG. 44 is a perspective view as seen from the driving side of the cartridge according to the embodiment of the present invention.

(45) FIG. 45 is side view which illustrates an inserting state of the cartridge to the apparatus main assembly according to the embodiment of the present invention.

(46) FIG. **46** is a perspective view which illustrates an attaching state of a locking member to a drum bearing member according to a fourth embodiment of the present invention.

(47) FIG. **47** is an exploded perspective view which illustrates the drum bearing member, a coupling, and a drum shaft according to the embodiment of the present invention.

(48) FIG. **48** is a perspective view which illustrates a driving side of the cartridge according to the embodiment of the present invention.

(49) FIG. **49** is perspective views and longitudinal sectional views which illustrate an engaged state between a drive shaft and a coupling according to the embodiment of the present invention.

(50) FIG. **50** is an exploded perspective view which illustrates a state where a pressing member was mounted to a drum bearing member according to a fifth embodiment of the present invention.

(51) FIG. **51** is exploded perspective views which illustrate the drum bearing member, a coupling, and a drum shaft according to the embodiment of the present invention.

(52) FIG. **52** is a perspective view which illustrates the driving side of a cartridge according to the embodiment of the present invention.

(53) FIG. **53** is perspective views and longitudinal sectional views which illustrate an engaged state between a drive shaft and the coupling according to the embodiment of the present invention.

(54) FIG. **54** is an exploded perspective view which illustrates a cartridge before assembling the major members according to a sixth embodiment of the present invention.

(55) FIG. **55** is a side view which illustrates a driving side according to the embodiment of the present invention.

(56) FIG. **56** is schematic longitudinal sectional views of a drum shaft and a coupling according to the embodiment of the present invention.

(57) FIG. **57** is longitudinal sectional views which illustrate the engagement between a drive shaft and coupling according to the embodiment of the present invention.

(58) FIG. **58** is sectional views which illustrate a modified example of a coupling locking member according to the embodiment of the present invention.

(59) FIG. **59** is a perspective view which illustrates an attaching state of a magnet member to a drum bearing member according to a seventh embodiment of the present invention.

(60) FIG. **60** is an exploded perspective view which illustrates the drum bearing member, a coupling, and a drum shaft according to the embodiment of the present invention.

(61) FIG. **61** is a perspective view which illustrates a driving side of the cartridge according to the embodiment of the present invention.

(62) FIG. **62** is perspective views and longitudinal sectional views which illustrate an engaged state between a drive shaft and coupling according to the embodiment of the present invention.

(63) FIG. **63** is a perspective view which illustrates the driving side of a cartridge according to an eighth embodiment of the present invention.

(64) FIG. **64** is n exploded perspective views which illustrate a state before the assembly of a bearing member according to the embodiment of the present invention.

(65) FIG. **65** is longitudinal sectional views which illustrate the structures of a drum shaft, a coupling, and a bearing member according to the embodiment of the present invention.

(66) FIG. **66** is a perspective view which illustrates a driving side of an apparatus main assembly guide according to the embodiment of the present invention.

(67) FIG. **67** is longitudinal sectional views which illustrate a disengagement state of a locking member according to the embodiment of the present invention.

(68) FIG. **68** is longitudinal sectional views which illustrate the engagement between a drive shaft and a coupling according to the embodiment of the present invention.

(69) FIG. **69** is side views which illustrate a driving side of a cartridge according to a ninth embodiment of the present invention.

(70) FIG. **70** is a perspective view which illustrates a driving side of an apparatus main assembly guide according to the embodiment of the present invention.

(71) FIG. **71** is side views which illustrate a relation between the cartridge and the main assembly guide according to the embodiment of the present invention.

(72) FIG. **72** is perspective views which illustrate a relation between the main assembly guide and the coupling according to the embodiment of the present invention.

(73) FIG. **73** is side views, as seen from the driving side, which illustrate a process of the mounting to the main assembly of the cartridge, according to the embodiment of the present invention.

(74) FIG. **74** is a perspective view which illustrates a driving side of a main assembly guide according to a tenth embodiment of the present invention.

(75) FIG. **75** is a side view which illustrates a relation between the main assembly guide and a coupling according to the embodiment of the present invention.

(76) FIG. **76** is a perspective view which illustrates a relation between the main assembly guide and the coupling according to the embodiment of the present invention.

(77) FIG. **77** is a side view which illustrates a relation between the cartridge and the main assembly guide according to the embodiment of the present invention.

(78) FIG. **78** is perspective views which illustrate a relation between the main assembly guide and the coupling according to the embodiment of the present invention.

(79) FIG. **79** is a side view which illustrates a relation between the main assembly guide and the coupling according to the embodiment of the present invention.

(80) FIG. **80** is a perspective view which illustrates a relation between the main assembly guide and the coupling according to the embodiment of the present invention.

(81) FIG. **81** is a side view which illustrates a relation between the main assembly guide and the coupling according to the embodiment of the present invention.

(82) FIG. **82** is a perspective view and a sectional view of a coupling according to an eleventh embodiment of the present invention.

(83) FIG. **83** is a perspective view and a sectional view of the coupling according to the embodiment of the present invention.

(84) FIG. **84** is a perspective view and a sectional view of the coupling according to the embodiment of the present invention.

(85) FIG. **85** is perspective views and sectional views of a coupling according to a twelfth embodiment of the present invention.

(86) FIG. **86** is perspective views which illustrate a coupling according to a thirteenth embodiment of the present invention.

(87) FIG. **87** is a sectional view which illustrates a drum shaft, a drive shaft, the coupling, and an urging member according to the embodiment of the present invention.

(88) FIG. **88** is sectional views which illustrate the drum shaft, the coupling, a bearing member, and the drive shaft according to the embodiment of the present invention.

(89) FIG. **89** is a perspective view which illustrates a drum shaft and a coupling according to a 14th embodiment of the present invention.

(90) FIG. **90** is perspective views which illustrate a process of the engagement between a drive shaft and coupling according to the embodiment of the present invention.

(91) FIG. **91** is perspective views and sectional views which illustrate a drum shaft, a coupling, and a bearing member according to a 15th embodiment of the present invention.

(92) FIG. **92** is perspective views which illustrate a supporting method for a coupling (mounting method) according to a 16th embodiment of the present invention.

(93) FIG. **93** is perspective views which illustrate a supporting method for a coupling (mounting method) according to a 17th embodiment of the present invention.

(94) FIG. **94** is a perspective view of a cartridge according to an embodiment of the present invention.

(95) FIG. **95** illustrates only a coupling according to the embodiment of the present invention.

(96) FIG. **96** illustrates a drum flange having a coupling according to an embodiment of the present invention.

invention.

(97) FIG. **97** is sectional views taken along **S22-S22** of FIG. **84**.

(98) FIG. **98** is a sectional view of a photosensitive drum unit according to an embodiment of the present invention.

(99) FIG. **99** is a sectional view taken along **S23-S23** of FIG. **85**.

(100) FIG. **100** is perspective views which illustrate a combined state of a drum shaft and a coupling according to an embodiment of the present invention.

(101) FIG. **101** is perspective views which illustrate an inclined state of a coupling according to an embodiment of the present invention.

(102) FIG. **102** is perspective views which illustrate a process of the engagement between a drive shaft and a coupling according to an embodiment of the present invention.

(103) FIG. **103** is perspective views which illustrate a process of the engagement between a drive shaft and a coupling according to an embodiment of the present invention.

(104) FIG. **104** is an exploded perspective view which illustrates a drive shaft, a driving gear, a coupling, and a drum shaft according to an embodiment of the present invention.

(105) FIG. **105** is perspective views which illustrate a process of the disengagement of a coupling from a drive shaft according to an embodiment of the present invention.

(106) FIG. **106** is perspective views which illustrate a combined state between a drum shaft and a coupling according to an embodiment of the present invention.

(107) FIG. **107** is perspective views which illustrate a combined state between a drum shaft and a coupling according to an embodiment of the present invention.

(108) FIG. **108** is perspective views showing a combined state between a drum shaft and a coupling according to an embodiment of the present invention.

(109) FIG. **109** is a perspective view of a first frame unit which has a photosensitive drum, as seen from the driving side, according to an embodiment of the present invention.

(110) FIG. **110** is a perspective view which illustrates a drum shaft and a coupling according to an embodiment of the present invention.

(111) FIG. **111** is a sectional view taken along **S20-S20** in FIG. **79**.

(112) FIG. **112** is a perspective view of a photosensitive drum unit according to an embodiment of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

(113) The process cartridge and an electrophotographic image forming apparatus according to according to an embodiment of the present invention will be described.

Embodiment 1

(114) (1) Brief description of process cartridge

(115) A process cartridge B to which an embodiment of the present invention is applied will be described with reference to FIGS. **1** to **4**. FIG. **1** is a sectional view of the cartridge B. FIGS. **2** and **3** are perspective views of the cartridge B. FIG. **4** is a sectional view of an electrophotographic image forming apparatus main assembly A (hereinafter referred to as an “apparatus main assembly A”). The apparatus main assembly A corresponds to a portion of the electrophotographic image forming apparatus from which the cartridge B is excluded.

(116) Referring to FIGS. **1** to **3**, the cartridge B includes an electrophotographic photosensitive drum **107**. The photosensitive drum **107** is rotated by receiving a rotational force from the apparatus main assembly A by a coupling mechanism when the cartridge B is mounted in the apparatus main assembly A as shown in FIG. **4**. The cartridge B is mountable to and demountable from the apparatus main assembly A by a user.

(117) A charging roller **108** as a charging means (process means) is provided in contact with an outer peripheral surface of the photosensitive drum **107**. The charging roller **108** electrically charges the photosensitive drum **107** by voltage application from the apparatus main assembly A. The charging roller **108** is rotated by the rotation of the photosensitive drum **107**.

(118) The cartridge B includes a developing roller **110** as a developing means (process means). The developing roller **110** supplies a developer to a developing area of the photosensitive drum **107**. The developing roller **110** develops an electrostatic latent image formed on the photosensitive drum **107** with the developer t. The developing roller **110** contains therein a magnet roller (fixed magnet) **111**. In contact with a peripheral surface of the developing roller **110**, a developing blade **112** is provided. The developing blade **112** defines an amount of the developer t to be deposited on the peripheral surface of the developing roller **110**. The developing blade **112** imparts triboelectric charges to the developer t.

(119) The developer t contained in a developer accommodating container **114** is sent to a developing chamber **113a** by rotation of stirring members **115** and **116**, so that the developing roller **110** supplied with a voltage is rotated. As a result, a developer layer to which the electric charges are imparted by the developing blade **112** is formed on the surface of the developing roller **110**. The developer t is transferred onto the photosensitive drum **107** depending on the latent image. As a result, the latent image is developed.

(120) The developer image formed on the photosensitive drum **107** is transferred onto a recording medium **102** by a transfer roller **104**. The recording medium **102** is used for forming an image of the developer thereon and, e.g., is recording paper, label, OHP sheet, and so on

(121) In contact with the outer peripheral surface of the photosensitive drum **107**, an elastic cleaning blade **117a** as a cleaning means (process means) is disposed. The cleaning blade **117a** elastically contacts the photosensitive drum **107** at its end and removes the developer t remaining on the photosensitive drum **107** after the developer image is transferred onto the recording medium **102**. The developer t removed from the surface of the photosensitive drum **107** by the cleaning blade **117a** is accommodated in a removed developer reservoir **117b**.

(122) The cartridge B is integrally constituted by a first frame unit **119** and a second frame unit **120**.

(123) The first frame unit **119** is constituted by a first frame **113** as a part of a cartridge frame B1. The first frame unit **119** includes the developing roller **110**, the developing blade **112**, the developing chamber **113a**, the developer accommodating container **114**, and the stirring members **115** and **116**.

(124) The second frame unit **120** is constituted by a second frame **118** as a part of the cartridge frame B1. The second frame unit **120** includes the photosensitive drum **107**, the cleaning blade **117a**, the removed developer reservoir **117b**, and the charging roller **108**.

(125) The first frame unit **119** and the second frame unit **120** are rotatably connected with each other by a pin P. By an elastic member **135** (FIG. 3) provided between the first and second frame units **119** and **120**, the developing roller **110** is pressed against the photosensitive drum **107**.

(126) The user attaches (mounts) the cartridge B to a cartridge mounting portion **130a** of the apparatus main assembly A by gripping a grip. During the mounting, as described later, a driving shaft **180** (FIG. 17) of the apparatus main assembly A and a coupling member **150** (described later) as a rotational force transmitting part of the cartridge B are connected with each other in synchronism with the mounting operation of the cartridge B. The photosensitive drum **107** or the like is rotated by receiving the rotational force from the apparatus main assembly A.

(127) (2) Description of Electrophotographic Image Forming Apparatus

(128) With reference to FIG. 4, the electrophotographic image forming apparatus using the above described cartridge B will be described.

(129) In the following, a laser beam printer will be described as an example of the apparatus main assembly A.

(130) During image formation, the surface of the rotating photosensitive drum **107** is electrically charged uniformly by the charging roller **108**. Then, the surface of the photosensitive drum **107** is irradiated with laser light, depending on image information, emitted from an optical means **101** including unshown members such as a laser diode, a polygonal mirror, a lens, and a reflecting

mirror. As a result, on the photosensitive drum **107**, an electrostatic latent image depending on the image information is formed. The latent image is developed by the above described developing roller **110**.

(131) On the other hand, in synchronism with the image formation, the recording medium **102** set in a cassette **103a** is conveyed to a transfer position by a feeding roller **103b** and conveying roller pairs **103c**, **103d** and **103e**. At the transfer position, the transfer roller **104** as a transfer means is disposed. To the transfer roller **104**, a voltage is applied. As a result, the developer image formed on the photosensitive drum **107** is transferred onto the recording medium **102**.

(132) The recording medium **102** onto which the developer image is transferred is conveyed to a fixing means **105** through a guide **103f**. The fixing means **105** includes a driving roller **105c** and a fixing roller **105b** containing therein a heater **105a**. To the passing recording medium **102**, heat and pressure are applied, so that the developer image is fixed on the recording medium **102**. As a result, on the recording medium **102**, an image is formed. Thereafter, the recording medium **102** is conveyed by roller pairs **103g** and **103h** and discharged on a tray **106**. The above described roller **103b**, the conveying roller pairs **103c**, **103d** and **103e**, the guide **103f**, the roller pairs **103g** and **103h**, and the like constitute a conveying means **103** for conveying the recording medium **102**.

(133) The cartridge mounting portion **130a** is a portion (space) for mounting the cartridge B therein. In a state in which the cartridge B is positioned in the space, the coupling member **150** (described later) of the cartridge B is connected with the driving shaft of the apparatus main assembly A. In this embodiment, the mounting of the cartridge B to the mounting portion **130a** is referred to as mounting of the cartridge B to the apparatus main assembly A. Further, demounting (removal) of the cartridge B from the mounting portion **130b** is referred to as demounting of the cartridge B from the apparatus main assembly A.

(134) (3) Description of Constitution of Drum Flange

(135) First, a drum flange at a side where the rotational force is transmitted from the apparatus main assembly A to the photosensitive drum **107** (hereinafter simply referred to a “drive side”) will be described with reference to FIG. 5. FIG. 5(a) is a perspective view of the drum flange at the drive side and FIG. 5(b) is a sectional view of the drum flange taken along S1-S1 line shown in FIG. 5(a). Incidentally, with respect to an axial line direction of the photosensitive drum, a side opposite from the drive side is referred to as a “non-drive side”).

(136) A drum flange **151** is formed of a resinous material by ejection molding. Examples of the resinous material may include polyacetal, polycarbonate, and so on. A drum shaft **153** is formed of a metallic material such as iron, stainless steel, or the like. Depending on a load torque for rotating the photosensitive drum **107**, it is possible to select appropriately the materials for the drum flange **151** and the drum shaft **153**. For example, the drum flange **151** may also be formed of the metallic material and the drum shaft **153** may also be formed of the resinous material. When both of the drum flange **151** and the drum shaft **153** are formed of the resinous material, they can be integrally molded.

(137) The flange **151** is provided with an engaging portion **151a** which engages with an inner surface of the photosensitive drum **107**, a gear portion (helical gear or spur gear) **151c** for transmitting a rotational force to the developing roller **110**, and an engaging portion **151d** rotatably supported on a drum bearing. More specifically, as for the flange **151**, the engaging portion **151a** engages with one end of a cylindrical drum **107a** as will be described hereinafter. These are disposed co-axially with a rotation axis L1 of the photosensitive drum **107**. And, the drum engaging portion **151a** has a cylindrical shape, and a base **151b** perpendicular thereto is provided. The base **151b** is provided with a drum shaft **153** outwardly projected with respect to the direction of the axis L1. This drum shaft **153** is co-axial with the drum engaging portion **151a**. These are fixed so as to be co-axial with the rotation axis L1. As for the fixing method thereof the press-fitting, the bonding, the insert molding, and so on are available, and they are selected properly. As shown in FIG. 7 (a), the drum flange **151** includes an inner surface adjacent to a hollow portion in the drum

flange **151**. The hollow portion is open to outside of the drum flange **151**.

(138) The drum shaft **153** comprises the circular column portion **153a** which has a projection configuration, and is disposed so as to be co-axially with the rotation axis of the photosensitive drum **107**. The drum shaft **153** is provided on the end part of the photosensitive drum **107** on the axis **L1** of the photosensitive drum **107**. In addition, the drum shaft **153** is about 5-15 mm in diameter in consideration of the material, the load, and the space. A free end portion **153b** of the circular column portion **153a** has a semi-spherical surface configuration so that it can incline smoothly, when an axis of a drum coupling member **150** which is a rotating force transmitting portion inclines, as will be described in detail hereinafter. In addition, in order to receive the rotational force from the drum coupling member **150**, a rotating force transmitting pin (rotating force receiving member (portion) **155** are provided on the photosensitive drum **107** side of the free end of the drum shaft **153**. The pin **155** is extended in the direction substantially perpendicular to the axis of the drum shaft **153**.

(139) The pin **155** as the rotational force receiving member has a cylindrical shape which has a diameter smaller than that of the circular column portion **153a** of the drum shaft **153**, and is made of the metal or the resin material. And, it is fixed by press-fitting, bonding, and so on to the drum shaft **153**. And, the pin **155** is fixed in the direction which the axis thereof intersects the axis **L1** of the photosensitive drum **107**. Preferably, it is desirable to dispose the axis of the pin **155** so as to pass the center **P2** of the spherical surface of the free end portion **153b** of the drum shaft **153** (FIG. 5(b)). Although the free end portion **153b** is the semi-spherical surface configuration actually, the center **P2** is the center of a phantom spherical surface that the semispherical surface makes the part thereof. In addition, the number of the pins **155** can be selected properly. In this embodiment, a single pin **155** is used from the standpoint of the assembling property and in order to transmit driving torque assuredly. The pin **155** passes said center **P2**, and is through the drum shaft **153**. And, the pin **155** is outwardly projected at the positions of the peripheral surface of the drum shaft **153** which are diametrically opposite (**155a1**, **155a2**). More particularly, the pin **155** is projected in the direction perpendicular to the axis (axis **L1**) of the drum shaft **153** relative to the drum shaft **153** at the two opposite places (**155a1**, **155a2**). By this, the drum shaft **153** receives the rotational force from the drum coupling member **150** at the two places. In this embodiment, the pin **155** is mounted to the drum shaft **153** in the range of 5 mm from the free end of the drum shaft **153**. However, this does not limit the present invention.

(140) In addition, a space portion **151e** formed by the engaging portion **151d** and the base **151b** receives a part of drum coupling member **150**, in mounting the drum coupling member **150** (which will be described hereinafter) to the flange **151**.

(141) In this embodiment, the gear portion **151a** for transmitting the rotational force to the developing roller **110** is mounted to the flange **151**. However, the rotation of the developing roller **110** may be transmitted not through the flange **151**. In that case, the gear portion **151c** is unnecessary. However, in the case of disposing the gear portion **151a** at the flange **151**, integral molding, with the flange **151**, of the gear portion **151a** can be utilized.

(142) The flange **151**, the drum shaft **153**, and the pin **155** function as the rotational force receiving member which receives the rotational force from the drum coupling member **150** as will be described hereinafter.

(143) (4) Structure of Electrophotographic Photosensitive Member Drum Unit

(144) Referring to FIG. 6 and FIG. 7, the structure of an electrophotographic photosensitive member drum unit ("drum unit") will be described. FIG. 6(a) is a perspective view, as seen from the driving side, of the drum unit **U1**, and FIG. 6(b) is a perspective view as seen from the non-driving side. In addition, FIG. 7 is a sectional view taken along **S2-S2** of FIG. 6(a).

(145) The photosensitive drum **107** has a cylindrical drum **107a** coated with a photosensitive layer **107b** on the peripheral surface.

(146) The cylindrical drum **107a** has an electroconductive cylinder, such as the aluminum, and the

photosensitive layer **107b** applied thereon. The opposite ends thereof are provided with the drum surface and the substantially co-axial opening **107a1**, **107a2**, in order to engage the drum flange (**151**, **152**). More particularly, the drum shaft **153** is provided on the end part of the cylindrical drum **107a** co-axially with the cylindrical drum **107a**. Designated by **151c** is a gear and transmits a rotational force which the coupling **150** received from a drive shaft **180** to a developing roller **110**. The gear **151c** is integrally molded with the flange **15**.

(147) The cylinder **107a** may be hollow or solid.

(148) As to the drum flange **151** of the driving side, since it has been described in the foregoing, the description is omitted.

(149) A drum flange **152** of the non-driving side is made of the resin material similarly to the driving side with injection molding. And, a drum engaging portion **152b** and a bearing portion **152a** are substantially co-axially disposed with each other. In addition, the flange **152** is provided with a drum grounding plate **156**. The drum grounding plate **156** is an electroconductive thin plate (metal). The drum grounding plate **156** includes contact portions **156b1**, **156b2** which contact the inner surface of the electroconductive cylindrical drum **107a**, and a contact portion **156a** which contacts the drum grounding shaft **154** (which will be described hereinafter). And, for the purpose of grounding the photosensitive drum **107**, the drum grounding plate **156** is electrically connected with the apparatus main assembly A.

(150) A drum flange **152** of the non-driving side is made of the resin material, similarly to the driving side with injection molding. And, a drum engaging portion **152b** and a bearing portion **152a** are substantially co-axially disposed with each other. In addition, the flange **152** is provided with a drum grounding plate **156**. The drum grounding plate **156** is an electroconductive thin plate (metal). The drum grounding plate **156** includes contact portions **156b1**, **156b2** which contact the inner surface of the electroconductive cylindrical drum **107a**, and a contact portion **156a** which contacts the drum grounding shaft **154** (which will be described hereinafter). And, for the purpose of grounding the photosensitive drum **107**, the drum grounding plate **156** is electrically connected with the apparatus main assembly A.

(151) Although it has been described that the drum grounding plate **156** is provided in the flange **152**, the present invention is not limited to such an example. For example, the drum grounding plate **156** may be disposed at the drum flange **151**, and it is possible to select properly the position which can be connected with the ground.

(152) Thus, the drum unit U1 comprises the photosensitive drum **107** which has the cylinder **107a**, the flange **151**, the flange **152**, the drum shaft **153**, the pin **155**, and the drum grounding plate **156**.

(153) (5) Rotational Force Transmitting Portion (Drum Coupling Member)

(154) The description will be made, referring to FIG. 8 as to an example of the drum coupling member which is the rotational force transmitting portion. FIG. 8 (a) is a perspective view, as seen from the apparatus main assembly side, of the drum coupling member, FIG. 8 (b) is a perspective view, as seen from the photosensitive drum side, of the drum coupling member, and FIG. 8 (c) is a view seen in the direction perpendicular to the direction of the coupling rotation shaft L2. In addition, FIG. 8 (d) is the side view, as seen from the apparatus main assembly side, of the drum coupling member, FIG. 8 (e) is the Figure, as seen from the photosensitive drum side, and FIG. 8 (f) is a sectional view taken along S3 in FIG. 8 (d).

(155) The drum coupling member ("coupling") **150** engages with a drive shaft **180** (FIG. 17) of the apparatus main assembly A in the state where the cartridge B is mounted set to the installation section **130a**. In addition, the coupling **150** is disengaged from the drive shaft **180**, when the cartridge B is taken out from the apparatus main assembly A. And, the coupling **150** receives a rotational force from a motor provided in the apparatus main assembly A through the drive shaft **180** in the state where it is engaged with the drive shaft **180**. In addition, the coupling **150** transmits the rotational force thereof to the photosensitive drum **107**. The materials available for the coupling **150** are the resin materials, such as polyacetal and the polycarbonate PPS. However, in order to

raise a rigidity of the coupling **150**, the glass fibers, the carbon fibers, and so on may be mixed in the above described resin material correspondingly to a required load torque. In the case of mixing said material, the rigidity of the coupling **150** can be raised. In addition, in the resin material, the metal may be inserted, then the rigidity may further be raised, and the whole coupling may be manufactured from the metal and so on.

(156) The coupling **150** mainly comprises three portions.

(157) The first portion is engageable with the drive shaft **180** (which will be described hereinafter), and it is a coupling side driven portion **150a** for receiving the rotational force from the rotational force transmitting pin **182** which is a rotational force applying portion (main assembly side rotational force transmitting portion) provided on the drive shaft **180**. In addition, the second portion is engageable with the pin **155**, and it is a coupling side driving portion **150b** for transmitting the rotational force to the drum shaft **153**. In addition, the third portion is a connecting portion **150c** for connecting the driven portion **150a** and the driving portion **150b** with each other (FIGS. **8** (c) and (f)).

(158) The driven portion **150a**, the driving portion **150b**, and the connecting portion **150c** may be molded integrally, or, alternatively, the separate parts may be connected with each other. In this embodiment, these are integrally molded with resin material. By this, the manufacturing of the coupling **150** is easy and the accuracy as the parts is high. As shown in FIG. **8** (f) the driven portion **150a** is provided with a drive shaft insertion opening portion **150m** which expands toward the rotation axis L2 of the coupling **150**. The driving portion **150b** has a drum shaft insertion opening portion **150l**, which expands toward the rotation axis L2.

(159) The opening **150m** has a conical driving shaft receiving surface **150f** as an expanded part which expands toward the drive shaft **180** side in the state where the coupling **150** is mounted to the apparatus main assembly A. The receiving surface **150f** constitutes a recess **150z** as shown in FIG. **8** (f). The recess **150z** includes the opening **150m** at a position opposite the side adjacent the photosensitive drum **107** with respect to the direction of the axis L2.

(160) By this, regardless of rotation phase of the photosensitive drum **107** in the cartridge B, the coupling **150** can pivot among a rotational force transmitting angular position, a pre-engagement angular position, and a disengaging angular position relative to the axis L1 of the photosensitive drum **107** without being prevented by the free end portion of the drive shaft **180**. The rotational force transmitting angular position, the pre-engagement angular position, and the disengaging angular position will be described hereinafter.

(161) A plurality of projections (the engaging portions) **150d1-150d4** are provided at equal intervals on a circumference about the axis L2 on an end surface of the recess **150z**. Between the adjacent projections **150d 1**, **150d 2**, **150d3**, **150d4**, the standing-by portions **150k1**, **150k2**, **150k3**, **150k4** are provided. An intervals between the adjacent projections **150d1-150d4** is larger than the outer diameter of the pin **182**, so that the rotational force transmitting pins of the drive shaft **180** provided in the apparatus main assembly A (rotational force applying portions) **182** are received. The recesses between the adjacent projections are the standing-by portions **150k1-k4**. When the rotational force is transmitted to the coupling **150** from the drive shaft **180**, the transmission pins **182a1**, **182a2** are received by any of the standing-by portions **150k1-k4**. In addition, in FIG. **8** (d), the rotational force reception surfaces (rotational force receiving portions) **150e** crossing with a rotational direction of the coupling **150** and (**150e1-150e4**) are provided in the downstream with respect to the clockwise direction (X1) of each projection **150d**. More particularly, the projection **150d1** has a receiving surface **150e1**, the projection **150d2** has a receiving surface **150e2**, the projection **150d3** has a receiving surface **150e3**, and, and, a projection **150d4** has a receiving surface **150e4**. In the state where the drive shaft **180** rotates, the pin **182a1**, **182a2** contacts to any of the receiving surface **150e1-150e4**. By doing so, the receiving surface **150e** contacted by the pin **182a1**, **182a2** is pushed by the pin **182**. By this, the coupling **150** rotates about the axis L2. The receiving surface **150e1-150e4** is extended in the direction crossing with the rotational direction of

the coupling **150**.

(162) In order to stabilize the running torque transmitted to the coupling **150** as much as possible, it is desirable to dispose the rotational force receiving surfaces **150e** on the same circumference that has the center on the axis **L2**. By this, the rotational force transmission radius is constant and the running torque transmitted to the coupling **150** is stabilized. In addition, as for the projections **150d1-150d4**, it is preferable that the position of the by coupling **150** is stabilized by the balance of the forces which the coupling receives. For that reason, in this embodiment, the receiving surfaces **150e** are disposed at the diametrically opposed positions (180 degrees). More particularly, in this embodiment, the receiving surface **150e1** and the receiving surface **150e3** are diametrically opposed relative to each other, and the receiving surface **150e2** and the surface **150e4** are diametrically opposed relative to each other (FIG. 8 (d)). By this arrangement, the forces which the coupling **150** receives constitute a force couple. Therefore, the coupling **150** can continue rotary motion only by receiving the force couple. For this reason, the coupling **150** can rotate without the necessity of being specified in the position of the rotation axis **L2** thereof. In addition, as for the number thereof, as long as the pins **182** of the drive shaft **180** (the rotational force applying portion) can enter the standing-by portions **150k1-150k2**, it is possible to select suitably. In this embodiment, as shown in FIG. 8 the four receiving surfaces are provided. This embodiment is not limited to this example. For example, the receiving surfaces **150e** (projections **150d1-150d4**) do not need to be disposed on the same circumference (the phantom circle **C1** and FIG. 8 (d)). Or, it is not necessary to dispose at the diametrically opposed positions. However, the effects described above can be provided by disposing the receiving surfaces **150e** as described above.

(163) Here, in this embodiment, the diameter of the pin is approximately 2 mm, and a circumferential length of the stand-by portion **150k** is approximately 8 mm. The circumferential length of the stand-by portion **150k** is an interval between adjacent projections **150d** (on the phantom circle). The dimensions are not limiting to the present invention.

(164) Similarly to the opening **150m**, a drum shaft insertion opening portion **150l** has a conical rotational force receiving surface **150i** of an as an expanded part which expands toward the drum shaft **153** in the state where it is mounted to the cartridge B. The receiving surface **150i** constitutes a recess **150q**, as shown in FIG. 8 (f).

(165) By this, irrespective of the rotation phase of the photosensitive drum **107** in the cartridge B, the coupling **150** can pivot among a rotational force transmitting angular position, a pre-engagement angular position, and a disengaging angular position to the drum axis **L1** without being prevented by the free end portion of the drum shaft **153**. The recess **150q** is constituted in the illustrated example by a conical receiving surface **150i** which it has centering on the axis **L2**. The standby openings **150g 1** or **150g2** ("opening") are provided in the receiving surface **150i** (FIG. 8b). As for the coupling **150**, the pins **155** can be inserted into the inside of this opening **150g 1** or **150g2** so that it may be mounted to the drum shaft **153**. And, the size of the openings **150g 1** or **150g2** is larger than the outer diameter of the pin **155**. By doing so, irrespective of the rotation phase of the photosensitive drum **107** in the cartridge B, the coupling **150** is pivotable among the rotational force transmitting angular position and the pre-engagement angular position (or disengaging angular position) as will be described hereinafter without being prevented by the pin **155**.

(166) More particularly, the projection **150d** is provided adjacent to the free end of the recess **150z**. And, the projections (projections) **150d** project in the intersection direction crossing with the rotational direction in which the coupling **150** rotates, and are provided with the intervals along the rotational direction. And, in the state where the cartridge B is mounted to the apparatus main assembly A, the receiving surfaces **150e** engage to or abutted to the pin **182**, and are pushed by the pin **182**.

(167) By this, the receiving surfaces **150e** receive the rotational force from the drive shaft **180**. In addition, the receiving surfaces **150e** are disposed in equidistant from the axis **L2**, and constitute a

pair interposing the axis L2 they are constituted by the surface in the intersection direction in the projections **150d**. In addition, the standing-by portions (recesses) **150k** are provided along the rotational direction, and they are depressed in the direction of the axis L2.

(168) The standing-by portion **150k** is formed as a space between the adjacent projections **150d**. In the state where the cartridge B is mounted to the apparatus main assembly A, the pin **182** enters the standing-by portion **150k**, and it stands by for being driven. And, when the drive shaft **180** rotates, the pin **182** pushes the receiving surface **150e**.

(169) By this, the coupling **150** rotates.

(170) The rotational force receiving surface (rotational force receiving member (portion)) **150e** may be disposed inside of the driving shaft receiving surface **150f**. Or, the receiving surface **150e** may be provided in the portion outwardly projected from the receiving surface **150f** with respect to the direction of the axis L2. When the receiving surface **150e** is disposed inside of the receiving surface **150f**, the standing-by portion **150k** is disposed inside of the receiving surface **150f**.

(171) More particularly, the standing-by portion **150k** is the recess provided between the projections **150d** in the inside of the arc part of the receiving surface **150f**. In addition, when the receiving surface **150e** is disposed at the position which outwardly projects, the standing-by portion **150k** is the recess positioned between the projections **150d**. Here, the recess may be a through hole extended in the direction of the axis L2, or it may be closed at one end thereof. More particularly, the recess is provided by the space region provided between the projection **150d**. And, what is necessary is just to be able to enter the pin **182** into the region in the state where the cartridge B is mounted to the apparatus main assembly A.

(172) These structures of the standing-by portion apply similarly to the embodiments as will be described hereinafter.

(173) In FIG. 8 (e), the rotational force transmission surfaces (the rotational force transmitting portions) **150h** and (**150h 1** or **150h2**) are provided in the upstream, with respect to the clockwise direction (X1), of the opening **150g 1** or **150g2**. And, the rotational force is transmitted to the photosensitive drum **107** from the coupling **150** by the convection sections **150h 1** or **150h2** contacting to any of the pins **155a1**, **155a2**. More particularly, the transmitting surfaces **150h 1** or **150h2** push the side surface of the pin **155**. By this, the coupling **150** rotates with the center thereof aligned with the axis L2. The transmitting surface **150h 1** or **150h2** is extended in the direction crossing with the rotational direction of the coupling **150**.

(174) Similarly to the projection **150d**, it is desirable to dispose the transmitting surfaces **150h 1** or **150h2** diametrically opposed relative to each other on the same circumference.

(175) At the time of manufacturing the drum coupling member **150** with an injection molding, the connecting portion **150c** may become thin. This is because the coupling is manufactured so that the driving force receiving portion **150a**, the driving portion **150b** and the connecting portion **150c** have a substantially uniform thickness. When the rigidity of the connecting portion **150c** is insufficient, therefore, it is possible to make the connecting portion **150c** thick so that driven portion **150a**, the driving portion **150b**, and the connecting portion **150c** have the substantially equivalent thickness.

(176) (6) Drum Bearing Member

(177) The description will be made, referring to FIG. 9, about a drum bearing member. FIG. 9(a) is a perspective view, as seen from a drive shaft side, and FIG. 9(b) is a perspective view, as seen from the photosensitive drum side.

(178) The drum bearing member **157** rotatably supports the photosensitive drum **107** on the second frame **118**. In addition, the bearing member **157** has a function of positioning the second frame unit **120** in the apparatus main assembly A. Further, it has the function of retaining the coupling **150** so that the rotational force can be transmitted to the photosensitive drum **107**. As shown in FIG. 2, the bearing member **157** faces outside of the casing of the cartridge at a first end portion of the casing, which is opposite to a second end portion of the casing.

(179) As shown in FIG. 9 an engaging portion (supporting projection) **157d** positioned to the second frame **118** and a peripheral part **157c** positioned in the apparatus main assembly A are substantially co-axially disposed. The engaging portion **157d** and the peripheral part **157c** are annular. And, the coupling **150** is disposed in the space portion **157b** inside thereof. The engaging portion **157d** and the peripheral part **157c** are provided with a rib **157e** for retaining the coupling **150** in the cartridge B in the neighborhood of the central portion with respect to the axial direction. The bearing member **157** is provided with holes **157g 1** or **157g2** which penetrate the abutment surface **157f** and the fixing screw for fixing the bearing member **157** to the second frame **118**. As will be described hereinafter, the guide portion **157a** for mounting and demounting on and the cartridge B relative to the apparatus main assembly A is integrally provided on the bearing member **157**. As also shown in FIG. 9 (a), the bearing member **157** includes a projected part **157h** projecting in a direction away from the second end portion of the casing in the direction of the rotational axis of the photosensitive drum **107a**, and a surface of the bearing member **157** is adjacent to an open space that extends to the rotational axis of the photosensitive drum **107a** in a direction perpendicular to the rotational axis of the photosensitive drum **107a**.

(180) As can be seen and understood from FIGS. 9, 12, and the other figures, a distance between at least a part of the supporting projection **157d** and the second end portion of the casing in the direction of the rotational axis of the photosensitive drum **107a** is shorter than a distance between the surface of the bearing member and the second end portion of the casing in the direction of the rotational axis of the photosensitive drum **107a**, and a distance between at least a part of the projected part **157h** and the second end portion of the casing in the direction of the rotational axis of the photosensitive drum **107a** is longer than the distance between the surface of the bearing member and the second end portion of the casing in the direction of the rotational axis of the photosensitive drum **107a**.

(181) As can be seen and understood from FIG. 1, 2, 9, 12, and the other figures, the rotational axis of the developing roller **110**, the rotational axis of the photosensitive drum **107a**, and a part of the surface of the bearing member **157** are positioned in this order along a first line. Further, a distance from the rotational axis of the photosensitive drum **107a** to at least a part of the projected part **157h** as measured along a second line that is perpendicular to the rotational axis of the photosensitive drum **107a** is shorter than a radius of the photosensitive drum that extends from the rotational axis of the photosensitive drum **107a** to an outer surface of the photosensitive drum **107a**. Also, a distance from the rotational axis of the photosensitive drum **107a** to at least a part of the surface of the bearing member **157** as measured along a third line that is perpendicular to the rotational axis of the photosensitive drum **107a** and is different than the second line is shorter than the radius of the photosensitive drum **107a**.

(182) (7) Coupling Mounting Method

(183) Referring to FIG. 10-FIG. 16, the description will be made as to the mounting method of the coupling. FIG. 10 (a) is an enlarged view, as seen from the driving side surface, of the major part around the photosensitive drum. FIG. 10 (b) is an enlarged view, as seen from the non-driving side surface, of the major part. FIG. 10 (c) is a sectional view taken along S4-S4 of FIG. 10 (a). FIGS. 11 (a) and (b) are an exploded perspective views which illustrate the state before attachment of the primary members of the second frame unit. FIG. 11 (c) is a sectional view taken along S5-S5 in FIG. 11 (a). FIG. 12 is a sectional view which illustrates a state after attaching. FIG. 13 is a sectional view taken along S6-S6 of FIG. 11 (a). FIG. 14 is a sectional view which illustrates a state after rotating the coupling and the photosensitive drum through 90 degrees from the state of FIG. 13. FIG. 15 is a perspective view which illustrates the combined state of the drum shaft and the coupling. FIGS. 15(a1)-(a5) are front views, as seen from the axial direction of the photosensitive drum, and FIGS. 15(b1)-(b5) are perspective views. FIG. 16 is a perspective view which illustrates the state where the coupling is inclined in the process cartridge.

(184) As shown in FIG. 15 the coupling **150** is mounted so that the axis L2 thereof can incline in

any direction relative to the axis L1 of the drum shaft **153** (coaxial with the photosensitive drum **107**).

(185) In FIG. **15 (a1)** and FIG. **15 (b1)**, the axis L2 of the coupling **150** is co-axial with the axis L1 of the drum shaft **153**. The state when the coupling **150** is inclined upward from this state is illustrated in FIG. **15 (a2)** and **(b2)**. As shown in this Figure, when the coupling **150** is inclined toward the opening **150g** side, the opening **150g** moves along the pin **155**. As a result, the coupling **150** is inclined about an axis AX perpendicular to the axis of the pin **155**.

(186) In FIG. **15 (a3)** and **(b3)**, the state where the coupling **150** is inclined rightward is shown. As shown in this Figure, when the coupling **150** inclines in the orthogonality direction of the opening **150g**, the opening **150g** rotates about the pin **155**. The axis of rotation is the axis line AY of the pin **155**.

(187) The state where the coupling **150** is inclined downward is shown in FIG. **15 (a4)** and **(b4)**, and the state where the coupling **150** is inclined leftward is shown in FIG. **15 (a5)** and **(b5)**. The rotation axes AX and AY have been described in the foregoing.

(188) In the directions different from the inclining direction described in the foregoing, for example, in the 45-degree direction in FIG. **15 (a1)** and so on, the inclination is made by combining the rotations in the axes AX and the directions of AY. Thus, the axis L2 can be pivoted in any direction relative to the axis L1.

(189) More particularly, the transmitting surface (rotational force transmitting portion) **150h** is movable relative to the pin (rotational force receiving portion) **155**. The pin **155** has the transmitting surface **150** in the movable condition. And, the transmitting surface **150h** and the pin **155** are engaged to each other in the rotational direction of the coupling **150**. In this manner, the coupling **150** is mounted to the cartridge. In order to accomplish this, the gap is provided between the transmitting surface **150h** and the pin **155**. By this, the coupling **150** is pivotable in all directions substantially relative to the axis L1.

(190) As described above, the opening **150g** is extended in the direction (the rotational axis direction of the coupling **150**) crossing with the projection direction of the pins **155** at least. Therefore, as has been described hereinbefore, the coupling **150** is pivotable in all the directions.

(191) It has been mentioned that the axis L2 is slantable or inclinable in any direction relative to the axis L1. However, the axis L2 does not necessarily need to be linearly slantable to the predetermined angle in the full range of 360-degree direction in the coupling **150**. For example, the opening **150g** can be selected to be slightly wider in the circumferential direction. By doing so, the time of the axis L2 inclining relative to the axis L1, even if it is the case where it cannot incline to the predetermined angle linearly, the coupling **150** can rotate to a slight degree around the axis L2. Therefore, it can be inclined to the predetermined angle. In other words, the amount of the play in the rotational direction of the opening **150g** is selected properly if necessary.

(192) In this manner, the coupling **150** is revolvable or swingable over the full-circumference substantially relative to drum shaft (rotational force receiving member) **153**. More particularly, the coupling **150** is pivotable over the full-circumference thereof substantially relative to the drum shaft **153**.

(193) Furthermore, as will be understood from the foregoing explanation, the coupling **150** is capable of whirling in and substantially over the circumferential direction of the drum shaft **153**. Here, the whirling motion is not a motion with which the coupling itself rotates about the axis L2, but the inclined axis L2 rotates about the axis L1 of the photosensitive drum, although the whirling here does not preclude the rotation of the coupling per se about the axis L2 of the coupling **150**.

(194) The process of the assembling the parts will be described.

(195) First, the photosensitive drum **107** is mounted in the direction X1 in FIG. **11(a)** and FIG. **11 (b)**. At this time, the bearing portion **151d** of the flange **151** is made to substantially co-axially engage with the centering portion **118h** of the second frame **118**. In addition, bearing hole **152a** (FIG. 7 of the flange **152(a)**) is substantially co-axially engaged with the centering portion **118g** of

the second frame **118**.

(196) The drum grounding shaft **154** is inserted into the direction X2. And, the centering portion **154b** is penetrated through the bearing hole **152a** (FIG. **6b**) and the centering hole **118g** (FIG. **10** (b)). At this time, the centering portion **154b** and the bearing hole **152a** are supported so that the photosensitive drum **107** is rotatable. On the other hand, the centering portion **154b** and the centering hole **118g** are supported fixedly by the press-fitting and so on. By this, the photosensitive drum **107** is rotatably supported relative to the second frame. Alternatively, it may be fixed non-rotatably relative to the flange **152**, and the drum grounding shaft **154** (centering portion **154b**) may be rotatably mounted to the second frame **118**.

(197) The coupling **150** and the bearing member **157** are inserted in the direction X3. First, the driving portion **150b** is inserted toward the direction X3 downstream, while maintaining the axis L2 (FIG. **11c**) in parallel with X3. At this time, the phase of the pin **155** and the phase of the opening **150g** are matched with each other, and the pin **155** is made inserted into the openings **150g1** or **150g2**. And, the free end portion **153b** of the drum shaft **153** is abutted to the drum bearing surface **150i**. The free end portion **153b** is the spherical surface and the drum bearing surface **150i** is a conic surface. That is, the drum bearing surface **150i** of the conic surface which is the recess, and the free end portion **153b** of the drum shaft **153** which is the projection contact to each other. Therefore, the driving portion **150b** side is positioned relative to the free end portion **153b**. As has been described hereinbefore, when the coupling **150** rotates by the transmission of the rotational force from the apparatus main assembly A, the pin **155** positioned in the opening **150g** will be pushed by the rotational force transmission surfaces (the rotational force transmitting portions) **150h1** or **150h2** and (FIG. **8b**). By this, the rotational force is transmitted to the photosensitive drum **107**. Thereafter, the engaging portion **157d** is inserted downstream with respect to the direction X3. By this, a part of coupling **150** is received in the space portion **157b**. And, the engaging portion **157d** supports the bearing portion **151d** of the flange **151**, so that the photosensitive drum **107** is rotatable. In addition, the engaging portion **157d** engages with the centering portion **118h** of the second frame **118**. The abutment surface **157f** of the bearing member **157** abuts to the abutment surface **118j** of the second frame **118**. And, the screws **158a**, **158b** are penetrated through the holes **157g1** or **157g2**, and they are fixed to the screw holes **118k1**, **118k2** of the second frame **118**, so that the bearing member **157** is fixed to the second frame **118** (FIG. **12**).

(198) The dimensions of the various portions of the coupling **150** will be described. As shown in FIG. **11** (c), a maximum outer diameter of the driven portion **150a** is $\Phi D2$, a maximum outer diameter of the driving portion **150b** is $\Phi D1$, and a small diameter of the standby opening **150g** is $\Phi D3$. In addition, a maximum outer diameter of the pin **155** is $\Phi D5$, and an inner diameter of the retention rib **157e** of the bearing member **157** is $\Phi D4$. Here, the maximum outer diameter is the outer diameter of a maximum rotation locus about the axis L1 or the axis L2. At this time, since $\Phi D5 < \Phi D3$ is satisfied, the coupling **150** can be assembled to the predetermined position by the straight mounting operation in the direction X3 therefore, the assembling property is high (the state after the assembly is shown in FIG. **12**). The diameter of the inner surface $\Phi D4$ of the retention rib **157e** of the bearing member **157** is larger than $\Phi D2$ of the coupling **150**, and smaller than $\Phi D1$ ($\Phi D2 < \Phi D4 < \Phi D1$). By this, just the step attached to the direction X3 straight is sufficient to assemble the bearing member **157** to the predetermined position. For this reason, the assembling property can be improved (the state after the assembly is shown in FIG. **12**).

(199) As shown in FIG. **12**, the retention rib **157e** of the bearing member **157** is disposed closely to a flange portion **150j** of the coupling **150** in the direction of the axis L1. More specifically, in the direction of the axis L1, the distance from an end surface **150j1** of the flange portion **150j** to the axis L4 of the pin **155** is $n1$. In addition, the distance from an end surface **157e1** of the rib **157e** to the other end surface **157j2** of the flange portion **150j** is $n2$. The distance $n2 < \text{distance } n1$ is satisfied.

(200) In addition, with respect to the direction perpendicular to the axis L1, the flange portion **150j** and the rib **157e** are disposed so that they are overlapped relative to each other. More specifically, the distance n4 from the inner surface **157e3** of the rib **157e** to the outer surface **150j3** of the flange portion **150j** is the overlap amount n4 with respect to the orthogonality direction of the axis L1.

(201) By such settings, the pin **155** is prevented from disengaging from the opening **150g**. That is, the movement of the coupling **150** is limited by the bearing member **157**. Thus, the coupling **150** does not disengage from the cartridge. The prevention of disengagement can be accomplished without additional parts. The dimensions described above are desirable from the standpoint of reduction of manufacturing and assembling costs. However, the present invention is not limited to these dimensions.

(202) As described above (FIG. 10 (c) and FIG. 13), the receiving surface **150i** which is the recess **150q** of the coupling **150** is in contact with the free end surface **153b** of the drum shaft **153** which is the projection. Therefore, the coupling **150** is swung along the free end portion (the spherical surface) **153b** about the center P2 of the free end portion (the spherical surface) **153b** in other words, the axis L2 is pivotable substantially in all directions irrespective of the phase of the drum shaft **153**. The axis L2 of the coupling **150** is pivotable in all directions substantially. As will be described hereinafter, in order that the coupling **150** may engage with the drive shaft **180**, the axis L2 is inclined toward the downstream with respect to the mounting direction of the cartridge B relative to the axis L1, just before the engagement. In other words, as shown in FIG. 16, the axis L2 inclines so that the driven portion **150a** positions at the downstream side with respect to the mounting direction X4 relative to the axis L1 of the photosensitive drum **107** (the drum shaft **153**). In FIGS. 16 (a)-(c), although the positions of the driven portion **150a** slightly differ relative to each other, they are positioned at the downstream side with respect to the mounting direction X4 in any case.

(203) The still more detailed description will be made.

(204) As shown in FIG. 12, a distance n3 between a maximum outer diameter part and bearing member **157** of the driving portion **150b** is selected so that a slight gap is provided between them. By this, as has been described hereinbefore, the coupling **150** is pivotable.

(205) As shown in FIG. 9, the rib **157e** is a semi-circular rib. The rib **157e** is disposed at the downstream with respect to the mounting direction X4 of the cartridge B. Therefore, as shown in FIG. 10 (c), the driven portion **150a** side of the axis L2 is greatly pivotable in the direction X4. In other words, the driving portion **150b** side of the axis L2 is greatly pivotable in the direction of angle $\alpha 3$ at phase (FIG. 9(a) at which the rib **157e** is not disposed. FIG. 10 (c) illustrates the state where the axis L2 inclined. In addition, it can also be pivoted to the state substantially parallel to the axis L1 by which it is shown in FIG. 13 from the state of the inclined axis L2 shown in FIG. 10 (c). In this manner, the rib **157e** is disposed. By this, the coupling **150** can be mounted by the simple method to the cartridge B. Further, in addition, no matter the drum shaft **153** may stop with what phase, the axis L2 is pivotable relative to the axis L1. The rib is not limited to the semi-circular rib. As long as the coupling **150** is pivotable to the predetermined direction, and it is possible to mount the coupling **150** to Cartridge B (photosensitive drum **107**), any rib is usable. In this manner, the rib **157e** has a function as the regulating means for regulating the inclining direction of the coupling **150**.

(206) In addition, a distance n2 (FIG. 12) in the direction of the axis L1 from the rib **157e** to the flange portion **150j** is shorter than a distance n1 from the center of the pin **155** to the driving portion **150b** side edge. By this, the pin **155** does not disengage from the opening **150g**.

(207) As described above, the coupling **150** is supported by the both of the drum shaft **153** and the drum bearing **157** substantially. More particularly, the coupling **150** is mounted to the cartridge B by the drum shaft **153** and the drum bearing **157** substantially.

(208) The coupling **150** has a play (the distance n2) in the direction of the axis L1 relative to the drum shaft **153**. Therefore, the receiving surface **150i** (the conic surface) may not contact snugly

the drum shaft free end portion **153b** (the spherical surface). In other words, the center of the pivoting may deviate from the center of curvature P2 of the spherical surface. However, even in such a case, the axis L2 is pivotable relative to the axis L1. For this reason, the purpose of this embodiment can be accomplished.

(209) In addition, maximum possible inclination angle α_4 (FIG. 10 (c)) between the axis L1 and the axis L2 is the one half of the taper angle (α_1 , FIG. 8(f)) between the axis L2 and the receiving surface **150i**. The receiving surface **150i** has conical shape and the drum shaft **153** has the cylindrical shape. For this reason, the gap g of angle $\alpha_1/2$ is provided between them. By this, the taper angle α_1 changes, and therefore, the inclination angle α_4 of the coupling **150** are set to the optimal value. In this manner, since the receiving surface **150i** is the conic surface, the circular column portion **153a** of the drum shaft **153** is satisfactory with the simple cylindrical shape. In other words, the drum shaft does not need to have a complicated configuration. Therefore, the machining cost of the drum shaft can be suppressed.

(210) In addition, as shown in FIG. 10 (c), when the coupling **150** inclines, a part of coupling can circumvent into illustration) by space portion **151e** (hatching of the flange **151**. By this, the lightening cavity (Space portion **151e**) of the gear portion **151c** can be used without futility. Therefore, effective use of the space can be done. Incidentally, the lightening cavity (Space portion **151e**) is not usually used.

(211) As described above, in the embodiment of FIG. 10 (c), the coupling **150** is mounted so that a part of a coupling **150** may locate at the position which overlaps the gear portion **151c** with respect to the direction of the axis L2. In the case of the flange which does not have the gear portion **151c**, a part of coupling **150** can further enter into the cylinder **107a**.

(212) When the axis L2 inclines, the width of the opening **150g** is selected in consideration of the size of the pin **155** so that the pin **155** may not interfere.

(213) More particularly, the transmitting surface (rotational force transmitting portion) **150h** is movable relative to the pin (rotational force receiving portion) **155**. The pin **155** has the transmitting surface **150** in the movable condition. And, the transmitting surface **150h** and the pin **155** are engaged to each other in the rotational direction of the coupling **150**. In this manner, the coupling **150** is mounted to the cartridge. In order to accomplish this, the gap is provided between the transmitting surface **150h** and the pin **155**. By this, the coupling **150** is pivotable in all directions substantially relative to the axis L1.

(214) The locus of the flange portion **150j** when the driven portion **150a** side inclines in the direction X5 is illustrated by the region T1 in FIG. 14. As shown in the Figure, even if the coupling **150** inclines, the interference with the pin **155** does not occur, and therefore, the flange portion **150j** can be provided over the full-circumference of the coupling **150** (FIG. 8 (b)). In other words, the shaft receiving surface **150i** has conical shape, and therefore, when the coupling **150** inclines, the pin **155** does not enter in the region T1. For this reason, the cutting away range of the coupling **150** is minimized. Therefore, the rigidity of the coupling **150** can be assured.

(215) In the above described mounting process, the process (the non-driving side) in the direction X2 and the process (the driving side) in the direction X3 may be exchanged.

(216) The bearing member **157** has been described as being fixed on the screws to the second frame **118**. However, the present invention is not limited to such an example. For example, like the bonding, if the bearing member **157** is fixable to the second frame **118**, the any method will be usable.

(217) (8) Drive Shaft and Driving Structure of the Apparatus Main Assembly

(218) Referring to FIG. 17, the description will be made as to the structure for driving the photosensitive drum **107** in the apparatus main assembly A. FIG. 17(a) is a partly broken perspective view of the side plate of the driving side in the state where the cartridge B is not mounted to the apparatus main assembly A. FIG. 17(b) is a perspective view which illustrates only the drum driving structure. FIG. 17(c) is the sectional view taken along S7-S7 of FIG. 17(b).

(219) The drive shaft **180** has the substantially similar structure as the above described drum shaft **153**. In other words, the free end portion **180b** thereof forms a semispherical surface. In addition, it has a rotational force transmitting pin **182** as a rotational force applying portion of the main part **180a** of the cylindrical shape which penetrates the center substantially. The rotational force is transmitted to the coupling **150** by this pin **182**.

(220) A drum driving gear **181** substantially co-axial with the axis of the drive shaft **180** is provided on the longitudinally opposite side of the free end portion **180b** of the drive shaft **180**. The gear **181** is fixed non-rotatably relative to the drive shaft **180**. Therefore, the rotation of the gear **181** will also rotate the drive shaft **180**.

(221) In addition, the gear **181** is engaged with a pinion gear **187** for receiving the rotational force from the motor **186**. Therefore, the rotation of the motor **186** will rotate the drive shaft **180** through the gear **181**.

(222) In addition, the gear **181** is rotatably mounted to the apparatus main assembly A by the bearing members **183**, **184**. At this time, the gear **181** does not move relative to the direction of the axial direction L3 of the drive shaft **180** (the gear **181**), that is, it is positioned with respect to the axial direction L3. Therefore, the gears **181** and the bearing members **183** and **184** can be closely disposed relative to each other with respect to the axial direction. In addition, the drive shaft **180** does not move with respect to the direction thereof of the axis L3. Therefore, the drive shaft **180** and the gap between the bearing members **183** and **184** have the sizes which permit the rotation of the drive shaft **180**. For this reason, the position of the gear **181** with respect to the diametrical direction relative to the gear **187** is determined correctly.

(223) In addition, although it has been described that the drive is directly transmitted to the gear **181** from the gear **187**, the present invention is not limited to such an example. For example, it is the satisfactory using a plurality of gears on account of the motor disposed at the apparatus main assembly A. Alternatively, it is possible to transmit the rotational force by a belt and so on.

(224) (9) Main Assembly Side Mounting Guide for Guiding Cartridge B

(225) As shown in FIGS. **18** and **19**, the mounting means **130** of this embodiment includes main assembly guides **130R1**, **130R2**, **130L1**, **130L2** provided in the apparatus main assembly A.

(226) They are provided opposed to the both side surfaces of the cartridge mounting space (the cartridge set portion **130a**) provided in the apparatus main assembly A (the driving side surface in FIG. **18**) (the side surface in FIG. **19** in which it does not drive). The main assembly guides **130R1**, **130R2** are provided in the main assembly opposed to the driving side of the cartridge B, and they are extended along the mounting direction of the cartridge B. On the other hand, the main assembly guides **130L1**, **130L2** are provided in the main assembly side opposed to the non-driving side of the cartridge B, and they are extended along the mounting direction of the cartridge B. The main assembly guides **130R1**, **130R2** and the main assembly guides **130L1**, **130L2** are opposed to each other. At the time of mounting the cartridge B to the apparatus main assembly A these guides **130R1**, **130R2**, **130L1**, **130L2** guide the cartridge guides as will be described hereinafter. At the time of mounting the cartridge B to the apparatus main assembly A, the cartridge door **109** which can be opened and closed relative to the apparatus main assembly A about a shaft **109a** is opened. And, the mounting, into the apparatus main assembly A, of the cartridge B is completed by closing the door **109**. At the time of taking out the cartridge B from the apparatus main assembly A, the door **109** is opened. These operations are effected by the user.

(227) (10) Positioning Portion, Relative to Mounting Guide and Apparatus Main Assembly a for Cartridge B

(228) As shown in FIGS. **2** and **3**, in this embodiment, the outer periphery **157a** of the outside end of the bearing member **157** functions also as a cartridge guide **140R1**. In addition, the outer periphery **154a** of the outside end of the drum grounding shaft **154** functions also as a cartridge guide **140L1**.

(229) In addition, the one longitudinal end (the driving side) of the second frame unit **120** is

provided with the cartridge guide **140R2** on the upper portion of the cartridge guide **140R1**. And, the other end (the non-driving side) in the longitudinal direction is provided with the cartridge guide **140L2** on the upper portion of the cartridge guide **140L1**.

(230) More particularly, the one longitudinal end of the photosensitive drum **107** is provided with the cartridge side guides **140R1**, **140R2** outwardly projected from the cartridge frame **B1**. In addition, the other end in the longitudinal direction is provided with the cartridge side guides **140L1**, **140L2** outwardly projected from the cartridge frame **B1**. The guides **140R1**, **140R2**, **140L1**, **140L2** is projected toward the along said longitudinal direction here and there outside. More particularly, the guides **140R1**, **140R2**, **140L1**, **140L2** are projected from the cartridge frame **B1** along the axis **L1**. And, at the time of mounting the cartridge **B** to the apparatus main assembly **A**, and at the time of demounting the cartridge **B** from the apparatus main assembly **A** the guide **140R1** is guided by the guide **130R1**, and the guide **140R2** is guided by the guide **130R2**. In addition, at the time of mounting the cartridge **B** to the apparatus main assembly **A** and at the time of demounting the cartridge **B** from the apparatus main assembly **A** the guide **140L1** is guided by the guide **130L1**, and the guide **140L2** is guided by the guide **130L2**. In this manner, the cartridge **B** is mounted to the apparatus main assembly **A**, moving in the direction substantially perpendicular to the axial direction **L3** of the drive shaft **180**, and it is similarly demounted from the apparatus main assembly **A**. In addition, in this embodiment, the cartridge guides **140R1**, **140R2** are molded integrally with the second frame **118**. However, separate members are usable as the cartridge guides **140R1**, **140R2**.

(231) (11) Mounting Operation of Process Cartridge

(232) Referring to FIG. **20**, the mounting operation, into the apparatus main assembly **A**, of the cartridge **B** will be described. FIG. **20** shows the mounting process. FIG. **20** is a sectional view taken along **S9-S9** of FIG. **18**.

(233) As shown in FIG. **20(a)**, the door **109** is opened by the user. And, the cartridge **B** is dismountably mounted relative to the cartridge mounting means **130** (the installation section **130a**) provided in the apparatus main assembly **A**.

(234) At the time of mounting the cartridge **B** to the apparatus main assembly **A**, in the driving side, the cartridge guides **140R1**, **140R2** are inserted along the main assembly guides **130R1**, **130R2**, as shown in FIG. **20(b)**. In addition, also about the non-driving side, the cartridge guides **140L1**, **140L2** (FIG. **3**) are inserted along the main assembly guides **130L1**, **130L2** (FIG. **19**).

(235) When the cartridge **B** is further inserted in the direction of the arrow **X4**, the coupling between the drive shaft **180** and the cartridge **B** is established and then, the cartridge **B** is mounted to the predetermined position (the installation section **130a**) (the provision). In other words, as shown in FIG. **20 (c)**, the cartridge guide **140R1** contacts to the positioning portion **130R1a** of the main assembly guide **130R1**, and the cartridge guide **140R2** contacts to the positioning portion **130R2a** of the main assembly guide **130R2**. In addition, the cartridge guide **140L1** contacts to the positioning portion **130L1a** (FIG. **19**) of the main assembly guide **130L1**, and the cartridge guide **140L2** contacts to the positioning portion **130L2a** of the main assembly guide **130L2** since this state is substantially symmetrical, the illustration is not made. In this manner, the cartridge **B** is dismountably mounted to the installation section **130a** by the mounting means **130**. More particularly, the cartridge **B** is mounted in the state positioned in the apparatus main assembly **A**. And, in the state where the cartridge **B** is mounted to the installation section **130a**, the drive shaft **180** and the coupling **150** are in the engaged state relative to each other.

(236) More particularly, the coupling **150** is in a rotational force transmitting angular position as will be described hereinafter.

(237) The image forming operation is enabled by the cartridge **B** being mounted to the set portion **130a**.

(238) When the cartridge **B** is provided at the predetermined position, a pressing receptor portion **140R1b** (FIG. **2**) of the cartridge **B** receives the urging force from an urging spring **188R** (FIG. **18**,

FIG. 19, and FIG. 20). In addition, from an urging spring **188L**, a pressing receptor portion **140L1b** (FIG. 3) of the cartridge B receives the urging force. By this, the cartridge B (photosensitive drum **107**) is correctly positioned relative to the transfer roller, the optical means, and so on of the apparatus main assembly A.

(239) The user may enter the cartridge B to the set portion **130a** as described above. Alternatively, the user enters the cartridge B to the position halfway, and the last mounting operation may be effected by another means. For example, utilizing the operation which shuts the door **109**, a part of door **109** acts on the cartridge B which is in the position in the course of the mounting to push the cartridge B into the final mounted position. Further alternatively, the user pushes, into the cartridge B to the middle, the cartridge B, and lets it fall into the set portion **130a** by the weight, after that.

(240) Here, as shown in FIG. 18-20, the mounting and demounting of the cartridge B relative to the apparatus main assembly A is effected by the movement in the direction substantially perpendicular to the direction of the axis L3 of the drive shaft **180** (FIG. 21) corresponding to these operations, the position between the drive shaft **180** and the coupling **150** change between the engaged state and the disengagement state.

(241) Here, the description will be made about “perpendicular substantially”.

(242) Between the cartridge B and the apparatus main assembly A, in order to mount and demount the cartridge B smoothly, small gaps are provided. More specifically, the small gaps are provided between the guide **140R1** and the guide **130R1** with respect to the longitudinal direction, between the guide **140R2** and the guide **130R2** with respect to the longitudinal direction, between the guide **140L1** and the guide **130L1** with respect to the longitudinal direction, and between the guide **140L2** and the guide **130L2** with respect to the longitudinal direction. Therefore, at the time of the mounting and demounting of the cartridge B relative to the apparatus main assembly A, the whole cartridge B can slightly incline within the limits of the gaps. For this reason, the perpendicularity is not meant strictly. However, even in such a case, the present invention is accomplished with the effects thereof. Therefore, the term “perpendicular substantially” covers the case where the cartridge slightly inclines.

(243) (12) Coupling Engaging Operations and Drive Transmission

(244) As stated in the foregoing, immediately before or substantially simultaneously with positioning in a predetermined position of the apparatus main assembly A, the coupling **150** is engaged with the drive shaft **180**. More particularly, the coupling **150** positions at the rotational force transmitting angular position. Here, the predetermined position is the set portion **130a**. Referring to FIGS. 21, 22, and 23, the description will be made with respect to the engaging operation of this coupling. FIG. 21 is a perspective view which illustrates the major part of the drive shaft and the driving side of the cartridge. FIG. 22 is a longitudinal sectional view, as seen from the lower part of the apparatus main assembly. FIG. 23 is a longitudinal sectional view, as seen from the lower part of the apparatus main assembly. Here, the engagement means the state in which the axis L2 and the axis L3 are substantially co-axial relative to each other, and the drive transmission is possible.

(245) As shown in FIG. 22, the cartridge B is mounted to the apparatus main assembly A in the direction (arrow X4) substantially perpendicular to the axis L3 of the drive shaft **180**. Or, it is demounted from the apparatus main assembly A. In the pre-engagement angular position, the axis L2 (FIG. 22 a) of the coupling **150** inclines toward downstream with respect to the mounting direction X4 beforehand relative to the axis L1 (FIG. 22(a)) of the drum shaft **153** (FIG. 21 a and FIG. 22(a)).

(246) In order to incline the coupling toward the pre-engagement angular position beforehand, the structure of the embodiment 3-embodiment 9 as will be described hereinafter is used, for example.

(247) Because of the inclination of the coupling **150**, the downstream free end **150A1** with respect to the mounting direction X4 is closer to the photosensitive drum **107** than the drive shaft free end **180b3** in the direction of the axis L1. In addition, the upstream free end **150A2** with respect to the

mounting direction is closer to the pin **182** than the drive shaft free end **180b3** (FIG. 22(a), (b)). Here, the free end position is the position nearest to the drive shaft of the driven portion **150a** shown in FIGS. 8(a) and (c) with respect to the direction of the axis L2, and it is the remotest position from the axis L2. In other words, it is an edge line of the driven portion **150a** of the coupling **150**, or an edge line of the projection **150d** depending on the rotation phase of the coupling **150** (**150A**) in FIGS. 8(a) and (c).

(248) The free end position **150A1** of the coupling **150** passes by the drive shaft free end **180b3**. And, after the coupling **150** carries out by passage of the drive shaft free end **180b3**, the receiving surface (cartridge side contact portion) **150f** or the projection (cartridge side contact portion) **150d** contacts with the free end portion **180b** of drive shaft (main assembly side engaging portion) **180**, or pin (main assembly side engaging portion) (rotational force applying portion) **182**. And, corresponding to the mounting operation of the cartridge (B), the axis L2 is inclined so that it may align substantially with the axis L1 (FIG. 22(c)). And, when the coupling **150** inclines from said pre-engagement angular position and the axis L2 thereof aligns substantially with the axis L1, the rotational force transmitting angular position is reached. And, finally, the position of the cartridge (B) is determined relative to the apparatus main assembly (A). Here, the drive shaft **180** and the drum shaft **153** are substantially co-axial relative to each other. In addition, the receiving surface **150f** opposes to the spherical free end portion **180b** of the drive shaft **180**. This state is the engaged state between the coupling **150** and the drive shaft **180** (FIG. 21(b) and FIG. 22(d)). At this time, the pin **155** (unshown) is positioned in the opening **150g** (FIG. 8 (b)). In other words, the pin **182** takes the standing-by portion **150k**. Here, the coupling **150** covers the free end portion **180b**.

(249) The receiving surface **150f** constitutes the recess **150z**. And, the recess **150z** has the conical shape.

(250) As has been described above, the coupling **150** is pivotable relative to the axis L1. And, corresponding to the movement of the cartridge (B), a part of coupling **150** (the receiving surface **150f** and/or **150d** of projections) which is the cartridge side contact portion contacts to the main assembly side engaging portion (the drive shaft **180** and/or the pin **182**). By this, the pivoting motion of the coupling **150** is effected. As shown in FIG. 22, the coupling **150** is mounted with the state of overlapping, with respect to the direction of the axis L1, with the drive shaft **180**. However, the coupling **150** and the drive shaft **180** are engageable relative to each other with the overlapping state by the pivoting motion of the couplings, as described above.

(251) The mounting operation of the coupling **150** described above can be performed regardless of the phases of the drive shaft **180** and the coupling **150**. Referring to FIG. 15 and FIG. 23, the detailed description will be made. FIG. 23 illustrates the phase relation between the coupling and the drive shaft. In FIG. 23(a), in a downstream position with respect to the mounting direction X4 of the cartridge, the pin **182** and the receiving surface **150f** face to each other. In FIG. 23(b), the pin **182** and the projection **150d** face to each other. In FIG. 23(c), the free end portion **180b** and the projection **150d** face to each other. In FIG. 23(d), the free end portion **180b** and the receiving surface **150f** face to each other.

(252) As shown in FIG. 15, the coupling **150** is pivotably mounted in any direction relative to the drum shaft **153**. More particularly, the coupling **150** is revolvable. Therefore, as shown in FIG. 23, it can incline toward the mounting direction X4 irrespective of the phase of the drum shaft **153** relative to the mounting direction X4 of the cartridge (B). In addition, the inclination angle of the coupling **150** is set, so that regardless of the phases of the drive shaft **180** and the coupling **150**, the free end position **150A1** is made closer to the photosensitive drum **107** than the axial free end **180b3** with respect to the direction of the axis L1. In addition, the inclination angle of the coupling **150** is set, so that the free end position **150A2** is made closer to the pin **182** than the axial free end **180b3**. With such a setting, corresponding to the mounting operation of the cartridge (B), the free end position **150A1** is passed by the axial free end **180b3** in the mounting direction X4. And, in the case of FIG. 23(a), the receiving surface **150f** contacts the pin **182**. In the case of FIG. 23(b), the

projection (the engaging portion) **150d** contacts the pin (rotational force applying portion) **182**. In the case of FIG. **23(c)**, the projection **150d** contacts to the free end portion **180b**. In the case of FIG. **23(d)**, the receiving surface **150f** contacts to the free end portion **180b**. In addition, by the contact force generated at the time of mounting the cartridge (B), the axis L2 of the coupling **150** moves so that it substantially becomes co-axial with the axis L1. By this, the coupling **150** is engaged with the drive shaft **180**. More particularly, the coupling recess **150z** covers the free end portion **180b**. For this reason, the coupling **150** can be engaged with the drive shaft **180** (the pin **182**) irrespective of the phases of the drive shaft **180**, the coupling **150** and the drum shaft **153**.

(253) In addition, as shown in FIG. **22**, the gap is provided between the drum shaft **153** and the coupling **150**, so that the coupling is swingable (revolvable, pivotable).

(254) In this embodiment, the coupling **150** moves in a plane of the sheet of the drawing of FIG. **22**. However, the coupling **150** of this embodiment is capable of whirling, as described above.

Therefore, the motion of the coupling **150** may include motion not included in the plane of the sheet of the drawing of FIG. **22**. In such a case, the change from the state of FIG. **22(a)** to the state of FIG. **22(d)** occurs. This applies to the embodiments which will be described hereinafter unless otherwise stated.

(255) Referring to FIG. **24**, the rotational force transmitting operation at the time of rotating the photosensitive drum **107** will be described. The drive shaft **180** rotates with the gear **181** in the direction (Figure, X8) by the rotational force received from the driving source (the motor **186**). And, the pin **182** integral with the drive shaft **180** (**182a1**, **182a2**) contacts to any of the rotational force receiving surfaces (rotational force receiving portion) **150e1-150e4**. More particularly, the pin **182a1** contacts any one of the rotational force receiving surfaces **150e1-150e4**. In addition, the pin **182a2** contacts with any of the rotational force receiving surfaces **150e1-150e4**. By this, the rotational force of the drive shaft **180** is transmitted to the coupling **150** to rotate the coupling **150**. Furthermore, by the rotation of the coupling **150**, the rotational force transmission surfaces (the rotational force transmitting portion) **150h 1** or **150h2** of the coupling **150** contact to the pin **155** integral with the drum shaft **153**. By this, the rotational force of the drive shaft **180** is transmitted to the photosensitive drum **107** through the coupling **150**, the rotational force transmission surface **150h 1** or **150h2**, the pin **155**, the drum shaft **153**, and the drum flange **151**. In this manner, the photosensitive drum **107** is rotated.

(256) In the rotational force transmitting angular position, the free end portion **153b** is contacted with the receiving surface **150i**. And, the free end portion (the positioning portion) **180b** of the drive shaft **180** is contacted with the receiving surface (the positioning portion) **150f**. By this, the coupling **150** is positioned relative to the drive shaft **180** in the state where it is over the drive shaft **180** (FIG. **22(d)**).

(257) Here, in this embodiment, even if the axis L3 and the axis L1 deviate from the co-axial relations somewhat, the coupling **150** can effect the transmission of the rotational force because the coupling **150** inclines slightly. Even if it is such a case, the coupling **150** can rotate without covering the large additional load over the drum shaft **153** and the drive shaft **180**. Therefore, the high precision position arrangement operation of the drive shaft **180** and the drum shaft **153** at the time of the assembling is easy. For this reason, the assembling operativity can be improved.

(258) This is also one of the effects of this embodiment.

(259) In addition, in FIG. **17**, as has been described, the position of the drive shaft **180** and the gear **181** is positioned with respect to the diametrical direction and the axial direction in the predetermined position (Set portion **130a**) of the apparatus main assembly (A). In addition, the cartridge (B) is positioned in the predetermined position of the apparatus main assembly as described above. And, the drive shaft **180** positioned in said predetermined position and the cartridge (B) positioned in said predetermined position are coupled by the coupling **150**. The coupling **150** is swingable (pivotable) relative to the photosensitive drum **107**. For this reason, as described above, the coupling **150** can transmit the rotational force smoothly between the drive

shaft **180** positioned in the predetermined position and the cartridge (B) positioned in the predetermined position. In other words, even if there is some axial deviation between the drive shaft **180** and the photosensitive drum **107**, the coupling **150** can transmit the rotational force smoothly.

(260) This is also one of the effects of this embodiment.

(261) In addition, as described above, the cartridge (B) is positioned in the predetermined position. For this reason, the photosensitive drum **107** which is the constituent-element of the cartridge (B) is correctly positioned relative to the apparatus main assembly (A). Therefore, the spatial relationship between the photosensitive drum **107**, and the optical means **101**, the transfer roller **104** or recording material **102** can be maintained with high precision. In other words, those position deviations can be reduced.

(262) The coupling **150** contacts to the drive shaft **180**. By this, although it has been mentioned that the coupling **150** swings from the pre-engagement angular position to the rotational force transmitting angular position, the present invention is not limited to such an example. For example, it is possible to provide the abutting portion as the main assembly side engaging portion in the position other than the drive shaft of the apparatus main assembly. And, in the mounting process of the cartridge (B), after the free end position **150A1** passes by the drive shaft free end **180b3**, a part of coupling **150** (cartridge side contact portion) contacts with this abutting portion. By this, the coupling can receive the force of the shaking direction (pivoting direction), and it can also be made to swing so that the axis L2 becomes substantially co-axial with the axis L3 (the pivoting). In other words, another means is sufficient, if the axis L1 can substantially co-axially position with the axis L3 in interrelation with the mounting operation of the cartridge (B).

(263) (13) The Disengaging Operation of the Coupling, and the Removing Operation of the Cartridge

(264) Referring to FIG. 25, the operation for disengaging the coupling **150** from the drive shaft **180** will be described at the time of taking out the cartridge (B) from the apparatus main assembly (A). FIG. 25 is the longitudinal sectional view, as seen from the apparatus main assembly lower.

(265) First, the position of the pin **182** at the time of demounting the cartridge (B) will be described. After the image formation finishes, as will be apparent from the foregoing description, the pin **182** is positioned at any 2 of the standing-by portions **150k1-150k4** (FIG. 8). And, the pin **155** is positioned in the opening **150g 1** or **150g2**.

(266) The description will be made with respect to the operation for disengaging the coupling **150** from the drive shaft **180** in interrelation with the operation for taking out the cartridge (B).

(267) As shown in FIG. 25, the cartridge (B) is drawn out in the direction (the direction of the arrow X6) substantially perpendicular to the axis L3, at the time of demounting from the apparatus main assembly (A).

(268) In the state where the drive for the drum shaft **153** has stopped, the axis L2 is substantially co-axial relative to the axis L1 in the coupling **150** (rotational force transmitting angular position) (FIG. 25(a)). And, the drum shaft **153** moves in the dismounting direction X6 with the cartridge (B), and the receiving surface **150f** or the projection **150d** in the upstream of the coupling **150** with respect to the dismounting direction contacts at least to the free end portion **180b** of the drive shaft **180** (FIG. 25 (a)). And, the axis L2 begins to incline toward the upstream with respect to the dismounting direction X6 (FIG. 25(b)). This direction is the same as that of the inclination of the coupling **150** at the time of the mounting of the cartridge (B) (the pre-engagement angular position). It moves, while the upstream free end portion **150 A3** with respect to the dismounting direction X6 contacts to the free end portion **180b** by the dismounting operation from the apparatus main assembly (A) of this cartridge (B). In more detail, corresponding to the movement to the dismounting direction of the cartridge (B), while a part of coupling **150** (the receiving surface **150f** and/or **150d** of projections) which is the cartridge side contact portion contacts with the main assembly side engaging portion (the drive shaft **180** and/or the pin **182**), the coupling moves. And,

in the axis L2, the free end portion **150 A3** inclines to the free end **180b3** (disengaging angular position) (FIG. 25(c)). And, in this state, the coupling **150** is passed by the drive shaft **180**, contacting to the free end **180b3**, and is disengaged from the drive shaft **180** (FIG. 25(d)). Thereafter, the cartridge (B) follows the process opposite from that of the mounting process described in FIG. 20, and is taken out from the apparatus main assembly (A).

(269) As will be apparent from the foregoing description, the angle of the pre-engagement angular position relative to the axis L1 is larger than the angle of the disengaging angular position relative to the axis L1. This is because it is preferable that the free end position **150A1** passes assuredly by the free end portion **180b3** in the pre-engagement angular position in consideration of the dimensional tolerance of the parts at the time of the engagement of the coupling. More particularly, it is preferable that the gap exists between the coupling **150** and the free end portion **180b3** in the pre-engagement angular position (FIG. 22(b)). On the contrary, at the time of the coupling disengagement, the axis L2 inclines in interrelation with the dismounting operation of the cartridge in the disengaging angular position. Therefore, the coupling **150 A3** moves along the free end portion **180b3**. In other words, the upstream portion, with respect to the cartridge dismounting direction, of the coupling and the free end portion of the drive shaft are in the substantially same position (FIG. 25(c)). For this reason, the angle of the pre-engagement angular position relative to the axis L1 is larger than the angle of the disengaging angular position relative to the axis L1.

(270) In addition, similarly to the case of mounting the cartridge (B) to the apparatus main assembly (A), the cartridge (B) can be taken out irrespective of the phase difference between the coupling **150** and the pin **182**.

(271) As shown in FIG. 22, in the rotational force transmitting angular position of the coupling **150**, the angle relative to the axis L1 of the coupling **150** is such that in the state where the cartridge (B) is mounted to the apparatus main assembly (A), the coupling **150** receives the transmission of the rotational force from the drive shaft **180**, and it rotates.

(272) The rotational force transmitting angular position of the coupling **150**, the rotational force for rotating the photosensitive drum is transmitted to the drum.

(273) In addition, in the pre-engagement angular position of the coupling **150**, the angular position relative to the axis L1 of the coupling **150** is such that it is in the state immediately before the coupling **150** engages with the drive shaft **180** in the mounting operation to the apparatus main assembly (A) of the cartridge (B). More particularly, it is the angular position relative to the axis L1 which the downstream free end portion **150A1** of the coupling **150** can pass by the drive shaft **180** with respect to the mounting direction of the cartridge (B).

(274) In addition, the disengaging angular position of the coupling **150** is the angular position relative to the axis L1 of the coupling **150** at the time of taking out the cartridge (B) from the apparatus main assembly (A), in the case that the coupling **150** disengages from the drive shaft **180**. More particularly, as shown in FIG. 25, it is the angular position relative to the axis L1 with which the free end portion **150 A3** of the coupling **150** can pass by the drive shaft **180** with respect to the removing direction of the cartridge (B).

(275) In the pre-engagement angular position or the disengaging angular position, the angle theta 2 which the axis L2 makes with the axis L1 is larger than the angle theta 1 which the axis L2 makes with the axis L1 in the rotational force transmitting angular position. As for the angle theta 1, 0 degree is preferable. However, in this embodiment, if the angle theta 1 is less than about 15 degrees, the smooth transmission of the rotational force is accomplished. This is also one of the effects of this embodiment. As for the angle theta 2, the range of about 20-60 degrees is preferable.

(276) As has been described hereinbefore, the coupling is pivotably mounted to the axis L1. And, the coupling **150** in the state in which it overlaps with the drive shaft **180** with respect to the direction of the axis L1 can be disengaged from the drive shaft **180** because the coupling inclines correspondingly to the dismounting operation of the cartridge (B). More particularly, by moving the cartridge (B) in the direction substantially perpendicular to the axial direction of the drive shaft

180, the coupling **150** which covers the drive shaft **180** can be disengaged from the drive shaft **180**. (277) In the above described description, the receiving surface **150f** of the coupling **150** or the projection **150d** contacts with the free end portion **180b** (the pin **182**) in interrelation with the movement of the cartridge (B) in the dismounting direction X6. By this, it has been described that the axis L1 starts the inclination to the dismounting direction upstream. However, the present invention is not limited to such an example. For example, the coupling **150** has a structure beforehand, so that it is urged toward the upstream in the dismounting direction. And, corresponding to the movement of the cartridge (B), this urging force starts the inclination of the axis L1 toward the downstream in the dismounting direction. And, the free end **150A3** passes by the free end **180b3**, and the coupling **150** disengages from the drive shaft **180**. In other words, the receiving surface **150f** in the upstream side with respect to the dismounting direction or projection **150d** does not contact with the free end portion **180b**, and therefore, it can be disengaged from the drive shaft **180**. For this reason, the any structure can be applied if the axis L1 can be inclined in interrelation with the dismounting operation of the cartridge (B).

(278) By the point of time immediately before the coupling **150** is mounted to the drive shaft **180**, the driven portion of the coupling **150** is inclined, so that it is inclined toward the downstream with respect to the mounting direction. In other words, the coupling **150** is beforehand put on in the state of the pre-engagement angular position.

(279) In the foregoing, the motion in the plane in the sheet of the drawing of FIG. 25 has been described, but the motion may include the whirling motion as in the case of FIG. 22.

(280) As to the structure therefor, the structure of any that will be described in Embodiment 2 et seq. is usable.

(281) Referring to FIG. 26 and FIG. 27, the description will be made about the other embodiment of the drum shaft. FIG. 26 is a perspective view of the neighborhood of the drum shaft. FIG. 27 illustrates a characteristic portion.

(282) In the embodiment described above, the free end of the drum shaft **153** is formed into the spherical surface, and the coupling **150** is in contact with the spherical surface thereof. However, as shown in FIGS. 26(a) and 27(a), the free end **1153b** of the drum shaft **1153** may be a flat surface. In the case of this embodiment, the edge portion **1153c** of the peripheral surface thereof contacts the conic surface of the coupling **150**, by which the rotation is transmitted. Even with such a structure, the axis L2 can be assuredly inclined relative to the axis L1. In the case of this embodiment, there is no necessity for the spherical surface machining. Therefore, the machining cost can be reduced.

(283) In the embodiment described above, another rotational force transmitting pin is mounted to the drum shaft. However, as shown in FIGS. 26(b) and 27(b), it is possible to mold the drum shaft **1253** and the pin **1253c** integrally. In the case of integral molding using injection molding and so on, the geometrical latitude becomes high. In this case, the pin **1253c** can be integrally formed with the drum shaft **1253**. For this reason, the wide area of the drive transmitting portion **1253d** can be provided. Therefore, the running torque can be assuredly transmitted to the drum shaft made of the resin material. In addition, since integral molding is utilized, the manufacturing cost is reduced.

(284) As shown in FIGS. 26(c) and 27(c), the opposite ends **1355a1**, **1355a2** of rotational force transmitting pin (rotational force receiving member) **1355** are beforehand fixed by the press-fitting and so on to the standby opening **1350g 1** or **1350g2** of the coupling **1350**. Thereafter, it is possible to insert the drum shaft **1353** which has a free end portion **1353c1**, **1353c2** formed into a screw slotted shape (concave). At this time, in order to provide a pivotability of the coupling **1350**, the engaging portion **1355b** of the pin **1355** relative to the free end portion (unshown) of the drum shaft **1353** is formed into a spherical shape. Thus, the pin **1355** (rotational force applying portion) is fixed beforehand. By this, the size of the opening **1350g** of the coupling **1350** can be reduced. Therefore, the rigidity of the coupling **1350** can be increased.

(285) In the foregoing, the structure by which the inclination of the axis L1 is made along the free

end of the drum shaft has been described. However, as shown in FIGS. 26(d), 26(e), and 27(d), it is possible to incline along the contact surface **1457a** of the contact member **1457** on the axis of the drum shaft **1453**. In this case, the free end surface **1453b** of the drum shaft **1453** has a height comparable to the end surface of the contact member **1457**. In addition, the rotational force transmitting pin (the rotational force receiving member) **1453c** projected beyond the free end surface **1453b** is inserted into the standby opening **1450g** of the coupling **1450**. The pin **1453c** contacts to the rotational force transmission surface (the rotational force transmitting portion) **1450h** of the coupling **1450**. By this, the rotational force is transmitted to the drum **107**. In this manner, the contact surface **1457a** at the time of the coupling **1450** inclining is provided in the contact member **1457**. By this, there is no necessity of processing the drum shaft directly. Therefore, the machining cost can be lowered.

(286) In addition, similarly, the spherical surface at the free end may be a molded resin part of separate member. In this case, the machining cost of the shaft can be lowered. This is because the configuration of the shaft to be processed by the cutting and so on can be simplified. In addition, when the range of the spherical surface at the axial free end is decreased, the range of the processing which requires high degree of accuracy can be made small. By this, the machining cost can be lowered.

(287) Referring to FIG. 28, the description will be made about another embodiment of the drive shaft. FIG. 28 is perspective views of a drive shaft and a drum driving gear.

(288) First, as shown in FIG. 28(a), the free end of the drive shaft **1180** is made into the flat surface **1180b**. By this, since the configuration of the shaft is simple, the machining cost can be lowered.

(289) In addition, as shown in FIG. 28(b), it is possible to mold the rotational force applying portion (drive transmitting portion) **1280** (**1280c1**, **1280c2**) integrally with the drive shaft **1280**. When the drive shaft **1280** is the molded resin part, the rotational force applying portion can be molded integrally. Therefore, the cost reduction can be accomplished. Designated by **1280b** is the flat surface portion.

(290) In addition, as shown in FIG. 28(c), the range of the free end portion **1380b** of the drive shaft **1380** is decreased. For this purpose, it is possible to make the outer diameter of the shaft free end **1380c** smaller than the outer diameter of the main part **1380a**. As described above, the free end portion **1380b** requires a certain amount of accuracy, in order to determine the position of the coupling **150**. Therefore, the spherical range is limited only to the contact portion of the coupling. By this, the portion other than the surface where accuracy of finishing is required is omitted. By this, the machining cost is lowered. In addition, similarly, it is possible to cut the free end of the unnecessary spherical surface. Designated by **1382** is a pin (the rotational force applying portion).

(291) The positioning method of the photosensitive drum **107** with respect to the direction of the axis **L1** will be described. In other words, the coupling **1550** is provided with a tapered surface (the inclined plane) **1550e**, **1550h**. And, a force is produced in the thrust direction by the rotation of the drive shaft **181**. The positioning, with respect to the direction of the axis **L1**, of the coupling **1550** and the photosensitive drum **107** is effected by this thrust force. Referring to FIG. 29 and FIG. 30, this will be described in detail. FIG. 29 is a perspective view and a top plan view of the coupling alone. FIG. 30 is an exploded perspective view which illustrates the drive shaft, the drum shaft, and the coupling.

(292) As shown in FIG. 29(b), the rotational force receiving surface **1550e** (the inclined plane) (rotational force receiving portion) is inclined by the angle $\alpha 5$ relative to the axis **L2**. When the drive shaft **180** rotates in the direction **T1**, the pin **182** and the rotational force receiving surface **1550e** contact to each other. Then, a component force is applied to the coupling **1550** in the direction **T2**, and it moves in the direction **T2**. And, the coupling **1550** moves to the axial direction until the driving shaft receiving surface **1550f** (FIG. 30a) abuts to the free end **180b** of the drive shaft **180**. By this, the position of the coupling **1550** with respect to the direction of the axis **L2** is determined. In addition, the free end **180b** of the drive shaft **180** is formed into the spherical

surface, and the receiving surface **1550f** has the conic surface. Therefore, with respect to the direction perpendicular to the axis **L2**, the position of the driven portion **1550a** relative to the drive shaft **180** is determined. In cases where the coupling **1550** is mounted to the drum **107**, the drum **107** also moves to the axial direction depending on the size of the force in which it is added in the direction **T2**. In this case, with respect to the longitudinal direction, the position of the drum **107** relative to the apparatus main assembly is determined. The drum **107** is mounted with play in the longitudinal direction thereof in the cartridge frame **B1**.

(293) As shown in FIG. **29(c)**, the rotational force transmission surface (the rotational force transmitting portion) **1550h** is inclined by the angle $\alpha 6$ relative to the axis **L2**. When the coupling **1550** rotates in the direction **T1**, the transmitting surface **1550h** and the pin **155** abut relative to each other. Then, a component force is applied to the pin **155** in the direction **T2**, and it moves in the direction **T2**. And, the drum shaft **153** moves until the free end **153b** of the drum shaft **153** contacts to the drum bearing surface **1550i** (FIG. **30(b)**) of the coupling **1550**. By this, the position of the drum shaft **155** (the photosensitive drum) with respect to the direction of the axis **L2** is determined. In addition, the drum bearing surface **1550i** has a conic surface, and the free end **153b** of the drum shaft **153** is formed into a spherical surface. Therefore, with respect to the direction perpendicular to the axis **L2**, the position of the driving portion **1550b** relative to the drum shaft **153** is determined.

(294) The taper angles $\alpha 5$ and $\alpha 6$ are set to the degree with which the force effective to move the coupling and the photosensitive drum in the thrust direction is produced. However, the forces thereof differ depending on the running torque of the photosensitive drum **107**. However, if there is provided means which is effective to determine the position in the thrust direction, the taper angles $\alpha 5$ and $\alpha 6$ may be small.

(295) As has been described hereinbefore, the taper for being drawn in the coupling in the direction of the axis **L2** and the conic surface for determining the position at the axis **L2** with respect to the orthogonality direction are provided. By this, a position with respect to the direction of the axis **L1** of the coupling and a position with respect to the direction perpendicular to the axis **L1**, are determined simultaneously. In addition, the coupling can transmit the rotational force assuredly. Furthermore, as compared with the case where the rotational force receiving surface (rotational force receiving portion) or the rotational force transmission surface (the rotational force transmitting portion) of the coupling does not have the taper angle as described above, the contact between the rotational force applying portion of the drive shaft and the rotational force receiving portion of the coupling can be stabilized. In addition, the contact abutment between the rotational force receiving portion of the drum shaft and the rotational force transmitting portion of the coupling can be stabilized.

(296) However, the tapered surface (the inclined plane) for pulling in the coupling in the direction of the axis **L2** and the conic surface for determining the position of the axis **L2** with respect to the orthogonal direction may be omitted. For example, in place of the taper for drawing in the direction of the axis **L2**, it is possible to add a part for urging the drum in the direction of the axis **L2**. Hereinafter, as long as there is no particular mentioning, the tapered surface and the conic surface are provided. In addition, the tapered surface and the conic surface are provided also in the coupling **150** described above.

(297) Referring to FIG. **31**, the regulating means for regulating the inclining direction relative to the cartridge of the coupling will be described. FIG. **31(a)** is a side view which illustrates the major part of the driving side of the process cartridge, and FIG. **31(b)** is a sectional view taken along S7-S7 of FIG. **31(a)**.

(298) In this embodiment, the coupling **150** and the drive shaft **180** of the apparatus main assembly can be more assuredly engaged by providing the regulating means.

(299) In this embodiment, as the regulating means, the regulating portions **1557h 1** or **1557h2** are provided on the drum bearing member **1557**. The coupling **150** can be regulated in swinging

directions relative to the cartridge (B) by this regulating means. The structure is such that by the time, immediately before the coupling **150** engages with the drive shaft **180**, this regulating portion **1557h 1** or **1557h2** is parallel to the mounting direction **X4** of the cartridge (B). In addition, the intervals **D6** is slightly larger than the outer diameter **D7** of the driving portion **150b** of the coupling **150**. By doing so, the coupling **150** is pivotable only to the mounting direction **X4** of the cartridge (B). In addition, the coupling **150** can be inclined in any direction relative to the drum shaft **153**. Therefore, irrespective of the phase of the drum shaft **153**, the coupling **150** can be inclined in the regulated direction. Therefore, the opening **150m** of the coupling **150** can receive the drive shaft **180** more assuredly. By this, the coupling **150** is more assuredly engageable with the drive shaft **180**.

(300) Referring to FIG. **32**, another structure for regulating the inclining direction of the coupling will be described. FIG. **32(a)** is a perspective view which illustrates the inside of the apparatus main assembly driving side, and FIG. **32(b)** is a side view of a cartridge, as seen from the upstream with respect to the mounting direction **X4**.

(301) The regulating portions **1557h 1** or **1557h2** are provided in the cartridge (B) in the above described description. In this embodiment, a part of mounting guide **1630R1** of the driving side of the apparatus main assembly (A) is a rib-like regulating portion **1630R1a**. The regulating portion **1630R1a** is the regulating means for regulating the swinging directions of the coupling **150**. And, the structure is such that, when the user inserts the cartridge (B), the outer periphery of a connecting portion **150c** of the coupling **150** contacts to the upper surface **1630R1a-1** of the regulating portion **1630R1a**. By this, the coupling **150** is guided by the upper surface **1630R1a-1**. For this reason, the inclining direction of the coupling **150** is regulated. In addition, similarly to the embodiment described above, irrespective of the phase of the drum shaft **153**, the coupling **150** is inclined in the direction in which it regulated.

(302) The regulating portion **1630R1a** is provided below the coupling **150** in the example shown in FIG. **32(a)**. However, similarly to the regulating portion **1557h2** shown in FIG. **31**, the more assured regulation can be accomplished when the regulating portion is added to the upper side.

(303) As described above, it may be combined with the structure in which the regulating portion is provided in the cartridge (B). In this case, more assured regulation can be accomplished.

(304) However, in this embodiment, by which the means for regulating the inclining direction of the coupling may be omitted for example, the coupling **150** is beforehand inclined downstream with respect to the mounting direction of the cartridge (B). And, the driving shaft receiving surface **150f** of the coupling is enlarged. By this, the engagement between the drive shaft **180** and the coupling **150** can be established.

(305) In addition, in the foregoing description, the angle in the pre-engagement angular position of the coupling **150** relative to the drum axis **L1** is larger than the angle in the disengaging angular position (FIGS. **22** and **25**). However, the present invention is not limited to such an example.

(306) Referring to FIG. **33**, the description will be made. FIG. **33** is a longitudinal sectional view which illustrates the process for taking out the cartridge (B) from the apparatus main assembly (A).

(307) In the process for taking out the cartridge (B) from the apparatus main assembly (A), the angle in the disengaging angular position (in the state FIG. **33c**) of the coupling **1750** relative to the axis **L1** may be equivalent to the angle in the pre-engagement angular position of the coupling **1750** relative to the axis **L1** at the time of the coupling **1750** engaging. Here, the process in which the coupling **1750** disengages is shown by (a)-(b)-(c)-(d) in FIG. **33**.

(308) More particularly, the setting is such that, when the upstream free end portion **1750 A3** with respect to the dismounting direction **X6** of the coupling **1750** passes by the free end portion **180b3** of the drive shaft **180**, the distance between the free end portion **1750 A3** and the free end portion **180b3** is comparable as the distance at the time of the pre-engagement angular position. With such a setting, the coupling **1750** can be disengaged from the drive shaft **180**.

(309) The other operations at the time of demounting the cartridge (B) are the same as the above

described operations, and therefore, the description is omitted.

(310) In addition, in the foregoing description, at the time of mounting the cartridge (B) to the apparatus main assembly (A), the downstream free end with respect to the mounting direction of the coupling is closer to the drum shaft than the free end of the drive shaft **180**. However, the present invention is not limited to such an example.

(311) Referring to FIG. **34**, the description will be made. FIG. **34** is a longitudinal sectional view for illustrating the mounting process of the cartridge (B). As shown in FIG. **34**, in the state of (a) the mounting process of the cartridge (B), in the direction of the axis **L1**, the downstream free end position **1850A1** with respect to the mounting direction **X4** is closer to the direction of the pin **182** (the rotational force applying portion) than the drive shaft free end **180b3**. In the state of (b), the free end position **1850A1** is contacted to the free end portion **180b**. At this time, the free end position **1850A1** moves toward the drum shaft **153** along the free end portion **180b**. And, the free end position **1850A1** passes by the free end portion **180b3** of the drive shaft **180** at this position, the coupling **150** takes the pre-engagement angular position (FIG. **34(c)**). And, finally the engagement between the coupling **1850** and the drive shaft **180** is established ((rotational force transmitting angular position) FIG. **34(d)**).

(312) An example of this embodiment will be described.

(313) First, the shaft diameter of the drum shaft **153** is $\Phi Z1$, the shaft diameter of the pin **155** is $\Phi Z2$, and the length is **Z3** (FIG. **7(a)**). The maximum outer diameter of the driven portion **150a** of the coupling **150** is $\Phi Z4$ the diameter of a phantom circle **C1** which passes the inner ends of the projections **150d 1** or **150d 2** or **150d3**, **150d4** is $\Phi Z5$, and the maximum outer diameter of the driving portion **150b** is $\Phi Z6$ (FIG. **8(d)**, **(f)**). The angle formed between the coupling **150** and the receiving surface **150f** is $\alpha 2$, and the angle formed between the coupling **150** and the receiving surface **150i** is $\alpha 1$. A shaft diameter of the drive shaft **180** is $\Phi Z7$, the shaft diameter of the pin **182** is $\Phi Z8$, and the length is **Z9** (FIG. **17(b)**). In addition, the angle relative to the axis **L1** in the rotational force transmitting angular position is $\beta 1$, the angle in the pre-engagement angular position is $\beta 2$, and the angle in the disengaging angular position is $\beta 3$. In this example, **Z1**=8 mm; **Z2**=2 mm; **Z3**=12 mm; **Z4**=15 mm; **Z5**=10 mm; **Z6**=19 mm; **Z7**=8 mm; **Z8**=2 mm; **Z9**=14 mm; $\alpha 1$ =70 degrees; $\alpha 2$ =120 degrees; $\beta 1$ =0 degree; $\beta 2$ =35 degrees; $\beta 3$ =30 degrees.

(314) It has been confirmed with these settings, the engagement between the coupling **150** and the drive shaft **180** is possible. However, these settings do not limit the present invention. In addition, the coupling **150** can transmit the rotational force to the drum **107** with high precision. The values given above are the examples, and the present invention is not limited to these values.

(315) In addition, in this embodiment, the pin (the rotational force applying portion) **182** is disposed in the range of 5 mm from the free end of the drive shaft **180**. In addition, the rotational force receiving surface (rotational force receiving surface) **150e** provided in the projection **150d** is disposed at the range of 4 mm from the free end of the coupling **150**. In this manner, the pin **182** is disposed at the free end side of the drive shaft **180** in addition, the rotational force receiving surface **150e** is disposed at the free end side of the coupling **150**.

(316) By this, at the time of mounting the cartridge (B) to the apparatus main assembly (A), the drive shaft **180** and the coupling **150** can engage smoothly with each other. In more detail, the pin **182** and the rotational force receiving surface **150e** can engage smoothly with each other.

(317) In addition, at the time of demounting the cartridge (B) from the apparatus main assembly (A), the drive shaft **180** and the coupling **150** can disengage smoothly from each other. More particularly, the pin **182** and the rotational force receiving surface **150e** can disengage smoothly from each other.

(318) The values are the examples, and the present invention is not limited to these values. However, the effects described above are further enhance (d) by the pin (rotational force applying portion) **182** and the rotational force receiving surface **150e** being disposed in these numerical value ranges.

(319) As described in the foregoing, in the described embodiment, the coupling member **150** is capable of taking the rotational force transmitting angular position for transmitting the rotational force for rotating the electrophotographic photosensitive drum to the electrophotographic photosensitive drum and the disengaging angular position in which the coupling member **150** is inclined away from the axis of the electrophotographic photosensitive drum from the rotational force transmitting angular position. When the process cartridge is dismounted from the main assembly of the electrophotographic image forming apparatus in a direction substantially perpendicular to the axis of the electrophotographic photosensitive drum, the coupling member moves from the rotational force transmitting angular position to the disengaging angular position. When the process cartridge is mounted to the main assembly of the electrophotographic image forming apparatus in a direction substantially perpendicular to the axis of the electrophotographic photosensitive drum, the coupling member moves from the disengaging angular position to the rotational force transmitting angular position. This applies to the following embodiments, although the following embodiment 2 is related with the dismounting only.

Embodiment 2

(320) Referring to FIG. 35-FIG. 40, the second embodiment to which applied the present invention will be described.

(321) In the description of this embodiment, the same reference numerals as in Embodiment 1 are assigned to the elements having the corresponding functions in this embodiment, and the detailed description thereof is omitted for simplicity. This applies also about the other embodiment described in the below.

(322) The this embodiment is effective not only for the case of the mounting and the dismounting of the cartridge (B) relative to the apparatus main assembly (A) but also the case of the dismounting only of the cartridge (B) from the apparatus main assembly (A).

(323) More particularly, when the drive shaft **180** stops, the drive shaft **180** is stopped with the predetermined phase by the control of the apparatus main assembly (A) in other words, it stops so that the pin **182** may become at a predetermined position. Moreover, the phase of the coupling **14150 (150)** is set in alignment with the phase of the stopped drive shaft **180** for example, the position of standing-by portion **14150k (150k)** is set so that it may align with the stop position of the pin **182** with such a setting, at the time of mounting the cartridge (B) to the apparatus main assembly (A), even if the coupling **14150 (150)** is not pivoted, it will become in the state of being opposed to the drive shaft **180**. And, the rotational force from the drive shaft **180** is transmitted to the coupling **14150 (150)** by the drive shaft **180** rotating. By this, the coupling **14150 (150)** can rotate with high precision.

(324) However, this embodiment is effective at the time of demounting the cartridge (B) from the apparatus main assembly (A) by moving in the direction substantially perpendicular to the direction of the axis L3. This is because even if the drive shaft **180** stops with the predetermined phase, the pin **182** and rotational force receiving surface **14150e1, 14150e2 (150e)** are in engagement relative to each other. For this reason, in order to disengage the coupling **14150 (150)** from the drive shaft **180**, the coupling **14150 (150)** needs to pivot.

(325) In addition, in the embodiment 1 described above, at the time of mounting the cartridge (B) to the apparatus main assembly (A) and at the time of demounting it, the coupling **14150 (150)** pivots. Therefore, the control of the apparatus main assembly (A) described above is unnecessary, and, at the time of mounting the cartridge (B) to the apparatus main assembly (A), it is not necessary to set the phase of the coupling **14150 (150)** in accordance with the phase of the stopped drive shaft **180** beforehand.

(326) The description will be made referring to the drawing.

(327) FIG. 35 is a perspective view which illustrates the phase control means for the drive shaft, the driving gear, and the drive shaft of the apparatus main assembly. FIG. 36 is a perspective view and a top plan view of the coupling. FIG. 37 is a perspective view which illustrates the mounting

operation of the cartridge. FIG. 38 is a top plan view, as seen from the direction of the mounting direction at the time of the cartridge mounting. FIG. 39 is a perspective view which illustrates in the state of the drive stop of the cartridge (the photosensitive drum). FIG. 40 is a longitudinal sectional view and a perspective view which illustrate the operation for taking out the cartridge.

(328) In this embodiment, the description will be made about the cartridge detachably mountable to apparatus main assembly (A) provided with the control means (unshown) which can control the phase of the stop position of the pin 182. The one end side (an unshown photosensitive drum 107 side) of the drive shaft 180 is the same as that of the first embodiment, as shown in FIG. 35(a), and therefore, the description is omitted. On the other hand, as shown in FIG. 35(b), the other end side (the opposite side of the unshown photosensitive drum 107 side) is provided with a flag 14195 projected from the drive shaft 180 outer periphery of the drive shaft 180. And, the flag 14195 passes through the photo-interrupter 14196 fixed to the apparatus main assembly (A) by the rotation thereof. And, a control means (unshown) effects the control, so that after the rotation (for example, image forming rotation) of the drive shaft 180, when the flag 14195 interrupts the photo-interrupter 14196 first, a motor 186 stops. By this, the pin 182 stops at a predetermined position relative to the rotation axis of the drive shaft 180. As for the motor 186, in the case of this embodiment, it is desirably a stepping motor with which the positioning control is easy.

(329) Referring to FIG. 36, the coupling used in this embodiment will be described.

(330) The coupling 14150 mainly comprises three portions. As shown in FIG. 36(c), they are a driven portion 14150a for receiving the rotational force from the drive shaft 180, a driving portion 14150b for transmitting the rotational force to the drum shaft 153, and a connecting portion 14150c which connects the driven portion 14150a and the driving portion 14150b with each other.

(331) The driven portion 14150a has a drive shaft inserting portion 14150m constituted by 2 surfaces which expand in a direction away from an axis L2. In addition, the driving portion 14150b has a drum shaft inserting portion 14150v constituted in the two surfaces which expand away from the axis L2.

(332) The inserting portion 14150m has a tapered driving shaft receiving surfaces 14150f 1 or 14150f2. And, each end surface is provided with a projection 14150d 1 or 14150d2. The projections 14150d 1 or 14150d2 are disposed on a circumference about the axis L2 of the coupling 14150. The receiving surfaces 14150f 1, 14150f2 constitute a recess 14150z, as shown in the Figure. In addition, as shown in FIG. 36(d), the downstream of the projection 14150d 1, 14150d2 with respect to the clockwise direction is provided with a rotational force receiving surface (rotational force receiving portion) 14150e (14150e1, 14150e2). A pin (rotational force applying portion) 182 abuts to this receiving surface 14150e1, 14150e2. By this, the rotational force is transmitted to the coupling 14150. An interval (W) between the adjacent projections 14150d1-d2 is larger than the outer diameter of the pin 182, in order to permit the entrance of the pin 182. This interval is the standing-by portions 14150k.

(333) In addition, the inserting portion 14150v is constituted by the two surfaces 14150i1, 14150i2. And, the standby openings 14150g 1 or 14150g2 are provided in these surfaces 14150i1, 14150i2 (the FIG. 36a FIG. 36e). In addition, in FIG. 36(e), at the upstream of the openings 14150g 1 or 14150g2 with respect to the clockwise direction, a rotational force transmission surface (rotational force transmitting portion) 14150h (14150h 1 or 14150h2) is provided. And, as described above, the pin (the rotational force receiving portion) 155a contacts with the rotational force transmission surfaces 14150h 1 or 14150h2. By this, the rotational force is transmitted to the photosensitive drum 107 from the coupling 14150.

(334) With the shape of coupling 1415, the coupling is over the free end of the driving shaft in the state that the cartridge is mounted to the main assembly of the apparatus.

(335) And, with the similar structure as the structure described by the first embodiment, the coupling 14150 can be inclined in any direction relative to the drum shaft 153.

(336) Referring to FIG. 37 and FIG. 38, a mounting operation of the coupling will be described.

FIG. 37(a) is a perspective view which illustrates the state before the coupling is mounted. FIG. 37 (b) is a perspective view which illustrates the state where the coupling engaged. FIG. 38(a) is a top plan view thereof, as seen from the mounting direction. FIG. 38(b) is a top plan view thereof, as seen from the top relative to the mounting direction.

(337) An axis L3 of the pin (rotational force applying portion) 182 is parallel to the mounting direction X4 by the control means described above. In addition, as to the cartridge, the phase aligns so that the receiving surfaces 14150f1 and 14150f2 are opposite from each other in the direction perpendicular to the mounting direction X4 (FIG. 37(a)). As a structure for aligning the phase, any one side of the receiving surfaces 14150f1 or 14150f2 is aligned with a mark 14157z provided on the bearing member 14157, as shown in the Figure, for example. This is carried out before shipping the cartridge from the plant. However, the user may carry out, before mounting the cartridge (B) to the apparatus main assembly. In addition, other phase adjusting means may be used. By doing so, the coupling 14150 and the drive shaft 180 (the pin 182) are not interfered with each other with respect to the mounting direction, as shown in FIG. 38(a), in the positional relation. Therefore, the coupling 14150 and the drive shaft 180 are engageable without the problem (FIG. 37(b)). And, the drive shaft 180 rotates in the direction X8, so that the pin 182 contacts to the receiving surface 14150e1, 14150e2. By this, the rotational force is transmitted to the photosensitive drum 107.

(338) Referring to FIG. 39 and FIG. 40, the description will be made as to the operation in which the coupling 14150 disengages from the drive shaft 180 in interrelation with the operation for taking out the cartridge (B) from the apparatus main assembly (A). The phase of the pin 182 relative to the drive shaft 180 stops at the predetermined position by the control means. As described above, when the easiness of the mounting of the cartridge (B) is considered, it is desirable for the pin 182 to stop with the phase parallel to the cartridge dismounting direction X6 (FIG. 39b). The operation at the time of taking out the cartridge (B) is illustrated in FIG. 40. In this state (FIG. 40(a1) and (b1)), the coupling 14150 takes the rotational force transmitting angular position and the axis L2 and the axis L1 are substantially co-axial with each other. At this time, similarly to the case of mounting the cartridge (B), the coupling 14150 can be inclined in any direction relative to the drum shaft 153 (FIG. 40 a1, FIG. 40 b1). Therefore, the axis L2 inclines in the direction opposite from the dismounting direction relative to the axis L1 in interrelation with the dismounting operation of the cartridge (B). More particularly, the cartridge (B) is demounted in the direction (the direction of the arrow X6) substantially perpendicular to the axis L3. And, in the dismounting process of the cartridge, the axis L2 is inclined until the free end 14150 A3 of the coupling 14150 becomes along the free end 180b of the drive shaft 180 (the disengaging angular position). Or, it is inclined until the axis L2 comes to the drum shaft 153 side with respect to the free end portion 180b3 (FIG. 40(a2), FIG. 40(b2)). In this state, the coupling 14150 is passed by near the free end portion 180b3. By doing so, the coupling 14150 is demounted from the drive shaft 180.

(339) In addition, as shown in FIG. 39 (a), the axis of the pin 182 may stop in the state perpendicular to the cartridge dismounting direction X6. The pin 182 usually stops at the position shown in FIG. 39 (b) by the control of the control means. However, the voltage source of the device (the printer) may become OFF and the control means may not work. The pin 182 may stop at the position as shown in FIG. 39 (a) in such a case. However, even in such a case, the axis L2 is inclined relative to the axis L1 similarly to the above described case, and the removal operation is possible. When the device is in the state of the drive stop, the pin 182 is in the downstream beyond the projection 14150d2 with respect to the dismounting direction X6. Therefore, the free end 14150 A3 of the projection 14150d1 of the coupling passes the drum shaft 153 side beyond the pin 182 by the axis L2 inclining. By this, the coupling 14150 is demounted from the drive shaft 180.

(340) As has been described hereinbefore, even if it is the case where the coupling 14150 is engaged relative to the drive shaft 180 by a certain method on the occasion of the mounting of the cartridge (B) the axis L2 inclines relative to the axis L1 in the case of the dismounting operation.

By this, the coupling **14150** can be demounted from the drive shaft **180** only by such dismounting operation.

(341) As has been described hereinbefore, according to this embodiment 2, this embodiment is effective even for the case of demounting the cartridge from the main assembly of the apparatus, in addition to the case of mounting and demounting the cartridge (B) relative to the apparatus main assembly (A).

Embodiment 3

(342) Referring to FIG. **41**-FIG. **45**, a third embodiment will be described.

(343) FIG. **41** is a sectional view which illustrates a state where a door of an apparatus main assembly A is open. FIG. **42** is a perspective view which illustrates a mounting guide. FIG. **43** is the enlarged view of a driving side surface of the cartridge. FIG. **44** is a perspective view, as seen from a driving side, of the cartridge. FIG. **45** shows a view which illustrates a state of inserting the cartridge into an apparatus main assembly.

(344) In this embodiment, for example, as in the case of the clamshell type image forming device, the cartridge is mounted downwardly. A typical clamshell type image forming apparatus is shown in FIG. **41**. The apparatus main assembly A2 comprises a lower casing D2 and an upper casing E2. And, the upper casing E2 is provided with a door **2109** and an inside exposure device **2101** of the door **2109**. Therefore, when the upper casing E2 is opened upward, the exposure device **2101** retracts. And, an upper portion of the cartridge set portion **2130a** is opened. When the user mounts the cartridge B-2 to a set portion **2130a**, the user drops the cartridge B-2 on X4B downward. The mounting completes with this, and therefore, the mounting of the cartridge is easy. In addition, the jam clearance operation of the adjacent a fixing device **105** can effect from the device upper portion. Therefore, it excels in the easiness of the jam clearance. Here, the jam clearance is the operation for a removing a recording material **102** jammed in the course of the feeding.

(345) More specifically, the set portion for the cartridge B-2 will be described. As shown in FIG. **42**, the image forming device A2 is provided with a mounting guide **2130R** in a driving side, and is provided with a mounting guide unshown in a non-driving side opposed to it As mounting means **2130**. The set portion **2130a** is formed as the space surrounded by the guides to oppose. The rotational force is transmitted to the coupling **150** of the cartridge B-2 provided at this set portion **2130a** from the apparatus main assembly A.

(346) The mounting guide **2130R** is provided with a groove **2130b** which extends in the perpendicular direction substantially. In addition, an abutting portion **2130Ra** for determining the cartridge B-2 at the predetermined position is provided in the lowermost portion thereof. In addition, a drive shaft **180** projects from the groove **2130b**. In the state where the cartridge B-2 is positioned in the predetermined position, the drive shaft **180** transmits the rotational force to the coupling **150** from the apparatus main assembly A. In addition, in order to position the cartridge B-2 in the predetermined position assuredly, an urging spring **2188R** is provided in the lower part of the mounting guide **2130R**. By the structure described above, the cartridge B-2 is positioned in the set portion **2130a**.

(347) As shown in FIG. **43** and FIG. **44**, the cartridge B-2 is provided with the cartridge side mounting guides **2140R1** and **2140R2**. The orientation of the cartridge B-2 is stabilized by this guide at the time of the mounting. And, the mounting guide **2140R1** is integrally formed on the drum bearing member **2157**. In addition, the mounting guide **2140R2** is provided substantially above the mounting guide **2140R1**. And, the guide **2140R2** is provided in the second frame **2118**, and it is in the form of a rib.

(348) The mounting guides **2140R1**, **2140R2** of the cartridge B-2 and the mounting guide **2130R** of the apparatus main assembly A2 have the structures described above. More particularly, it is the same as that of the structure of the guide which has been described in conjunction with FIGS. **2** and **3**. In addition, the structure of the guide of the other end is also the same. Therefore, the cartridge B-2 is mounted while being moved to the apparatus main assembly A2 in the direction substantially

perpendicular to the direction of the axis L3 of the drive shaft **180**, and, in addition, it is similarly demounted from the apparatus main assembly A2.

(349) As shown in FIG. **45**, at the time of mounting the cartridge B-2, the upper casing E2 is clockwise rotated about a shaft **2109a** and, the user brings the cartridge B-2 to the upper portion of the lower casing D2. At this time, the coupling **150** is inclined downwardly by the weight FIG. **43**. In other words, the axis L2 of the coupling inclines relative to the drum axis L1 so that the driven portion **150a** of the coupling **150** may face down the pre-engagement angular position.

(350) In addition, as has been described with respect to Embodiment 1, FIGS. **9** and **12**, it is desirable to provide the semi-circular retention rib **2157e** FIG. **43**. In this embodiment, the mounting direction of the cartridge B-2 is downward. Therefore, the rib **2157e** is disposed in the lower part. By this, as has been described with respect to Embodiment 1, the axis L1 and the axis L2 are pivotable relative to each other, and the retention of the coupling **150** is accomplished. The retention rib prevents the coupling **150** from separating from the cartridge B-2. When the coupling **150** is mounted to the photosensitive drum **107**, it is preventing separation from the photosensitive drum **107k**.

(351) In this state, as shown in FIG. **45**, the user lowers the cartridge B-2 downwardly, aligning the mounting guides **2140R1**, **2140R2** of the cartridge B-2 with the mounting guides **2130R** of the apparatus main assembly A2. The cartridge B-2 can be mounted to the set portion **2130a** of the apparatus main assembly A2 only by this operation. In this mounting process, similarly to Embodiment 1, FIG. **22**, the coupling **150** can be engaged with the drive shaft **180** of the apparatus main assembly (the coupling takes the rotational force transmitting angular position in this state). More particularly, by moving in cartridge B-2 in the direction substantially perpendicular to the direction of the axis L3 of the drive shaft **180**, the coupling **150** is engaged with the drive shaft **180**. In addition, at the time of demounting the cartridge, similarly to Embodiment 1, the coupling **150** can be disengaged from the drive shaft **180** only by the operation which demounts the cartridge (the coupling moves to the disengaging angular position from the rotational force transmitting angular position, FIG. **25**). More particularly, by moving the cartridge B-2 in the direction substantially perpendicular to the direction of the axis L3 of the drive shaft **180**, the coupling **150** is disengaged from the drive shaft **180**.

(352) As has been described hereinbefore, since the coupling inclines downwardly by the weight when downwardly mounting the cartridge to the apparatus main assembly, it can engage with the drive shaft of the apparatus main assembly assuredly.

(353) In this embodiment, the clamshell type image forming device has been described. However, the present invention is not limited to such an example. For example, the present embodiment can be applied if the mounting direction of the cartridge is downward. In addition, the mounting path thereof is not limited to straight downward. For example, it may be inclined downward in initial mounting stage of the cartridge, and it may become downward finally. The present embodiment is effective if the mounting path immediately before reaching the predetermined position (the cartridge set portion) is downward.

Embodiment 4

(354) Referring to FIG. **46**-FIG. **49**, the fourth embodiment of the present invention will be described.

(355) In this embodiment, means to maintain the axis L2 at the inclined state relative to the axis L1 will be described.

(356) Only the member relating to the description of this portion of the present embodiment is shown in the drawing, and the other members are omitted. It is similar also in the other embodiments as will be described hereinafter.

(357) FIG. **46** is a perspective view which illustrates a coupling locking member (this is peculiar to the present embodiment) pasted on the drum bearing member. FIG. **47** is an exploded perspective view which illustrates the drum bearing member, the coupling, and the drum shaft. FIG. **48** is an

enlarged perspective view of a major part of the driving side of the cartridge. FIG. 49 is a perspective view and a longitudinal sectional view which illustrate an engaged state between the drive shaft and the coupling.

(358) As shown in FIG. 46, the drum bearing member 3157 has a space 3157b which surrounds a part of coupling. A coupling locking member 3159 as a maintaining member for maintaining the inclination of the coupling 3150 is pasted on a cylinder surface 3157i which constitutes the space thereof. As will be described hereinafter, this locking member 3159 is a member for maintaining temporarily the state where the axis L2 inclines relative to the axis L1. In other words, as shown in FIG. 48, the flange portion 3150j of the coupling 3150 contacts to this locking member 3159. By this, the axis L2 maintains the state of inclining toward the downstream with respect to the mounting direction (X4) of the cartridge relative to the axis L1 (FIG. 49(a1)). Therefore, as shown in FIG. 46, the locking member 3159 is disposed on the upstream cylinder surface 3157i of the bearing member 3157 with respect to the mounting direction X4. As the material of the locking member 3159, the material which has a relatively high coefficient of friction, such as the rubber and the elastomer, or the elastic materials, such as the sponge and the flat spring, are suitable. This is because, the inclination of the axis L2 can be maintained by the frictional force, the elastic force, and so on. In addition, similarly to Embodiment 1 (it illustrates in FIG. 31), the bearing member 3157 is provided with the inclining direction regulation rib 3157h. The inclining direction of the coupling 3150 can be assuredly determined by this rib 3157h. In addition, the flange portion 3150j and the locking member 3159 can contact relative to each other more assuredly. Referring to FIG. 47, the assembly method of the coupling 3150 will be described. As shown in FIG. 47, the pin (rotational force receiving portion) 155 enters the standing-by space 3150g of the coupling 3150. In addition, a part of coupling 3150 is inserted into the space portion 3157b which the drum bearing member 3157 has. At this time, preferably, a distance D12 between an inner surface end of the rib 3157e and the locking member 3159 is set, so that it is larger than maximum outer diameter of the driven portion 3150a $\Phi D10$. In addition, the distance D12 is set so that it is smaller than the maximum outer diameter of the driving portion 3150b $\Phi D11$. By this, the bearing member 3157 can be assembled straight. Therefore, the assembling property is improved. However, the present embodiment is not limited to this relation.

(359) Referring to FIG. 49, the engaging operation (a part of mounting operation of the cartridge) for engaging the coupling 3150 with the drive shaft 180 will be described. FIGS. 49(a1) and (b1) illustrate the state immediately before the engagement, and FIGS. 49(a2) and (b2) illustrate the state of the completion of the engagement.

(360) As shown in FIG. 49(a1) and FIG. 49(b1), the axis L2 of the coupling 3150 inclines toward the downstream with respect to the mounting direction X4 relative to the axis L1 beforehand by the force of the locking member 3159 (pre-engagement angular position). By this inclination of the coupling 3150, by, in the direction of the axis L1, the downstream (with respect to the mounting direction) free end portion 3150A1 is closer to the photosensitive drum 107 direction side than the drive shaft free end 180b3. And, the upstream (with respect to the mounting direction) free end portion 3150A2 is closer to the pin 182 than the free end 180b3 of the drive shaft 180 in addition, at this time, as has been described in the foregoing, the flange portion 3150j is contacted to the locking member 3159. And, the inclined state of the axis L2 is maintained by the frictional force thereof.

(361) Thereafter, the cartridge B moves to the mounting direction X4. By this, the free end surface 180b or the free end of the pin 182 contacts to the driving shaft receiving surface 3150f of the coupling 3150. And, the axis L2 approaches to the direction in parallel with the axis L1 by the contact force (mounting force of the cartridge) thereof. At this time, the flange portion 3150j is departed from the locking member 3159, and becomes into the non-contact state. And, finally, the axis L1 and the axis L2 are substantially co-axial with each other. And, the coupling 3150 is in the waiting (stand-by) state for transmitting the rotational force (FIG. 49(a2), (b2)). (rotational force

transmitting angular position).

(362) Similarly to Embodiment 1, from the motor **186**, the rotational force is transmitted through the drive shaft **180** to the coupling **3150**, the pin (rotational force receiving portion) **155**, the drum shaft **153**, and the photosensitive drum **107**. The axis **L2** is substantially co-axial with the axis **L1** at the time of the rotation. Therefore, the locking member **3159** is not in contact with the coupling **3150**. Therefore, the locking member **3159** does not affect the rotation of the coupling **3150**.

(363) In addition, the operations follow the step similar to Embodiment 1 in the process in which the cartridge B is taken out from the apparatus main assembly A (FIG. 25). In other words, the free end portion **180b** of the drive shaft **180** pushes the driving shaft receiving surface **3150f** of the coupling **3150**. By this, the axis **L2** inclines relative to the axis **L1**, and the flange portion **3150j** is brought into contact to the locking member **3159**. By this, the inclined state of the coupling **3150** is maintained again. In other words, the coupling **3150** moves to the pre-engagement angular position from the rotational force transmitting angular position.

(364) As has been described hereinbefore, the inclined state of the axis **L2** is maintained by the locking member **3159** (maintaining member). By this, the coupling **3150** can be more assuredly engaged with the drive shaft **180**.

(365) In this embodiment, the locking member **3159** is pasted on the upstreammost portion, with respect to cartridge mounting direction **X4**, of the inner surface **3157i** of the bearing member **3157**. However, the present invention is not limited to this example. For example, when the axis **L2** inclines, any position which can maintain the inclined state thereof is usable.

(366) In addition, in this embodiment, the locking member **3159** is contacted to the flange portion **3150j** provided in the driving portion **3150b** (FIG. 49(b1)) side. However, the contact position may be the driven portion **3150a**.

(367) In addition, the locking member **3159** used in this embodiment is a separate member in the bearing member **3157**. However, the present embodiment is not limited to this example. For example, the locking member **3159** may be integrally molded with the bearing member **3157** (for example, two-color molding). Or, the bearing member **3157** may be directly contacted to the coupling **3150** in place of the locking member **3159**. Or the surface thereof may be roughened for the purpose of raising the coefficient of friction.

(368) In addition, in this embodiment, the locking member **3159** is pasted on the bearing member **3157**. However, if the locking member **3159** is the member fixed to the cartridge B, it may be pasted on any position.

Embodiment 5

(369) Referring to FIG. 50-FIG. 53, the fifth embodiment of the present invention will be described.

(370) In the present embodiment, another means for maintaining in the state of inclining the axis **L2** relative to the axis **L1** will be described.

(371) FIG. 50 is an exploded perspective view of the coupling urging member (it is peculiar to the present embodiment) mounted to the drum bearing member. FIG. 51 is an exploded perspective view which illustrates the drum bearing member, the coupling, and the drum shaft. FIG. 52 is an enlarged perspective view of a major part of the driving side of the cartridge. FIG. 53 is a perspective view and a longitudinal sectional view which illustrate the drive shaft and the engaged state between the coupling.

(372) As shown in FIG. 50, a retaining hole **4157j** is provided in the retention rib **4157e** of the drum bearing member **4157**. A coupling urging members **4159a**, **4159b** as a maintaining member for maintaining the inclination of the coupling **4150** in the retaining hole **4157j** thereof are mounted. The urging members **4159a**, **4159b** urge the coupling **4150**, so that the axis **L2** inclines toward the downstream with respect to the mounting direction of the cartridge B-2 relative to the axis **L1**. Each urging member **4159a**, **4159b** is a coiled compression spring (elastic material). As shown in FIG. 51, the urging members **4159a**, **4159b** urge the flange portion **4150j** of the coupling

4150 toward the axis **L1** (arrow of **FIG. 51** an **X13**). The contact position where the urging members contact with the flange portion **4150j** is the downstream of the center of the drum shaft **153** with respect to the cartridge mounting direction **X4**. Therefore, as for the axis **L2**, the driven portion **4150a** side inclines toward the downstream with respect to the mounting direction (**X4**) of the cartridge relative to the axis **L1** by the elastic force by the urging member **4159a**, **4159b** (**FIG. 52**).

(373) In addition, as shown in **FIG. 50**, the coupling side free end of each urging member **4159a**, **4159b** which is the coil spring is provided with a contact member **4160a**, **4160b**. The contact member **4160a**, **4160b** contacts the flange portion **4150j**. Therefore, the material of the contact member **4160a**, **4160b** is preferably material of the high slidability. In addition, by using such the material, as will be described hereinafter, at the time of the rotational force transmission, the influence to the rotation of the coupling **4150** of an urging force by the urging member **4159a**, **4159b** is lessened. However, if the load relative to the rotation is sufficiently small, and the coupling **4150** satisfactorily rotates, the contact members **4160a**, **4160b** is not be inevitable).

(374) In the present embodiment, two urging members are provided. However, if the axis **L2** can incline toward the downstream with respect to the mounting direction of the cartridge relative to the axis **L1**, the number of the urging members may be any. For example, in the case of the single urging member, as for the energizing position, it is desirably the downstreammost position with respect to the mounting direction **X4** of the cartridge. By this, the coupling **4150** can be stably inclined toward the downstream with respect to the mounting direction.

(375) In addition, the urging member is a compression coil spring in the present embodiment. However, as the urging member, if an elastic force can be produced as with the flat spring, the torsion spring, the rubber, the sponge, and so on, it may be any. However, in order to incline the axis **L2**, a certain amount of stroke is required. Therefore, as with the coil spring etc, it is desirable that the stroke can be provided.

(376) Referring to **FIG. 51**, the description will be made about the mounting method of the coupling **4150**.

(377) As shown in **FIG. 51**, the pin **155** enters the standing-by space **4150g** of the coupling **4150**. And, a part of coupling **4150** is inserted into the space **4157b** of the drum bearing member **4157**. At this time, as has been described hereinbefore, the urging members **4159a**, **4159b** push the flange portion **4157j** onto the predetermined position through the contact member **4160a**, **4160b**. The screw (**4158a** of **FIG. 52**, **4158b**) is threaded into the hole **4157g 1** or **4157g2** provided in the bearing member **4157**, by which, the bearing member **4157** is fixed to the second frame **118**. By this, the urging force to the coupling **4150** by the urging member **4159a**, **4159b** can be assured. And, the axis **L2** is inclined relative to the axis **L1** (**FIG. 52**).

(378) Referring to **FIG. 53**, the operation (a part of mounting operation of the cartridge) of engaging the coupling **4150** with the drive shaft **180** will be described. **FIGS. 53(a1)** and **(b1)** illustrate the state immediately before the engagement, **FIGS. 53(a2)** and **(b2)** illustrate the state of the engagement completion, and **FIG. 53(c1)** illustrates the state therebetween.

(379) In **FIGS. 53(a1)** and **(b1)**, the axis **L2** of the coupling **4150** inclines toward the mounting direction **X4** relative to the axis **L1** beforehand (pre-engagement angular position). By the coupling **4150** inclining, the downstream free end position **4150A1** with respect to the direction of the axis **L1** is closer to the photosensitive drum **107** than the free end **180b3**. In addition, the free end position **4150A2** is closer to the pin **182** than the free end **180b3**. In other words, as has been described hereinbefore, the flange portion **4150j** of the coupling **4150** is pressed by the urging member **4159**. Therefore, the axis **L2** is inclined relative to the axis **L1** by the urging force thereof.

(380) Thereafter, by the cartridge **B** moving to the mounting direction **X4**, the free end surface **180b** or the free end (the main assembly side engaging portion) of the pin (rotational force applying portion) **182** is brought into contact to the driving shaft receiving surface **4150f** or the projection **4150d** of the coupling **4150** (the cartridge side contact portion). **FIG. 53(c1)** illustrates the state

where the pin **182** is in contact with the receiving surface **4150f**. And, the axis **L2** approaches toward the direction in parallel with the axis **L1** by the contact force (mounting force of the cartridge). Simultaneously, the pressing portion **4150j1** pressed by the elastic force of the spring **4159** provided in the flange portion **4150j** moves in the compression direction of the spring **4159**. And, finally, the axis **L1** and the axis **L2** becomes co-axial. And, the coupling **4150** takes the standby position for effecting the transmission of the rotational force (Figure (rotational force transmitting angular position) **53 (a2, b2)**)).

(381) Similarly to Embodiment 1, the rotational force is transmitted to the coupling **4150**, the pin **155**, the drum shaft **153**, and the photosensitive drum **107** through the drive shaft **180** from the motor **186**. The urging force of the urging member **4159** act on the coupling **4150** at the time of the rotation. However, as has been described hereinbefore, the urging force of the urging member **4159** act to the coupling **4150** through the contact member **4160**. Therefore, the coupling **4150** can be rotated without high load. In addition, the contact member **4160** may not be provided if the driving torque of the motor **186** is sufficiently large. In this case, even if the contact member **4160** is not provided, the coupling **4150** can transmit the rotational force with high precision.

(382) In addition, in the process in which the cartridge B is demounted from the apparatus main assembly A, the step opposite from the step to mount is followed. In other words, the coupling **4150** is normally urged to the downstream with respect to the mounting direction **X4** by the urging member **4159**. Therefore, in the dismounting process of the cartridge B, the receiving surface **4150f** is in contact with the free end portion **182A** of the pin **182** in the upstream side with respect to the mounting direction **X4** (FIG. **53(c1)**)). In addition, a gap **n50** is necessarily provided between the free end **180b** of the transmitting surface **4150f** and the drive shaft **180** in the downstream with respect to the mounting direction **X4**. In the above-described embodiments, in the dismounting process of the cartridge, the receiving surface **150f** or the projection **150d** in the downstream with respect to the mounting direction **X4** of the coupling has been described as contacting to the free end portion **180b** of the drive shaft **180** at least (for example, FIG. **25**). However, as in the present embodiment, the receiving surface **150f** or the projection **4150d** in the downstream with respect to the mounting direction **X4** of the coupling does not contact to the free end portion **180b** of the drive shaft **180**, but corresponding to the dismounting operation of the cartridge B, the coupling **4150** can separate from the drive shaft **180**. And, even after the coupling **4150** departs from the drive shaft **180**, by the urging force of the urging member **4159**, the axis **L2** inclines toward the downstream with respect to the mounting direction **X4** relative to the axis **L1** (disengaging angular position). More particularly, in this embodiment, the angle of the pre-engagement angular position and the angle of the disengaging angular position relative to the axis **L1** are equivalent relative to each other. This is because the coupling **4150** is urged by the elastic force of the spring.

(383) In addition, the urging member **4159** has the function of inclining the axis **L2**, and it further has the function of regulating the inclining direction of the coupling **4150**. More particularly, the urging member **4159** functions also as the regulating means for regulating the inclining direction of the coupling **4150**.

(384) As has been described hereinbefore, in this embodiment, the coupling **4150** is urged by the elastic force of the urging member **4159** provided in the bearing member **4157**. By this, the axis **L2** is inclined relative to the axis **L1**. Therefore, the inclined state of the coupling **4150** is maintained. Therefore, the coupling **4150** can be assuredly engaged with the drive shaft **180**.

(385) The urging member **4159** described in this embodiment is provided in the rib **4157e** of the bearing member **4157**. However, the present embodiment is not limited to such an example. For example, it may be another portion of the bearing member **4157** and may be any member fixed to the cartridge B (other than the bearing member).

(386) In addition, in this embodiment, the urging direction of the urging member **4159** is the direction of the axis **L1**. However, the urging direction may be any direction if the axis **L2** inclines toward the downstream with respect to the mounting direction **X4** of the cartridge B.

(387) In addition, in order to incline the coupling **4150** more assuredly toward the downstream with respect to the mounting direction of the cartridge B, a regulating portion for regulating the inclining direction of the coupling may be provided in the process cartridge (FIG. **31**).

(388) In addition, in this embodiment, the energizing position of the urging member **4159** is at the flange portion **4150j**. However, the position of the coupling may be any if the axis **L2** is inclined toward the downstream with respect to the mounting direction of the cartridge.

(389) In addition, the present embodiment may be implemented in combination with Embodiment 4. In this case, the mounting and dismounting operation of the coupling can further be ensured. Embodiment 6

(390) Referring to FIG. **54**-FIG. **58**, the sixth embodiment of the present invention will be described. In this embodiment, another means to maintain the state where the axis **L1** is inclined relative to the axis **L1** will be described.

(391) FIG. **54** is an exploded perspective view of the process cartridge of this embodiment. FIG. **55** is an enlarged side view of the driving side of the cartridge. FIG. **56** is a schematic longitudinal sectional view of the drum shaft, the coupling, and the bearing member. FIG. **57** is a longitudinal sectional view which illustrates the operation which mounts the coupling relative to the drive shaft. FIG. **58** is a sectional view which illustrates a modified example of a coupling locking member.

(392) As shown in FIG. **54** and FIG. **56**, the drum bearing member **5157** is provided with a coupling locking member **5157k**. At the time of assembling the bearing member **5157** in the direction of the axis **L1**, a part of a locking surface **5157k1** of the locking member **5157k** engages with the upper surface **5150j1** of a flange portion **5150j**, while contacting to the inclined surface **5150m** of the coupling **5150**. At this time, the flange portion **5150j** is supported with the play (angle α **49**), in the rotational direction, between locking surface **5157k1** of the locking portion **5157k**, and circular column portion of the drum shaft **153 153a**. The following effects are provided by providing this play (angle α **49**). More particularly, even if the dimensions of the coupling **5150**, the bearing member **5157**, and the drum shaft **153** vary within the limits of the tolerance thereof, an upper surface **5150j1** can be locked assuredly in a lock face **5157k1**.

(393) And, as shown in FIG. **56(a)**, as for the axis **L2**, the driven portion **5150a** side relative to the axis **L1** inclines toward the downstream with respect to the mounting direction (**X4**) of the cartridge. In addition, since the flange portion **5150j** exists over the full-circumference, it can retain irrespective of the phase of the coupling **5150**. Furthermore, as has been described with respect to Embodiment 1, the coupling **5150** can be inclined only in the mounting direction **X4** by the regulating portion **5157h 1** or **5157h2** (FIG. **55**) as the regulating means. In addition, in this embodiment, the coupling locking member **5157k** is provided in the downstreammost side with respect to the mounting direction (**X4**) of the cartridge.

(394) As will be described hereinafter, in the state where the coupling **5150** is in engagement the drive shaft **180**, the flange portion **5150j** is released from the locking member **5157k** as shown in FIG. **56(b)**. And, the coupling **5150** is free from the locking member **5157k**. When it is not able to retain the state of inclining the coupling **5150** in the case of the assembling of the bearing member **5157**, the driven portion **5150a** of the coupling is pushed by tool and so on (FIG. **56(b)**, arrow **X14**). By doing so, the coupling **5150** can be easily returned to the inclined holding state (FIG. **56(a)**).

(395) In addition, the rib **5157m** is provided in order to protect from the user touching on the coupling easily. The rib **5157m** is set to the substantially same height as the free end position in the inclined state of the coupling (FIG. **56(a)**). Referring to FIG. **57**, the operation (a part of mounting operation of the cartridge) for engaging the coupling **5150** with the drive shaft **180** will be described. In FIG. **57**, (a) illustrates the state of the coupling immediately before engaging, (b) illustrates the state after a part of coupling **5150** passes the drive shaft **180**, (c) illustrates the state where the inclination of the coupling **5150** is released by the drive shaft **180**, and (d) illustrates the engaged state.

(396) In the states of (a) and (b), the axis L2 of the coupling **5150** inclines toward the mounting direction X4 relative to the axis L1 beforehand (pre-engagement angular position). By the coupling **5150** inclining, the free end position **5150A1** is closer to the photosensitive drum than the free end **180b3** in the direction of the axis L1. In addition, the free end position **5150A2** is closer to the pin **182** than the free end **180b3**. In addition, as has been described hereinbefore, at this time, the flange portion **5150j** is in contact with the locking surface **5157k1**, and the inclined state of the coupling **5150** is maintained.

(397) Thereafter, as shown in (c), the receiving surface **5150f** or the projection **5150d** contacts to the free end portion **180b** or the pin **182** by the cartridge B moving to the mounting direction X4. The flange portion **5150j** separates from the locking surface **5157kl** by the contact force thereof. And, the lock relative to the bearing member **5157** of the coupling **5150** is released. And, in response to the cartridge mounting operation, the coupling is inclined so that the axis L2 thereof becomes substantially co-axial with the axis L1. After the flange portion **5150j** passes, the locking member **5157k** returns to the previous position by restoring force. At this time, the coupling **5150** is free from the locking member **5157k**. And, finally, as shown in (d), the axis L1 and the axis L2 become substantially co-axial, and the rotation stand-by state is established (rotational force transmitting angular position).

(398) In addition, the step similar to Embodiment 1 is followed in the process in which the cartridge B is demounted from the apparatus main assembly A (FIG. 25). More particularly, the coupling **5150** is changed in the order of (d), (c), (b), and (a) by the movement in the dismounting direction X6 of the cartridge. First, the free end portion **180b** pushes the receiving surface **5150f** (the cartridge side contact portion). By this, the axis L2 inclines relative to the axis L1, and the lower surface **5150j2** of the flange portion begins to contact to the inclined surface **5157k2** of the locking member **5157k**. And, an elastic portion **5157k3** of the locking member **5157k** bends, and a locking surface free end **5157k4** departs from the inclining locus of the flange portion **5150j** (FIG. 57 (c)). Furthermore, the flange portion **5150j** and the locking surface **5157kl** contact relative to each other as the cartridge advances in the dismounting direction (X6). By this, the inclination angle of the coupling **5150** is maintained (FIG. 57(b)). More particularly, the coupling **5150** is swung (pivoted) from the rotational force transmitting angular position to the disengaging angular position.

(399) As has been described hereinbefore, the angular position of the coupling **5150** is maintained by the locking member **5157k**. By this, the inclination angle of the coupling is maintained. Therefore, the coupling **5150** can be assuredly engaged with the drive shaft **180**. Furthermore, at the time of the rotation, the locking member **5157k** is not in contact with the coupling **5150**. Therefore, the stabilized rotation can be accomplished by the coupling **5150**.

(400) The motion of the coupling shown in FIGS. 56, 57 and 58 may include whirling motion.

(401) In this embodiment, the locking member **5157k** is provided with an elastic portion. However, it may be the rib which does not have the elastic portion. More particularly, an amount of engagement between the locking member **5157k** and the flange portion **5150j** is decreased. By this, the similar effect can be provided by making the flange portion **5150j** deform to a slight degree (FIG. 58(a)).

(402) In addition, the locking member **5157k** is provided in the downstreammost side with respect to the mounting direction X4. However, if the inclination toward the predetermined direction of the axis L2 can be maintained, the position of the locking member **5157k** may be any.

(403) FIGS. 58(b) and (c) illustrate the example in which the coupling locking portion **5357k** (FIGS. 58b)) and **5457k** (FIG. 58c) are provided in the upstream with respect to the mounting direction X4.

(404) In addition, the locking member **5157k** has been constituted by a part of bearing member **5157** in the above-described embodiment. However, if it is fixed to the cartridge B, the locking member **5157k** may be constituted as a part of a member other than the bearing member. In

addition, the locking member may be a separate member.

(405) In addition, the present embodiment may be implemented with Embodiment 4 or Embodiment 5. In this case, the mounting and dismounting operation with the more assured coupling is accomplished.

Embodiment 7

(406) Referring to FIG. 59-FIG. 62, the seventh embodiment of the present invention will be described.

(407) In this embodiment, another means for maintaining the axis of the coupling at the inclined state relative to the axis of the photosensitive drum will be described.

(408) FIG. 59 is a perspective view which illustrates the state of pasting a magnet member (peculiar to the present embodiment) on the drum bearing member. FIG. 60 is an exploded perspective view. FIG. 61 is an enlarged perspective view of a major part of the driving side of the cartridge. FIG. 62 is a perspective view and a longitudinal sectional view which illustrate the drive shaft and an engaged state between the coupling.

(409) As shown in FIG. 59, a drum bearing member **8157** constitutes a space **8157b** which surrounds a part of coupling. A magnet member **8159** as a maintaining member for maintaining the inclination of the coupling **8150** is pasted on a cylinder surface **8157i** which constitutes the space thereof. In addition, as shown in FIG. 59, the magnet member **8159** is provided in the upstream (with respect to the mounting direction **X4**) of the cylinder surface **8157i**. As will be described hereinafter, this magnet member **8159** is a member for maintaining temporarily the state where the axis **L2** inclines relative to the axis **L1**. Here, a part of coupling **8150** is made of magnetic material. And, the magnetic portion is attracted to the magnet member **8159** by a magnetic force of a magnet member **8159**. In this embodiment, the substantially full-circumference of the flange portion **8150j** is made of the metal magnetic material **8160**. In other words, as shown in FIG. 61, the flange portion **8150j** contacts to this magnet member **8159** by the magnetic force. By this, the axis **L2** maintains the state of inclining toward the downstream with respect to the mounting direction (**X4**) of the cartridge relative to the axis **L1** (FIG. 62 (a1)). Similarly to Embodiment 1 (FIG. 31), an inclining direction regulation rib **8157h** is preferably provided in the bearing member **8157**. The inclining direction of the coupling **8150** is more assuredly determined by provision of the rib **8157h**. And, the flange portion **8150j** of magnetic material and the magnet member **8159** can contact to each other more assuredly. Referring to FIG. 60, the description will be made about the assembly method of the coupling **8150**.

(410) As shown in FIG. 60, the pin **155** enters a standing-by space **8150g** of the coupling **8150**, and a part of coupling **8150** is inserted into a space portion **8157b** of the drum bearing member **8157**. At this time, preferably, a distance **D12** between an inner surface end of a retention rib **8157e** of the bearing member **8157** and the magnet member **8159** is larger than the maximum outer diameter of a driven portion **8150a** $\Phi D10$. In addition, the distance **D12** is smaller than the maximum outer diameter of a driving portion **8150b** $\Phi D11$. By this, the bearing member **8157** can be assembled straight. Therefore, the assembling property improves. However, the present embodiment is not limited to this relation.

(411) Referring to FIG. 62, the engaging operation (a part of mounting operation of the cartridge) for engaging the coupling **8150** with the drive shaft **180** will be described. FIGS. 62(a1) and (b1) illustrates the state immediately before the engagement, and FIGS. 62(a2) and (b2) illustrate the state of the engagement completion.

(412) As shown in FIGS. 62(a1) and (b1), the axis **L2** of the coupling **8150** inclines toward the downstream with respect to the mounting direction **X4** relative to the axis **L1** beforehand by the force of the magnet member (maintaining member) **8159** (pre-engagement angular position).

(413) Thereafter, the free end surface **180b** or the pin **182** free end contacts to the driving shaft receiving surface **8150f** of the coupling **8150** by the cartridge **B** moving to the mounting direction **X4**. And, the axis **L2** approaches so that it may become substantially co-axial with the axis **L1** by

the contact force (mounting force of the cartridge) thereof. At this time, the flange portion **8150j** separates from the magnet member **8159**, and is in the non-contact state. And, finally, the axis L1 and the axis L2 become substantially co-axial. And, the coupling **8150** is in the rotation latency state (FIG. **62(a2)**, Figure (b2)) (rotational force transmitting angular position).

(414) The motion shown in FIG. **62** may include whirling motion.

(415) As has been described hereinbefore, in this embodiment, the inclined state of the axis L2 is maintained by the magnetic force of the magnet member **8159** (maintaining member) pasted on the bearing member **8157**. By this, the coupling can be more assuredly engaged with the drive shaft.

Embodiment 8

(416) Referring to FIG. **63**-FIG. **68**, the eighth embodiment of the present invention will be described.

(417) In this embodiment, another means to maintain the state where the axis L2 is inclined relative to the axis L1 will be described.

(418) FIG. **63** is a perspective view which illustrates a driving side of a cartridge. FIG. **64** is an exploded perspective view which illustrates a state before assembling a drum bearing member. FIG. **65** is a schematic longitudinal sectional view of a drum shaft, a coupling, and a drum bearing member. FIG. **66** is a perspective view which illustrates a driving side of an apparatus main assembly guide. FIG. **67** is a longitudinal sectional view which illustrates disengagement of a lock member. FIG. **68** is a longitudinal sectional view which illustrates the engaging operation of the coupling to the drive shaft.

(419) As shown in FIG. **63**, the coupling **6150** is inclined toward the downstream with respect to the mounting direction (X4) by the locking member **6159** and the spring member **6158**.

(420) First, referring to FIG. **64**, the description will be made about a drum bearing member **6157**, a locking member **6159**, and a spring member **6158**. The bearing member **6157** is provided with an opening **6157v**. And, the opening **6157v** and the locking portion (locking member) **6159a** engage with each other. By this, a free end **6159a1** of the locking portion **6159a** projects into a space portion **6157b** of the bearing member **6157**. As will be described hereinafter, the state of inclining the coupling **6150** by this locking portion **6159a** is maintained. The locking member **6159** is mounted to the space **6157p** of the bearing member **6157**. The spring member **6158** is mounted by the boss **6157m** of the hole **6159b** and the bearing member **6157**. The spring member **6158** in the present embodiment employs a compression coil spring which has a spring force (elastic force) of about 50 g-300 g. However, if it is a spring which produces the predetermined spring force, any may be used. In addition, the locking member **6159** is the movable in the mounting direction X4 by the engagement with the slot **6159d** and the rib **6157k**.

(421) When the cartridge B is outside the apparatus main assembly A (state where the cartridge B is not mounted to the apparatus main assembly A), the coupling **6150** is in the state of inclining. In this state, a locking portion free end **6159a1** of the locking member **6159** is in the movable range T2 (hatching) of the flange portion **6150j**. FIG. **64(a)** shows an orientation of the coupling **6150**. By this, the inclination orientation of the coupling can be maintained. Furthermore, the locking member **6159** is abutted to an outer surface **6157q** (FIG. **64(b)**) of the bearing member **6157** by the spring force of the spring member **6158**. By this, the coupling **6150** can maintain the stabilized orientation. In order to engage the coupling **6150** with the drive shaft **180**, this lock is released to permit the inclination of the axis L2. In other words, as shown in FIG. **65(b)**, the locking portion free end **6159a1** moves in the direction of X12 to retract from the movable range T2 of the flange portion **6150j**.

(422) The description will further be made about the releasing of the locking member **6159**.

(423) As shown in FIG. **66**, the main assembly guide **6130R1** is provided with the lock releasing member **6131**. At the time of mounting the cartridge B to the apparatus main assembly A, the releasing member **6131** and the locking member **6159** engage with each other. By this, the position of the locking member **6159** in the cartridge B changes. Therefore, the coupling **6150** becomes

pivotable.

(424) Referring to FIG. 67, the releasing of the locking member **6159** will be described. When the free end position **6150A1** of the coupling **6150** comes to the neighborhood of the shaft free-end **180b3** by the movement, in the mounting direction **X4**, of the cartridge B, the releasing member **6131** and the locking member **6159** engage with each other. At this time, a rib **6131a** of the releasing member **6131** (contact portion) and a hook portion **6159c** of the locking member **6159** (force receiving portion) contact to each other. By this, the position of the locking member **6159** in the inside of the apparatus main assembly A is fixed (b). Thereafter, the locking portion free end **6159a1** is located in the space portion **6157b** by the cartridge moving through 1-3 mm in the mounting direction. Therefore, the drive shaft **180** and the coupling **6150** are engageable with each other, and the coupling **6150** is in the swingable (pivotable) state (c).

(425) Referring to FIG. 68, the engaging operation of the coupling relative to the drive shaft and the position of the locking member will be described.

(426) In the state of FIGS. 68(a) and (b), the axis **L2** of the coupling **6150** inclines toward the mounting direction **X4** relative to the axis **L1** beforehand (pre-engagement angular position). At this time, with respect to the direction of the axis **L1**, the free end position **6150A1** is closer to the photosensitive drum **107** than the shaft free-end **180b3** and, the free end position **6150A2** is closer to the pin **182** than the shaft free-end **180b3**. In the state of (a), the locking member (force receiving portion) **6159** is engaged in the state for receiving the force from the lock releasing member (contact portion) **6131**. And, in the state of (b), the locking portion free end **6159a1** retracts from the space portion **6157b**. By this, the coupling **6150** is released from the orientation maintenance state. More particularly, the coupling **6150** becomes swingable (pivotable).

(427) Thereafter, as shown in (c), by the movement of the cartridge toward the mounting direction **X4**, driving shaft receiving surface **6150f** of the coupling **6150** (the cartridge side contact portion) or projection **6150d** contacts to the free end portion **180b** or the pin **182**. And, in response to the movement of the cartridge, the axis **L2** approaches so that it may become substantially co-axial with the axis **L1**. And, finally, as shown in (d), the axis **L1** and the axis **L2** become substantially co-axial. By this, the coupling **6150** is in the rotation latency state (rotational force transmitting angular position).

(428) The timing at which the locking member **6159** retracts is as follows. More particularly, after the free end position **6150A1** passes by the shaft free-end **180b3**, and before the receiving surface **6150f** or the projection **6150d** contacts to the free end portion **180b** or the pin **182**, the locking member **6159** retracts. By doing so, the coupling **6150** does not receive an excessive load, and the assured mounting operation is accomplished. The receiving surface **6150f** has a tapered shape.

(429) In addition, in the dismounting process from the apparatus main assembly A of the cartridge B, the step opposite from the step to mount is followed. More particularly, by moving the cartridge B in the dismounting direction, the free end portion **180b** of the drive shaft (the main assembly side engaging portion) **180** pushes the receiving surface **6150f** (the cartridge side contact portion). By this, the axis **L2** begins (FIG. 68(c)) to incline relative to the axis **L1**. And, the coupling **6150** passes by the shaft free-end **180b3** completely (FIG. 68(b)). The hook portion **6159c** spaces from the rib **6131a** immediately after that. And, the locking portion free end **6159a1** contacts to the lower surface **6150j2** of the flange portion. Therefore, the inclined state of the coupling **6150** is maintained (FIG. 68(a)). More particularly, the coupling **6150** is pivoted to the disengaging angular position from the rotational force transmitting angular position (swinging).

(430) The motion shown in FIGS. 67 and 68 may include whirling motion.

(431) As has been described hereinbefore, the inclination angle position of the coupling **6150** is maintained by the locking member **6159**. By this, the inclined state of the coupling is maintained. Therefore, the coupling **6150** is more assuredly mounted relative to the drive shaft **180**.

Furthermore, at the time of the rotation, the locking member **6159** does not contact to the coupling **6150**. Therefore, the coupling **6150** can effect more stabilized rotation.

(432) In the embodiment described above, the locking member is provided in the upstream with respect to the mounting direction. However, the position of the locking member may be any if the inclination in the predetermined direction of the axis of the coupling is maintained.

(433) In addition, the present embodiment may be implemented with Embodiments 4-7. In this case, mounting and dismounting operations of the coupling can be ensured.

Embodiment 9

(434) Referring to FIG. 69-FIG. 73, the ninth embodiment of the present invention will be described.

(435) In this embodiment, another means for inclining the axis L2 relative to the axis L1 will be described.

(436) FIG. 69 is an enlarged side view of a driving side of a cartridge. FIG. 70 is a perspective view which illustrates a driving side of an apparatus main assembly guide. FIG. 71 is a side view which illustrates a relation between the cartridge and the main assembly guide. FIG. 72 is a side view and a perspective view which illustrate a relation between the main assembly guide and the coupling. FIG. 73 is a side view which illustrates a mounting process.

(437) FIG. 69(a1) and FIG. 69(b1) are a side views of the cartridge (as seen from the drive shaft side), and FIG. 69(a2) and FIG. 69(b2) are a side views of the drive shaft (as seen from the opposite side) of the cartridge. As shown in FIG. 69, in the pivotable state toward the downstream with respect to the mounting direction (X4), the coupling 7150 is mounted to the drum bearing member 7157. In addition, as for the inclining direction, as has been described with respect to Embodiment 1, it is pivotable only to the downstream with respect to the mounting direction X4 by the retention rib (regulating means) 7157e. In addition, in FIG. 69(b1), the axis L2 of the coupling 7150 inclines with the angle $\alpha 60$ relative to the horizontal line. The reason why the coupling 7150 inclines with the angle $\alpha 60$ is as follows. In the flange portion 7150j of the coupling 7150, a regulating portion 7157h 1 or 7157h2 as the regulating means regulate. Therefore, the downstream side (mounting direction) of the coupling 7150 is pivotable toward the direction upwardly inclined by the angle $\alpha 60$.

(438) Referring to FIG. 70, the description will be made about the main assembly guide 7130R. The main assembly guide 7130R1 includes a guide rib 7130R1a for guiding the cartridge B through the coupling 7150, and cartridge positioning portions 7130R1e, 7130R1f. The rib 7130R1a is on the mounting locus of the cartridge B. And, the rib 7130R1a is extended to just before the drive shaft 180 with respect to the cartridge mounting direction. And, the rib 7130R1b adjacent to the drive shaft 180 has the height to avoid interference When the coupling 7150 engages with the drive shaft 180. The main assembly guide 7130R2 mainly includes a guide portion 7130R2a and the cartridge positioning portion 7130R2c for determining the orientation at the time of the mounting of the cartridge by guiding a part cartridge frames B1.

(439) The relation between the main assembly guide 7130R and the cartridge at the time of mounting the cartridge will be described.

(440) As shown in FIG. 71(a), in the driving side, while a connecting portion (force receiving portion) 7150c of the coupling 7150 contacts to the guide rib (contact portion) 7130R1a, a cartridge B moves. At this time, the cartridge guide 7157a of the bearing member 7157 is separated from the guide surface 7130R1c by n59. Therefore, the weight of the cartridge B is applied to the coupling 7150. In addition, on the other hand, as has been described hereinbefore, the coupling 7150 is set, so that it is pivotable toward the direction to which the downstream side with respect to the mounting direction upwardly inclines by the angle $\alpha 60$ relative to the mounting direction (X4). Therefore, the driven portion 7150a of the coupling 7150 inclines toward the downstream (direction inclined by the angle $\alpha 60$ from the mounting direction) with respect to the mounting direction X4 (FIG. 72).

(441) The reason for the inclination of the coupling 7150 is as follows. The connecting portion 7150c receives the reaction force corresponding to the weight of the cartridge B from the guide rib

7130R1a. And, the reaction force applies to the regulating portion **7157h 1** or **7157h2** for regulating the inclining direction. By this, the coupling is inclined to the predetermined direction.

(442) Here, when the connecting portion **7150c** moves on the guide rib **7130R1a**, a frictional force is between the connecting portion **7150c** and the guide rib **7130R1a**. Therefore, the coupling **7150** receives a force in the direction opposite from the mounting direction **X4** by this frictional force. However, the frictional force produced by the coefficient of friction between the connecting portion **7150c** and the guide rib **7130R1a** is smaller than the force for pivoting the coupling **7150** to the downstream with respect to the mounting direction **X4** by the reaction force. Therefore, the coupling **7150** overcomes the frictional force is pivoted to the downstream with respect to the mounting direction **X4**.

(443) The regulating portion **7157p** (FIG. 69) of the bearing member **7157** may be used as the regulating means for regulating the inclination. By this, the regulation of the inclining direction of the coupling is carried out at the different positions with respect to the direction of the axis **L2** by the regulating portions **7157h 1**, **7157h2** (FIG. 69) and the regulating portion **7157p**. By this, the direction which the coupling **7150** inclines can be regulated more assuredly. In addition, it can always be inclined toward the angle of approximately α **60**. However, the regulation of the inclining direction of the coupling **7150** may be made by another means.

(444) In addition, the guide rib **7130R1a** is in the space **7150s** constituted by the driven portion **7150a**, the driving portion **7150b**, and the connecting portion **7150c**. Therefore, in the mounting process, the longitudinal position (the direction of the axis **L2**) in the inside of the apparatus main assembly **A** of the coupling **7150** is regulated (FIG. 71). By the longitudinal position of the coupling **7150** being regulated, the coupling **7150** can be more assuredly engaged relative to the drive shaft **180**.

(445) The engaging operation for engaging the coupling **7150** with the drive shaft **180** will be described. The engaging operation is the same as that of Embodiment 1 substantially (FIG. 22). Here, referring to FIG. 73, the description will be made about the relation among the main assembly guide main assembly guide **7130R2**, the bearing member **7157**, and the coupling **7150** to the process which the coupling engages with the drive shaft **180**. As long as the connecting portion **7150c** contacts to the rib **7130R1a**, the cartridge guide **7157a** is separate from the guide surface **7130R1c**. By this, the coupling **7150** is inclined (FIG. 73(a), FIG. 73(d)) (pre-engagement angular position). At the time of the free end **7150A1** of the inclined coupling **7150** passing by the shaft free-end **180b3**, the connecting portion **7150c** is departed from the guide rib **7130R1a** (FIG. 73(b), FIG. 73(e)). At this time, the cartridge guide **7157a** passes the guide surface **7130R1c**, and begins to contact to the positioning surface **7130R1e** through the inclined surface **7130R1d** (FIG. 73(b), FIG. 73 (e)). After that, the receiving surface **7150f** or the projection **7150d** contacts to the free end portion **180b** or the pin **182**. And, in response to the cartridge mounting operation, the axis **L2** becomes substantially co-axial with the axis **L1**, and the center of the drum shaft and the center of the coupling align with each other. And, finally, as shown in FIG. 73(c) and FIG. 73(f), the axis **L1** and the axis **L2** are co-axial relative to each other. And, the coupling **7150** is in the rotation latency state (rotational force transmitting angular position).

(446) In addition, the step substantially opposite from the engaging operation is followed in the process which takes out the cartridge **B** from the apparatus main assembly **A**. In other words, the cartridge **B** moves in the dismounting direction. By this, the free end portion **180b** pushes the receiving surface **7150f**. By this, the axis **L2** begins to incline relative to the axis **L1**. The upstream free end portion **7150A1** with respect to the dismounting direction moves on the shaft free-end **180b** by dismounting operation of the cartridge, and, the axis **L2** inclines until the upper free end portion **A1** reaches the drive shaft free-end **180b3**. And, the coupling **7150** passes by the shaft free-end **180b3** completely in this state (FIG. 73 (b)). After that, the connecting portion **7150c** contacts the coupling **7150** to the rib **7130R1a**. By this, the coupling **7150** is taken out in the state inclined toward the downstream with respect to the mounting direction. In other words, the coupling **5150** is

pivoted to the disengaging angular position from the rotational force transmitting angular position (swinging).

(447) As has been described hereinbefore, the coupling swings by the user mounting the cartridge to the main assembly, and it engages with the main assembly driving shaft. In addition, a special means for maintaining the orientation of the coupling is unnecessary. However, the orientation maintenance structure as in the embodiment 4-embodiment 8 may be used with the present embodiment.

(448) In this embodiment, the coupling is inclined toward the mounting direction by applying the weight to the guide rib. However, not only the weight, the spring force and so on may be utilized further.

(449) In this embodiment, the coupling is inclined by the connecting portion of the coupling receiving the force. However, the present embodiment is not limited to this example. For example, if the coupling is inclined by receiving the force from a contact portion of the main assembly, the portion other than the connecting portion may be contacted to the contact portion.

(450) In addition, the present embodiment may be implemented with any of the embodiment 4-embodiment 8. In this case, the engagement and disengagement relative to the drive shaft of the coupling can be ensured.

Embodiment 10

(451) Referring to FIG. 74-FIG. 81, the tenth embodiment of the present invention will be described.

(452) In this embodiment, another means for inclining the axis L2 relative to the axis L1 will be described.

(453) FIG. 74 is a perspective view which illustrates a driving side of an apparatus main assembly.

(454) Referring to FIG. 74, a main assembly guide and a coupling urging means will be described.

(455) The present embodiment is effectively applied, in the case that the frictional force described in Embodiment 9 would be larger than the force of pivoting the coupling 7150 toward the downstream (mounting direction X4) by the reaction force. More particularly, for example, even if the frictional force increases by rubbing action to the connecting portion or the main assembly guide, the coupling can be assuredly pivoted to the pre-engagement angular position, according to this embodiment. The main assembly guide 1130R1 includes. A guide surface 1130R1b for guiding the cartridge B through the cartridge guide 140R1 (FIG. 2), A guide rib 1130R1c which guides the coupling 150, and cartridge positioning portion 1130R1a. The guide rib 1130R1c is on the mounting locus of the cartridge B. And, the guide rib 1130R1c is extended to just before the drive shaft 180 with respect to the cartridge mounting direction. In addition, a rib 1130R1d provided adjacent to the drive shaft 180 has a height not causing interference when the coupling 150 engages.

(456) A part of a rib 1130R1c is cut away. And, the main assembly guide slider 1131 is mounted to the rib 1130R1c slidably in the direction of an arrow W. The slider 1131 is pressed by an elastic force of an urging spring 1132. And, the position is determined by the slider 1131 abutting to the abutment surface 1130R1e of the main assembly guide 1130R1. In this state, the slider 1131 projects from the guide rib 1130R1c.

(457) The main assembly guide 1130R2 has a guide portion 1130R2b for determining the orientation at the time of the mounting of the cartridge B by guiding a part of cartridge frames B1, and a cartridge positioning portion 1130R2a.

(458) Referring to FIG. 75-FIG. 77, the among relation of the main assembly guide 1130R1, 1130R2, the slider 1131, and the cartridge B, at the time of mounting the cartridge B, will be described. FIG. 75 is a side view, as seen from the main assembly driving shaft 180 (FIGS. 1 and 2) side, and FIG. 76 is a perspective view thereof. FIG. 77 is a sectional view taken along Z-Z of FIG. 75.

(459) As shown in FIG. 75, in the driving side, while the cartridge guide 140R1 of the cartridge

contacts to the guide surface **1130R1b**, the cartridge moves. At this time, as shown in FIG. 77, the connecting portion **150c** is separated from the guide rib **1130R1c** by **n1**. Therefore, the force is not applied to the coupling **150**. In addition, as shown in FIG. 75, the coupling **150** is regulated by the regulating portion **140R1a** at the upper surface and the left side. Therefore, the coupling **150** is freely pivotable only in the mounting direction (X4).

(460) Referring to FIG. 78-FIG. 81, the operation of moving the slider **1131** to the retreating position from the energizing position while the coupling **150** contacts to the slider **1131**, will be described. In FIG. 78-FIG. 79, the coupling **150** contacts in the apex **1131b** of the slider **1131**, more particularly, the slider **1131** is in the retreating position. The connecting portion **150c** and the inclined surface of the projection of the slider **1131** **1131a** contact with each other by the entrance of the coupling **150** pivotable only in the mounting direction (X4). By this, the slider **1131** is depressed and it moves to the retreating position.

(461) Referring to FIG. 80-FIG. 81, the operation after the coupling **150** rides over an apex **1131b** of the slider **1131** will be described. FIG. 80-FIG. 81 illustrate the state after the coupling **150** ride over the apex **1131b** of the slider **131**.

(462) When the coupling **150** rides over the apex **1131b**, the slider **1131** tends to return from the retreating position to the energizing position by the elastic force of the urging spring **132**. In that case, a part of connecting portion **150c** of the coupling **150** receives the force **F** from the inclined surface **1131c** of the slider **1131**. More particularly, the inclined surface **1131c** functions as the force applying portion and it functions as the force receiving portion for a part of connecting portion **150c** to receive this force. As shown in FIG. 80, the force receiving portion is provided in the upstream of the connecting portion **150c** with respect to the cartridge mounting direction. Therefore, the coupling **150** can be inclined smoothly. As shown in FIG. 81, in addition, the force **F** is divided into a component force **F1** and a component force **F2**. At this time, the upper surface of the coupling **150** is regulated by the regulating portion **140R1a**. Therefore, the coupling **150** is inclined toward the mounting direction (X4) by the component force **F2**. More particularly, the coupling **150** is inclined toward the pre-engagement angular position. By this, the coupling **150** becomes engageable with the drive shaft **180**.

(463) In the embodiment described above, the connecting portion receives the force and the coupling is inclined. However, the present embodiment is not limited to this example. For example, if the coupling is pivotable by receiving the force from the contact portion of the main assembly, the portion other than the connecting portion may contact with the contact portion.

(464) In addition, the present embodiment may be implemented with any of the embodiment 4-embodiment 9. In this case, the engagement and disengagement of the coupling relative to the drive shaft can be ensured.

Embodiment 11

(465) Referring to FIG. 82-FIG. 84, the eleventh embodiment of the present invention will be described.

(466) In the present embodiment, the configuration of the coupling will be described. FIG. 82-FIG. 84(a) are perspective views of couplings, FIG. 82-FIG. 84(b) are sectional views of the couplings.

(467) In the previous embodiments, the driving shaft receiving surface and the drum bearing surface of the coupling have conical shapes, respectively. However, in this embodiment, the different configuration will be described.

(468) A coupling **12150** shown in FIG. 82 mainly comprises three portions similarly to the coupling shown in FIG. 8. More particularly, as shown in FIG. 82(b), the coupling **12150** comprises an a driven portion **12150a** for receiving the drive from the drive shaft, a driving portion **12150b** for transmitting the drive to a drum shaft, and a connecting portion **12150c** which connects the driven portion **12150a** and the driving portion **12150b** with each other.

(469) As shown in FIG. 82(b), the driven portion **12150a** has a drive shaft insertion opening portion **12150m** as an expanded part which expands toward the drive shaft **180** relative to the axis

L2 the driving portion **12150b** has a drum shaft insertion opening portion **12150v** as an expanded part which expands toward the drum shaft **153**. An opening **12150m** and an opening **12150v** are constituted by the driving shaft receiving surface **12150f** of a divergent shape, and the drum bearing surface **12150i** of a divergent shape, respectively. The receiving surface **12150f** and the receiving surface **12150i** have the recesses **12150x**, **12150z** as shown in the Figure. At the time of the rotational force transmission, the recess **12150z** opposes to the free end of the drive shaft **180**. More particularly, the recess **12150z** covers the free end of the drive shaft **180**.

(470) Referring to FIG. **83**, a coupling **12250** will be described. As shown in FIG. **83(b)**, a driven portion **12250a** has a drive shaft insertion opening portion **12250m** as an expanded part which expands toward the drive shaft **180** relative to the axis L2 a driving portion **12250b** has a drum shaft insertion opening portion **12250v** as the expanded part which expands toward the drum shaft **153** relative to the axis L2.

(471) An opening **12250m** and an opening **12250v** are constituted by the driving shaft receiving surface **12250f** of a bell-like shape, and the drum bearing surface **12250i** of a bell-like shape, respectively. A receiving surface **12250f** and a receiving surface **12250i** constitute the recesses **12250x**, **12250z** as shown in the Figure. At the time of the rotational force transmission, the recess **12250z** engages with the free end portion of the drive shaft **180**. Referring to FIG. **84**, a coupling **12350** will be described. As shown in FIG. **84(a)**, a driven portion **12350a** includes drive receiving projections **12350d 1** or **12350d 2** or **12350d3** and **12350d4** which are directly extended from a connecting portion **12350c** and which expand radially toward the drive shaft **180** relative to the axis L2. In addition, the portion between the adjacent projections **12350d1-121350d4** constitutes the standing-by portion. Furthermore, the rotational force receiving surfaces (rotational force receiving portion) **12350e** (**12350e1-e4**) are provided in the upstream with respect to the rotational direction X7. At the time of the rotation, a rotational force is transmitted to the rotational force receiving surfaces **12350e1-e4** from the pin (rotational force applying portion) **182**. At the time of the rotational force transmission, the recess **12250z** opposes to the free end portion of the drive shaft which is the projection of the apparatus main assembly. More particularly, the recess **12250z** covers the free end of the drive shaft **180**.

(472) In addition, if the effect similar to Embodiment 1 is provided, the configuration of the opening **12350v** may be any.

(473) In addition, the mounting method to the cartridge of the coupling is the same as that of Embodiment 1, and therefore, the description is omitted. In addition, the operation of mounting the cartridge to the apparatus main assembly, and the operation of extracting from the apparatus main assembly are the same as those of Embodiment 1 (FIGS. **22** and **25**), and therefore, the description is omitted.

(474) As has been described hereinbefore, the drum bearing surface of the coupling has the expanding configuration, and the coupling can be mounted relative to the axis of the drum shaft for inclination. In addition, the driving shaft receiving surface of the coupling has the expanding configuration and can incline the coupling, without interfering with the drive shaft in response to the mounting operation or the dismounting operation of the cartridge B. By this, also in this embodiment, the effects similar to the first embodiment or the second embodiment can be provided.

(475) In addition, as for the configurations of the opening **12150m**, **12250m** and the opening **12150v**, **12250v**, they may be a combination of the divergent, bell-like shapes.

Embodiment 12

(476) Referring to FIG. **85**, the twelfth embodiment of the present invention will be described.

(477) The present embodiment is different from Embodiment 1 in the configuration of the coupling FIG. **85(a)** is a perspective view of a coupling which has a substantially cylindrical shape, and FIG. **85(b)** is a sectional view when the coupling mounted to the cartridge engages with a drive shaft.

(478) A drive side edge of the coupling **9150** is provided with a plurality of driven projections

9150d. In addition, a drive receiving stand-by portion **9150k** is provided between the drive receiving projections **9150d**. The projection **9150d** is provided with a rotational force receiving surface (rotational force receiving portion) **9150e**. A rotational force transmitting pin (rotational force applying portion) **9182** of the drive shaft **9180** as will be described hereinafter contacts to the rotational force receiving surface **9150e**. By this, a rotational force is transmitted to the coupling **9150**.

(479) In order to stabilize the running torque transmitted to the coupling, a plurality of rotational force receiving surfaces **150e** are desirably disposed on the same circumference (on the phantom circle C1 of FIG. 8 (d)). By the disposition in this manner, the rotational force transmission radius is constant and the torque transmitted is stabilized. In addition, from the viewpoint of the stabilization of the drive transmission, the receiving surfaces **9150e** are desirably provided on the opposed positions (180 degrees) diametrically. In addition, the number of the receiving surfaces **9150e** may be any if the pin **9182** of the drive shaft **9180** can be received by the stand-by portion **9150k**. In the present embodiment, the number is two. The rotational force receiving surfaces **9150e** may not be on the same circumference, or they may not be disposed diametrically opposed positions.

(480) In addition, the cylinder surface of the coupling **9150** is provided with the standby opening **9150g**. In addition, the opening **9150g** is provided with the rotational force transmission surface (rotational force transmitting portion) **9150h**. The drive transmission pin (rotational force receiving member) **9155** (FIG. 85(b)) of the drum shaft as will be described hereinafter contacts to this rotational force transmission surface **9150h**. By this, the rotational force is transmitted to the photosensitive drum **107**.

(481) Similarly to the projection **9150d**, the rotational force transmission surface **9150h** is desirably disposed diametrically opposed on the same circumference.

(482) The structures of the drum shaft **9153** and the drive shaft **9180** will be described. In Embodiment 1, the cylindrical end is a spherical surface. In this embodiment, however, a diameter of a spherical free end portion **9153b** of the drum shaft **9153** is larger than a diameter of a main part **9153a**. With this structure, even if the coupling **9150** has the cylindrical shape as illustrated, it is pivotable relative to the axis L1. In other words, a gap g as illustrated is provided between the drum shaft **9153** and the coupling **9150** by this, the coupling **9150** is pivotable (swingable) relative to the drum shaft **9153**. The configuration of the drive shaft **9180** is the same as that of the drum shaft **9150** substantially. In other words, the configuration of the free end portion **9180b** is the spherical surface, and the diameter thereof is larger than the diameter of the main part **9180a** of the cylindrical shape portion. In addition, the pin **9182** which pierces through the substantial center of the free end portion **9180b** which is the spherical surface is provided the pin **9182** transmits the rotational force to the rotational force receiving surface **9150e** of the coupling **9150**.

(483) The drum shaft **9150** and the spherical surface of the drive shaft **9180** are in engagement with the inner surface **9150p** of the coupling **9150**. By this, the relative position between the drum shaft **9150** and the coupling **9150** of the drive shaft **9180** is determined. The operation with respect to the mounting and demounting of the coupling **9150** is the same as Embodiment 1, and therefore, the description thereof is omitted.

(484) As has been described hereinbefore, the coupling has the cylindrical shape, and therefore, the position with respect to the direction perpendicular to the direction of the axis L2 of the coupling **9150** can be determined relative to the drum shaft or the drive shaft. A modified example of the coupling will be described further. In the configuration of the coupling **9250** shown in FIG. 85(c), a cylindrical shape and a conical shape are put together. FIG. 85 (d) is a sectional view of the coupling of this modified example. A driven portion **9250a** of the coupling **9250** has a cylindrical shape, and an inner surface **9250p** thereof engages with the spherical surface of the drive shaft. Furthermore, it has the abutment surface **9250q** and can effect the positioning with respect to the axial direction between the coupling **9250** and the drive shaft **180**. The driving portion **9250b** has a

conical shape, and, similarly to Embodiment 1, the position relative to the drum shaft **153** is determined by the drum bearing surface **9250i**.

(485) The configuration of the coupling **9350** shown in FIG. **85(e)** is a combination of a cylindrical shape and a conical shape. FIG. **85(f)** is a sectional view of this modified example the driven portion **9350a** of the coupling **9350** has a cylindrical shape, and the inner surface **9350p** thereof engages with the spherical surface of the drive shaft **180**. The positioning in the axial direction is effected by abutting the spherical surface of the drive shaft to the edge portion **9350q** formed between the cylindrical portions having different diameters.

(486) The configuration of the coupling **9450** shown in FIG. **85(g)** is a combination of a spherical surface, a cylindrical shape, and a conical shape. FIG. **85(h)** is a sectional view of this modified example a driven portion **9450a** of the coupling **9450** has a cylindrical shape, and the inner surface **9450p** thereof engages with the spherical surface of the drive shaft **180**. A spherical surface of the drive shaft **180** is contacted to a spherical surface **9450q** which is a part of the spherical surface. By this, the position can be determined with respect to the direction of the axis **L2**.

(487) In addition, in this embodiment, the coupling has the substantially cylindrical shape and the free end portions of the drum shaft or the drive shaft have the spherical configurations in addition, it has been described that the diameter thereof is larger than the diameter of the main part of the drum shaft or the drive shaft. However, the present embodiment is not limited to such an example. The coupling has a cylindrical shape and the drum shaft or the drive shaft has a cylindrical shape and, a diameter of the drum shaft or the drive shaft is small relative to an inner diameter of an inner surface of the coupling within limits in which the pin does not disengage from the coupling. By this, the coupling is pivotable relative to the axis **L1** the coupling can be inclined without interfering with the drive shaft in response to the mounting operation or the dismounting operation of the cartridge **B**. In view of this, also in this embodiment, the effects similar to Embodiment 1 or Embodiment 2 can be provided.

(488) In addition, in this embodiment, although an example of the combination of the cylindrical shape and conical shape has been described as the configuration of the coupling, it may be opposite to the example. In other words, the drive shaft side may be formed into a conical shape, and the drum shaft side may be formed into a cylindrical shape.

Embodiment 13

(489) Referring to FIG. **86**-FIG. **88**, the thirteenth embodiment of the present invention will be described.

(490) The present embodiment is different from Embodiment 1 in the mounting operation relative to the drive shaft of the coupling, and the structure with respect to it. FIG. **86** is a perspective view which illustrates a configuration of a coupling **10150** of the present embodiment. The configuration of the coupling **10150** is a combination of the cylindrical shape and conical shape which have been described in Embodiment 10. In addition, a tapered surface **10150r** is provided on the free end side of a coupling **10150**. In addition, the surface of an opposite side of the drive receiving projection **10150d** with respect to the direction of the axis **L1** is provided with an urging force receiving surface **10150s**.

(491) Referring to FIG. **87**, the structure of the coupling will be described.

(492) An inner surface **10150p** and a spherical surface **10153b** of a drum shaft **10153** of the coupling **10150** are in engagement with each other. An urging member **10634** is interposed between a receiving surface **10150s** described in the foregoing and a bottom surface **10151b** of a drum flange **10151**. By this, the coupling **10150** is urged toward the drive shaft **180**. In addition, similarly to the foregoing embodiments, a retention rib **10157e** is provided in the drive shaft **180** side of the flange portion **10150j** with respect to the direction of the axis **L1**. By this, the disengagement of the coupling **10150** from the cartridge is prevented the inner surface **10150p** of the coupling **10150** is cylindrical. Therefore, it is the movable in the direction of the axis **L2**.

(493) FIG. **88** is for illustrating the orientation of the coupling in the case that the coupling engages

with the drive shaft. FIG. 88(a) is a sectional view of the coupling 150 of Embodiment 1, and FIG. 88(c) is a sectional view of a coupling 10150 of the present embodiment. And, FIG. 88(b) is a sectional view before reaching the state of FIG. 88(c) the mounting direction is shown by X4 and the chain line L5 is a line drawn in parallel with the mounting direction from the free end of the drive shaft 180.

(494) In order for the coupling to engage with the drive shaft 180, the downstream free end position 10150A1 with respect to the mounting direction needs to pass the free end portion 180b3 of the drive shaft 180. In the case of Embodiment 1, the axis L2 inclines by more than angle $\alpha 104$. By this, the coupling moves to the position where the free end position 150A1 does not interfere with the free end portion 180b3 (FIG. 88(a)).

(495) On the other hand, in the coupling 10150 of the present embodiment, it in the state where it does not be in engagement with the drive shaft 180, the coupling 10150 takes the position nearest to the drive shaft 180 by the restoring force of the urging member 10634. In this state, when it moves in the mounting direction X4, a part of drive shafts 180 contact the cartridge B at the tapered surface 10150r of the coupling 10150 (FIG. 88(b)). At this time, the force is applied to the tapered surface 10150r in the direction opposite the X4 direction therefore, the coupling 10150 is retracted in the longitudinal direction X11 by a component force thereof. And, the free end portion 10153b of the drum shaft 10153 abuts to an abutting portion 10150t of the coupling 10150 in addition, the coupling 10150 rotates clockwise about the center P1 of the free end portion 10153b (pre-engagement angular position). By this, the free end position 10150A1 of the coupling passes by the free end 180b of the drive shaft 180 (FIG. 88(c)). When the drive shaft 180 and the drum shaft 10153 becomes substantially co-axial, a driving shaft receiving surface 10150f of the coupling 10150 contacts to the free end portion 180b by the restoring force of the urging spring 10634. By this, the coupling becomes in the rotation latency state (FIG. 87). (rotational force transmitting angular position). With such a structure, the movement in the direction of the axis L2 and the pivoting motion (swinging operation) are combined, and the coupling is swung from the pre-engagement angular position to the rotational force transmitting angular position.

(496) By this structure, even if the angle $\alpha 106$ (inclination amount of the axis L2) is small, the cartridge can be mounted to the apparatus main assembly A. Therefore, the space required by the pivoting motion of the coupling 10150 is small. Therefore, latitude in the design of the apparatus main assembly A is improved.

(497) The rotation according to the drive shaft 180 of the coupling 10150 is the same as Embodiment 1, and therefore, the description thereof is omitted. At the time of taking out the cartridge B from the apparatus main assembly A, the free end portion 180b is forced on the conical shape driving shaft receiving surface 10150f of the coupling 10150 by removing force. The coupling 10150 is pivoted by this force, while retracting toward the direction of the axis L2 by this, the coupling is demounted from the drive shaft 180. In other words, the moving operation in the direction of the axis L2 and the pivoting motion are combined (whirling motion may be includes), the coupling can be pivoted to the disengaging angular position from the rotational force transmitting angular position.

Embodiment 14

(498) Referring to FIG. 89-FIG. 90, the 14th embodiment of the present invention will be described.

(499) The point in which the present embodiment is different from Embodiment 1 is in the engaging operation and the structure with respect to it relative to the drive shaft of the coupling.

(500) FIG. 89 is a perspective view which illustrates only the coupling 21150 and the drum shaft 153 FIG. 90 is a longitudinal sectional view, as seen from the lower of the apparatus main assembly As shown in FIG. 89, the magnet member 21100 is mounted to the end of the driving portion 21150a of the coupling 21150 The drive shaft 180 shown in FIG. 90 comprises magnetic material Therefore, in this embodiment, the magnet member 21100 is inclined in the coupling 21150 by the

magnetic force between the drive shaft **180** of it and magnetic material.

(501) First, as shown in FIG. **90(a)**, the coupling **21150** is not particularly inclined relative to the drum shaft **153** at this time, the magnet member **21100** is positioned in the driving portion **21150a** in the upstream with respect to the mounting direction **X4**.

(502) When it is inserted to the position shown in FIG. **90(b)**, the magnet member **21100** is attracted toward the drive shaft **180**. And, as illustrated, the coupling **21150** begins the swinging motion by the magnetic force thereof.

(503) Thereafter, the leading end position **21150A1** of the coupling **21150** with respect to the mounting direction (**X4**) passes by the drive shaft free-end **180b3** which has the spherical surface. And, the driving shaft receiving surface **21150f** of a conical shape or the driven projection **21150d** (the cartridge side contact portion) which constitutes the recess **21150z** of the coupling **21150** contacts the free end portion **180b** or **182** after the passage (FIG. **90(c)**).

(504) And, it inclines so that the axis **L2** becomes substantially co-axial with the axis **L1** in response to the mounting operation of the cartridge B (FIG. **90 (d)**).

(505) Finally, the axis **L1** and the axis **L2** become substantially co-axial with each other. In this state, the recess **21150z** covers the free end portion **180b**. The axis **L2** pivots the coupling **21150** to the rotational force transmitting angular position from the pre-engagement angular position so that it is substantially co-axial with the axis **L1**. The coupling **21150** and the drive shaft **180** are engaged with each other (FIG. **90(e)**).

(506) Motion of the coupling shown in FIG. **90** may also include the revolution.

(507) It is necessary to position the magnet member **21100** in the upstream of the driving portion **21150a** with respect to the mounting direction **X4**.

(508) Therefore, at the time of mounting the cartridge B to the apparatus main assembly A, it is necessary to align the phase of the coupling **21150**. The method described with respect to Embodiment 2 is usable for the method of doubling the phase of the coupling.

(509) The state of receiving rotation driving force and rotating after the mounting completion is the same as Embodiment 1 and therefore, the description is omitted.

Embodiment 15

(510) Referring to FIG. **91**, the 15th embodiment of the present invention will be described.

(511) The point in which the present embodiment is different from Embodiment 1 is the manner of support of the coupling. In embodiment 1, the axis **L2** of the coupling thereof is pivotable, while being interposed between the free end portion of the drum shaft and the retention rib. On the other hand, in the present embodiment, the axis **L2** of the coupling is pivotable only by the drum bearing member. This will be described in more detail.

(512) FIG. **91(a)** is a perspective view which illustrates the state in the course of mounting the coupling. FIG. **91(b)** is a longitudinal sectional view thereof. FIG. **91(c)** is a perspective view which illustrates the state where the axis **L2** inclines relative to the axis **L1**. FIG. **91(d)** is a longitudinal sectional view thereof. FIG. **91(e)** is a perspective view which illustrates the state where the coupling rotates. FIG. **91(f)** is a longitudinal sectional view thereof.

(513) In this embodiment, the drum shaft **153** is placed in a space defined by an inner surface of a space portion **11157b** of a drum bearing member **11157**. In addition, the rib **11157e** and the rib **11157p** are provided on the inner surface opposite from the drum shaft **153** (at the different positions with respect to the direction of the axis **L1**).

(514) With this structure, a flange portion **11150j** and a drum bearing surface **11150i** are regulated by an inner end surface **11157p1** and circular column portion **11153a** of the rib in the state in which the axis **L2** is inclined (FIG. **91(d)**). Here, the end surface **11157p1** is provided in the bearing member **11157**. In addition, the circular column portion **11153a** is a part of drum shaft **11153**. And, when the axis **L2** becomes substantially co-axial with the axis **L1** (FIG. **91 (f)**), the flange portion **11150j** and the taper outer surface **11150q** are regulated by the outer end **11157p2** of the rib **11157e** and the rib of the bearing member **11157**.

(515) Therefore, the coupling **11150** is retained in the bearing member **11157** by selecting the configuration of the bearing member **11157** to the appropriate in addition, the coupling **11150** can be pivotably mounted relative to the axis **L1**.

(516) In addition, the drum shaft **11153** has only the drive transmitting portion in the free end thereof and, the spherical surface portion for regulating the movement of the coupling **11150** and so on is unnecessary therefore, the processing of the drum shaft **11153** is easy.

(517) In addition, the rib **11157e** and the rib **11157p** are disposed offset. By this, as shown in FIG. **91(a)** and FIG. **91(b)**, the coupling **11150** is assembled into the bearing member **11157** in a slightly oblique direction (in the Figure **X12**) more particularly, the special method of assembling is unnecessary thereafter, the bearing member **11157** to which the coupling **11150** was mounted temporarily is assembled into the drum shaft **11153** (in the Figure the **X13** direction).

Embodiment 16

(518) Referring to FIG. **92**, the 16th embodiment of the present invention will be described.

(519) The point of difference of the present embodiment from Embodiment 1 is in the mounting method of the coupling. In Embodiment 1, the coupling is interposed between the free end portion and the retention rib of the drum shaft. On the contrary, in this embodiment, the retention of the coupling is effected by a rotational force transmitting pin (rotational force receiving member) **13155** of a drum shaft **13153**. More particularly, in this embodiment, a coupling **13150** is held by a pin **13155**.

(520) This will be described in more detail.

(521) FIG. **92** illustrates the coupling held at the end of the photosensitive drum **107** (cylindrical drum **107a**) a part of driving side of the photosensitive drum **107** is shown, and the others are omitted for simplicity.

(522) In FIG. **92(a)**, the axis **L2** is substantially co-axial relative to the axis **L1** in this state, a coupling **13150** receives a rotational force from a drive shaft **180** at a driven portion **13150a**. And, the coupling **13150** transmits the rotational force to the photosensitive drum **107**.

(523) And, as shown in FIG. **92(b)**, the coupling **13150** is mounted to a drum shaft **13153** so that it is pivotable in any direction relative to the axis **L1**. The configuration of the driven portion **13150a** may be the same as the configuration of the driven portion described with respect to FIG. **82**-FIG. **85** and, this photosensitive drum unit **U13** is assembled into the second frame in the manner described with respect to Embodiment 1. And, at the time of mounting and demounting the cartridge **B** relative to the apparatus main assembly **A**, the coupling is engageable and detachable relative to the drive shaft.

(524) The mounting method according to the present embodiment will be described. The free end (unshown) of the drum shaft **13153** is covered by the coupling **13150** thereafter, the pin (rotational force receiving member) **13155** is inserted into a hole (unshown) of the drum shaft **13153** in the direction perpendicular to the axis **L1**. In addition, the opposite ends of the pin **13155** outwardly project beyond an internal surface of a flange portion **13150j**. The pin **13155** is prevented from separating from the standby opening **13150g** by these settings. By this, it is not necessary to add a part for preventing the disengagement of the coupling **13150**.

(525) As mentioned above, according to the embodiment described above, the drum unit **U13** is constituted by the cylindrical drum **107a**, the coupling **13150**, the photosensitive drum **107**, the drum flange **13151**, the drum shaft **13153**, the drive transmission pin **13155**, and so on. However, the structure of the drum unit **U13** is not limited to this example.

(526) As means for inclining the axis **L2** to the pre-engagement angular position, immediately before the coupling engages with the drive shaft, the embodiment 3-embodiment 10 described until now can be employed.

(527) In addition, with respect to engagement and disengagement between the coupling and the drive shaft operated interrelatedly with the mounting and the dismounting of the cartridge, it is the same as that of Embodiment 1, and therefore, the description is omitted.

(528) In addition, as has been described with respect to Embodiment 1 (FIG. 31), the inclining direction of the coupling is regulated by the bearing member. By this, the coupling can be more assuredly engaged with the drive shaft.

(529) With the above-described structures, the coupling **13150** is a part of the photosensitive drum unit integral with the photosensitive drum. Therefore, at the time of the assembling, handling is easy, and therefore, the assembling property can be improved.

Embodiment 17

(530) Referring to FIG. 93, the 17th embodiment of the present invention will be described.

(531) The point that the present embodiment is different from Embodiment 1 is in the mounting method of the coupling. With respect to Embodiment 1, the coupling is mounted to the free end side of the drum shaft, so that, the axis **L2** is slantable in any direction relative to axis **L1**. On the contrary, in this embodiment, the coupling **15150** is directly mounted to the end of the cylindrical drum **107a** of the photosensitive drum **107**, so that it is slantable in any direction.

(532) This will be described in more detail.

(533) FIG. 93 shows an electrophotographic photosensitive member drum unit ("drum unit") **U**. A coupling **15150** is mounted to an end part of the photosensitive drum **107** (cylindrical drum **107a**) in this Figure. As for the photosensitive drum **107**, a part of driving side is shown and the others are omitted for the simplification.

(534) The axis **L2** is substantially co-axial relative to the axis **L1** in FIG. 93(a). In this state, the coupling **15150** receives a rotational force from the drive shaft **180** at a driven portion **15150a**. And, the coupling **15150** transmits the received rotational force to the photosensitive drum **107**.

(535) And, an example is shown in FIG. 93(b), wherein the coupling **15150** is mounted to the end part of the cylindrical drum **107a** of the photosensitive drum **107**, so that it is slantable in any direction. In this embodiment, one end of the coupling is mounted not to the drum shaft (projection) but into the recess (rotational force receiving member) provided at the end part of the cylinder **107a**. And, the coupling **15150** is pivotable also in any direction relative to the axis **L1**. As for the driven portion **15150a**, the configuration described with respect to Embodiment 1 is shown, but it may be a configuration of the driven portion of the coupling described in Embodiment 10 or Embodiment 11. And, as has been described with respect to Embodiment 1, this drum unit **U** is assembled into the second frame **118** (drum frame), and it is constituted as the detachably mountable cartridge to the apparatus main assembly.

(536) Thus, the drum unit **U** is constituted by the coupling **15150**, the photosensitive drum **107** (cylindrical drum **107a**), the drum flange **15151**, and so on.

(537) As for a structure for inclining the axis **L2** toward the pre-engagement angular position, immediately before the coupling **15150** engages with the drive shaft **180**, any of embodiment 3-embodiment 9 is usable.

(538) In addition, the engagement and disengagement between the coupling and the drive shaft which are operated interrelatedly with the mounting and the dismounting of the cartridge are the same as those of Embodiment 1. Therefore, the description is omitted.

(539) In addition, as has been described with respect to Embodiment 1 (FIG. 31), the drum bearing member is provided with regulating means for regulating inclining direction of the coupling relative to axis **L1**. By this, the coupling can be more assuredly engaged with the drive shaft.

(540) With this structure, the coupling can be slantably mounted without the drum shaft which was described heretofore in any direction relative to the photosensitive drum. Therefore, the cost reduction can be accomplished.

(541) In addition, according to the above structure, the coupling **15150** is a part of the drum units comprising the photosensitive drum as a unit. Therefore, in the cartridge, handling is easy at the time of the assembling, and the assembling property is improved.

(542) Referring to FIG. 94-FIG. 105, the present embodiment will further be described.

(543) FIG. 94 is a perspective view of the process cartridge **B-2** which uses the coupling **15150** of

the present embodiment. The outer periphery **15157a** of an outside end of a drum bearing member **15157** provided at the driving side functions as a cartridge guide **140R1**.

(544) In addition, in the one longitudinal end (driving side) of the second frame unit **120**, a cartridge guide **140R2** which outwardly projects is provided substantially above a cartridge guide **140R1** which outwardly projects.

(545) The process cartridge is supported detachably in the apparatus main assembly by these cartridge guides **140R1**, **1402** and a cartridge guide (unshown) provided at the non-driving side. More particularly, the cartridge B is moved to the apparatus main assembly A in the direction substantially perpendicular to the direction of the axis **L3** of the drive shaft **180**, when it is mounted to the apparatus main assembly A2 or is demounted from it.

(546) FIG. **95(a)** is a perspective view of the coupling, as seen from the driving side, FIG. **95(b)** is a perspective view of the coupling, as seen from the photosensitive drum side, and FIG. **95(c)** shows a view of the coupling, as seen from the direction perpendicular to the axis **L2**. FIG. **95(d)** is a side view of the coupling, as seen from the driving side, FIG. **95(e)** shows a view, as seen from the photosensitive drum side, and FIG. **95(f)** is a sectional view taken along S21-S21 of FIG. **95(d)**.

(547) The coupling **15150** is engaged with the drive shaft **180** in the state where the cartridge B is mounted to the set portion **130a** provided in the apparatus main assembly A. And, by removing the cartridge B from the set portion **103a**, it is disengaged from the drive shaft **180**. And, in the state where it engaged with the drive shaft **180**, the coupling **15150** receives the rotational force from the motor **186**, and transmits a rotational force to the photosensitive drum **107**.

(548) The coupling **15150** mainly comprises three portions (FIG. **95(c)**). A first portion is a driven portion (a portion to be driven) **15150a** which has a rotational force reception surface (rotational force receiving portion) **15150e** (**15150e1-15150e4**) for engaging with a drive shaft **180** and receiving a rotational force from a pin **182**. A second portion is a driving portion **15150b** which engages with a drum flange **15151** (pin **15155** (rotational force receiving member)), and transmits a rotational force. A third portion is a connecting portion **15150c** which connects the driven portion **15150a** and the driving portion **15150b**. The materials of these portions are resin materials, such as polyacetal, the polycarbonate, and PPS. However, in order to enhance rigidity of the member, the glass fiber, the carbon fiber, and so on may be mixed in the resin material depending on the required load torque. In addition, the rigidity may further be enhance (d) by inserting metal in the above described resin material, and the whole coupling may be made with the metal and so on. The driven portion **15150a** is provided with a drive shaft insertion opening portion **15150m** in the form of an expanded part which expands into a conical shape relative to the axis **L2** as shown in FIG. **95(f)**. The opening **15150m** constitutes a recess **15150z** as shown in the Figure.

(549) The driving portion **15150b** has a spherical driving shaft receiving surface **15150i**. The coupling **15150** can pivot between the rotational force transmitting angular position and the pre-engagement angular position (disengaging angular position) relative to the axis **L1** by the receiving surface **15150i**. By this, the coupling **15150** is engaged with the drive shaft **180** without being prevented by the free end portion **180b** of the drive shaft **180** irrespective of the rotation phase of the photosensitive drum **107**. The driving portion **15150b** has the convex configuration as shown in the Figure.

(550) And, a plurality of drive receiving projections **15150d1-d4** are provided on a circumference (phantom circle in FIG. **8 (d)** C1) of an end surface of the driven portion **15150a**. In addition, the spaces between the adjacent projections **15150d 1** or **15150d 2** or **15150d3** and **15150d4** function as drive receiving stand-by portions **15150k1**, **15150k2**, **15150k3**, **15150k4**. Each interval between the adjacent projections **15150d1-d4** are larger than the outer diameter of the pin **182**, so that the pin (rotational force applying portion) **182** is received these intervals are standing-by portions **15150k1-k4**. In addition, in FIG. **95(d)**, in the clockwise downstream of the projection **15150d**, the rotational force receiving surfaces (rotational force receiving portion) **15150e1-15150e4** facing faced in the direction crossing with the direction of the rotational movement of the coupling **15150**

is provided. When the drive shaft **180** rotates, the pin **182** abuts or contacts to one of the drive force receiving surfaces **15150e1-15150e4**. And, the drive force receiving facing **15150** is pushed by the side surface of the pin **182**, and rotates the coupling **15150** about the axis L2.

(551) In addition, the driving portion **15150b** has a spherical surface. The coupling **15150** can be pivoted between the rotational force transmitting angular position and the pre-engagement angular position (or disengaging angular position) by the provision of the spherical surface irrespective of the rotation phase of the photosensitive drum **107** in the cartridge B (swinging). In the illustrated example, spherical surface is a spherical drum bearing surface **15150i** which has its axis aligned with the axis L2. And, a hole **15150g** for penetration anchoring for the pin (rotational force transmitting portion) **15155** is formed through the center thereof.

(552) Referring to FIG. **96**, the description will be made as to an example of a drum flange **15151** which mounts the coupling **15150**. FIG. **96(a)** shows a view as seen from the drive shaft side, and FIG. **96(b)** is a sectional view taken along S22-S22 of FIG. **96 (a)**.

(553) The openings **15151g 1**, **15151g2** shown in FIG. **96(a)** are in the form of grooves extended in the circumferential direction of the flange **15151**. An opening **15151g3** is provided between the opening **15151g1** and the opening **15151g2**. At the time of mounting the coupling **15150** to the flange **15151**, the pin **15155** is accommodated in these openings **15151g 1**, **15151g2**. In addition, the drum bearing surface **15150i** is accommodated in the opening **15151g3**.

(554) With the above-described structures, irrespective of the rotation phase of the photosensitive drum **107** (irrespective of the stop position of the pin **15155**) in the cartridge B-2, the coupling **15150** is pivotable (swingable) between the rotational force transmitting angular position and the pre-engagement angular positions (or disengaging angular position).

(555) In addition, in FIG. **96(a)**, the rotational force transmission surfaces (rotational force receiving members) **15151h 1**, **15151h2** are provided in the clockwise upstream of the openings **15151g 1** or **15151g2**. And, the side surfaces of the rotational force transmitting pin (rotational force transmitting portion) **15155** of the coupling **15150** contact to the rotational force transmission surfaces **15151h 1**, **15151h2**. By this, a rotational force is transmitted from the coupling **15150** to the photosensitive drum **107**. Here, the transmitting surfaces **15151h 1-15151h2** are faced in the circumferential direction of the rotational movement of the flange **15151**. By this, the transmitting surfaces **15151h 1-15151h2** are pushed to the side surfaces of the pin **15155**. And, in the state of the axis L1 and the axis L2 being substantially co-axial, the coupling **15150** rotates about the axis L2.

(556) Here, the flange **15151** has a transmission receiving portion **15151h 1**, **15151h2**, and therefore, it functions as a rotational force receiving member.

(557) The retaining portion **15151i** shown in FIG. **96(b)** has the function of retaining the coupling **15150** to the flange **15151**, so that the coupling can pivot between the rotational force transmitting angular position and the pre-engagement angular positions (or disengaging angular position) in addition, it has the function of regulating the movement of the coupling **15150** in the direction of the axis L2. Therefore, the opening **15151j** has diameter $\Phi D15$ smaller than the diameter of the bearing surface **15150i**. Thus, the motion of the coupling is limited by the flange **15151**. Because of this, the coupling **15150** does not disengage from the photosensitive drum (cartridge).

(558) As has been shown in FIG. **96**, the driving portion **15150b** of the coupling **15150** is in engagement with the recess provided in the flange **15151**.

(559) FIG. **96(c)** is a sectional view which illustrates the process in which the coupling **15150** is assembled to the flange **15151**.

(560) The driven portion **15150a** and the connecting portion **15150c** are inserted in the direction X33 into the flange **15151**. In addition, the positioning member **15150p** (driving portion **15150b**) which has the bearing surface **15150i** is put in the direction of an arrow X32. The pin **15155** penetrates a fixing hole **15150g** of the positioning member **15150p**, and the fixing hole **15150r** of the connecting portion **15150c**. By this, the positioning member **15150p** is fixed to the connecting

portion **15150c**.

(561) FIG. **96(d)** shows a sectional view which illustrates the process in which the coupling **15150** is fixed to the flange **15151**.

(562) The coupling **15150** is moved in the X32 direction, so that the bearing surface **15150i** is brought into contact or proximity with the retaining portion **15151i**. The retaining portion material **15156** is inserted in the direction of the arrow X32, and it is fixed to the flange **15151**. The coupling **15150** is mounted to the flange **15151** with a play (gap) to the positioning member **15150p** in this mounting method. By this, the coupling **15150** can change the direction thereof.

(563) Similarly to the projection **15150d**, the rotational force transmission surfaces **15150h 1**, **15150h2** are desirably disposed diametrically opposed (180 degrees) on the same circumference.

(564) Referring to FIG. **97** and FIG. **98**, the structure of a photosensitive drum unit U3 will be described. FIG. **97(a)** is a perspective view of the drum unit, as seen from the driving side, and FIG. **97(b)** is a perspective view, as seen from the non-driving side. In addition, FIG. **98** is a sectional view taken along S23-S23 of FIG. **97(a)**.

(565) A drum flange **15151** mounted to the coupling **15150** is fixed to one end side of the photosensitive drum **107** (cylindrical drum **107a**), so that a transmission part **15150a** is exposed. In addition, the drum flange **152** of the non-driving side is fixed to the other end side of the photosensitive drum **107** (cylindrical drum **107a**). This fixing method is crimping, bonding, welding, or the like.

(566) And, in the state where the driving side is supported by the bearing member **15157** and the non-driving side is supported by the drum supporting pin (unshown), the drum unit U3 is rotatably supported by the second frame **118**. And, it is unified into the process cartridge by mounting the first frame unit **119** to the second frame unit **120** (FIG. **94**).

(567) Designated by **15151c** is a gear, and has a function of transmitting a rotational force received by the coupling **15150** from the drive shaft **180** to the developing roller **110**. The gear **15151c** is integrally molded with the flange **15151**.

(568) The drum unit U3 described in this embodiment comprises the coupling **15150**, the photosensitive drum **107** (cylindrical drum **107a**), and the drum flange **15151**. The peripheral surface of the cylindrical drum **107a** is coated with a photosensitive layer **107b**. In addition, the drum unit comprises the photosensitive drum coated with the photosensitive layer **107b**, and the coupling mounted to one end thereof. The structure of the coupling is not limited to the structure described in this embodiment. For example, it may have the structure described hereinbefore as the embodiments of the coupling. In addition, it may be another structure if it has the structure in which the effects of the present invention are provided.

(569) Here, as shown in FIG. **100**, the coupling **15150** is mounted so that it can incline in any direction relative to the axis L1 of the axis L2 thereof. FIGS. **100(a1)-(a5)** are views as seen from the drive shaft **180**, and FIGS. **100(b1)-(b5)** are perspective views thereof. FIGS. **100(b1)-(b5)** is partly broken views of substantially the entirety of the coupling **15150**, wherein a part of a flange **15151** is cut away for better illustration.

(570) In FIGS. **100(a1) (b1)**, the axis L2 is co-axially positioned relative to the axis L1. When the coupling **15150** is inclined upward from this state It is in the state shown in FIGS. **100(a2) (b2)**. As shown in this Figure, when the coupling **15150** inclines toward an opening **15151g** A pin **15155** is moved along the opening **15151g**. As a result, the coupling **15150** is inclined about the axis AX perpendicular to the opening **15151g**.

(571) The coupling **15150** is inclined rightward in FIG. **100(a3) (b3)**. As shown in this Figure, when the coupling **15150** inclines in the orthogonal direction of the opening **15151g**, it rotates in the opening **15151g**. The pin **15155** rotates about the axis line AY of the pin **15155**.

(572) The state where the coupling **15150** is inclined leftward and the state where it is inclined downward are shown in FIGS. **100(a4) (b4)** and **100 (a5) (b5)**. Since the description of the rotation axis AX, AY has been made in the foregoing, the description therefor is omitted for simplicity.

(573) the rotation in the direction different from these inclining directions, for example, 45-degree rotation shown in FIG. **100(a1)**, is provided by a combination of the rotations around the rotation axes AX, AY. In this manner, the axis L2 can be inclined in any directions relative to the axis L1.

(574) The opening **15151g** is extended in the direction crossing with the projection direction of the pin **15155**.

(575) In addition, between the flange (rotational force receiving member) **15151** and the coupling **15150**, a gap is provided as shown in the Figure. With this structure, as has been described hereinbefore, the coupling **15150** is pivotable in all the directions.

(576) More particularly, the transmitting surfaces (rotational force transmitting portions) **15151h** (**15151h1**, **15151h2**) are in the operative positions relative to the pins **15155** (the rotational force transmitting portion). The pin **15155** is movable relative to the transmitting surface **15151h**. The transmitting surface **15151h** and the pin **15155** are engaged or abutted to each other. To accomplish this motion, a gap is provided between the pin **15155** and the transmitting surface **15155h**. By this, the coupling **15150** is pivotable relative to the axis L1 in all directions. In this manner, the coupling **15150** is mounted to the end of the photosensitive drum **107**.

(577) The axis L2 has been mentioned as being pivotable in any direction relative to the axis L1. However, the coupling **15150** does not necessarily need to be linearly pivotable to the predetermined angle over the 360-degree range. This is applied to all the couplings described as the embodiments in the foregoing.

(578) In this embodiment, the opening **15151g** is formed slightly overwidely in the circumferential direction. With this structure, when the axis L2 inclines relative to the axis L1, even if it is the case where it cannot incline to the predetermined angle linearly, the coupling **15150** can incline to the predetermined angle by rotating to a slight degree about the axis L2 in other words, the play of the opening **15151g** in the rotational direction is selected properly in view of this, if necessary.

(579) In this manner, the coupling **15150** is pivotable in all the directions substantially. Therefore, the coupling **15150** is revolvable (pivotable) over the full-circumference substantially relative to the flange **15151**.

(580) As has been described hereinbefore, (FIG. **98**), the spherical surface **15150i** of the coupling **15150** contacts to the retaining portion (a part of recess) **15151i**. Therefore, the center P2 of the spherical surface **15150i** aligns with the rotation axis, and the coupling **15150** is mounted. More particularly, the axis L2 of the coupling **15150** is pivotable irrespective of the phase of the flange **15151**.

(581) In addition, in order for the coupling **15150** to engage with the drive shaft **180**, the axis L2 is inclined toward the downstream with respect to the mounting direction of the cartridge B-2 relative to the axis L1 just before the engagement. More particularly, as shown in FIG. **101**, the axis L2 is inclined relative to the axis L1, so that the driven portion **15150a** is the downstream with respect to the mounting direction X4. In FIGS. **101(a)-(c)**, the position of the driven portion **15150a** is downstream with respect to the mounting direction X4, in any case.

(582) FIG. **94** illustrates the state where the axis L2 is inclined relative to the axis L1. In addition, FIG. **98** is a sectional view taken along S24-S24 of FIG. **94**. As shown in FIG. **99**, by the structure described heretofore, from the state of the axis L2 being inclined, it can change to the state of being substantially parallel to the axis L1. In addition, the maximum possible inclination angle $\alpha 4$ (FIG. **99**) between the axis L1 and the axis L2 is the angle at the time of inclining until the driven portion **15150a** or the connecting portion **15150c** contacts with the flange **15151** or the bearing member **15157**. This inclination angle is the value required for engagement and disengagement relative to the drive shaft of the coupling at the time of mounting and demounting the cartridge relative to the apparatus main assembly.

(583) Immediately before or simultaneously with the cartridge B being set at the predetermined position of the apparatus main assembly A, the coupling **15150** and the drive shaft **180** engage with each other. Referring to FIG. **102** and FIG. **103**, the description will be made with respect to the

engaging operation of this coupling **15150**. FIG. **102** is a perspective view which illustrates the major parts of the drive shaft and driving side of the cartridge. FIG. **103** is a longitudinal sectional view, as seen from the lower part of the apparatus main assembly.

(584) In the mounting process of the cartridge B, as shown in FIG. **102**, the cartridge B is mounted into the apparatus main assembly A in the direction (the direction of the arrow X4) substantially perpendicular to the axis L3. The axis L2 of the coupling **15150** inclines to the downstream with respect to the mounting direction X4 relative to the axis L1 beforehand (pre-engagement angular position) (FIG. **102(a)**, FIG. **103(a)**). By this inclination of the coupling **15150**, with respect to the direction of the axis L1, the free end position **15150A1** is closer to the photosensitive drum **107** than the shaft free-end **180b3** with respect to the direction of the axis L1. In addition, the free end position **15150A2** is closer to the pin **182** than the shaft free-end **180b3** with respect to the direction of the axis L1 (FIG. **103(a)**).

(585) First, the free end position **15150A1** passes by the drive shaft free-end **180b3**. Thereafter, the driving shaft receiving surface **150f** of conical shape or the driven projection **150d** contacts to the free end portion **180b** of the drive shaft **180**, or the rotational force drive transmission pin **182**. Here, the receiving surface **150f** and/or the projection **150d** are the contact portions of the cartridge side. In addition, the free end portion **180b** and/or the pin **182** are the engaging portions of the main assembly side. And, in response to the movement of the cartridge B, the coupling **15150** is inclined so that the axis L2 becomes substantially co-axial with the axis L1 (FIG. **103(c)**). And, when the position of the cartridge B is finally determined relative to the apparatus main assembly A, the drive shaft **180** and the photosensitive drum **107** are substantially co-axial. More particularly, in the state of the contact portion of the cartridge side contacting with the engaging portion of the main assembly side, in response to the insertion toward the back side of the apparatus main assembly A of the cartridge B, the coupling **15150** is pivoted to the rotational force transmitting angular position from the pre-engagement angular position, so that the axis L2 becomes substantially co-axial with the axis L1. And, the coupling **15150** and the drive shaft **180** are engaged with each other (FIG. **102(b)**, FIG. **103(d)**).

(586) As has been described hereinbefore, the coupling **15150** is mounted for inclining motion relative to the axis L1. And, it can be engaged with the drive shaft **180** by the pivoting of the coupling **15150** corresponding to the mounting operation of the cartridge B.

(587) In addition, similarly to Embodiment 1, the engaging operation of the coupling **15150** described above can be carried out regardless of the phase of the drive shaft **180** and the coupling **15150**.

(588) In this manner, according to the present embodiment, the coupling **15150** is mounted for revolving or whirling motion (swinging) around the axis L1 substantially. The motion illustrated in FIG. **103** may include the whirling motion.

(589) Referring to FIG. **104**, the description will be made about the rotational force transmitting operation at the time of rotating the photosensitive drum **107**. The drive shaft **180** rotates with the drum driving gear **181** in the direction of X8 in the Figure by the rotational force received from the motor **186**. The gear **181** is a helical gear and the diameter thereof is the approx. 80 mm. And, the pin **182** integral with the drive shaft **180** contacts to any two of receiving surfaces **150e** (four places) (rotational force receiving portions) of the coupling **15150**. And, the coupling **15150** rotates by the pin **182** pushing the receiving surface **150e**. In addition, in the coupling **15150**, the rotational force transmitting pin **15155** (coupling side engaging portion, rotational force transmitting portion) contacts to the rotational force transmission surface (rotational force receiving member) **15151h1**, **15151h2**. By this, the coupling **15150** is coupled, for transmission of driving force, with the photosensitive drum **107**. Therefore, the photosensitive drum **107** rotates through the flange **15151** by the rotation of the coupling **15150**.

(590) In addition, when the axis L1 and the axis L2 are deviated to a slight degree, the coupling **15150** inclines a little. By this, the coupling **15150** can rotate without applying large load to the

photosensitive drum **107** and the drive shaft **180**. Therefore, at the time of assembling the drive shaft **180** and the photosensitive drum **107**, no precise adjustment is necessary. Therefore, the manufacturing can be reduced.

(591) Referring to FIG. **105**, the description will be made as to the dismounting operation of the coupling **15150** at the time of taking out the process cartridge B-2 from the apparatus main assembly A. FIG. **105** is a longitudinal sectional view, as seen from the lower part of the apparatus main assembly. When the cartridge B is demounted from the apparatus main assembly A as shown in FIG. **105**, it is moved in the direction (the direction of the arrow X6) substantially perpendicular to the axis L3. First, similarly to embodiment 1, at the time of demounting the cartridge B-2, the drive transmission pin **182** of the drive shaft **180** is positioned in any two of standing-by portions **15150k1-15150k4** (Figure).

(592) After the drive of the photosensitive drum **107** stops, the coupling **15150** takes the rotational force transmitting angular position, wherein the axis L2 is substantially co-axial with the axis L1. And, when the cartridge B moves toward the front side of the apparatus main assembly A (the dismounting direction X6), the photosensitive drum **107** is moved toward the front side. In response to this movement, shaft receiving surface **15150f** or the projection **15150d** in the upstream with respect to the dismounting direction of the coupling **15150** contacts at least to the free end portion **180b** of the drive shaft **180** (FIG. **105a**). And, the axis L2 begins (FIG. **105(b)**) to incline upstream with respect to the dismounting direction X6. This inclining direction is the same as the inclination of the coupling **15150** at the time of the mounting of the cartridge B. By the dismounting operation of this cartridge B, the cartridge B is moved while the upstream free end portion **15150 A3** with respect to the dismounting direction X6 contacts to the free end portion **180b**. And, the coupling **15150** is inclined until the upstream free end portion **15150 A3** reaches to the drive shaft free-end **180b3** (FIG. **105(c)**). The angular position of the coupling **15150** in this case is the disengaging angular position. And, in this state, the coupling **15150** is passed by the drive shaft free-end **180b3**, contacting with the drive shaft free-end **180b3** (FIG. **105(d)**). Thereafter, the cartridge B-2 is taken out of the apparatus main assembly A.

(593) As has been described hereinbefore, the coupling **15150** is mounted for pivoting motion relative to the axis L1. And, the coupling **15150** can be disengaged from the drive shaft **180** by the coupling **15150** pivoting correspondingly to the dismounting operation of the cartridge B-2.

(594) The motion illustrated in FIG. **105** may include the whirling motion.

(595) With the structure as described above, the coupling **15150** is integral part of the photosensitive drum as the photosensitive drum unit. Therefore, at the time of the assembling, handling is easy and the assembling property is improved.

(596) In order to incline the axis L2 to the pre-engagement angular position immediately before the coupling **15150** engages with the drive shaft **180**, any one of structures of the embodiment 3-embodiment 9 is usable.

(597) In addition, in this embodiment, it has been described that the drum flange of the driving side is a separate member from the photosensitive drum. However, the present invention is not limited to such an example. In other words, the rotational force receiving portion may be directly provided on the cylindrical drum, not on the drum flange.

Embodiment 18

(598) Referring to FIG. **106**, FIG. **107**, and FIG. **108**, the 18th embodiment of the present invention will be described.

(599) The present embodiment is a modified example of the coupling described in Embodiment 17. The configurations of the drum flange and retaining member of the driving side differ in Embodiment 17. In any case, the coupling is pivotable in the given direction irrespective of the phase of the photosensitive drum. In addition, the structure for mounting of the photosensitive drum unit to the second frame as will be described below is the same as that of the foregoing embodiment, and therefore, the description is omitted.

(600) FIGS. **106(a)** and **(b)** illustrate a first modified example of the photosensitive drum unit. In FIGS. **106(a)** and **(b)**, since the photosensitive drum and the non-driving side drum flange are the same as those of Embodiment 16, these are not illustrated.

(601) More particularly, the coupling **16150** is provided with a supporting portion **16150p** of a ring shape which is pierced by the pin **155**. The edge lines **16150p1**, **16150p2** of the peripheral part of the supporting portion **16150p** are equidistant from the axis of the pin **155**.

(602) And, an inner periphery of the drum flange (rotational force receiving member) **16151** constitutes a spherical surface portion **16151i** (recess). A center of the spherical surface portion **16151i** is disposed on the axis of the pin **155**. In addition, a slot **16151u** is provided and this is the hole which extends in the direction of the axis **L1**. By the provision of this hole, the pin **155** is not interfered when the axis **L2** inclines.

(603) In addition, a retaining member **16156** is provided between the driven portion **16150a** and the supporting portion **16150p**. And, the portion opposed to the supporting portion **16150p** is provided with the spherical surface portion **16156a**. Here, the spherical surface portion **16156a** is concentric with the spherical surface portion **16151i**. In addition, a slot **16156u** is disposed so that it is continuous with the slot **16151u** in the direction of the axis **L1**. Therefore, when the axis **L1** pivots, the pin **155** can move the inside of the slots **16151u**, **16156u**.

(604) And, the drum flange, the coupling, and the retaining member for these driving side structures are mounted to the photosensitive drum. By this, the photosensitive drum unit is constituted.

(605) With the structure as described above, when the axis **L2** is inclined, the edge lines **16150p1**, **16150p2** of the supporting portion **16150p** move along the spherical surface portion **16151i** and the spherical surface portion **16156a**. By this, similarly to the foregoing embodiment, the coupling **16150** can be inclined assuredly.

(606) In this manner, the supporting portion **16150p** is pivotable relative to the spherical surface portion **16151i** that is, the suitable gap is provided between the flange **16151** and the coupling **16150**, so that the coupling **16150** is swingable.

(607) Therefore, the effects similar to the effects described in Embodiment 17 are provided.

(608) FIGS. **107(a)** and **(b)** illustrate a second modified example of the photosensitive drum unit. In FIGS. **107(a)** and **(b)**, since the photosensitive drum and the non-driving side drum flange are the same as those of Embodiment 17, the illustration is omitted.

(609) More particularly, similarly to Embodiment 17, a coupling **17150** is provided with a spherical supporting portion **17150p** which has an intersection between axis of the pin **155**, and axis **L2** as the center substantially.

(610) A drum flange **17151** is provided with a conical portion **17151i** contacted on the surface of the supporting portion **17150p** (recess).

(611) In addition, a retaining member **17156** is provided between the driven portion **17150a** and the supporting portion **17150p**. In addition, an edge line portion **17156a** contacts with the surface of the supporting portion **17150p**.

(612) And, the structure (the drum flange, coupling, and retaining member) of this driving side is mounted to the photosensitive drum. By this, the photosensitive drum unit is constituted.

(613) With the structure as described above, when the axis **L2** inclines, the supporting portion **17150p** becomes movable along the conical portion **17151i** and the edge line **17156a** of retaining member. By this, the coupling **17150** can be inclined assuredly.

(614) As described above, the supporting portion **17150p** is pivotable (swingable) relative to the conical portion **17151i**. Between the flange **17151** and the coupling **17150**, a gap is provided in order to permit the pivoting of the coupling **17150**. Therefore, the effects similar to the effects described in Embodiment 17 are provided.

(615) FIGS. **108(a)** and **(b)** illustrate a third modified example of the photosensitive drum unit **U7**. The photosensitive drum and the non-driving side drum flange are the same as that of Embodiment

17 in the modified example of FIGS. **108(a)** and **(b)**, and therefore, the illustration is omitted.

(616) More particularly, they are disposed co-axially with the rotation axis of a pin **20155**. In addition, a coupling **20150** has a flat surface portion **20150r** perpendicular to the axis **L2**. In addition, it is provided with a semi-spherical supporting portion **20150p** which has an intersection between axis of a pin **20155** and the axis **L2** as the center substantially.

(617) The flange **20151** is provided with the conical portion **20151i** which has an apex **20151g** on the axis thereof. The apex **20151g** is contacted with the flat surface portion **20150r** of the coupling.

(618) In addition, a retaining member **20156** is provided between the driven portion **20150a** and the supporting portion **20150p**. In addition, an edge line portion **20156a** contacts with a surface of the supporting portion **20150p**.

(619) And, the structure (the drum flange, coupling, and retaining member) of this driving side is mounted to the photosensitive drum. By this, the photosensitive drum unit is constituted.

(620) With the structure as described above, even if the axis **L2** inclines, the coupling **20150** and the flange **20151** are always in contact to each other substantially at the one point. Therefore, the coupling **20150** can be inclined assuredly.

(621) As described above, the flat surface portion **20150r** of the coupling is swingable relative to the conical portion **20151i**. Between the flange **20151** and the coupling **20150**, in order to permit the swinging of the coupling **17150**, a gap is provided.

(622) The effects described above can be provided by constituting the photosensitive drum unit in this manner.

(623) As means for inclining the coupling to the pre-engagement angular position, any one of the structures of Embodiment 3 to the embodiment 9 is used.

Embodiment 19

(624) Referring to FIG. **109**, FIG. **110**, and FIG. **111**, the 19th embodiment of the present invention will be described.

(625) The point in which the present embodiment is different from Embodiment 1 is the mounting structure of the photosensitive drum, and rotational force transmission structure from the coupling to the photosensitive drum.

(626) FIG. **109** is a perspective view which illustrates a drum shaft and a coupling. FIG. **111** is a perspective view of a second frame unit, as seen from the driving side. FIG. **110** is a sectional view taken along **S20-S20** of FIG. **111**.

(627) In this embodiment, the photosensitive drum **107** is supported by a drum shaft **18153** extended from a driving side of a second frame **18118** to a non-driving side thereof. By this, a position of the photosensitive drum **107** can further accurately be determined. This will be described more in the detail.

(628) The drum shaft (rotational force receiving member) **18153** supports a positioning hole **18151g**, **18152g** of flanges **18151** and **18152** at the opposite ends of the photosensitive drum **107**. In addition, the drum shaft **18153** rotates integrally with the photosensitive drum **107** by a drive transmitting portion **18153c**. In addition, the drum shaft **18153** is rotatably supported by the second frame **18118** through bearing members **18158** and **18159** in the neighborhood of the opposite ends thereof.

(629) A free end portion **18153b** of the drum shaft **18153** has the same as configuration as the configuration described with respect to Embodiment 1. More particularly, the free end portion **18153b** has a spherical surface and its drum bearing surface **150f** of the coupling **150** is slidable along the spherical surface. By doing so, the axis **L2** is pivotable in any direction relative to the axis **L1**. In addition, the disengagement of the coupling **150** is prevented by the drum bearing member **18157**. And, they are unified as the process cartridge by connecting a first frame unit (unshown) with the second frame **18118**.

(630) And, the rotational force is transmitted from the coupling **150** through a pin (rotational force receiving member) **18155** to the photosensitive drum **107**. The pin **18155** is through the center of

the free end portion (spherical surface) **18153** of the drum shaft.

(631) In addition, the coupling **150** is prevented by the drum bearing member **18157** from disengagement.

(632) The engagement and disengagement between the coupling and the apparatus main assembly in interrelation with the mounting and dismounting operations of the cartridge are the same as that of Embodiment 1, and therefore, the description is omitted.

(633) As for the structure for inclining the axis L2 toward the pre-engagement angular position, any one of the structures of the embodiment 3-embodiment 10 is usable.

(634) In addition, the structure described with respect to Embodiment 1 as to the configuration at the free end of the drum shaft can be used.

(635) In addition, as has been described with respect to Embodiment 1 (FIG. 31), the inclining direction of the coupling relative to the cartridge is regulated by the drum bearing member. By this, the coupling can be more assuredly engaged with the drive shaft.

(636) The structure will not be limited, if the rotational force receiving portion is provided to the end part of the photosensitive drum, and it rotates integrally with the photosensitive drum. For example, it may be provided on the drum shaft provided at the end part of the photosensitive drum (cylindrical drum) as has been described with respect to Embodiment 1. Or, as has been described in this embodiment, it may be provided at the end part of the drum penetrating shaft which is through the photosensitive drum (cylindrical drum). Further alternatively, as has been described with respect to Embodiment 17, it may be provided on the drum flange provided at the end part of the photosensitive drum (cylindrical drum).

(637) The engagement (coupling) between the drive shaft and the coupling means the state where the coupling is abutted to or contacted to the drive shaft and/or the rotational force applying portion in addition, in addition, it means that when the drive shaft in addition, starts the rotation to the meaning, the coupling abuts to or contacts to the rotational force applying portion and the rotational force can be received from the drive shaft.

(638) In the embodiments described above, as for alphabetical suffixes of the referential signs in the coupling, the same alphabetical suffixes are assigned to the members which have the corresponding functions.

(639) FIG. 112 is a perspective view of a photosensitive drum unit U according to an embodiment of the present invention.

(640) In the Figure, the photosensitive drum **107** is provided with a helical gear **107c** at the end which has the coupling **150**. The helical gear **107c** transmits the rotational force which the coupling **150** receives from the apparatus main assembly A to the developing roller (process means) **110**. This structure is applied to the drum unit U3 shown in FIG. 97.

(641) In addition, the photosensitive drum **107** is provided with a gear **107d** at the end opposite from the end which has the helical gear **107c**. In this embodiment, this gear **107d** is a helical gear. The gear **107d** transmits the rotational force which the coupling **150** receives from the apparatus main assembly A to the transfer roller **104** (FIG. 4) provided in the apparatus main assembly A.

(642) In addition, the charging roller (process means) **108** contacts over the longitudinal range to the photosensitive drum **107**. By this, the charging roller **108** rotates with the photosensitive drum **107**. The transfer roller **104** may be contacted to the photosensitive drum **107** over the longitudinal range thereof. By this, the transfer roller **104** may be rotated by the photosensitive drum **107**. In this case, the gear for the rotation of the transfer roller **104** is unnecessary.

(643) In addition, as shown in FIG. 98, the photosensitive drum **107** is provided with a helical gear **15151c** at the end which has the coupling **15150**. The gear **15151c** transmits the rotational force received by the coupling **15150** from the apparatus main assembly A to the developing roller **110** and, with respect to the direction of the axis L1 of the photosensitive drum **107**, the position in which the gear **15151c** is provided, and the position in which the rotational force transmitting pin (rotational force transmitting portion) **15150h1, h2** is provided overlap relative to each other (the

overlapping position is shown by **3** in FIG. **98**).

(644) In this manner, the gear **15151c** and the rotational force transmitting portion overlap relative to each other with respect to the direction of the axis **L1**. By this, the force tending to deform the cartridge frame **B1** is reduced. In addition, the length of the photosensitive drum **107** can be reduced.

(645) The couplings of the embodiments described above can apply to this drum unit.

(646) Each coupling described above has the following structure.

(647) The coupling (for example, the couplings **150**, **1550**, **1750**, and **1850**, **3150**, **4150**, **5150**, **6150**, **7150**, **8150**, **1350**, **1450**, **11150**, **12150**, **12250**, **12350**, **13150**, **14150**, **15150**, **16150**, **17150**, **20150**, **21150**, and so on) engages with the rotational force applying portion (for example, the pins **182**, **1280**, **1355**, **1382**, **9182** and so on) provided in the apparatus main assembly **A**. And, the coupling receives the rotational force for rotating the photosensitive drum **107**. In addition, this each coupling is pivotable between the rotational force transmitting angular position for transmitting the rotational force for rotating the photosensitive drum **107** by engaging with the rotational force applying portion to the photosensitive drum **107**, and the disengaging angular position inclined in the direction away from the axis **L1** of the photosensitive drum **107** from the rotational force transmitting angular position. In addition, at the time of demounting the cartridge **B** from the apparatus main assembly **A** in the direction substantially perpendicular to the axis **L1**, the coupling is pivoted from the rotational force transmitting angular position to the disengaging angular position.

(648) As described in the foregoing, the rotational force transmitting angular position and the disengaging angular portion may be the same or equivalent to each other.

(649) In addition, at the time of mounting the cartridge **B** to the apparatus main assembly **A**, the operation is as follows. The coupling is pivoted from the pre-engagement angular position to the rotational force transmitting angular position in response to moving the cartridge **B** in the direction substantially perpendicular to the axis **L1**, so as to permit the part of the coupling (for example, the portion at the downstream free end position **A1**) positioned in the downstream with respect to the direction in which the cartridge **B** is mounted to the apparatus main assembly **A** to circumvent the drive shaft. And, the coupling is positioned at the rotational force transmitting angular position.

(650) The substantial perpendicularity has been explained hereinbefore.

(651) The coupling member has a recess (for example **150z**, **12150z**, **12250z**, **14150z**, **15150z**, **21150z**) in which a rotational axis **L2** the coupling member extends through a center of the shape defining the recess. The recess is over a free end of the driving shaft (for example, **180**, **1180**, **1280**, **1380**, **9180**) in the state in which the coupling member is positioned at the rotational force transmitting angular position. The rotating force receiving portion (for example rotating force receiving surface **150e**, **9150e**, **12350e**, **14150e**, **15150e**) is projected from a portion adjacent the driving shaft in the direction perpendicular to the axis **L3** and is engageable or abutable to the rotating force applying portion in the rotational direction of the coupling. By doing so, the coupling receives the rotating force from the driving shaft thereby to rotate. When the process cartridge is dismounted from the main assembly of the electrophotographic image forming apparatus, the coupling member pivots from the rotational force transmitting angular position to the disengaging angular position so that part (upstream end portion **150A3**, **1750A3**, **14150A3**, **15150A3** with respect to the dismounting direction) of the coupling member circumvents the driving shaft in response to movement of the process cartridge in the direction substantially perpendicular to the axis of the electrophotographic photosensitive drum. By doing so, the coupling is disengaged from the driving shaft.

(652) A plurality of such rotational force receiving portions are provided on a phantom circle **C1** (FIG. **8**, (d), FIG. **95(d)**) having a center **0** (FIGS. **8**, (d), FIG. **95(d)**) on the rotational axis of the coupling member at positions substantially diametrically opposite to each other.

(653) The recess of the coupling has an expanding portion (for example, FIGS. **8**, **29**, **33**, **34**, **36**,

47, 51, 54, 60, 63, 69, 72, 82, 83, 90, 91, 92, 93, 106, 107 108). A plurality of the rotational force receiving portions are provided at regular intervals along a rotational direction of the coupling member. The rotating force applying portion (for example, **182a, 182b**) is projected at each of two positions and is extended in the direction perpendicular to the axis of the driving shaft. One of the rotating force receiving portions is engaged to one of the two rotating force applying portions. The other one of the rotating force receiving portions which is opposed to the one of the rotating force receiving portion is engaged to the other one of the two rotating force applying portions. By doing so, the coupling receives the rotating force from the driving shaft thereby to rotate. With such a structure, the rotating force can be transmitted to the photosensitive drum by the coupling.

(654) The expanding portion has a conical shape. The conical shape has an apex on the rotational axis of the coupling member, and in the state in which coupling member is positioned at the rotational force transmitting angular position, the apex is opposed to the free end of the driving shaft. The coupling member is over the free end of the driving shaft when the rotational force is transmitted to the coupling member. With such a structure, the coupling can engage (connect) with the driving shaft projected in the main assembly of the apparatus with overlapping with respect to the direction of axis L2. Therefore, the coupling can engage with the driving shaft with stability.

(655) The free end portion of the coupling covers the free end of the driving shaft. Therefore, the coupling may be easily disengaged from the driving shaft. The coupling can receive the rotating force with high accuracy from the driving shaft.

(656) The coupling having the expanding portion and therefore the driving shaft can be cylindrical. Because of this, the machining of the driving shaft is easy.

(657) The coupling has the expanding portion of a conical shape, so that above-described effects can be enhanced.

(658) When the coupling is in the rotational force transmitting angular position, the axis L2 and the axis L1 are substantially coaxial. In the state in which coupling member is positioned at the disengaging angular position, the rotational axis of the coupling member is inclined relative to the axis of the electrophotographic photosensitive drum so as to permit an upstream portion of the coupling member passes by the free end of the driving shaft in a removing direction in which the process cartridge is dismounted from the main assembly of the electrophotographic image forming apparatus. The coupling member includes a rotating force transmitting portion (for example, **150h, 1550h, 9150h, 14150h, 15150h**) for transmitting the rotating force to the electrophotographic photosensitive drum, and a connecting portion (for example, **7150c** between the rotating force receiving portion and the rotating force transmitting portion, wherein the rotating force receiving portion, the connecting portion, the rotating force transmitting portion are arranged along the rotational axis direction. When the process cartridge is moved in the direction substantially perpendicular to the driving shaft, the pre-engagement angular position is provided by the connecting portion contacting a fixed portion (guide rib (contact portion) **7130R1a**) provided in the main assembly of the electrophotographic image forming apparatus.

(659) The cartridge B comprises a maintaining member (locking member **3159**, urging member **4159a, 4159b**, locking member **5157k**, magnet member **8159**) for maintaining the coupling member at the pre-engagement angular position, wherein the coupling member is maintained at the pre-engagement angular position by a force exerted by the maintaining member. The coupling is positioned at the pre-engagement angular position by the force of the maintaining member. The maintaining member may be an elastic member (urging member **4159a, 4159b**). By the elastic force of the elastic member, the coupling is maintained at the engagement angle position. The maintaining member may be a friction member (locking member **3159**). By the frictional force of the friction member, the coupling is maintained at the engagement angle position. The maintaining member may be a locking member (locking member **5157k**). The maintaining member may be a magnetic member (portion **8159**) provided on the coupling. By the magnetic force of the magnetic member, the coupling is maintained at the engagement angle position.

(660) The rotating force receiving portion is engaged with the rotating force applying portion which is rotatable integrally with the driving shaft. The rotating force receiving portion is engageable to the rotating force applying portion integrally rotatable with the driving shaft, wherein when the rotating force receiving portion receives the driving force for rotating the coupling member, and the rotating force receiving portion is inclined in a direction to receive a force toward the driving shaft. By the attracting force, the coupling is assured to contact the free end of the driving shaft. Then, the position of the coupling with respect to the direction of axis L2 relative to the driving shaft. When the photosensitive drum **107** is also attracted, the position of the photosensitive drum **107** is determined relative to the main assembly of the apparatus with respect to the direction of the axis L1. The pulling force may be properly set by one skilled in the art.

(661) The coupling member is provided to an end of the electrophotographic photosensitive drum and is capable of tilting relative to the axis of the electrophotographic photosensitive drum substantially in all directions. By doing so, the coupling can pivot smoothly between the pre-engagement angular position and the rotational force transmitting angular position and between the rotational force transmitting angular position and the disengaging angular position.

(662) Substantially all directions is intended to mean that coupling can pivot to the rotational force transmitting angular position irrespective of the phase at which the rotating force applying portion stops.

(663) In addition, the coupling can pivot to the disengaging angular position irrespective of the phase at which the rotating force applying portion stops.

(664) A gap is provided between the rotating force transmitting portion (for example, **150h**, **1550h**, **9150h**, **14150h**, **15150h**) and the rotating force receiving member for example, pin **155**, **1355**, **9155**, **13155**, **15155**, **15151h**) so that coupling member is capable of tilting relative to the axis of the electrophotographic photosensitive drum substantially in all directions, wherein the rotating force transmitting portion is provided at an end of the electrophotographic photosensitive drum and is movable relative to the rotating force receiving member, and the rotating force transmitting portion and the rotating force receiving member are engageable to each other in a rotational direction of the coupling member. The coupling is mounted to the end of the drum in this manner. The coupling is capable of inclination substantially in all directions relative to the axis L1.

(665) The main assembly of the electrophotographic image forming apparatus includes an urging member (for example, slider **1131**) movable between an urging position and a retracted position retracted from the urging position. When the process cartridge is mounted to the main assembly of the electrophotographic image forming apparatus, the coupling member moves to the pre-engagement angular position by being urged by an elastic force of the urging member restoring to the urging position after being temporarily retracted to the retracted position by being contacted by the process cartridge. With this structure, even if the connecting portion is retarded by friction, the coupling can be assuredly pivoted to the pre-engagement angular position.

(666) The photosensitive drum unit comprises the following structures. The photosensitive drum unit (U, U1, U3, U7, U13) is mountable to and dismountable from the main assembly of the electrophotographic image forming apparatus in a direction substantial perpendicular with an axial direction of the driving shaft. The drum unit has an electrophotographic photosensitive drum having a photosensitive layer (**107b**) at a peripheral surface thereof, the electrophotographic photosensitive drum being rotatable about an axis thereof. It also includes a coupling for engagement with the rotating force applying portion and for receiving the rotating force for rotating the photosensitive drum **107**. The coupling may have the structures described in the foregoing.

(667) The drum unit is mounted into the cartridge. By the cartridge being mounted to the main assembly of the apparatus, the drum unit may be mounted to the main assembly of the apparatus.

(668) The cartridge (B, B2) has the following structures.

(669) The cartridge is mountable to and dismountable from the main assembly of the apparatus in the direction substantial perpendicular to the axial direction of the driving shaft. The cartridge

comprises a drum having a photosensitive layer (107b) at a peripheral surface thereof, the electrophotographic photosensitive drum being rotatable about an axis thereof. It further comprises process means actable on the photosensitive drum 107 (for example, cleaning blade 117a, charging roller 108, and developing roller 100). It further comprises the coupling for receiving the rotating force for rotating the drum 107 through engagement with the rotating force applying portion. The coupling may have the structures described in the foregoing.

(670) The electrophotographic image forming apparatus can be loaded by the drum unit.

(671) The electrophotographic image forming apparatus can be loaded by the process cartridge.

(672) The axis L1 is an axis of rotation of the photosensitive drum.

(673) The axis L2 is an axis of rotation of the coupling.

(674) The axis L3 is an axis of rotation of the driving shaft.

(675) The whirling motion is not a motion with which the coupling itself rotates about the axis L2, but the inclined axis L2 rotates about the axis L1 of the photosensitive drum, although the whirling here does not preclude the rotation of the coupling per se about the axis L2 of the coupling 150.

OTHER EMBODIMENTS

(676) The mounting-and-demounting path extends in slanted or non-slanted up-down direction relative to the drive shaft of the apparatus main assembly in the embodiment described above. However, the present invention is not limited to such examples. The embodiments can suitably be applied to the process cartridge which can be mount and demounted in the direction perpendicular to the drive shaft depending on the structure of the apparatus main assembly, for example.

(677) In addition, in the embodiment described above, although the mounting path is rectilinear relative to the apparatus main assembly, the present invention is not limited to such an example. For example, the mounting path may be a combination of the straight lines, or it may be a curvilinear path.

(678) In addition, the cartridges of the embodiment described above form the monochrome image. However, the embodiments described above can suitably be applied to the cartridges for forming the images (for example, two color images, three color images, or full-color and so on) of the plural colors by a plurality of developing devices.

(679) In addition, the process cartridge described above includes an electrophotographic photosensitive member and the at least one process means, for example. Therefore, the process cartridge may contain the photosensitive drum and the charging means as the process means integrally. The process cartridge may contain the photosensitive drum and the developing means as the process means in unification. The process cartridge may contain the photosensitive drum and the cleaning means as the process means integrally. Further, the process cartridge may contain the photosensitive drum and the two process means or more integrally.

(680) In addition, the process cartridge is mount and demounted by a user relative to the apparatus main assembly. Therefore, the maintenance of the apparatus main assembly is in effect carried out by the user. According to the embodiments described above, relative to the apparatus main assembly which is not provided with the mechanism for moving the main assembly side drum coupling member for transmitting the rotational force to the photosensitive drum in the axial direction thereof, the process cartridge is detachably mountable in the direction substantially perpendicular to the axis of the drive shaft. And, the photosensitive drum can be rotated smoothly. In addition, according to the embodiment described above, the process cartridge can be demounted from the main assembly of the electrophotographic image forming device provided with the drive shaft in the direction substantially perpendicular to the axis of the drive shaft.

(681) In addition, according to the embodiment described above, the process cartridge can be mounted to the main assembly of the electrophotographic image forming device provided with the drive shaft in the direction substantially perpendicular to the axis of the drive shaft. In addition, according to the embodiment described above, the process cartridge is mountable and demountable in the direction substantially perpendicular to the axis of the drive shaft relative to the main

assembly of the electrophotographic image forming device provided with the drive shaft.

(682) In addition, according to the coupling described above, even if it does not make the driving gear provided in the main assembly move in the axial direction thereof, they are mountable and demountable relative to the apparatus main assembly by the movement of the process cartridge in the direction substantially perpendicular to the axis of the drive shaft.

(683) In addition, according to the embodiment described above, in the drive connecting portion between the main assembly and the cartridge, the photosensitive drum can rotate smoothly as compared with the case of the engagement between gears.

(684) In addition, according to the embodiment described above, the process cartridge is detachably mountable in the direction substantially perpendicular to the axis of the drive shaft provided in the main assembly, and, simultaneously, the photosensitive drum can rotate smoothly

(685) In addition, according to the embodiment described above, the process cartridge is detachably mountable in the direction substantially perpendicular to the axis of the drive shaft provided in the main assembly, and, simultaneously, the smooth rotation of the photosensitive drum can be carried out.

(686) As has been described hereinbefore, in the present invention, the axis of the drum coupling member can take the different angular positions relative to the axis of the photosensitive drum. The drum coupling member can be engaged with the drive shaft in the direction substantially perpendicular to the axis of the drive shaft provided in the main assembly by this structure. In addition, the drum coupling member can be disengaged from the drive shaft in the direction substantially perpendicular to the axis of the drive shaft. The present invention can be applied to the process cartridge, the electrophotographic photosensitive member drum unit, the rotational force transmitting portion (drum coupling member), and the electrophotographic image forming device.

(687) While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth, and this application is intended to cover such modification or changes as may come within the purposes of the improvements or the scope of the following claims.

(688) This application claims priority from Japanese Patent Applications Nos. 346190/2006 filed Dec. 22, 2006, 042665/2007 filed Feb. 22, 2007, and 330303/2007 filed Dec. 21, 2007, which are hereby incorporated by reference.

Claims

1. A cartridge comprising: a photosensitive drum having a rotational axis about which the photosensitive drum is rotatable; a developing roller having a rotational axis about which the developing roller is rotatable; a developing frame rotatably supporting the developing roller; a drum flange connected to an end of the photosensitive drum, the drum flange including an inner surface facing the rotational axis of the photosensitive drum and a hollow portion inside of the drum flange; and a casing including a bearing member rotatably supporting the photosensitive drum, the bearing member being positioned at a first end portion of the casing in a direction of the rotational axis of the photosensitive drum, the bearing member including (i) a surface that faces outside of the cartridge and extends perpendicular to a rotational axis of the photosensitive drum, (ii) an opening to the hollow portion of the drum flange, with the rotational axis of the photosensitive drum being positioned within the opening, (iii) a supporting projection rotatably supporting the drum flange by contacting the inner surface of the drum flange, the supporting projection being projected in the direction of the rotational axis of the photosensitive drum toward a second end portion of the casing that is opposite to the first end portion of the casing in the direction of the rotational axis of the photosensitive drum, and (iv) a projected part projecting in a direction away from the second end portion of the casing in the direction of the rotational axis of the photosensitive drum, wherein a distance between at least a part of the supporting projection and

the second end portion of the casing in the direction of the rotational axis of the photosensitive drum is shorter than a distance between the surface of the bearing member and the second end portion of the casing in the direction of the rotational axis of the photosensitive drum, wherein a distance between at least a part of the projected part and the second end portion of the casing in the direction of the rotational axis of the photosensitive drum is longer than the distance between the surface of the bearing member and the second end portion of the casing in the direction of the rotational axis of the photosensitive drum, wherein, as seen in the direction of the rotational axis of the photosensitive drum, (i) the projected part extends part way around the rotational axis of the photosensitive drum, (ii) the surface of the bearing member extends part way around the rotational axis of the photosensitive drum, and (iii) the rotational axis of the developing roller, the rotational axis of the photosensitive drum, and a part of the surface of the bearing member are positioned in this order along a first line, wherein a distance from the rotational axis of the photosensitive drum to at least a part of the projected part as measured along a second line that is perpendicular to the rotational axis of the photosensitive drum is shorter than a radius of the photosensitive drum that extends from the rotational axis of the photosensitive drum to an outer surface of the photosensitive drum, wherein a distance from the rotational axis of the photosensitive drum to at least a part of the surface of the bearing member as measured along a third line that is perpendicular to the rotational axis of the photosensitive drum and is different than the second line is shorter than the radius of the photosensitive drum, and wherein the surface of the bearing member is adjacent to an open space that extends to the rotational axis of the photosensitive drum in a direction perpendicular to the rotational axis of the photosensitive drum.

2. A cartridge according to claim 1, wherein, as viewed along the rotational axis of the photosensitive drum, the projected part is arc-shaped.

3. A cartridge according to claim 1, further comprising a rotatable shaft that extends in the direction of the rotational axis of the photosensitive drum and is operatively connected to the drum flange, the rotatable shaft being rotatable together with the drum flange, and at least a part of the rotatable shaft being positioned in the hollow portion of the drum flange.

4. A cartridge according to claim 3, wherein the space inside of the hollow portion is formed between the inner surface and the rotatable shaft in the direction perpendicular to the rotational axis of the photosensitive drum.

5. A cartridge according to claim 1, wherein at least a part of the projecting part extends in a direction that is perpendicular to the surface of bearing member.

6. A cartridge according to claim 1, further comprising a coupling member rotatable about an axis of the coupling member, the coupling member being operatively connected to the photosensitive drum by the drum flange such that a rotational force can be transmitted from the coupling member to the photosensitive drum.

7. A cartridge according to claim 6, wherein the coupling member is movable between a first position where the axis of the coupling member is coaxial with the axis of the photosensitive drum and a second position where the axis of the coupling member is inclined from the axis of the photosensitive drum.

8. A cartridge according to claim 1, wherein the open space extends parallel to the first line.

9. A cartridge according to claim 1, wherein, as seen in the direction of the rotational axis of the photosensitive drum, at least a part of the projected part, the rotational axis of the photosensitive drum, and at least a part of the surface of the bearing member are positioned in this order along a fourth line that is perpendicular to the first line.

10. A cartridge according to claim 9, wherein the open space extends in a direction perpendicular to the rotational axis of the photosensitive drum and parallel to the fourth line.

11. A cartridge according to claim 1, wherein the supporting projection includes an outer surface facing away from the rotational axis of the photosensitive drum and contacting the inner surface of the drum flange.

12. A cartridge according to claim 11, wherein the supporting projection is annular shaped around the opening of the bearing member.

13. A cartridge according to claim 1, further comprising a developing frame rotatably supporting the developing roller.
