

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403004
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Cooper; Alexander H. et al.

Method for replacing a tricuspid valve

Abstract

A method of implanting a prosthetic heart valve at a native tricuspid valve region includes delivering a prosthetic heart valve to the native tricuspid valve region via the inferior vena cava or the superior vena cava and deploying the prosthetic heart valve from a sheath of a delivery apparatus. The prosthetic heart valve includes a radially compressible and expandable frame assembly having an inflow end, an outflow end, and a double-body structure having an annular inner frame and an annular outer frame. The outer frame preferably includes an atrial flange portion configured to contact an atrial face of the native tricuspid valve region. The prosthetic heart valve can further include a plurality of ventricular anchors, each comprising a free end portion and a fixed end portion connected to and extending from the frame assembly at a location spaced from the outflow end of the frame assembly.

Inventors: Cooper; Alexander H. (Costa Mesa, CA), Peterson; Matthew A. (Costa Mesa, CA), Brunnett; William C. (Mission Viejo, CA)

Applicant: EDWARDS LIFESCIENCES CORPORATION (Irvine, CA)

Family ID: 54767429

Assignee: EDWARDS LIFESCIENCES CORPORATION (Irvine, CA)

Appl. No.: 18/195891

Filed: May 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230277309 A1	Sep. 07, 2023

Related U.S. Application Data

continuation parent-doc US 16902773 20200616 US 11684471 child-doc US 18195891
continuation parent-doc US 16015003 20180621 US 10687939 20200623 child-doc US 16902773
continuation parent-doc US 15382429 20161216 US 10010414 20180703 child-doc US 16015003

Publication Classification

Int. Cl.: A61F2/24 (20060101); A61F2/95 (20130101)

U.S. Cl.:

CPC A61F2/2418 (20130101); A61F2/2409 (20130101); A61F2/2436 (20130101); A61F2002/9534 (20130101); A61F2220/0008 (20130101); A61F2230/005 (20130101); A61F2230/0065 (20130101); A61F2230/0078 (20130101)

Field of Classification Search

CPC: A61F (2/2418); A61F (2/2409); A61F (2/2436); A61F (2/447); A61F (2002/9534); A61F (2220/0008)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3409013	12/1967	Berry	N/A	N/A
3472230	12/1968	Fogarty	N/A	N/A
3548417	12/1969	Kischer et al.	N/A	N/A
3587115	12/1970	Shiley	N/A	N/A
3657744	12/1971	Ersek	N/A	N/A
3671979	12/1971	Moulopoulos	N/A	N/A
3714671	12/1972	Edwards et al.	N/A	N/A
3739402	12/1972	Cooley et al.	N/A	N/A
3755823	12/1972	Hancock	N/A	N/A
4011947	12/1976	Sawyer	N/A	N/A
4035849	12/1976	Angell et al.	N/A	N/A
4056854	12/1976	Boretos et al.	N/A	N/A
4079468	12/1977	Liotta et al.	N/A	N/A
4106129	12/1977	Carpentier et al.	N/A	N/A
4204283	12/1979	Bellhouse et al.	N/A	N/A
4222126	12/1979	Boretos et al.	N/A	N/A
4265694	12/1980	Boretos et al.	N/A	N/A
4297749	12/1980	Davis et al.	N/A	N/A
4339831	12/1981	Johnson	N/A	N/A
4340977	12/1981	Brownlee et al.	N/A	N/A
4343048	12/1981	Ross et al.	N/A	N/A
4345340	12/1981	Rosen	N/A	N/A
4373216	12/1982	Klawitter	N/A	N/A
4406022	12/1982	Roy	N/A	N/A
4470157	12/1983	Love	N/A	N/A
4477930	12/1983	Totten et al.	N/A	N/A
4490859	12/1984	Black et al.	N/A	N/A
4535483	12/1984	Klawitter et al.	N/A	N/A
4553545	12/1984	Maass et al.	N/A	N/A

4574803	12/1985	Storz	N/A	N/A
4592340	12/1985	Boyles	N/A	N/A
4605407	12/1985	Black et al.	N/A	N/A
4612011	12/1985	Kautzky	N/A	N/A
4643732	12/1986	Pietsch et al.	N/A	N/A
4655771	12/1986	Wallsten	N/A	N/A
4692164	12/1986	Dzemeshevich et al.	N/A	N/A
4733665	12/1987	Palmaz	N/A	N/A
4759758	12/1987	Gabbay	N/A	N/A
4762128	12/1987	Rosenbluth	N/A	N/A
4777951	12/1987	Cribier et al.	N/A	N/A
4787899	12/1987	Lazarus	N/A	N/A
4787901	12/1987	Baykut	N/A	N/A
4796629	12/1988	Grayzel	N/A	N/A
4829990	12/1988	Thuroff et al.	N/A	N/A
4851001	12/1988	Taheri	N/A	N/A
4856516	12/1988	Hillstead	N/A	N/A
4865600	12/1988	Carpentier et al.	N/A	N/A
4878495	12/1988	Grayzel	N/A	N/A
4878906	12/1988	Lindemann et al.	N/A	N/A
4883458	12/1988	Shiber	N/A	N/A
4922905	12/1989	Strecker	N/A	N/A
4966604	12/1989	Reiss	N/A	N/A
4979939	12/1989	Shiber	N/A	N/A
4986830	12/1990	Owens et al.	N/A	N/A
4994077	12/1990	Dobben	N/A	N/A
5007896	12/1990	Shiber	N/A	N/A
5026366	12/1990	Leckrone	N/A	N/A
5032128	12/1990	Alonso	N/A	N/A
5037434	12/1990	Lane	N/A	N/A
5047041	12/1990	Samuels	N/A	N/A
5059177	12/1990	Towne et al.	N/A	N/A
5080668	12/1991	Bolz et al.	N/A	N/A
5085635	12/1991	Cragg	N/A	N/A
5089015	12/1991	Ross	N/A	N/A
5108370	12/1991	Walinsky	N/A	N/A
5152771	12/1991	Sabbaghian et al.	N/A	N/A
5163953	12/1991	Vince	N/A	N/A
5167628	12/1991	Boyles	N/A	N/A
5192297	12/1992	Hull	N/A	N/A
5232446	12/1992	Arney	N/A	N/A
5266073	12/1992	Wall	N/A	N/A
5282847	12/1993	Trescony et al.	N/A	N/A
5295958	12/1993	Shturman	N/A	N/A
5326371	12/1993	Love et al.	N/A	N/A
5332402	12/1993	Teitelbaum	N/A	N/A
5360444	12/1993	Kusuhara	N/A	N/A
5370685	12/1993	Stevens	N/A	N/A
5397351	12/1994	Pavcnik et al.	N/A	N/A
5411055	12/1994	Kane	N/A	N/A
5411522	12/1994	Trott	N/A	N/A
5411552	12/1994	Andersen et al.	N/A	N/A

5415667	12/1994	Frater	N/A	N/A
5443446	12/1994	Shturman	N/A	N/A
5480424	12/1995	Cox	N/A	N/A
5500014	12/1995	Quijano et al.	N/A	N/A
5545209	12/1995	Roberts et al.	N/A	N/A
5545214	12/1995	Stevens	N/A	N/A
5549665	12/1995	Vesely et al.	N/A	N/A
5554185	12/1995	Block et al.	N/A	N/A
5571175	12/1995	Vanney et al.	N/A	N/A
5591185	12/1996	Kilmer et al.	N/A	N/A
5599305	12/1996	Hermann et al.	N/A	N/A
5607464	12/1996	Trescony et al.	N/A	N/A
5609626	12/1996	Quijano et al.	N/A	N/A
5639274	12/1996	Fischell et al.	N/A	N/A
5665115	12/1996	Cragg	N/A	N/A
5697382	12/1996	Love et al.	N/A	N/A
5716417	12/1997	Girard et al.	N/A	N/A
5728068	12/1997	Leone et al.	N/A	N/A
5749890	12/1997	Shaknovich	N/A	N/A
5756476	12/1997	Epstein et al.	N/A	N/A
5769812	12/1997	Stevens et al.	N/A	N/A
5800508	12/1997	Goicoechea et al.	N/A	N/A
5840081	12/1997	Andersen et al.	N/A	N/A
5855597	12/1998	Jayaraman	N/A	N/A
5855601	12/1998	Bessler et al.	N/A	N/A
5855602	12/1998	Angell	N/A	N/A
5906619	12/1998	Olson et al.	N/A	N/A
5925063	12/1998	Khosravi	N/A	N/A
5957949	12/1998	Leonhardt et al.	N/A	N/A
5968068	12/1998	Dehdashtian et al.	N/A	N/A
6027525	12/1999	Suh et al.	N/A	N/A
6042607	12/1999	Williamson et al.	N/A	N/A
6086612	12/1999	Jansen	N/A	N/A
6113631	12/1999	Jansen	N/A	N/A
6132473	12/1999	Williams et al.	N/A	N/A
6168614	12/2000	Andersen et al.	N/A	N/A
6171335	12/2000	Wheatley et al.	N/A	N/A
6174327	12/2000	Mertens et al.	N/A	N/A
6210408	12/2000	Chandrasekaran et al.	N/A	N/A
6217585	12/2000	Houser et al.	N/A	N/A
6221091	12/2000	Khosravi	N/A	N/A
6231602	12/2000	Carpentier et al.	N/A	N/A
6245040	12/2000	Inderbitzen et al.	N/A	N/A
6245102	12/2000	Jayaraman	N/A	N/A
6251093	12/2000	Valley et al.	N/A	N/A
6287339	12/2000	Vazquez et al.	N/A	N/A
6299637	12/2000	Shaolian et al.	N/A	N/A
6302906	12/2000	Goicoechea et al.	N/A	N/A
6306141	12/2000	Jervis	N/A	N/A
6312465	12/2000	Griffin et al.	N/A	N/A
6338740	12/2001	Carpentier	N/A	N/A
6350277	12/2001	Kocur	N/A	N/A

6358277	12/2001	Duran	N/A	N/A
6379372	12/2001	Dehdashtian et al.	N/A	N/A
6425916	12/2001	Garrison et al.	N/A	N/A
6440164	12/2001	DiMatteo et al.	N/A	N/A
6454799	12/2001	Schreck	N/A	N/A
6458153	12/2001	Bailey et al.	N/A	N/A
6461382	12/2001	Cao	N/A	N/A
6468660	12/2001	Ogle et al.	N/A	N/A
6482228	12/2001	Norred	N/A	N/A
6488704	12/2001	Connelly et al.	N/A	N/A
6527800	12/2002	McGuckin et al.	N/A	N/A
6527979	12/2002	Constantz et al.	N/A	N/A
6540782	12/2002	Snyders	N/A	N/A
6569196	12/2002	Vesely	N/A	N/A
6575959	12/2002	Sarge et al.	N/A	N/A
6582462	12/2002	Andersen et al.	N/A	N/A
6605112	12/2002	Moll et al.	N/A	N/A
6610088	12/2002	Gabbay	N/A	N/A
6629534	12/2002	St. Goar et al.	N/A	N/A
6676698	12/2003	McGuckin et al.	N/A	N/A
6695878	12/2003	McGuckin et al.	N/A	N/A
6712836	12/2003	Berg et al.	N/A	N/A
6716207	12/2003	Farnholtz	N/A	N/A
6729356	12/2003	Baker et al.	N/A	N/A
6730118	12/2003	Spenser et al.	N/A	N/A
6733525	12/2003	Yang et al.	N/A	N/A
6746422	12/2003	Noriega et al.	N/A	N/A
6749560	12/2003	Konstorum et al.	N/A	N/A
6767362	12/2003	Schreck	N/A	N/A
6780200	12/2003	Jansen	N/A	N/A
6790229	12/2003	Berrekouw	N/A	N/A
6790230	12/2003	Beyersdorf et al.	N/A	N/A
6830584	12/2003	Seguin	N/A	N/A
6875231	12/2004	Anduiza et al.	N/A	N/A
6893460	12/2004	Spenser et al.	N/A	N/A
6908481	12/2004	Cribier	N/A	N/A
6974476	12/2004	McGuckin et al.	N/A	N/A
7018406	12/2005	Seguin et al.	N/A	N/A
7186265	12/2006	Sharkawy et al.	N/A	N/A
7192440	12/2006	Andreas et al.	N/A	N/A
7198646	12/2006	Figulla et al.	N/A	N/A
7201772	12/2006	Schwammenthal et al.	N/A	N/A
7276078	12/2006	Spenser et al.	N/A	N/A
7276084	12/2006	Yang et al.	N/A	N/A
7318278	12/2007	Zhang et al.	N/A	N/A
7374571	12/2007	Pease et al.	N/A	N/A
7381210	12/2007	Zarbatany et al.	N/A	N/A
7381219	12/2007	Salahieh et al.	N/A	N/A
7393360	12/2007	Spenser et al.	N/A	N/A
7429269	12/2007	Schwammenthal et al.	N/A	N/A
7442204	12/2007	Schwammenthal et al.	N/A	N/A
7445631	12/2007	Salahieh et al.	N/A	N/A

7462191	12/2007	Spenser et al.	N/A	N/A
7510575	12/2008	Spenser et al.	N/A	N/A
7524330	12/2008	Berrekouw	N/A	N/A
7530253	12/2008	Spenser et al.	N/A	N/A
7553324	12/2008	Andreas et al.	N/A	N/A
7579381	12/2008	Dove	N/A	N/A
7585321	12/2008	Cribier	N/A	N/A
7618446	12/2008	Andersen et al.	N/A	N/A
7621948	12/2008	Herrmann et al.	N/A	N/A
7704222	12/2009	Wilk et al.	N/A	N/A
7736327	12/2009	Wilk et al.	N/A	N/A
7748389	12/2009	Salahieh et al.	N/A	N/A
7753949	12/2009	Lamphere et al.	N/A	N/A
7806919	12/2009	Bloom et al.	N/A	N/A
7824443	12/2009	Salahieh et al.	N/A	N/A
7837727	12/2009	Goetz et al.	N/A	N/A
7892281	12/2010	Seguin et al.	N/A	N/A
7914569	12/2010	Nguyen et al.	N/A	N/A
7914575	12/2010	Guyenot et al.	N/A	N/A
7959672	12/2010	Salahieh et al.	N/A	N/A
7972378	12/2010	Tabor et al.	N/A	N/A
7981151	12/2010	Rowe	N/A	N/A
7993392	12/2010	Righini et al.	N/A	N/A
7993394	12/2010	Hariton et al.	N/A	N/A
8007992	12/2010	Tian et al.	N/A	N/A
8016877	12/2010	Seguin et al.	N/A	N/A
8029556	12/2010	Rowe	N/A	N/A
8052750	12/2010	Tuval et al.	N/A	N/A
8070800	12/2010	Lock et al.	N/A	N/A
8070802	12/2010	Lamphere et al.	N/A	N/A
8075615	12/2010	Eberhardt et al.	N/A	N/A
8080054	12/2010	Rowe	N/A	N/A
8092520	12/2011	Quadri	N/A	N/A
8092521	12/2011	Figulla et al.	N/A	N/A
8109996	12/2011	Stacchino et al.	N/A	N/A
8118866	12/2011	Herrmann et al.	N/A	N/A
8136218	12/2011	Millwee et al.	N/A	N/A
8137398	12/2011	Tuval et al.	N/A	N/A
8157852	12/2011	Bloom et al.	N/A	N/A
8167932	12/2011	Bourang et al.	N/A	N/A
8167934	12/2011	Styrc et al.	N/A	N/A
8182530	12/2011	Huber	N/A	N/A
8206437	12/2011	Bonhoeffer et al.	N/A	N/A
8216174	12/2011	Wilk et al.	N/A	N/A
8216301	12/2011	Bonhoeffer et al.	N/A	N/A
8219229	12/2011	Cao et al.	N/A	N/A
8220121	12/2011	Hendriksen et al.	N/A	N/A
8236045	12/2011	Benichou et al.	N/A	N/A
8246675	12/2011	Zegdi	N/A	N/A
8246678	12/2011	Salahieh et al.	N/A	N/A
8252051	12/2011	Chau et al.	N/A	N/A
8252052	12/2011	Salahieh et al.	N/A	N/A

8287584	12/2011	Salahieh et al.	N/A	N/A
8313525	12/2011	Tuval et al.	N/A	N/A
8317858	12/2011	Straubinger et al.	N/A	N/A
8323335	12/2011	Rowe et al.	N/A	N/A
8337541	12/2011	Quadri et al.	N/A	N/A
8353953	12/2012	Giannetti et al.	N/A	N/A
8398704	12/2012	Straubinger et al.	N/A	N/A
8403983	12/2012	Quadri et al.	N/A	N/A
8414644	12/2012	Quadri et al.	N/A	N/A
8414645	12/2012	Dwork et al.	N/A	N/A
8416643	12/2012	Magee	N/A	N/A
8444689	12/2012	Zhang	N/A	N/A
8449599	12/2012	Chau et al.	N/A	N/A
8454685	12/2012	Hariton et al.	N/A	N/A
8460368	12/2012	Taylor et al.	N/A	N/A
8460370	12/2012	Zakay et al.	N/A	N/A
8470023	12/2012	Eidenschink et al.	N/A	N/A
8470028	12/2012	Thornton et al.	N/A	N/A
8475521	12/2012	Suri et al.	N/A	N/A
8475523	12/2012	Duffy	N/A	N/A
8479380	12/2012	Malewicz et al.	N/A	N/A
8491650	12/2012	Wiemeyer et al.	N/A	N/A
8500733	12/2012	Watson	N/A	N/A
8500798	12/2012	Rowe et al.	N/A	N/A
8511244	12/2012	Holecek et al.	N/A	N/A
8512401	12/2012	Murray et al.	N/A	N/A
8518096	12/2012	Nelson	N/A	N/A
8518106	12/2012	Duffy et al.	N/A	N/A
8562663	12/2012	Mearns et al.	N/A	N/A
8579963	12/2012	Tabor	N/A	N/A
8579964	12/2012	Lane et al.	N/A	N/A
8591570	12/2012	Revuelta et al.	N/A	N/A
8617236	12/2012	Paul et al.	N/A	N/A
8640521	12/2013	Righini et al.	N/A	N/A
8647381	12/2013	Essinger et al.	N/A	N/A
8652145	12/2013	Maimon et al.	N/A	N/A
8652201	12/2013	Oberti et al.	N/A	N/A
8652202	12/2013	Alon et al.	N/A	N/A
8652203	12/2013	Quadri et al.	N/A	N/A
8668733	12/2013	Haug et al.	N/A	N/A
8679174	12/2013	Ottma et al.	N/A	N/A
8679404	12/2013	Liburd et al.	N/A	N/A
8685086	12/2013	Navia et al.	N/A	N/A
8721708	12/2013	Sèguin et al.	N/A	N/A
8721714	12/2013	Kelley	N/A	N/A
8728154	12/2013	Alkhatib	N/A	N/A
8728155	12/2013	Montorfano et al.	N/A	N/A
8740974	12/2013	Lambrecht et al.	N/A	N/A
8740976	12/2013	Tran et al.	N/A	N/A
8747458	12/2013	Tuval et al.	N/A	N/A
8747459	12/2013	Nguyen et al.	N/A	N/A
8758432	12/2013	Solem	N/A	N/A

8764818	12/2013	Gregg	N/A	N/A
8771344	12/2013	Tran et al.	N/A	N/A
8778020	12/2013	Gregg et al.	N/A	N/A
8784337	12/2013	Voeller et al.	N/A	N/A
8784478	12/2013	Tuval et al.	N/A	N/A
8784481	12/2013	Alkhatib et al.	N/A	N/A
8790387	12/2013	Nguyen et al.	N/A	N/A
8795357	12/2013	Yohanan et al.	N/A	N/A
8808356	12/2013	Braido et al.	N/A	N/A
8828078	12/2013	Salahieh et al.	N/A	N/A
8828079	12/2013	Thielen et al.	N/A	N/A
8834564	12/2013	Tuval et al.	N/A	N/A
8858620	12/2013	Salahieh et al.	N/A	N/A
8870948	12/2013	Erzberger et al.	N/A	N/A
8870950	12/2013	Hacohen	N/A	N/A
8876893	12/2013	Dwork et al.	N/A	N/A
8911455	12/2013	Quadri et al.	N/A	N/A
8926693	12/2014	Duffy et al.	N/A	N/A
8926694	12/2014	Costello	N/A	N/A
8939960	12/2014	Rosenman et al.	N/A	N/A
8945209	12/2014	Bonyuet et al.	N/A	N/A
8961593	12/2014	Bonhoeffer et al.	N/A	N/A
8961595	12/2014	Alkhatib	N/A	N/A
8974524	12/2014	Yeung et al.	N/A	N/A
8979922	12/2014	Jayasinghe et al.	N/A	N/A
8986375	12/2014	Garde et al.	N/A	N/A
8998980	12/2014	Shipley et al.	N/A	N/A
9005273	12/2014	Salahieh et al.	N/A	N/A
9011521	12/2014	Haug et al.	N/A	N/A
9011523	12/2014	Seguin	N/A	N/A
9011524	12/2014	Eberhardt	N/A	N/A
9028545	12/2014	Taylor	N/A	N/A
9034032	12/2014	McLean et al.	N/A	N/A
9055937	12/2014	Rowe et al.	N/A	N/A
9066801	12/2014	Kovalsky et al.	N/A	N/A
9078749	12/2014	Lutter et al.	N/A	N/A
9078751	12/2014	Naor	N/A	N/A
9125738	12/2014	Figulla et al.	N/A	N/A
9173737	12/2014	Hill et al.	N/A	N/A
9180004	12/2014	Alkhatib	N/A	N/A
9186249	12/2014	Rolando et al.	N/A	N/A
9277990	12/2015	Klima et al.	N/A	N/A
9277993	12/2015	Gamarra et al.	N/A	N/A
9289291	12/2015	Gorman et al.	N/A	N/A
9295551	12/2015	Straubinger et al.	N/A	N/A
9445897	12/2015	Bishop et al.	N/A	N/A
9456877	12/2015	Weitzner et al.	N/A	N/A
9532870	12/2016	Cooper	N/A	A61F 2/2418
9681968	12/2016	Goetz et al.	N/A	N/A
9687345	12/2016	Rabito et al.	N/A	N/A
9700329	12/2016	Metzger et al.	N/A	N/A
9700411	12/2016	Klima et al.	N/A	N/A

9724083	12/2016	Quadri et al.	N/A	N/A
9730790	12/2016	Quadri et al.	N/A	N/A
9730791	12/2016	Ratz et al.	N/A	N/A
9795479	12/2016	Lim et al.	N/A	N/A
9833313	12/2016	Board et al.	N/A	N/A
9861473	12/2017	Lafontaine	N/A	N/A
9861476	12/2017	Salahieh et al.	N/A	N/A
9861477	12/2017	Backus et al.	N/A	N/A
9867698	12/2017	Kovalsky et al.	N/A	N/A
9877830	12/2017	Lim et al.	N/A	N/A
9889029	12/2017	Li et al.	N/A	N/A
9895225	12/2017	Rolando et al.	N/A	N/A
9925045	12/2017	Creaven et al.	N/A	N/A
10004599	12/2017	Rabito et al.	N/A	N/A
10010414	12/2017	Cooper	N/A	A61F 2/2418
10117744	12/2017	Ratz et al.	N/A	N/A
10179044	12/2018	Ratz et al.	N/A	N/A
10219897	12/2018	Essinger et al.	N/A	N/A
10350065	12/2018	Quadri	N/A	N/A
10350066	12/2018	Cooper et al.	N/A	N/A
10376363	12/2018	Quadri et al.	N/A	N/A
10555809	12/2019	Hastings et al.	N/A	N/A
10575951	12/2019	Johnson et al.	N/A	N/A
10583000	12/2019	Ratz et al.	N/A	N/A
10639146	12/2019	Quadri et al.	N/A	N/A
10687939	12/2019	Cooper	N/A	A61F 2/2418
10695177	12/2019	Hariton et al.	N/A	N/A
10758344	12/2019	Hariton et al.	N/A	N/A
11406499	12/2021	Zhang et al.	N/A	N/A
11452598	12/2021	Essinger et al.	N/A	N/A
11672658	12/2022	Hariton et al.	N/A	N/A
11684471	12/2022	Cooper	623/2.14	A61F 2/2418
11701225	12/2022	Hammer et al.	N/A	N/A
11903829	12/2023	Ma et al.	N/A	N/A
2001/0021872	12/2000	Bailey et al.	N/A	N/A
2002/0032481	12/2001	Gabbay	N/A	N/A
2002/0045929	12/2001	Diaz	N/A	N/A
2002/0052644	12/2001	Shaolian et al.	N/A	N/A
2002/0107565	12/2001	Greenhalgh	N/A	N/A
2002/0123802	12/2001	Snyders	N/A	N/A
2002/0173842	12/2001	Buchanan	N/A	N/A
2003/0050694	12/2002	Yang et al.	N/A	N/A
2003/0100939	12/2002	Yodfat et al.	N/A	N/A
2003/0105517	12/2002	White et al.	N/A	N/A
2003/0120333	12/2002	Ouriel et al.	N/A	N/A
2003/0130729	12/2002	Paniagua et al.	N/A	N/A
2003/0149477	12/2002	Gabbay	N/A	N/A
2003/0149478	12/2002	Figulla et al.	N/A	N/A
2003/0158597	12/2002	Quiachon et al.	N/A	N/A
2003/0176914	12/2002	Rabkin et al.	N/A	N/A
2003/0199971	12/2002	Tower et al.	N/A	N/A
2003/0212454	12/2002	Scott et al.	N/A	N/A

2003/0220683	12/2002	Minasian et al.	N/A	N/A
2004/0039436	12/2003	Spenser et al.	N/A	N/A
2004/0092858	12/2003	Wilson et al.	N/A	N/A
2004/0093075	12/2003	Kuehne	N/A	N/A
2004/0117009	12/2003	Cali et al.	N/A	N/A
2004/0133263	12/2003	Dusbabek et al.	N/A	N/A
2004/0133273	12/2003	Cox	N/A	N/A
2004/0186563	12/2003	Lobbi	N/A	N/A
2004/0186565	12/2003	Schreck	N/A	N/A
2004/0210307	12/2003	Khairkhahan	N/A	N/A
2004/0215325	12/2003	Penn et al.	N/A	N/A
2004/0225353	12/2003	McGuckin et al.	N/A	N/A
2004/0236411	12/2003	Sarac et al.	N/A	N/A
2004/0260389	12/2003	Case et al.	N/A	N/A
2005/0033398	12/2004	Seguin	N/A	N/A
2005/0075727	12/2004	Wheatley	N/A	N/A
2005/0090887	12/2004	Pryor	N/A	N/A
2005/0096738	12/2004	Cali et al.	N/A	N/A
2005/0107872	12/2004	Mensah et al.	N/A	N/A
2005/0137682	12/2004	Justino	N/A	N/A
2005/0137686	12/2004	Salahieh et al.	N/A	N/A
2005/0137687	12/2004	Salahieh et al.	N/A	N/A
2005/0137688	12/2004	Salahieh et al.	N/A	N/A
2005/0137691	12/2004	Salahieh et al.	N/A	N/A
2005/0137698	12/2004	Salahieh et al.	N/A	N/A
2005/0159811	12/2004	Lane	N/A	N/A
2005/0182486	12/2004	Gabbay	N/A	N/A
2005/0203614	12/2004	Forster et al.	N/A	N/A
2005/0203617	12/2004	Forster et al.	N/A	N/A
2005/0216079	12/2004	MaCoviak	N/A	N/A
2005/0234546	12/2004	Nugent et al.	N/A	N/A
2005/0288766	12/2004	Plain et al.	N/A	N/A
2006/0020327	12/2005	Lashinski et al.	N/A	N/A
2006/0025857	12/2005	Bergheim et al.	N/A	N/A
2006/0058872	12/2005	Salahieh et al.	N/A	N/A
2006/0095115	12/2005	Bladillah et al.	N/A	N/A
2006/0142837	12/2005	Haverkost et al.	N/A	N/A
2006/0149350	12/2005	Patel et al.	N/A	N/A
2006/0161249	12/2005	Realyvasquez et al.	N/A	N/A
2006/0173537	12/2005	Yang et al.	N/A	N/A
2006/0195134	12/2005	Crittenden	N/A	N/A
2006/0195183	12/2005	Navia et al.	N/A	N/A
2006/0212110	12/2005	Osborne et al.	N/A	N/A
2006/0229719	12/2005	Marquez et al.	N/A	N/A
2006/0241745	12/2005	Solem	N/A	N/A
2006/0259135	12/2005	Navia et al.	N/A	N/A
2006/0259137	12/2005	Artof et al.	N/A	N/A
2006/0276874	12/2005	Wilson et al.	N/A	N/A
2006/0293745	12/2005	Carpentier et al.	N/A	N/A
2007/0005131	12/2006	Taylor	N/A	N/A
2007/0010877	12/2006	Salahieh et al.	N/A	N/A
2007/0027534	12/2006	Bergheim et al.	N/A	N/A

2007/0043435	12/2006	Seguin et al.	N/A	N/A
2007/0050021	12/2006	Johnson	N/A	N/A
2007/0066863	12/2006	Rafiee et al.	N/A	N/A
2007/0088431	12/2006	Bourang et al.	N/A	N/A
2007/0100432	12/2006	Case et al.	N/A	N/A
2007/0100439	12/2006	Cangialosi et al.	N/A	N/A
2007/0112422	12/2006	Dehdashtian	N/A	N/A
2007/0129794	12/2006	Realyvasquez	N/A	N/A
2007/0142906	12/2006	Figulla et al.	N/A	N/A
2007/0156224	12/2006	Cioanta et al.	N/A	N/A
2007/0203503	12/2006	Salahieh et al.	N/A	N/A
2007/0203575	12/2006	Forster et al.	N/A	N/A
2007/0213813	12/2006	Von Segesser et al.	N/A	N/A
2007/0255394	12/2006	Ryan	N/A	N/A
2007/0270943	12/2006	Solem et al.	N/A	N/A
2008/0021546	12/2007	Patz et al.	N/A	N/A
2008/0065011	12/2007	Marchand et al.	N/A	N/A
2008/0071361	12/2007	Tuval et al.	N/A	N/A
2008/0071362	12/2007	Tuval et al.	N/A	N/A
2008/0071363	12/2007	Tuval et al.	N/A	N/A
2008/0071366	12/2007	Tuval et al.	N/A	N/A
2008/0071368	12/2007	Tuval et al.	N/A	N/A
2008/0071369	12/2007	Tuval et al.	N/A	N/A
2008/0082164	12/2007	Friedman	N/A	N/A
2008/0082165	12/2007	Wilson et al.	N/A	N/A
2008/0082166	12/2007	Styrc et al.	N/A	N/A
2008/0097581	12/2007	Shanley	N/A	N/A
2008/0114442	12/2007	Mitchell et al.	N/A	N/A
2008/0125853	12/2007	Bailey et al.	N/A	N/A
2008/0147179	12/2007	Cai et al.	N/A	N/A
2008/0147183	12/2007	Styrc	N/A	N/A
2008/0154355	12/2007	Benichou et al.	N/A	N/A
2008/0161910	12/2007	Revuelta et al.	N/A	N/A
2008/0177381	12/2007	Navia et al.	N/A	N/A
2008/0183273	12/2007	Mesana et al.	N/A	N/A
2008/0208328	12/2007	Antocci et al.	N/A	N/A
2008/0208332	12/2007	Lamphere et al.	N/A	N/A
2008/0221672	12/2007	Lamphere et al.	N/A	N/A
2008/0228254	12/2007	Ryan	N/A	N/A
2008/0255660	12/2007	Guyenot et al.	N/A	N/A
2008/0255661	12/2007	Straubinger et al.	N/A	N/A
2008/0281411	12/2007	Berrekouw	N/A	N/A
2009/0005863	12/2008	Goetz et al.	N/A	N/A
2009/0054968	12/2008	Bonhoeffer et al.	N/A	N/A
2009/0054974	12/2008	McGuckin et al.	N/A	N/A
2009/0076598	12/2008	Salahieh et al.	N/A	N/A
2009/0112309	12/2008	Jaramillo et al.	N/A	N/A
2009/0138079	12/2008	Tuval et al.	N/A	N/A
2009/0157175	12/2008	Benichou	N/A	N/A
2009/0164005	12/2008	Dove et al.	N/A	N/A
2009/0171432	12/2008	Von Segesser et al.	N/A	N/A
2009/0171447	12/2008	Von Segesser et al.	N/A	N/A

2009/0171456	12/2008	Kveen et al.	N/A	N/A
2009/0182413	12/2008	Burkart et al.	N/A	N/A
2009/0188964	12/2008	Orlov	N/A	N/A
2009/0216310	12/2008	Straubinger et al.	N/A	N/A
2009/0216313	12/2008	Straubinger et al.	N/A	N/A
2009/0216322	12/2008	Le et al.	N/A	N/A
2009/0222076	12/2008	Figulla et al.	N/A	N/A
2009/0234443	12/2008	Ottma et al.	N/A	N/A
2009/0240320	12/2008	Tuval et al.	N/A	N/A
2009/0270972	12/2008	Lane	N/A	N/A
2009/0276027	12/2008	Glynn	N/A	N/A
2009/0276040	12/2008	Rowe et al.	N/A	N/A
2009/0281618	12/2008	Hill et al.	N/A	N/A
2009/0281619	12/2008	Le et al.	N/A	N/A
2009/0287296	12/2008	Manasse	N/A	N/A
2009/0287299	12/2008	Tabor et al.	N/A	N/A
2009/0292350	12/2008	Eberhardt et al.	N/A	N/A
2009/0306768	12/2008	Quadri	N/A	N/A
2009/0319037	12/2008	Rowe et al.	N/A	N/A
2010/0016958	12/2009	St. Goar et al.	N/A	N/A
2010/0024818	12/2009	Stenzler et al.	N/A	N/A
2010/0049313	12/2009	Alon et al.	N/A	N/A
2010/0069852	12/2009	Kelley	N/A	N/A
2010/0114305	12/2009	Kang et al.	N/A	N/A
2010/0131054	12/2009	Tuval et al.	N/A	N/A
2010/0137979	12/2009	Tuval et al.	N/A	N/A
2010/0145438	12/2009	Barone	N/A	N/A
2010/0174362	12/2009	Straubinger et al.	N/A	N/A
2010/0191326	12/2009	Alkhatib	N/A	N/A
2010/0204781	12/2009	Alkhatib	N/A	N/A
2010/0217382	12/2009	Chau et al.	N/A	N/A
2010/0249894	12/2009	Oba et al.	N/A	N/A
2010/0249911	12/2009	Alkhatib	N/A	N/A
2010/0256723	12/2009	Murray	N/A	N/A
2010/0262231	12/2009	Tuval et al.	N/A	N/A
2010/0305685	12/2009	Millwee et al.	N/A	N/A
2010/0312333	12/2009	Navia et al.	N/A	N/A
2011/0015616	12/2010	Straubinger et al.	N/A	N/A
2011/0015729	12/2010	Jimenez et al.	N/A	N/A
2011/0029072	12/2010	Gabbay	N/A	N/A
2011/0137397	12/2010	Chau et al.	N/A	N/A
2011/0178597	12/2010	Navia et al.	N/A	N/A
2011/0208290	12/2010	Straubinger et al.	N/A	N/A
2011/0208297	12/2010	Tuval et al.	N/A	N/A
2011/0208298	12/2010	Tuval et al.	N/A	N/A
2011/0224785	12/2010	Hacohen	N/A	N/A
2011/0238159	12/2010	Guyenot et al.	N/A	N/A
2011/0264196	12/2010	Savage et al.	N/A	N/A
2011/0264198	12/2010	Murray et al.	N/A	N/A
2011/0288634	12/2010	Tuval et al.	N/A	N/A
2011/0313515	12/2010	Quadri et al.	N/A	N/A
2011/0319989	12/2010	Lane et al.	N/A	N/A

2012/0022639	12/2011	Hacohen et al.	N/A	N/A
2012/0035722	12/2011	Tuval	N/A	N/A
2012/0041550	12/2011	Salahieh et al.	N/A	N/A
2012/0046741	12/2011	Tuval et al.	N/A	N/A
2012/0046742	12/2011	Tuval et al.	N/A	N/A
2012/0078360	12/2011	Rafiee	N/A	N/A
2012/0101570	12/2011	Tuval et al.	N/A	N/A
2012/0101571	12/2011	Thambar et al.	N/A	N/A
2012/0101572	12/2011	Kovalsky et al.	N/A	N/A
2012/0123529	12/2011	Levi et al.	N/A	N/A
2012/0185039	12/2011	Tuval et al.	N/A	N/A
2012/0197386	12/2011	Von Segesser et al.	N/A	N/A
2012/0209374	12/2011	Bonhoeffer et al.	N/A	N/A
2012/0215303	12/2011	Quadri et al.	N/A	N/A
2012/0271398	12/2011	Essinger et al.	N/A	N/A
2012/0283823	12/2011	Bonhoeffer et al.	N/A	N/A
2012/0290062	12/2011	McNamara et al.	N/A	N/A
2012/0296418	12/2011	Bonyuet et al.	N/A	N/A
2012/0310328	12/2011	Olson et al.	N/A	N/A
2012/0310336	12/2011	Figulla et al.	N/A	N/A
2013/0006294	12/2012	Kashkarov et al.	N/A	N/A
2013/0035759	12/2012	Gross et al.	N/A	N/A
2013/0073035	12/2012	Tuval et al.	N/A	N/A
2013/0079869	12/2012	Straubinger et al.	N/A	N/A
2013/0172992	12/2012	Gross et al.	N/A	N/A
2013/0190861	12/2012	Chau et al.	N/A	N/A
2013/0190862	12/2012	Pintor et al.	N/A	N/A
2013/0197622	12/2012	Mitra et al.	N/A	N/A
2013/0211508	12/2012	Lane et al.	N/A	N/A
2013/0253635	12/2012	Straubinger et al.	N/A	N/A
2013/0253642	12/2012	Brecker	N/A	N/A
2013/0310928	12/2012	Morriss et al.	N/A	N/A
2013/0331929	12/2012	Mitra et al.	N/A	N/A
2013/0338766	12/2012	Hastings et al.	N/A	N/A
2013/0345786	12/2012	Behan	N/A	N/A
2014/0018912	12/2013	Delaloye et al.	N/A	N/A
2014/0025163	12/2013	Padala et al.	N/A	N/A
2014/0039611	12/2013	Lane et al.	N/A	N/A
2014/0052237	12/2013	Lane et al.	N/A	N/A
2014/0100651	12/2013	Kheradvar et al.	N/A	N/A
2014/0163668	12/2013	Rafiee	N/A	N/A
2014/0172077	12/2013	Bruchman et al.	N/A	N/A
2014/0172083	12/2013	Bruchman et al.	N/A	N/A
2014/0194981	12/2013	Menk et al.	N/A	N/A
2014/0207231	12/2013	Hacohen et al.	N/A	N/A
2014/0214157	12/2013	Börtlein et al.	N/A	N/A
2014/0222136	12/2013	Geist et al.	N/A	N/A
2014/0222139	12/2013	Nguyen et al.	N/A	N/A
2014/0222142	12/2013	Kovalsky et al.	N/A	N/A
2014/0222144	12/2013	Eberhardt et al.	N/A	N/A
2014/0243966	12/2013	Garde et al.	N/A	N/A
2014/0257467	12/2013	Lane et al.	N/A	N/A

2014/0277390	12/2013	Ratz et al.	N/A	N/A
2014/0277403	12/2013	Peter	N/A	N/A
2014/0277412	12/2013	Börtlein et al.	N/A	N/A
2014/0277422	12/2013	Ratz et al.	N/A	N/A
2014/0277426	12/2013	Dakin et al.	N/A	N/A
2014/0277427	12/2013	Ratz et al.	N/A	N/A
2014/0296973	12/2013	Bergheim et al.	N/A	N/A
2014/0296975	12/2013	Tegels et al.	N/A	N/A
2014/0303719	12/2013	Cox et al.	N/A	N/A
2014/0309728	12/2013	Dehdashtian et al.	N/A	N/A
2014/0324160	12/2013	Benichou et al.	N/A	N/A
2014/0324164	12/2013	Gross et al.	N/A	N/A
2014/0330368	12/2013	Gloss et al.	N/A	N/A
2014/0330371	12/2013	Gloss et al.	N/A	N/A
2014/0330372	12/2013	Weston et al.	N/A	N/A
2014/0336754	12/2013	Gurskis et al.	N/A	N/A
2014/0343669	12/2013	Lane et al.	N/A	N/A
2014/0343670	12/2013	Bakis et al.	N/A	N/A
2014/0350666	12/2013	Righini	N/A	N/A
2014/0350668	12/2013	Delaloye et al.	N/A	N/A
2014/0358223	12/2013	Rafiee et al.	N/A	N/A
2014/0364939	12/2013	Deshmukh et al.	N/A	N/A
2014/0364943	12/2013	Conklin	N/A	N/A
2014/0371842	12/2013	Marquez et al.	N/A	N/A
2014/0371844	12/2013	Dale et al.	N/A	N/A
2014/0371847	12/2013	Madrid et al.	N/A	N/A
2014/0371848	12/2013	Murray et al.	N/A	N/A
2015/0005863	12/2014	Para	N/A	N/A
2015/0018944	12/2014	O'Connell et al.	N/A	N/A
2015/0039083	12/2014	Rafiee	N/A	N/A
2015/0142100	12/2014	Morriss et al.	N/A	N/A
2015/0142103	12/2014	Mdlund	N/A	N/A
2015/0148731	12/2014	McNamara et al.	N/A	N/A
2015/0173897	12/2014	Raanani et al.	N/A	N/A
2015/0196390	12/2014	Ma et al.	N/A	N/A
2015/0209141	12/2014	Braido et al.	N/A	N/A
2015/0272737	12/2014	Dale et al.	N/A	N/A
2015/0297346	12/2014	Duffy et al.	N/A	N/A
2015/0335429	12/2014	Morriss et al.	N/A	N/A
2015/0351903	12/2014	Morriss et al.	N/A	N/A
2015/0359629	12/2014	Ganesan et al.	N/A	N/A
2016/0000591	12/2015	Lei et al.	N/A	N/A
2016/0030169	12/2015	Shahriari	N/A	N/A
2016/0030170	12/2015	Alkhatib et al.	N/A	N/A
2016/0030171	12/2015	Quijano et al.	N/A	N/A
2016/0038280	12/2015	Morriss et al.	N/A	N/A
2016/0038281	12/2015	Delaloye et al.	N/A	N/A
2016/0074160	12/2015	Christianson et al.	N/A	N/A
2016/0106537	12/2015	Christianson et al.	N/A	N/A
2016/0113765	12/2015	Ganesan et al.	N/A	N/A
2016/0113768	12/2015	Ganesan et al.	N/A	N/A
2016/0143732	12/2015	Glimsdale	N/A	N/A

2016/0158010	12/2015	Lim et al.	N/A	N/A
2016/0166383	12/2015	Lim et al.	N/A	N/A
2016/0184097	12/2015	Lim et al.	N/A	N/A
2016/0199206	12/2015	Lim et al.	N/A	N/A
2016/0213473	12/2015	Hacohen et al.	N/A	N/A
2016/0235529	12/2015	Ma et al.	N/A	N/A
2016/0278923	12/2015	Krans et al.	N/A	N/A
2016/0279386	12/2015	Dale et al.	N/A	N/A
2016/0310267	12/2015	Zeng et al.	N/A	N/A
2017/0042678	12/2016	Ganesan et al.	N/A	N/A
2017/0079785	12/2016	Li	N/A	N/A
2017/0128209	12/2016	Morriss et al.	N/A	N/A
2017/0216023	12/2016	Lane et al.	N/A	N/A
2017/0216575	12/2016	Asleson et al.	N/A	N/A
2017/0257902	12/2016	Xing et al.	N/A	N/A
2017/0258614	12/2016	Griffin	N/A	N/A
2017/0325945	12/2016	Dale et al.	N/A	N/A
2017/0325954	12/2016	Perszyk	N/A	N/A
2017/0333186	12/2016	Spargias	N/A	N/A
2017/0348096	12/2016	Anderson	N/A	N/A
2017/0367821	12/2016	Landon et al.	N/A	N/A
2017/0367823	12/2016	Hariton et al.	N/A	N/A
2018/0014931	12/2017	Morriss et al.	N/A	N/A
2018/0021129	12/2017	Peterson et al.	N/A	N/A
2018/0055629	12/2017	Oba et al.	N/A	N/A
2018/0055636	12/2017	Valencia et al.	N/A	N/A
2018/0085218	12/2017	Eidenschink	N/A	N/A
2018/0110534	12/2017	Gavala et al.	N/A	N/A
2018/0110622	12/2017	Gregg et al.	N/A	N/A
2018/0116790	12/2017	Ratz et al.	N/A	N/A
2018/0126119	12/2017	McNIVEN et al.	N/A	N/A
2018/0296341	12/2017	Noe et al.	N/A	N/A
2018/0344457	12/2017	Gross et al.	N/A	N/A
2018/0344490	12/2017	Fox et al.	N/A	N/A
2019/0008639	12/2018	Landon et al.	N/A	N/A
2019/0008640	12/2018	Cooper et al.	N/A	N/A
2019/0060072	12/2018	Zeng	N/A	N/A
2019/0262129	12/2018	Cooper et al.	N/A	N/A
2020/0000579	12/2019	Manash et al.	N/A	N/A
2020/0108225	12/2019	Jamal et al.	N/A	N/A
2020/0138572	12/2019	Zhao et al.	N/A	N/A
2020/0323668	12/2019	Diedering et al.	N/A	N/A
2020/0345494	12/2019	Srinimukesh et al.	N/A	N/A
2020/0352718	12/2019	Rowe et al.	N/A	N/A
2021/0015615	12/2020	Groothuis et al.	N/A	N/A
2021/0145576	12/2020	Becerra et al.	N/A	N/A
2021/0228354	12/2020	Rafiee et al.	N/A	N/A
2021/0259835	12/2020	Tyler et al.	N/A	N/A
2021/0307900	12/2020	Hacohen	N/A	N/A
2021/0378817	12/2020	Nia et al.	N/A	N/A
2021/0386544	12/2020	Cooper et al.	N/A	N/A
2022/0142777	12/2021	Scheinblum et al.	N/A	N/A

2022/0287836	12/2021	Landon et al.	N/A	N/A
2022/0346993	12/2021	Srinimukesh et al.	N/A	N/A
2023/0000624	12/2022	Okabe et al.	N/A	N/A
2023/0200980	12/2022	Peterson et al.	N/A	N/A
2023/0218391	12/2022	Dass et al.	N/A	N/A
2023/0380963	12/2022	Kaufman et al.	N/A	N/A
2023/0390052	12/2022	Okafor et al.	N/A	N/A
2023/0404753	12/2022	Luong et al.	N/A	N/A
2024/0008978	12/2023	Nawalakhe et al.	N/A	N/A
2024/0091000	12/2023	King et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2304325	12/2007	CA	N/A
2246526	12/1972	DE	N/A
19532846	12/1996	DE	N/A
19546692	12/1996	DE	N/A
19857887	12/1999	DE	N/A
19907646	12/1999	DE	N/A
10049812	12/2001	DE	N/A
10049813	12/2001	DE	N/A
10049814	12/2001	DE	N/A
10049815	12/2001	DE	N/A
10010074	12/2004	DE	N/A
102006052564	12/2006	DE	N/A
0144167	12/1984	EP	N/A
0103546	12/1987	EP	N/A
0592410	12/1994	EP	N/A
0850607	12/1997	EP	N/A
0597967	12/1998	EP	N/A
1057460	12/1999	EP	N/A
1088529	12/2000	EP	N/A
1469797	12/2003	EP	N/A
1259194	12/2004	EP	N/A
1171059	12/2004	EP	N/A
1255510	12/2006	EP	N/A
1239901	12/2006	EP	N/A
1849440	12/2006	EP	N/A
1570809	12/2008	EP	N/A
1472996	12/2008	EP	N/A
1653888	12/2008	EP	N/A
1935377	12/2009	EP	N/A
1369098	12/2013	EP	N/A
2124826	12/2013	EP	N/A
2745805	12/2014	EP	N/A
2749254	12/2014	EP	N/A
2918249	12/2014	EP	N/A
2168536	12/2015	EP	N/A
2413842	12/2016	EP	N/A
2446915	12/2017	EP	N/A
3057541	12/2017	EP	N/A
3037064	12/2017	EP	N/A
3046511	12/2017	EP	N/A

3142603	12/2017	EP	N/A
3075354	12/2017	EP	N/A
3184083	12/2018	EP	N/A
2918249	12/2019	EP	N/A
3417813	12/2019	EP	N/A
2777616	12/2019	EP	N/A
3139864	12/2019	EP	N/A
2750630	12/2020	EP	N/A
2777617	12/2021	EP	N/A
2948103	12/2021	EP	N/A
2967858	12/2022	EP	N/A
3570779	12/2022	EP	N/A
3294220	12/2022	EP	N/A
2788217	12/1999	FR	N/A
1264471	12/1971	GB	N/A
1315844	12/1972	GB	N/A
2056023	12/1980	GB	N/A
2398245	12/2003	GB	N/A
1271508	12/1985	SU	N/A
1991016041	12/1990	WO	N/A
1991017720	12/1990	WO	N/A
1992017118	12/1991	WO	N/A
1993001768	12/1992	WO	N/A
1997024080	12/1996	WO	N/A
1998029057	12/1997	WO	N/A
1999033414	12/1998	WO	N/A
1999040964	12/1998	WO	N/A
1999047075	12/1998	WO	N/A
2000018333	12/1999	WO	N/A
2000041652	12/1999	WO	N/A
2000047139	12/1999	WO	N/A
2000061034	12/1999	WO	N/A
2001028459	12/2000	WO	N/A
2001035878	12/2000	WO	N/A
2001049213	12/2000	WO	N/A
2001054624	12/2000	WO	N/A
2001054625	12/2000	WO	N/A
2001062189	12/2000	WO	N/A
2001064137	12/2000	WO	N/A
2001076510	12/2000	WO	N/A
2002036048	12/2001	WO	N/A
2003047468	12/2002	WO	N/A
2003092554	12/2002	WO	N/A
2004030569	12/2003	WO	N/A
2005011534	12/2004	WO	N/A
2005034812	12/2004	WO	N/A
WO-2005062980	12/2004	WO	N/A
2005087140	12/2004	WO	N/A
2005102015	12/2004	WO	N/A
2006014233	12/2005	WO	N/A
2006034008	12/2005	WO	N/A
2006085225	12/2005	WO	N/A

2006108090	12/2005	WO	N/A
2006111391	12/2005	WO	N/A
2006138173	12/2005	WO	N/A
2007025028	12/2006	WO	N/A
2008005405	12/2007	WO	N/A
2008035337	12/2007	WO	N/A
2008125153	12/2007	WO	N/A
2008147964	12/2007	WO	N/A
2008150529	12/2007	WO	N/A
2009024859	12/2008	WO	N/A
2009026563	12/2008	WO	N/A
2009042196	12/2008	WO	N/A
2009091509	12/2008	WO	N/A
2009094500	12/2008	WO	N/A
2010005524	12/2009	WO	N/A
2010008549	12/2009	WO	N/A
2010121076	12/2009	WO	N/A
2011002996	12/2010	WO	N/A
2011081997	12/2010	WO	N/A
2012032187	12/2011	WO	N/A
2012095455	12/2011	WO	N/A
2013028387	12/2012	WO	N/A
2013106585	12/2012	WO	N/A
2014018432	12/2013	WO	N/A
2014079291	12/2013	WO	N/A
2014145338	12/2013	WO	N/A
2014149865	12/2013	WO	N/A
2014163706	12/2013	WO	N/A
2014194178	12/2013	WO	N/A
2015057407	12/2014	WO	N/A
2015077274	12/2014	WO	N/A
2016016899	12/2015	WO	N/A
2017035487	12/2016	WO	N/A
2018213209	12/2017	WO	N/A
2022002054	12/2021	WO	N/A
2023006048	12/2022	WO	N/A
2023076103	12/2022	WO	N/A
2023081236	12/2022	WO	N/A
2023091769	12/2022	WO	N/A
2023096804	12/2022	WO	N/A
2023154250	12/2022	WO	N/A
2023196150	12/2022	WO	N/A
2023244454	12/2022	WO	N/A
2023244767	12/2022	WO	N/A
2023250114	12/2022	WO	N/A
2024001789	12/2023	WO	N/A
2024003620	12/2023	WO	N/A
2024007575	12/2023	WO	N/A
2024009540	12/2023	WO	N/A
2024010739	12/2023	WO	N/A
2024030520	12/2023	WO	N/A

OTHER PUBLICATIONS

Andersen, et al., "Transluminal implantation of artificial heart valves. Description of a new expandable aortic valve and initial results with implantation by catheter technique in closed chest pigs." *European Heart Journal* (1992), 13, 704-708. cited by applicant

Andersen, Henning Rud, "History of Percutaneous Aortic Valve Prosthesis," *Herz* 34 2009 Nr. 5, Urban&Vogel, pp. 343-346, Skejby University Hospital Department of Cardiology, Aarhus, Denmark. cited by applicant

Dotter, M.D., Charles T., "Transluminal Treatment of Arteriosclerotic Obstruction," University of Oregon's Minthorn Memorial Laboratory for Cardiovascular Research through Radiology, *Circulation*, vol. XXX, Nov. 1964, pp. 654-670. cited by applicant

Inoue, M.D., Kanji, et al., "Clinical Application of Transvenous Mitral Commissurotomy by a New Balloon Catheter," *The Journal of Thoracic and Cardiovascular Surgery* 87:394-402, 1984. cited by applicant

Pavcnik, M.D., Ph.D., Dusan, et al. "Development and Initial Experimental Evaluation of a Prosthetic Aortic Valve for Transcatheter Placement," *Cardiovascular Radiology* 1992; 183:151-154. cited by applicant

Rösch, M.D., Josef, "The Birth, Early Years and Future of Interventional Radiology," *J Vasc Interv Radiol* 2003; 14:841-853. cited by applicant

Ross, F.R.C.S., D.N., "Aortic Valve Surgery," *Guy's Hospital*, London, pp. 192-197, approximately 1968. cited by applicant

Sabbah, Ph.D., Hani N., et al., "Mechanical Factors in the Degeneration of Porcine Bioprosthetic Valves: An Overview," *Journal of Cardiac Surgery*, vol. 4, No. 4, pp. 302-309, Dec. 1989; ISSN 0886-0440. cited by applicant

Wheatley, M.D., David J., "Valve Prostheses," *Rob&Smith's Operative Surgery*, Fourth Edition, pp. 415-424, Butterworths 1986. cited by applicant

Backer, Ole De, MD, et al., "Percutaneous Transcatheter Mitral Valve Replacement—An Overview of Devices in Preclinical and Early Clinical Evaluation," *Contemporary Reviews in Interventional Cardiology*, *Circ Cardiovasc Interv.* 2014;7:400-409. cited by applicant

Bavaria, Joseph E. M.D.: "CardiAQ Valve Technologies: Transcatheter Mitral Valve Implantation," Sep. 21, 2009. cited by applicant

Berrekouw, Eric, PhD, et al., "Sutureless Mitral Valve Replacement With Bioprostheses and Nitinol Attachment Rings: Feasibility In Acute Pig Experiments," *The Journal of Thoracic and Cardiovascular Surgery*, vol. 142, No. 2, Aug. 2011 in 7 pages. cited by applicant

Boudjemline, Younes, et al., "Steps Toward the Percutaneous Replacement of Atrioventricular Valves," *JACC*, vol. 46, No. 2, Jul. 19, 2005:360-5. cited by applicant

CardiAQ Valve Technologies, "Innovations in Heart Valve Therapy," In3 San Francisco, Jun. 18, 2008, PowerPoint presentation in 19 slides. cited by applicant

Chiam, Paul T.L., et al., "Percutaneous Transcatheter Aortic Valve Implantation: Assessing Results, Judging Outcomes, and Planning Trials," *JACC: Cardiovascular Interventions*, The American College of Cardiology Foundation, vol. 1, No. 4, Aug. 2008:341-50. cited by applicant

Condado, Jose Antonio, et al., "Percutaneous Treatment of Heart Valves," *Rev Esp Cardio.* 2006;59(12):1225-31. cited by applicant

Feldman, Ted, MD. "Prospects for Percutaneous Valve Therapies," *Circulation* 2007; 116:2866-2877. cited by applicant

Fornell, Dave, "Transcatheter Mitral Valve replacement Devices in Development," *Diagnostic and Interventional Cardiology*, Dec. 30, 2014, p. 3, <<http://www.dicardiology.com/article/transcatheter-mitral-valve-replacement-devices-development>>. cited by applicant

Grube, E. et al., "Percutaneous aortic valve replacement for severe aortic stenosis in high-risk patients using the second- and current third-generation self-expanding CoreValve prosthesis: device success and 30-day clinical outcome." *J Am Coll Cardiol.* Jul. 3, 2007;50(1):69-76. Epub Jun. 6, 2007. cited by applicant

Karimi, Houshang, et al., ".Percutaneous Valve Therapies," *SIS 2007 Yearbook*, Chapter 11, pp. 1-11. cited by applicant

Kronemyer, Bob, "CardiAQ Valve Technologies: Percutaneous Mitral Valve Replacement," *Start Up—Windhover Review of Emerging Medical Ventures*, vol. 14, Issue No. 6, Jun. 2009, pp. 48-49. cited by applicant

Leon, Martin B., et al., "Transcatheter Aortic Valve Replacement in Patients with Critical Aortic Stenosis: Rationale, Device Descriptions, Early Clinical Experiences, and Perspectives," *Semin. Thorac. Cardiovasc. Surg.* 18:165-174, 2006 in 10 pages. cited by applicant

Lutter, Georg, et al., "Off-Pump Transapical Mitral Valve Replacement," *European Journal of Cardio-thoracic Surgery* 36 (2009) 124-128. cited by applicant

Ma, Liang, et al., "Double-Crowned Valved Stents For Off-Pump Mitral Valve Replacement," *European Journal of Cardio-thoracic Surgery* 28 (2005) 194-199. cited by applicant

Ostrovsky, Gene, "Transcatheter Mitral Valve Implantation Technology from CardiAQ," *medGadget*, Jan. 15, 2010, available at: http://www.medgadget.com/2010/01/transcatheter_mitral_valve_implantation_technology_from_cardiaq.html. cited by applicant

Preston-Maher, Georgia L., et al., "A Technical Review of Minimally Invasive Mitral Valve Replacements," *Cardiovascular Engineering and Technology*, vol. 6, No. 2, Jun. 2015, pp. 174-184. cited by applicant

Ratz, J. Brent, "LSI EMT Spotlight," May 15, 2009. cited by applicant

Ratz, J. Brent et al., "Any experiences making an expandable stent frame?" *Arch-Pub.com*, Architecture Forums: Modeling, Multiple forum postings from Feb. 3, 2009 to Feb. 4, 2009, <http://www.arch-pub.com>. cited by applicant

Ratz, J. Brent, "In3 Company Overview," Jun. 24, 2009. cited by applicant

Spillner, J. et al., "New Sutureless 'Atrial-Mitral-Valve Prosthesis' For Minimally Invasive Mitral Valve Therapy," *Textile Research Journal*, 2010, in 7 pages. cited by applicant

Sondergaard, Lars, et al., "Transcatheter Mitral Valve Implantation: CardiAQ™," *TCT 2013*. cited by applicant

Sondergaard, Lars, et al., "Transcatheter Mitral Valve Implantation: CardiAQ™," *EuroPCR 2013*. cited by applicant

Treede et al.: "Transapical transcatheter aortic valve implantation using the JenaValve™ system: acute and 30-day results of the multicentre CE-mark study." <http://ejcts.oxfordjournals.org/content/41/6/e131.long>. Apr. 16, 2012. cited by applicant

Taramasso et al.: "New devices for TAVI: technologies and initial clinical experiences" <http://www.nature.com/nrcardio/journal/v11/n3/full/nrcardio.2013.221.html?message-global=remove#access>. Jan. 21, 2014. cited by applicant

Webb, John G., et al., "Transcatheter Aortic Valve Implantation: The Evolution Of Prostheses, Delivery Systems And Approaches," *Archives of Cardiovascular Disease* (2012) 105, 153-159. cited by applicant

Wayback Machine, Cleveland Clinic Lerner Research Institute, Transcatheter Mitral Stent/Valve Prosthetic, <https://web.archive.org/web/20130831094624/http://mds.clevelandclinic.org/Portfolio.aspx?n=331>, indicated as archived on Aug. 31, 2013. cited by applicant

"CardiAQ Valve Technologies, Percutaneous Mitral Valve Replacement, Company Overview," at TVT on Jun. 25, 2009. cited by applicant

BioSpace, "CardiAQ Valve Technologies (CVT) Reports First-In-Human Percutaneous Transfemoral, Transseptal Implantation With Its Second Generation Transcatheter Bioprosthesis Mitral Heart Valve," Jun. 23, 2015, p. 1, <http://www.biospace.com/News/cardiaq-valve-technologies-cvt-reports-first-in/382370>. cited by applicant

BioSpace, "CardiAQ Valve Technologies (CVT) Reports Cardiovascular Medicine Milestone: First-In-Humans Percutaneous Implantation of a Bioprosthesis Mitral Heart Valve," Jun. 14, 2012, p. 1, <http://www.biospace.com/News/cardiaq-valve-technologies-cvt-reports/263900>. cited by applicant

Neovasc corporate presentation, Oct. 2009, available at <http://www.neovasc.com/investors/documents/Neovasc-Corporate-Presentation-October-2009.pdf>. cited by applicant

Bavaria, Joseph E. M.D., "CardiAQ Valve Technologies Transcatheter Mitral Valve Implantation", 11 p. 2009, CardiAQ Valve Technologies, Inc., Irvine, California. cited by applicant

Fitzgerald P.J., "Tomorrow's Technology: Percutaneous mitral valve replacement, chordal shortening, and beyond," *Transcatheter Valve Therapies (TVT) Conference*, Jun. 7, 2010, 25 pages, Seattle, Washington. cited by applicant

Herrmann, Howard C., M.D., “Advances in Transseptal Transcatheter Mitral Valve Replacement,” Cardiovascular Research Foundation, tct, Sep. 21-25, 2018, 10 Pages, San Diego, California. cited by applicant

Mack, Michael M.D., “Antegrade Transcatheter Mitral Valve Implantation: A Short-term Experience in Swine Model”, TVT, Sep. 2011, 10 pages, Washington D.C. cited by applicant

Mack, Michael M.D., “Antegrade Transcatheter Mitral Valve Implantation: On-Going Experience in Swine Model,” TVT, Sep. 2011, 16 Pages, Washington D.C. cited by applicant

Transcatheter Aortic Valve Delivery Catheter System Compression Loading System, Medtronic CoreValve™ System, Medtronic Inc, 2014, 61 pages, Santa Ana, California. cited by applicant

Neale, Todd, “Flushing TAVI Valves With Carbon Dioxide May Protect Against Brain Injury”, Conference News, May 16, 2023, 6 Pages, EuroPCR 2023, Paris, France. cited by applicant

Quadri, Arshad., M.D., “Transcatheter Mitral Valve Implantation (TMVI) (An Acute In Vivo Study),” Sep. 21-25, 2010, pp. 1-19, TCT, Washington, D.C. cited by applicant

Rashkind et al., “Historical Aspects of Interventional Cardiology: Past, Present, and Future”, Texas Heart Institute Journal, Interventional Cardiology, vol. 13, No. 4, Dec. 1986, pp. 363-367, Houston, Texas. cited by applicant

Ruiz et al., “Glimpse into the Future New Transcatheter Mitral Valve Treatment, Overview of Novel Transcatheter Valve Technologies,” May 25-28, 2010, 14 pages, EuroPCR 2010, Paris France. cited by applicant

Sondergaard, Lars, “CardiAQ Tmvr Fih - Generation 2,” Cardiovascular Research Foundation, Jun. 2014, 23 pages, TVT, Vancouver, BC. cited by applicant

Primary Examiner: Stewart; Alvin J

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 16/902,773, filed Jun. 16, 2020, which is a continuation of U.S. patent application Ser. No. 16/015,003, filed Jun. 21, 2018, now U.S. Pat. No. 10,687,939, which is a continuation of U.S. application Ser. No. 15/382,429, filed on Dec. 16, 2016, now U.S. Pat. No. 10,010,414, which is a continuation of U.S. application Ser. No. 14/730,639, filed on Jun. 4, 2015, now U.S. Pat. No. 9,532,870, which claims the benefit of U.S. Provisional Application No. 62/009,072, filed Jun. 6, 2014. The prior applications are incorporated herein by reference in their entirety.

FIELD

(1) This disclosure pertains generally to prosthetic devices for repairing and/or replacing native heart valves, and in particular to prosthetic valves for replacing defective mitral valves, as well as methods and devices for delivering and implanting the same within a human heart.

BACKGROUND

(2) Prosthetic valves have been used for many years to treat cardiac valvular disorders. The native heart valves (i.e., the aortic, pulmonary, tricuspid, and mitral valves) serve critical functions in assuring the forward flow of an adequate supply of blood through the cardiovascular system. These heart valves can be rendered less effective by congenital malformations, inflammatory processes, infectious conditions, or disease. Such damage to the valves can result in serious cardiovascular compromise or death. For many years the definitive treatment for such disorders was the surgical repair or replacement of the valve during open-heart surgery. Such surgeries are highly invasive and are prone to many complications, however. Therefore, elderly and frail patients with defective heart valves often go untreated. More recently a transvascular technique has been developed for introducing and implanting a prosthetic heart valve using a flexible catheter in a manner that is much less invasive than open-heart surgery.

(3) In this technique, a prosthetic valve is mounted in a crimped state on the end portion of a flexible

catheter and advanced through a blood vessel of the patient until the prosthetic valve reaches the implantation site. The prosthetic valve at the catheter tip is then expanded to its functional size at the site of the defective native valve, such as by inflating a balloon on which the prosthetic valve is mounted.

(4) Another known technique for implanting a prosthetic aortic valve is a transapical approach where a small incision is made in the chest wall of a patient and the catheter is advanced through the apex (i.e., bottom tip) of the heart. Like the transvascular approach, the transapical approach can include a balloon catheter having a steering mechanism for delivering a balloon-expandable prosthetic heart valve through an introducer to the aortic annulus. The balloon catheter can include a deflectable segment just proximal to the distal balloon to facilitate positioning of the prosthetic heart valve in the proper orientation within the aortic annulus.

(5) The above techniques and others have provided numerous options for high operative risk patients with aortic valve disease to avoid the consequences of open heart surgery and cardiopulmonary bypass. While devices and procedures for the aortic valve are well-developed, such catheter-based procedures are not necessarily applicable to the mitral valve due to the distinct differences between the aortic and mitral valve. The mitral valve has a complex subvalvular apparatus, e.g., the chordae tendineae and papillary muscles, which is not present in the aortic valve.

(6) Surgical mitral valve repair techniques (e.g., mitral annuloplasty) have increased in popularity due to their high success rates, and clinical improvements after repair. In addition to existing mitral valve repair technologies, there are a number of new technologies aimed at making mitral valve repair a less invasive procedure. These technologies range from iterations of the Alfieri stitch procedure, to coronary-sinus-based modifications of mitral anatomy, to subvalvular plications or ventricular remodeling devices, which would incidentally correct mitral regurgitation.

(7) However, for mitral valve replacement, few less-invasive options are available. There are approximately 25,000 mitral valve replacements (MVR) each year in the United States. However, it is estimated that over 300,000 patients meeting the guidelines for treatment are denied treatment based on their ages and/or co-morbidities. Thus, a need exists for minimally invasive techniques for replacing the mitral valve.

(8) In particular, a need exists for minimally invasive techniques with enhanced ease of implantation and reduced risk of misplacement due to operator error or biological variability. Specifically, a need exists for prosthetic heart valves that can be deployed within the valve annulus and that do not require a particular angular alignment. A need also exists for prosthetic heart valves that can move synchronously with the native valve annulus.

SUMMARY

(9) In one representative embodiment, a prosthetic device is provided for implanting at a native mitral or tricuspid valve region of the heart, the native valve region having a native valve annulus and native leaflets. The prosthetic device can comprise a main body configured for placement within the native mitral valve annulus, the main body having a lumen extending between an atrial end and a ventricular end. The prosthetic device can also have an atrial cap extending radially outwardly from the atrial end of the main body. The prosthetic device can also have a plurality of ventricular anchors spaced angularly around a circumference of the main body. Each ventricular anchor can have a proximal end portion connected to the main body at locations proximate the ventricular end, an intermediate portion extending away from the atrial end and then back toward the atrial end so as to define a first bend, and a free distal end portion that extends from the intermediate portion, the distal end portion comprising a first section, a second section, and a second bend between the first and second sections, the first section extending from the intermediate portion in a direction toward the atrial end and radially away from the main body.

(10) In some embodiments, at least one of the ventricular anchors of the prosthetic device comprises a pattern of repeating turns (such as a serpentine pattern).

(11) In some embodiments, the atrial cap comprises a plurality of angularly spaced atrial anchors, each having a proximal end portion connected to the atrial end of the main body and a distal end portion extending generally downwardly toward the ventricular end.

(12) In some embodiments, the proximal end portions of the atrial anchors project upward into the

atrium and curved intermediate portions of the atrial anchors connect the proximal end portions to the distal end portions.

(13) In some embodiments, the atrial cap blocks blood from flowing beyond the atrial end of the main body, along the outside of the main body, when the prosthetic device is implanted.

(14) In some embodiments, the main body is radially compressible to a radially compressed state for delivery into the heart and can self-expand from the compressed state to a radially expanded state.

(15) In some embodiments, in a radially compressed state, each ventricular anchor is linearly extended, such that the proximal end portions and distal end portions are axially aligned, parallel to the axis of the main body.

(16) In some embodiments, the plurality of ventricular anchors is connected to the main body independently of each other without frame segments interconnecting adjacent ventricular anchors.

(17) In some embodiments, the free end portions of the ventricular anchors each comprise a curved or rounded element.

(18) In some embodiments, the plurality of atrial anchors is connected to the main body independently of each other without frame segments interconnecting adjacent atrial anchors.

(19) In some embodiments, the first sections of the distal end portions of the ventricular anchors extend away from a longitudinal axis of the main body and the second sections of the distal end portions extend substantially parallel to the longitudinal axis.

(20) In some embodiments, the second sections of the distal end portions curve toward the atrial end and back toward the ventricular end of the main body.

(21) In some embodiments, the atrial anchors have varying lengths and/or the ventricular anchors have varying lengths.

(22) In some embodiments, the ventricular anchors can be connected to the ventricular end of the main body.

(23) In some embodiments, the ventricular anchors can be connected to the main body at locations spaced from the ventricular end of the main body.

(24) In another representative embodiment, a prosthetic device can have a main body and an atrial cap extending radially outward from the atrial end of the main body. When released from a delivery sheath, the atrial cap can transform from a radially compressed, cylindrical shape extending from the atrial end of the main body to a deployed state in which the atrial cap extends radially outward and curls below the atrial end toward the ventricular end of the main body.

(25) In some embodiments, the prosthetic device can have a plurality of ventricular anchors extending from the ventricular end of the main body.

(26) In some embodiments, the main body can have a cylindrical inlet portion defining an inlet diameter of the main body and a tapered outlet portion defining an outlet diameter of the main body, wherein the outlet diameter is smaller than the inlet diameter.

(27) In some embodiments, the ventricular anchors can have curved portions that extend away from the ventricular end of the main body and curve back toward the atrial end of the main body, wherein the curved portions have a reduced thickness relative to the remaining portions of the anchors.

(28) In another representative embodiment, a method is provided for implanting a prosthetic heart valve at a native atrioventricular valve region having a native valve annulus and a plurality of native leaflets. The method can comprise providing a transcatheter prosthetic heart valve contained within an interior of a sheath of a delivery apparatus, wherein the prosthetic heart valve comprises an annular main body and a plurality of ventricular anchors extending from the main body, the ventricular anchors being connected to the main body independently of each other without frame segments interconnecting adjacent anchors. The method can further comprise delivering the prosthetic device to the native valve region and deploying the prosthetic heart valve from the sheath such that the main body expands within the native annulus and the plurality of ventricular anchors extend behind the native leaflets. Each ventricular anchor has a proximal end portion extending in a direction away from the atrial end of the main body, an intermediate portion extending back toward the atrial end, and a distal end portion extending toward the atrial end and radially away from the main body.

(29) In some embodiments, the native valve annulus is the mitral valve annulus and the prosthetic heart

valve is delivered to the annulus via the left atrium.

(30) In some embodiments, a distal end portion of one or more of the plurality of ventricular anchors projects upward to contact a ventricular surface of the native valve annulus.

(31) In some embodiments, the method further comprises wrapping one or more of the ventricular anchors behind the native leaflets.

(32) In some embodiments, delivering the prosthetic valve comprises transporting the prosthetic heart valve across the atrial septum into the left atrium.

(33) In some embodiments, deployment of the main body causes the distal end portions of the ventricular anchors to rotate toward the main body.

(34) In some embodiments, following deployment, the prosthetic valve and the native valve annulus move in a generally synchronous manner during cardiac cycling.

(35) In some embodiments, the method further comprises advancing the outer sheath distally to recapture the plurality of ventricular anchors within the interior of the outer sheath.

Description

BRIEF DESCRIPTION OF THE FIGURES

(1) FIG. 1A is a side schematic view of an exemplary prosthetic valve, according to one embodiment.

(2) FIG. 1B is a side schematic view of another exemplary prosthetic valve.

(3) FIG. 2 is a top schematic view of the prosthetic valve of FIG. 1A or FIG. 1B.

(4) FIGS. 3A-3C are side schematic views of three bare frames for use in a prosthetic valve, which illustrate three exemplary methods for manufacturing and shaping a frame according to the present disclosure.

(5) FIG. 4 is a top-sided perspective view of an exemplary frame for use in a prosthetic valve.

(6) FIG. 5 is a bottom-sided perspective view of another exemplary frame for use in a prosthetic valve.

(7) FIGS. 6A-6C show three exemplary ventricular anchors for use in a prosthetic valve, each featuring a repeating pattern of turns. FIG. 6A shows a ventricular anchor having a pattern of coils. FIG. 6B shows a ventricular anchor having a serpentine pattern. FIG. 6C shows a ventricular anchor having a helical pattern.

(8) FIG. 7 is a top-sided perspective view of another exemplary frame for use in a prosthetic valve.

(9) FIG. 8 is a bottom-sided perspective view of the prosthetic valve of FIG. 7.

(10) FIG. 9 is a side view of another exemplary frame for use in a prosthetic valve, with a single atrial anchor and a corresponding ventricular anchor shown in a deployed configuration for purposes of illustration. The remaining atrial and ventricular anchors are shown in a non-deployed, delivery configuration. FIG. 9A is an enlarged view of the atrial anchor and the ventricular anchor that are shown in the deployed configuration in FIG. 9.

(11) FIG. 10 is a side schematic view of another exemplary frame for use in a prosthetic valve, with a single atrial anchor and a corresponding ventricular anchor shown in a deployed configuration for purposes of clarity. The remaining atrial and ventricular anchors are shown in a non-deployed, delivery configuration.

(12) FIG. 11 is a top-sided perspective view of another exemplary frame for use in a prosthetic valve.

(13) FIG. 12 is a bottom-sided perspective view of the prosthetic valve of FIG. 11.

(14) FIG. 13 is a top view of another exemplary prosthetic valve with an atrial cap having serpentine arms.

(15) FIG. 14 is a top view of another exemplary prosthetic valve with an atrial cap having a combination of serpentine arms and non-serpentine arms.

(16) FIGS. 15A-15C show an exemplary method for deploying a prosthetic valve from a retractable sheath.

(17) FIGS. 16A-16D show an exemplary method for implanting a prosthetic valve at the mitral valve annulus region via a transseptal approach.

(18) FIG. 17 shows another exemplary method for implanting a prosthetic valve at the mitral valve annulus region, via a transatrial approach.

- (19) FIG. **18** shows another exemplary method for implanting a prosthetic valve at the mitral valve annulus region, via a transfemoral approach.
- (20) FIG. **19** shows another exemplary method for implanting a prosthetic valve at the mitral valve annulus region, via a transventricular approach.
- (21) FIG. **20** illustrates the ventricle side of a native mitral valve having ventricular anchors that engage the tissue of the native valve, creating a seal against the outer surface of the main body of the frame. The prosthetic leaflets and material layers are omitted for clarity of illustration.
- (22) FIG. **21** shows a side elevation view of another exemplary embodiment of a frame for a prosthetic valve.
- (23) FIG. **22** shows a side view of a metal tube for forming the frame of FIG. **21**, shown with an area of reduced thickness that forms a portion of the ventricular anchors.
- (24) FIG. **23** shows the tube of FIG. **22** and a pattern for laser cutting the frame from the tube.
- (25) FIG. **24** shows a cross-sectional view of a ventricular anchor of the frame of FIG. **21**.
- (26) FIG. **25** shows a side elevation view of another exemplary embodiment of a frame for a prosthetic valve.
- (27) FIG. **26** shows the frame of FIG. **25** covered by an outer skirt.
- (28) FIG. **27** is an enlarged, perspective view of a ventricular anchor of the frame of FIG. **25**.

DETAILED DESCRIPTION

(29) Overview

- (30) When a native valve fails to function properly, a prosthetic valve replacement can help restore the proper functionality. Compared to the aortic valve, however, which has a relatively round and firm annulus (especially in the case of aortic stenosis), the mitral valve annulus can be relatively less firm and more unstable. Consequently, it may not be possible to secure a prosthetic valve that is designed primarily for the aortic valve within the native mitral valve annulus by relying solely on friction from the radial force of an outer surface of a prosthetic valve pressed against the native mitral annulus.
- (31) Described herein are embodiments of prosthetic valves and components thereof that are primarily intended to be implanted at the mitral valve region of a human heart, as well as devices and methods for implanting the same. The prosthetic valves can be used to help restore and/or replace the functionality of a defective native valve. These prosthetic valves are not restricted to use at the native mitral valve annulus, however, and can be used to replace other valves within the heart, such as the tricuspid valve, aortic valve, and pulmonary valve. In some cases, the disclosed devices can also be used to replace a venous valve or generate a valved or valveless fistula or patent foramen ovale (PFO).
- (32) In general, the prosthetic valves described herein employ an “atrial cap” and ventricular anchors instead of (or in addition to) radial friction forces, to secure the prosthetic valve within the native valve annulus. The atrial cap can comprise a plurality of atrial anchors spaced angularly around a circumference of the prosthetic valve. The atrial anchors can together form an atrial sealing portion that extends radially outward and downward, from the main body, to cover the atrial surface of the native annulus.
- (33) FIGS. **1A**, **1B** and **2** illustrate the general concept for the prosthetic valve, showing two exemplary prosthetic valve embodiments **10**. FIG. **1A** is a side view of a first embodiment of the prosthetic valve. FIG. **1B** is a side view of a second embodiment of the prosthetic valve. FIG. **2** is a top plan view applicable to both embodiments. Each prosthetic valve **10** has a valve structure **4** comprising a plurality of leaflets **6**, and a frame comprising a main body (which is covered by an outer skirt **12**), an atrial cap member **14** extending from the inflow end of the main body, and a plurality of ventricular anchors **16** extending from the outflow end of the main body. The atrial cap **14** can be configured to apply a constant pressure on the atrial surface of the native valve annulus. As shown in FIG. **1B**, the atrial cap **14** can be angled downwardly toward the ventricular anchors to produce or to augment this pressure. In other embodiments, as shown in FIG. **1A**, the cap **14** is substantially flat and extends radially outwardly at about a 90-degree angle relative to the main body.
- (34) The atrial cap **14** can further comprise a plurality of radially-extending support elements, arms, struts, or anchors **18** (FIG. **2**). The support elements **18** and/or the spaces in between the elements **18** can be covered by a blood-impermeable material cover or layer **20** (e.g., a biocompatible fabric or tissue

material layer). In this manner, the atrial cap **14** can block blood from flowing back into the left atrium between the outer surfaces of the prosthetic valve **100** and the native valve tissue during systole. The atrial cap can also ensure that all, or substantially all, of the blood passes through the one-way valve as it flows from the left atrium to the left ventricle during diastole. As such, the atrial cap prevents or reduces perivalvular leakage.

(35) The skirt **12** can be connected to the inner and/or outer surfaces of the main body to form at least one layer or envelope covering some or all of the openings in the main body. The skirt **12** can be connected to the frame, for example, by sutures. The skirt **12** and the layer **20** can comprise a fabric that is impermeable to blood but can allow for tissue ingrowth. The skirt **12** and the layer **20** can comprise synthetic materials, such as polyester material or a biocompatible polymer. One example of a polyester material is polyethylene terephthalate (PET). Another example is expanded polytetrafluoroethylene (ePTFE), either alone, or in combination at least one other material. Alternative materials can also be used. For example, the skirt **12** and the layer **20** can comprise biological matter, such as pericardial tissue (e.g., bovine, porcine, or equine pericardium) or other biological tissue.

(36) In some embodiments, the atrial cap **14** can comprise a plurality of atrial arms or anchors, which can project radially outward and/or downward to provide an effective, atraumatic sealing configuration, as further described below. These atrial anchors and/or the spaces between the anchors can be covered by a blood-impermeable material.

(37) As discussed above, in the embodiment illustrated in FIG. **1B**, the atrial cap **14** is angled or concave downwards. The atrial cap comprises atrial anchors **18** (FIG. **2**) that angle downwards from an inlet end of a frame **58** (FIGS. **3A-3C**), forming acute angles therewith.

(38) Some embodiments of an angled atrial cap **14** generate a downward force on the native valve annulus, improving a compressive seal with the native valve annulus. Moreover, in some embodiments in which at least one atrial anchor **18** or one group of atrial anchors is independently movable or positionable with respect to another, the atrial anchors **18** better conform to the shape of the native valve. For example, the native mitral valve complex, including the annulus, trigones, and leaflets, typically has a saddle shape on the atrial side. Such atrial anchors **18** also permit the atrial cap **14** to accommodate movement of the heart tissue over the cardiac cycle. This adaptability to the shape and/or movement of the native tissue improves sealing and/or reduces perivalvular leakage in some embodiments.

(39) The ventricular anchors **16** can be configured to extend into the ventricle and to project back upward towards the native valve annulus. The ventricular anchors **16** can be spaced angularly around a circumference of a ventricular end of the prosthetic valve **10**. In the illustrated embodiment, the ventricular anchors are connected to the main body of the frame independently of each other, that is, without additional metal frame segments or struts interconnecting adjacent anchors. In this manner, each ventricular anchor can flex relative to the others, as well as relative to the main body to ensure or facilitate the anchors closely engaging adjacent tissue in the left ventricle, including the native leaflets, the trigone areas, and/or the chordae tendineae. The anchors **16** can be configured such that their distal ends contact a ventricular side of the native valve annulus and/or an adjacent tissue region (such as one or more trigone areas). Proximal end portions of the anchors **16** can extend downward from the main body into the ventricle, intermediate portions of the anchors can wrap behind the leaflets, and distal end portions can extend upward to (optionally) contact the native annulus and/or adjacent tissue areas. One or more of the ventricular anchors **16** can, but need not necessarily, pin or otherwise capture a leaflet between the anchor and the main body.

(40) In some embodiments, the individual atrial and/or ventricular anchors have equal lengths and/or are substantially symmetrically arranged around the main body. In other embodiments, at least one atrial and/or ventricular anchor independently has a different length and/or is asymmetrically arranged around the respective end of the main body compared with one or more other anchors of the same type. In some cases, the native valve annulus is asymmetrical in shape, such that having atrial and/or ventricular anchors with non-equal lengths and/or asymmetrical arrangements is desirable. In some cases, shorter atrial and/or ventricular anchors can be placed adjacent to thinner areas of the atrial or ventricular septum. Additionally, the aortic valve is positioned behind the anterior leaflet of the native mitral valve,

so the atrial anchors and/or ventricular anchors facing anteriorly (i.e., facing the aortic valve) may be relatively shorter to avoid disrupting or otherwise interfering with the function of the aortic valve. Finally, some embodiments comprise longer ventricular anchors that project upward to contact the native valve annulus and shorter ventricular anchors that do not project as far upward. In some embodiments, one or more of the shorter ventricular anchors projects upward to interact with the chordae tendineae.

(41) In some embodiments, the individual atrial and/or ventricular anchors have a consistent thickness along their respective lengths. In other embodiments, one or more of the individual atrial and/or ventricular anchors have a variable thickness along its length. Varying the thickness of anchor can provide benefits with regard to strain reduction, for example, helping to reduce plastic deformation and risk of fracture. A variable thickness can also make the anchors flexible at certain points to help reduce the stress placed on adjacent anatomical structures.

(42) When used to refer to portions of a ventricular or atrial anchor, the terms “proximal” and “distal” refer to locations relative to the attachment point of the anchor to the main body of the frame. The “proximal end” of the anchor is the end closest to the attachment point of the anchor to the main body. The “distal end” of the anchor is the end farthest away from the attachment point of the anchor to the main body when the anchor is fully extended.

(43) The plurality of ventricular anchors **16** can be spaced around the circumference of the prosthetic valve at about equal intervals. In other embodiments, the spacing between ventricular anchors is not equal. In some embodiments, the ventricular anchors can extend radially outward and upward (toward the annulus), and thus, in certain embodiments, the distance between distal end portions of adjacent ventricular anchors is greater than the distance between proximal end portions of the ventricular anchors. In various embodiments, the contact between the ventricular anchors (which may be covered with a layer of fabric or tissue) and tissue in the vicinity of the native valve annulus (along the ventricular side) can also promote tissue in-growth.

(44) By “sandwiching” the native valve annulus from the atrial and ventricular sides, the prosthetic valve **10** can move with the native annulus in a generally synchronous manner.

(45) Synchronous movement of an implanted prosthetic valve **10** can confer specific advantages, including faster and/or improved endothelialization, enhanced in-growth, reduced abrasion of surrounding tissue, and enhanced durability of the prosthetic device. Furthermore, in addition to providing an anchoring means for the prosthetic valve **10**, the ventricular anchors **16** can remodel the left ventricle to help treat an underlying cause of mitral regurgitation: left ventricle enlargement/dilation. The ventricular anchors **16** can pull the native mitral valve leaflets closer together and toward the left atrium and, via the chordae tendineae, thereby pull the papillary muscles closer together, which can positively remodel the ventricle acutely and prevent the left ventricle from further enlarging. Thus, the ventricular anchors **16** can also be referred to as tensioning members or reshaping members.

(46) As used herein, the terms “downward” and “upward” are merely terms of convenience. A prosthetic device for implantation in a mitral valve annulus, for example, will be positioned such that a ventricular anchor configured to project back toward the atrium and native valve annulus will thereby be substantially extending “upward.” Likewise, an atrial anchor or other rim portion configured to project in the direction of the ventricle will thereby be extending “downward.” In general, because the use of the terms “upward” and “downward” are merely conventions, there is no absolute requirement for the ventricular anchor to be oriented substantially or even partially “downward” (relative to the user, subject or environment) when the device is in use. Except for when indicated, the positions and orientations of frame components (such as ventricular anchors) are described in the expanded configuration.

(47) Additional Frame and Prosthetic Valve Embodiments

(48) FIGS. 3A-3C show three exemplary frame configurations **52** that can be used for the prosthetic valve **10**, including manufacturing details and assembly techniques. The frame **52** can comprise a main body **58**, an atrial cap **64** and plurality of ventricular anchors **66**. The main body **58** can comprise three (or more) rows of circumferentially-extending, angled struts **74**. The atrial cap **64** can be substantially flat and can comprise a plurality of arms **70** projecting radially outward from points along the main body **58**, spaced circumferentially apart around an atrial end **60** of the main body.

(49) As shown in FIG. 3A, the ventricular anchors **66** can be manufactured as separate pieces, and subsequently connected together at a plurality of connection locations **82** spaced circumferentially apart around a ventricular end **62** of the main body **58**. To assemble the frame, a proximal end portion **72** of each ventricular anchor **66** can be brought into the vicinity of a connection location **82**, and a sleeve **84** (such as a crimp sleeve) can be passed over both the connection location **82** and the proximal end portion **72**. The sleeve **84** can then be compressed (e.g., crimped) to securely join the proximal end portion **72** to the connection location **82**. In addition to or in lieu of the sleeve **84**, the anchors **66** can be welded to the frame **52** at the connection points **82**.

(50) Alternatively, as shown in FIGS. 3B-3C, the frame **52**, the atrial arms **70**, and the plurality of ventricular anchors **66** can be manufactured as a single unitary structure, such as by laser cutting the frame from a metal tube. The ventricular anchors **66** can then be shape set, such as through the use of heat, to produce the requisite conformational properties, including having an upward bias.

(51) As shown in FIG. 3B, in some embodiments, the anchors **66** can be manufactured such that they extend axially away from the main body. A “fold line” **L** is shown extending through the proximal end portions **72** of the anchors **66**, which guides shape setting. From this fold line, the anchors **66** can be biased to turn upward toward the frame **52** (as shown in FIGS. 1A and 1B).

(52) In alternative embodiments, as shown in FIG. 3C, the frame **52** can have an extra row of struts **74** (compared to the embodiments shown in FIGS. 3A-3B), with the anchors **66** projecting radially outwardly from the bottom row of struts and toward the atrial end of the main body.

(53) FIGS. 4-5 illustrate two exemplary bare frames **102** (in an expanded configuration) for use in a prosthetic valve. The frame **102** can comprise a tubular or annular main body **108**, an atrial cap **114** extending radially outwardly from an atrial end **110** of the main body **108**, and a plurality of ventricular anchors **116** extending from a ventricular end **112** of the main body **108**. When the frame **102** is implanted in the native mitral valve region of the heart, the main body **108** can be positioned within the native mitral valve annulus with the ventricular end **112** of the main body **108** being a lower, outlet end, the atrial end **110** of the main body **108** being an upper, inlet end, the ventricular anchors **116** being located in the left ventricle, and the atrial cap **114** being located in the left atrium. The embodiments of FIGS. 4 and 5 are similar except for the particular locations at which the atrial cap **114** connects to the main body, as further described below.

(54) The prosthetic valve can comprise a valve structure supported by and/or within the frame **102**. The valve structure can include a plurality of prosthetic leaflets and/or other components for regulating the flow of blood in one direction through the prosthetic valve. For example, valve structure can be oriented within the frame **102** such that an upper end of the valve structure is the inflow end and a lower end of the valve structure is the outflow end. The leaflets can comprise any of various suitable materials, such as natural tissue (e.g., bovine pericardial tissue) or synthetic materials. The valve structure can be mounted to the frame **102** using suitable techniques and mechanisms. In some embodiments, leaflets can be sutured to the frame **102** in a tricuspid arrangement. The prosthetic valve can also include a blood-impermeable skirt mounted on the outside and/or the inside of the main body.

(55) Additional details regarding components and assembly of prosthetic valves (including techniques for mounting leaflets to the frame) are described, for example, in U.S. Patent Application Publication No. 2009/0276040 A1 and U.S. Patent Publication No. 2010/0217382 A1, which are incorporated by reference herein.

(56) In an expanded state, as shown in FIGS. 4-5, the main body **108** of the frame **102** can form an open-ended tube. An outer surface of the main body **108** can have dimensions similar to that of the mitral orifice, i.e., the inner surface of the mitral annulus, but not necessarily. In some embodiments, for example, the outer surface of the main body **108** can have diametrical dimensions that are smaller than the diametrical dimensions of the native mitral orifice, such that the main body **108** can fit within the mitral orifice in the expanded state without substantially stretching the native mitral annulus. In such embodiments, the frame **102** need not rely on a pressure fit, or friction fit, between the outer surface of the main body **108** and the inner surface of the mitral annulus for prosthetic valve retention. Instead, the frame **102** can rely on the ventricular anchors **116** and/or the atrial cap **114** for retention. In other embodiments, however, the main body **108** can be configured to expand to an equal or greater size than

the native mitral orifice and thereby create a pressure fit when implanted, which can be complementary to the use of ventricular anchors and/or the atrial cap for retention.

(57) The frame **102** can have a wire mesh configuration and can be radially collapsible and expandable between a radially expanded state and a radially compressed state to enable delivery and implantation at an atrioventricular valve region of the heart (i.e., at the mitral or tricuspid valve region). The wire mesh can include metal wires or struts arranged in a lattice pattern, such as a sawtooth or zig-zag pattern, but other patterns may also be used. The frame **102** can comprise a shape-memory material, such as nitinol, to enable self-expansion from the radially compressed state to the expanded state. In other embodiments, the frame **102** can be plastically expandable from a radially compressed state to an expanded state by an expansion device, such as an inflatable balloon (not shown), for example. Such plastically expanding frames can comprise stainless steel, chromium alloys, and/or other suitable materials.

(58) In the illustrated embodiment, the frame **102** comprises a total of twelve ventricular anchors **116**. In other embodiments, the frame can have a fewer or greater number of ventricular anchors, however. The ventricular anchors **116** can each further comprise a proximal or fixed end portion **122**, an intermediate portion **124** and a distal or free end portion **126**. The proximal end portion **122** can be connected directly to the ventricular end **112** of the main body **108**, and can project downwardly (into the ventricle toward the apex). The intermediate portion **124**, located between the proximal end portion **122** and the distal end portion **126**, can be curved such that the intermediate portion **124** extends downwardly from the proximal end portion **122** and then changes direction to extend upwardly toward the mitral valve annulus. The curved intermediate portion **124** can form between about a quarter-turn and about a half-turn, such that the curved segment forms an atraumatic surface for contacting adjacent tissue and structures, such as the chordae tendineae. In some embodiments, the anchors **116** also extend radially outward relative to the main body **108**, and thereby project in an angled direction.

(59) The distal end portion **126** can finally terminate in a curved, atraumatic head portion **128** having a distal end surface **130** for contacting the native valve annulus. Each distal head portion **128** can comprise a pair of open areas **129** through which tissue can protrude (e.g., tissue on the ventricular side of the native valve annulus tissue). Some embodiments of the head portion have a different shape, for example, a closed shape, a circle, an oval shape, a teardrop shape, a cupped shape, a coil, a spiral, or a serpentine shape. Some embodiments of the frame **102** comprise at least one first distal portion with a different shape from at least one second distal head portion. In some embodiments, the head portion **128** is angled relative to the remainder of the distal end portion **126**. For example, as shown in FIGS. 4-5, the head portions **128** can be configured to splay radially outward relative to the rest of the distal end portions **126**. Thus, the angle of the head portion **128**, relative to the longitudinal axis of the main body **108**, can be greater than the angle of the remainder of the distal end portion **126**. As shown, the distal end portion **126** comprises an upper section **127** (proximal to the head portion **128**) which splays radially outward, relative to the remainder of the distal end portion **126**. In some embodiments, the upper section **127** is curved. In some embodiments, the head portion **128** splays radially outward, while the upper section **127** does not splay radially outward.

(60) One or more of the ventricular anchors **116** can be substantially flexible (and/or more flexible than the other anchors **116**) and may include a pattern of repeating turns **120**. FIGS. 4-5 show two such flexible ventricular anchors **116a** positioned adjacent to one another. Other embodiments include a greater or fewer number of flexible ventricular anchors **116a**. For example, some embodiments include no flexible ventricular anchors, while in other embodiments all of the ventricular anchors are flexible ventricular anchors. A “turn” as used herein can refer to any curved portion which forms a generally circular path and/or encompasses a complete change in direction. FIGS. 6A-6C show different configurations for a ventricular anchor **116** comprising a pattern of repeating turns.

(61) A turn can encompass, for example, a two-dimensional looped coil configuration (FIG. 6A), a three-dimensional helical configuration (FIG. 6C), or a serpentine configuration (FIGS. 4-5 and 6B). “Serpentine,” as used herein, refers to a configuration in which a series of numerous segments are connected by curved intermediate portions to form a generally linear overall arrangement. In some cases, at least one of the anchors has a serpentine configuration comprising a plurality of substantially

straight, parallel segments. In some cases, at least one of the anchors has a serpentine configuration comprising a plurality of substantially curved segments. In some cases, as shown in FIG. 6B, at least one of the anchors has a serpentine segment comprising both a plurality of substantially straight, parallel segments and a plurality of substantially curved segments. In other embodiments, a flexible ventricular anchor **116a** comprises a different pattern, for example, a zigzag or sinusoidal pattern. Some embodiments of the flexible ventricular anchor comprises a combination of at least one more flexible portion, for example, a portion comprising a pattern of repeating turns, and at least one less flexible portion, for example, a substantially straight portion. Some embodiments comprise a combination of flexible portions, for example, a serpentine portion and a helical portion.

(62) In various embodiments, the more flexible ventricular anchors **116a** can be positioned adjacent to sensitive anatomical structures, such as adjacent the ventricular septum in the vicinity of the native mitral valve annulus. In various embodiments, the more flexible (e.g., serpentine) anchors can have the same overall shape as the less flexible ventricular anchors, to various extents. For example, while they can be shaped or otherwise biased to curve upward like the other anchors, it may not be necessary to specifically shape them to splay radially outward, given their flexibility. The possible variations for the ventricular anchors **116**, for example, length and radial extent, also apply to the flexible ventricular anchors.

(63) As shown in FIG. 6B, ventricular anchors **116** having a serpentine shape can comprise a group of substantially straight, parallel segments **148** and/or a group of substantially curved segments **152**. The segments **148** can be interconnected by curved connecting segments or bends **149**. In some embodiments, the anchors **116** can have straighter portions nearer the main body **108** (i.e., the proximal end portions **122**) and more curved portions nearer the terminal ends (i.e., the distal end portions **126**). In some embodiments, the serpentine shape (such as the parallel segments and/or the curved bends) can be thicker at the proximal end portions **122** than at the distal end portions **126**. Including a serpentine shape in the anchors **116** can decrease their stiffness and/or decrease the chance of they will fail due to fatigue. In some embodiments, by increasing the thickness of the serpentine anchors, their flexibility is decreased, and by decreasing their thickness, their flexibility is increased.

(64) Referring again to FIGS. 4-5, the atrial cap **114** can be integral with the main body **108** and comprised of the same wire mesh lattice as the main body **108** such that the atrial cap **114** can also be radially collapsible and expandable. The atrial cap **114** can also be radially collapsible and expandable. The atrial cap **114** can be cut from the same tubing as the main body **108** of the frame **102**. In other embodiments, the atrial cap is manufactured as a separate component and subsequently attached to the main body, for example, using any of the methods described above for attaching the ventricular anchors **116** to the main body. The atrial cap **114** desirably exhibits sufficient stiffness to prevent the main body **108** from embolizing into the ventricle, but enough flexibility to avoid or reduce trauma to the native valve anatomy.

(65) In some embodiments, in the expanded state, the atrial cap **114** is generally frustoconical. In some embodiments, the atrial cap **114** has a cellular structure. In some embodiments, the contact between the atrial cap **114** and the tissue of the atrial walls and/or the atrial face of the native valve annulus can promote tissue in-growth with the frame, which can improve retention and reduce perivalvular leakage. The atrial cap **114** is desirably configured to provide a substantially effective seal immediately on implantation, and thus does not necessarily require tissue in-growth for effective sealing. Nonetheless, an atrial cap that requires tissue in-growth to provide an effective seal may be desirable in certain circumstances, and is encompassed within the scope of the present disclosure.

(66) The atrial cap **114** can comprise an integrated structure with an outer rim **140** sized and shaped to contact the atrial side of the mitral annulus and tissue of the left atrium when the frame **102** is implanted. The end plan view profile of the outer rim **140** can have a generally circular, oval, or other shape (e.g., a D-shape) that generally corresponds to the native geometry of the atrial wall and the mitral annulus. The outer rim **140** can have a stellate profile comprising a pattern of outwardly protruding triangular rim portions **144** extending around a circumference of the frame **102** at the atrial end **110**.

(67) The rim portions **144** comprise a plurality of angled struts **160** connected to each other at radial outer junctions or nodes **162** and at radial inner junctions or nodes **164**. The struts **160** can be connected

to the main body by radially extending struts **146**. As shown in FIGS. 4-5, the struts **146** can extend from every other junction **164** of adjacent triangular rim portions **144** to the atrial end **110** of the main body **108**. In other embodiments, the struts **146** and junctions **164** have a different periodicity, for example, from 1:3, 1:4, a different ratio, or a combination of ratios. In some cases, as shown in FIG. 4, the struts **146** can be connected to the apices **117** of the angled struts **115** of the uppermost row of struts of the main body at the atrial end **110** of the main body. Alternatively, as shown in FIG. 5, the struts **146** can be connected to junctions or nodes **121** at which adjacent angled struts **115** from the uppermost row of struts intersect the ends of struts **123** in an adjacent row of struts. Some embodiments include at least one strut connected to an apex and at least one strut connected to a node.

(68) In the embodiments illustrated in FIGS. 4 and 5, the body **108** of the frame **102** has a double-body structure, including an annular outer portion overlapping an annular inner portion. In the illustrated embodiments, the atrial cap **114** extends from the outer portion of the body **108**, while the ventricular anchors **116** extend from the inner portion. In other embodiments, the configuration is reversed, with the atrial cap **114** associated with the outer portion and the ventricular anchors **116** with the inner portion; or with both the atrial cap **114** and the ventricular anchors **116** extending from the same portion; or with another combination. In the illustrated embodiments, the atrial cap **114** and the outer portion are integral; and the ventricular anchors **116** and the inner portion are integral. As discussed above, in some embodiments, at least some of the ventricular anchors and/or atrial cap portions are manufactured separately from the body **108** and later attached thereto.

(69) In the illustrated embodiments, the inner and outer portions of the body **108** are coextensive and their struts structures mirror each other and completely overlap each other. In other embodiments, each of the struts of the inner and/or outer portion does not have a counterpart in the other portion. The inner and outer portions are attached to each other, for example, by welding, using interlocking tabs, using suture or wire, and/or with pins.

(70) Embodiments of stent bodies **108** having double-body structures permit increased control over the stent properties, for example, a body with both stiffer and more flexible portions. In some embodiments, one of the inner portion and outer portion is thicker than the other, resulting in thicker ventricular anchors or a thicker atrial cap. Some embodiments are better able to withstand mechanical strain during delivery and/or the cardiac cycle.

(71) FIGS. 7-10 show additional alternative prosthetic valve frame embodiments **202** which comprise a main body **208** (having an atrial end **210** and ventricular end **212**), ventricular anchors **216**, and an atrial cap **214** having a plurality of atrial anchors **220**. The atrial anchors **220** and the ventricular anchors **216** can be spaced angularly apart around the circumference of the atrial end **210** and ventricular end **212**, respectively. In some cases, the atrial anchors **220** and/or the ventricular anchors **216** are spaced apart at equal intervals. The atrial anchors **220** in the illustrated embodiment are connected to the main body **208** independently of each other, without additional frame segments or struts interconnecting adjacent atrial anchors **220**, allowing the atrial anchors to flex relative to each other and the main body **208**. For purposes of illustration, only one atrial anchor **220** and one ventricular anchor **216** are shown in the deployed configuration in FIGS. 9-10. Gaps **213** between adjacent atrial anchors **220** accommodate tissue, including the mitral valve annulus, the trigones, and the native mitral valve leaflets, as well as permitting the atrial anchors to independently adjust to and conform to each patient's particular anatomy.

(72) The atrial anchors **220** can extend generally downwardly from and relative to the atrial end **210** to contact an atrial side of the native valve annulus and/or tissue of the left atrium. Each anchor **220** can extend from an upper row of circumferentially-extending, angled struts **215** at the atrial end **210**. In some embodiments, as shown in FIGS. 7-8, the anchors **220** extend outward from the apices **217** of the struts **215** at the atrial end **210**. In other embodiments, as shown in FIGS. 9-10, the anchors **220** extend from junctions or nodes **219** at which two adjacent circumferential struts **218** of the second row (from the atrial end **210**) intersect the ends of the struts **215** of the uppermost row of struts.

(73) Each atrial anchor **220** can comprise a proximal or fixed end portion **232** connected to the atrial end **210**, an intermediate portion **234**, and a distal or free end portion **236** that projects radially outwardly from the atrial end **210**. The distal end portion **236** can also project downwardly and/or contact the atrial side of the native valve annulus. The proximal end portion **232** can project upwardly from the atrial end

210, and the intermediate portion **234** can comprise a curved portion (or other type of bend) that curves upwardly then downwardly to connect to the distal end portion **236**. The distal end portion **236** can comprise a terminal portion **240** having a head portion **238** at its terminus. The head portion **238** can have an opening **239** (such as a teardrop shaped opening as shown) through which atrial and/or native valve annulus tissue can protrude when pressed against the head portion **238** (FIGS. 7-8). Other embodiments of the head portion have another shape, for example, any of the shapes discussed above for the distal head portion **128** of the ventricular anchor. In the illustrated embodiments, an atrial-tissue-contacting face of the head portion **238** is convex, although in other embodiments, the atrial-tissue-contacting face has another shape, for example, substantially planar, concave, convex, or combinations thereof. In the expanded configuration, the terminal portion **240** can splay radially outward relative to the remainder of the distal end portion **236**.

(74) The atrial anchors **220** can have a flexible and/or serpentine configuration, or can be substantially stiff. In various embodiments, one or more atrial anchors **220** can comprise a repeating pattern of turns (e.g., such as shown in FIGS. 8A-8C) to enhance the flexibility of the anchors, which can be positioned adjacent to sensitive anatomical structures, such as adjacent to the atrial septum in the vicinity of the native mitral valve annulus. The atrial anchors **220** and/or the spaces between the anchors **220** can be covered by a blood-impermeable fabric or tissue material.

(75) The ventricular anchors **216** can project upward, as described above for frame **102**, toward a ventricular side of the native valve annulus (such as to contact the native valve annulus and/or adjacent tissue). Each anchor **216** can have a proximal end portion **222** connected to the ventricular end **212**, an intermediate portion **224** having a bend (such as a curve or angle), and a distal end portion **226**. As shown in the drawings, each proximal end portion **222** can connect to an apex **223** defined by the intersection of two adjacent circumferential struts **221** of a bottom row of struts of the frame **202** at the ventricular end **212**. In alternative embodiments, the proximal end portions **222** of the anchors **216** can connect to nodes or junctions **225** defined by where two adjacent circumferential struts **221** intersect the ends of two struts **218** of a row immediately adjacent the lower most row of struts. The ventricular anchors **216** can have distal end portions **226** with atraumatic head portions **228**, which may be curved and/or rounded. These head portions **228** can each have a teardrop-shaped opening **229** through which ventricular tissue and/or native valve annulus tissue can protrude, or can have another shape, for example, any of the shapes discussed above for the distal head portion **128** of the ventricular anchor.

(76) The terminal ends of the fully deployed ventricular anchors **216** can point in a generally upward direction, substantially parallel to the longitudinal axis of the main body **208**. As shown in FIG. 9, the distal end portions **226** can each have a first section **252** that extends in an angled direction relative to the main body (upward toward the atrial end **210** and away from the main body **208**) and a second section **254**, distal to the first section **252**, that extends more directly upward (toward and generally parallel to the longitudinal axis of the main body **208**).

(77) The distal end portions **226** can thereby comprise a bend (such as an angled bend as shown in FIG. 9 or a curved bend) between the first section **252** and the second section **254**. As a result, the ventricular anchors **216** can comprise two bends over the intermediate and distal end portions **224**, **226**. The two bends of the ventricular anchors **216** can, in some cases, facilitate wrapping of the ventricular anchors **216** around the native leaflets. The second section **254** of the distal end portion **226** can comprise the head portion **228** (which can be located at the terminus of the second section **254**). In some embodiments, the head portion **228** is configured to extend even more directly upward than the rest of the second section **254**.

(78) Referring to FIG. 9A, the first section **252** of the distal end portion **226** extends toward the atrial end **210** at an angle **260** with respect to a line that is parallel to the longitudinal axis of the frame. In particular embodiments, the angle **260** is between about 10 degrees to about 80 degrees, with about 25 degrees being a specific example. The second section **254** extends at an angle **262** relative to the first section **252** in the range of about 100 degrees to about 240 degrees, with about 155 degrees being a specific example.

(79) FIG. 10 shows an alternative embodiment of a second section **254**, which is curved to form a rounded (atraumatic) upward-directed surface for contacting the native valve annulus and/or adjacent

tissue. This atraumatic portion can be formed by the second section **254** alone, or in conjunction with the head portion **228**. Alternatively, the second section **254** can be substantially straight (extending in the same direction as the first segment of the distal end portion **226**), and the head portion **228** can be curved to form a rounded portion facing the atrial end **210** (for example, with a contoured side profile as shown in FIG. 7). As in other embodiments, such a curved head portion **228** can have one or more openings **229** through which tissue can protrude.

(80) FIGS. **11-12** show a top perspective view and a bottom perspective view of another exemplary prosthetic valve frame **302** comprising a main body **308**, an atrial cap **314** extending radially outward from an atrial end **310** of the main body **308**, and a plurality of ventricular anchors **316** extending from a ventricular end **312** of the main body **308**. The atrial cap **314** can comprise a stellate pattern, similar to as described above for frame **102**. In this embodiment, as shown, the triangular frame elements do not extend uniformly around the circumference of the atrial end **310**. Rather, the atrial cap **314** can comprise discrete groups **340** of triangular rim portions **344** that are not directly connected to each other with interconnecting struts.

(81) FIGS. **11-12** show an embodiment having three groups **340** of six triangular rim portions **344**. The groups **340** can be spaced angularly apart around the circumference of the atrial end **310**. The atrial cap **314** can have open areas **342** in between the groups **340** where there are no triangular rim portions **344** or other atrial cap elements. Each group **340** can have four struts **346**, which can be spaced equally apart, connecting the triangular portions **344** to the atrial end **310**. In particular, the struts **346** can be connected to apices **317** along a first row of circumferential struts **315** at the atrial end **310**. For each group **340**, the struts **346** can extend from the main body **308** to the peripheral edges of the outermost triangular portions **344**, and from the main body **308** to every other junction **348** of adjacent triangular rim portions **344** (starting from the outer edges of the outermost triangular rim portions). The ventricular anchors **316** can be shaped and configured similar to as described above for frame **202**. Other embodiments independently include greater or fewer than three groups of rim portions **344**, greater or fewer than four struts **346** per group **340** of rim portions, and or struts that are spaced unequally.

(82) FIGS. **13-14** show top views of two additional prosthetic valve embodiments **400**, each having an atrial cap member **414** with radially extending arm-like atrial anchors or struts **418**. Each arm-like strut **418** extends radially outward from an originating rim portion **438** to an outer rim portion **440**. In some cases, as shown in FIG. **13**, the struts **418** each have a flexible, serpentine configuration (such as also shown in FIG. **8B**). The prosthetic valves **400** can each have at least one layer of fabric or other biocompatible material **412** extending between pairs of struts and covering the terminal portions of each strut **418**. In some embodiments, the material layer **412** covers the struts **418** themselves.

(83) In some cases, the distribution and/or composition of the struts **418** is symmetrical (FIG. **13**). In some embodiments, the composition of the struts **418** is asymmetrical and can include one or more relatively more flexible struts **418a** and one or more less flexible struts **418b**. As shown in FIG. **14**, the more flexible or distensible struts **418a** can be concentrated in one area. For example, the struts which face the atrial septum and/or abutting other sensitive structures (native or foreign) can be more flexible and/or more distensible relative to the other struts. In alternative embodiments, the struts **418** can have any of configurations described above for the ventricular anchors in connection with FIGS. **8A-8C**.

(84) Delivery Techniques and Assemblies

(85) In some cases, for safety and/or other reasons, the disclosed prosthetic devices may be delivered from the atrial side of the atrioventricular valve annulus. Delivery from the atrial side of the native valve annulus can be accomplished in various manners. For example, a transatrial approach can be made through an atrial wall, which can be accessed, for example, by an incision through the chest. Atrial delivery can also be made intravascularly, such as from a pulmonary vein. The prosthetic valve can be delivered to the right atrium via the inferior or superior vena cava. In some cases, left atrial delivery can be made via a transeptal approach (FIGS. **16A-16D**). In a transeptal approach, an incision can be made in the atrial portion of the septum to allow access to the left atrium from the right atrium. The prosthetic valve can also be delivered via transventricular (FIG. **19**), transatrial (FIG. **17**), or transfemoral (FIG. **18**) approaches with small or minimal modifications to the delivery process.

(86) To deliver the prosthetic valve to the native mitral valve annulus, the prosthetic valve can be

radially crimped into a collapsed configuration within a sheath of a delivery catheter. Delivery and placement of the prosthetic valve can be angularly independent, such that the prosthetic valve does not require any special rotational alignment relative to the axis of the prosthetic valve. Thus, during delivery, the prosthetic valve may not require any special rotational placement so as to align the ventricular anchors with particular anatomical landmarks (such as the native valve leaflets, particular portions thereof, native valve commissures, chordae tendineae, and/or location of the aortic valve). (87) While in certain embodiments, the prosthetic valve is positioned such that certain atrial and/or ventricular arms or anchors face sensitive structures (such as the atrial or ventricular septum), this positioning can be approximate and may not necessarily require precise rotational alignment. Thus, such a positioning will generally not require the user to exert a considerable effort achieving a particular rotational alignment for the valve.

(88) In some embodiments, the prosthetic valve can fit inside of a 30 French (F) catheter (in a collapsed state). In some embodiments, the prosthetic valve can be configured to fit into even smaller catheters, such as a 29 F, 28 F, 27 F, or 26 F catheter.

(89) FIGS. 15A-15C show an exemplary prosthetic valve delivery assembly, including the process of expanding the prosthetic valve using a sheath, with reference to an embodiment of the prosthetic valve using the frame illustrated in FIG. 4, although the delivery assembly and method are applicable to each of the frame embodiments disclosed herein. In the delivery configuration (FIG. 15A), a retractable sheath 502 of a delivery catheter 500 can be advanced over the collapsed prosthetic valve, with the main body 108, atrial cap 114 (not shown) and ventricular anchors 116 all in a radially collapsed configuration. The ventricular anchors 116 can be contained within the sheath 502 in a substantially linear arrangement, distal to the main body 108, such that the distal end portions 126 are axially aligned with the intermediate portions 124 and the proximal end portions 122. Thus, while the distal end portions 126 may be biased to extend upward (in the direction of the main body 108) when deployed, the constraining or restraining force applied by the sheath 502 on the anchors 116 can force the distal end portions 126 to extend downward (away from the main body 108 in a generally apical direction) during delivery.

(90) Once the prosthetic valve 100 is delivered to the native annulus region, the sheath 502 can be retracted relative to the prosthetic valve 100, thereby allowing the prosthetic valve 100 to expand radially outward. The release of the prosthetic valve 100 can be conducted in stages. In particular, the ventricular anchors 116 can be released from the sheath 502 (FIG. 15B) prior to the release of the main body 108 (FIG. 15C). As shown in FIG. 15B, when the ventricular anchors 116 are released, the anchors 116 can spread out away from the main body 108, with distal end portions 126 directed radially outward and upward. Then, with release of the main body, the anchors 116 can rotate toward the main body 108, such that the distal end portions 126 can pivot toward the vertical (longitudinal) axis and wrap around the native leaflets.

(91) FIGS. 16A-16D show the process of delivering the prosthetic valve assembly to the native mitral valve annulus, according to one embodiment. FIG. 16A shows the catheter 500 (carrying the prosthetic valve 100 within the sheath 502 at its distal end) introduced into the right atrium of the heart, then across the atrial septum and into the left atrium. The catheter 500 can be further advanced such that the sheath 502 (carrying the prosthetic valve) extends between the native leaflets of the mitral valve and into the left ventricle. At this point, the prosthetic valve 100 can be advanced out of the distal end of the sheath 502, such as by advancing a pusher device distally against the prosthetic valve and/or retracting the sheath 502 relative to the prosthetic valve 100, resulting in the deployment of the ventricular anchors 116 (FIG. 16B).

(92) As shown in FIG. 16B, the deployed ventricular anchors 116 can extend radially outwardly behind the native leaflets 602. The surgeon or other user can then optionally reposition the partially retracted valve 100 as desired, then retract the sheath 502 further to cause the ventricular anchors 116 to engage the native valve annulus (FIG. 16C). In particular, the anchors 116 can be configured to point more directly upward upon full deployment, as compared to when they are partially deployed from the sheath 502. At this point, the user can assess engagement of the ventricular anchors 116 with the native valve annulus (such as through imaging means), prior to retracting the sheath 502 further to deploy the main

body **108** and the atrial cap **114** (FIG. **16D**). As shown in FIGS. **16C-16D**, the ventricular anchors **116** can progressively pivot with deployment of the main body **108**, such that the distal end portions **126** pivot or rotate to point more directly upward.

(93) The head portions **128** of the upward directed distal end portions **126** can contact a ventricular side of the native valve annulus and/or adjacent tissue (such as trigone areas) (FIG. **16D**). In some cases, however, at least one of the ventricular anchors **116** does not reach the native valve annulus or adjacent tissue, but can nonetheless produce stable placement of the prosthetic valve **100**. For example, in some cases, the at least one ventricular anchor **116** can produce this stable placement at the native valve annulus region by engaging the chordae tendineae below the native valve annulus.

(94) In some implementations, one or more ventricular anchors **116** engage the chordae tendineae, one or more ventricular anchors engage the trigone areas, and/or one or more ventricular anchors engage the native leaflets at A2 and/or P2 positions (i.e., between the commissure of the native leaflets). The ventricular anchors that engage the native leaflets and the trigone areas can capture or “sandwich” the native tissue between the outer surface of the main body of the prosthetic valve and the ventricular anchors (or portions thereof) such that the tissue is compressed and engaged by the main body of the prosthetic valve on one side and by the ventricular anchors on the other side. In some embodiments, due to the capturing of the native tissue (such as the native leaflets) between the ventricular anchors and the main body, the native tissue forms a seal around the main body (through 360 degrees) within the left ventricle that impedes blood from traveling along the outside of the main body (as best shown in FIG. **20**). In some embodiments, tissue is also or alternatively sandwiched between the atrial cap **114** and ventricular anchors **116**. By virtue of their relatively thin profile and because the ventricular anchors are not interconnected to each other, the distal ends of the ventricular anchors adjacent the chordae tendineae can pass between individual chords extending from the native leaflets, allowing those anchors to flex/pivot upwardly and assume their fully deployed positions.

(95) Finally, as shown in FIG. **16D**, the sheath **502** can be retracted further to release the atrial cap **114**. The atrial cap **114** forms a seal against the native annulus within the left atrium. The seal created in the left atrium by the atrial cap **114** and the seal created by the ventricular anchors **116** in the left ventricle together prevent, reduce, or minimize the flow of blood between the native annulus and the outside of the main body **108** during diastole and systole. In some embodiments, the main body **108** and the atrial cap **114** are released simultaneously, while in other embodiments, the main body **108** is released prior to the atrial cap **114**. Upon full deployment of the ventricular anchors **116** and the main body **108**, the distal end portions **126** can be positioned against the native valve annulus and/or adjacent tissue (e.g., trigone areas). All stages of deployment of the prosthetic valve **100** can thus be controlled by the catheter **500** without additional activation or manipulation necessary. In certain embodiments, however, the prosthetic valve **100** and/or the catheter **500** can comprise a switch or other control to regulate the release and/or subsequent movement of ventricular anchors **116** or the main body **108**.

(96) In alternative embodiments, the prosthetic valve **100** can be delivered to the native mitral valve via the left ventricle (FIGS. **18-19**). FIGS. **18-19** illustrate deliveries and deployments of embodiments of prosthetic valves incorporating the frame illustrated in FIGS. **7** and **8**, but the assemblies and methods are applicable to prosthetic valves including any of the frames disclosed herein. In a transventricular approach (FIG. **19**), for example, the delivery catheter **500** can be inserted into the left ventricle through a surgical incision made at or near the bare spot on the lower anterior ventricle wall. In this approach and in the transfemoral approach (FIG. **18**), the prosthetic valve **100** can be loaded into the sheath **502** in the reverse position such that the atrial cap **214** is closest to the distal end of the sheath. During implantation, the atrial cap **214** can be deployed first, followed by the main body **208** (FIGS. **7-8**) and the ventricular anchors **216**.

(97) In various embodiments, portions of the prosthetic valve **100** can be partially or fully recaptured during the delivery process entirely through manipulation of the sheath **502**. The ability to recapture the prosthetic valve **100** can be advantageous, for example, in case of damage to the prosthetic valve **100** during delivery and/or in case of operator error in placement of the prosthetic valve **100**. In some embodiments, the ventricular anchors **116** can be recaptured following release from the sheath **502**, simply by advancing the sheath **502** over the deployed anchors **116**, thereby bringing the anchors **116**

back into a linear configuration within the confines of the sheath 502. In some embodiments, the main body 108 can also be recaptured, also by advancing the sheath 502 over the deployed body 108.

(98) Some embodiments of the delivery system include an inner sheath, located within the sheath 502, which contains the main body 108 and the atrial cap 114 but does not contain the ventricular anchors 116. In this case, the sheath 502 can be fully retracted to release the ventricular anchors 116, with release of the main body 108 and atrial cap 114 controlled by retraction of the inner sheath.

(99) FIG. 21 is a side elevation view of another prosthetic valve frame 702 that can be implemented in a prosthetic valve. The frame 702 comprises an annular main body 708, an atrial cap 714 extending radially outward from the atrial end 710 of the main body, and a plurality of ventricular anchors 716 extending from the ventricular end 712 of the main body. The atrial cap 714 can comprise a continuous annular rim 718 formed from a plurality of circumferentially extending angled struts 720. The atrial cap 714 can comprise a plurality of radially extending connecting struts 722. Each connecting strut 722 has a first end connected to an apex 724 of two struts 720 and a second end connected to an apex 726 of two angled struts 728 of the main body 708.

(100) As can be seen in FIG. 21, the second ends of the connecting struts 722 are connected to the apices 726 of struts 728 that form a row of circumferentially extending struts adjacent the uppermost row of struts 730 that form the atrial end 710 of the main body. In this manner, when the frame 702 is deployed from a delivery sheath, the atrial cap 714 curls or deflects downwardly below the atrial end 710 toward the ventricular end 712, which assists in pushing the prosthetic valve further upwardly into the left atrium to minimize obstruction of the left ventricular outflow tract (LVOT). In particular embodiments, the entire atrial cap 714 is spaced below the atrial end 710 of the main body 708. In alternative embodiments, the connecting struts 722 can be connected to the apices of struts 730 that form the atrial end 710 of the main body 708.

(101) The main body 708 can have an overall tapered shape defining an inlet diameter D1 at the atrial end 710 and a smaller outlet diameter D2 at the ventricular end 712. In the illustrated embodiment, the main body 708 comprises a first, substantially cylindrically-shaped inlet portion 732 defining the inlet diameter and a second, conically-shaped outlet portion 734 defining the outlet diameter, which tapers in a direction extending from the lower end of the inlet portion 732 toward the ventricular end 712 of the main body. The inlet end portion 732 can be relatively large and oversized relative to the native mitral valve annulus to establish a good seal between the outer surface of the prosthetic valve and the native leaflets 602 to prevent or minimize paravalvular leakage while the relatively smaller outlet end portion 734 prevents or minimizes obstruction of the LVOT. In certain embodiments, the inlet diameter D1 of the inlet end portion 732 is at least about 30 mm to about 50 mm, with about 40 mm being a specific example, while the outlet diameter D2 of the outlet end portion 732 is about 20 to about 40, with about 30 mm being a specific example.

(102) Each ventricular anchor 716 can have a fixed end portion 736 connected to the ventricular end 712 of the main body, an intermediate portion 738 having a bend, and a free end portion 740. As shown in the drawings, each fixed end portion 736 can be connected to an apex 742 formed by two angled struts at the ventricular end 712 of the main body. The free end portions 740 can have atraumatic head portions 744, which may be curved and/or rounded. The head portions 744 can each have a teardrop-shaped opening through which ventricular tissue and/or native valve annulus tissue can protrude, or can have another shape, for example, any of the shapes discussed above for the distal head portion 128 of the ventricular anchor.

(103) The ventricular anchors 716 are relatively wide and stiff in the lateral direction to minimize side-to-side movement of the anchors to permit crimping and deployment without the anchors becoming entangled with each other. To minimize axial stiffness (to facilitate crimping and deployment), the thickness of the intermediate portions 738 can be reduced relative to other portions of the anchors 716 and the main body 708. In certain embodiments, for example, the intermediate portions 738 can be thinner than the fixed end portions 736, the free end portions 740, and the main body 708.

(104) FIGS. 22 and 23 show one technique for forming a frame 702 with ventricular anchors 716 having a reduced thickness. FIG. 22 shows a metal tube 750 (e.g., a Nitinol tube) for forming the frame 702. The tube 750 is treated by, for example, machining, grinding, or electro-polishing, to produce a recessed

portion 752 having a reduced thickness relative to the remainder of the tube 750. FIG. 23 shows the pattern for laser cutting the frame 702 from the tube 750. As can be seen, the intermediate portions 738 are formed from the recessed portion 752 of the tube such that the finished frame (fully cut from the tube) is thinner along the intermediate portions 738 compared to the remainder of the frame.

(105) FIG. 24 shows a cross-section of a ventricular anchor 716 taken through the intermediate portion 738. In certain embodiments, the anchors 716 have width W of about 0.8 mm to about 2.0 mm, with about 1.4 mm being a specific example. The width W can be constant along the entire length of the anchor. In certain embodiments, the intermediate portions 738 of the anchors have a thickness T of about 0.4 mm and the remainder of the frame 702 (including the fixed end portions 736 and the free end portions 740 of the anchors) can have a thickness of about 0.5 mm.

(106) FIG. 25 is a side elevation view of another prosthetic valve frame 802 that can be implemented in a prosthetic valve. FIG. 26 shows the frame 802 covered by an outer skirt or sealing member 846. The frame 802 comprises an annular main body 808, an atrial cap 814 extending radially outward from the atrial end 810 of the main body, and a plurality of ventricular anchors 816 extending from the main body at a location proximate the ventricular end 812 of the main body. The atrial cap 814 can comprise a continuous annular rim 818 formed from a plurality of circumferentially extending angled struts 820. The atrial cap 814 can comprise a plurality of radially extending connecting struts 822. Each connecting strut 822 has a first end connected to an apex 824 of two struts 820 and a second end connected to an apex 826 of two angled struts 828 of the main body 808, spaced from the atrial end 810 of the main body. In alternative embodiments, the connecting struts 822 can be connected to the apices at the atrial end 810 of the main body.

(107) The main body 808 can have an overall tapered or conical shape defining an inlet diameter D1 at the atrial end 810 and a smaller outlet diameter D2 at the ventricular end 812. In certain embodiments, the inlet diameter D1 is at least about 30 mm to about 50 mm, with about 40 mm being a specific example, while the outlet diameter D2 is about 20 to about 40, with about 30 mm being a specific example.

(108) Each ventricular anchor 816 can have a fixed end portion 836 connected to the main body, an intermediate portion 838 having a bend, and a free end portion 840. As shown in the drawings, each fixed end portion 836 can be connected to an apex 842 formed by two angled struts 828 forming a row of struts spaced from the ventricular end 812 of the main body.

(109) Mounting the ventricular anchors 816 at a location closer toward the atrial end reduces the distance between atrial cap 814 and the ventricular anchors to enhance anchoring of the prosthetic valve. In addition, the ventricular anchor 816, being spaced from the ventricular end 812 of the main body, are mounted to a relatively stiff region of the frame to minimize distortion of the frame during crimping and deployment. In alternative embodiments, the ventricular anchors 816 can be connected to the apices at the ventricular end 812 of the main body.

(110) The free end portions 840 of the ventricular anchors can have atraumatic head portions 844, which may be curved and/or rounded. The head portions 844 can each have a teardrop-shaped opening through which ventricular tissue and/or native valve annulus tissue can protrude, or can have another shape, for example, any of the shapes discussed above for the distal head portion 128 of the ventricular anchor.

(111) As best shown in FIG. 27, the fixed end portion 836 of each ventricular anchor 816 can be tapered such that the fixed end portion is reduced in width W where it is connected to an apex 842 to enhance flexibility of the connection between the anchors and the main body. The intermediate portion 838 of each anchor can have a reduced thickness T relative to other portions of the anchors 816 and the main body 808 to minimize axial stiffness of the anchors.

GENERAL CONSIDERATIONS

(112) For purposes of this description, certain aspects, advantages, and novel features of the embodiments of this disclosure are described herein. The disclosed methods, devices, and systems should not be construed as limiting in any way. Instead, the present disclosure is directed toward all novel and nonobvious features and aspects of the various disclosed embodiments, alone and in various combinations and sub-combinations with one another. The methods, devices, and systems are not limited to any specific aspect or feature or combination thereof, nor do the disclosed embodiments

require that any one or more specific advantages be present or problems be solved.

(113) Features, integers, characteristics, compounds, chemical moieties or groups described in conjunction with a particular aspect, embodiment or example of the invention are to be understood to be applicable to any other aspect, embodiment or example described herein unless incompatible therewith. All of the features disclosed in this specification (including any accompanying claims, abstract and drawings), and/or all of the steps of any method or process so disclosed, may be combined in any combination, except combinations where at least some of such features and/or steps are mutually exclusive. The invention is not restricted to the details of any foregoing embodiments. The invention extends to any novel one, or any novel combination, of the features disclosed in this specification (including any accompanying claims, abstract and drawings), or to any novel one, or any novel combination, of the steps of any method or process so disclosed.

(114) Although the operations of some of the disclosed methods are described in a particular, sequential order for convenient presentation, it should be understood that this manner of description encompasses rearrangement, unless a particular ordering is required by specific language. For example, operations described sequentially may in some cases be rearranged or performed concurrently. Moreover, for the sake of simplicity, the attached figures may not show the various ways in which the disclosed methods can be used in conjunction with other methods. As used herein, the terms “a”, “an”, and “at least one” encompass one or more of the specified element. That is, if two of a particular element are present, one of these elements is also present and thus “an” element is present. The terms “a plurality of” and “plural” mean two or more of the specified element.

(115) As used herein, the term “and/or” used between the last two of a list of elements means any one or more of the listed elements. For example, the phrase “A, B, and/or C” means “A”, “B”, “C”, “A and B”, “A and C”, “B and C”, or “A, B, and C.”

(116) As used herein, the term “coupled” generally means physically coupled or linked and does not exclude the presence of intermediate elements between the coupled items absent specific contrary language.

(117) In view of the many possible embodiments to which the principles of the disclosed invention may be applied, it should be recognized that the illustrated embodiments are only preferred examples of the invention and should not be taken as limiting the scope of the invention. Rather, the scope of the invention is at least as broad as the following exemplary claims. We therefore claim at least all that comes within the scope of the following claims.

Claims

1. A method of implanting a prosthetic heart valve at a native tricuspid valve region having a native valve annulus and a plurality of native leaflets, comprising: delivering a prosthetic heart valve to the native tricuspid valve region via the inferior vena cava or the superior vena cava, the prosthetic heart valve contained within an interior of a sheath of a delivery apparatus, the prosthetic heart valve comprising: a radially compressible and expandable frame assembly comprising an inflow end, an outflow end, and a double-body structure having an annular inner frame and an annular outer frame, the inner frame having a main body comprising a plurality of circumferentially extending rows of angled struts and the annular outer frame having a main body and an atrial flange portion configured to contact an atrial face of the native valve annulus; a plurality of prosthetic leaflets mounted within the inner frame for regulating the flow of blood in one direction through the inner frame; and a plurality of ventricular anchors, each comprising a free end portion and a fixed end portion connected to and extending from the frame assembly at a location spaced from the outflow end of the frame assembly; and deploying the prosthetic heart valve from the sheath such that the main bodies of the inner and outer frames expand within the native annulus, the atrial flange portion is deployed in an atrium adjacent the native annulus, and each of the plurality of ventricular anchors extend behind one of the native leaflets.
2. The method of claim 1, wherein the plurality of ventricular anchors are asymmetrically arranged around the frame.
3. The method of claim 1, wherein the plurality of ventricular anchors are unevenly spaced around a

circumference of the frame.

4. The method of claim 1, wherein the plurality of ventricular anchors are separately formed and connected to the frame assembly.
5. The method of claim 1, wherein each of the plurality of ventricular anchors has a serpentine shape.
6. The method of claim 1, wherein the free end portion of each of the plurality of ventricular anchors comprises a curved head portion.
7. The method of claim 1, wherein the fixed end portion of each of the plurality of ventricular anchors extends in a downward direction.
8. The method of claim 1, wherein the free end portion of each of the plurality of ventricular anchors extends in an upward direction.
9. The method of claim 1, wherein each of the plurality of ventricular anchors is connected to the main body independently of each other without frame segments interconnecting adjacent ventricular anchors.
10. A method of implanting a prosthetic heart valve at a native tricuspid valve region having a native valve annulus and a plurality of native leaflets, comprising: delivering a prosthetic heart valve to the native tricuspid valve region via the inferior vena cava or the superior vena cava, the prosthetic heart valve contained within an interior of a sheath of a delivery apparatus, the prosthetic heart valve comprising: a radially compressible and expandable frame assembly comprising an inflow end and an outflow end; a plurality of prosthetic leaflets mounted within the frame assembly for regulating the flow of blood in one direction through the frame assembly; an atrial flange portion extending from the frame assembly, wherein the atrial flange portion comprises a plurality of angularly spaced atrial anchors and is configured to contact an atrial face of the native valve annulus; and a plurality of ventricular anchors, each comprising a free end portion and a fixed end portion connected to and extending from the frame assembly at a location spaced from the outflow end of the frame assembly; and deploying the prosthetic heart valve from the sheath such that the frame assembly expands within the native annulus, the atrial flange portion is deployed in an atrium adjacent the native annulus, and each of the plurality of ventricular anchors extend behind one of the native leaflets.
11. The method of claim 10, wherein an outer rim of the atrial flange portion has an oval shape.
12. The method of claim 10, wherein a first one of the plurality of atrial anchors has a first length and a second one of the plurality of atrial anchors has a second, different length.
13. The method of claim 10, wherein each of the plurality of atrial anchors extends from the frame assembly at a location spaced from the inflow end of the frame assembly.
14. The method of claim 10, wherein each of the plurality of atrial anchors is independently coupled to the frame assembly without frame segments interconnecting adjacent atrial anchors.
15. The method of claim 10, wherein each of the plurality of atrial anchors comprises a teardrop-shaped opening.
16. The method of claim 10, further comprising a fabric layer extending over the atrial flange portion.
17. A method of implanting a prosthetic heart valve at a native tricuspid valve region having a native valve annulus and a plurality of native leaflets, comprising: delivering a prosthetic heart valve to the native tricuspid valve region via the superior vena cava, the prosthetic heart valve contained within an interior of a sheath of a delivery apparatus, the prosthetic heart valve comprising: a radially compressible and expandable frame assembly comprising an inflow end, an outflow end, and a double-body structure having an annular inner frame coupled to an annular outer frame, the inner frame comprising a main body and the outer frame comprising a main body and an atrial flange portion, wherein the inner and outer frames are separately formed and coupled to each other with suture or wire; a plurality of prosthetic leaflets mounted within the main body of the inner frame for regulating the flow of blood in one direction through the main body; and a plurality of ventricular anchors, each comprising a free end portion and a fixed end portion connected to and extending from the frame assembly at a location spaced from the outflow end of the frame assembly; and deploying the prosthetic heart valve from the sheath such that the main bodies of the inner and outer frames expand within the native annulus, the atrial flange portion is deployed in an atrium adjacent the native annulus, and each of the plurality of ventricular anchors extend behind one of the native leaflets.
18. The method of claim 17, wherein each of the ventricular anchors has a serpentine shape.

19. The method of claim 17, wherein the frame assembly is self-expandable when deployed from the sheath.

20. The method of claim 17, wherein the inner frame further comprises a plurality of axially extending tabs, and wherein each tab extends axially from an apex formed by the intersection of adjacent angled struts at an end of the inner frame.
