



US012403620B2

(12) **United States Patent**
Bucks

(10) **Patent No.:** **US 12,403,620 B2**

(45) **Date of Patent:** ***Sep. 2, 2025**

(54) **CUTTING HEAD FOR A CENTRIFUGAL CUTTING APPARATUS AND CENTRIFUGAL CUTTING APPARATUS EQUIPPED WITH SAME**

(58) **Field of Classification Search**
CPC B26D 7/2614; B26D 1/03; B26D 7/0691;
B26D 7/2628; B26D 2210/02
See application file for complete search history.

(71) Applicant: **FAM, Kontich (BE)**

(56) **References Cited**

(72) Inventor: **Brent L. Bucks**, Lakewood Ranch, FL (US)

U.S. PATENT DOCUMENTS

(73) Assignee: **FAM, Kontich (BE)**

1,474,797 A 11/1923 Spicer
2,195,879 A 4/1940 Urschel et al.
(Continued)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.
This patent is subject to a terminal disclaimer.

FOREIGN PATENT DOCUMENTS

BE 1020687 A3 3/2014
BE 1020824 A5 5/2014
(Continued)

(21) Appl. No.: **18/314,186**

OTHER PUBLICATIONS

(22) Filed: **May 9, 2023**

Exhibit A.

(Continued)

(65) **Prior Publication Data**

US 2023/0278248 A1 Sep. 7, 2023

Primary Examiner — Omar Flores Sanchez

(74) *Attorney, Agent, or Firm* — Ipsilon USA—NLO

Related U.S. Application Data

(62) Division of application No. 17/591,018, filed on Feb. 2, 2022, now Pat. No. 11,673,286, and a division of (Continued)

Foreign Application Priority Data

Oct. 2, 2017 (EP) 17194379

(51) **Int. Cl.**

B26D 7/26 (2006.01)

B26D 1/03 (2006.01)

B26D 7/06 (2006.01)


(52) **U.S. Cl.**

CPC **B26D 7/2614** (2013.01); **B26D 1/03** (2013.01); **B26D 7/0691** (2013.01); **B26D 7/2628** (2013.01); **B26D 2210/02** (2013.01)

(57) **ABSTRACT**

A cutting head for a centrifugal cutting apparatus includes a rim structure; and a plurality of cutting stations mounted onto the rim structure, each of said cutting stations comprising a cutting element for cutting food products at a leading end of the cutting station and an inner wall extending from the leading end to a trailing end and forming a product sliding surface, along which the food product slides between successive cuts. The cutting stations are assembled adjacent one another onto the rim structure in such a way that a gap is present between each pair of adjacent cutting stations through which a product slice exits the cutting head upon being cut. The cutting head also includes a gap setting mechanism for setting the radial size of the gap by adjusting the radial offset of the trailing end of the respective cutting station with respect to the rim structure.

16 Claims, 6 Drawing Sheets



Related U.S. Application Data

application No. 17/175,725, filed on Feb. 15, 2021, now Pat. No. 11,305,449, and a division of application No. 16/147,956, filed on Oct. 1, 2018, now Pat. No. 10,919,173.

(56)

References Cited**U.S. PATENT DOCUMENTS**

2,436,410	A	2/1948	Urschel et al.
2,832,387	A	4/1958	Woodward, Jr.
2,875,800	A	3/1959	Urschel
2,934,117	A	4/1960	Urschel
3,033,204	A	5/1962	Wood
3,196,916	A	7/1965	Urschel
3,255,646	A	6/1966	Urschel
3,395,742	A	8/1968	Sanders
3,472,297	A	10/1969	Urschel
3,823,880	A	7/1974	Urschel
3,888,426	A	6/1975	Urschel et al.
3,989,196	A	11/1976	Urschel
4,042,183	A	8/1977	Cumpston
4,523,503	A	6/1985	Julian et al.
4,604,925	A	8/1986	Wisdom
4,610,397	A	9/1986	Fischer et al.
4,660,778	A	4/1987	Fischer et al.
4,813,317	A	3/1989	Urschel
4,937,084	A	6/1990	Julian
5,274,899	A	1/1994	Sentagnes et al.
5,555,787	A	9/1996	Barber et al.
5,694,824	A	12/1997	Jacko et al.
5,819,628	A	10/1998	Cogan et al.
5,964,138	A	10/1999	Metzner et al.
6,116,130	A	9/2000	Cogan
6,155,151	A	12/2000	Reichert
6,314,849	B1	11/2001	Arrasmith
6,536,691	B2	3/2003	Prewitt et al.
6,883,411	B2	4/2005	Arrasmith et al.
6,920,813	B2	7/2005	Bucks
7,270,040	B2	9/2007	King et al.
7,525,672	B1	4/2009	Chen et al.
8,033,204	B2	10/2011	Bucks
9,352,478	B2	5/2016	Koide
9,517,572	B2	12/2016	Michel et al.
9,862,113	B2	1/2018	Jacko
9,902,080	B2	2/2018	Michel et al.
10,279,495	B2	5/2019	Jacko
10,632,640	B2	4/2020	Bucks
10,780,602	B2	9/2020	Gereg et al.
10,786,922	B2	9/2020	Gereg
11,186,005	B2	11/2021	Bucks
2004/0216572	A1	11/2004	King et al.
2004/0237747	A1*	12/2004	King B26D 7/2614 83/932
2006/0172816	A1	8/2006	Johnson
2007/0189766	A1	8/2007	Kuwahara et al.
2008/0022822	A1	1/2008	Jacko et al.
2008/0022828	A1	1/2008	Bucks
2009/0202694	A1	8/2009	Julian et al.
2010/0015312	A1	1/2010	Bellmunt-Molins
2010/0130981	A1	5/2010	Richards
2010/0206185	A1	8/2010	Bucks
2013/0276604	A1	10/2013	King et al.
2014/0007751	A1	1/2014	Michel et al.
2014/0060278	A1	3/2014	Koide

2014/0230620	A1	8/2014	Bucks
2014/0230621	A1	8/2014	Bucks
2014/0257413	A1	9/2014	Appenzeller et al.
2014/0290451	A1	10/2014	Jacko
2016/0075047	A1*	3/2016	Bucks B26D 7/2614 83/403

2016/0361831	A1	12/2016	Fant
2017/0050329	A1	2/2017	Michel
2017/0106550	A1	4/2017	Jacko
2018/0229390	A1	8/2018	Gereg
2019/0143554	A1	5/2019	Gereg
2019/0210239	A1	7/2019	Baxter
2019/0232514	A1	8/2019	Bucks
2019/0329437	A1	10/2019	Gereg
2019/0375126	A1	12/2019	Baxter

FOREIGN PATENT DOCUMENTS

BE	1022372	B1	3/2016
BE	1022746	A1	8/2016
EP	0301996	A2	2/1989
EP	0289220	A3	1/1990
EP	0301996	A3	3/1991
EP	0756534	B1	7/2003
EP	2124772	A1	12/2009
EP	2249668	A2	11/2010
EP	2012982	B1	5/2011
EP	2326471	B1	5/2012
EP	1617977	B1	5/2013
EP	1626844	B1	5/2013
EP	1638741	B1	2/2015
EP	2964122	A2	1/2016
EP	2981181	B1	12/2016
EP	3461605	A1	4/2019
EP	3414063	B1	1/2021
EP	3802028	A1	4/2021
EP	3243613	B1	10/2021
EP	3981563	A1	4/2022
EP	3706969	B1	7/2022
EP	3307499	B1	10/2022
EP	3580027	B1	7/2024
EP	2800652	B2	12/2024
WO	02068122	A1	9/2002
WO	2004106015	A2	12/2004
WO	2013101621	A1	7/2013
WO	2014165572	A1	10/2014
WO	2015075179	A1	5/2015
WO	2015075180	A1	5/2015
WO	2016201400	A1	12/2016

OTHER PUBLICATIONS

Exhibit B—Diversacut Sprint™ Dicer, Instruction Manual, Urschel Laboratories.

Exhibit C—Model GRL, Instruction Manual, Urschel Laboratories.

Exhibit D—Quanticut® Dicer, Model Q, Instruction Manual, Urschel Laboratories.

E—Sprint 2™ Dicer, Model MSPR2, Parts Manual, Urschel.

Brunner-Anliker product information on the IR 250 Industrial Food Process, “Industrial pre-rotating grinder for cheese, nuts, chocolate or rework for a production volume of up to 2 tons per hour”. Available at <https://www.brunner-anliker.com/en/food-industry/nut-and-cheese-graters/ir-250/>.

* cited by examiner

Fig. 1




Fig. 2




Fig. 3 Prior art.








Fig. 4

Fig. 5



1

CUTTING HEAD FOR A CENTRIFUGAL CUTTING APPARATUS AND CENTRIFUGAL CUTTING APPARATUS EQUIPPED WITH SAME

FIELD OF THE INVENTION

The present invention relates to a cutting head for a centrifugal cutting apparatus. More particularly, this invention relates to cutting heads suitable for cutting food product slices. The present invention further relates to a centrifugal cutting apparatus equipped with such a cutting head, such as for example a food cutting apparatus.

BACKGROUND ART

A centrifugal cutting apparatus comprises an impeller which is arranged to rotate concentrically within a cutting head so as to impart a centrifugal force to the food products to be cut. The cutting head is commonly an assembly of a plurality of cutting stations, also referred to as shoes, each provided with a cutting element arranged for cutting or reducing the food product concentrically rotating in the cutting head.

A centrifugal cutting apparatus is for example known from WO2013101621. As used therein, the term “rake-off angle” is measured as the angle that a slice shall deviate relative to a tangent line that begins at an intersection defined by the knife edge and a path of a product sliding surface defined by the interior surface of a leading shoe (cutting station), i.e. the shoe immediately upstream of a particular knife. The line is then tangent to the radial product sliding surface of the leading shoe.

In prior art centrifugal cutting apparatuses, including the one described in WO2013101621, the rake-off angle is 20.5° or more. It has been found that a rake-off angle of such magnitude may lead to cracking of the food slices, especially in potato slices.

SUMMARY OF THE INVENTION

It is an aim of the present invention to provide a cutting head for a centrifugal cutting apparatus with which the risk of cracking of food slices can be reduced.

This aim is achieved with the cutting head showing the technical characteristics of the first claim.

The invention provides, in a first aspect, a cutting head which comprises a plurality of cutting stations. Each cutting station is provided with a cutting element for cutting food products at a leading end of the cutting station and comprises an inner wall extending from the leading end to a trailing end and forming a product sliding surface, along which the food product slides between successive cuts. The cutting stations are assembled adjacent one another in such a way that a gap is present between each pair of adjacent cutting stations. A “rake-off angle” OR is defined as the angle that a product slice deviates upon being cut by one of the cutting elements and exiting the cutting head through the respective gap, said angle being measured relative to a tangent line to the product sliding surface at the trailing end of the respective preceding cutting station. According to the invention, for each cutting station a rear part of the product sliding surface at the trailing end is adapted such that the rake-off angle θ_R is below 17°.

It has been found that by adapting the rear part of the product sliding surface at the trailing end of each cutting station, the rake-off angle θ_R and consequently the risk of cracking of food slices can be reduced.

2

In embodiments according to the invention, the rear part of the product sliding surface at the trailing end is adapted such that the rake-off angle θ_R is below 16°.

In embodiments according to the invention, the rear part of the product sliding surface at the trailing end is adapted such that the rake-off angle θ_R is between 12° and 15°. It has been found that in this range the risk of cracking of the food slices can be minimized while still leaving enough physical space to accommodate the cutting element.

In embodiments according to the invention, each cutting station has a concave inner wall with a wall curvature $R1^{-1}$ (with R1 being the radius of curvature and the curvature being the inverse of said radius R1) corresponding to an inner diameter of the cutting head, the rear part of the product sliding surface having a reduced curvature with respect to said wall curvature. This means that the rear part of the product sliding surface (i.e. the adapted part of the inner surface of the cutting station) deviates outwards from the mathematical (or theoretical) cylinder defined by the inner diameter of the cutting head. The rear part of the product sliding surface may have a reduced curvature $R2^{-1}$ with respect to the wall curvature (or the mathematical cylinder) or even be a straight surface which extends tangent to the concave part of the inner wall. The length of the product sliding surface may for example be in the range of 3 to 30 mm, preferably in the range of 5 to 20 mm.

In embodiments according to the invention, the cutting element is a knife blade and the rear part of the product sliding surface is a straight surface which extends substantially parallel to a longitudinal direction of the knife blade. In other words, in this embodiment, the rear part of the product sliding surface and the outer surface of the knife blade or cutting element form substantially parallel surfaces between which the cut slice can exit.

In embodiments according to the invention, the size of the gap is set by means of gap setting elements. The (radial) size of the gap is defined by the relative position, or radial offset, of the rear part of the product sliding surface at the trailing end of one cutting station (the cutting station preceding the gap) and a front edge of the cutting element at the leading end of the other cutting station (the cutting station subsequent to the gap). The size of the gap determines the slice thickness. The gap setting elements may for example be formed by spacers mounted in between the leading and/or trailing ends of the cutting stations and a surrounding rim structure, or by spacers mounted in between overlapping parts of the cutting stations, or otherwise.

In embodiments according to the invention, the cutting head may be configured for cutting flat slices. This means that each cutting station is provided with a flat or substantially straight cutting element.

In embodiments according to the invention, the cutting head may be configured for cutting corrugated slices. This means that each cutting station is provided with a corrugated cutting element. The inner walls of the cutting stations may be formed with a corrugated shape (corrugated in height direction) corresponding to that of the corrugated slices so as to support the product in between successive cuts.

The invention provides, in a second aspect, a cutting head which comprises a substantially cylindrical drum with at least one cutting station arranged for cutting food product that is circulated in the drum by means of a rotating impeller. Each cutting station is provided with a cutting element for cutting the food product at a leading end of the cutting station. Each cutting station is rotationally preceded by a preceding section of the drum which comprises an inner wall extending up to a trailing end of the preceding section and

forming a product sliding surface, along which the food product slides towards the respective cutting station. Each cutting station is assembled to the drum in such a way that a gap is present between the trailing end of the preceding section of the drum and the leading end of the cutting station. A “rake-off angle” θ_R is defined as the angle that a product slice deviates upon being cut by one of the cutting elements and exiting the cutting head through the respective gap, said angle being measured relative to a tangent line to the product sliding surface at the trailing end of the respective preceding section of the drum. According to the invention, a rear part of each product sliding surface is adapted such that the rake-off angle θ_R is below 17° .

It has been found that by adapting, for each cutting station, the rear part of the rotationally preceding product sliding surface, which is located at the trailing end of the respective preceding section of the drum, the rake-off angle θ_R and consequently the risk of cracking of food slices can be reduced.

In embodiments according to the invention, the rear part of each product sliding surface is adapted such that the rake-off angle θ_R is below 16° .

In embodiments according to the invention, the rear part of each product sliding surface is adapted such that the rake-off angle θ_R is between 12° and 15° . It has been found that in this range the risk of cracking of the food slices can be minimized while still leaving enough physical space to accommodate the cutting element.

In embodiments according to the invention, the drum generally has a concave inner wall with a wall curvature $R1^{-1}$ (with $R1$ being the radius of curvature and the curvature being the inverse of said radius $R1$) corresponding to an inner diameter of the cutting head, except for the rear part of each product sliding surface where the curvature is reduced with respect to said wall curvature. This means that the rear part of each product sliding surface (i.e. the adapted part of the inner surface of the preceding section of the drum) deviates outwards from the mathematical (or theoretical) cylinder defined by the inner diameter of the cutting head. The rear part of the product sliding surface may have a reduced curvature $R2^{-1}$ with respect to the wall curvature (or the mathematical cylinder) or even be a straight surface which extends tangent to the concave inner wall. The length of the product sliding surface may for example be in the range of 3 to 30 mm, preferably in the range of 5 to 20 mm.

In embodiments according to the invention, the size of the gap is set by means of a gap setting mechanism. The (radial) size of the gap is defined by the relative position, or radial offset, of the rear part of the respective product sliding surface and a front edge of the cutting element at the leading end of the respective cutting station. The size of the gap determines the slice thickness.

In embodiments according to the invention, the cutting head may be configured for cutting flat slices. This means that each cutting station is provided with a flat or substantially straight cutting element.

In embodiments according to the invention, the cutting head may be configured for cutting corrugated slices. This means that each cutting station is provided with a corrugated cutting element. The inner wall of the drum may be formed with a corrugated shape (corrugated in height direction) corresponding to that of the corrugated slices so as to support the product in between successive cuts.

The invention further provides a centrifugal cutting apparatus comprising a cutting head as described herein and an impeller which is arranged to rotate concentrically inside the cutting head.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention will be discussed in more detail below, with reference to the attached drawings.

FIG. 1 shows a side view of a cutting head according to the invention.

FIG. 2 shows a cross-section of the cutting head along line A-A of FIG. 1.

FIG. 3 shows a detail of a cutting head of the prior art.

FIG. 4 shows a detail of a cutting head according to the invention.

FIG. 5 shows a detail of another cutting head according to the invention.

FIG. 6 shows a cross-section of yet another cutting apparatus according to the invention.

FIG. 7 shows a detail of FIG. 6

DESCRIPTION OF EMBODIMENTS

The present invention will be described with respect to particular embodiments and with reference to certain drawings but the invention is not limited thereto but only by the claims. The drawings described are only schematic and are non-limiting. In the drawings, the size of some of the elements may be exaggerated and not drawn on scale for illustrative purposes. The dimensions and the relative dimensions do not necessarily correspond to actual reductions to practice of the invention.

Furthermore, the terms first, second, third and the like in the description and in the claims, are used for distinguishing between similar elements and not necessarily for describing a sequential or chronological order. The terms are interchangeable under appropriate circumstances and the embodiments of the invention can operate in other sequences than described or illustrated herein.

Moreover, the terms top, bottom, over, under and the like in the description and the claims are used for descriptive purposes and not necessarily for describing relative positions. The terms so used are interchangeable under appropriate circumstances and the embodiments of the invention described herein can operate in other orientations than described or illustrated herein.

Furthermore, the various embodiments, although referred to as “preferred” are to be construed as exemplary manners in which the invention may be implemented rather than as limiting the scope of the invention.

The term “comprising”, used in the claims, should not be interpreted as being restricted to the elements or steps listed thereafter; it does not exclude other elements or steps. It needs to be interpreted as specifying the presence of the stated features, integers, steps or components as referred to, but does not preclude the presence or addition of one or more other features, integers, steps or components, or groups thereof. Thus, the scope of the expression “a device comprising A and B” should not be limited to devices consisting only of components A and B, rather with respect to the present invention, the only enumerated components of the device are A and B, and further the claim should be interpreted as including equivalents of those components.

FIG. 1 shows a cutting head 100 for a centrifugal cutting apparatus, according to the an embodiment of the invention, comprising a plurality of cutting stations 101, 201, 301, each provided with a cutting element 105, 205, 305 for cutting food products at a leading end 104, 204, 304 of the cutting station, and having an inner wall 110, 210, 310 which forms a product sliding surface and extends from the leading end up to the trailing end 107, 207, 307 of the cutting station.

5

The cutting stations **101**, **201**, **301** are assembled adjacent one another in such a way that a gap **109** (see FIGS. 3-5) is present between each pair of adjacent cutting stations.

The size of the gap **109** sets the slice thickness. The size of the gap is commonly known to refer to the offset in radial direction between the rear part **108'**, **108"** of the product sliding surface **110**, at the trailing end **107** of the one cutting station **101**, and the front edge of the cutting element **205** at the leading end **204** of the other cutting station **201**. The size of the gap can be adjusted by means of gap setting elements, embodiments of which will be described below.

The so-called "rake-off angle" θ_R is defined as the angle that a product slice deviates upon being cut by the cutting element **205** and being pushed through the gap **109** (by an impeller paddle, not shown). This angle is measured relative to a tangent line to the rear part of the product sliding surface of the preceding cutting station. According to the invention, for each cutting station **101**, **201**, **301** the rear part **108'**, **108"** (see FIGS. 4 and 5) of the product sliding surface is adapted to reduce the rake-off angle θ_R below 17° , preferably below 16° , more preferably between 12° and 15° .

As shown in FIGS. 3-5, the cutting elements **105**, **205** of each cutting station **101**, **201** are clamped onto the leading end **104**, **204** of the cutting station by means of a clamp **106**, **206**. The cutting station, cutting element and clamp together form a knife assembly, embodiments of which have been described at length in WO2015075179 and WO2015075180, the descriptions of which are hereby incorporated by reference in their entirety.

In alternative embodiments, the cutting elements **105**, **205** may also be formed by single-piece knives or cutting elements which are fixed to the cutting station without a clamp. In such embodiments, the rake-off angle θ_R may be further reduced and even be 0° if the rear part **108'**, **108"** extends parallel to the outer surface of the knife (the top surface of the knife on the outside of the cutting head).

Each cutting station **101**, **201**, **301** has a concave inner wall **110**, **210**, **310** with a wall curvature $R1^{-1}$ corresponding to an inner diameter of the cutting head **100**. The adapted rear part **108'**, **108"** of the product sliding surface may for example be embodied as a rear part **108'** with a reduced curvature $R2^{-1}$ with respect to said wall curvature $R1^{-1}$ (as shown in FIG. 4), or as a substantially straight surface **108"** which is then preferably tangent to the concave part of the inner wall **110** (as shown in FIG. 5), or otherwise. The rear part **108'**, **108"** may for example have a length of 3 to 30 mm, preferably 5 to 20 mm.

In the embodiment shown in FIGS. 1, 2 and 4, 5, the cutting stations are separately or individually mounted onto a rim structure **102**, **103** by means of bolts **112** and the gap setting elements are spacers **111** mounted in between the leading and/or trailing ends of the cutting stations and the rim structure. This principle has been described at length in EP2918384, the description of which is hereby incorporated by reference in its entirety.

In an alternative embodiment (not shown), the cutting stations are assembled to each other at overlapping parts at the leading and trailing ends, said gap setting elements being spacers which are mounted between the overlapping parts. This principle has been described at length in WO2013045684, the description of which is hereby incorporated by reference in its entirety.

The cutting head **100** may be configured for cutting flat slices and may therefore be equipped with flat or straight knife assemblies as described at length in WO2015075179, the description of which is hereby incorporated by reference in its entirety.

6

The cutting head **100** shown in the figures is configured for cutting corrugated slices and is therefore equipped with corrugated knife assemblies as described at length in WO2015075180, the description of which is hereby incorporated by reference in its entirety. Each cutting station **101**, **201**, **301** may have an inner wall **110**, **210**, **310** with a corrugated shape corresponding to that of the corrugated slices, so as to better ensure that the cuts are aligned.

More in detail, the invention is described with reference to FIGS. 3-5.

FIG. 3 shows a detail of a prior art cutting head of the applicant. The inner wall **110** of the cutting stations **101**, **201**, **301** is entirely corresponding to the inner diameter of the cutting head and has a curvature $R1^{-1}$. The rake-off angle $\theta R1$ is measured between the tangent line **T1** to the product sliding surface **110** at the trailing end **107** and the line **TC** which is drawn on the slanted surface of the clamp **206** and which is the direction along which a product slice exits the cutting head. In FIG. 3, the rake-off angle $\theta R1$ is 20.5° .

FIG. 4 shows a detail of a first embodiment according to the invention. The inner wall **110** has a main concave part **108** which corresponds to the inner diameter of the cutting head and has the curvature $R1^{-1}$, and a rear part **108'** which has a reduced curvature $R2^{-1}$ and which, as a result, deviates radially outward. As a result of this outward deviation, the rake-off angle $\theta R2$ which is here measured between the tangent line **T2** to the rear part **108'** and the line **TC**, is reduced with respect to FIG. 3. In FIG. 4, the rake-off angle $\theta R2$ is about 15° .

FIG. 5 shows a detail of a second embodiment according to the invention. The inner wall **110**, **210** has a main concave part **108**, **208** which corresponds to the inner diameter of the cutting head and has the curvature $R1^{-1}$, and a rear part **108"** which is straight (the curvature is 0) and tangent to the end of the main concave part **108**, and which, as a result, deviates radially outward. As a result of this outward deviation, the rake-off angle $\theta R3$ which is here measured between the tangent line **T3** to the rear part **108"** (**T3** is also the direction of the straight part **108"**) and the line **TC**, is further reduced with respect to FIG. 4. In FIG. 5, the rake-off angle $\theta R3$ is 13.5° . For example, the rear part **108"** may extend substantially parallel to the longitudinal direction of the knife blade **205**.

The adapted rear parts **108'**, **108"** of the embodiments of FIGS. 4 and 5 can for example be obtained by milling off a part of the inner wall of the cutting station near the trailing end **107**. Other manufacturing methods are also possible.

The cutting apparatus **400** shown in FIG. 6 is of the type comprising a cylindrical drum **401** with a single cutting element **405**. A section **402** of the drum leading up to the cutting element **405** is movably mounted, in particular pivotally mounted, such that the position of the product sliding surface **410** with respect to the cutting element **405** and hence the slice thickness can be adjusted. An impeller (not shown) circulates the product to be cut inside the drum, so that the product is pushed against the inner wall of the drum by centrifugal force. Applicant manufactures and sells cutting apparatuses of this type under the brand "ILC".

In FIG. 6, such an apparatus **400** is shown but adapted according to the invention. The product sliding surface of the movable section **402** has a main concave part **408** and a rear part **408'**, which is modified in the same way as described for the rear part of the cutting stations of the other embodiments described herein so as to reduce the "rake-off angle". In particular, the rear part **408'** deviates outward and has a reduced curvature with respect to that of the inner wall of the drum **401** and the main part **408** of the movable

section **402**. In preferred embodiments, the rear part **408'** may be straight. The cutting element **405** may be formed by a single-piece knife which is fixed to the drum without a clamp. In this embodiment, the rake-off angle θ_R may be 0° if the rear part **408'**, extends parallel to the outer surface of the knife (the top surface of the knife on the outside of the drum). In alternative embodiments, a knife assembly such as has been described herein for the embodiments of FIGS. **1-5** may also be used in this type of apparatus **400**.

While the invention has been described with reference to exemplary embodiments, it will be understood by those skilled in the art that various changes may be made and equivalents may be substituted for elements thereof without departing from the scope of the invention. In addition, many modifications may be made to adapt a particular situation or material to the teachings of the invention without departing from the essential scope thereof. Therefore, it is intended that the invention not be limited to the particular embodiments disclosed, but that the invention will include all embodiments falling within the scope of the appended claims.

REFERENCE LIST

100 cutting head
101, 201, 301 cutting station
102, 103 rim structure
104, 204, 304 leading end of cutting station
105, 205, 305 cutting element
106, 206 clamp
107, 207, 307 trailing end of cutting station
108, 208 main concave part
108', 108" rear part
109 gap
110, 210, 310 inner wall/product sliding surface
111 spacer
112 bolt
R1⁻¹ inner wall curvature
T1, T2, T3, TC tangent line
R2⁻¹ reduced curvature
OR1, OR2, OR3 rake-off angle
400 cutting apparatus
401 drum
402 movable section
405 cutting element
408 main concave part
408' rear part
410 inner wall/product sliding surface
 The invention claimed is:
 1. A cutting head for a centrifugal cutting apparatus, said cutting head comprising
 a rim structure;
 a plurality of cutting stations which are mounted onto the rim structure, each of which is provided with a cutting element for cutting food products at a leading end of the cutting station and comprises an inner wall extending from the leading end to a trailing end and forming a product sliding surface, along which the food product slides between successive cuts, said cutting stations being assembled adjacent one another in such a way

that a gap is present between each pair of adjacent cutting stations through which a product slice exits the cutting head upon being cut by one of the cutting elements;

a gap setting mechanism provided between the trailing ends of the cutting stations and the rim structure for setting the radial size of the gap by adjusting the radial offset of the trailing end of the respective cutting station with respect to the rim structure;

wherein for each cutting station a rear part of the product sliding surface at the trailing end is adjusted.

2. The cutting head according to claim 1, wherein the gap setting mechanism adjusts the rear part of the respective cutting station without adjusting the position of the leading end of the respective cutting station.

3. The cutting head according to claim 1, wherein the curvature of the rear part of the product sliding surface is adjusted.

4. The cutting head according to claim 3, wherein the curvature is adjusted to reduce the rake-off angle.

5. The cutting head according to claim 4, wherein the rake-off angle is below 17° .

6. The cutting head according to claim 4, wherein the rake-off angle is below 16° .

7. The cutting head according to claim 4, wherein the rake-off angle is between 12° and 15° .

8. The cutting head according to claim 1, wherein for each cutting station the inner wall is generally concave with a wall curvature, wherein the adjusted rear part of the product sliding surface has a reduced curvature with respect to said wall curvature.

9. The cutting head according to claim 1, wherein the rear part of the product sliding surface is a straight surface extending tangent to a concave part of the inner wall.

10. The cutting head according to claim 1, wherein the rear part of the product sliding surface has a length of 3 to 30 mm.

11. The cutting head according to claim 1, wherein the cutting stations are separately mounted onto the rim structure and the gap setting mechanism comprises spacers between the trailing ends of the cutting stations and the rim structure.

12. The cutting head according to claim 1, wherein the cutting stations are mounted onto the rim structure by means of bolts.

13. The cutting head according to according to claim 1, wherein the cutting head comprises knives for cutting flat slices.

14. The cutting head according to according to claim 1, wherein the cutting head comprises knives for cutting corrugated slices.

15. The cutting head according to claim 14, wherein at least part of the product sliding surface of each cutting station has a corrugated shape corresponding to that of the corrugated slices.

16. A centrifugal cutting apparatus comprising a cutting head according to claim 1 and an impeller which is arranged to rotate concentrically within the cutting head.

* * * * *