

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12405466

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Shams; Nima L. et al.

Optical systems for head-worn computers

Abstract

Aspects of the present disclosure relate to optical systems with ergonomic presentation of content for use in head-worn computing systems. A method for controlling a head-worn computer when viewing virtual images, including image content, that encourages an ergonomic head position to reduce neck pain, includes determining an angle of the head-worn computer relative to horizontal, determining an angle of a line of sight to the center of the virtual image as presented to a user's eye, determining a deviation between the determined angle of the line of sight and a predetermined ergonomic angle, and shifting the image content of the virtual image vertically as displayed to the user's eye so that a portion of the image content is not viewable, wherein the amount of shifting is in reverse correspondence to the magnitude of the determined deviation.

Inventors: Shams; Nima L. (San Jose, CA), Border; John N. (Eaton, NH), Haddick; John D. (Mill Valley, CA)

Applicant: Mentor Acquisition One, LLC (Plantation, FL)

Family ID: 59724285

Assignee: Mentor Acquisition One, LLC (Plantation, FL)

Appl. No.: 18/655089

Filed: May 03, 2024

Prior Publication Data

Document Identifier

Publication Date

US 20240280816 A1

Aug. 22, 2024

Related U.S. Application Data

continuation parent-doc US 18073424 20221201 US 12007562 child-doc US 18655089

continuation parent-doc US 17485083 20210924 US 11592669 20230228 child-doc US 18073424

Publication Classification

Int. Cl.: **G02B27/00** (20060101); **G02B27/01** (20060101); **G06F1/16** (20060101); **G06F3/01** (20060101); **G06F3/0346** (20130101); **G06T3/02** (20240101); **G06T3/4015** (20240101); **G06T7/73** (20170101)

U.S. Cl.:

CPC **G02B27/017** (20130101); **G02B27/0093** (20130101); **G06F1/163** (20130101); **G06F3/011** (20130101); **G06F3/012** (20130101); **G06F3/013** (20130101); **G06F3/0346** (20130101); **G06T3/02** (20240101); **G06T3/4015** (20130101); **G06T7/73** (20170101); G02B2027/0114 (20130101); G02B2027/0118 (20130101); G02B2027/013 (20130101); G02B2027/0174 (20130101); G06T2207/30201 (20130101)

Field of Classification Search

CPC: G02B (27/017); G02B (27/0093); G02B (2027/0114); G02B (2027/0118); G02B (2027/013); G02B (2027/0174); G06F (1/163); G06F (3/011); G06F (3/012); G06F (3/013); G06F (3/0346); G06T (3/02); G06T (3/4015); G06T (7/73); G06T (2207/30201)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1897833	12/1932	Benway	N/A	N/A
4788535	12/1987	Chikara	N/A	N/A
4852988	12/1988	Velez	N/A	N/A
D327674	12/1991	Kuo	N/A	N/A
5394203	12/1994	Murphy	N/A	N/A
5579026	12/1995	Tabata	N/A	N/A
D376790	12/1995	Taylor	N/A	N/A
5596451	12/1996	Handschy	N/A	N/A
5717422	12/1997	Ferguson	N/A	N/A
5808800	12/1997	Handschy	N/A	N/A
5818381	12/1997	Williams	N/A	N/A
5991085	12/1998	Rallison	N/A	N/A
6028608	12/1999	Jenkins	N/A	N/A
6195136	12/2000	Handschy	N/A	N/A
6198395	12/2000	Sussman	N/A	N/A
6359723	12/2001	Handschy	N/A	N/A
6369952	12/2001	Rallison	N/A	N/A
6392656	12/2001	Someya	N/A	N/A
6433760	12/2001	Vaissie	N/A	N/A
6491391	12/2001	Blum et al.	N/A	N/A
D470144	12/2002	Li	N/A	N/A
6535182	12/2002	Stanton	N/A	N/A

D473871	12/2002	Santos	N/A	N/A
6549231	12/2002	Matsui	N/A	N/A
6675030	12/2003	Ciurczak	N/A	N/A
6847336	12/2004	Lemelson	N/A	N/A
6943754	12/2004	Aughey	N/A	N/A
6972771	12/2004	Nakano	N/A	N/A
6977776	12/2004	Volkenandt et al.	N/A	N/A
6987787	12/2005	Mick	N/A	N/A
7088234	12/2005	Naito	N/A	N/A
7199934	12/2006	Yamasaki	N/A	N/A
7206134	12/2006	Weissman	N/A	N/A
7347551	12/2007	Ferguson et al.	N/A	N/A
7488294	12/2008	Torch	N/A	N/A
7626569	12/2008	Lanier	N/A	N/A
7735230	12/2009	Barany	N/A	N/A
7758185	12/2009	Lewis	N/A	N/A
7812842	12/2009	Gordon	N/A	N/A
7830370	12/2009	Yamazaki	N/A	N/A
7855743	12/2009	Sako	N/A	N/A
7928926	12/2010	Yamamoto	N/A	N/A
8004765	12/2010	Amitai	N/A	N/A
8014666	12/2010	Neiman	N/A	N/A
8018579	12/2010	Krah	N/A	N/A
8166421	12/2011	Magal	N/A	N/A
8228315	12/2011	Starner	N/A	N/A
8235529	12/2011	Raffle	N/A	N/A
8353594	12/2012	Lewis	N/A	N/A
8378924	12/2012	Jacobsen	N/A	N/A
8427396	12/2012	Kim	N/A	N/A
8473241	12/2012	Foxlin	N/A	N/A
8494215	12/2012	Kimchi	N/A	N/A
8564883	12/2012	Totani	N/A	N/A
8570273	12/2012	Smith	N/A	N/A
8576276	12/2012	Bar-zeev	N/A	N/A
8576491	12/2012	Takagi	N/A	N/A
8587869	12/2012	Totani	N/A	N/A
8594467	12/2012	Lu	N/A	N/A
8611015	12/2012	Wheeler	N/A	N/A
8638498	12/2013	Bohn et al.	N/A	N/A
8662686	12/2013	Takagi	N/A	N/A
8670183	12/2013	Clavin	N/A	N/A
8681073	12/2013	Robbins	N/A	N/A
8696113	12/2013	Lewis	N/A	N/A
8698157	12/2013	Hanamura	N/A	N/A
8711487	12/2013	Takeda	N/A	N/A
8733927	12/2013	Lewis	N/A	N/A
8733928	12/2013	Lewis	N/A	N/A
8743052	12/2013	Keller	N/A	N/A
8745058	12/2013	Garcia-Barrio	N/A	N/A
8750541	12/2013	Dong	N/A	N/A

8752963	12/2013	Mcculloch	N/A	N/A
8787006	12/2013	Golko	N/A	N/A
8803867	12/2013	Oikawa	N/A	N/A
8823071	12/2013	Oyamada	N/A	N/A
8832557	12/2013	Fadell	N/A	N/A
8837880	12/2013	Takeda	N/A	N/A
8922530	12/2013	Pance	N/A	N/A
8929589	12/2014	Publicover et al.	N/A	N/A
8947323	12/2014	Raffle	N/A	N/A
8948935	12/2014	Peeters	N/A	N/A
8970495	12/2014	Biffle	N/A	N/A
9010929	12/2014	Lewis	N/A	N/A
9129157	12/2014	Chao	N/A	N/A
9213403	12/2014	Raffle	N/A	N/A
9229233	12/2015	Osterhout	N/A	N/A
9229234	12/2015	Osterhout	N/A	N/A
9230501	12/2015	Starner	N/A	N/A
9235051	12/2015	Salter	N/A	N/A
9235064	12/2015	Lewis	N/A	N/A
9239473	12/2015	Lewis	N/A	N/A
9244293	12/2015	Lewis	N/A	N/A
9274338	12/2015	Robbins et al.	N/A	N/A
9286728	12/2015	Osterhout	N/A	N/A
9292973	12/2015	Bar-zeev et al.	N/A	N/A
9294660	12/2015	O'Neill	N/A	N/A
9323325	12/2015	Perez et al.	N/A	N/A
9423612	12/2015	Border	N/A	N/A
9529192	12/2015	Border	N/A	N/A
9658473	12/2016	Lewis	N/A	N/A
9720505	12/2016	Gribetz et al.	N/A	N/A
9746686	12/2016	Haddick	N/A	N/A
9784973	12/2016	Osterhout	N/A	N/A
9841602	12/2016	Osterhout	N/A	N/A
9852545	12/2016	Osterhout	N/A	N/A
10013053	12/2017	Cederlund et al.	N/A	N/A
10025379	12/2017	Drake et al.	N/A	N/A
10062182	12/2017	Haddick	N/A	N/A
10151937	12/2017	Lewis	N/A	N/A
10185147	12/2018	Lewis	N/A	N/A
10591728	12/2019	Shams	N/A	N/A
11156834	12/2020	Shams et al.	N/A	N/A
11592669	12/2022	Shams et al.	N/A	N/A
12007562	12/2023	Shams	N/A	N/A
2001/0050817	12/2000	Travers	N/A	N/A
2002/0021498	12/2001	Ohtaka	N/A	N/A
2002/0044152	12/2001	Abbott	N/A	N/A
2002/0057280	12/2001	Anabuki	N/A	N/A
2002/0126396	12/2001	Dolgoff	N/A	N/A
2002/0181115	12/2001	Massof	N/A	N/A
2003/0030597	12/2002	Geist	N/A	N/A

2003/0125055	12/2002	Kim	N/A	N/A
2004/0008177	12/2003	Ahn	N/A	N/A
2004/0030448	12/2003	Solomon	N/A	N/A
2004/0101178	12/2003	Fedorovskaya	N/A	N/A
2005/0052613	12/2004	Kidouchim	N/A	N/A
2006/0022993	12/2005	Hammond	N/A	N/A
2006/0023158	12/2005	Howell et al.	N/A	N/A
2006/0072820	12/2005	Porjo	N/A	N/A
2006/0183986	12/2005	Rice	N/A	N/A
2006/0256110	12/2005	Okuno	N/A	N/A
2007/0030243	12/2006	Ishii	N/A	N/A
2007/0035563	12/2006	Biocca	N/A	N/A
2007/0109284	12/2006	Yamazaki	N/A	N/A
2008/0036653	12/2007	Huston	N/A	N/A
2008/0071559	12/2007	Arrasvuori	N/A	N/A
2008/0219025	12/2007	Spitzer	N/A	N/A
2008/0300010	12/2007	Border	348/E5.046	H04N 21/41407
2009/0279180	12/2008	Amitai	N/A	N/A
2009/0307828	12/2008	Ludlow	N/A	N/A
2010/0056274	12/2009	Uusitalo	N/A	N/A
2010/0130140	12/2009	Waku	N/A	N/A
2010/0141555	12/2009	Rorberg	N/A	N/A
2010/0225473	12/2009	Leuthardt	N/A	N/A
2010/0245387	12/2009	Bachelder	N/A	N/A
2011/0007081	12/2010	Gordon	N/A	N/A
2011/0029903	12/2010	Schooleman	345/157	H04N 13/239
2011/0089325	12/2010	Ottney	N/A	N/A
2011/0102234	12/2010	Adams	N/A	N/A
2011/0118870	12/2010	Sugihara	N/A	N/A
2011/0130958	12/2010	Stahl	N/A	N/A
2011/0131495	12/2010	Bull	N/A	N/A
2011/0164047	12/2010	Pance	N/A	N/A
2011/0164163	12/2010	Bilbrey	N/A	N/A
2011/0170061	12/2010	Gordon	N/A	N/A
2011/0175925	12/2010	Kane	N/A	N/A
2011/0196610	12/2010	Waldman	N/A	N/A
2011/0199171	12/2010	Prest	N/A	N/A
2011/0199202	12/2010	De Mers	N/A	N/A
2011/0201213	12/2010	Dabov	N/A	N/A
2011/0202823	12/2010	Berger	N/A	N/A
2011/0211056	12/2010	Publicover et al.	N/A	N/A
2011/0213664	12/2010	Osterhout	N/A	N/A
2011/0221672	12/2010	Osterhout	N/A	N/A
2011/0221896	12/2010	Haddick	N/A	N/A
2011/0249230	12/2010	Blum	N/A	N/A
2012/0021806	12/2011	Maltz	N/A	N/A
2012/0032874	12/2011	Mukawa	N/A	N/A
2012/0033080	12/2011	Watanabe	N/A	N/A
2012/0038641	12/2011	Levantovsky	N/A	N/A

2012/0050138	12/2011	Sato et al.	N/A	N/A
2012/0050493	12/2011	Ernst	N/A	N/A
2012/0062850	12/2011	Travis	N/A	N/A
2012/0075168	12/2011	Osterhout	N/A	N/A
2012/0088543	12/2011	Lindner	N/A	N/A
2012/0092329	12/2011	Koo	N/A	N/A
2012/0113514	12/2011	Rodman	N/A	N/A
2012/0127284	12/2011	Bar-Zeev	N/A	N/A
2012/0188245	12/2011	Hyatt	N/A	N/A
2012/0212398	12/2011	Border	N/A	N/A
2012/0212593	12/2011	Na	N/A	N/A
2012/0223885	12/2011	Perez	N/A	N/A
2012/0242698	12/2011	Haddick	N/A	N/A
2012/0250152	12/2011	Larson	N/A	N/A
2012/0264510	12/2011	Wigdor	N/A	N/A
2012/0293548	12/2011	Perez	N/A	N/A
2012/0294478	12/2011	Publicover	N/A	N/A
2012/0306850	12/2011	Balan	N/A	N/A
2012/0327116	12/2011	Liu	N/A	N/A
2013/0009366	12/2012	Hannegan	N/A	N/A
2013/0027337	12/2012	Chen	N/A	N/A
2013/0044042	12/2012	Olsson	N/A	N/A
2013/0044130	12/2012	Geisner	N/A	N/A
2013/0063496	12/2012	Basler	N/A	N/A
2013/0069924	12/2012	Robinson	N/A	N/A
2013/0077049	12/2012	Bohn	N/A	N/A
2013/0077147	12/2012	Efimov	N/A	N/A
2013/0083009	12/2012	Geisner	N/A	N/A
2013/0083055	12/2012	Piemonte	N/A	N/A
2013/0100259	12/2012	Ramaswamy	N/A	N/A
2013/0120841	12/2012	Shpunt	N/A	N/A
2013/0135198	12/2012	Hodge	N/A	N/A
2013/0154913	12/2012	Genc	N/A	N/A
2013/0154918	12/2012	Vaught	N/A	N/A
2013/0162632	12/2012	Varga	N/A	N/A
2013/0163980	12/2012	Lazaridis	N/A	N/A
2013/0194389	12/2012	Vaught	N/A	N/A
2013/0196757	12/2012	Latta	N/A	N/A
2013/0207970	12/2012	Shpunt	N/A	N/A
2013/0215235	12/2012	Russell	N/A	N/A
2013/0230215	12/2012	Gurman	N/A	N/A
2013/0241948	12/2012	Kimura	N/A	N/A
2013/0257622	12/2012	Davalos	N/A	N/A
2013/0265227	12/2012	Julian	N/A	N/A
2013/0300652	12/2012	Raffle	N/A	N/A
2013/0314555	12/2012	Vartanian	N/A	N/A
2013/0321265	12/2012	Bychkov	N/A	N/A
2013/0321271	12/2012	Bychkov	N/A	N/A
2013/0335301	12/2012	Wong	N/A	N/A
2013/0335435	12/2012	Ambrus	N/A	N/A

2013/0336629	12/2012	Mulholland	N/A	N/A
2013/0342591	12/2012	Sagan	N/A	N/A
2014/0028704	12/2013	Wu	N/A	N/A
2014/0043682	12/2013	Hussey	N/A	N/A
2014/0062854	12/2013	Cho	N/A	N/A
2014/0063473	12/2013	Pasolini	N/A	N/A
2014/0078282	12/2013	Aoki	N/A	N/A
2014/0125668	12/2013	Steed	N/A	N/A
2014/0129328	12/2013	Mathew	N/A	N/A
2014/0146394	12/2013	Tout	N/A	N/A
2014/0147829	12/2013	Jerauld	N/A	N/A
2014/0152530	12/2013	Venkatesha	N/A	N/A
2014/0152558	12/2013	Salter	N/A	N/A
2014/0152676	12/2013	Rohn	N/A	N/A
2014/0159995	12/2013	Adams	N/A	N/A
2014/0160055	12/2013	Margolis	N/A	N/A
2014/0160137	12/2013	Martin	N/A	N/A
2014/0160157	12/2013	Poulos	N/A	N/A
2014/0160170	12/2013	Lyons	N/A	N/A
2014/0168735	12/2013	Yuan	N/A	N/A
2014/0176591	12/2013	Klein	N/A	N/A
2014/0176603	12/2013	Kumar	N/A	N/A
2014/0177023	12/2013	Gao	N/A	N/A
2014/0195918	12/2013	Friedlander	N/A	N/A
2014/0204759	12/2013	Guo	N/A	N/A
2014/0213280	12/2013	Sandel	N/A	N/A
2014/0225814	12/2013	English	N/A	N/A
2014/0240313	12/2013	Varga	N/A	N/A
2014/0247286	12/2013	Chi	N/A	N/A
2014/0253588	12/2013	Mandala	N/A	N/A
2014/0253605	12/2013	Border	N/A	N/A
2014/0267419	12/2013	Ballard	N/A	N/A
2014/0267594	12/2013	Furumura et al.	N/A	N/A
2014/0372957	12/2013	Keane	N/A	N/A
2014/0375680	12/2013	Ackerman	N/A	N/A
2014/0375683	12/2013	Salter	N/A	N/A
2014/0378810	12/2013	Davis	N/A	N/A
2015/0022542	12/2014	Baba	N/A	N/A
2015/0029222	12/2014	Hofmann	N/A	N/A
2015/0134143	12/2014	Willenborg	N/A	N/A
2015/0146004	12/2014	Kritt	N/A	N/A
2015/0153572	12/2014	Miao	N/A	N/A
2015/0161822	12/2014	Basu	N/A	N/A
2015/0168731	12/2014	Robbins	N/A	N/A
2015/0169038	12/2014	Kim	N/A	N/A
2015/0172545	12/2014	Szabo	N/A	N/A
2015/0177514	12/2014	Maimone	N/A	N/A
2015/0193098	12/2014	Kauffmann	N/A	N/A
2015/0205126	12/2014	Schowengerdt	N/A	N/A
2015/0205494	12/2014	Scott	N/A	N/A

2015/0226966	12/2014	Osterhout	N/A	N/A
2015/0226967	12/2014	Osterhout	N/A	N/A
2015/0228099	12/2014	Osterhout	N/A	N/A
2015/0228119	12/2014	Osterhout	N/A	N/A
2015/0228120	12/2014	Osterhout	N/A	N/A
2015/0235429	12/2014	Miller	N/A	N/A
2015/0253573	12/2014	Sako	N/A	N/A
2015/0254882	12/2014	Englert	N/A	N/A
2015/0260986	12/2014	Nortrup	N/A	N/A
2015/0277113	12/2014	Border	N/A	N/A
2015/0277118	12/2014	Border	N/A	N/A
2015/0277122	12/2014	Border	N/A	N/A
2015/0277549	12/2014	Border	N/A	N/A
2015/0279010	12/2014	Cianfrone	N/A	N/A
2015/0279104	12/2014	Border	N/A	N/A
2015/0279107	12/2014	Border	N/A	N/A
2015/0279108	12/2014	Border	N/A	N/A
2015/0302646	12/2014	Osterhout	N/A	N/A
2015/0302647	12/2014	Osterhout	N/A	N/A
2015/0302773	12/2014	Stone	N/A	N/A
2015/0304368	12/2014	Vaccari	N/A	N/A
2015/0316766	12/2014	Weaver	N/A	N/A
2015/0331240	12/2014	Poulos	N/A	N/A
2015/0331241	12/2014	Haddick	N/A	N/A
2015/0332032	12/2014	Alameh	N/A	N/A
2015/0338915	12/2014	Publicover	N/A	N/A
2016/0000316	12/2015	Copland	N/A	N/A
2016/0026853	12/2015	Wexler	382/103	H04N 23/50
2016/0026873	12/2015	Wexler	N/A	N/A
2016/0045810	12/2015	Minkovitch	N/A	N/A
2016/0048019	12/2015	Haddick	N/A	N/A
2016/0048023	12/2015	Haddick	N/A	N/A
2016/0048160	12/2015	Haddick	N/A	N/A
2016/0049008	12/2015	Haddick	N/A	N/A
2016/0054566	12/2015	Osterhout	N/A	N/A
2016/0077342	12/2015	Osterhout	N/A	N/A
2016/0089272	12/2015	Li	N/A	N/A
2016/0117972	12/2015	Yoshiyama	N/A	N/A
2016/0131912	12/2015	Border	N/A	N/A
2016/0140826	12/2015	Sahiholnasab	N/A	N/A
2016/0147063	12/2015	Border	N/A	N/A
2016/0147064	12/2015	Border	N/A	N/A
2016/0147065	12/2015	Border	N/A	N/A
2016/0189426	12/2015	Thomas	N/A	N/A
2016/0202946	12/2015	Osterhout	N/A	N/A
2016/0239985	12/2015	Haddick	N/A	N/A
2016/0240008	12/2015	Haddick	N/A	N/A
2016/0306173	12/2015	Tsukahara	N/A	N/A
2016/0360160	12/2015	Eizenberg	N/A	N/A
2017/0025091	12/2016	Haddick	N/A	N/A

2017/0092235	12/2016	Osman	N/A	N/A
2017/0099433	12/2016	Cleveland	N/A	N/A
2017/0148216	12/2016	Birman	N/A	N/A
2017/0186230	12/2016	Ivers	N/A	N/A
2017/0200296	12/2016	Jones	N/A	N/A
2017/0246070	12/2016	Osterhout	N/A	N/A
2017/0248788	12/2016	Osterhout	N/A	N/A
2017/0248792	12/2016	Border	N/A	N/A
2017/0249860	12/2016	Osterhout	N/A	N/A
2017/0249861	12/2016	Border	N/A	N/A
2017/0249862	12/2016	Border	N/A	N/A
2017/0307880	12/2016	Shrubsole	N/A	N/A
2017/0322422	12/2016	Stone	N/A	N/A
2017/0329141	12/2016	Border	N/A	N/A
2017/0329142	12/2016	Ye	N/A	N/A
2018/0004008	12/2017	Froissard	N/A	N/A
2018/0059421	12/2017	Osterhout	N/A	N/A
2018/0318704	12/2017	Ikenoue et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2316473	12/2000	CA	N/A
2362895	12/2001	CA	N/A
2388766	12/2002	CA	N/A
368898	12/1989	EP	N/A
777867	12/1996	EP	N/A
2333652	12/2010	EP	N/A
2486450	12/2011	EP	N/A
2502410	12/2011	EP	N/A
2011085829	12/2010	JP	N/A
8809942	12/1987	WO	N/A
9600401	12/1995	WO	N/A
9606378	12/1995	WO	N/A
2010062481	12/2009	WO	N/A
2011060525	12/2010	WO	N/A
2011143655	12/2010	WO	N/A
2012058175	12/2011	WO	N/A
2013050650	12/2012	WO	N/A
2013103825	12/2012	WO	N/A
2013110846	12/2012	WO	N/A
2013170073	12/2012	WO	N/A
2014155072	12/2013	WO	N/A
2014168499	12/2013	WO	N/A
2017143128	12/2016	WO	N/A
2017151494	12/2016	WO	N/A

OTHER PUBLICATIONS

US 8,743,465, 1/2012, Totani (withdrawn). cited by applicant

US 8,792,178, 1/2012, Totani (withdrawn). cited by applicant

Azuma, Ronald T. (Aug. 1997). "A Survey of Augmented Reality," In Presence: Teleoperators and Virtual Environments 6, 4, Hughes Research Laboratories, Malibu, CA, located at: <https://web.archive.org/web/20010604100006/http://www.cs.unc.edu/~azuma/ARpresence.pdf> , retrieved on Oct. 26, 2020. cited by applicant

Bimber, Oliver et al. (2005). "Spatial Augmented Reality: Merging Real and Virtual Worlds," A. K. Peters, Ltd., Wellesley, MA. cited by applicant

Final Office Action mailed Mar. 10, 2021, for U.S. Appl. No. 16/719,815, filed Dec. 18, 2019, twenty four pages. cited by applicant

Final Office Action mailed Nov. 23, 2018, for U.S. Appl. No. 15/058,383, filed Mar. 2, 2016, 35 pages. cited by applicant

Final Office Action mailed Sep. 7, 2017, for U.S. Appl. No. 15/058,383, filed Mar. 2, 2016, 34 pages. cited by applicant

Gonzalez et al. "Digital Image Processing Second Edition," http://users.dcc.uchile.cl/~jsaavedr/libros/dip_gw.pdf, 2002, pp. 1-190. cited by applicant

Hopkins et al. "In-VIVO NIR Diffuse-Reflectance Tissue Spectroscopy of Human Subjects," <http://citeseerx.ist.psu.edu/viewdoc/download?doi=10.1.1.596.955&rep=rep1&type=pdf>, 1999, 1-11. cited by applicant

Hu, P., et al., (2013, June). "ViRi: view it right", In Proceeding of the 11th annual international conference on Mobile systems, applications, and services (pp. 277-290). cited by applicant

Huang, Jia-Bin, "Image Completion Using Planar Structure Guidance", ACM Transactions on Graphics, vol. 33, No. 4, Article 129, Jul. 2014, pp. 1-10. cited by applicant

Jacob, R. "Eye Tracking in Advanced Interface Design", Virtual Environments and Advanced Interface Design, Oxford University Press, Inc. (Jun. 1995). cited by applicant

Janin, Adam L. et al. (1993). "Calibration of Head-Mounted Displays for Augmented Reality Applications", Research and Technology Boeing Computer Services MS 7L-48 P.O. Box 24346 Seattle, WA 98124-0346 Virtual Reality Annual International Symposium, 1993., 1993 IEEE, 10 Pages. cited by applicant

Logbar Inc., "Ring: Shortcut Everything", <https://www.kickstarter.com/projects/1761670738/ring-shortcut-everything>, Dec. 2014, 22 pages. cited by applicant

Non-Final Office Action mailed Dec. 21, 2023, for U.S. Appl. No. 18/073,424, filed Dec. 1, 2022, nine pages. cited by applicant

Non-Final Office Action mailed Feb. 9, 2017, for U.S. Appl. No. 15/058,383, filed Mar. 2, 2016, 32 pages. cited by applicant

Non-Final Office Action mailed Jul. 22, 2022, for U.S. Appl. No. 17/485,083, filed Sep. 24, 2021, eight pages. cited by applicant

Non-Final Office Action mailed Mar. 26, 2018, for U.S. Appl. No. 15/058,383, filed Mar. 2, 2016, 37 pages. cited by applicant

Non-Final Office Action mailed Oct. 20, 2020, for U.S. Appl. No. 16/719,815, filed Dec. 18, 2019, twenty six pages. cited by applicant

Notice of Allowance mailed Apr. 1, 2024, for U.S. Appl. No. 18/073,424, filed Dec. 1, 2022, ten pages. cited by applicant

Notice of Allowance mailed Jun. 29, 2021, for U.S. Appl. No. 16/719,815, filed Dec. 18, 2019, eight pages. cited by applicant

Notice of Allowance mailed Nov. 2, 2022, for U.S. Appl. No. 17/485,083, filed Sep. 24, 2021, nine pages. cited by applicant

Notice of Allowance mailed Oct. 30, 2019, for U.S. Appl. No. 15/058,383, filed Mar. 2, 2016, nine pages. cited by applicant

PCT/US2017/019665, "International Application Serial No. PCT/US2017/019665, International Preliminary Report on Patentability and Written Opinion mailed Sep. 13, 2018", Osterhout Group, Inc., 6 Pages. cited by applicant

PCT/US2017/019665, Application Serial No. PCT/US2017/019665, International Search Report and the Written Opinion mailed May 19, 2017, eight pages. cited by applicant
Petty et al. "Screening Controlled Substances Using The Near-Infrared Fourier Transform Raman Technique,"
http://www.nicoletcz.cz/userfiles/file/vjegy/AN51242_Screening%20Controlled%20Substances.pdf, 1996, 2008. cited by applicant
Rolland, J. et al., "High- resolution inset head- mounted display", Optical Society of America, vol. 37, No. 19, Applied Optics, (Jul. 1, 1998). cited by applicant
Schedwill, "Bidirectional OLED Microdisplay", Fraunhofer Research Institution for Organics, Materials and Electronic Device COMEDD, Apr. 11, 2014, 2 pages. cited by applicant
Tanriverdi, V. et al. (Apr. 2000). "Interacting With Eye Movements In Virtual Environments," Department of Electrical Engineering and Computer Science, Tufts University, Medford, MA 02155, USA, Proceedings of the SIGCHI conference on Human Factors in Computing Systems, eight pages. cited by applicant
Vogel, et al., "Data glasses controlled by eye movements", Information and communication, Fraunhofer-Gesellschaft, Sep. 22, 2013, 2 pages. cited by applicant
Yoshida, A. et al., "Design and Applications of a High Resolution Insert Head Mounted Display", (Jun. 1994). cited by applicant
"Continental Head-Up Display Augmented Reality HUD", <http://continental-head-up-display.com/> (2014) (last visited: Jan. 31, 2017). pp. 1-10. cited by applicant
"Genius Ring Mice," <http://www.geniusnet.com/Genius/wSite/productCompare/compare.jsp>, Dec. 23, 2014, one page. cited by applicant

Primary Examiner: Lhymn; Sarah

Attorney, Agent or Firm: Morrison & Foerster LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. Non-Provisional application Ser. No. 18/073,424, filed on Dec. 1, 2022, which is a continuation of U.S. Non-Provisional application Ser. No. 17/485,083, filed on Sep. 24, 2021, now U.S. Pat. No. 11,592,669, issued on Feb. 28, 2023, which is a continuation of U.S. Non-Provisional application Ser. No. 16/719,815, filed on Dec. 18, 2019, now U.S. Pat. No. 11,156,834, issued on Oct. 26, 2021, which is a continuation of U.S. Non-Provisional application Ser. No. 15/058,383, filed on Mar. 2, 2016, now U.S. Pat. No. 10,591,728, issued on Mar. 17, 2020, the contents of which are incorporated by reference herein in their entirety.

BACKGROUND

Field of the Invention

(1) This disclosure relates to optical systems for head-worn computer systems.

Description of Related Art

(2) Head mounted displays (HMDs) and particularly HMDs that provide a see-through view of the environment are valuable instruments. The presentation of content in the see-through display can be a complicated operation when attempting to ensure that the user experience is optimized.

Improved systems and methods for presenting content in the see-through display are required to improve the user experience.

SUMMARY

(3) Aspects of the present disclosure relate to methods and systems for providing optical systems in

head-worn computer systems.

(4) These and other systems, methods, objects, features, and advantages of the present disclosure will be apparent to those skilled in the art from the following detailed description of the preferred embodiment and the drawings. All documents mentioned herein are hereby incorporated in their entirety by reference.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Embodiments are described with reference to the following Figures. The same numbers may be used throughout to reference like features and components that are shown in the Figures:
- (2) FIG. 1 illustrates a head worn computing system in accordance with the principles of the present disclosure.
- (3) FIG. 2 illustrates a head worn computing system with optical system in accordance with the principles of the present disclosure.
- (4) FIG. 3 illustrates upper and lower optical modules in accordance with the principles of the present disclosure.
- (5) FIG. 4 illustrates angles of combiner elements in accordance with the principles of the present disclosure.
- (6) FIG. 5 illustrates upper and lower optical modules in accordance with the principles of the present disclosure.
- (7) FIG. 6 illustrates upper and lower optical modules in accordance with the principles of the present disclosure.
- (8) FIG. 7 illustrates upper and lower optical modules in accordance with the principles of the present disclosure.
- (9) FIG. 8 illustrates upper and lower optical modules in accordance with the principles of the present disclosure.
- (10) FIGS. 9, 10a, 10b and 11 illustrate light sources and filters in accordance with the principles of the present disclosure.
- (11) FIGS. 12a to 12c illustrate light sources and quantum dot systems in accordance with the principles of the present disclosure.
- (12) FIGS. 13a to 13c illustrate peripheral lighting systems in accordance with the principles of the present disclosure.
- (13) FIGS. 14a to 14h illustrate light suppression systems in accordance with the principles of the present disclosure.
- (14) FIG. 15 illustrates an external user interface in accordance with the principles of the present disclosure.
- (15) FIG. 16 illustrates external user interfaces in accordance with the principles of the present disclosure.
- (16) FIGS. 17 and 18 illustrate structured eye lighting systems according to the principles of the present disclosure.
- (17) FIG. 19 illustrates eye glint in the prediction of eye direction analysis in accordance with the principles of the present disclosure.
- (18) FIG. 20a illustrates eye characteristics that may be used in personal identification through analysis of a system according to the principles of the present disclosure.
- (19) FIG. 20b illustrates a digital content presentation reflection off of the wearer's eye that may be analyzed in accordance with the principles of the present disclosure.
- (20) FIG. 21 illustrates eye imaging along various virtual target lines and various focal planes in accordance with the principles of the present disclosure.

- (21) FIG. 22 illustrates content control with respect to eye movement based on eye imaging in accordance with the principles of the present disclosure.
- (22) FIG. 23 illustrates eye imaging and eye convergence in accordance with the principles of the present disclosure.
- (23) FIG. 24 illustrates light impinging an eye in accordance with the principles of the present disclosure.
- (24) FIG. 25 illustrates a view of an eye in accordance with the principles of the present disclosure.
- (25) FIGS. 26a and 26b illustrate views of an eye with a structured light pattern in accordance with the principles of the present disclosure.
- (26) FIG. 27 illustrates a user interface in accordance with the principles of the present disclosure.
- (27) FIG. 28 illustrates a user interface in accordance with the principles of the present disclosure.
- (28) FIGS. 29 and 29a illustrate haptic systems in accordance with the principles of the present disclosure.
- (29) FIG. 30 is an illustration of a cross section of an emissive image source such as an OLED.
- (30) FIG. 31 shows a color filter layout wherein the colors repeat in rows and the rows are offset from one another by one subpixel.
- (31) FIG. 32 shows a color filter layout wherein the colors repeat in rows.
- (32) FIG. 33 shows a color filter layout wherein the colors repeat in rows and each row is offset from neighboring rows by 1½ subpixels.
- (33) FIG. 34 shows an illustration of rays of image light as emitted by a single subpixel in a pixel.
- (34) FIG. 35 is an illustration of how the ray angles of the image light sampled by a lens in forming an image for display in a typical compact head-worn computer vary across an image source.
- (35) FIG. 35a shows an illustration of a compact optical system with a folded optical path wherein light rays are shown passing through the optics from the emissive image source to the eyebox where the user can view the image.
- (36) FIG. 35b shows a thin lens layout with a relatively long focal length and a relatively narrow field of view.
- (37) FIG. 35c shows a thin lens layout with a reduced length and a wider field of view.
- (38) FIG. 36 is an illustration of the chief ray angles sampled by the lens over the surface of the image source.
- (39) FIG. 37 is an illustration of a cross section of a portion of an image source wherein Pixel 1 is a center pixel and Pixel 5 is an edge pixel.
- (40) FIG. 38 shows a modified color filter array wherein the color filter array is somewhat larger than the array of subpixels.
- (41) FIG. 39 shows the effect of the progressively offset color filter array.
- (42) FIG. 40 shows an illustration of an optical solution wherein the rays from each subpixel are repointed so that zero angle rays become rays with the chief ray angle matched to the sampling of the lens.
- (43) FIG. 41 shows an illustration of an array of subpixels on an image source, where the center point of the image source is a subpixel in the array of subpixels.
- (44) FIG. 42 illustrates a user looking at a phone.
- (45) FIGS. 43 and 44 illustrate a user wearing a HWC.
- (46) FIG. 45 illustrates a see-through head-worn display with displayed content.
- (47) FIG. 46 illustrates a user wearing a HWC.
- (48) FIG. 47 illustrates a see-through head-worn display with displayed content.
- (49) While the disclosure has been described in connection with certain preferred embodiments, other embodiments would be understood by one of ordinary skill in the art and are encompassed herein.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT(S)

- (50) Aspects of the present disclosure relate to head-worn computing (“HWC”) systems. HWC

involves, in some instances, a system that mimics the appearance of head-worn glasses or sunglasses. The glasses may be a fully developed computing platform, such as including computer displays presented in each of the lenses of the glasses to the eyes of the user. In embodiments, the lenses and displays may be configured to allow a person wearing the glasses to see the environment through the lenses while also seeing, simultaneously, digital imagery, which forms an overlaid image that is perceived by the person as a digitally augmented image of the environment, or augmented reality (“AR”).

(51) HWC involves more than just placing a computing system on a person's head. The system may need to be designed as a lightweight, compact and fully functional computer display, such as wherein the computer display includes a high resolution digital display that provides a high level of emersion comprised of the displayed digital content and the see-through view of the environmental surroundings. User interfaces and control systems suited to the HWC device may be required that are unlike those used for a more conventional computer such as a laptop. For the HWC and associated systems to be most effective, the glasses may be equipped with sensors to determine environmental conditions, geographic location, relative positioning to other points of interest, objects identified by imaging and movement by the user or other users in a connected group, compass heading, head tilt, where the user is looking and the like. The HWC may then change the mode of operation to match the conditions, location, positioning, movements, and the like, in a method generally referred to as a contextually aware HWC. The glasses also may need to be connected, wirelessly or otherwise, to other systems either locally or through a network. Controlling the glasses may be achieved through the use of an external device, automatically through contextually gathered information, through user gestures captured by the glasses sensors, and the like. Each technique may be further refined depending on the software application being used in the glasses. The glasses may further be used to control or coordinate with external devices that are associated with the glasses.

(52) Referring to FIG. 1, an overview of the HWC system **100** is presented. As shown, the HWC system **100** comprises a HWC **102**, which in this instance is configured as glasses to be worn on the head with sensors such that the HWC **102** is aware of the objects and conditions in the environment **114**. In this instance, the HWC **102** also receives and interprets control inputs such as gestures and movements **116**. The HWC **102** may communicate with external user interfaces **104**. The external user interfaces **104** may provide a physical user interface to take control instructions from a user of the HWC **102** and the external user interfaces **104** and the HWC **102** may communicate bi-directionally to affect the user's command and provide feedback to the external device **108**. The HWC **102** may also communicate bi-directionally with externally controlled or coordinated local devices **108**. For example, an external user interface **104** may be used in connection with the HWC **102** to control an externally controlled or coordinated local device **108**. The externally controlled or coordinated local device **108** may provide feedback to the HWC **102** and a customized GUI may be presented in the HWC **102** based on the type of device or specifically identified device **108**. The HWC **102** may also interact with remote devices and information sources **112** through a network connection **110**. Again, the external user interface **104** may be used in connection with the HWC **102** to control or otherwise interact with any of the remote devices **108** and information sources **112** in a similar way as when the external user interfaces **104** are used to control or otherwise interact with the externally controlled or coordinated local devices **108**. Similarly, HWC **102** may interpret gestures **116** (e.g captured from forward, downward, upward, rearward facing sensors such as camera(s), range finders, IR sensors, etc.) or environmental conditions sensed in the environment **114** to control either local or remote devices **108** or **112**.

(53) We will now describe each of the main elements depicted on FIG. 1 in more detail; however, these descriptions are intended to provide general guidance and should not be construed as limiting. Additional description of each element may also be further described herein.

(54) The HWC **102** is a computing platform intended to be worn on a person's head. The HWC **102** may take many different forms to fit many different functional requirements. In some situations, the HWC **102** will be designed in the form of conventional glasses. The glasses may or may not have active computer graphics displays. In situations where the HWC **102** has integrated computer displays the displays may be configured as see-through displays such that the digital imagery can be overlaid with respect to the user's view of the environment **114**. There are a number of see-through optical designs that may be used, including ones that have a reflective display (e.g. LCOS, DLP), emissive displays (e.g. OLED, LED), hologram, TIR waveguides, and the like. In embodiments, lighting systems used in connection with the display optics may be solid state lighting systems, such as LED, OLED, quantum dot, quantum dot LED, etc. In addition, the optical configuration may be monocular or binocular. It may also include vision corrective optical components. In embodiments, the optics may be packaged as contact lenses. In other embodiments, the HWC **102** may be in the form of a helmet with a see-through shield, sunglasses, safety glasses, goggles, a mask, fire helmet with see-through shield, police helmet with see through shield, military helmet with see-through shield, utility form customized to a certain work task (e.g. inventory control, logistics, repair, maintenance, etc.), and the like.

(55) The HWC **102** may also have a number of integrated computing facilities, such as an integrated processor, integrated power management, communication structures (e.g. cell net, WiFi, Bluetooth, local area connections, mesh connections, remote connections (e.g. client server, etc.)), and the like. The HWC **102** may also have a number of positional awareness sensors, such as GPS, electronic compass, altimeter, tilt sensor, IMU, and the like. It may also have other sensors such as a camera, rangefinder, hyper-spectral camera, Geiger counter, microphone, spectral illumination detector, temperature sensor, chemical sensor, biologic sensor, moisture sensor, ultrasonic sensor, and the like.

(56) The HWC **102** may also have integrated control technologies. The integrated control technologies may be contextual based control, passive control, active control, user control, and the like. For example, the HWC **102** may have an integrated sensor (e.g. camera) that captures user hand or body gestures **116** such that the integrated processing system can interpret the gestures and generate control commands for the HWC **102**. In another example, the HWC **102** may have sensors that detect movement (e.g. a nod, head shake, and the like) including accelerometers, gyros and other inertial measurements, where the integrated processor may interpret the movement and generate a control command in response. The HWC **102** may also automatically control itself based on measured or perceived environmental conditions. For example, if it is bright in the environment the HWC **102** may increase the brightness or contrast of the displayed image. In embodiments, the integrated control technologies may be mounted on the HWC **102** such that a user can interact with it directly. For example, the HWC **102** may have a button(s), touch capacitive interface, and the like.

(57) As described herein, the HWC **102** may be in communication with external user interfaces **104**. The external user interfaces may come in many different forms. For example, a cell phone screen may be adapted to take user input for control of an aspect of the HWC **102**. The external user interface may be a dedicated UI (e.g. air mouse, finger mounted mouse), such as a keyboard, touch surface, button(s), joy stick, and the like. In embodiments, the external controller may be integrated into another device such as a ring, watch, bike, car, and the like. In each case, the external user interface **104** may include sensors (e.g. IMU, accelerometers, compass, altimeter, and the like) to provide additional input for controlling the HWD **104**.

(58) As described herein, the HWC **102** may control or coordinate with other local devices **108**. The external devices **108** may be an audio device, visual device, vehicle, cell phone, computer, and the like. For instance, the local external device **108** may be another HWC **102**, where information may then be exchanged between the separate HWCs **108**.

(59) Similar to the way the HWC **102** may control or coordinate with local devices **106**, the HWC

102 may control or coordinate with remote devices **112**, such as the HWC **102** communicating with the remote devices **112** through a network **110**. Again, the form of the remote device **112** may have many forms. Included in these forms is another HWC **102**. For example, each HWC **102** may communicate its GPS position such that all the HWCs **102** know where all of HWC **102** are located.

(60) FIG. 2 illustrates a HWC **102** with an optical system that includes an upper optical module **202** and a lower optical module **204**. While the upper and lower optical modules **202** and **204** will generally be described as separate modules, it should be understood that this is illustrative only and the present disclosure includes other physical configurations, such as that when the two modules are combined into a single module or where the elements making up the two modules are configured into more than two modules. In embodiments, the upper module **202** includes a computer controlled display (e.g. LCOS, FLCOS, DLP, OLED, backlit LCD, etc.) and image light delivery optics. In embodiments, the lower module includes eye delivery optics that are configured to receive the upper module's image light and deliver the image light to the eye of a wearer of the HWC. In FIG. 2, it should be noted that while the upper and lower optical modules **202** and **204** are illustrated in one side of the HWC such that image light can be delivered to one eye of the wearer, that it is envisioned by the present disclosure that embodiments will contain two image light delivery systems, one for each eye.

(61) FIG. 3 illustrates a combination of an upper optical module **202** with a lower optical module **204**. In this embodiment, the image light projected from the upper optical module **202** may or may not be polarized. The image light is reflected off a flat combiner element **602** such that it is directed towards the user's eye. Wherein, the combiner element **602** is a partial mirror that reflects image light while transmitting a substantial portion of light from the environment so the user can look through the combiner element and see the environment surrounding the HWC.

(62) The combiner **602** may include a holographic pattern, to form a holographic mirror. If a monochrome image is desired, there may be a single wavelength reflection design for the holographic pattern on the surface of the combiner **602**. If the intention is to have multiple colors reflected from the surface of the combiner **602**, a multiple wavelength holographic mirror may be included on the combiner surface. For example, in a three-color embodiment, where red, green and blue pixels are generated in the image light, the holographic mirror may be reflective to wavelengths substantially matching the wavelengths of the red, green and blue light provided in the image light. This configuration can be used as a wavelength specific mirror where pre-determined wavelengths of light from the image light are reflected to the user's eye. This configuration may also be made such that substantially all other wavelengths in the visible pass through the combiner element **602** so the user has a substantially clear view of the environmental surroundings when looking through the combiner element **602**. The transparency between the user's eye and the surrounding may be approximately 80% when using a combiner that is a holographic mirror. Wherein holographic mirrors can be made using lasers to produce interference patterns in the holographic material of the combiner where the wavelengths of the lasers correspond to the wavelengths of light that are subsequently reflected by the holographic mirror.

(63) In another embodiment, the combiner element **602** may include a notch mirror comprised of a multilayer coated substrate wherein the coating is designed to substantially reflect the wavelengths of light provided in the image light by the light source and substantially transmit the remaining wavelengths in the visible spectrum. For example, in the case where red, green and blue light is provided by the light source in the upper optics to enable full color images to be provided to the user, the notch mirror is a tristimulus notch mirror wherein the multilayer coating is designed to substantially reflect narrow bands of red, green and blue light that are matched to the what is provided by the light source and the remaining visible wavelengths are substantially transmitted through the coating to enable a view of the environment through the combiner. In another example where monochrome images are provided to the user, the notch mirror is designed to reflect a single

narrow band of light that is matched to the wavelength range of the image light provided by the upper optics while transmitting the remaining visible wavelengths to enable a see-thru view of the environment. The combiner **602** with the notch mirror would operate, from the user's perspective, in a manner similar to the combiner that includes a holographic pattern on the combiner element **602**. The combiner, with the tristimulus notch mirror, would reflect image light associated with pixels, to the eye because of the match between the reflective wavelengths of the notch mirror and the wavelengths or color of the image light, and the wearer would simultaneously be able to see with high clarity the environmental surroundings. The transparency between the user's eye and the surrounding may be approximately 80% when using the tristimulus notch mirror. In addition, the image provided with the notch mirror combiner can provide higher contrast images than the holographic mirror combiner because the notch mirror acts in a purely reflective manner compared to the holographic mirror which operates through diffraction, and as such the notch mirror is subject to less scattering of the imaging light by the combiner. In another embodiment, the combiner element **602** may include a simple partial mirror that reflects a portion (e.g. 50%) of all wavelengths of light in the visible.

(64) Image light can escape through the combiner **602** and may produce face glow from the optics shown in FIG. 3, as the escaping image light is generally directed downward onto the cheek of the user. When using a holographic mirror combiner or a tristimulus notch mirror combiner, the escaping light can be trapped to avoid face glow. In embodiments, if the image light is polarized before the combiner, a linear polarizer can be laminated, or otherwise associated, to the combiner, with the transmission axis of the polarizer oriented relative to the polarized image light so that any escaping image light is absorbed by the polarizer. In embodiments, the image light would be polarized to provide S polarized light to the combiner for better reflection. As a result, the linear polarizer on the combiner would be oriented to absorb S polarized light and pass P polarized light. This provides the preferred orientation of polarized sunglasses as well.

(65) If the image light is unpolarized, a microlouvered film such as a privacy filter can be used to absorb the escaping image light while providing the user with a see-thru view of the environment. In this case, the absorbance or transmittance of the microlouvered film is dependent on the angle of the light. Where steep angle light is absorbed and light at less of an angle is transmitted. For this reason, in an embodiment, the combiner with the microlouver film is angled at greater than 45 degrees to the optical axis of the image light (e.g. the combiner can be oriented at 50 degrees so the image light from the file lens is incident on the combiner at an oblique angle).

(66) FIG. 4 illustrates an embodiment of a combiner element **602** at various angles when the combiner element **602** includes a holographic mirror. Normally, a mirrored surface reflects light at an angle equal to the angle that the light is incident to the mirrored surface. Typically, this necessitates that the combiner element be at 45 degrees, **602a**, if the light is presented vertically to the combiner so the light can be reflected horizontally towards the wearer's eye. In embodiments, the incident light can be presented at angles other than vertical to enable the mirror surface to be oriented at other than 45 degrees, but in all cases wherein a mirrored surface is employed (including the tristimulus notch mirror described previously), the incident angle equals the reflected angle. As a result, increasing the angle of the combiner **602a** requires that the incident image light be presented to the combiner **602a** at a different angle which positions the upper optical module **202** to the left of the combiner as shown in FIG. 4. In contrast, a holographic mirror combiner, included in embodiments, can be made such that light is reflected at a different angle from the angle that the light is incident onto the holographic mirrored surface. This allows freedom to select the angle of the combiner element **602b** independent of the angle of the incident image light and the angle of the light reflected into the wearer's eye. In embodiments, the angle of the combiner element **602b** is greater than 45 degrees (shown in FIG. 4) as this allows a more laterally compact HWC design. The increased angle of the combiner element **602b** decreases the front to back width of the lower optical module **204** and may allow for a thinner HWC display (i.e. the furthest element

from the wearer's eye can be closer to the wearer's face).

(67) FIG. 5 illustrates another embodiment of a lower optical module **204**. In this embodiment, polarized or unpolarized image light provided by the upper optical module **202**, is directed into the lower optical module **204**. The image light reflects off a partial mirror **804** (e.g. polarized mirror, notch mirror, holographic mirror, etc.) and is directed toward a curved partially reflective mirror **802**. The curved partial mirror **802** then reflects the image light back towards the user's eye, which passes through the partial mirror **804**. The user can also see through the partial mirror **804** and the curved partial mirror **802** to see the surrounding environment. As a result, the user perceives a combined image comprised of the displayed image light overlaid onto the see-thru view of the environment. In a preferred embodiment, the partial mirror **804** and the curved partial mirror **802** are both non-polarizing so that the transmitted light from the surrounding environment is unpolarized so that rainbow interference patterns are eliminated when looking at polarized light in the environment such as provided by a computer monitor or in the reflected light from a lake.

(68) While many of the embodiments of the present disclosure have been referred to as upper and lower modules containing certain optical components, it should be understood that the image light production and management functions described in connection with the upper module may be arranged to direct light in other directions (e.g. upward, sideward, etc.). In embodiments, it may be preferred to mount the upper module **202** above the wearer's eye, in which case the image light would be directed downward. In other embodiments it may be preferred to produce light from the side of the wearer's eye, or from below the wearer's eye. In addition, the lower optical module is generally configured to deliver the image light to the wearer's eye and allow the wearer to see through the lower optical module, which may be accomplished through a variety of optical components.

(69) FIG. 6 illustrates an embodiment of the present disclosure where the upper optical module **202** is arranged to direct image light into a total internal reflection (TIR) waveguide **810**. In this embodiment, the upper optical module **202** is positioned above the wearer's eye **812** and the light is directed horizontally into the TIR waveguide **810**. The TIR waveguide is designed to internally reflect the image light in a series of downward TIR reflections until it reaches the portion in front of the wearer's eye, where the light passes out of the TIR waveguide **812** in a direction toward the wearer's eye. In this embodiment, an outer shield **814** may be positioned in front of the TIR waveguide **810**.

(70) FIG. 7 illustrates an embodiment of the present disclosure where the upper optical module **202** is arranged to direct image light into a TIR waveguide **818**. In this embodiment, the upper optical module **202** is arranged on the side of the TIR waveguide **818**. For example, the upper optical module may be positioned in the arm or near the arm of the HWC when configured as a pair of head worn glasses. The TIR waveguide **818** is designed to internally reflect the image light in a series of TIR reflections until it reaches the portion in front of the wearer's eye, where the light passes out of the TIR waveguide **818** in a direction toward the wearer's eye **812**.

(71) FIG. 8 illustrates yet further embodiments of the present disclosure where an upper optical module **202** directs polarized image light into an optical guide **828** where the image light passes through a polarized reflector **824**, changes polarization state upon reflection of the optical element **822** which includes a $\frac{1}{4}$ wave film for example and then is reflected by the polarized reflector **824** towards the wearer's eye, due to the change in polarization of the image light. The upper optical module **202** may be positioned behind the optical guide **828** wherein the image light is directed toward a mirror **820** that reflects the image light along the optical guide **828** and towards the polarized reflector **824**. Alternatively, in other embodiments, the upper optical module **202** may direct the image light directly along the optical guide **828** and towards the polarized reflector **824**. It should be understood that the present disclosure comprises other optical arrangements intended to direct image light into the wearer's eye.

(72) FIG. 9 illustrates a light source **1100** that may be used in association with the upper optics

module **202**. In embodiments, the light source **1100** may provide light to a backlighting optical system that is associated with the light source **1100** and which serves to homogenize the light and thereby provide uniform illuminating light to an image source in the upper optics. In embodiments, the light source **1100** includes a tristimulus notch filter **1102**. The tristimulus notch filter **1102** has narrow band pass filters for three wavelengths, as indicated in FIG. **10b** in a transmission graph **1108**. The graph shown in FIG. **10a**, as **1104** illustrates an output of three different colored LEDs. One can see that the bandwidths of emission are narrow, but they have long tails. The tristimulus notch filter **1102** can be used in connection with such LEDs to provide a light source **1100** that emits narrow filtered wavelengths of light as shown in FIG. **11** as the transmission graph **1110**. Wherein the clipping effects of the tristimulus notch filter **1102** can be seen to have cut the tails from the LED emission graph **1104** to provide narrower wavelength bands of light to the upper optical module **202**. The light source **1100** can be used in connection with a matched combiner **602** that includes a holographic mirror or tristimulus notch mirror that substantially reflects the narrow bands of image light toward the wearer's eye with a reduced amount of image light that does not get reflected by the combiner, thereby improving efficiency of the head-worn computer (HWC) or head-mounted display (HMD) and reducing escaping light that can cause faceglow.

(73) FIG. **12a** illustrates another light source **1200** that may be used in association with the upper optics module **202**. In embodiments, the light source **1200** may provide light to a backlighting optical system that homogenizes the light prior to illuminating the image source in the upper optics as described previously herein. In embodiments, the light source **1200** includes a quantum dot cover glass **1202**. Where the quantum dots absorb light of a shorter wavelength and emit light of a longer wavelength (FIG. **12b** shows an example wherein a UV spectrum **1202** applied to a quantum dot results in the quantum dot emitting a narrow band shown as a PL spectrum **1204**) that is dependent on the material makeup and size of the quantum dot. As a result, quantum dots in the quantum dot cover glass **1202** can be tailored to provide one or more bands of narrow bandwidth light (e.g. red, green and blue emissions dependent on the different quantum dots included as illustrated in the graph shown in FIG. **12c** where three different quantum dots are used. In embodiments, the LED driver light emits UV light, deep blue or blue light. For sequential illumination of different colors, multiple light sources **1200** would be used where each light source **1200** would include a quantum dot cover glass **1202** with at least one type of quantum dot selected to emit at one of each of the desired colors. The light source **1100** can be used in connection with a combiner **602** with a holographic mirror or tristimulus notch mirror to provide narrow bands of image light that are reflected toward the wearer's eye with less wasted image light that does not get reflected.

(74) Another aspect of the present disclosure relates to the generation of peripheral image lighting effects for a person wearing a HWC. In embodiments, a solid state lighting system (e.g. LED, OLED, etc), or other lighting system, may be included inside the optical elements of an lower optical module **204**. The solid state lighting system may be arranged such that lighting effects outside of a field of view (FOV) associated with displayed digital content is presented to create an immersive effect for the person wearing the HWC. To this end, the lighting effects may be presented to any portion of the HWC that is visible to the wearer. The solid state lighting system may be digitally controlled by an integrated processor on the HWC. In embodiments, the integrated processor will control the lighting effects in coordination with digital content that is presented within the FOV of the HWC. For example, a movie, picture, game, or other content, may be displayed or playing within the FOV of the HWC. The content may show a bomb blast on the right side of the FOV and at the same moment, the solid state lighting system inside of the upper module optics may flash quickly in concert with the FOV image effect. The effect may not be fast, it may be more persistent to indicate, for example, a general glow or color on one side of the user. The solid state lighting system may be color controlled, with red, green and blue LEDs, for example, such that color control can be coordinated with the digitally presented content within the field of

view.

(75) FIG. 13a illustrates optical components of a lower optical module **204** together with an outer lens **1302**. FIG. 13a also shows an embodiment including effects LED's **1308a** and **1308b**. FIG. 13a illustrates image light **1312**, as described herein elsewhere, directed into the upper optical module where it will reflect off of the combiner element **1304**, as described herein elsewhere. The combiner element **1304** in this embodiment is angled towards the wearer's eye at the top of the module and away from the wearer's eye at the bottom of the module, as also illustrated and described in connection with FIG. 8 (e.g. at a 45 degree angle). The image light **1312** provided by an upper optical module **202** (not shown in FIG. 13a) reflects off of the combiner element **1304** towards the collimating mirror **1310**, away from the wearer's eye, as described herein elsewhere. The image light **1312** then reflects and focuses off of the collimating mirror **1304**, passes back through the combiner element **1304**, and is directed into the wearer's eye. The wearer can also view the surrounding environment through the transparency of the combiner element **1304**, collimating mirror **1310**, and outer lens **1302** (if it is included). As described herein elsewhere, the image light may or may not be polarized and the see-through view of the surrounding environment is preferably non-polarized to provide a view of the surrounding environment that does not include rainbow interference patterns if the light from the surrounding environment is polarized such as from a computer monitor or reflections from a lake. The wearer will generally perceive that the image light forms an image in the FOV **1305**. In embodiments, the outer lens **1302** may be included. The outer lens **1302** is an outer lens that may or may not be corrective and it may be designed to conceal the lower optical module components in an effort to make the HWC appear to be in a form similar to standard glasses or sunglasses.

(76) In the embodiment illustrated in FIG. 13a, the effects LEDs **1308a** and **1308b** are positioned at the sides of the combiner element **1304** and the outer lens **1302** and/or the collimating mirror **1310**. In embodiments, the effects LEDs **1308a** are positioned within the confines defined by the combiner element **1304** and the outer lens **1302** and/or the collimating mirror. The effects LEDs **1308a** and **1308b** are also positioned outside of the FOV **1305** associated with the displayed digital content. In this arrangement, the effects LEDs **1308a** and **1308b** can provide lighting effects within the lower optical module outside of the FOV **1305**. In embodiments the light emitted from the effects LEDs **1308a** and **1308b** may be polarized and the outer lens **1302** may include a polarizer such that the light from the effects LEDs **1308a** and **1308b** will pass through the combiner element **1304** toward the wearer's eye and will be absorbed by the outer lens **1302**. This arrangement provides peripheral lighting effects to the wearer in a more private setting by not transmitting the lighting effects through the front of the HWC into the surrounding environment. However, in other embodiments, the effects LEDs **1308a** and **1308b** may be non-polarized so the lighting effects provided are made to be purposefully viewable by others in the environment for entertainment such as giving the effect of the wearer's eye glowing in correspondence to the image content being viewed by the wearer.

(77) FIG. 13b illustrates a cross section of the embodiment described in connection with FIG. 13a. As illustrated, the effects LED **1308a** is located in the upper-front area inside of the optical components of the lower optical module. It should be understood that the effects LED **1308a** position in the described embodiments is only illustrative and alternate placements are encompassed by the present disclosure. Additionally, in embodiments, there may be one or more effects LEDs **1308a** in each of the two sides of HWC to provide peripheral lighting effects near one or both eyes of the wearer.

(78) FIG. 13c illustrates an embodiment where the combiner element **1304** is angled away from the eye at the top and towards the eye at the bottom (e.g. in accordance with the holographic or notch filter embodiments described herein). In this embodiment, the effects LED **1308a** may be located on the outer lens **1302** side of the combiner element **1304** to provide a concealed appearance of the lighting effects. As with other embodiments, the effects LED **1308a** of FIG. 13c may include a

polarizer such that the emitted light can pass through a polarized element associated with the combiner element **1304** and be blocked by a polarized element associated with the outer lens **1302**. Alternatively the effects LED **13087a** can be configured such that at least a portion of the light is reflected away from the wearer's eye so that it is visible to people in the surrounding environment. This can be accomplished for example by using a combiner **1304** that is a simple partial mirror so that a portion of the image light **1312** is reflected toward the wearer's eye and a first portion of the light from the effects LED **13087a** is transmitted toward the wearer's eye and a second portion of the light from the effects LED **1308a** is reflected outward toward the surrounding environment.

(79) FIGS. **14a**, **14b**, **14c** and **14d** show illustrations of a HWC that includes eye covers **1402** to restrict loss of image light to the surrounding environment and to restrict the ingress of stray light from the environment. Where the eye covers **1402** can be removably attached to the HWC with magnets **1404**. Another aspect of the present disclosure relates to automatically configuring the lighting system(s) used in the HWC **102**. In embodiments, the display lighting and/or effects lighting, as described herein, may be controlled in a manner suitable for when an eye cover **1402** is attached or removed from the HWC **102**. For example, at night, when the light in the environment is low, the lighting system(s) in the HWC may go into a low light mode to further control any amounts of stray light escaping from the HWC and the areas around the HWC. Covert operations at night, while using night vision or standard vision, may require a solution which prevents as much escaping light as possible so a user may clip on the eye cover(s) **1402** and then the HWC may go into a low light mode. The low light mode may, in some embodiments, only go into a low light mode when the eye cover **1402** is attached if the HWC identifies that the environment is in low light conditions (e.g. through environment light level sensor detection). In embodiments, the low light level may be determined to be at an intermediate point between full and low light dependent on environmental conditions.

(80) Another aspect of the present disclosure relates to automatically controlling the type of content displayed in the HWC when eye covers **1402** are attached or removed from the HWC. In embodiments, when the eye cover(s) **1402** is attached to the HWC, the displayed content may be restricted in amount or in color amounts. For example, the display(s) may go into a simple content delivery mode to restrict the amount of information displayed. This may be done to reduce the amount of light produced by the display(s). In an embodiment, the display(s) may change from color displays to monochrome displays to reduce the amount of light produced. In an embodiment, the monochrome lighting may be red to limit the impact on the wearer's eyes to maintain an ability to see better in the dark.

(81) Another aspect of the present disclosure relates to a system adapted to quickly convert from a see-through system to a non-see-through or very low transmission see-through system for a more immersive user experience. The conversion system may include replaceable lenses, an eye cover, and optics adapted to provide user experiences in both modes. The outer lenses, for example, may be 'blacked-out' with an opaque cover **1412** to provide an experience where all of the user's attention is dedicated to the digital content and then the outer lenses may be switched out for high see-through lenses so the digital content is augmenting the user's view of the surrounding environment. Another aspect of the disclosure relates to low transmission outer lenses that permit the user to see through the outer lenses but remain dark enough to maintain most of the user's attention on the digital content. The slight see-through can provide the user with a visual connection to the surrounding environment and this can reduce or eliminate nausea and other problems associated with total removal of the surrounding view when viewing digital content.

(82) FIG. **14d** illustrates a head-worn computer system **102** with a see-through digital content display **204** adapted to include a removable outer lens **1414** and a removable eye cover **1402**. The eye cover **1402** may be attached to the head-worn computer **102** with magnets **1404** or other attachment systems (e.g. mechanical attachments, a snug friction fit between the arms of the head-worn computer **102**, etc.). The eye cover **1402** may be attached when the user wants to cut stray

light from escaping the confines of the head-worn computer, create a more immersive experience by removing the otherwise viewable peripheral view of the surrounding environment, etc. The removable outer lens **1414** may be of several varieties for various experiences. It may have no transmission or a very low transmission to create a dark background for the digital content, creating an immersive experience for the digital content. It may have a high transmission so the user can see through the see-through display and the outer lens **1414** to view the surrounding environment, creating a system for a heads-up display, augmented reality display, assisted reality display, etc. The outer lens **1414** may be dark in a middle portion to provide a dark background for the digital content (i.e. dark backdrop behind the see-through field of view from the user's perspective) and a higher transmission area elsewhere. The outer lenses **1414** may have a transmission in the range of 2 to 5%, 5 to 10%, 10 to 20% for the immersion effect and above 10% or 20% for the augmented reality effect, for example. The outer lenses **1414** may also have an adjustable transmission to facilitate the change in system effect. For example, the outer lenses **1414** may be electronically adjustable tint lenses (e.g. liquid crystal or have crossed polarizers with an adjustment for the level of cross).

(83) In embodiments, the eye cover **1402** may have areas of transparency or partial transparency to provide some visual connection with the user's surrounding environment. This may also reduce or eliminate nausea or other feelings associated with the complete removal of the view of the surrounding environment.

(84) FIG. **14e** illustrates a HWC **102** assembled with an eye cover **1402** without outer lenses in place. The outer lenses, in embodiments, may be held in place with magnets **1418** for ease of removal and replacement. In embodiments, the outer lenses may be held in place with other systems, such as mechanical systems.

(85) Another aspect of the present disclosure relates to an effects system that generates effects outside of the field of view in the see-through display of the head-worn computer. The effects may be, for example, lighting effects, sound effects, tactile effects (e.g. through vibration), air movement effects, etc. In embodiments, the effect generation system is mounted on the eye cover **1402**. For example, a lighting system (e.g. LED(s), OLEDs, etc.) may be mounted on an inside surface **1420**, or exposed through the inside surface **1420**, as illustrated in FIG. **14f**, such that they can create a lighting effect (e.g. a bright light, colored light, subtle color effect) in coordination with content being displayed in the field of view of the see-through display. The content may be a movie or a game, for example, and an explosion may happen on the right side of the content, as scripted, and matching the content, a bright flash may be generated by the effects lighting system to create a stronger effect. As another example, the effects system may include a vibratory system mounted near the sides or temples, or otherwise, and when the same explosion occurs, the vibratory system may generate a vibration on the right side to increase the user experience indicating that the explosion had a real sound wave creating the vibration. As yet a further example, the effects system may have an air system where the effect is a puff of air blown onto the user's face. This may create a feeling of closeness with some fast moving object in the content. The effects system may also have speakers directed towards the user's ears or an attachment for ear buds, etc.

(86) In embodiments, the effects generated by the effects system may be scripted by an author to coordinate with the content. In embodiments, sensors may be placed inside of the eye cover to monitor content effects (e.g. a light sensor to measure strong lighting effects or peripheral lighting effects) that would then cause an effect(s) to be generated.

(87) The effects system in the eye cover may be powered by an internal battery and the battery, in embodiments, may also provide additional power to the head-worn computer **102** as a back-up system. In embodiments, the effects system is powered by the batteries in the head-worn computer. Power may be delivered through the attachment system (e.g. magnets, mechanical system) or a dedicated power system.

(88) The effects system may receive data and/or commands from the head-worn computer through

a data connection that is wired or wireless. The data may come through the attachment system, a separate line, or through Bluetooth or other short range communication protocol, for example.

(89) In embodiments, the eye cover **1402** is made of reticulated foam, which is very light and can contour to the user's face. The reticulated foam also allows air to circulate because of the open-celled nature of the material, which can reduce user fatigue and increase user comfort. The eye cover **1402** may be made of other materials, soft, stiff, pliable, etc. and may have another material on the periphery that contacts the face for comfort. In embodiments, the eye cover **1402** may include a fan to exchange air between an external environment and an internal space, where the internal space is defined in part by the face of the user. The fan may operate very slowly and at low power to exchange the air to keep the face of the user cool. In embodiments the fan may have a variable speed controller and/or a temperature sensor may be positioned to measure temperature in the internal space to control the temperature in the internal space to a specified range, temperature, etc. The internal space is generally characterized by the space confined space in front of the user's eyes and upper cheeks where the eye cover encloses the area.

(90) Another aspect of the present disclosure relates to flexibly mounting an audio headset on the head-worn computer **102** and/or the eye cover **1402**. In embodiments, the audio headset is mounted with a relatively rigid system that has flexible joint(s) (e.g. a rotational joint at the connection with the eye cover, a rotational joint in the middle of a rigid arm, etc.) and extension(s) (e.g. a telescopic arm) to provide the user with adjustability to allow for a comfortable fit over, in or around the user's ear. In embodiments, the audio headset is mounted with a flexible system that is more flexible throughout, such as with a wire-based connection.

(91) FIG. **14g** illustrates a head-worn computer **102** with removable lenses **1414** along with a mounted eye cover **1402**. The head-worn computer, in embodiments, includes a see-through display (as disclosed herein). The eye cover **1402** also includes a mounted audio headset **1422**. The mounted audio headset **1422** in this embodiment is mounted to the eye cover **1402** and has audio wire connections (not shown). In embodiments, the audio wires' connections may connect to an internal wireless communication system (e.g. Bluetooth, NFC, WiFi) to make connection to the processor in the head-worn computer. In embodiments, the audio wires may connect to a magnetic connector, mechanical connector or the like to make the connection.

(92) FIG. **14h** illustrates an unmounted eye cover **1402** with a mounted audio headset **1422**. As illustrated, the mechanical design of the eye cover is adapted to fit onto the head-worn computer to provide visual isolation or partial isolation and the audio headset.

(93) In embodiments, the eye cover **1402** may be adapted to be removably mounted on a head-worn computer **102** with a see-through computer display. An audio headset **1422** with an adjustable mount may be connected to the eye cover, wherein the adjustable mount may provide extension and rotation to provide a user of the head-worn computer with a mechanism to align the audio headset with an ear of the user. In embodiments, the audio headset includes an audio wire connected to a connector on the eye cover and the eye cover connector may be adapted to removably mate with a connector on the head-worn computer. In embodiments, the audio headset may be adapted to receive audio signals from the head-worn computer **102** through a wireless connection (e.g. Bluetooth, WiFi). As described elsewhere herein, the head-worn computer **102** may have a removable and replaceable front lens **1414**. The eye cover **1402** may include a battery to power systems internal to the eye cover **1402**. The eye cover **1402** may have a battery to power systems internal to the head-worn computer **102**.

(94) In embodiments, the eye cover **1402** may include a fan adapted to exchange air between an internal space, defined in part by the user's face, and an external environment to cool the air in the internal space and the user's face. In embodiments, the audio headset **1422** may include a vibratory system (e.g. a vibration motor, piezo motor, etc. in the armature and/or in the section over the ear) adapted to provide the user with a haptic feedback coordinated with digital content presented in the see-through computer display. In embodiments, the head-worn computer **102** includes a vibratory

system adapted to provide the user with a haptic feedback coordinated with digital content presented in the see-through computer display.

(95) In embodiments, the eye cover **1402** is adapted to be removably mounted on a head-worn computer with a see-through computer display. The eye cover **1402** may also include a flexible audio headset mounted to the eye cover **1402**, wherein the flexibility provides the user of the head-worn computer **102** with a mechanism to align the audio headset with an ear of the user. In embodiments, the flexible audio headset is mounted to the eye cover **1402** with a magnetic connection. In embodiments, the flexible audio headset may be mounted to the eye cover **1402** with a mechanical connection.

(96) In embodiments, the audio headset **1422** may be spring or otherwise loaded such that the headset presses inward towards the user's ears for a more secure fit.

(97) Referring to FIG. **15**, we now turn to describe a particular external user interface **104**, referred to generally as a pen **1500**. The pen **1500** is a specially designed external user interface **104** and can operate as a user interface, to many different styles of HWC **102**. The pen **1500** generally follows the form of a conventional pen, which is a familiar user handled device and creates an intuitive physical interface for many of the operations to be carried out in the HWC system **100**. The pen **1500** may be one of several user interfaces **104** used in connection with controlling operations within the HWC system **100**. For example, the HWC **102** may watch for and interpret hand gestures **116** as control signals, where the pen **1500** may also be used as a user interface with the same HWC **102**. Similarly, a remote keyboard may be used as an external user interface **104** in concert with the pen **1500**. The combination of user interfaces or the use of just one control system generally depends on the operation(s) being executed in the HWC's system **100**.

(98) While the pen **1500** may follow the general form of a conventional pen, it contains numerous technologies that enable it to function as an external user interface **104**. FIG. **15** illustrates technologies comprised in the pen **1500**. As can be seen, the pen **1500** may include a camera **1508**, which is arranged to view through lens **1502**. The camera may then be focused, such as through lens **1502**, to image a surface upon which a user is writing or making other movements to interact with the HWC **102**. There are situations where the pen **1500** will also have an ink, graphite, or other system such that what is being written can be seen on the writing surface. There are other situations where the pen **1500** does not have such a physical writing system so there is no deposit on the writing surface, where the pen would only be communicating data or commands to the HWC **102**. The lens **1502** configuration is described in greater detail herein. The function of the camera **1508** is to capture information from an unstructured writing surface such that pen strokes can be interpreted as intended by the user. To assist in the predication of the intended stroke path, the pen **1500** may include a sensor, such as an IMU **1512**. Of course, the IMU could be included in the pen **1500** in its separate parts (e.g. gyro, accelerometer, etc.) or an IMU could be included as a single unit. In this instance, the IMU **1512** is used to measure and predict the motion of the pen **1500**. In turn, the integrated microprocessor **1510** would take the IMU information and camera information as inputs and process the information to form a prediction of the pen tip movement.

(99) The pen **1500** may also include a pressure monitoring system **1504**, such as to measure the pressure exerted on the lens **1502**. As will be described in greater detail herein, the pressure measurement can be used to predict the user's intention for changing the weight of a line, type of a line, type of brush, click, double click, and the like. In embodiments, the pressure sensor may be constructed using any force or pressure measurement sensor located behind the lens **1502**, including for example, a resistive sensor, a current sensor, a capacitive sensor, a voltage sensor such as a piezoelectric sensor, and the like.

(100) The pen **1500** may also include a communications module **1518**, such as for bi-directional communication with the HWC **102**. In embodiments, the communications module **1518** may be a short distance communication module (e.g. Bluetooth). The communications module **1518** may be security matched to the HWC **102**. The communications module **1518** may be arranged to

communicate data and commands to and from the microprocessor **1510** of the pen **1500**. The microprocessor **1510** may be programmed to interpret data generated from the camera **1508**, IMU **1512**, and pressure sensor **1504**, and the like, and then pass a command onto the HWC **102** through the communications module **1518**, for example. In another embodiment, the data collected from any of the input sources (e.g. camera **1508**, IMU **1512**, pressure sensor **1504**) by the microprocessor may be communicated by the communication module **1518** to the HWC **102**, and the HWC **102** may perform data processing and prediction of the user's intention when using the pen **1500**. In yet another embodiment, the data may be further passed on through a network **110** to a remote device **112**, such as a server, for the data processing and prediction. The commands may then be communicated back to the HWC **102** for execution (e.g. display writing in the glasses display, make a selection within the UI of the glasses display, control a remote external device **112**, control a local external device **108**), and the like. The pen may also include memory **1514** for long or short term uses.

(101) The pen **1500** may also include a number of physical user interfaces, such as quick launch buttons **1522**, a touch sensor **1520**, and the like. The quick launch buttons **1522** may be adapted to provide the user with a fast way of jumping to a software application in the HWC system **100**. For example, the user may be a frequent user of communication software packages (e.g. email, text, Twitter, Instagram, Facebook, Google+, and the like), and the user may program a quick launch button **1522** to command the HWC **102** to launch an application. The pen **1500** may be provided with several quick launch buttons **1522**, which may be user programmable or factory programmable. The quick launch button **1522** may be programmed to perform an operation. For example, one of the buttons may be programmed to clear the digital display of the HWC **102**. This would create a fast way for the user to clear the screens on the HWC **102** for any reason, such as for example to better view the environment. The quick launch button functionality will be discussed in further detail below. The touch sensor **1520** may be used to take gesture style input from the user. For example, the user may be able to take a single finger and run it across the touch sensor **1520** to affect a page scroll.

(102) The pen **1500** may also include a laser pointer **1524**. The laser pointer **1524** may be coordinated with the IMU **1512** to coordinate gestures and laser pointing. For example, a user may use the laser **1524** in a presentation to help with guiding the audience with the interpretation of graphics and the IMU **1512** may, either simultaneously or when the laser **1524** is off, interpret the user's gestures as commands or data input.

(103) FIG. **16** illustrates yet another embodiment of the present disclosure. FIG. **16** illustrates a watchband clip-on controller **2000**. The watchband clip-on controller may be a controller used to control the HWC **102** or devices in the HWC system **100**. The watchband clip-on controller **2000** has a fastener **2018** (e.g. rotatable clip) that is mechanically adapted to attach to a watchband, as illustrated at **2004**.

(104) The watchband controller **2000** may have quick launch interfaces **2008** (e.g. to launch applications and choosers as described herein), a touch pad **2014** (e.g. to be used as a touch style mouse for GUI control in a HWC **102** display) and a display **2012**. The clip **2018** may be adapted to fit a wide range of watchbands so it can be used in connection with a watch that is independently selected for its function. The clip, in embodiments, is rotatable such that a user can position it in a desirable manner. In embodiments the clip may be a flexible strap. In embodiments, the flexible strap may be adapted to be stretched to attach to a hand, wrist, finger, device, weapon, and the like.

(105) In embodiments, the watchband controller may be configured as a removable and replacable watchband. For example, the controller may be incorporated into a band with a certain width, segment spacing's, etc. such that the watchband, with its incorporated controller, can be attached to a watch body. The attachment, in embodiments, may be mechanically adapted to attach with a pin upon which the watchband rotates. In embodiments, the watchband controller may be electrically connected to the watch and/or watch body such that the watch, watch body and/or the watchband

controller can communicate data between them.

(106) The watchband controller **2000** may have 3-axis motion monitoring (e.g. through an IMU, accelerometers, magnetometers, gyroscopes, etc.) to capture user motion. The user motion may then be interpreted for gesture control.

(107) In embodiments, the watchband controller **2000** may comprise fitness sensors and a fitness computer. The sensors may track heart rate, calories burned, strides, distance covered, and the like. The data may then be compared against performance goals and/or standards for user feedback.

(108) In embodiments directed to capturing images of the wearer's eye, light to illuminate the wearer's eye can be provided by several different sources including: light from the displayed image (i.e. image light); light from the environment that passes through the combiner or other optics; light provided by a dedicated eye light, etc. FIGS. **17** and **18** show illustrations of dedicated eye illumination lights **3420**. FIG. **17** shows an illustration from a side view in which the dedicated illumination eye light **3420** is positioned at a corner of the combiner **3410** so that it doesn't interfere with the image light **3415**. The dedicated eye illumination light **3420** is pointed so that the eye illumination light **3425** illuminates the eyebox **3427** where the eye **3430** is located when the wearer is viewing displayed images provided by the image light **3415**. FIG. **18** shows an illustration from the perspective of the eye of the wearer to show how the dedicated eye illumination light **3420** is positioned at the corner of the combiner **3410**. While the dedicated eye illumination light **3420** is shown at the upper left corner of the combiner **3410**, other positions along one of the edges of the combiner **3410**, or other optical or mechanical components, are possible as well. In other embodiments, more than one dedicated eye light **3420** with different positions can be used. In an embodiment, the dedicated eye light **3420** is an infrared light that is not visible by the wearer (e.g. 800 nm) so that the eye illumination light **3425** doesn't interfere with the displayed image perceived by the wearer.

(109) In embodiments, the eye imaging camera is inline with the image light optical path, or part of the image light optical path. For example, the eye camera may be positioned in the upper module to capture eye image light that reflects back through the optical system towards the image display. The eye image light may be captured after reflecting off of the image source (e.g. in a DLP configuration where the mirrors can be positioned to reflect the light towards the eye image light camera), a partially reflective surface may be placed along the image light optical path such that when the eye image light reflects back into the upper or lower module that it is reflected in a direction that the eye imaging camera can capture light eye image light. In other embodiments, the eye image light camera is positioned outside of the image light optical path. For example, the camera(s) may be positioned near the outer lens of the platform.

(110) FIG. **19** shows a series of illustrations of captured eye images that show the eye glint (i.e. light that reflects off the front of the eye) produced by a dedicated eye light mounted adjacent to the combiner as previously described herein. In this embodiment of the disclosure, captured images of the wearer's eye are analyzed to determine the relative positions of the iris **3550**, pupil, or other portion of the eye, and the eye glint **3560**. The eye glint is a reflected image of the dedicated eye light **3420** when the dedicated light is used. FIG. **19** illustrates the relative positions of the iris **3550** and the eye glint **3560** for a variety of eye positions. By providing a dedicated eye light **3420** in a fixed position, combined with the fact that the human eye is essentially spherical, or at least a reliably repeatable shape, the eye glint provides a fixed reference point against which the determined position of the iris can be compared to determine where the wearer is looking, either within the displayed image or within the see-through view of the surrounding environment. By positioning the dedicated eye light **3420** at a corner of the combiner **3410**, the eye glint **3560** is formed away from the iris **3550** in the captured images. As a result, the positions of the iris and the eye glint can be determined more easily and more accurately during the analysis of the captured images, since they do not interfere with one another. In a further embodiment, the combiner includes an associated cut filter that prevents infrared light from the environment from entering the

HWC and the eye camera is an infrared camera, so that the eye glint **3560** is only provided by light from the dedicated eye light. For example, the combiner can include a low pass filter that passes visible light while reflecting infrared light from the environment away from the eye camera, reflecting infrared light from the dedicated eye light toward the user's eye and the eye camera can include a high pass filter that absorbs visible light associated with the displayed image while passing infrared light associated with the eye image.

(111) In an embodiment of the eye imaging system, the lens for the eye camera is designed to take into account the optics associated with the upper module **202** and the lower module **204**. This is accomplished by designing the eye camera to include the optics in the upper module **202** and optics in the lower module **204**, so that a high MTF image is produced, at the image sensor in the eye camera, of the wearer's eye. In yet a further embodiment, the eye camera lens is provided with a large depth of field to eliminate the need for focusing the eye camera to enable sharp images of the eye to be captured. Where a large depth of field is typically provided by a high $f/\#$ lens (e.g. $f/\# > 5$). In this case, the reduced light gathering associated with high $f/\#$ lenses is compensated by the inclusion of a dedicated eye light to enable a bright image of the eye to be captured. Further, the brightness of the dedicated eye light can be modulated and synchronized with the capture of eye images so that the dedicated eye light has a reduced duty cycle and the brightness of infrared light on the wearer's eye is reduced.

(112) In a further embodiment, FIG. **20a** shows an illustration of an eye image that is used to identify the wearer of the HWC. In this case, an image of the wearer's eye **3611** is captured and analyzed for patterns of identifiable features **3612**. The patterns are then compared to a database of eye images to determine the identity of the wearer. After the identity of the wearer has been verified, the operating mode of the HWC and the types of images, applications, and information to be displayed can be adjusted and controlled in correspondence to the determined identity of the wearer. Examples of adjustments to the operating mode depending on who the wearer is determined to be or not be include: making different operating modes or feature sets available, shutting down or sending a message to an external network, allowing guest features and applications to run, etc.

(113) FIG. **20b** is an illustration of another embodiment using eye imaging, in which the sharpness of the displayed image is determined based on the eye glint produced by the reflection of the displayed image from the wearer's eye surface. By capturing images of the wearer's eye **3611**, an eye glint **3622**, which is a small version of the displayed image can be captured and analyzed for sharpness. If the displayed image is determined to not be sharp, then an automated adjustment to the focus of the HWC optics can be performed to improve the sharpness. This ability to perform a measurement of the sharpness of a displayed image at the surface of the wearer's eye can provide a very accurate measurement of image quality. Having the ability to measure and automatically adjust the focus of displayed images can be very useful in augmented reality imaging where the focus distance of the displayed image can be varied in response to changes in the environment or changes in the method of use by the wearer.

(114) An aspect of the present disclosure relates to controlling the HWC **102** through interpretations of eye imagery. In embodiments, eye-imaging technologies, such as those described herein, are used to capture an eye image or a series of eye images for processing. The image(s) may be processed to determine a user intended action, an HWC predetermined reaction, or other action. For example, the imagery may be interpreted as an affirmative user control action for an application on the HWC **102**. Or, the imagery may cause, for example, the HWC **102** to react in a pre-determined way such that the HWC **102** is operating safely, intuitively, etc.

(115) FIG. **21** illustrates an eye imagery process that involves imaging the HWC **102** wearer's eye(s) and processing the images (e.g. through eye imaging technologies described herein) to determine in what position **3702** the eye is relative to its neutral or forward looking position and/or the FOV **3708**. The process may involve a calibration step where the user is instructed, through

guidance provided in the FOV of the HWC **102**, to look in certain directions such that a more accurate prediction of the eye position relative to areas of the FOV can be made. In the event the wearer's eye is determined to be looking towards the right side of the FOV **3708** (as illustrated in FIG. **21**, the eye is looking out of the page) a virtual target line may be established to project what in the environment the wearer may be looking towards or at. The virtual target line may be used in connection with an image captured by camera on the HWC **102** that images the surrounding environment in front of the wearer. In embodiments, the field of view of the camera capturing the surrounding environment matches, or can be matched (e.g. digitally), to the FOV **3708** such that making the comparison is made more clear. For example, with the camera capturing the image of the surroundings in an angle that matches the FOV **3708** the virtual line can be processed (e.g. in 2d or 3d, depending on the camera images capabilities and/or the processing of the images) by projecting what surrounding environment objects align with the virtual target line. In the event there are multiple objects along the virtual target line, focal planes may be established corresponding to each of the objects such that digital content may be placed in an area in the FOV **3708** that aligns with the virtual target line and falls at a focal plane of an intersecting object. The user then may see the digital content when he focuses on the object in the environment, which is at the same focal plane. In embodiments, objects in line with the virtual target line may be established by comparison to mapped information of the surroundings.

(116) In embodiments, the digital content that is in line with the virtual target line may not be displayed in the FOV until the eye position is in the right position. This may be a predetermined process. For example, the system may be set up such that a particular piece of digital content (e.g. an advertisement, guidance information, object information, etc.) will appear in the event that the wearer looks at a certain object(s) in the environment. A virtual target line(s) may be developed that virtually connects the wearer's eye with an object(s) in the environment (e.g. a building, portion of a building, mark on a building, gps location, etc.) and the virtual target line may be continually updated depending on the position and viewing direction of the wearer (e.g. as determined through GPS, e-compass, IMU, etc.) and the position of the object. When the virtual target line suggests that the wearer's pupil is substantially aligned with the virtual target line or about to be aligned with the virtual target line, the digital content may be displayed in the FOV **3704**.

(117) In embodiments, the time spent looking along the virtual target line and/or a particular portion of the FOV **3708** may indicate that the wearer is interested in an object in the environment and/or digital content being displayed. In the event there is no digital content being displayed at the time a predetermined period of time is spent looking at a direction, digital content may be presented in the area of the FOV **3708**. The time spent looking at an object may be interpreted as a command to display information about the object, for example. In other embodiments, the content may not relate to the object and may be presented because of the indication that the person is relatively inactive. In embodiments, the digital content may be positioned in proximity to the virtual target line, but not in-line with it such that the wearer's view of the surroundings are not obstructed but information can augment the wearer's view of the surroundings. In embodiments, the time spent looking along a target line in the direction of displayed digital content may be an indication of interest in the digital content. This may be used as a conversion event in advertising. For example, an advertiser may pay more for an add placement if the wearer of the HWC **102** looks at a displayed advertisement for a certain period of time. As such, in embodiments, the time spent looking at the advertisement, as assessed by comparing eye position with the content placement, target line or other appropriate position may be used to determine a rate of conversion or other compensation amount due for the presentation.

(118) An aspect of the disclosure relates to removing content from the FOV of the HWC **102** when the wearer of the HWC **102** apparently wants to view the surrounding environments clearly. FIG. **22** illustrates a situation where eye imagery suggests that the eye has or is moving quickly so the digital content **3804** in the FOV **3808** is removed from the FOV **3808**. In this example, the wearer

may be looking quickly to the side indicating that there is something on the side in the environment that has grabbed the wearer's attention. This eye movement **3802** may be captured through eye imaging techniques (e.g. as described herein) and if the movement matches a predetermined movement (e.g. speed, rate, pattern, etc.) the content may be removed from view. In embodiments, the eye movement is used as one input and HWC movements indicated by other sensors (e.g. IMU in the HWC) may be used as another indication. These various sensor movements may be used together to project an event that should cause a change in the content being displayed in the FOV. (119) Another aspect of the present disclosure relates to determining a focal plane based on the wearer's eye convergence. Eyes are generally converged slightly and converge more when the person focuses on something very close. This is generally referred to as convergence. In embodiments, convergence is calibrated for the wearer. That is, the wearer may be guided through certain focal plane exercises to determine how much the wearer's eyes converge at various focal planes and at various viewing angles. The convergence information may then be stored in a database for later reference. In embodiments, a general table may be used in the event there is no calibration step or the person skips the calibration step. The two eyes may then be imaged periodically to determine the convergence in an attempt to understand what focal plane the wearer is focused on. In embodiments, the eyes may be imaged to determine a virtual target line and then the eye's convergence may be determined to establish the wearer's focus, and the digital content may be displayed or altered based thereon.

(120) FIG. **23** illustrates a situation where digital content is moved **3902** within one or both of the FOVs **3908** and **3910** to align with the convergence of the eyes as determined by the pupil movement **3904**. By moving the digital content to maintain alignment, in embodiments, the overlapping nature of the content is maintained so the object appears properly to the wearer. This can be important in situations where 3D content is displayed.

(121) An aspect of the present disclosure relates to controlling the HWC **102** based on events detected through eye imaging. A wearer winking, blinking, moving his eyes in a certain pattern, etc. may, for example, control an application of the HWC **102**. Eye imaging (e.g. as described herein) may be used to monitor the eye(s) of the wearer and once a pre-determined pattern is detected an application control command may be initiated.

(122) An aspect of the disclosure relates to monitoring the health of a person wearing a HWC **102** by monitoring the wearer's eye(s). Calibrations may be made such that the normal performance, under various conditions (e.g. lighting conditions, image light conditions, etc.) of a wearer's eyes may be documented. The wearer's eyes may then be monitored through eye imaging (e.g. as described herein) for changes in their performance. Changes in performance may be indicative of a health concern (e.g. concussion, brain injury, stroke, loss of blood, etc.). If detected the data indicative of the change or event may be communicated from the HWC **102**.

(123) Aspects of the present disclosure relate to security and access of computer assets (e.g. the HWC itself and related computer systems) as determined through eye image verification. As discussed herein elsewhere, eye imagery may be compared to known person eye imagery to confirm a person's identity. Eye imagery may also be used to confirm the identity of people wearing the HWCs **102** before allowing them to link together or share files, streams, information, etc.

(124) A variety of use cases for eye imaging are possible based on technologies described herein. An aspect of the present disclosure relates to the timing of eye image capture. The timing of the capture of the eye image and the frequency of the capture of multiple images of the eye can vary dependent on the use case for the information gathered from the eye image. For example, capturing an eye image to identify the user of the HWC may be required only when the HWC has been turned ON or when the HWC determines that the HWC has been put onto a wearer's head to control the security of the HWC and the associated information that is displayed to the user, wherein the orientation, movement pattern, stress or position of the carhorns (or other portions of

the HWC) of the HWC can be used to determine that a person has put the HWC onto their head with the intention to use the HWC. Those same parameters may be monitored in an effort to understand when the HWC is dismounted from the user's head. This may enable a situation where the capture of an eye image for identifying the wearer may be completed only when a change in the wearing status is identified. In a contrasting example, capturing eye images to monitor the health of the wearer may require images to be captured periodically (e.g. every few seconds, minutes, hours, days, etc.). For example, the eye images may be taken in minute intervals when the images are being used to monitor the health of the wearer when detected movements indicate that the wearer is exercising. In a further contrasting example, capturing eye images to monitor the health of the wearer for long-term effects may only require that eye images be captured monthly. Embodiments of the disclosure relate to selection of the timing and rate of capture of eye images to be in correspondence with the selected use scenario associated with the eye images. These selections may be done automatically, as with the exercise example above where movements indicate exercise, or these selections may be set manually. In a further embodiment, the selection of the timing and rate of eye image capture is adjusted automatically depending on the mode of operation of the HWC. The selection of the timing and rate of eye image capture can further be selected in correspondence with input characteristics associated with the wearer including age and health status, or sensed physical conditions of the wearer including heart rate, chemical makeup of the blood and eye blink rate.

(125) FIG. 24 illustrates a cross section of an eyeball of a wearer of an HWC with focus points that can be associated with the eye imaging system of the disclosure. The eyeball 5010 includes an iris 5012 and a retina 5014. Because the eye imaging system of the disclosure provides coaxial eye imaging with a display system, images of the eye can be captured from a perspective directly in front of the eye and inline with where the wearer is looking. In embodiments of the disclosure, the eye imaging system can be focused at the iris 5012 and/or the retina 5014 of the wearer, to capture images of the external surface of the iris 5012 or the internal portions of the eye, which includes the retina 5014. FIG. 24 shows light rays 5020 and 5025 that are respectively associated with capturing images of the iris 5012 or the retina 5014 wherein the optics associated with the eye imaging system are respectively focused at the iris 5012 or the retina 5014. Illuminating light can also be provided in the eye imaging system to illuminate the iris 5012 or the retina 5014. FIG. 25 shows an illustration of an eye including an iris 5130 and a sclera 5125. In embodiments, the eye imaging system can be used to capture images that include the iris 5130 and portions of the sclera 5125. The images can then be analyzed to determine color, shapes and patterns that are associated with the user. In further embodiments, the focus of the eye imaging system is adjusted to enable images to be captured of the iris 5012 or the retina 5014. Illuminating light can also be adjusted to illuminate the iris 5012 or to pass through the pupil of the eye to illuminate the retina 5014. The illuminating light can be visible light to enable capture of colors of the iris 5012 or the retina 5014, or the illuminating light can be ultraviolet (e.g. 340 nm), near infrared (e.g. 850 nm) or mid-wave infrared (e.g. 5000 nm) light to enable capture of hyperspectral characteristics of the eye.

(126) FIGS. 26a and 26b illustrate captured images of eyes where the eyes are illuminated with structured light patterns. In FIG. 26a, an eye 5220 is shown with a projected structured light pattern 5230, where the light pattern is a grid of lines. A light pattern of such as 5230 can be provided by the light source 5355 by including a diffractive or a refractive device to modify the light 5357 as are known by those skilled in the art. A visible light source can also be included for the second camera, which can include a diffractive or refractive to modify the light 5467 to provide a light pattern. FIG. 26b illustrates how the structured light pattern of 5230 becomes distorted to 5235 when the user's eye 5225 looks to the side. This distortion comes from the fact that the human eye is not completely spherical in shape, instead the iris sticks out slightly from the eyeball to form a bump in the area of the iris. As a result, the shape of the eye and the associated shape of the reflected structured light pattern is different depending on which direction the eye is pointed, when

images of the eye are captured from a fixed position. Changes in the structured light pattern can subsequently be analyzed in captured eye images to determine the direction that the eye is looking. (127) The eye imaging system can also be used for the assessment of aspects of health of the user. In this case, information gained from analyzing captured images of the iris **5130** or sclera **5125** are different from information gained from analyzing captured images of the retina **5014**. Where images of the retina **5014** are captured using light that illuminates the inner portions of the eye including the retina **5014**. The light can be visible light, but in an embodiment, the light is infrared light (e.g. wavelength 1 to 5 microns) and the eye camera is an infrared light sensor (e.g. an InGaAs sensor) or a low resolution infrared image sensor that is used to determine the relative amount of light that is absorbed, reflected or scattered by the inner portions of the eye. Wherein the majority of the light that is absorbed, reflected or scattered can be attributed to materials in the inner portion of the eye including the retina where there are densely packed blood vessels with thin walls so that the absorption, reflection and scattering are caused by the material makeup of the blood. These measurements can be conducted automatically when the user is wearing the HWC, either at regular intervals, after identified events or when prompted by an external communication. In a preferred embodiment, the illuminating light is near infrared or mid infrared (e.g. 0.7 to 5 microns wavelength) to reduce the chance for thermal damage to the wearer's eye. In a further embodiment, the light source and the camera together comprise a spectrometer wherein the relative intensity of the light reflected by the eye is analyzed over a series of narrow wavelengths within the range of wavelengths provided by the light source to determine a characteristic spectrum of the light that is absorbed, reflected or scattered by the eye. For example, the light source can provide a broad range of infrared light to illuminate the eye and the camera can include: a grating to laterally disperse the reflected light from the eye into a series of narrow wavelength bands that are captured by a linear photodetector so that the relative intensity by wavelength can be measured and a characteristic absorbance spectrum for the eye can be determined over the broad range of infrared. In a further example, the light source can provide a series of narrow wavelengths of light (ultraviolet, visible or infrared) to sequentially illuminate the eye and camera includes a photodetector that is selected to measure the relative intensity of the series of narrow wavelengths in a series of sequential measurements that together can be used to determine a characteristic spectrum of the cyc. The determined characteristic spectrum is then compared to known characteristic spectra for different materials to determine the material makeup of the eye. In yet another embodiment, the illuminating light is focused on the retina and a characteristic spectrum of the retina is determined and the spectrum is compared to known spectra for materials that may be present in the user's blood. For example, in the visible wavelengths 540 nm is useful for detecting hemoglobin and 660 nm is useful for differentiating oxygenated hemoglobin. In a further example, in the infrared, a wide variety of materials can be identified as is known by those skilled in the art, including: glucose, urea, alcohol and controlled substances.

(128) Another aspect of the present disclosure relates to an intuitive user interface mounted on the HWC **102** where the user interface includes tactile feedback (otherwise referred to as haptic feedback) to the user to provide the user an indication of engagement and change. In embodiments, the user interface is a rotating element on a temple section of a glasses form factor of the HWC **102**. The rotating element may include segments such that it positively engages at certain predetermined angles. This facilitates a tactile feedback to the user. As the user turns the rotating element it 'clicks' through it's predetermined steps or angles and each step causes a displayed user interface content to be changed. For example, the user may cycle through a set of menu items or selectable applications. In embodiments, the rotating element also includes a selection element, such as a pressure-induced section where the user can push to make a selection.

(129) FIG. **27** illustrates a human head wearing a head-worn computer in a glasses form factor. The glasses have a temple section **11702** and a rotating user interface element **11704**. The user can rotate the rotating element **11704** to cycle through options presented as content in the see-through

display of the glasses. FIG. 28 illustrates several examples of different rotating user interface elements **11704a**, **11704b** and **11704c**. Rotating element **11704a** is mounted at the front end of the temple and has significant side and top exposure for user interaction. Rotating element **11704b** is mounted further back and also has significant exposure (e.g. 270 degrees of touch). Rotating element **11704c** has less exposure and is exposed for interaction on the top of the temple. Other embodiments may have a side or bottom exposure.

(130) Another aspect of the present disclosure relates to a haptic system in a head-worn computer. Creating visual, audio, and haptic sensations in coordination can increase the enjoyment or effectiveness of awareness in a number of situations. For example, when viewing a movie or playing a game while digital content is presented in a computer display of a head-worn computer, it is more immersive to include coordinated sound and haptic effects. When presenting information in the head-worn computer, it may be advantageous to present a haptic effect to enhance or be the information. For example, the haptic sensation may gently cause the user of the head-worn computer believe that there is some presence on the user's right side, but out of sight. It may be a very light haptic effect to cause the 'tingling' sensation of a presence of unknown origin. It may be a high intensity haptic sensation to coordinate with an apparent explosion, either out of sight or in-sight in the computer display. Haptic sensations can be used to generate a perception in the user that objects and events are close by. As another example, digital content may be presented to the user in the computer displays and the digital content may appear to be within reach of the user. If the user reaches out his hand in an attempt to touch the digital object, which is not a real object, the haptic system may cause a sensation and the user may interpret the sensation as a touching sensation. The haptic system may generate slight vibrations near one or both temples for example and the user may infer from those vibrations that he has touched the digital object. This additional dimension in sensory feedback can be very useful and create a more intuitive and immersive user experience.

(131) Another aspect of the present disclosure relates to controlling and modulating the intensity of a haptic system in a head-worn computer. In embodiments, the haptic system includes separate piezo strips such that each of the separate strips can be controlled separately. Each strip may be controlled over a range of vibration levels and some of the separate strips may have a greater vibration capacity than others. For example, a set of strips may be mounted in the arm of the head-worn computer (e.g. near the user's temple, ear, rear of the head, substantially along the length of the arm, etc.) and the further forward the strip the higher capacity the strip may have. The strips of varying capacity could be arranged in any number of ways, including linear, curved, compound shape, two dimensional array, one dimensional array, three dimensional array, etc.). A processor in the head-worn computer may regulate the power applied to the strips individually, in sub-groups, as a whole, etc. In embodiments, separate strips or segments of varying capacity are individually controlled to generate a finely controlled multi-level vibration system. Patterns based on frequency, duration, intensity, segment type, and/or other control parameters can be used to generate signature haptic feedback. For example, to simulate the haptic feedback of an explosion close to the user, a high intensity, low frequency, and moderate duration may be a pattern to use. A bullet whipping by the user may be simulated with a higher frequency and shorter duration. Following this disclosure, one can imagine various patterns for various simulation scenarios.

(132) Another aspect of the present disclosure relates to making a physical connection between the haptic system and the user's head. Typically, with a glasses format, the glasses touch the user's head in several places (e.g. ears, nose, forehead, etc.) and these areas may be satisfactory to generate the necessary haptic feedback. In embodiments, an additional mechanical element may be added to better translate the vibration from the haptic system to a desired location on the user's head. For example, a vibration or signal conduit may be added to the head-worn computer such that there is a vibration translation medium between the head-worn computers internal haptic system and the user's temple area.

(133) FIG. 29 illustrates a head-worn computer 102 with a haptic system comprised of piezo strips 29002. In this embodiment, the piezo strips 29002 are arranged linearly with strips of increasing vibration capacity from back to front of the arm 29004. The increasing capacity may be provided by different sized strips, for example. This arrangement can cause a progressively increased vibration power 29003 from back to front. This arrangement is provided for case of explanation; other arrangements are contemplated by the inventors of the present application and these examples should not be construed as limiting. The head-worn computer 102 may also have a vibration or signal conduit 29001 that facilitates the physical vibrations from the haptic system to the head of the user 29005. The vibration conduit may be malleable to form to the head of the user for a tighter or more appropriate fit.

(134) An aspect of the present invention relates to a head-worn computer, comprising: a frame adapted to hold a computer display in front of a user's eye; a processor adapted to present digital content in the computer display and to produce a haptic signal in coordination with the digital content display; and a haptic system comprised of a plurality of haptic segments, wherein each of the haptic segments is individually controlled in coordination with the haptic signal. In embodiments, the haptic segments comprise a piezo strip activated by the haptic signal to generate a vibration in the frame. The intensity of the haptic system may be increased by activating more than one of the plurality of haptic segments. The intensity may be further increased by activating more than 2 of the plurality of haptic segments. In embodiments, each of the plurality of haptic segments comprises a different vibration capacity. In embodiments, the intensity of the haptic system may be regulated depending on which of the plurality of haptic segments is activated. In embodiments, each of the plurality of haptic segments are mounted in a linear arrangement and the segments are arranged such that the higher capacity segments are at one end of the linear arrangement. In embodiments, the linear arrangement is from back to front on an arm of the head-worn computer. In embodiments, the linear arrangement is proximate a temple of the user. In embodiments, the linear arrangement is proximate an ear of the user. In embodiments, the linear arrangement is proximate a rear portion of the user's head. In embodiments, the linear arrangement is from front to back on an arm of the head-worn computer, or otherwise arranged.

(135) An aspect of the present disclosure provides a head-worn computer with a vibration conduit, wherein the vibration conduit is mounted proximate the haptic system and adapted to touch the skin of the user's head to facilitate vibration sensations from the haptic system to the user's head. In embodiments, the vibration conduit is mounted on an arm of the head-worn computer. In embodiments, the vibration conduit touches the user's head proximate a temple of the user's head. In embodiments, the vibration conduit is made of a soft material that deforms to increase contact area with the user's head.

(136) An aspect of the present disclosure relates to a haptic array system in a head-worn computer. The haptic array(s) that can correlate vibratory sensations to indicate events, scenarios, etc. to the wearer. The vibrations may correlate or respond to auditory, visual, proximity to elements, etc. of a video game, movie, or relationships to elements in the real world as a means of augmenting the wearer's reality. As an example, physical proximity to objects in a wearer's environment, sudden changes in elevation in the path of the wearer (e.g. about to step off a curb), the explosions in a game or bullets passing by a wearer. Haptic effects from a piezo array(s) that make contact the side of the wearer's head may be adapted to effect sensations that correlate to other events experienced by the wearer.

(137) FIG. 29a illustrates a haptic system according to the principles of the present disclosure. In embodiments the piezo strips are mounted or deposited with varying width and thus varying force Piezo Elements on a rigid or flexible, non-conductive substrate attached, to or part of the temples of glasses, goggles, bands or other form factor. The non-conductive substrate may conform to the curvature of a head by being curved and it may be able to pivot (e.g. in and out, side to side, up and down, etc.) from a person's head. This arrangement may be mounted to the inside of the temples of

a pair of glasses. Similarly, the vibration conduit, described herein elsewhere, may be mounted with a pivot. As can be seen in FIG. 29a, the piezo strips 29002 may be mounted on a substrate and the substrate may be mounted to the inside of a glasses arm, strap, etc. The piezo strips in this embodiment increase in vibration capacity as they move forward.

(138) To make compact optics for head-worn computers, it is advantageous to use a wide cone of light from the image source. A wide cone of light from the image source is especially important if the optics are to provide the user with a wide field of view as the wide cone makes it easier for the optics to spread the ray bundles of the image light from the small image source to the larger area of the combiner when providing the wide angular field of image light that makes up the wide field of view. In this way, the optics for head worn computers are very different from a display such as a television where a viewer sees the display from a very limited cone of image light.

(139) FIG. 35a shows an illustration of a typical compact optical system 35060 with a folded optical path wherein light rays are shown passing through the optics from the emissive image source 35030 to the eyebox 35065 where the user can view the image. as shown in FIG. 35a, image light is emitted by the image source 35030. The image light is then condensed by the lens 35075 so that a converging field of view is provided to the eyebox after being reflected by the beam splitter 35070. In this example, the angular size of the field of view is ultimately established by the size of the lens 35075 and the optical distance from the lens 35075 to the eyebox 35065. This can be seen by following the diverging rays 35064 from the eyebox 35065 to the beam splitter 35070 where they are folded by reflection from the beam splitter 35070 and then to the lens 35075. Where the angle between the outermost rays 35064 form the field of view associated with the displayed image. To make the optical system 35060 lower cost and light weight, it is advantageous to use a small image source 35030. To make the optical system 35060 compact, it is advantageous to use a folded optical path as shown in FIG. 35a wherein the fold is provided by the beam splitter 35070, but other folded configurations are also possible. Another important factor that enables the optical system 35060 to be compact is to use a wide cone of image light from the image source 35030 which enables the image source 35030 to be positioned close to the lens 35075. FIGS. 35b and 35c illustrate how using a short focal length lens in an optical system enables a more compact overall length while also providing a wider field of view to the user's eye. FIG. 35b shows a typical thin lens layout with a relatively long focal length and a relatively narrow field of view, wherein the image source 35085 is positioned at the focal length of the lens 35082 and the eye 35080 is positioned approximately at the same distance from the lens as the focal length. The aperture of the lens system is determined by the eyebox 35081. The ray bundles from any point on the image source 35085 provide a cone of light that as sampled by the lens 35082 will cover the area of the eyebox 35081. With the relatively long focal length lens 35082, the chief rays 35086 and 35087 at the center of each ray bundle are shown as essentially parallel and as a result, the chief rays 35086 and 35087 sampled by the lens 35082 all have a chief ray angle (the angle between the chief ray and the surface normal of the image source) of nearly zero. In contrast, FIG. 35c shows a thin lens layout with a reduced length and a wider field of view. This is provided by using a lens 35090 with a shorter focal length. The image source 35085 is again positioned at the focal length of the lens 35090 to provide a sharp image. However in this case, the chief rays 35092 and 35091 are substantially diverging in order to provide the increased field of view to the eyebox 35081 and the user's eye 35080. Where the field of view is the subtended angle between the rays provided to the eyebox 35081. As such, for a given size of image source 35085, optical systems that provide a wide field of view will be associated with larger chief ray angles as sampled by the lens 35090 to provide the image to the user's eye 35080.

(140) In a display system for a head-worn computer such as the optical system 35060 shown in FIG. 35a, the lens 35075 samples the image light provided by the image source 35030 such that the chief ray angles associated with the ray bundles of image light that is used to form the image seen by the user, will vary with the radial distance from the center of the image source 35030.

Consequently, the chief ray angle is typically zero at the center of the image source **35030** and the chief ray angle increases out to the corner of the image source **35030** where it reaches its greatest value. For an optical system **35060** that provides a field of view of 30 degrees or greater, the chief ray angle can be 25 degrees or greater. For an optical system **35060** that provides a field of view of 50 degrees or greater, the chief ray angle can be 40 degrees or greater. Where the chief ray is the center of a cone of light rays for each pixel in the image and the subtended angle of the cone of light rays in the ray bundle is determined by the f # of the optical system **35060**. As such the angular distribution of the image light that provides the image to the user at the eyebox **35065** is determined by the chief ray angles and the f # of the optical system **35060**. To provide uniform brightness and color to the user over the entire image, the image source **35030** must be capable of providing uniform brightness and color for all of the pixels in the image regardless of the chief ray angle associated with the pixel.

(141) FIG. **30** is an illustration of a cross section of an emissive image source **35030** such as an OLED as it is typically provided. Wherein the image source **35030** is comprised of pixels **30005** where each pixel **30005** includes a set of subpixels **30000**. For simplicity in FIG. **30** and others (FIGS. **37**, **38**, **39**, and **40**) Pixel 1 is presented as the center pixel on the image source **35030** and Pixel 5 is positioned near the edge of the image source **35030**. Each set of subpixels **30000** provide the color set associated with each pixel **30005**, such as red, green and blue, or cyan, magenta, yellow but other configurations of sets of subpixels **30000** are possible such as including a white subpixel with each pixel **30005**. While the subpixels **30000** can be made to directly emit different colors, in many cases, it is advantageous for manufacturers of OLED image sources to provide subpixels **30000** comprised of white emitting subpixels **30000** with an associated color filter array **30020** to convert the emitted white light from each subpixel **30000** to the appropriate color for the subpixel **30000**. Where the color filter array **30020** can be separated from the white emitting subpixels **30000** by a transparent layer **30010** that is provided for a variety of reasons such as to provide a moisture barrier over the pixels **30005**. The color filter array **30020** can also be protected by a cover glass (not shown) that is positioned directly over the color filter array **30020**. Many of the OLED microdisplays available at this time are made in this way with white emitting subpixels **30000**, a transparent layer **30010** and a color filter array **30020** with a cover glass. This alignment of the color filters **30020** directly over associated subpixels **30000** provides good color rendition across the image when viewed from a position directly above the image source **35030** where the viewing angle is relatively uniform. However, when viewed from an angle so that a chief ray angle of greater than approximately 20 degrees such in the optical system shown in FIG. **35c**, the color rendition changes and a shift in the color of the image is observed. The reasons for this color shift will be explained in more detail below.

(142) FIGS. **31**, **32** and **33** show illustrations of examples of common layouts for the color filters associated with subpixels on image sources. FIG. **31** shows a color filter layout **31010** wherein the colors repeat in rows and the rows are offset from one another by one subpixel. FIG. **32** shows a color filter layout **33010** wherein the colors repeat in rows. FIG. **33** shows a color filter layout **33010** wherein the colors repeat in rows and each row is offset from neighboring rows by 1½ subpixels. As shown in FIG. **31**, a pixel **31015** is comprised of three subpixels **30000** with red, green and blue color filters arranged in a linear pattern. While the pixel **31015** is shown to be rectangular with square subpixels **30000** for simplicity, pixels **31015** are typically actually square with rectangular subpixels **30000**. Similarly, FIG. **32** shows pixels **33015** comprised of subpixels **30000** with red-green and blue color filter linearly arranged. FIG. **33** shows a different layout wherein a pixel **33015** is comprised of subpixels **30000** that include red, green and blue color filters. However, in this case, the subpixels **30000** and color filters are arranged in a triangle to make the pixel appear as more of a round spot in the image.

(143) FIG. **34** shows an illustration of rays **34025** of image light as emitted by a single subpixel **30000** in a pixel **30005**. The subpixel **30000** emits white light with an angular cone subtended by

the rays **34025**. The rays **34025** then pass through the transparent layer **30010** and the color filters **30020**. However the angular cone subtended by the rays **34025** is large enough that the rays pass through not only the color filter **30020** associated with the particular subpixel **30000**, but also the adjacent color filters **30020** that are associated with adjacent subpixels **30000**. Since as shown in FIGS. **31**, **32** and **33** the adjacent subpixels may have color filters of different colors, the rays **34025** will have different colors depending on which color filter they have passed through. As such, the color produced by a subpixel **30000** varies depending on the angle that it is viewed from above the image source **130**. This effect is responsible for causing a color shift in images displayed in head-worn computers that becomes more noticeable as the chief ray angle increases such as near the edges or sides of the displayed image.

(144) FIG. **35** is an illustration of how the ray angles of the image light sampled by a lens in forming an image for display in a typical compact head-worn computer vary across an image source **35030**. Image light rays **35040** as sampled by the lens **35035** to form an image for display to a user have a chief ray angle that varies across the image source **35030**. In the center of the image source **35030**, the ray **35045** has a zero chief ray angle. In contrast, the ray **35050** at an edge of the image source **35030** has a chief ray angle that is approximately 45 degrees as shown. FIG. **36** is an illustration of the chief ray angles sampled by the lens **35035** over the surface of the image source **35030**. This illustration shows how the chief ray angle varies based on the radial distance from the center of the image source **35030**. Ray **35050** has the largest chief ray angle because the associated pixel **30005** is located adjacent to the corner of the image source **35030** thereby positioning the pixel **30005** radially furthest from the center of the image source **35030**. As such, when the chief ray angle for the rays **35040** is considered in combination with the effect described with FIG. **34** and the thickness of the transparent layer **30010**, ray **35045** would be of the intended color and ray **35050** would be of another color that came from an adjacent color filter **30020**. These color differences will be visible in the image that is displayed to the user

(145) FIG. **37** is an illustration of a cross section of a portion of an image source **35030** wherein Pixel 1 is a center pixel and Pixel 5 is an edge pixel. Rays **34025** are shown emitted as a cone of rays (only half of the cone of rays emitted by each subpixel is shown to simplify the figure) for one subpixel **30000** in each pixel **30005**. While each subpixel **30000** emits the same cone of rays **34025**, the lens **35035** only samples a small portion of the rays **34025** emitted by each subpixel **30000**. Where the sampled portion of the rays **34025** is different for each subpixel **30000** depending on the chief ray angle associated with the pixel **30005** and the radial position of the pixel **30005** relative to the center of the image source **35030**. As a result, while each subpixel **30000** shown with emitted rays **34025** in FIG. **37** can be thought of as a red subpixel because a red color filter is positioned directly over each subpixel **30000**, the colors of the sampled rays (shown as dark lines in FIG. **37**) will progressively shift from red (ray **37045**) to green (ray **37050**). Consequently methods are needed to compensate for the color shift encountered at the edges and corners of images displayed in head-worn computers when the optical systems use high chief ray angles.

(146) FIG. **38** shows a modified color filter array **38020** wherein the color filter array **38020** is somewhat larger than the array of subpixels **30000**. As a result, the position of the color filters over the subpixels **30000** is progressively outwardly offset for subpixels that are positioned further away from the center of the image source. FIG. **39** shows the effect of the progressively offset color filter array **39020**. Each of the subpixels **30000** emits the same cone of rays **34025** as shown in FIG. **37**, but now the rays that are sampled by the lens **39045** (shown as dark lines) all pass through the red color filter in the color filter array **39020** so that each of the subpixels **30000** shown in the same relative position within the pixels **30005** produce the same red color in the image displayed to the user in the optical system **35060**. As such, the progressively offset color filter array **39020** effectively compensates for the increasing chief ray angle that enables compact optical systems with a wide field of view. Where the progressive offset of the color filter array can be radially based, linearly based with a progressive X direction shift or rectilinearly based with a progressive

X direction and Y direction shift. Where a radial shift or a rectilinear shift are well suited for a symmetric arrangement of the subpixels and color filters such as is shown in FIG. 33. A linearly based shift is well suited for a more rectangular arrangement of subpixels and color filters such as shown in FIG. 32 or a version of FIG. 31 wherein the pixels are square and the subpixels and color filters are rectangular. This embodiment can be implemented by changing the color filter array pattern that is applied to the image source.

(147) FIG. 40 shows an illustration of an optical solution wherein the rays from each subpixel **30000** are repointed so that zero angle rays (rays that are emitted perpendicular to the surface of the image source) become rays with the chief ray angle matched to the sampling of the lens. As shown in FIG. 40, zero angle rays from all of the subpixels are repointed by an optical film **40060** thereby forming rays with progressively greater chief ray angles in correspondence to what the lens **35035** samples to form the image for the user. As shown in FIG. 40, the optical film **40060** is a diffractive lens or a Fresnel lens that progressively refracts the zero angle ray provided by subpixels **30000** and pixels **30005** so that subpixels **30000** and pixels **30005** that are positioned farther from the center of the image source **35030** are refracted more to give them a greater chief ray angle. The optical film **40060** can be attached to the upper surface of the image source **35030** (or attached to a cover glass over the color filter array) to make a compensated image source module or the optical film **40060** can be retained separately. This embodiment provides a further advantage in that the zero angle rays, which are emitted perpendicular to the surface of the subpixel **30000**, include the most intense image light so that the image provided to the user will be brighter.

(148) In alternative embodiments, the optical film **40060** can include microlenses to repoint the zero angle. The microlenses can be provided as a microlens array in an optical film or alternatively the microlenses can be applied directly to a cover glass over the color filter array. Microlenses provide a further advantage in that the cone of light emitted by the subpixel can be condensed to utilize more of the light emitted by the subpixel and thereby improve energy efficiency.

(149) In a further embodiment, the color shift caused by the chief ray angle of the rays sampled by the lens **35035** and the thickness of the transparent layer **30010**, is compensated in the digital image by changing the digital code values presented to the pixels in the digital image. In this case, the layout of the color filter array **30020** is also taken into account so that a digital shift equation is applied to the digital image prior to being displayed on the head-worn display. Where the digital shift equation includes the position of the subpixel relative to the center of the image source, the chief ray angle for rays sampled by the lens at that position, the thickness of the transparent layer as well as the relative position of the color filters adjacent to and surrounding the subpixel. FIG. 41 shows an illustration of an array of subpixels on an image source, where **41080** is the center point of the image source and **41082** is a subpixel in the array of subpixels. The arrow shown shows the distance from the center **41080** to the subpixel **41082**. The digital shift equation thereby determines which pixels will have a color shift caused by the emitted light exiting through an adjacent color filter and then determining how the code values associated with the pixel need to be shifted between subpixels within the digital image to provide a modified digital image that when viewed by the user in the head-worn computer will have the colors intended to be included in the digital image. The distance of the pixel **41082** from the center of the image source **41080** and the lens characteristics (e.g. focal length) determines the chief ray angle for the pixel which along with the thickness of the transparent layer **30010** determines whether the sampled ray from the subpixel **41082** will exit through the intended color filter as shown in FIG. 37 as ray **37045**, or whether the sampled ray will exit through an adjacent color filter as shown by ray **37050**. To compensate for the sampled rays exiting through adjacent color filters, the code values for the pixel in the digital image are shifted in the opposite direction (e.g. toward the center of the image) to an adjacent subpixel. Wherein each code value associated with a pixel determines how brightly each subpixel in the set of subpixels will emit white light, and consequently how bright each color associated with the pixel in the image will be. As such in this method, the relationship between the subpixels and the colors

produced by the subpixels in the displayed image is changed to take into account the effect of the lens and the distribution of ray angles used by the lens to provide the displayed image within the head-worn computer. When shifting the code values to an adjacent subpixel, the adjacent subpixel may be in the same pixel or in an adjacent pixel. Equation 1 is an example of a digital shift equation for a subpixel, wherein: P_s is the number of subpixels that the code value is to be laterally shifted by; d is the distance from the center of the image source to the position of the subpixel; t is the thickness of the transparent layer; f_L is the focal length of the lens; C is a function of the color filter array layout surrounding the subpixel; and $f(a)$ is a function of the angle of the chief ray angle relative to the color filter array layout. Equation 1 is shown as an example of a digital shift equation but other equations are possible.

$$(150) \quad P_s = (dXt / f_L)(CXf(\quad)) \quad \text{Equation 1}$$

(151) For example as shown in FIG. 37, the code values for pixels 1 and 2 will not be shifted because the sampled rays from each subpixel (samples rays are shown as dark lines) exit through their intended color filters as shown by ray **37045** exiting through a red color filter. In contrast, the code values for pixels 4 and 5 will be shifted by one subpixel because the sampled rays exit through the adjacent color filter as shown by ray **37050** which exits through a green color filter. As such the code values for all the subpixels in pixels 4 and 5 will be shifted to the left by one subpixel so that the emitted light will exit through the intended color filter. For cases such as shown by ray **37052** where the sampled ray from a subpixel in pixel 3 exits partially through a red color filter and partially through a green color filter, the code values for the pixel 3 subpixels can be shared between subpixels, for example by averaging the code values between the two subpixels and thereby providing a $\frac{1}{2}$ subpixel shift. Alternatively, code value shifts can be limited to whole subpixels and the code value shift is only applied when the majority of the sampled ray associated with the subpixel will exit through the adjacent color filter.

(152) Looking at the color filter array patterns shown in FIGS. 31, 32 and 33, code value shifts between subpixels will vary depending on the color filter array pattern. For the color filter array pattern shown in FIG. 32, code values shifts between subpixels are only provided to reduce color shifts in the horizontal direction. Since the color filter array includes vertical stripes of the same color, increasing chief ray angle will only cause a color shift in the horizontal direction and not in the vertical direction. However, for the color filter array patterns shown in FIGS. 31 and 33, code shifting between subpixels will be needed in both X and Y directions as the chief ray angle increases toward the corners of the image. For example for the color filter array shown in FIG. 31, for a pixel positioned horizontally from the center of the image source with a chief ray angle that causes the emitted light from a subpixel to go into the adjacent color filter, red code values will need to be shifted left into the subpixel under the blue color filter. Similarly the green code values will need to be shifted left into the subpixel under the red color filter and likewise, the blue code value will need to be shifted left to the subpixel under the green color filter. For a pixel located in the top right corner of the image source code values will need to be shifted to the left and down to make the light rays emitted by the subpixel and sampled by the lens to exit through the intended color filter.

(153) It should be noted that all of the methods described including color filter shifts, ray repointing and digital pixel shifts will produce an image that when viewed from a position directly above the image source such as when viewed by eye, will actually produce an image that has poor color rendition. This is because when viewed in this manner the chief ray angles will all be close to zero degrees. It is only when a lens with a relatively short focal length so that chief rays with substantial chief ray angles are sampled by the lens when viewing the image, that the color rendition will be improved by these methods. As such, the method would not be useful on a television type display or in a display system that uses telecentric image light. The color shift that is the topic of this invention is only important when compact optics are included with a short focal

length lens relative to the size of the image source such as is used to provide a head-worn computer with a wide display field of view with compact optical systems.

(154) Users of smartphones often complain of neck pain caused by the repetitive stress of looking downward at the smartphone while texting, emailing or internet surfing. An illustration of a user **42010** using a smartphone **42015** wherein the user is looking at the smartphone with an extreme downward line of sight **42030** is shown in FIG. **42**. The neck pain condition has been called a variety of descriptive names including “text neck, iPhone neck, smartphone neck, etc (for example see: <http://health.clevelandclinic.org/2015/03/text-neck-is-smartphone-use-causing-your-neck-pain/>). While the issue can be reduced if the user holds the smartphone directly in front, this is typically not comfortable for the user's arms. The problem is that the user is limited to being either having an uncomfortable neck when looking at the smartphone or having uncomfortable arms holding the smartphone. A head-worn computer (HWC) is not limited in these ways because the HWC is mounted on the user's head. In addition the user interface for an HWC can be held separately in the user's hands (e.g. a separate keyboard). As a result a HWC can be used in more ergonomic positions than a smartphone.

(155) The disclosure provides a method of operation of a HWC that promotes an ergonomic positioning of the user's head when viewing images on the HWC. To avoid interfering with augmented reality uses when the user is moving through an environment, the user's activities are monitored to determine the type of activity that the user is engaged in. When the user is determined to be engaged in an activity that includes limited motion where an ergonomic position would be beneficial, the position of the image in the HWC is modified so that the image content is only fully viewable when the user's head is at an ergonomically advantaged position.

(156) Neck pain caused by the prolonged use of a smartphone **42015** is connected with the user looking downwards thereby tilting their head downwards, as shown in FIG. **42**, for extended periods of time. Wherein, the user's line of sight **42030** is approximately 45 degrees below horizontal or greater. In contrast, when using an HWC, the image presented by the HWC can be viewed at any angle the user chooses to position their head. FIG. **43** is an illustration of a user **42010** looking at an image in an HWC **43020**, wherein the user's head is positioned neutrally so the user **42010** looks straight forward or slightly downward when viewing images. FIG. **44** shows the relative position of the user's line of sight **44037** to the center of the virtual image which is preferably approximately 15 degrees below horizontal. The disclosure provides a method of operation that limits viewing of images with full image content to head angles that are ergonomic.

(157) HWCs are used in a variety of use cases including use cases where the user moves about in a surrounding environment, such as by walking or running in which case head position is determined at least in part by the surrounding environment. In this case, neck pain is not as much of an issue and limiting the viewing of images to ergonomic head positions would actually interfere with functional aspects of the use case. Similarly, in certain types of augmented reality use cases such as gaming where the user may not be moving in the environment, but the use case calls for the user to move their head around a lot, neck pain is not as much of an issue and limiting the view of image to ergonomic head angles would interfere with functional aspects of the use case. However, in those use cases where the user keeps their head relatively still while viewing images for extended periods of time such as when watching a movie or while reading email, limiting the viewing of images to head angles that are ergonomic provides a significant advantage in user comfort.

(158) To be able to differentiate between use cases wherein ergonomic head position is an advantage and use cases where an ergonomic head position would interfere with functional aspects of the use case, the HWC needs to be able to identify what the user is doing. In embodiments this determination can be done by a combination of sensors to determine how the user is moving. In embodiments, a marker can also be associated with the use case that identifies the use case to be one that needs the image to be locked in position within the display field of view of the HWC or one that would provide improved user comfort if the viewing was limited to ergonomic head

positions.

(159) Determining what the user is doing relative to whether ergonomic head positioning should be provided or not, involves determining whether the user is moving about in the environment and whether the user is substantially moving their head. The HWC can include various sensors that can be used to determine what the user is doing. The sensors may include an inertial measurement unit (IMU), which can include gyroscopes and accelerometers to measure movement and tilt, a magnetometer to measure compass heading, a global navigation satellite sensor (GNSS or GPS) to measure position on the earth and an altimeter to measure altitude. Polling of the IMU and GPS can be used to determine whether the user is moving about in the environment and at what speed the user is moving. Slow speed (e.g. below 20 miles per hour) as indicated by the GPS along with cyclic up and down measurements from the IMU can be used to determine whether the user is walking or running. Measurements from the GPS and altimeter can be used to determine whether the user is in a vehicle. High speed movement (e.g. above 20 miles per hour) at a low altitude can indicate the user is in a vehicle such as a car. High speed movement wherein the compass heading is largely the same as the GPS movement aside from some periodic differences to the left and right, can indicate that the user is driving a vehicle. High speed movement wherein the compass heading is different from the GPS movement can indicate that the user is a passenger in a vehicle and if the tilt is downward the user can be indicated to be reading. Very high speed (e.g. above 150 miles per hour) movement at a high altitude can indicate that the user is flying in a plane. Rapid head movements back and forth can indicate that the user is looking for something. If the head movements correspond to changes in the displayed image, the user can be determined to be reacting to augmented reality imagery. Thus movement signatures corresponding to combinations of different types of measurement patterns from sensors in the HWC can be used to determine what the user is doing.

(160) In cases where the user is determined to be stationary or to be a passenger in a vehicle or a plane, the HWC can automatically switch to a mode of operation in which the image content is only fully viewable when the HWC is oriented within a range of degrees from horizontal (e.g. -10 to -20 degrees from horizontal) that is considered ergonomically advantaged. Wherein the HWC is preferably setup to follow the ergonomic recommendations for a workspace that includes a computer monitor. In the ergonomic recommendations for computer workstations (for example see <http://www.cbs.state.or.us/osha/pdf/pubs/1863.pdf>) the upper edge of the monitor should be positioned to be horizontally opposite to the user's eye and the middle of the monitor should be viewable with the user's eye at 15 degrees below horizontal. FIG. 44 is an illustration showing a user 42010 with an HWC 43020 positioned to provide a line of sight 44037 to the center of a virtual image 44040 that is approximately 15 degrees below horizontal and the line of sight to the top of the virtual image 44035 is approximately horizontal. FIG. 45 shows an example of a virtual image 44040 as seen by the user 42010 when the user's head is positioned as shown in FIGS. 43 and 44 where the user is presented with a full view of the virtual image 44040 including all the image content.

(161) In contrast, FIG. 46 shows an example in which the user is looking downward at approximately 30 degrees. In this case, the disclosure provides a modified virtual image 47040 comprised of less than half of the image content included in virtual image 44040 and the half of the image content is presented in the upper portion of the modified virtual image 47040 as shown in FIG. 47. In this way the user is encouraged to view images with his head held at an ergonomic angle where the user can view virtual image 44040 that includes all of the image content. Larger display fields of view may increase the difference between the angle of the line of sight to the top of the virtual image and the angle of the line of sight to the center of the virtual image.

(162) In a more general case, a portion of the image content 47045 included in the virtual image 44040 is presented in the modified virtual image 47040 in correspondence to the deviation between a target ergonomic angle for the line of sight to the center of the image 44037 and the actual angle

for the line of sight to the center of the image. The larger the deviation, the smaller the portion of the image content **47045** that is presented within the modified virtual image **47040**. By moving the portion of the image content **47045** upwards in the modified virtual image **47040** as the user moves his head downwards, the image content appears to be locked in place vertically relative to the environment. At the same time, in the method of the disclosure the image content does not move laterally within the modified virtual image **47040** if the user moves his head laterally, because this type of movement does not affect ergonomics when using an HWC **42010**. As such the method provided by the disclosure differs from world locking of a virtual image to objects in the environment, because world locking typically includes locking of the virtual image both vertically and laterally relative to objects in the surrounding environment in response to movements of the user's head. Since the user of an HWC **42010** can choose the positioning of his head laterally, he will tend to choose a comfortable and ergonomic lateral position for his head, which is approximately looking straight ahead. This also allows the user of a HWC **42010** that provides a see-through view of the surrounding environment to freely move his head laterally in response to changes in the surrounding environment while being encouraged to hold his head in an ergonomic position vertically.

(163) In embodiments the target angle for the line of sight **44037** to the center of the virtual image **44040** is in the range of 10 to 20 degrees below horizontal. In addition, the virtual image **44040** is presented by the HWC **43020** so that the line of sight **44037** is perpendicular to the line of sight **44037** so that the angle of the line of sight to the top and bottom of the virtual image **44040** is substantially the same thereby making it easier for the user **42010** to view the entire image. This is different from a computer workstation wherein the display is typically oriented vertically to reduce the space required by the workstation. Instead the HWC **43020** provides a virtual image **44040** that is presented more like a laptop wherein the display is tilted to orient the display perpendicular to the user's line of sight.

(164) The angle of the line of sight **44037** to the center of the virtual image can be determined from the geometry of the optics of the HWC **42010** (how the virtual image is presented relative to the frame of the HWC **42010**) and a measurement of the angle of the HWC **42010** provided by the tilt of the IMU. The modified virtual image **47040** can be constructed by cropping the image content and shifting the cropped digital image content **47045** vertically within the image content of the modified virtual image **47040**, and then adding solid digital image content **47047** in the modified virtual image **47040** to form the modified virtual image **47040**. The solid digital content **47045** is comprised of a solid color such as for example black or white as best matches the current use case of the HWC **42010**. Typically, for an HWC **42010** that provides a see-through view of the surrounding environment, the solid digital image content **47047** would be black as shown in FIG. **47** to provide the user with a clear view of the surrounding environment through the portion of the modified virtual image **47040** that constitutes the solid digital content **47047**. Where the black portions of the modified virtual image **47040** provide no light to the user's eye and as such, the user sees a clear see-through view of the surrounding environment.

(165) In embodiments, if the HWC **42010** is determined to be at an extreme angle relative to horizontal (e.g greater than 30 degrees from horizontal) as measured by the IMU in either a vertical or sideways angle the user is determined to be lying down. If the user is lying down, the user's head is typically supported by a pillow or other padding so that head position doesn't change strain the neck muscles and neck pain is not an issue. Consequently, the virtual image **44040** are presented with full image content (no cropping or moving) to the user.

(166) In embodiments, a camera is included in the HWC **43020** that can capture an image of a portion of the user's body, such as the user's chest, to determine the angle of the HWC **43020** relative to the user's body. The method of presenting the virtual image to encourage an ergonomic position of the user's head while viewing images for an extended period of time is then changed to be in correspondence to the measured angle of the HWC **43020** relative to the user's body. This

embodiment can provide a more accurate measure of the angle of the user's head position relative to the user's body in cases when the user's body is angled such as when the user is sitting in a chair and leaning back or when the user is leaning forward or backward.

(167) While many of the embodiments herein describe see-through computer displays, the scope of the disclosure is not limited to see-through computer displays. In embodiments, the head-worn computer may have a display that is not see-through. For example, the head-worn computer may have a sensor system (e.g. camera, ultrasonic system, radar, etc.) that images the environment proximate the head-worn computer and then presents the images to the user such that the user can understand the local environment through the images as opposed to seeing the environment directly. In embodiments, the local environment images may be augmented with additional information and content such that an augmented image of the environment is presented to the user. In general, in this disclosure, such see-through and non-see through systems may be referred to as head-worn augmented reality systems, augmented reality displays, augmented reality computer displays, etc.

(168) Although embodiments of HWC have been described in language specific to features, systems, computer processes and/or methods, the appended claims are not necessarily limited to the specific features, systems, computer processes and/or methods described. Rather, the specific features, systems, computer processes and/or methods are disclosed as non-limited example implementations of HWC. All documents referenced herein are hereby incorporated by reference.

(169) The methods and systems described herein may be deployed in part or in whole through a machine that executes computer software, program codes, and/or instructions on a processor. The processor may be part of a server, cloud server, client, network infrastructure, mobile computing platform, stationary computing platform, or other computing platform. A processor may be any kind of computational or processing device capable of executing program instructions, codes, binary instructions and the like. The processor may be or include a signal processor, digital processor, embedded processor, microprocessor or any variant such as a co-processor (math co-processor, graphic co-processor, communication co-processor and the like) and the like that may directly or indirectly facilitate execution of program code or program instructions stored thereon. In addition, the processor may enable execution of multiple programs, threads, and codes. The threads may be executed simultaneously to enhance the performance of the processor and to facilitate simultaneous operations of the application. By way of implementation, methods, program codes, program instructions and the like described herein may be implemented in one or more thread. The thread may spawn other threads that may have assigned priorities associated with them; the processor may execute these threads based on priority or any other order based on instructions provided in the program code. The processor may include memory that stores methods, codes, instructions and programs as described herein and elsewhere. The processor may access a storage medium through an interface that may store methods, codes, and instructions as described herein and elsewhere. The storage medium associated with the processor for storing methods, programs, codes, program instructions or other type of instructions capable of being executed by the computing or processing device may include but may not be limited to one or more of a CD-ROM, DVD, memory, hard disk, flash drive, RAM, ROM, cache and the like.

(170) A processor may include one or more cores that may enhance speed and performance of a multiprocessor. In embodiments, the process may be a dual core processor, quad core processors, other chip-level multiprocessor and the like that combine two or more independent cores (called a die).

(171) The methods and systems described herein may be deployed in part or in whole through a machine that executes computer software on a server, client, firewall, gateway, hub, router, or other such computer and/or networking hardware. The software program may be associated with a server that may include a file server, print server, domain server, internet server, intranet server and other variants such as secondary server, host server, distributed server and the like. The server may

include one or more of memories, processors, computer readable transitory and/or non-transitory media, storage media, ports (physical and virtual), communication devices, and interfaces capable of accessing other servers, clients, machines, and devices through a wired or a wireless medium, and the like. The methods, programs or codes as described herein and elsewhere may be executed by the server. In addition, other devices required for execution of methods as described in this application may be considered as a part of the infrastructure associated with the server.

(172) The server may provide an interface to other devices including, without limitation, clients, other servers, printers, database servers, print servers, file servers, communication servers, distributed servers and the like. Additionally, this coupling and/or connection may facilitate remote execution of program across the network. The networking of some or all of these devices may facilitate parallel processing of a program or method at one or more location without deviating from the scope of the invention. In addition, all the devices attached to the server through an interface may include at least one storage medium capable of storing methods, programs, code and/or instructions. A central repository may provide program instructions to be executed on different devices. In this implementation, the remote repository may act as a storage medium for program code, instructions, and programs.

(173) The software program may be associated with a client that may include a file client, print client, domain client, internet client, intranet client and other variants such as secondary client, host client, distributed client and the like. The client may include one or more of memories, processors, computer readable transitory and/or non-transitory media, storage media, ports (physical and virtual), communication devices, and interfaces capable of accessing other clients, servers, machines, and devices through a wired or a wireless medium, and the like. The methods, programs or codes as described herein and elsewhere may be executed by the client. In addition, other devices required for execution of methods as described in this application may be considered as a part of the infrastructure associated with the client.

(174) The client may provide an interface to other devices including, without limitation, servers, other clients, printers, database servers, print servers, file servers, communication servers, distributed servers and the like. Additionally, this coupling and/or connection may facilitate remote execution of program across the network. The networking of some or all of these devices may facilitate parallel processing of a program or method at one or more location without deviating from the scope of the invention. In addition, all the devices attached to the client through an interface may include at least one storage medium capable of storing methods, programs, applications, code and/or instructions. A central repository may provide program instructions to be executed on different devices. In this implementation, the remote repository may act as a storage medium for program code, instructions, and programs.

(175) The methods and systems described herein may be deployed in part or in whole through network infrastructures. The network infrastructure may include elements such as computing devices, servers, routers, hubs, firewalls, clients, personal computers, communication devices, routing devices and other active and passive devices, modules and/or components as known in the art. The computing and/or non-computing device(s) associated with the network infrastructure may include, apart from other components, a storage medium such as flash memory, buffer, stack, RAM, ROM and the like. The processes, methods, program codes, instructions described herein and elsewhere may be executed by one or more of the network infrastructural elements.

(176) The methods, program codes, and instructions described herein and elsewhere may be implemented on a cellular network having multiple cells. The cellular network may either be frequency division multiple access (FDMA) network or code division multiple access (CDMA) network. The cellular network may include mobile devices, cell sites, base stations, repeaters, antennas, towers, and the like.

(177) The methods, programs codes, and instructions described herein and elsewhere may be implemented on or through mobile devices. The mobile devices may include navigation devices,

cell phones, mobile phones, mobile personal digital assistants, laptops, palmtops, netbooks, pagers, electronic books readers, music players and the like. These devices may include, apart from other components, a storage medium such as a flash memory, buffer, RAM, ROM and one or more computing devices. The computing devices associated with mobile devices may be enabled to execute program codes, methods, and instructions stored thereon. Alternatively, the mobile devices may be configured to execute instructions in collaboration with other devices. The mobile devices may communicate with base stations interfaced with servers and configured to execute program codes. The mobile devices may communicate on a peer to peer network, mesh network, or other communications network. The program code may be stored on the storage medium associated with the server and executed by a computing device embedded within the server. The base station may include a computing device and a storage medium. The storage device may store program codes and instructions executed by the computing devices associated with the base station.

(178) The computer software, program codes, and/or instructions may be stored and/or accessed on machine readable transitory and/or non-transitory media that may include: computer components, devices, and recording media that retain digital data used for computing for some interval of time; semiconductor storage known as random access memory (RAM); mass storage typically for more permanent storage, such as optical discs, forms of magnetic storage like hard disks, tapes, drums, cards and other types; processor registers, cache memory, volatile memory, non-volatile memory; optical storage such as CD, DVD; removable media such as flash memory (e.g. USB sticks or keys), floppy disks, magnetic tape, paper tape, punch cards, standalone RAM disks, Zip drives, removable mass storage, off-line, and the like; other computer memory such as dynamic memory, static memory, read/write storage, mutable storage, read only, random access, sequential access, location addressable, file addressable, content addressable, network attached storage, storage area network, bar codes, magnetic ink, and the like.

(179) The methods and systems described herein may transform physical and/or or intangible items from one state to another. The methods and systems described herein may also transform data representing physical and/or intangible items from one state to another, such as from usage data to a normalized usage dataset.

(180) The elements described and depicted herein, including in flow charts and block diagrams throughout the figures, imply logical boundaries between the elements. However, according to software or hardware engineering practices, the depicted elements and the functions thereof may be implemented on machines through computer executable transitory and/or non-transitory media having a processor capable of executing program instructions stored thereon as a monolithic software structure, as standalone software modules, or as modules that employ external routines, code, services, and so forth, or any combination of these, and all such implementations may be within the scope of the present disclosure. Examples of such machines may include, but may not be limited to, personal digital assistants, laptops, personal computers, mobile phones, other handheld computing devices, medical equipment, wired or wireless communication devices, transducers, chips, calculators, satellites, tablet PCs, electronic books, gadgets, electronic devices, devices having artificial intelligence, computing devices, networking equipment, servers, routers and the like. Furthermore, the elements depicted in the flow chart and block diagrams or any other logical component may be implemented on a machine capable of executing program instructions. Thus, while the foregoing drawings and descriptions set forth functional aspects of the disclosed systems, no particular arrangement of software for implementing these functional aspects should be inferred from these descriptions unless explicitly stated or otherwise clear from the context. Similarly, it will be appreciated that the various steps identified and described above may be varied, and that the order of steps may be adapted to particular applications of the techniques disclosed herein. All such variations and modifications are intended to fall within the scope of this disclosure. As such, the depiction and/or description of an order for various steps should not be understood to require a particular order of execution for those steps, unless required by a particular application, or

explicitly stated or otherwise clear from the context.

(181) The methods and/or processes described above, and steps thereof, may be realized in hardware, software or any combination of hardware and software suitable for a particular application. The hardware may include a dedicated computing device or specific computing device or particular aspect or component of a specific computing device. The processes may be realized in one or more microprocessors, microcontrollers, embedded microcontrollers, programmable digital signal processors or other programmable device, along with internal and/or external memory. The processes may also, or instead, be embodied in an application specific integrated circuit, a programmable gate array, programmable array logic, or any other device or combination of devices that may be configured to process electronic signals. It will further be appreciated that one or more of the processes may be realized as a computer executable code capable of being executed on a machine readable medium.

(182) The computer executable code may be created using a structured programming language such as C, an object oriented programming language such as C++, or any other high-level or low-level programming language (including assembly languages, hardware description languages, and database programming languages and technologies) that may be stored, compiled or interpreted to run on one of the above devices, as well as heterogeneous combinations of processors, processor architectures, or combinations of different hardware and software, or any other machine capable of executing program instructions.

(183) Thus, in one aspect, each method described above and combinations thereof may be embodied in computer executable code that, when executing on one or more computing devices, performs the steps thereof. In another aspect, the methods may be embodied in systems that perform the steps thereof, and may be distributed across devices in a number of ways, or all of the functionality may be integrated into a dedicated, standalone device or other hardware. In another aspect, the means for performing the steps associated with the processes described above may include any of the hardware and/or software described above. All such permutations and combinations are intended to fall within the scope of the present disclosure.

(184) While the invention has been disclosed in connection with the preferred embodiments shown and described in detail, various modifications and improvements thereon will become readily apparent to those skilled in the art. Accordingly, the spirit and scope of the present invention is not to be limited by the foregoing examples, but is to be understood in the broadest sense allowable by law.

Claims

1. A method of presenting content to a user of a wearable head device, the method comprising: receiving initial content for presentation via a display of the wearable head device; determining, via one or more sensors of the wearable head device, a viewing axis of the user; determining whether an angle between the viewing axis and a horizontal axis is between a first predetermined angle and a second predetermined angle; in accordance with a determination that the angle is not between the first predetermined angle and the second predetermined angle: cropping the initial content to produce cropped initial content, wherein the cropped initial content comprises a portion of the initial content; and presenting, via the display, the cropped initial content; and in accordance with a determination that the angle between the viewing axis and the horizontal axis is between the first predetermined angle and the second predetermined angle, presenting, via the display, the initial content.
2. The method of claim 1, wherein the cropped initial content comprises a portion of the initial content between the viewing axis and the horizontal axis.
3. The method of claim 1, wherein said presenting the cropped initial content comprises shifting the cropped initial content toward a point between the viewing axis and the horizontal axis.

4. The method of claim 3, wherein a magnitude of said shifting is based on a difference between the determined viewing axis and a desired viewing axis.
5. The method of claim 3, wherein said shifting the cropped initial content comprises aligning a top of the cropped initial content with the horizontal axis.
6. The method of claim 1, wherein said presenting the cropped initial content comprises presenting the cropped initial content along a plane orthogonal to the viewing axis.
7. The method of claim 1, wherein a vertical position of the presented cropped initial content is locked relative to an environment of the user.
8. The method of claim 7, wherein a horizontal position of the presented cropped initial content is nonresponsive to lateral motion of the user.
9. The method of claim 1, wherein: the first predetermined angle is 10 degrees below the horizontal axis, and the second predetermined angle is 20 degrees below the horizontal axis.
10. The method of claim 1, wherein the first predetermined angle and the second predetermined angle are determined based on a plane of the initial content.
11. The method of claim 1, wherein said determining the viewing axis comprises: receiving, via the one or more sensors, an image of an eye of the user; and determining the viewing axis based on the image.
12. The method of claim 1, wherein said determining the viewing axis comprises determining an orientation of the wearable head device relative to the user, and wherein the viewing axis is determined based on the orientation.
13. The method of claim 1, wherein the one or more sensors comprises an inertial measurement unit (IMU), an accelerometer, a tilt sensor, a GPS unit, an altimeter, a magnetometer, or any combination thereof.
14. A wearable head device comprising: a display; one or more sensors; one or more processors configured to perform: receiving initial content for presentation via the display; determining, via the one or more sensors, a viewing axis of the user; determining whether an angle between the viewing axis and a horizontal axis is between a first predetermined angle and a second predetermined angle; in accordance with a determination that the angle is not between the first predetermined angle and the second predetermined angle: cropping the initial content to produce cropped initial content, wherein the cropped initial content comprises a portion of the initial content; and presenting, via the display, the cropped initial content; and in accordance with a determination that the angle between the viewing axis and the horizontal axis is between the first predetermined angle and the second predetermined angle, presenting, via the display, the initial content.
15. The wearable head device of claim 14, wherein the cropped initial content comprises a portion of the initial content between the viewing axis and the horizontal axis.
16. The wearable head device of claim 14, wherein said presenting the cropped initial content comprises shifting the cropped initial content toward a point between the viewing axis and the horizontal axis.
17. The wearable head device of claim 14, wherein a vertical position of the presented cropped initial content is locked relative to an environment of the user.
18. The wearable head device of claim 17, wherein a horizontal position of the presented cropped initial content is nonresponsive to lateral motion of the user.
19. The wearable head device of claim 14, wherein the one or more sensors comprises an IMU, an accelerometer, a tilt sensor, a GPS unit, an altimeter, a magnetometer, or any combination thereof.
20. A non-transitory computer readable storage medium storing instructions that, when executed, cause one or more processors to perform a method comprising: receiving initial content for presentation via a display of a wearable head device; determining, via one or more sensors of the wearable head device, a viewing axis of the user; determining whether an angle between the viewing axis and a horizontal axis is between a first predetermined angle and a second

predetermined angle; in accordance with a determination that the angle is not between the first predetermined angle and the second predetermined angle: cropping the initial content to produce cropped initial content, wherein the cropped initial content comprises a portion of the initial content; and presenting, via the display, the cropped initial content; and in accordance with a determination that the angle between the viewing axis and the horizontal axis is between the first predetermined angle and the second predetermined angle, presenting, via the display, the initial content.
