

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405581
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Sridharan; Ashok et al.

Building automation system with integrated building information model

Abstract

A building automation system (BAS) includes building equipment located within a building and a BAS network configured to facilitate communications between the building equipment. The building equipment operate to affect a variable state or condition within the building. The BAS includes a BAS-BIM integrator configured to receive BAS points from the BAS network and to integrate the BAS points with a building information model (BIM). The BIM includes a plurality of BIM objects representing the building equipment. The BAS includes an integrated BAS-BIM viewer configured to use the BIM with the integrated BAS points to generate a user interface. The user interface includes a graphical representation of the BIM objects and the BAS points integrated therewith.

Inventors: Sridharan; Ashok (Tiruchirappalli, IN), Patil; Jayesh (Borivali West Mumbai, IN), Bhattacharya; Subrata (Singapore, SG), Chatterjee; Abhigyan (Asansol, IN)

Applicant: Johnson Controls Technology Company (Auburn Hills, MI)

Family ID: 58558499

Assignee: JOHNSON CONTROLS TECHNOLOGY COMPANY (Auburn Hills, MI)

Appl. No.: 17/832234

Filed: June 03, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220291644 A1	Sep. 15, 2022

Related U.S. Application Data

continuation parent-doc US 16694859 20191125 US 11353831 child-doc US 17832234
continuation parent-doc US 14919516 20151021 US 10534326 20200114 child-doc US 16694859

Publication Classification

Int. Cl.: G06F3/048 (20130101); G05B13/04 (20060101); G05B15/02 (20060101)

U.S. Cl.:

CPC G05B13/04 (20130101); G05B15/02 (20130101); G05B2219/25011 (20130101); G05B2219/2642 (20130101)

Field of Classification Search

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5301109	12/1993	Landauer et al.	N/A	N/A
5446677	12/1994	Jensen et al.	N/A	N/A
5581478	12/1995	Cruse et al.	N/A	N/A
5812962	12/1997	Kovac	N/A	N/A
5960381	12/1998	Singers et al.	N/A	N/A
5973662	12/1998	Singers et al.	N/A	N/A
6014612	12/1999	Larson et al.	N/A	N/A
6031547	12/1999	Kennedy	N/A	N/A
6134511	12/1999	Subbarao	N/A	N/A
6157943	12/1999	Meyer	N/A	N/A
6285966	12/2000	Brown et al.	N/A	N/A
6363422	12/2001	Hunter et al.	N/A	N/A
6385510	12/2001	Hoog et al.	N/A	N/A
6389331	12/2001	Jensen et al.	N/A	N/A
6401027	12/2001	Xu et al.	N/A	N/A
6437691	12/2001	Sandelman et al.	N/A	N/A
6477518	12/2001	Li et al.	N/A	N/A
6487457	12/2001	Hull et al.	N/A	N/A
6493755	12/2001	Hansen et al.	N/A	N/A
6577323	12/2002	Jamieson et al.	N/A	N/A
6626366	12/2002	Kayahara et al.	N/A	N/A
6646660	12/2002	Patty	N/A	N/A
6704016	12/2003	Oliver et al.	N/A	N/A
6732540	12/2003	Sugihara et al.	N/A	N/A
6764019	12/2003	Kayahara et al.	N/A	N/A
6782385	12/2003	Natsumeda et al.	N/A	N/A
6813532	12/2003	Eryurek et al.	N/A	N/A
6816811	12/2003	Seem	N/A	N/A
6823680	12/2003	Jayanth	N/A	N/A
6826454	12/2003	Sulfstede	N/A	N/A
6865511	12/2004	Frerichs et al.	N/A	N/A
6925338	12/2004	Eryurek et al.	N/A	N/A
6986138	12/2005	Sakaguchi et al.	N/A	N/A
7031880	12/2005	Seem et al.	N/A	N/A
7401057	12/2007	Eder	N/A	N/A
7552467	12/2008	Lindsay	N/A	N/A
7627544	12/2008	Chkodrov et al.	N/A	N/A
7818249	12/2009	Lovejoy et al.	N/A	N/A
7889051	12/2010	Billig et al.	N/A	N/A
7996488	12/2010	Casabella et al.	N/A	N/A
8078330	12/2010	Brickfield et al.	N/A	N/A
8104044	12/2011	Scofield et al.	N/A	N/A
8229470	12/2011	Ranjan et al.	N/A	N/A
8401991	12/2012	Wu et al.	N/A	N/A
8434027	12/2012	Jones	N/A	N/A
8495745	12/2012	Schrecker et al.	N/A	N/A
8516016	12/2012	Park et al.	N/A	N/A
8532808	12/2012	Drees et al.	N/A	N/A
8532839	12/2012	Drees et al.	N/A	N/A
8595652	12/2012	Retlich	N/A	N/A
8600556	12/2012	Nesler et al.	N/A	N/A
8635182	12/2013	Mackay	N/A	N/A

8682921	12/2013	Park et al.	N/A	N/A
8731724	12/2013	Drees et al.	N/A	N/A
8737334	12/2013	Ahn et al.	N/A	N/A
8738334	12/2013	Jiang et al.	N/A	N/A
8751487	12/2013	Byrne et al.	N/A	N/A
8788097	12/2013	Drees et al.	N/A	N/A
8805995	12/2013	Oliver	N/A	N/A
8843238	12/2013	Wenzel et al.	N/A	N/A
8874071	12/2013	Sherman et al.	N/A	N/A
8941465	12/2014	Pineau et al.	N/A	N/A
8990127	12/2014	Taylor	N/A	N/A
9070113	12/2014	Shafiee et al.	N/A	N/A
9116978	12/2014	Park et al.	N/A	N/A
9185095	12/2014	Moritz et al.	N/A	N/A
9189527	12/2014	Park et al.	N/A	N/A
9196009	12/2014	Drees et al.	N/A	N/A
9229966	12/2015	Aymeloglu et al.	N/A	N/A
9274684	12/2015	Han et al.	N/A	N/A
9286582	12/2015	Drees et al.	N/A	N/A
9311807	12/2015	Schultz et al.	N/A	N/A
9344751	12/2015	Ream et al.	N/A	N/A
9354968	12/2015	Wenzel et al.	N/A	N/A
9447985	12/2015	Johnson	N/A	N/A
9507686	12/2015	Horn et al.	N/A	N/A
9524594	12/2015	Ouyang et al.	N/A	N/A
9558196	12/2016	Johnston et al.	N/A	N/A
9652813	12/2016	Gifford et al.	N/A	N/A
9753455	12/2016	Drees	N/A	N/A
9811249	12/2016	Chen et al.	N/A	N/A
9838844	12/2016	Emeis et al.	N/A	N/A
9846531	12/2016	McFarland	N/A	G06F 3/0482
9886478	12/2017	Mukherjee	N/A	N/A
9948359	12/2017	Horton	N/A	N/A
10055114	12/2017	Shah et al.	N/A	N/A
10055206	12/2017	Park et al.	N/A	N/A
10116461	12/2017	Fairweather et al.	N/A	N/A
10169454	12/2018	Ait-Mokhtar et al.	N/A	N/A
10171297	12/2018	Stewart et al.	N/A	N/A
10171586	12/2018	Shaashua et al.	N/A	N/A
10187258	12/2018	Nagesh et al.	N/A	N/A
10514963	12/2018	Shrivastava et al.	N/A	N/A
10515098	12/2018	Park et al.	N/A	N/A
10534326	12/2019	Sridharan et al.	N/A	N/A
10536295	12/2019	Fairweather et al.	N/A	N/A
10564993	12/2019	Deutsch et al.	N/A	N/A
10705492	12/2019	Harvey	N/A	N/A
10708078	12/2019	Harvey	N/A	N/A
10732804	12/2019	Ericsson et al.	N/A	N/A
10760815	12/2019	Janakiraman et al.	N/A	N/A
10762475	12/2019	Song et al.	N/A	N/A
10824120	12/2019	Ahmed	N/A	N/A
10845771	12/2019	Harvey	N/A	N/A
10854194	12/2019	Park et al.	N/A	N/A
10862928	12/2019	Badawy et al.	N/A	N/A
10871756	12/2019	Johnson et al.	N/A	N/A
10908578	12/2020	Johnson et al.	N/A	N/A
10921760	12/2020	Harvey	N/A	N/A
10921768	12/2020	Johnson et al.	N/A	N/A
10921972	12/2020	Park et al.	N/A	N/A

10969133	12/2020	Harvey	N/A	N/A
10986121	12/2020	Stockdale et al.	N/A	N/A
11016998	12/2020	Park et al.	N/A	N/A
11024292	12/2020	Park et al.	N/A	N/A
11038709	12/2020	Park et al.	N/A	N/A
11041650	12/2020	Li et al.	N/A	N/A
11054796	12/2020	Holaso	N/A	N/A
11070390	12/2020	Park et al.	N/A	N/A
11073976	12/2020	Park et al.	N/A	N/A
11108587	12/2020	Park et al.	N/A	N/A
11113295	12/2020	Park et al.	N/A	N/A
11156978	12/2020	Johnson et al.	N/A	N/A
11229138	12/2021	Harvey et al.	N/A	N/A
11314726	12/2021	Park et al.	N/A	N/A
11314788	12/2021	Park et al.	N/A	N/A
11353831	12/2021	Sridharan et al.	N/A	N/A
11556105	12/2022	Cooley et al.	N/A	N/A
11561522	12/2022	Cooley et al.	N/A	N/A
11561523	12/2022	Cooley et al.	N/A	N/A
11573551	12/2022	Cooley et al.	N/A	N/A
11586167	12/2022	Cooley et al.	N/A	N/A
2002/0010562	12/2001	Schleiss et al.	N/A	N/A
2002/0016639	12/2001	Smith et al.	N/A	N/A
2002/0059229	12/2001	Natsumeda et al.	N/A	N/A
2002/0123864	12/2001	Eryurek et al.	N/A	N/A
2002/0147506	12/2001	Eryurek et al.	N/A	N/A
2002/0177909	12/2001	Fu et al.	N/A	N/A
2003/0005486	12/2002	Ridolfo et al.	N/A	N/A
2003/0014130	12/2002	Grumelart	N/A	N/A
2003/0073432	12/2002	Meade, II	N/A	N/A
2003/0158704	12/2002	Triginai et al.	N/A	N/A
2003/0171851	12/2002	Brickfield et al.	N/A	N/A
2003/0200059	12/2002	Ignatowski et al.	N/A	N/A
2004/0068390	12/2003	Saunders	N/A	N/A
2004/0128314	12/2003	Katibah et al.	N/A	N/A
2004/0133314	12/2003	Ehlers et al.	N/A	N/A
2004/0199360	12/2003	Friman et al.	N/A	N/A
2005/0055308	12/2004	Meyer et al.	N/A	N/A
2005/0108262	12/2004	Fawcett et al.	N/A	N/A
2005/0154494	12/2004	Ahmed	N/A	N/A
2005/0278703	12/2004	Lo et al.	N/A	N/A
2005/0283337	12/2004	Sayal	N/A	N/A
2006/0010388	12/2005	Imhof et al.	N/A	N/A
2006/0095521	12/2005	Patinkin	N/A	N/A
2006/0140207	12/2005	Eschbach et al.	N/A	N/A
2006/0184479	12/2005	Levine	N/A	N/A
2006/0200476	12/2005	Gottumukkala et al.	N/A	N/A
2006/0265751	12/2005	Cosquer et al.	N/A	N/A
2006/0271589	12/2005	Horowitz et al.	N/A	N/A
2007/0028179	12/2006	Levin et al.	N/A	N/A
2007/0129645	12/2006	Hartley et al.	N/A	N/A
2007/0203693	12/2006	Estes	N/A	N/A
2007/0219645	12/2006	Thomas et al.	N/A	N/A
2007/0261062	12/2006	Bansal et al.	N/A	N/A
2007/0273497	12/2006	Kuroda et al.	N/A	N/A
2007/0273610	12/2006	Baillot	N/A	N/A
2008/0034425	12/2007	Overcash et al.	N/A	N/A
2008/0094230	12/2007	Mock et al.	N/A	N/A
2008/0097816	12/2007	Freire et al.	N/A	N/A

2008/0186160	12/2007	Kim et al.	N/A	N/A
2008/0249756	12/2007	Chaisuparasmikul	N/A	N/A
2008/0252723	12/2007	Park	N/A	N/A
2008/0281472	12/2007	Podgorny et al.	N/A	N/A
2009/0057425	12/2008	Sullivan	715/764	F24F 11/63
2009/0112532	12/2008	Foslien et al.	N/A	N/A
2009/0195349	12/2008	Frader-Thompson et al.	N/A	N/A
2010/0045439	12/2009	Tak et al.	N/A	N/A
2010/0058248	12/2009	Park	N/A	N/A
2010/0107070	12/2009	Devineni et al.	N/A	N/A
2010/0131533	12/2009	Ortiz	N/A	N/A
2010/0274366	12/2009	Fata et al.	N/A	N/A
2010/0281387	12/2009	Holland et al.	N/A	N/A
2010/0286937	12/2009	Hedley et al.	N/A	N/A
2010/0324962	12/2009	Nesler et al.	N/A	N/A
2011/0015802	12/2010	Imes	N/A	N/A
2011/0047418	12/2010	Drees et al.	N/A	N/A
2011/0061015	12/2010	Drees et al.	N/A	N/A
2011/0071685	12/2010	Huneycutt et al.	N/A	N/A
2011/0077950	12/2010	Hughston	N/A	N/A
2011/0087650	12/2010	Mackay et al.	N/A	N/A
2011/0087988	12/2010	Ray et al.	N/A	N/A
2011/0088000	12/2010	Mackay	N/A	N/A
2011/0125737	12/2010	Pothering et al.	N/A	N/A
2011/0137853	12/2010	Mackay	N/A	N/A
2011/0153603	12/2010	Adiba et al.	N/A	N/A
2011/0154363	12/2010	Karmarkar	N/A	N/A
2011/0157357	12/2010	Weisensale et al.	N/A	N/A
2011/0178977	12/2010	Drees	N/A	N/A
2011/0191343	12/2010	Heaton et al.	N/A	N/A
2011/0205022	12/2010	Cavallaro et al.	N/A	N/A
2011/0218777	12/2010	Chen et al.	N/A	N/A
2012/0011126	12/2011	Park et al.	N/A	N/A
2012/0011141	12/2011	Park et al.	N/A	N/A
2012/0022698	12/2011	Mackay	N/A	N/A
2012/0062577	12/2011	Nixon	N/A	N/A
2012/0064923	12/2011	Imes et al.	N/A	N/A
2012/0083930	12/2011	Ilic et al.	N/A	N/A
2012/0100825	12/2011	Sherman et al.	N/A	N/A
2012/0101637	12/2011	Imes et al.	N/A	N/A
2012/0135759	12/2011	Imes et al.	N/A	N/A
2012/0136485	12/2011	Weber et al.	N/A	N/A
2012/0158633	12/2011	Eder	N/A	N/A
2012/0259583	12/2011	Noboa et al.	N/A	N/A
2012/0272228	12/2011	Marndi et al.	N/A	N/A
2012/0278051	12/2011	Jiang et al.	N/A	N/A
2012/0310602	12/2011	Jacobi	703/1	G06F 30/13
2013/0007063	12/2012	Kalra et al.	N/A	N/A
2013/0038430	12/2012	Blower et al.	N/A	N/A
2013/0038707	12/2012	Cunningham et al.	N/A	N/A
2013/0060820	12/2012	Bulusu et al.	N/A	N/A
2013/0083012	12/2012	Han et al.	N/A	N/A
2013/0083035	12/2012	Han et al.	N/A	N/A
2013/0086497	12/2012	Ambuhl et al.	N/A	N/A
2013/0097706	12/2012	Titonis et al.	N/A	N/A
2013/0103221	12/2012	Raman et al.	N/A	N/A
2013/0167035	12/2012	Imes et al.	N/A	N/A
2013/0170710	12/2012	Kuoch et al.	N/A	N/A
2013/0204836	12/2012	Choi et al.	N/A	N/A

2013/0246916	12/2012	Reimann et al.	N/A	N/A
2013/0247205	12/2012	Schrecker et al.	N/A	N/A
2013/0262035	12/2012	Mills	N/A	N/A
2013/0275174	12/2012	Bennett et al.	N/A	N/A
2013/0275908	12/2012	Reichard	N/A	N/A
2013/0297050	12/2012	Reichard et al.	N/A	N/A
2013/0298244	12/2012	Kumar et al.	N/A	N/A
2013/0331995	12/2012	Rosen	N/A	N/A
2013/0338970	12/2012	Reggetti	N/A	N/A
2014/0032506	12/2013	Hoey et al.	N/A	N/A
2014/0059483	12/2013	Mairs et al.	N/A	N/A
2014/0081652	12/2013	Klindworth	N/A	N/A
2014/0089209	12/2013	Akcamete	705/305	G06Q 10/20
2014/0135952	12/2013	Maehara	N/A	N/A
2014/0152651	12/2013	Chen	345/419	G06T 19/003
2014/0172184	12/2013	Schmidt et al.	N/A	N/A
2014/0189861	12/2013	Gupta et al.	N/A	N/A
2014/0207282	12/2013	Angle et al.	N/A	N/A
2014/0236373	12/2013	Lee	N/A	N/A
2014/0258052	12/2013	Khuti et al.	N/A	N/A
2014/0269614	12/2013	Maguire et al.	N/A	N/A
2014/0277765	12/2013	Karimi et al.	N/A	N/A
2014/0278461	12/2013	Artz	N/A	N/A
2014/0325414	12/2013	Park	715/769	G05B 15/02
2014/0327555	12/2013	Sager et al.	N/A	N/A
2015/0019174	12/2014	Kiff et al.	N/A	N/A
2015/0042240	12/2014	Aggarwal et al.	N/A	N/A
2015/0081367	12/2014	Westlake	N/A	N/A
2015/0088916	12/2014	Stokoe et al.	N/A	N/A
2015/0105917	12/2014	Sasaki et al.	N/A	N/A
2015/0113462	12/2014	Chen et al.	N/A	N/A
2015/0145468	12/2014	Ma et al.	N/A	N/A
2015/0156031	12/2014	Fadell et al.	N/A	N/A
2015/0168931	12/2014	Jin	N/A	N/A
2015/0172300	12/2014	Cochenour	N/A	N/A
2015/0178421	12/2014	Borrelli et al.	N/A	N/A
2015/0185261	12/2014	Frader-Thompson et al.	N/A	N/A
2015/0186777	12/2014	Lecue et al.	N/A	N/A
2015/0202962	12/2014	Habashima et al.	N/A	N/A
2015/0204563	12/2014	Imes et al.	N/A	N/A
2015/0235267	12/2014	Steube et al.	N/A	N/A
2015/0241895	12/2014	Lu et al.	N/A	N/A
2015/0244730	12/2014	Vu et al.	N/A	N/A
2015/0244732	12/2014	Golshan et al.	N/A	N/A
2015/0261863	12/2014	Dey et al.	N/A	N/A
2015/0263900	12/2014	Polyakov et al.	N/A	N/A
2015/0286969	12/2014	Warner et al.	N/A	N/A
2015/0295796	12/2014	Hsiao et al.	N/A	N/A
2015/0304193	12/2014	Ishii et al.	N/A	N/A
2015/0316918	12/2014	Schleiss et al.	N/A	N/A
2015/0324422	12/2014	Elder	N/A	N/A
2015/0341212	12/2014	Hsiao et al.	N/A	N/A
2015/0348417	12/2014	Ignaczak et al.	N/A	N/A
2015/0379080	12/2014	Jochimski	N/A	N/A
2016/0011753	12/2015	McFarland	715/771	G06F 3/0482
2016/0033946	12/2015	Zhu et al.	N/A	N/A
2016/0035246	12/2015	Curtis	N/A	N/A
2016/0065601	12/2015	Gong et al.	N/A	N/A
2016/0070736	12/2015	Swan et al.	N/A	N/A

2016/0078229	12/2015	Gong et al.	N/A	N/A
2016/0090839	12/2015	Stolarczyk	N/A	N/A
2016/0103442	12/2015	Lyu et al.	N/A	N/A
2016/0119434	12/2015	Dong et al.	N/A	N/A
2016/0127712	12/2015	Alfredsson et al.	N/A	N/A
2016/0139752	12/2015	Shim et al.	N/A	N/A
2016/0163186	12/2015	Davidson et al.	N/A	N/A
2016/0170390	12/2015	Xie et al.	N/A	N/A
2016/0171862	12/2015	Das et al.	N/A	N/A
2016/0173816	12/2015	Huenerfauth et al.	N/A	N/A
2016/0179315	12/2015	Sarao et al.	N/A	N/A
2016/0179342	12/2015	Sarao et al.	N/A	N/A
2016/0179990	12/2015	Sarao et al.	N/A	N/A
2016/0195856	12/2015	Spero	N/A	N/A
2016/0212165	12/2015	Singla et al.	N/A	N/A
2016/0239660	12/2015	Azvine et al.	N/A	N/A
2016/0239756	12/2015	Aggour et al.	N/A	N/A
2016/0247129	12/2015	Song et al.	N/A	N/A
2016/0260063	12/2015	Harris et al.	N/A	N/A
2016/0267759	12/2015	Kerzner	N/A	N/A
2016/0313751	12/2015	Risbeck et al.	N/A	N/A
2016/0313752	12/2015	Przybylski	N/A	N/A
2016/0313902	12/2015	Hill et al.	N/A	N/A
2016/0335731	12/2015	Hall	N/A	N/A
2016/0350364	12/2015	Anicic et al.	N/A	N/A
2016/0357521	12/2015	Zhang et al.	N/A	N/A
2016/0357828	12/2015	Tobin et al.	N/A	N/A
2016/0358432	12/2015	Branscomb et al.	N/A	N/A
2016/0363336	12/2015	Roth et al.	N/A	N/A
2016/0370258	12/2015	Perez	N/A	N/A
2016/0378306	12/2015	Kresl et al.	N/A	N/A
2016/0379326	12/2015	Chan-Gove et al.	N/A	N/A
2017/0006135	12/2016	Siebel	N/A	N/A
2017/0011318	12/2016	Vigano et al.	N/A	N/A
2017/0017221	12/2016	Lamparter et al.	N/A	N/A
2017/0039255	12/2016	Raj et al.	N/A	N/A
2017/0052536	12/2016	Warner et al.	N/A	N/A
2017/0053441	12/2016	Nadumane et al.	N/A	N/A
2017/0063894	12/2016	Muddu et al.	N/A	N/A
2017/0068409	12/2016	Nair	N/A	N/A
2017/0070775	12/2016	Taxier et al.	N/A	N/A
2017/0075984	12/2016	Deshpande et al.	N/A	N/A
2017/0084168	12/2016	Janchookiat	N/A	N/A
2017/0090437	12/2016	Veeramani et al.	N/A	N/A
2017/0093700	12/2016	Gilley et al.	N/A	N/A
2017/0098086	12/2016	Hoernecke et al.	N/A	N/A
2017/0103327	12/2016	Penilla et al.	N/A	N/A
2017/0103403	12/2016	Chu et al.	N/A	N/A
2017/0123389	12/2016	Baez et al.	N/A	N/A
2017/0134415	12/2016	Muddu et al.	N/A	N/A
2017/0177715	12/2016	Chang et al.	N/A	N/A
2017/0180147	12/2016	Brandman et al.	N/A	N/A
2017/0188216	12/2016	Koskas et al.	N/A	N/A
2017/0212482	12/2016	Boettcher et al.	N/A	N/A
2017/0212668	12/2016	Shah et al.	N/A	N/A
2017/0220641	12/2016	Chi et al.	N/A	N/A
2017/0230930	12/2016	Frey	N/A	N/A
2017/0235817	12/2016	Deodhar et al.	N/A	N/A
2017/0251182	12/2016	Siminoff et al.	N/A	N/A

2017/0270124	12/2016	Nagano et al.	N/A	N/A
2017/0277769	12/2016	Pasupathy et al.	N/A	N/A
2017/0278003	12/2016	Liu	N/A	N/A
2017/0294132	12/2016	Colmenares	N/A	N/A
2017/0315522	12/2016	Kwon et al.	N/A	N/A
2017/0315697	12/2016	Jacobson et al.	N/A	N/A
2017/0322534	12/2016	Sinha et al.	N/A	N/A
2017/0323389	12/2016	Vavrasek	N/A	N/A
2017/0329289	12/2016	Kohn et al.	N/A	N/A
2017/0336770	12/2016	MacMillan	N/A	N/A
2017/0345287	12/2016	Fuller et al.	N/A	N/A
2017/0351957	12/2016	Lecue et al.	N/A	N/A
2017/0357225	12/2016	Asp et al.	N/A	N/A
2017/0357490	12/2016	Park et al.	N/A	N/A
2017/0357908	12/2016	Cabadi et al.	N/A	N/A
2018/0012159	12/2017	Kozloski et al.	N/A	N/A
2018/0013579	12/2017	Fairweather et al.	N/A	N/A
2018/0024520	12/2017	Sinha et al.	N/A	N/A
2018/0039238	12/2017	Gartner et al.	N/A	N/A
2018/0048485	12/2017	Pelton et al.	N/A	N/A
2018/0069932	12/2017	Tiwari et al.	N/A	N/A
2018/0114140	12/2017	Chen et al.	N/A	N/A
2018/0137288	12/2017	Polyakov	N/A	N/A
2018/0157930	12/2017	Rutschman et al.	N/A	N/A
2018/0162400	12/2017	Abdar	N/A	N/A
2018/0176241	12/2017	Manadhata et al.	N/A	N/A
2018/0198627	12/2017	Mullins	N/A	N/A
2018/0203961	12/2017	Aisu et al.	N/A	N/A
2018/0239982	12/2017	Rutschman et al.	N/A	N/A
2018/0275625	12/2017	Park et al.	N/A	N/A
2018/0276962	12/2017	Butler et al.	N/A	N/A
2018/0292797	12/2017	Lamparter et al.	N/A	N/A
2018/0336785	12/2017	Ghannam et al.	N/A	N/A
2018/0356775	12/2017	Harvey	N/A	N/A
2018/0359111	12/2017	Harvey	N/A	N/A
2018/0364654	12/2017	Locke et al.	N/A	N/A
2019/0005025	12/2018	Malabarba	N/A	N/A
2019/0013023	12/2018	Pourmohammad et al.	N/A	N/A
2019/0025771	12/2018	Park et al.	N/A	N/A
2019/0037135	12/2018	Hedge	N/A	N/A
2019/0042988	12/2018	Brown et al.	N/A	N/A
2019/0088106	12/2018	Grundstrom	N/A	N/A
2019/0094824	12/2018	Xie et al.	N/A	N/A
2019/0096217	12/2018	Pourmohammad et al.	N/A	N/A
2019/0102840	12/2018	Perl et al.	N/A	N/A
2019/0121801	12/2018	Jethwa et al.	N/A	N/A
2019/0138512	12/2018	Pourmohammad et al.	N/A	N/A
2019/0147883	12/2018	Mellenthin et al.	N/A	N/A
2019/0158309	12/2018	Park et al.	N/A	N/A
2019/0163152	12/2018	Worrall et al.	N/A	N/A
2019/0268178	12/2018	Fairweather et al.	N/A	N/A
2019/0310979	12/2018	Masuzaki et al.	N/A	N/A
2019/0377306	12/2018	Harvey	N/A	N/A
2020/0226156	12/2019	Borra et al.	N/A	N/A
2020/0285203	12/2019	Thakur et al.	N/A	N/A
2020/0336328	12/2019	Harvey	N/A	N/A
2020/0348632	12/2019	Harvey	N/A	N/A
2020/0387576	12/2019	Brett et al.	N/A	N/A
2020/0396208	12/2019	Brett et al.	N/A	N/A

2021/0042299	12/2020	Migliori	N/A	N/A
2021/0043221	12/2020	Yelchuru et al.	N/A	N/A
2021/0325070	12/2020	Endel et al.	N/A	N/A
2021/0342961	12/2020	Winter et al.	N/A	N/A
2021/0381711	12/2020	Harvey et al.	N/A	N/A
2021/0381712	12/2020	Harvey et al.	N/A	N/A
2021/0382445	12/2020	Harvey et al.	N/A	N/A
2021/0383041	12/2020	Harvey et al.	N/A	N/A
2021/0383042	12/2020	Harvey et al.	N/A	N/A
2021/0383200	12/2020	Harvey et al.	N/A	N/A
2021/0383219	12/2020	Harvey et al.	N/A	N/A
2021/0383235	12/2020	Harvey et al.	N/A	N/A
2021/0383236	12/2020	Harvey et al.	N/A	N/A
2022/0066402	12/2021	Harvey et al.	N/A	N/A
2022/0066405	12/2021	Harvey	N/A	N/A
2022/0066432	12/2021	Harvey et al.	N/A	N/A
2022/0066434	12/2021	Harvey et al.	N/A	N/A
2022/0066528	12/2021	Harvey et al.	N/A	N/A
2022/0066722	12/2021	Harvey et al.	N/A	N/A
2022/0066754	12/2021	Harvey et al.	N/A	N/A
2022/0066761	12/2021	Harvey et al.	N/A	N/A
2022/0067226	12/2021	Harvey et al.	N/A	N/A
2022/0067227	12/2021	Harvey et al.	N/A	N/A
2022/0067230	12/2021	Harvey et al.	N/A	N/A
2022/0069863	12/2021	Harvey et al.	N/A	N/A
2022/0070293	12/2021	Harvey et al.	N/A	N/A
2022/0121965	12/2021	Chatterji et al.	N/A	N/A
2022/0138684	12/2021	Harvey	N/A	N/A
2022/0147000	12/2021	Cooley et al.	N/A	N/A
2022/0150124	12/2021	Cooley et al.	N/A	N/A
2022/0215264	12/2021	Harvey et al.	N/A	N/A
2023/0010757	12/2022	Preciado	N/A	N/A
2023/0071312	12/2022	Preciado et al.	N/A	N/A
2023/0076011	12/2022	Preciado et al.	N/A	N/A
2023/0083703	12/2022	Meiners	N/A	N/A
2023/0214555	12/2022	Harvey et al.	N/A	N/A
2023/0252205	12/2022	Harvey et al.	N/A	N/A
2023/0334200	12/2022	Meiners	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019226217	12/2019	AU	N/A
2019226264	12/2019	AU	N/A
2957726	12/2015	CA	N/A
3043996	12/2017	CA	N/A
101415011	12/2008	CN	N/A
102136099	12/2010	CN	N/A
102136100	12/2010	CN	N/A
102650876	12/2011	CN	N/A
104040583	12/2013	CN	N/A
104603832	12/2014	CN	N/A
104919484	12/2014	CN	N/A
106204392	12/2015	CN	N/A
106406806	12/2016	CN	N/A
106960269	12/2016	CN	N/A
107147639	12/2016	CN	N/A
107598928	12/2017	CN	N/A
2 528 033	12/2011	EP	N/A
3 186 687	12/2016	EP	N/A
3 268 821	12/2017	EP	N/A

3 324 306	12/2017	EP	N/A
3 497 377	12/2018	EP	N/A
4 226 263	12/2022	EP	N/A
H10-049552	12/1997	JP	N/A
2003-162573	12/2002	JP	N/A
2007-018322	12/2006	JP	N/A
4073946	12/2007	JP	N/A
2008-107930	12/2007	JP	N/A
2013-152618	12/2012	JP	N/A
2014-044457	12/2013	JP	N/A
2016/0102923	12/2015	KR	N/A
WO-2009/020158	12/2008	WO	N/A
WO-2011/100255	12/2010	WO	N/A
WO-2013/050333	12/2012	WO	N/A
WO-2015/099394	12/2014	WO	N/A
WO-2015/106702	12/2014	WO	N/A
WO-2015/145648	12/2014	WO	N/A
WO-2017/035536	12/2016	WO	N/A
WO-2017/192422	12/2016	WO	N/A
WO-2017/194244	12/2016	WO	N/A
WO-2017/205330	12/2016	WO	N/A
WO-2017/213918	12/2016	WO	N/A
WO-2018/132112	12/2017	WO	N/A
WO-2020/061621	12/2019	WO	N/A
WO-2022/042925	12/2021	WO	N/A
WO-2022/103812	12/2021	WO	N/A
WO-2022/103813	12/2021	WO	N/A
WO-2022/103820	12/2021	WO	N/A
WO-2022/103822	12/2021	WO	N/A
WO-2022/103824	12/2021	WO	N/A
WO-2022/103829	12/2021	WO	N/A
WO-2022/103831	12/2021	WO	N/A

OTHER PUBLICATIONS

Quinn et al., Building Automation System Data Integration with BIM: Data Structure and Supporting Case Study, Oct. 2020, 10 pages (Year: 2020). cited by examiner

Malinowsky et al., Integrating Process Communication in Building Information Models with IFC and LON, 2010, IEEE, 10 pages (Year: 2010). cited by examiner

Balaji et al, “Brick: Metadata schema for portable smart building applications,” Applied Energy, 2018 20 pages. cited by applicant

Balaji et al, “Brick: Towards a Unified Metadata Schema for Buildings,” dated Nov. 16-17, 2016, 10 pages. cited by applicant

Balaji et al, Demo Abstract: Portable Queries Using the Brick Schema for Building Applications, dated Nov. 16-17, 2016, 2 pages. cited by applicant

Bhattacharya et al., Short Paper: Analyzing Metadata Schemas for Buildings—The Good, The Bad and The Ugly, ACM, dated Nov. 4-5, 2015, 4 pages. cited by applicant

Brick: Towards a Unified Metadata Schema for Buildings, dated Nov. 16, 2016, 46 pages. cited by applicant

Building Blocks for Smart Buildings, BrickSchema.org, dated Mar. 2019, 17 pages. cited by applicant

Fierro et al., Beyond a House of Sticks: Formalizing Metadata Tags with Brick, dated Nov. 13-14, 2019, 10 pages. cited by applicant

Fierro et al., Dataset: An Open Dataset and Collection Tool for BMS Point Labels, dated Nov. 10, 2019, 3 pages. cited by applicant

Fierro et al., Design and Analysis of a Query Processor for Brick, dated Jan. 2018, 25 pages. cited by applicant

Fierro et al., Design and Analysis of a Query Processor for Brick, dated Nov. 8-9, 2017, 10 pages. cited by applicant

Fierro et al., Mortar: An Open Testbed for Portable Building Analytics, dated Nov. 7-8, 2018, 10 pages. cited by applicant

Fierro et al., Why Brick is a Game Changer for Smart Buildings, URL: https://brickschema.org/papers/Brick_Memoori_Webinar_Presentation.pdf, Memoori Webinar, 2019, 67 pages. cited by applicant

Fierro, Writing Portable Building Analytics with the Brick Metadata Schema, UC Berkeley ACM E-Energy, 2019, 39 pages.

cited by applicant

Gao et al., A large-scale evaluation of automated metadata inference approaches on sensors from air handling units, dated May 1, 2018, pp. 14-30. cited by applicant

Koh et al., "Scrabble: Transferrable Semi-Automated Semantic Metadata Normalization using Intermediate Representation," dated Nov. 7-8, 2018, 10 pages. cited by applicant

Koh et al., Plaster: An Integration, Benchmark, and Development Framework for Metadata Normalization Methods, dated Nov. 7-8, 2018, 10 pages. cited by applicant

Koh et al., Who can Access What, and When?, dated Nov. 13-14, 2019, 4 pages. cited by applicant

Metadata Schema for Buildings, URL: <https://brickschema.org/docs/Brick-Leaflet.pdf>, Retrieved from Internet Dec. 24, 2019, 3 pages. cited by applicant

CoolingLogic, "CoolingLogic: Up early, saving billions." URL:

http://coolinglogic.com/documents/MarketingFlyer_FINAL_HiRes8.5x11.pdf, retrieved from internet Oct. 27, 2022 (1 page) cited by applicant

Incomplete File of Communication with Various Companies, etc. in 2016-2021, URL:

http://coolinglogic.com/documents/22072101_Letters_and_Signature_Receipts.pdf, published, as one document, on: Jul. 21, 2022 (211 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "Divine Grace Building Automation (Images)," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Oakland-County-Michigan/Building-Automation-Images.html>, retrieved from internet Oct. 27, 2022 (8 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "Divine Grace Building Automation," URL: <http://cooljohnson.com/Building-Automation-Systems-Michigan/Oakland-County-Michigan/Building-Automation-Divine-Grace.html>, retrieved from internet

Oct. 27, 2022 (3 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "Excel Rehabilitation Building Automation," URL: <http://cooljohnson.com/Building-Automation-Systems-Michigan/Waterford-Michigan/Building-Automation-System--Excel.html>, retrieved from internet Oct.

27, 2022 (2 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "Intertek Testing Services Building Automation," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Plymouth-Michigan/Building-Automation-System-Plymouth-Michigan.html>, retrieved from internet Oct. 27, 2022 (8 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "Jla Medical Building Building Automation," URL: <http://cooljohnson.com/Building-Automation-Systems-Michigan/Waterford-Michigan/Building-Automation-System--JLA.html>, retrieved from internet Oct.

27, 2022 (3 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "Mosaic Christian Building Automation (Images)," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Detroit/Building-Automation-Images.html>, retrieved from internet Oct. 27, 2022 (12 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "Mosaic Christian Building Automation," URL: <http://cooljohnson.com/Building-Automation-Systems-Michigan/Detroit/Mosaic-Christian.html>, retrieved from internet Oct. 27, 2022 (5 pages). cited by

applicant

Johnson Heating and Cooling L.L.C., "Shepherd's Gate Lutheran Church Building Automation," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Shelby-Township-Michigan/Building-Automation-Systems-SG.html>, retrieved from internet Oct. 27, 2022 (3 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "St. Clair County Residence Building Automation," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/St-Clair-Michigan/Building-Automation-System-St-Clair-Michigan.html>, retrieved from internet Oct. 27, 2022 (4 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "St. Joseph Mercy Oakland U. C. Building Automation," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Waterford-Michigan/Building-Automation-Systems-SJMO.html>, retrieved from internet Oct. 27, 2022 (2 pages). cited by applicant

Johnson Heating and Cooling L.L.C., "Waterford Internal Medicine Building Automation," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Waterford-Michigan/Building-Automation-Systems-WIM.html>, retrieved from internet Oct. 27, 2022 (3 pages). cited by applicant

Johnson Heating and Cooling, LLC, "Building Automation Clawson Michigan 2.0," URL: <http://cooljohnson.com/Building-Automation-Systems-Michigan/Clawson-Michigan/Building-Automation-Clawson-Manor-2.html>, retrieved from the internet

Oct. 27, 2022 (6 pages). cited by applicant

Johnson Heating and Cooling, LLC, "Building Automation Images Clawson Michigan 2.0," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Clawson-Michigan/Building-Automation-Clawson-Manor-2-Images.html>, retrieved from the internet Oct. 27, 2022 (14 pages). cited by applicant

Johnson Heating and Cooling, LLC, "Building Automation System Clawson Michigan Clawson Manor," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Clawson-Michigan/Building-Automation-System-Clawson-Manor.html>; retrieved from the internet Oct. 27, 2022 (3 pages). cited by applicant

Johnson Heating and Cooling, LLC, "Building Automation System in Michigan Images," URL:

<http://cooljohnson.com/Building-Automation-Systems-Michigan/Macomb-County-Michigan/Building-Automation-Images.html>; retrieved from the internet Oct. 27, 2022 (13 pages). cited by applicant

Johnson Heating and Cooling, LLC, “Building Automation System in Michigan,” URL: <http://cooljohnson.com/Building-Automation-Systems-Michigan/Macomb-County-Michigan/Building-Automation-Confidential-Customer.html>; retrieved from the internet, Oct. 27, 2022 (4 pages). cited by applicant

Johnson Solid State LLC, “Building Automation Equipment,” URL: http://cooljohnson.com/Video/Building_Automation/Confidential_Customer_BLD_2/Building_Automation_Equipment.mp4 retrieved from internet Oct. 27, 2022 (35 pages). cited by applicant

Johnson Solid State LLC, “Building Automation GUI,” URL: http://cooljohnson.com/Video/Building_Automation/Confidential_Customer_BLD_2/Building_Automation_GUI.mp4, retrieved from internet Oct. 27, 2022 (24 pages). cited by applicant

Johnson Solid State LLC, “Cooling Logic Overview,” URL: http://coolinglogic.com/documents/CoolingLogic_Overview_High_Quality.mp4, retrieved from internet Oct. 27, 2022 (16 pages). cited by applicant

Johnson Solid State LLC, “So what is CoolingLogic™?” URL: <http://coolinglogic.com/Coolinglogic-How-it-Works.html>, retrieved from the internet Oct. 27, 2022 (3 pages). cited by applicant

Johnson, David, “A Method to Increase HVAC System Efficiency and Decrease Energy Consumption,” White Paper: Johnson Solid State, LLC, URL: http://coolinglogic.com/documents/16102106_White_Paper_High_Resolution_Protected.pdf, Sep. 24, 2016 (51 pages). cited by applicant

Johnson, David, “CoolingLogic™: Changing the Way You Cool,” Report: Johnson Solid State, LLC, URL: http://coolinglogic.com/documents/18111303_Changing_the_way_you_Cool.pdf, Nov. 7, 2018 (12 pages). cited by applicant

Johnson, David, “CoolingLogic™: Mosaic Christian Church A Case Study,” Report: Johnson Solid State, LLC, URL: http://coolinglogic.com/documents/19020301_Mosaic_Christian_Coolinglogic_Case_Study.pdf, Feb. 2, 2019 (140 pages). cited by applicant

Johnson, David, “Excel Rehabilitation Building Automation: Building Automation System User Manual,” URL: <http://cooljohnson.com/Building-Automation-Systems-Michigan/Waterford-Michigan/Building-Automation-System-Excel-Manual.html>, 2012 (10 pages). cited by applicant

Johnson, David, “Temperature Control System and Methods for Operating Same,” Pre-Publication printout of U.S. Appl. No. 15/231,943, filed Aug. 9, 2016, URL: http://coolinglogic.com/documents/16080901_CIP_As_Filed.pdf (99 pages). cited by applicant

White et al., “Reduce building maintenance costs with AWS IoT TwinMaker Knowledge Graph,” The Internet of Things on AWS—Official Blog, URL: <https://aws.amazon.com/blogs/iot/reduce-building-maintenance-costs-with-aws-iot-twinmaker-knowledge-graph/>, Nov. 18, 2022 (10 pages). cited by applicant

U.S. Appl. No. 17/566,029, PassiveLogic, Inc. cited by applicant

U.S. Appl. No. 17/567,275, PassiveLogic, Inc. cited by applicant

U.S. Appl. No. 17/722,115, PassiveLogic, Inc. cited by applicant

Balaji et al, “Brick: Metadata schema for portable smart building applications,” Applied Energy, Sep. 15, 2018, 3 pages, (Abstract). cited by applicant

Bhattacharya, A., “Enabling Scalable Smart-Building Analytics,” Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2016-201, Dec. 15, 2016 (121 pages). cited by applicant

Chinese Office Action on CN Appl. No. 201780003995.9 dated Apr. 8, 2021 (21 pages with English language translation). cited by applicant

Chinese Office action on CN Appl. No. 201780043400.2 dated Apr. 25, 2021 (15 pages with English language translation). cited by applicant

Curry, E. et al., “Linking building data in the cloud: Integrating cross-domain building data using linked data.” Advanced Engineering Informatics, 2013, 27 (pp. 206-219). cited by applicant

Digital Platform Litigation Documents Part 1, includes cover letter, dismissal of case DDE-1-21-cv-01796, IPR2023-00022 (documents filed Jan. 26, 2023-Oct. 7, 2022), and IPR2023-00085 (documents filed Jan. 26, 2023-Oct. 20, 2022) (748 pages total). cited by applicant

Digital Platform Litigation Documents Part 10, includes DDE-1-21-cv-01796 (documents filed Nov. 1, 2022-Dec. 22, 2021) (1795 pages total). cited by applicant

Digital Platform Litigation Documents Part 2, includes IPR2023-00085 (documents filed Oct. 20, 2022) (172 pages total). cited by applicant

Digital Platform Litigation Documents Part 3, includes IPR2023-00085 (documents filed Oct. 20, 2022) and IPR2023-00170 (documents filed Nov. 28, 2022-Nov. 7, 2022) (397 pages total). cited by applicant

Digital Platform Litigation Documents Part 4, includes IPR2023-00170 (documents filed Nov. 7, 2022) and IPR2023-00217 (documents filed Jan. 18, 2023-Nov. 15, 2022) (434 pages total). cited by applicant

Digital Platform Litigation Documents Part 5, includes IPR2023-00217 (documents filed Nov. 15, 2022) and IPR2023-00257

(documents filed Jan. 25, 2023-Nov. 23, 2022) (316 pages total). cited by applicant

Digital Platform Litigation Documents Part 6, includes IPR2023-00257 (documents filed Nov. 23, 2022) and IPR 2023-00346 (documents filed Jan. 3, 2023-Dec. 13, 2022) (295 pages total). cited by applicant

Digital Platform Litigation Documents Part 7, includes IPR 2023-00346 (documents filed Dec. 13, 2022) and IPR2023-00347 (documents filed Jan. 3, 2023-Dec. 13, 2022) (217 pages total). cited by applicant

Digital Platform Litigation Documents Part 8, includes IPR2023-00347 (documents filed Dec. 13, 2022), EDTX-2-22-cv-00243 (documents filed Sep. 20, 2022-Jun. 29, 2022), and DDE-1-21-cv-01796 (documents filed Feb. 3, 2023-Jan. 10, 2023) (480 pages total). cited by applicant

Digital Platform Litigation Documents Part 9, includes DDE-1-21-cv-01796 (documents filed Jan. 10, 2023-Nov. 1, 2022) (203 pages total). cited by applicant

El Kaed, C. et al., "Building management insights driven by a multi-system semantic representation approach," 2016 IEEE 3rd World Forum on Internet of Things (WF-IoT), Dec. 12-14, 2016, (pp. 520-525). cited by applicant

Ellis, C. et al., "Creating a room connectivity graph of a building from per-room sensor units." BuildSys '12, Toronto, ON, Canada, Nov. 6, 2012 (7 pages). cited by applicant

Extended European Search Report on EP Application No. 18196948.6 dated Apr. 10, 2019 (9 pages). cited by applicant

Fierro, G., "Design of an Effective Ontology and Query Processor Enabling Portable Building Applications," Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2019-106, June 27, 2019 (118 pages). cited by applicant

File History for U.S. Appl. No. 12/776,159, filed May 7, 2010 (722 pages). cited by applicant

Final Conference Program, ACM BuildSys 2016, Stanford, CA, USA, Nov. 15-17, 2016 (7 pages). cited by applicant

Harvey, T., "Quantum Part 3: The Tools of Autonomy, How PassiveLogic's Quantum Creator and Autonomy Studio software works," URL: <https://www.automatedbuildings.com/news/jan22/articles/passive/211224010000passive.html>, Jan. 2022 (7 pages). cited by applicant

Harvey, T., "Quantum: The Digital Twin Standard for Buildings," URL: <https://www.automatedbuildings.com/news/feb21/articles/passivelogic/210127124501passivelogic.html>, Feb. 2021 (6 pages) cited by applicant

Hu, S. et al., "Building performance optimisation: A hybrid architecture for the integration of contextual information and time-series data," Automation in Construction, 2016, 70 (pp. 51-61). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/013831 dated Mar. 31, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/035524 dated Jul. 24, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion on PCT/US2017/052060, mailed Oct. 5, 2017, 11 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052633, mailed Oct. 23, 2017, 9 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052829, mailed Nov. 27, 2017, 24 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/024068, mailed Jun. 15, 2018, 22 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052971, dated Mar. 1, 2019, 19 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052974, mailed Dec. 19, 2018, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052975, mailed Jan. 2, 2019, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052994, mailed Jan. 7, 2019, 15 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2019/015481, dated May 17, 2019, 78 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2020/058381, dated Jan. 27, 2021, 30 pages. cited by applicant

Japanese Office Action on JP Appl. No. 2018-534963 dated May 11, 2021 (16 pages with English language translation). cited by applicant

Li et al., "Event Stream Processing with Out-of-Order Data Arrival," International Conferences on Distributed Computing Systems, 2007, (8 pages). cited by applicant

Nissin Electric Co., Ltd., "Smart power supply system (SPSS)," Outline of the scale verification plan, Nissin Electric Technical Report, Japan, Apr. 23, 2014, vol. 59, No. 1 (23 pages). cited by applicant

Passivelogic, "Explorer: Digital Twin Standard for Autonomous Systems. Made interactive." URL: <https://passivelogic.com/software/quantum-explorer/>, retrieved from internet Jan. 4, 2023 (13 pages). cited by applicant

Passivelogic, "Quantum: The Digital Twin Standard for Autonomous Systems, A physics-based ontology for next-generation control and AI." URL: <https://passivelogic.com/software/quantum-standard/>, retrieved from internet Jan. 4, 2023 (20 pages). cited by applicant

Quantum Alliance, "Quantum Explorer Walkthrough," 2022, (7 pages) (screenshots from video). cited by applicant

Results of the Partial International Search for PCT/US2018/052971, dated Jan. 3, 2019, 3 pages. cited by applicant

Sinha, Sudhi and AI Huraimel, Khaled, "Reimagining Businesses with AI" John Wiley & Sons, Inc., Hoboken, NJ, USA, 2021 (156 pages). cited by applicant

Sinha, R. and Park, Youngchoon, "Building an Effective IoT Ecosystem for Your Business," Johnson Controls International, Springer International Publishing, 2017 (286 pages). cited by applicant

Sinha, Sudhi, "Making Big Data Work for Your Business: A guide to effective Big Data analytics," Impackt Publishing LTD. Birmingham, UK, Oct. 2014 (170 pages). cited by applicant

The Virtual Nuclear Tourist, "Calvert Cliffs Nuclear Power Plant," URL: <http://www.nucleartourist.com/us/calvert.htm>, Jan. 11, 2006 (2 pages). cited by applicant

University of California at Berkeley, EECS Department, "Enabling Scalable Smart-Building Analytics," URL: <https://www2.eecs.berkeley.edu/Pubs/TechRpts/2016/EECS-2016-201.html>, retrieved from internet Feb. 15, 2022 (7 pages). cited by applicant

Van Hoof, Bert, "Announcing Azure Digital Twins: Create digital replicas of spaces and infrastructure using cloud, AI and IoT," URL: <https://azure.microsoft.com/en-us/blog/announcing-azure-digital-twins-create-digital-replicas-of-spaces-and-infrastructure-using-cloud-ai-and-iot/>, Sep. 24, 2018 (11 pages). cited by applicant

W3C, "SPARQL: Query Language for RDF," located on The Wayback Machine, URL: <https://web.archive.org/web/20161230061728/http://www.w3.org/TR/rdf-sparql-query/>, retrieved from internet Nov. 15, 2022 (89 pages). cited by applicant

Wei et al., "Development and Implementation of Software Gateways of Fire Fighting Subsystem Running on EBI," Control, Automation and Systems Engineering, IITA International Conference on, IEEE, Jul. 2009 (pp. 9-12). cited by applicant

Zhou, Q. et al., "Knowledge-infused and Consistent Complex Event Processing over Real-time and Persistent Streams," Further Generation Computer Systems, 2017, 76 (pp. 391-406). cited by applicant

Asen, Y., "Building Information Modeling Based Integration and Visualization for Facilities Management," Thesis, Concordia University, Montreal, Quebec, Canada, Jun. 2012 (129 pages). cited by applicant

Primary Examiner: Pham; Linh K

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 16/694,859 filed Nov. 25, 2019 which is a continuation of U.S. patent application Ser. No. 14/919,516 filed Oct. 21, 2015. The entirety of each of these patent applications is incorporated herein in their entireties.

BACKGROUND

(1) The present invention relates generally to a building automation system (BAS) and more particularly to a BAS configured to integrate BAS data with a building information model (BIM).

(2) A BIM is a representation of the physical and/or functional characteristics of a building. A BIM may represent structural characteristics of the building (e.g., walls, floors, ceilings, doors, windows, etc.) as well as the systems or components contained within the building (e.g., lighting components, electrical systems, mechanical systems, HVAC components, furniture, plumbing systems or fixtures, etc.). In some embodiments, a BIM is a 3D graphical model of the building. A BIM may be created using computer modeling software or other computer-aided design (CAD) tools and may be used by any of a plurality of entities that provide building-related services.

(3) A BAS is, in general, a system of devices configured to control, monitor, and/or manage equipment in or around a building or building area. A BAS can include, for example, a HVAC system, a security system, a lighting system, a fire alerting system, any other system that is capable of managing building functions or devices, or any combination thereof. Some BASs provide graphical user interfaces that allow a user to interact with components of the BAS. Generating graphics for the graphical user interfaces can be time consuming and often results in low quality graphics that do not adequately represent the building equipment. It would be desirable to use the graphics and modeling provided by a BIM as part of the BAS interface. However, it can be difficult and challenging to integrate BAS points with a BIM.

SUMMARY

(4) One implementation of the present disclosure is a building automation system (BAS). The BAS includes building equipment located within a building and a BAS network configured to facilitate communications between the building equipment. The building equipment operate to affect a variable state or condition within the building. The BAS includes a BAS-BIM integrator configured to receive BAS points from the BAS network and to integrate the BAS points with a building information model (BIM). The BIM includes a plurality of BIM objects representing the building equipment. The BAS includes an integrated BAS-BIM viewer configured to use the BIM with the integrated BAS points to generate a user interface. The user interface includes a graphical representation of the BIM objects and

the BAS points integrated therewith.

(5) In some embodiments, the BIM includes a three-dimensional model of the building. The BIM objects may include one or more objects representing structural components of the building and one or more objects representing spaces within the building.

(6) In some embodiments, the integrated BAS-BIM viewer uses the integrated BAS points to retrieve corresponding point values from the BAS network and displays the point values as part of the user interface. The point values may include at least one of values measured by the building equipment, values generated by the building equipment, setpoints for the building equipment, and operating parameters for the building equipment.

(7) In some embodiments, the integrated BAS-BIM viewer generates a graph including a history of values for at least one of the BAS points and displays the graph as part of the user interface.

(8) In some embodiments, the BAS-BIM integrator includes a BAS tree generator configured to generate a BAS tree comprising the BAS points, a BIM tree generator configured to generate a BIM tree comprising the BIM objects, and a mapping interface generator configured to generate a mapping interface comprising the BAS tree and the BIM tree. The BAS-BIM integrator may be configured to establish mappings between the BAS points and the BIM objects based on a user input received via the mapping interface. In some embodiments, the user input includes dragging and dropping the BAS points from the BAS tree onto BIM objects in the BIM tree.

(9) In some embodiments, the BAS-BIM integrator stores mappings between the BAS points and the BIM objects in a mappings database. The integrated BAS-BIM viewer may retrieve the mappings from the mappings database and use the mappings to generate the user interface.

(10) In some embodiments, the integrated BAS-BIM viewer receives a control action via the user interface and uses the control action to generate a control signal for the building equipment.

(11) Another implementation of the present disclosure is a system for integrating building automation system (BAS) points with a building information model (BIM). The system includes a BAS-BIM integrator configured to receive BAS points from a BAS network and to integrate the BAS points with a BIM. The BIM includes a plurality of BIM objects representing building equipment. The system includes an integrated BAS-BIM viewer configured to use the BIM with the integrated BAS points to generate a user interface. The user interface includes a graphical representation of the BIM objects and the BAS points integrated therewith.

(12) In some embodiments, the BIM includes a three-dimensional model of the building. The BIM objects may include one or more objects representing structural components of the building and one or more objects representing spaces within the building.

(13) In some embodiments, the integrated BAS-BIM viewer uses the integrated BAS points to retrieve corresponding point values from the BAS network and displays the point values as part of the user interface. The point values may include at least one of values measured by the building equipment, values generated by the building equipment, setpoints for the building equipment, and operating parameters for the building equipment.

(14) In some embodiments, the integrated BAS-BIM viewer generates a graph including a history of values for at least one of the BAS points and displays the graph as part of the user interface.

(15) In some embodiments, the BAS-BIM integrator includes a BAS tree generator configured to generate a BAS tree comprising the BAS points, a BIM tree generator configured to generate a BIM tree comprising the BIM objects, and a mapping interface generator configured to generate a mapping interface comprising the BAS tree and the BIM tree. The BAS-BIM integrator may be configured to establish mappings between the BAS points and the BIM objects based on a user input received via the mapping interface. In some embodiments, the user input includes dragging and dropping the BAS points from the BAS tree onto BIM objects in the BIM tree.

(16) In some embodiments, the BAS-BIM integrator stores mappings between the BAS points and the BIM objects in a mappings database. The integrated BAS-BIM viewer may retrieve the mappings from the mappings database and use the mappings to generate the user interface.

(17) In some embodiments, the integrated BAS-BIM viewer receives a control action via the user interface and uses the control action to generate a control signal for the building equipment.

(18) Another implementation of the present disclosure is a method for integrating building automation system (BAS) points with a building information model (BIM). The method includes receiving a BIM including a plurality of BIM objects representing building equipment, collecting BAS points from a BAS network, integrating the BAS points with the BIM, and using the BIM with the integrated BAS points to generate a user interface. The user interface includes a graphical representation of the BIM objects and the BAS points integrated therewith. The method includes detecting a control action received via the user interface and using the control action to generate a control signal for the building equipment in response to detecting the control action.

(19) Those skilled in the art will appreciate that the summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices and/or processes described herein, as defined solely by the claims, will become apparent in the detailed description set forth herein and taken in conjunction with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a drawing of a building equipped with a building automation system (BAS), according to an exemplary embodiment.
- (2) FIG. 2 is a block diagram of a waterside system which may be used to provide heating and/or cooling to the building of FIG. 1, according to an exemplary embodiment.
- (3) FIG. 3 is a block diagram of an airside system which may be used to provide heating and/or cooling to the building of FIG. 1, according to an exemplary embodiment.
- (4) FIG. 4 is a block diagram of a BAS which may be used to monitor and control building equipment in the building of FIG. 1, according to an exemplary embodiment.
- (5) FIG. 5 is a block diagram of a system for integrating BAS data with a building information model (BIM), according to an exemplary embodiment.
- (6) FIG. 6 is a block diagram illustrating the BAS-BIM integrator of FIG. 5 in greater detail, according to an exemplary embodiment.
- (7) FIG. 7 is a block diagram of another system for integrating BAS data with a BIM, according to an exemplary embodiment.
- (8) FIG. 8 is a block diagram of a BAS controller which may be used to integrate BAS data with a BIM, according to an exemplary embodiment.
- (9) FIGS. 9-18 are drawings of user interfaces which may be generated by the systems of FIGS. 5, 7, and/or 8 illustrating a graphical representation of a BIM with integrated BAS data, according to an exemplary embodiment.
- (10) FIG. 19 is a flowchart of a process for integrating BAS data with a BIM, according to an exemplary embodiment.

DETAILED DESCRIPTION

- (11) Referring generally to the FIGURES, a building automation system (BAS) with an integrated building information model (BIM) is shown, according to an exemplary embodiment. A BAS is, in general, a system of devices configured to control, monitor, and manage equipment in or around a building or building area. A BAS can include, for example, a HVAC system, a security system, a lighting system, a fire alerting system, any other system that is capable of managing building functions or devices, or any combination thereof.
- (12) A BIM is a representation of the physical and/or functional characteristics of a building. A BIM may represent structural characteristics of the building (e.g., walls, floors, ceilings, doors, windows, etc.) as well as the systems or components contained within the building (e.g., lighting components, electrical systems, mechanical systems, HVAC components, furniture, plumbing systems or fixtures, etc.). In some embodiments, a BIM is a 3D graphical model of the building. A BIM may be created using computer modeling software or other computer-aided design (CAD) tools and may be used by any of a plurality of entities that provide building-related services.
- (13) In some embodiments, a BIM represents building components as objects (e.g., software objects). For example, a BIM may include a plurality of objects that represent physical components within the building as well as building spaces. Each object may include a collection of attributes that define the physical geometry of the object, the type of object, and/or other properties of the object. For example, objects representing building spaces may define the size and location of the building space. Objects representing physical components may define the geometry of the physical component, the type of component (e.g., lighting fixture, air handling unit, wall, etc.), the location of the physical component, a material from which the physical component is constructed, and/or other attributes of the physical component.
- (14) The systems and methods described herein may be used to integrate BAS data with a BIM. Advantageously, the integration provided by the present invention allows dynamic BAS data (e.g., data points and their associated values) to be combined with the BIM. The integrated BIM with BAS data can be viewed using an integrated BAS-BIM viewer (e.g., CAD software, a CAD viewer, a web browser, etc.). The BAS-BIM viewer uses the geometric and location information from the BIM to generate 3D representations of physical components and building spaces.
- (15) In some embodiments, the BAS-BIM viewer functions as a user interface for monitoring and controlling the various systems and devices represented in the integrated BIM. For example, a user can view real-time data from the BAS and/or trend data for objects represented in the BIM simply by viewing the BIM with integrated BAS data. The user can view BAS points, change the values of BAS points (e.g., setpoints), configure the BAS, and interact with the BAS via the BAS-BIM viewer. These features allow the BIM with integrated BAS data to be used as a building control interface which provides a graphical 3D representation of the building and the equipment contained therein without requiring a user to manually create or define graphics for various building components. Additional features and advantages of the present invention are described in greater detail below.
- (16) Building Automation System and HVAC System
- (17) Referring now to FIGS. 1-4, an exemplary building automation system (BAS) and HVAC system in which the systems and methods of the present invention may be implemented are shown, according to an exemplary

embodiment. Referring particularly to FIG. 1, a perspective view of a building 10 is shown. Building 10 is served by a BAS which includes a HVAC system 100. HVAC system 100 may include a plurality of HVAC devices (e.g., heaters, chillers, air handling units, pumps, fans, thermal energy storage, etc.) configured to provide heating, cooling, ventilation, or other services for building 10. For example, HVAC system 100 is shown to include a waterside system 120 and an airside system 130. Waterside system 120 may provide a heated or chilled fluid to an air handling unit of airside system 130. Airside system 130 may use the heated or chilled fluid to heat or cool an airflow provided to building 10. An exemplary waterside system and airside system which may be used in HVAC system 100 are described in greater detail with reference to FIGS. 2-3.

(18) HVAC system 100 is shown to include a chiller 102, a boiler 104, and a rooftop air handling unit (AHU) 106. Waterside system 120 may use boiler 104 and chiller 102 to heat or cool a working fluid (e.g., water, glycol, etc.) and may circulate the working fluid to AHU 106. In various embodiments, the HVAC devices of waterside system 120 may be located in or around building 10 (as shown in FIG. 1) or at an offsite location such as a central plant (e.g., a chiller plant, a steam plant, a heat plant, etc.). The working fluid may be heated in boiler 104 or cooled in chiller 102, depending on whether heating or cooling is required in building 10. Boiler 104 may add heat to the circulated fluid, for example, by burning a combustible material (e.g., natural gas) or using an electric heating element. Chiller 102 may place the circulated fluid in a heat exchange relationship with another fluid (e.g., a refrigerant) in a heat exchanger (e.g., an evaporator) to absorb heat from the circulated fluid. The working fluid from chiller 102 and/or boiler 104 may be transported to AHU 106 via piping 108.

(19) AHU 106 may place the working fluid in a heat exchange relationship with an airflow passing through AHU 106 (e.g., via one or more stages of cooling coils and/or heating coils). The airflow may be, for example, outside air, return air from within building 10, or a combination of both. AHU 106 may transfer heat between the airflow and the working fluid to provide heating or cooling for the airflow. For example, AHU 106 may include one or more fans or blowers configured to pass the airflow over or through a heat exchanger containing the working fluid. The working fluid may then return to chiller 102 or boiler 104 via piping 110.

(20) Airside system 130 may deliver the airflow supplied by AHU 106 (i.e., the supply airflow) to building 10 via air supply ducts 112 and may provide return air from building 10 to AHU 106 via air return ducts 114. In some embodiments, airside system 130 includes multiple variable air volume (VAV) units 116. For example, airside system 130 is shown to include a separate VAV unit 116 on each floor or zone of building 10. VAV units 116 may include dampers or other flow control elements that can be operated to control an amount of the supply airflow provided to individual zones of building 10. In other embodiments, airside system 130 delivers the supply airflow into one or more zones of building 10 (e.g., via supply ducts 112) without using intermediate VAV units 116 or other flow control elements. AHU 106 may include various sensors (e.g., temperature sensors, pressure sensors, etc.) configured to measure attributes of the supply airflow. AHU 106 may receive input from sensors located within AHU 106 and/or within the building zone and may adjust the flow rate, temperature, or other attributes of the supply airflow through AHU 106 to achieve setpoint conditions for the building zone.

(21) Referring now to FIG. 2, a block diagram of a waterside system 200 is shown, according to an exemplary embodiment. In various embodiments, waterside system 200 may supplement or replace waterside system 120 in HVAC system 100 or may be implemented separate from HVAC system 100. When implemented in HVAC system 100, waterside system 200 may include a subset of the HVAC devices in HVAC system 100 (e.g., boiler 104, chiller 102, pumps, valves, etc.) and may operate to supply a heated or chilled fluid to AHU 106. The HVAC devices of waterside system 200 may be located within building 10 (e.g., as components of waterside system 120) or at an offsite location such as a central plant.

(22) In FIG. 2, waterside system 200 is shown as a central plant having a plurality of subplants 202-212. Subplants 202-212 are shown to include a heater subplant 202, a heat recovery chiller subplant 204, a chiller subplant 206, a cooling tower subplant 208, a hot thermal energy storage (TES) subplant 210, and a cold thermal energy storage (TES) subplant 212. Subplants 202-212 consume resources (e.g., water, natural gas, electricity, etc.) from utilities to serve the thermal energy loads (e.g., hot water, cold water, heating, cooling, etc.) of a building or campus. For example, heater subplant 202 may be configured to heat water in a hot water loop 214 that circulates the hot water between heater subplant 202 and building 10. Chiller subplant 206 may be configured to chill water in a cold water loop 216 that circulates the cold water between chiller subplant 206 and building 10. Heat recovery chiller subplant 204 may be configured to transfer heat from cold water loop 216 to hot water loop 214 to provide additional heating for the hot water and additional cooling for the cold water. Condenser water loop 218 may absorb heat from the cold water in chiller subplant 206 and reject the absorbed heat in cooling tower subplant 208 or transfer the absorbed heat to hot water loop 214. Hot TES subplant 210 and cold TES subplant 212 may store hot and cold thermal energy, respectively, for subsequent use.

(23) Hot water loop 214 and cold water loop 216 may deliver the heated and/or chilled water to air handlers located on the rooftop of building 10 (e.g., AHU 106) or to individual floors or zones of building 10 (e.g., VAV units 116). The air handlers push air past heat exchangers (e.g., heating coils or cooling coils) through which the water flows to provide heating or cooling for the air. The heated or cooled air may be delivered to individual zones of building 10 to

serve the thermal energy loads of building **10**. The water then returns to subplants **202-212** to receive further heating or cooling.

(24) Although subplants **202-212** are shown and described as heating and cooling water for circulation to a building, it is understood that any other type of working fluid (e.g., glycol, CO₂, etc.) may be used in place of or in addition to water to serve the thermal energy loads. In other embodiments, subplants **202-212** may provide heating and/or cooling directly to the building or campus without requiring an intermediate heat transfer fluid. These and other variations to waterside system **200** are within the teachings of the present invention.

(25) Each of subplants **202-212** may include a variety of equipment configured to facilitate the functions of the subplant. For example, heater subplant **202** is shown to include a plurality of heating elements **220** (e.g., boilers, electric heaters, etc.) configured to add heat to the hot water in hot water loop **214**. Heater subplant **202** is also shown to include several pumps **222** and **224** configured to circulate the hot water in hot water loop **214** and to control the flow rate of the hot water through individual heating elements **220**. Chiller subplant **206** is shown to include a plurality of chillers **232** configured to remove heat from the cold water in cold water loop **216**. Chiller subplant **206** is also shown to include several pumps **234** and **236** configured to circulate the cold water in cold water loop **216** and to control the flow rate of the cold water through individual chillers **232**.

(26) Heat recovery chiller subplant **204** is shown to include a plurality of heat recovery heat exchangers **226** (e.g., refrigeration circuits) configured to transfer heat from cold water loop **216** to hot water loop **214**. Heat recovery chiller subplant **204** is also shown to include several pumps **228** and **230** configured to circulate the hot water and/or cold water through heat recovery heat exchangers **226** and to control the flow rate of the water through individual heat recovery heat exchangers **226**. Cooling tower subplant **208** is shown to include a plurality of cooling towers **238** configured to remove heat from the condenser water in condenser water loop **218**. Cooling tower subplant **208** is also shown to include several pumps **240** configured to circulate the condenser water in condenser water loop **218** and to control the flow rate of the condenser water through individual cooling towers **238**.

(27) Hot TES subplant **210** is shown to include a hot TES tank **242** configured to store the hot water for later use. Hot TES subplant **210** may also include one or more pumps or valves configured to control the flow rate of the hot water into or out of hot TES tank **242**. Cold TES subplant **212** is shown to include cold TES tanks **244** configured to store the cold water for later use. Cold TES subplant **212** may also include one or more pumps or valves configured to control the flow rate of the cold water into or out of cold TES tanks **244**.

(28) In some embodiments, one or more of the pumps in waterside system **200** (e.g., pumps **222**, **224**, **228**, **230**, **234**, **236**, and/or **240**) or pipelines in waterside system **200** include an isolation valve associated therewith. Isolation valves may be integrated with the pumps or positioned upstream or downstream of the pumps to control the fluid flows in waterside system **200**. In various embodiments, waterside system **200** may include more, fewer, or different types of devices and/or subplants based on the particular configuration of waterside system **200** and the types of loads served by waterside system **200**.

(29) Referring now to FIG. **3**, a block diagram of an airside system **300** is shown, according to an exemplary embodiment. In various embodiments, airside system **300** may supplement or replace airside system **130** in HVAC system **100** or may be implemented separate from HVAC system **100**. When implemented in HVAC system **100**, airside system **300** may include a subset of the HVAC devices in HVAC system **100** (e.g., AHU **106**, VAV units **116**, ducts **112-114**, fans, dampers, etc.) and may be located in or around building **10**. Airside system **300** may operate to heat or cool an airflow provided to building **10** using a heated or chilled fluid provided by waterside system **200**.

(30) In FIG. **3**, airside system **300** is shown to include an economizer-type air handling unit (AHU) **302**. Economizer-type AHUs vary the amount of outside air and return air used by the air handling unit for heating or cooling. For example, AHU **302** may receive return air **304** from building zone **306** via return air duct **308** and may deliver supply air **310** to building zone **306** via supply air duct **312**. In some embodiments, AHU **302** is a rooftop unit located on the roof of building **10** (e.g., AHU **106** as shown in FIG. **1**) or otherwise positioned to receive both return air **304** and outside air **314**. AHU **302** may be configured to operate exhaust air damper **316**, mixing damper **318**, and outside air damper **320** to control an amount of outside air **314** and return air **304** that combine to form supply air **310**. Any return air **304** that does not pass through mixing damper **318** may be exhausted from AHU **302** through exhaust damper **316** as exhaust air **322**.

(31) Each of dampers **316-320** may be operated by an actuator. For example, exhaust air damper **316** may be operated by actuator **324**, mixing damper **318** may be operated by actuator **326**, and outside air damper **320** may be operated by actuator **328**. Actuators **324-328** may communicate with an AHU controller **330** via a communications link **332**. Actuators **324-328** may receive control signals from AHU controller **330** and may provide feedback signals to AHU controller **330**. Feedback signals may include, for example, an indication of a current actuator or damper position, an amount of torque or force exerted by the actuator, diagnostic information (e.g., results of diagnostic tests performed by actuators **324-328**), status information, commissioning information, configuration settings, calibration data, and/or other types of information or data that may be collected, stored, or used by actuators **324-328**. AHU controller **330** may be an economizer controller configured to use one or more control algorithms (e.g., state-based algorithms, extremum seeking control (ESC) algorithms, proportional-integral (PI) control algorithms, proportional-integral-

derivative (PID) control algorithms, model predictive control (MPC) algorithms, feedback control algorithms, etc.) to control actuators **324-328**.

(32) Still referring to FIG. 3, AHU **302** is shown to include a cooling coil **334**, a heating coil **336**, and a fan **338** positioned within supply air duct **312**. Fan **338** may be configured to force supply air **310** through cooling coil **334** and/or heating coil **336** and provide supply air **310** to building zone **306**. AHU controller **330** may communicate with fan **338** via communications link **340** to control a flow rate of supply air **310**. In some embodiments, AHU controller **330** controls an amount of heating or cooling applied to supply air **310** by modulating a speed of fan **338**.

(33) Cooling coil **334** may receive a chilled fluid from waterside system **200** (e.g., from cold water loop **216**) via piping **342** and may return the chilled fluid to waterside system **200** via piping **344**. Valve **346** may be positioned along piping **342** or piping **344** to control a flow rate of the chilled fluid through cooling coil **334**. In some embodiments, cooling coil **334** includes multiple stages of cooling coils that can be independently activated and deactivated (e.g., by AHU controller **330**, by BAS controller **366**, etc.) to modulate an amount of cooling applied to supply air **310**.

(34) Heating coil **336** may receive a heated fluid from waterside system **200** (e.g., from hot water loop **214**) via piping **348** and may return the heated fluid to waterside system **200** via piping **350**. Valve **352** may be positioned along piping **348** or piping **350** to control a flow rate of the heated fluid through heating coil **336**. In some embodiments, heating coil **336** includes multiple stages of heating coils that can be independently activated and deactivated (e.g., by AHU controller **330**, by BAS controller **366**, etc.) to modulate an amount of heating applied to supply air **310**.

(35) Each of valves **346** and **352** may be controlled by an actuator. For example, valve **346** may be controlled by actuator **354** and valve **352** may be controlled by actuator **356**. Actuators **354-356** may communicate with AHU controller **330** via communications links **358-360**. Actuators **354-356** may receive control signals from AHU controller **330** and may provide feedback signals to controller **330**. In some embodiments, AHU controller **330** receives a measurement of the supply air temperature from a temperature sensor **362** positioned in supply air duct **312** (e.g., downstream of cooling coil **334** and/or heating coil **336**). AHU controller **330** may also receive a measurement of the temperature of building zone **306** from a temperature sensor **364** located in building zone **306**.

(36) In some embodiments, AHU controller **330** operates valves **346** and **352** via actuators **354-356** to modulate an amount of heating or cooling provided to supply air **310** (e.g., to achieve a setpoint temperature for supply air **310** or to maintain the temperature of supply air **310** within a setpoint temperature range). The positions of valves **346** and **352** affect the amount of heating or cooling provided to supply air **310** by cooling coil **334** or heating coil **336** and may correlate with the amount of energy consumed to achieve a desired supply air temperature. AHU controller **330** may control the temperature of supply air **310** and/or building zone **306** by activating or deactivating coils **334-336**, adjusting a speed of fan **338**, or a combination of both.

(37) Still referring to FIG. 3, airside system **300** is shown to include a building automation system (BAS) controller **366** and a client device **368**. BAS controller **366** may include one or more computer systems (e.g., servers, supervisory controllers, subsystem controllers, etc.) that serve as system level controllers, application or data servers, head nodes, or master controllers for airside system **300**, waterside system **200**, HVAC system **100**, and/or other controllable systems that serve building **10**. BAS controller **366** may communicate with multiple downstream building systems or subsystems (e.g., HVAC system **100**, a security system, a lighting system, waterside system **200**, etc.) via a communications link **370** according to like or disparate protocols (e.g., LON, BACnet, etc.). In various embodiments, AHU controller **330** and BAS controller **366** may be separate (as shown in FIG. 3) or integrated. In an integrated implementation, AHU controller **330** may be a software module configured for execution by a processor of BAS controller **366**.

(38) In some embodiments, AHU controller **330** receives information from BAS controller **366** (e.g., commands, setpoints, operating boundaries, etc.) and provides information to BAS controller **366** (e.g., temperature measurements, valve or actuator positions, operating statuses, diagnostics, etc.). For example, AHU controller **330** may provide BAS controller **366** with temperature measurements from temperature sensors **362-364**, equipment on/off states, equipment operating capacities, and/or any other information that can be used by BAS controller **366** to monitor or control a variable state or condition within building zone **306**.

(39) Client device **368** may include one or more human-machine interfaces or client interfaces (e.g., graphical user interfaces, reporting interfaces, text-based computer interfaces, client-facing web services, web servers that provide pages to web clients, etc.) for controlling, viewing, or otherwise interacting with HVAC system **100**, its subsystems, and/or devices. Client device **368** may be a computer workstation, a client terminal, a remote or local interface, or any other type of user interface device. Client device **368** may be a stationary terminal or a mobile device. For example, client device **368** may be a desktop computer, a computer server with a user interface, a laptop computer, a tablet, a smartphone, a PDA, or any other type of mobile or non-mobile device. Client device **368** may communicate with BAS controller **366** and/or AHU controller **330** via communications link **372**.

(40) Referring now to FIG. 4, a block diagram of a building automation system (BAS) **400** is shown, according to an exemplary embodiment. BAS **400** may be implemented in building **10** to automatically monitor and control various building functions. BAS **400** is shown to include BAS controller **366** and a plurality of building subsystems **428**.

Building subsystems **428** are shown to include a building electrical subsystem **434**, an information communication technology (ICT) subsystem **436**, a security subsystem **438**, a HVAC subsystem **440**, a lighting subsystem **442**, a lift/escalators subsystem **432**, and a fire safety subsystem **430**. In various embodiments, building subsystems **428** can include fewer, additional, or alternative subsystems. For example, building subsystems **428** may also or alternatively include a refrigeration subsystem, an advertising or signage subsystem, a cooking subsystem, a vending subsystem, a printer or copy service subsystem, or any other type of building subsystem that uses controllable equipment and/or sensors to monitor or control building **10**. In some embodiments, building subsystems **428** include waterside system **200** and/or airside system **300**, as described with reference to FIGS. 2-3.

(41) Each of building subsystems **428** may include any number of devices, controllers, and connections for completing its individual functions and control activities. HVAC subsystem **440** may include many of the same components as HVAC system **100**, as described with reference to FIGS. 1-3. For example, HVAC subsystem **440** may include a chiller, a boiler, any number of air handling units, economizers, field controllers, supervisory controllers, actuators, temperature sensors, and other devices for controlling the temperature, humidity, airflow, or other variable conditions within building **10**. Lighting subsystem **442** may include any number of light fixtures, ballasts, lighting sensors, dimmers, or other devices configured to controllably adjust the amount of light provided to a building space. Security subsystem **438** may include occupancy sensors, video surveillance cameras, digital video recorders, video processing servers, intrusion detection devices, access control devices and servers, or other security-related devices.

(42) Still referring to FIG. 4, BAS controller **366** is shown to include a communications interface **407** and a BAS interface **409**. Interface **407** may facilitate communications between BAS controller **366** and external applications (e.g., monitoring and reporting applications **422**, enterprise control applications **426**, remote systems and applications **444**, applications residing on client devices **448**, etc.) for allowing user control, monitoring, and adjustment to BAS controller **366** and/or subsystems **428**. Interface **407** may also facilitate communications between BAS controller **366** and client devices **448**. BAS interface **409** may facilitate communications between BAS controller **366** and building subsystems **428** (e.g., HVAC, lighting security, lifts, power distribution, business, etc.).

(43) Interfaces **407**, **409** can be or include wired or wireless communications interfaces (e.g., jacks, antennas, transmitters, receivers, transceivers, wire terminals, etc.) for conducting data communications with building subsystems **428** or other external systems or devices. In various embodiments, communications via interfaces **407**, **409** may be direct (e.g., local wired or wireless communications) or via a communications network **446** (e.g., a WAN, the Internet, a cellular network, etc.). For example, interfaces **407**, **409** can include an Ethernet card and port for sending and receiving data via an Ethernet-based communications link or network. In another example, interfaces **407**, **409** can include a WiFi transceiver for communicating via a wireless communications network. In another example, one or both of interfaces **407**, **409** may include cellular or mobile phone communications transceivers. In one embodiment, communications interface **407** is a power line communications interface and BAS interface **409** is an Ethernet interface. In other embodiments, both communications interface **407** and BAS interface **409** are Ethernet interfaces or are the same Ethernet interface.

(44) Still referring to FIG. 4, BAS controller **366** is shown to include a processing circuit **404** including a processor **406** and memory **408**. Processing circuit **404** may be communicably connected to BAS interface **409** and/or communications interface **407** such that processing circuit **404** and the various components thereof can send and receive data via interfaces **407**, **409**. Processor **406** can be implemented as a general purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable electronic processing components.

(45) Memory **408** (e.g., memory, memory unit, storage device, etc.) may include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage, etc.) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present application. Memory **408** may be or include volatile memory or non-volatile memory. Memory **408** may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present application. According to an exemplary embodiment, memory **408** is communicably connected to processor **406** via processing circuit **404** and includes computer code for executing (e.g., by processing circuit **404** and/or processor **406**) one or more processes described herein.

(46) In some embodiments, BAS controller **366** is implemented within a single computer (e.g., one server, one housing, etc.). In various other embodiments BAS controller **366** may be distributed across multiple servers or computers (e.g., that can exist in distributed locations). Further, while FIG. 4 shows applications **422** and **426** as existing outside of BAS controller **366**, in some embodiments, applications **422** and **426** may be hosted within BAS controller **366** (e.g., within memory **408**).

(47) Still referring to FIG. 4, memory **408** is shown to include an enterprise integration layer **410**, an automated measurement and validation (AM&V) layer **412**, a demand response (DR) layer **414**, a fault detection and diagnostics (FDD) layer **416**, an integrated control layer **418**, and a building subsystem integration later **420**. Layers **410-420** may be configured to receive inputs from building subsystems **428** and other data sources, determine optimal control actions for building subsystems **428** based on the inputs, generate control signals based on the optimal control actions,

and provide the generated control signals to building subsystems **428**. The following paragraphs describe some of the general functions performed by each of layers **410-420** in BAS **400**.

(48) Enterprise integration layer **410** may be configured to serve clients or local applications with information and services to support a variety of enterprise-level applications. For example, enterprise control applications **426** may be configured to provide subsystem-spanning control to a graphical user interface (GUI) or to any number of enterprise-level business applications (e.g., accounting systems, user identification systems, etc.). Enterprise control applications **426** may also or alternatively be configured to provide configuration GUIs for configuring BAS controller **366**. In yet other embodiments, enterprise control applications **426** can work with layers **410-420** to optimize building performance (e.g., efficiency, energy use, comfort, or safety) based on inputs received at interface **407** and/or BAS interface **409**.

(49) Building subsystem integration layer **420** may be configured to manage communications between BAS controller **366** and building subsystems **428**. For example, building subsystem integration layer **420** may receive sensor data and input signals from building subsystems **428** and provide output data and control signals to building subsystems **428**. Building subsystem integration layer **420** may also be configured to manage communications between building subsystems **428**. Building subsystem integration layer **420** translate communications (e.g., sensor data, input signals, output signals, etc.) across a plurality of multi-vendor/multi-protocol systems.

(50) Demand response layer **414** may be configured to optimize resource usage (e.g., electricity use, natural gas use, water use, etc.) and/or the monetary cost of such resource usage in response to satisfy the demand of building **10**. The optimization may be based on time-of-use prices, curtailment signals, energy availability, or other data received from utility providers, distributed energy generation systems **424**, from energy storage **427** (e.g., hot TES **242**, cold TES **244**, etc.), or from other sources. Demand response layer **414** may receive inputs from other layers of BAS controller **366** (e.g., building subsystem integration layer **420**, integrated control layer **418**, etc.). The inputs received from other layers may include environmental or sensor inputs such as temperature, carbon dioxide levels, relative humidity levels, air quality sensor outputs, occupancy sensor outputs, room schedules, and the like. The inputs may also include inputs such as electrical use (e.g., expressed in kWh), thermal load measurements, pricing information, projected pricing, smoothed pricing, curtailment signals from utilities, and the like.

(51) According to an exemplary embodiment, demand response layer **414** includes control logic for responding to the data and signals it receives. These responses can include communicating with the control algorithms in integrated control layer **418**, changing control strategies, changing setpoints, or activating/deactivating building equipment or subsystems in a controlled manner. Demand response layer **414** may also include control logic configured to determine when to utilize stored energy. For example, demand response layer **414** may determine to begin using energy from energy storage **427** just prior to the beginning of a peak use hour.

(52) In some embodiments, demand response layer **414** includes a control module configured to actively initiate control actions (e.g., automatically changing setpoints) which minimize energy costs based on one or more inputs representative of or based on demand (e.g., price, a curtailment signal, a demand level, etc.). In some embodiments, demand response layer **414** uses equipment models to determine an optimal set of control actions. The equipment models may include, for example, thermodynamic models describing the inputs, outputs, and/or functions performed by various sets of building equipment. Equipment models may represent collections of building equipment (e.g., subplants, chiller arrays, etc.) or individual devices (e.g., individual chillers, heaters, pumps, etc.).

(53) Demand response layer **414** may further include or draw upon one or more demand response policy definitions (e.g., databases, XML, files, etc.). The policy definitions may be edited or adjusted by a user (e.g., via a graphical user interface) so that the control actions initiated in response to demand inputs may be tailored for the user's application, desired comfort level, particular building equipment, or based on other concerns. For example, the demand response policy definitions can specify which equipment may be turned on or off in response to particular demand inputs, how long a system or piece of equipment should be turned off, what setpoints can be changed, what the allowable set point adjustment range is, how long to hold a high demand setpoint before returning to a normally scheduled setpoint, how close to approach capacity limits, which equipment modes to utilize, the energy transfer rates (e.g., the maximum rate, an alarm rate, other rate boundary information, etc.) into and out of energy storage devices (e.g., thermal storage tanks, battery banks, etc.), and when to dispatch on-site generation of energy (e.g., via fuel cells, a motor generator set, etc.).

(54) Integrated control layer **418** may be configured to use the data input or output of building subsystem integration layer **420** and/or demand response later **414** to make control decisions. Due to the subsystem integration provided by building subsystem integration layer **420**, integrated control layer **418** can integrate control activities of the subsystems **428** such that the subsystems **428** behave as a single integrated supersystem. In an exemplary embodiment, integrated control layer **418** includes control logic that uses inputs and outputs from a plurality of building subsystems to provide greater comfort and energy savings relative to the comfort and energy savings that separate subsystems could provide alone. For example, integrated control layer **418** may be configured to use an input from a first subsystem to make an energy-saving control decision for a second subsystem. Results of these decisions can be communicated back to building subsystem integration layer **420**.

(55) Integrated control layer **418** is shown to be logically below demand response layer **414**. Integrated control layer **418** may be configured to enhance the effectiveness of demand response layer **414** by enabling building subsystems **428** and their respective control loops to be controlled in coordination with demand response layer **414**. This configuration may advantageously reduce disruptive demand response behavior relative to conventional systems. For example, integrated control layer **418** may be configured to assure that a demand response-driven upward adjustment to the setpoint for chilled water temperature (or another component that directly or indirectly affects temperature) does not result in an increase in fan energy (or other energy used to cool a space) that would result in greater total building energy use than was saved at the chiller.

(56) Integrated control layer **418** may be configured to provide feedback to demand response layer **414** so that demand response layer **414** checks that constraints (e.g., temperature, lighting levels, etc.) are properly maintained even while demanded load shedding is in progress. The constraints may also include setpoint or sensed boundaries relating to safety, equipment operating limits and performance, comfort, fire codes, electrical codes, energy codes, and the like. Integrated control layer **418** is also logically below fault detection and diagnostics layer **416** and automated measurement and validation layer **412**. Integrated control layer **418** may be configured to provide calculated inputs (e.g., aggregations) to these higher levels based on outputs from more than one building subsystem.

(57) Automated measurement and validation (AM&V) layer **412** may be configured to verify that control strategies commanded by integrated control layer **418** or demand response layer **414** are working properly (e.g., using data aggregated by AM&V layer **412**, integrated control layer **418**, building subsystem integration layer **420**, FDD layer **416**, or otherwise). The calculations made by AM&V layer **412** may be based on building system energy models and/or equipment models for individual BAS devices or subsystems. For example, AM&V layer **412** may compare a model-predicted output with an actual output from building subsystems **428** to determine an accuracy of the model.

(58) Fault detection and diagnostics (FDD) layer **416** may be configured to provide on-going fault detection for building subsystems **428**, building subsystem devices (i.e., building equipment), and control algorithms used by demand response layer **414** and integrated control layer **418**. FDD layer **416** may receive data inputs from integrated control layer **418**, directly from one or more building subsystems or devices, or from another data source. FDD layer **416** may automatically diagnose and respond to detected faults. The responses to detected or diagnosed faults may include providing an alert message to a user, a maintenance scheduling system, or a control algorithm configured to attempt to repair the fault or to work-around the fault.

(59) FDD layer **416** may be configured to output a specific identification of the faulty component or cause of the fault (e.g., loose damper linkage) using detailed subsystem inputs available at building subsystem integration layer **420**. In other exemplary embodiments, FDD layer **416** is configured to provide “fault” events to integrated control layer **418** which executes control strategies and policies in response to the received fault events. According to an exemplary embodiment, FDD layer **416** (or a policy executed by an integrated control engine or business rules engine) may shut-down systems or direct control activities around faulty devices or systems to reduce energy waste, extend equipment life, or assure proper control response.

(60) FDD layer **416** may be configured to store or access a variety of different system data stores (or data points for live data). FDD layer **416** may use some content of the data stores to identify faults at the equipment level (e.g., specific chiller, specific AHU, specific terminal unit, etc.) and other content to identify faults at component or subsystem levels. For example, building subsystems **428** may generate temporal (i.e., time-series) data indicating the performance of BAS **400** and the various components thereof. The data generated by building subsystems **428** may include measured or calculated values that exhibit statistical characteristics and provide information about how the corresponding system or process (e.g., a temperature control process, a flow control process, etc.) is performing in terms of error from its setpoint. These processes can be examined by FDD layer **416** to expose when the system begins to degrade in performance and alert a user to repair the fault before it becomes more severe.

(61) BAS-BIM Integration

(62) Referring now to FIG. 5, a system **500** for integrating building automation system data with a building information model is shown, according to an exemplary embodiment. A building information model (BIM) is a representation of the physical and/or functional characteristics of a building. A BIM may represent structural characteristics of the building (e.g., walls, floors, ceilings, doors, windows, etc.) as well as the systems or components contained within the building (e.g., lighting components, electrical systems, mechanical systems, HVAC components, furniture, plumbing systems or fixtures, etc.).

(63) In some embodiments, a BIM is a 3D graphical model of the building. A BIM may be created using computer modeling software or other computer-aided design (CAD) tools and may be used by any of a plurality of entities that provide building-related services. For example, a BIM may be used by architects, contractors, landscape architects, surveyors, civil engineers, structural engineers, building services engineers, building owners/operators, or any other entity to obtain information about the building and/or the components contained therein. A BIM may replace 2D technical drawings (e.g., plans, elevations, sections, etc.) and may provide significantly more information than traditional 2D drawings. For example, a BIM may include spatial relationships, light analyses, geographic information, and/or qualities or properties of building components (e.g., manufacturer details).

(64) In some embodiments, a BIM represents building components as objects (e.g., software objects). For example, a BIM may include a plurality of objects that represent physical components within the building as well as building spaces. Each object may include a collection of attributes that define the physical geometry of the object, the type of object, and/or other properties of the object. For example, objects representing building spaces may define the size and location of the building space. Objects representing physical components may define the geometry of the physical component, the type of component (e.g., lighting fixture, air handling unit, wall, etc.), the location of the physical component, a material from which the physical component is constructed, and/or other attributes of the physical component.

(65) In some embodiments, a BIM includes an industry foundation class (IFC) data model that describes building and construction industry data. An IFC data model is an object-based file format that facilitates interoperability in the architecture, engineering, and construction industry. An IFC model may store and represent building components in terms of a data schema. An IFC model may include multiple layers and may include object definitions (e.g., IfcObjectDefinition), relationships (e.g., IfcRelationship), and property definitions (e.g., IfcPropertyDefinition). Object definitions may identify various objects in the IFC model and may include information such as physical placement, controls, and groupings. Relationships may capture relationships between objects such as composition, assignment, connectivity, association, and definition. Property definitions may capture dynamically extensible properties about objects. Any type of property may be defined as an enumeration, a list of values, a table of values, or a data structure.

(66) A BIM can be viewed and manipulated using a 3D modeling program (e.g., CAD software), a model viewer, a web browser, and/or any other software capable of interpreting and rendering the information contained within the BIM. Appropriate viewing software may allow a user to view the representation of the building from any of a variety of perspectives and/or locations. For example, a user can view the BIM from a perspective within the building to see how the building would look from that location. In other words, a user can simulate the perspective of a person within the building.

(67) Advantageously, the integration provided by system **500** allows dynamic BAS data (e.g., data points and their associated values) to be combined with the BIM. The integrated BIM with BAS data can be viewed using an integrated BAS-BIM viewer (e.g., CAD software, a CAD viewer, a web browser, etc.). The BAS-BIM viewer uses the geometric and location information from the BIM to generate 3D representations of physical components and building spaces. In some embodiments, the BAS-BIM viewer functions as a user interface for monitoring and controlling the various systems and devices represented in the integrated BIM. For example, a user can view real-time data from the BAS and/or trend data for objects represented in the BIM simply by viewing the BIM with integrated BAS data. The user can view BAS points, change the values of BAS points (e.g., setpoints), configure the BAS, and interact with the BAS via the BAS-BIM viewer. These features allow the BIM with integrated BAS data to be used as a building control interface which provides a graphical 3D representation of the building and the equipment contained therein without requiring a user to manually create or define graphics for various building components.

(68) Still referring to FIG. 5, system **500** is shown to include a BAS-BIM integrator **502**, an integrated BAS-BIM viewer **504**, a BIM database **506**, a user interface **508**, a BAS network **510**, and building equipment **512**. In some embodiments, some or all of the components of system **500** are part of BAS **400**. For example, BAS network **510** may be a building automation and control network (e.g., a BACnet network, a LonWorks network, etc.) used by BAS **400** to communicate with building equipment **512**. Building equipment **512** may include any of the equipment described with reference to FIGS. 1-4. For example, building equipment **512** may include HVAC equipment (e.g., chillers, boilers, air handling units pumps, fans, valves, dampers, etc.), fire safety equipment, lifts/escalators, electrical equipment, communications equipment, security equipment, lighting equipment, or any other type of equipment which may be contained within a building.

(69) In some embodiments, BAS-BIM integrator **502**, integrated BAS-BIM viewer **504**, BIM database **506**, and user interface **508** are components of BAS controller **366**. In other embodiments, one or more of components **502-508** may be components of a user device. For example, integrated BAS-BIM viewer **504** may be an application running on the user device and may be configured to present a BIM with integrated BAS points via a user interface (e.g., user interface **508**) of the user device. BAS-BIM integrator **502** may be part of the same application and may be configured to integrate BAS points with a BIM model based on user input provided via user interface **508**. In further embodiments, integrated BAS-BIM viewer **504** is part of a user device that receives a BIM with integrated BAS points from a remote BAS-BIM integrator **502**. It is contemplated that components **502-508** may be part of the same system/device (e.g., BAS controller **366**, a user device, etc.) or may be distributed across multiple systems/devices. All such embodiments are within the scope of the present disclosure.

(70) Still referring to FIG. 5, BAS-BIM integrator **502** is shown receiving a BIM and BAS points. In some embodiments, BAS-BIM integrator **502** receives a BIM from BIM database **506**. In other embodiments, the BIM is uploaded by a user or retrieved from another data source. BAS-BIM integrator **502** may receive BAS points from BAS network **510** (e.g., a BACnet network, a LonWorks network, etc.). The BAS points may be measured data points, calculated data points, setpoints, or other types of data points used by the BAS, generated by the BAS, or

stored within the BAS (e.g., configuration settings, control parameters, equipment information, alarm information, etc.).

(71) BAS-BIM integrator **502** may be configured to integrate the BAS points with the BIM. In some embodiments, BAS-BIM integrator **502** integrates the BAS points with the BIM based on a user-defined mapping. For example, BAS-BIM integrator **502** may be configured to generate a mapping interface presents the BAS points as a BAS tree and presents the BIM objects as a BIM tree. The BAS tree and the BIM tree may be presented to a user via user interface **508**. The mapping interface may allow a user to drag and drop BAS points onto objects of the BIM or otherwise define associations between BAS points and BIM objects. An exemplary mapping interface is described in greater detail with reference to FIG. **18**. In other embodiments, BAS-BIM integrator **502** automatically maps the BAS points to BIM objects based on attributes of the BAS points and the BIM objects (e.g., name, attributes, type, etc.).

(72) In some embodiments, BAS-BIM integrator **502** updates or modifies the BIM to include the BAS points. For example, BAS-BIM integrator **502** may store the BAS points as properties or attributes of objects within the BIM (e.g., objects representing building equipment or spaces). The modified BIM with integrated BAS points may be provided to integrated BAS-BIM viewer **504** and/or stored in BIM database **506**. When the BIM is viewed, the BAS points can be viewed along with the other attributes of the BIM objects. In other embodiments, BAS-BIM integrator **502** generates a mapping between BIM objects and BAS points without modifying the BIM. The mapping may be stored in a separate database or included within the BIM. When the BIM is viewed, integrated BAS-BIM viewer **504** may use the mapping to identify BAS points associated with BIM objects.

(73) Integrated BAS-BIM viewer **504** is shown receiving the BIM with integrated BAS points from BAS-BIM integrator **502**. Integrated BAS-BIM viewer **504** may generate a 3D graphical representation of the building and the components contained therein, according to the attributes of objects defined by the BIM. As previously described, the BIM objects may be modified to include BAS points. For example, some or all of the objects within the BIM may be modified to include an attribute identifying a particular BAS point (e.g., a point name, a point ID, etc.). When integrated BAS-BIM viewer **504** renders the BIM with integrated BAS points, integrated BAS-BIM viewer **504** may use the identities of the BAS points provided by the BIM to retrieve corresponding point values from BAS network **510**. Integrated BAS-BIM viewer **504** may incorporate the BAS point values within the BIM to generate a BIM with integrated BAS points and values.

(74) Integrated BAS-BIM viewer **504** is shown providing the BIM with integrated BAS points and values to user interface **508**. User interface **508** may present the BIM with integrated BAS points and values to a user. Advantageously, the BIM with integrated BAS points and values may include real-time data from BAS network **510**, as defined by the integrated BAS points. A user can monitor the BAS and view present values of the BAS points from within the BIM. In some embodiments, the BIM with integrated BAS points and values includes trend data for various BAS points. User interface **508** may display the trend data to a user along with the BIM.

(75) In some embodiments, integrated BAS-BIM viewer **504** receives control actions via user interface **508**. For example, a user can write new values for any of the BAS points displayed in the BIM (e.g., setpoints), send operating commands or control signals to the building equipment displayed in the BIM, or otherwise interact with the BAS via the BIM. Control actions submitted via user interface **508** may be received at integrated BAS-BIM viewer **504** and provided to BAS network **510**. BAS network **510** may use the control actions to generate control signals for building equipment **512** or otherwise adjust the operation of building equipment **512**. In this way, the BIM with integrated BAS points and values not only allows a user to monitor the BAS, but also provides the control functionality of a graphical BAS management and control interface. Several examples of the control interface provided by the BIM with integrated BAS points and values are described in greater detail with reference to FIGS. **9-18**.

(76) Referring now to FIG. **6**, a block diagram illustrating BAS-BIM integrator **502** in greater detail is shown, according to an exemplary embodiment. BAS-BIM integrator **502** is shown to include a BIM tree generator **606** and a BAS tree generator **604**. BIM tree generator **606** may be configured to receive a BIM from BIM database **506**. Alternatively, the BIM may be uploaded by a user or retrieved from another location. BIM tree generator **606** may generate a BIM tree based on the BIM. The BIM tree may include a hierarchical listing of BIM objects referenced in the BIM. BAS tree generator **604** may receive BAS points from the BAS and may generate a BAS tree based on the BAS points. The BAS tree may include a hierarchical listing of BAS points. Exemplary BAS and BIM trees are shown in FIG. **18**.

(77) BAS-BIM integrator **502** is shown to include a mapping interface generator **602**. Mapping interface generator **602** may be configured to generate an interface for mapping BAS points to BIM objects. In some embodiments, the mapping interface includes the BAS tree and BIM tree. For example, the BAS tree may be displayed in a first portion of the mapping interface and the BIM tree may be displayed in a second portion of the mapping interface. The mapping interface may be presented to a user via user interface **508**. A user can define point mappings by dragging and dropping BAS points from the BAS tree onto BIM objects in the BIM tree. Mapping interface generator **602** may receive the point mappings from user interface **508** and may provide the point mappings to BIM updater **608**. An exemplary mapping interface which may be generated by mapping interface generator **602** is shown in FIG. **18**.

(78) BIM updater **608** may be configured to update or modify the BIM based on the BAS point mappings. For

example, BIM updater **208** may store the BAS points as properties or attributes of objects within the BIM (e.g., objects representing building equipment or spaces). The modified BIM with integrated BAS points may be provided to integrated BAS-BIM viewer **504** and/or stored in BIM database **506**. When the BIM is viewed, the BAS points mapped to a BIM object can be viewed along with other attributes of the BIM objects.

(79) Referring now to FIG. 7, another system **700** for integrating building automation system data with a building information model is shown, according to an exemplary embodiment. System **700** is shown to include many of the same components as system **500**. For example, system **700** is shown to include a BAS-BIM integrator **502**, an integrated BAS-BIM viewer **504**, a BIM database **506**, a user interface **508**, a BAS network **510**, and building equipment **512**. These components may be the same or similar as previously described with reference to FIGS. 5-6.

(80) System **700** is also shown to include a point mappings database **702**. In the embodiment shown in FIG. 7, BAS-BIM integrator **502** does not modify the BIM to include the BAS points, but rather stores the point mappings in point mappings database **702**. When the BIM is viewed, integrated BAS-BIM viewer **504** may retrieve the BIM from BIM database **506** and may retrieve the point mappings from point mappings database **702**. Integrated BAS-BIM viewer **504** may use the point mappings to identify BAS points associated with the BIM objects.

(81) Integrated BAS-BIM viewer **504** may generate a 3D graphical representation of the building and the components contained therein, according to the attributes of objects defined by the BIM. When integrated BAS-BIM viewer **504** renders the BIM, integrated BAS-BIM viewer **504** may use the identities of the BAS points provided by the point mappings to retrieve corresponding point values from BAS network **510**. Integrated BAS-BIM viewer **504** may incorporate the BAS point values within the BIM to generate a BIM with integrated BAS points and values.

(82) Integrated BAS-BIM viewer **504** is shown providing the BIM with integrated BAS points and values to user interface **508**. User interface **508** may present the BIM with integrated BAS points and values to a user.

Advantageously, the BIM with integrated BAS points and values may include real-time data from BAS network **510**, as defined by the integrated BAS points. A user can monitor the BAS and view present values of the BAS points from within the BIM. In some embodiments, the BIM with integrated BAS points and values includes trend data for various BAS points. User interface **508** may display the trend data to a user along with the BIM.

(83) Referring now to FIG. 8, a block diagram of a BAS controller **802** is shown, according to an exemplary embodiment. In some embodiments, many of the components of systems **500-700** are components of BAS controller **802**. For example, BAS controller **802** is shown to include a BAS-BIM integrator **502**, an integrated BAS-BIM viewer **504**, a user interface **508**, a mapping interface generator **602**, a BAS tree generator **604**, a BIM tree generator **606**, and a point mappings database **702**. These components may be the same or similar as previously described with reference to FIGS. 5-7. Controller **802** may also include some or all of the components of BAS controller **366**, as described with reference to FIGS. 3-4.

(84) Controller **802** is shown to include a data communications interface **804** and a processing circuit **808**. Interface **804** may facilitate communications between BAS controller **802** and external systems or applications (e.g., BIM database **506**, BAS network **510**, building equipment **512**, a user device, etc.). Interface **804** may include wired or wireless communications interfaces (e.g., jacks, antennas, transmitters, receivers, transceivers, wire terminals, etc.) for conducting data communications with BIM database **506**, BAS network **510**, or other external systems or devices. In various embodiments, communications via interface **804** may be direct (e.g., local wired or wireless communications) or via a communications network (e.g., a WAN, the Internet, a cellular network, etc.). For example, interface **804** may include an Ethernet card and port for sending and receiving data via an Ethernet-based communications link or network. In another example, interface **804** may include a WiFi transceiver for communicating via a wireless communications network, a cellular or mobile phone communications transceiver, or a power line communications interface.

(85) Processing circuit **808** is shown to include a processor **810** and memory **812**. Processor **810** may be a general purpose or specific purpose processor, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. Processor **810** is configured to execute computer code or instructions stored in memory **812** or received from other computer readable media (e.g., CDROM, network storage, a remote server, etc.).

(86) Memory **812** may include one or more devices (e.g., memory units, memory devices, storage devices, etc.) for storing data and/or computer code for completing and/or facilitating the various processes described in the present disclosure. Memory **812** may include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions. Memory **812** may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. Memory **812** may be communicably connected to processor **810** via processing circuit **818** and may include computer code for executing (e.g., by processor **810**) one or more processes described herein. When processor **810** executes instructions stored in memory **812**, processor **810** generally configures BAS controller **802** (and more particularly processing circuit **808**) to complete such activities.

(87) Still referring to FIG. 8, memory **812** is shown to include a BIM selector **814**. BIM selector **814** may be

configured to receive a selected BIM from user **820**. In some embodiments, user **820** uploads the BIM to BAS controller **802**. In other embodiments, BIM selector **814** retrieves the BIM from BIM database **606**. BIM selector **814** may provide the BIM to BIM tree generator **606** for use in generating the BIM tree. In some embodiments, BIM selector **814** provides the BIM to integrated BAS-BIM viewer **504**. In other embodiments, BIM selector **814** provides the BIM tree to BAS-BIM point integrator **502**.

(88) BAS tree generator **604** may receive the BAS points from BAS network **810** via data communications interface **804** and may use the BAS points to generate a BAS tree. The BIM tree and the BAS tree may be provided to mapping interface generator **602**. Mapping interface generator **602** uses the BAS tree and BIM tree to generate a mapping interface. The mapping interface may be presented to user **820** via user interface **508**. The user interacts with the mapping interface to define point mappings. The point mappings may be stored in point mappings database **702** and/or used by BAS-BIM integrator **502** to modify the BIM.

(89) Integrated BAS-BIM viewer **504** may receive the point mappings from point mappings database and may use the point mappings to identify BAS points associated with BIM objects referenced in the BIM. In other embodiments, integrated BAS-BIM viewer **504** receives a BIM with integrated BAS points from BAS-BIM point integrator **502**, as described with reference to FIG. 5. Integrated BAS-BIM viewer **504** may retrieve corresponding point values from BAS network **510** via data communications interface **804**. Integrated BAS-BIM viewer **504** may then present the BIM with integrated BAS points and values to user **820** via user interface **508**.

(90) Still referring to FIG. 8, memory **812** is shown to include an alarm manager **816** and an equipment controller **818**. Alarm manager **816** may receive alarms from BAS network **510** or may identify alarms based on the values of the BAS points. For example, alarm manager **816** may compare the values of the BAS points to alarm thresholds. If a BAS point is not within a range of values defined by the alarm thresholds, alarm manager **816** may determine that an alarm condition exists for the BAS point. Alarm manager **816** may provide alarms to integrated BAS-BIM viewer **504**. Integrated BAS-BIM viewer **504** may use the alarms to generate part of the user interface provided to user **820**.

(91) Equipment controller **818** may receive control actions from integrated BAS-BIM viewer **504**. The control actions may be user-defined control actions provided via the integrated BAS-BIM viewing interface. Equipment controller **818** may use the control actions to generate control signals for building equipment **512** or otherwise adjust the operation of building equipment **512**. In this way, the BIM with integrated BAS points and values not only allows a user to monitor the BAS, but also provides the control functionality of a graphical BAS management and control interface. Several exemplary graphical interfaces which may be generated by integrated BAS-BIM viewer **504** are described in greater detail with reference to FIGS. 9-18.

(92) User Interfaces

(93) Referring now to FIGS. 9-18, several user interfaces **900-1800** which may be generated by BAS-BIM integrator **502** and integrated BAS-BIM viewer **504** are shown, according to an exemplary embodiment. In some embodiments, interfaces **900-1800** are web interfaces and may be presented via a web browser running on a user device. The user device may be a computer workstation, a client terminal, a personal computer, or any other type of user device. In various embodiments, the user device may be a mobile device (e.g., a smartphone, a tablet, a PDA, a laptop, etc.) or a non-mobile device. In other embodiments, interfaces **900-1800** are presented via a specialized monitoring and control application. The application may run on BAS controller **366**, on a computer system within BAS **400**, on a server, or on a user device. In some embodiments, the application is a mobile application configured to run on a mobile device.

(94) Referring particularly to FIG. 9, an integrated BAS-BIM viewer interface **900** is shown, according to an exemplary embodiment. Interface **900** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM with integrated BAS points and values. Interface **900** is shown to include a perspective view of a building **902**. Building **902** is shown to include walls **904**, a roof **906**, and windows **908**. The geometry and locations of components **904-906** may be defined by the BIM objects within the BIM model.

(95) Interface **900** may be interactive and may allow a user to view building **902** from multiple different angles and/or perspectives. For example, interface **900** may provide interface options for zooming in, zooming out, panning vertically or horizontally, rotating the view, and/or otherwise changing the perspective. View buttons **912** may be used to select a particular view (e.g., top, side, front, back, left, right, back, perspective, etc.) of building **902**. Navigation buttons **910** may be used to display a tree of BIM objects, filter the BIM objects (e.g., by type, by location, etc.), display any alarms provided by the BAS, or otherwise manipulate the view of building **902**. Search box **914** can be used to search for particular BIM objects, search for BAS points, search for a particular room or zone, and/or search for building equipment. Selecting an item via navigation buttons **910** or search box **914** may change the view of building **902** based on the user selection (e.g., to view a selected component, to hide components, etc.).

(96) Referring now to FIG. 10, another integrated BAS-BIM viewer interface **1000** is shown, according to an exemplary embodiment. Interface **1000** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM with integrated BAS points and values. Interface **1000** shows a view of building **902** from a location within building **902**. Interface **1000** is shown to include structural components of building **902** such as walls **1006**, floor **1008**, ceiling **1010**, and doors **1012**. Interface **1000** also displays HVAC components **1014** (e.g., air ducts), lighting components **1016** (e.g., lighting fixtures), electronic components **1018** (e.g., computer monitors), and

furniture **1200** (e.g., desks). The geometry and locations of components **1006-1020** may be defined by the BIM objects within the BIM model.

(97) Interface **1000** is shown to include an object tree **1002**. Object tree **1002** may be displayed in response to selecting tree button **1004**. Object tree **1002** includes a hierarchical representation of building **902** and the various spaces and components contained therein. For example, object tree **1002** is shown to include objects representing a campus, a particular building within the campus (e.g., Jolly Board Tower), levels within the building (e.g., level 0, level 1, level 2, etc.), and spaces/components within each level (e.g., conference rooms, offices, AHUs, etc.). Selecting any of the objects displayed in object tree **1002** may cause interface **1000** to display the selected object or change the view to show the selected object.

(98) Referring now to FIG. **11**, another integrated BAS-BIM viewer interface **1100** is shown, according to an exemplary embodiment. Interface **1100** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM with integrated BAS points and values. Interface **1100** is shown to include the same view of building **902** as shown in interface **1000**. The view can be changed by selecting view button **1102**. For example, selecting view button **1102** may cause view menu **1116** to be displayed. View menu **1116** is shown to include a perspective button **1104**, a side button **1106**, a top button **1108**, and a front button **1110**. Selecting any of buttons **1104-1110** may cause the view to change to the selected view. Selecting activity button **1118** may allow a user to change the view to simulate the perspective of a person walking through building **902**.

(99) Interface **1110** is shown to include a filter menu **1114**. Filter menu **1114** may be displayed in response to selecting filter button **1112**. Filter menu **1114** includes several categories of objects which can be selectively filtered by checking or unchecking the boxes associated with each category. For example, filter menu **1114** is shown to include the categories of architecture, HVAC, lighting, and plumbing. As shown in FIG. **11**, unchecking the box associated with the HVAC category causes the HVAC components **1014** to be hidden.

(100) Referring now to FIG. **12**, a BIM viewer interface **1200** is shown, according to an exemplary embodiment. Interface **1200** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM. Interface **1200** is shown to include a view of an air handling unit (AHU) **1202** within building **902**. In some embodiments, the view shown in FIG. **12** is displayed in response to selecting an object associated with AHU **1202** via object tree **1002**. For example, the object named “Outdoor AHU—Horizontal 1:6 Square Feet of Coil” can be selected via object tree **1002** to cause AHU **1202** to be displayed.

(101) Interface **1200** shows a view of AHU **1202** before the BAS points are integrated with the BIM. For example, selecting or hovering over AHU **1202** may cause information window **1204** to be displayed. Since no BAS points are yet associated with AHU **1202**, information window **1204** displays only the node name of AHU **1202**. Once BAS points are integrated with the BIM, information window **1204** may be modified to display any BAS points/values that have been mapped to the BIM object representing AHU **1202**.

(102) Referring now to FIG. **13**, another integrated BAS-BIM viewer interface **1300** is shown, according to an exemplary embodiment. Interface **1300** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM with integrated BAS points and values. Interface **1300** shows a view of AHU **1202** after BAS points have been integrated with the BIM. In addition to the information shown in interface **1200**, information window **1204** is shown to include several BAS points and the present values associated with each BAS point. The point names may be stored as attributes of the BIM and loaded when the BIM is viewed. The present values may be retrieved from the BAS network and displayed within information window **1204** when AHU **1202** is selected.

(103) Interface **1300** is shown to include a BAS information window **1302**. Window **1302** is shown to include several types of information retrieved from the BAS. For example, window **1302** is shown to include BAS points **1304** that have been mapped to AHU **1202**, an EFIRM link **1306**, technical details about AHU **1202** (e.g., a product data sheet, a catalogue, drawings, etc.), and work order information **1310** describing any work orders that have been performed or scheduled for AHU **1202**. Any faults associated with BAS points **1304** or AHU **1202** may be displayed in BAS information window **1302**. For example, if the BAS points “HTG-O” and “WC-ADJ” are out of range or otherwise indicate a fault condition, these BAS points may be highlighted in window **1302** (e.g., by coloring portion **1312** red or flashing the BAS points or present values, etc.). Advantageously, interface **1300** allows a user to see not only the BIM information, but also integrated BAS information on a single display.

(104) Referring now to FIG. **14**, another integrated BAS-BIM viewer interface **1400** is shown, according to an exemplary embodiment. Interface **1400** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM with integrated BAS points and values. Interface **1400** is shown to include a plurality of BAS points **1418** associated with AHU **1202** in object tree **1002**. BAS points **1418** may include any point from the BAS that has been mapped to the object associated with AHU **1202** (e.g., a humidity measurement, a temperature measurements, a temperature setpoint, etc.).

(105) Interface **1400** is shown to include a point information window **1402**. Point information window **1402** may be displayed in response to selecting a BAS point **1408** in object tree **1002**. For example, point information window **1402** may be displayed when the BAS point “FEC.ZN-H” is selected in object tree **1002**. Point information window **1402** is shown to include a trend data portion **1404**. Trend data portion **1404** may include a graph **1406** of past values

of the selected BAS point within a user-defined time range. A user can define the time range for which trend data is displayed by entering times via text boxes **1412**. Graph **1406** may include a history of past values and can be selected to display the value of the BAS point at any instant in time.

(106) Point information window **1402** may include an alarm limits portion **1408** and an alarm history portion **1410**. Alarm limits portion **1408** may allow a user to define alarm limits for the BAS point. If the BAS point does not fall within the alarm limits, the BAS point may be indicated as a fault. Alarm history portion **1410** may allow a user to view a history of alarms associated with the BAS point.

(107) Point information window **1402** may allow a user to write new values for the BAS point. For example, point information window **1402** is shown to include a text box **1416** which can be used to enter a user-defined value for the BAS point. Selecting write button **1414** may send the user-defined value to the BAS. This feature may be useful for adjusting a setpoint or calibrating a BAS point.

(108) Referring now to FIG. **15**, another integrated BAS-BIM viewer interface **1500** is shown, according to an exemplary embodiment. Interface **1500** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM with integrated BAS points and values. Interface **1500** is shown to include an alarms summary window **1504**. Window **1504** may be displayed in response to selecting alarms button **1502**. Alarms summary window **1504** is shown to include an indication of any alarms faults associated with the BAS points. Window **1504** may describe each alarm by identifying BAS point associated with the alarm (e.g., by point name), an alarm status (e.g., high or low), a description of the alarm (e.g., heating output), an item reference associated with the alarm, and a device type for the associated BAS point. In some embodiments, alarms summary window **1504** provides user interface options to perform automated fault diagnostics to detect an underlying fault associated with the alarms or to respond to alarms. Selecting an alarm in alarms summary window **1504** may change the view of the building so that the object associated with the alarm is shown (e.g., navigating to a portion of the building that includes the object, zooming in on the object, etc.). The object associated with the alarm may be highlighted in the view of the building (e.g., colored red, flashing, etc.) so that the user can easily identify the object in the view window.

(109) Referring now to FIG. **16**, another integrated BAS-BIM viewer interface **1600** is shown, according to an exemplary embodiment. Interface **1600** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM with integrated BAS points and values. Interface **1600** is shown to include a trend window **1602**, which may be displayed in response to a user selecting trend button **1610**. Trend window **1602** may be configured to display trend data for multiple BAS points on the same graph. For example, trend window **1602** is shown displaying trend data for the BAS points “FEC.ZN-Q” and “FEC.WC-ADJ” concurrently on the same graph. Advantageously, trend window **1602** may display trend data (e.g., time series data) for all of the BAS points mapped to a particular BIM object in a single display without requiring any additional user input or configuration to identify the BAS points. BAS points can be displayed or removed from the graph by selecting or deselecting point labels **1608**. In some embodiments, interface **1600** includes a time range selector **1606** which allows a user to define the start time and the end time for the trend data displayed in trend window **1602**. In some embodiments, interface **1600** includes a value display box **1604** which displays values for one or more of the BAS points shown in the graph at a particular instant in time. A user can select or hover over a portion of the graph to specify the instant in time for which the data values are displayed.

(110) Referring now to FIG. **17**, another integrated BAS-BIM viewer interface **1700** is shown, according to an exemplary embodiment. Interface **1700** may be generated by integrated BAS-BIM viewer **504** to view and interact with a BIM with integrated BAS points and values. Interface **1700** is shown to include a search box **914**. Search box **914** can be used to search for particular BIM objects, BAS points, particular rooms or zones, building equipment, or other objects or data points that match a user-defined search term. Interface **1700** may be configured to search BAS point names, BIM object names, BIM object attributes, or other items included in the integrated BIM model. Results of the search may be displayed in search results list **1702**. Selecting an item in search results list **1702** may change the view of building **902** based on the user selection (e.g., to view a selected object or an object associated with a selected BAS point).

(111) Referring now to FIG. **18**, a point mapping interface **1800** is shown, according to an exemplary embodiment. Interface **1800** may be generated by integrated BAS-BIM integrator **502** to map BAS points to BIM objects. Interface **1800** may allow a user to identify a BIM or upload a BIM (e.g., by selecting upload button **1806**). The uploaded BIM may be used to generate a BIM tree **1804**, which may include a hierarchical listing of BIM objects. Interface **1800** may automatically identify a corresponding BAS and retrieve a BAS tree **1802** from the BAS network. Interface **1800** may allow a user to rename the identified BAS and/or identify a different BAS (e.g., by entering a campus name **1808**, building name **1810**, etc.). The identified BAS may be used to generate a BAS tree **1802**, which may include a hierarchical listing of BAS points. A user can define a mapping between BAS points and BIM objects by dragging and dropping BAS points from BAS tree **1802** onto BIM objects in BIM tree **1804**. In some embodiments, the point mappings are stored in a point mappings database. In other embodiments, the mapped BAS points are stored as attributes or properties of the BIM object to which the BAS points are mapped.

(112) Changes to the building or point mappings can be made by uploading a new BIM. For example, if a BAS device

is moved from one room in the building, an updated BIM reflecting the change can be uploaded via point mapping interface **1800**. Point mapping interface **1800** may be configured to retrieve a previous point mapping from the point mappings database and automatically apply the point mappings to the updated BIM (e.g., by selecting “keep record” button **1812**). Advantageously, this feature allows the point mappings to be updated and applied to new versions of the BIM without requiring a user to redefine the point mappings.

(113) BAS-BIM Integration Process

(114) Referring now to FIG. **19**, a flowchart of a process **1900** for generating and using a BIM with integrated BAS points is shown, according to an exemplary embodiment. Process **1900** may be performed by one or more components of system **500**, system **700**, or controller **800**, as described with reference to FIGS. **5-8**.

(115) Process **1900** is shown to include receiving a building information model (BIM) (step **1902**). The BIM may include a plurality of BIM objects representing building equipment. In some embodiments, the BIM includes a three-dimensional model of the building. The BIM objects may include one or more objects representing structural components of the building and one or more objects representing spaces within the building.

(116) Process **1900** is shown to include collecting building automation system (BAS) points from a BAS network (step **1904**). The BAS network may include a BACnet network, a LonWorks network, or any other network configured to facilitate communications between building equipment. The BAS points may be measured data points, calculated data points, setpoints, or other types of data points used by the BAS, generated by the BAS, or stored within the BAS (e.g., configuration settings, control parameters, equipment information, alarm information, etc.). In some embodiments, step **1904** includes retrieving corresponding point values from the BAS network. The point values may include at least one of values measured by the building equipment, values generated by the building equipment, setpoints for the building equipment, and operating parameters for the building equipment.

(117) Process **1900** is shown to include integrating the BAS points with the BIM (step **1906**). In some embodiments, step **1906** includes generating a BAS tree that includes the BAS points, generating a BIM tree that includes the BIM objects, and generating a mapping interface that includes the BAS tree and the BIM tree. Step **1906** may include establishing mappings between the BAS points and the BIM objects based on a user input received via the mapping interface. For example, the user input may include dragging and dropping the BAS points from the BAS tree onto BIM objects in the BIM tree. In some embodiments, step **1906** includes storing mappings between the BAS points and the BIM objects in a mappings database.

(118) Process **1900** is shown to include using the BIM with the integrated BAS points to generate a user interface including a graphical representation of the BIM objects and the BAS points (step **1908**). Several examples of user interfaces that may be generated in step **1908** are described with reference to FIGS. **9-18**. The user interface may be viewed using an integrated BAS-BIM viewer (e.g., CAD software, a CAD viewer, a web browser, etc.). The BAS-BIM viewer uses the geometric and location information from the BIM to generate 3D representations of physical components and building spaces. Advantageously, a user can view real-time data from the BAS and/or trend data for objects represented in the BIM simply by viewing the BIM with integrated BAS data.

(119) Process **1900** is shown to include detecting a control action received via the user interface (step **1910**) and using the control action to generate a control signal for the building equipment (step **1912**). In some embodiments, the user interface is an interactive interface that allows the user to view BAS points, change the values of BAS points (e.g., setpoints), configure the BAS, and/or interact with the BAS via the user interface. For example, the user can write new values for any of the BAS points displayed in the BIM (e.g., setpoints), send operating commands or control signals to the building equipment displayed in the BIM, or otherwise interact with the BAS via the BIM.

(120) Control actions submitted via the user interface may be provided to the BAS network. The BAS network may use the control actions to generate control signals for the building equipment or otherwise adjust the operation of the building equipment. In this way, the BIM with integrated BAS points and values not only allows a user to monitor the BAS, but also provides the control functionality of a graphical BAS management and control interface. These features allow the BIM with integrated BAS data to be used as a building control interface which provides a graphical 3D representation of the building and the equipment contained therein without requiring a user to manually create or define graphics for various building components.

Configuration of Exemplary Embodiments

(121) The construction and arrangement of the systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements may be reversed or otherwise varied and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

(122) The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

(123) Although the figures show a specific order of method steps, the order of the steps may differ from what is depicted. Also two or more steps may be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule based logic and other logic to accomplish the various connection steps, processing steps, comparison steps and decision steps.

(124) The background section is intended to provide a background or context to the invention recited in the claims. The description in the background section may include concepts that could be pursued, but are not necessarily ones that have been previously conceived or pursued. Therefore, unless otherwise indicated herein, what is described in the background section is not prior art to the present invention and is not admitted to be prior art by inclusion in the background section.

Claims

1. A building system of a building comprising one or more storage media having instructions stored thereon that, when executed by one or more processors, cause the one or more processors to: generate a plurality of mappings between a plurality of points of a building automation system (BAS) network for a plurality of pieces of building equipment and a plurality of graphic representations of the plurality of pieces of building equipment of a building information model (BIM), wherein the plurality of mappings map a point of the plurality of points of a piece of building equipment of the plurality of pieces of building equipment with a graphic representation of the piece of building equipment of the plurality of graphic representations; cause a user device to display an interface comprising: a graphic element comprising point names of the plurality of points mapped to the plurality of pieces of building equipment, wherein the graphic element comprises a hierarchical representation of the building, the hierarchical representation comprising a plurality of levels, wherein: a first level of the plurality of levels includes an indication of a floor of the building; a second level that depends from the first level includes an indication of the piece of building equipment, wherein the second level depending from the first level indicates that the piece of building equipment is located on the floor; and a third level depending from the second level including an indication of the point, wherein the third level depending from the second level indicates that the piece of building equipment includes the point; and a view of the BIM including at least one of the plurality of graphic representations of the plurality of pieces of building equipment; receive, via the graphic element, a selection of the point of the plurality of points, the point mapped to the graphic representation of the piece of building equipment; and modify, based on the plurality of mappings and the selection, the view of the BIM to display the graphic representation of the piece of building equipment mapped to the point.
2. The building system of claim 1, wherein the graphic element comprises a plurality of rows representing the plurality of points, wherein a row of the plurality of rows comprises: a name of the point; and an alarm indicator for the point, the alarm indicator based on values of the point; wherein the instructions cause the one or more processors to: receive, via the graphic element, the selection of the point of the plurality of points by receiving the selection of the row.
3. The building system of claim 1, wherein the instructions cause the one or more processors to: receive, via the graphic element, the selection of the point of the plurality of points by receiving the selection of the third level.
4. The building system of claim 1, wherein the graphic element is located below the view of the BIM within the interface.
5. The building system of claim 1, wherein the graphic element is located on a left side or a right side of the view of the BIM within the interface.
6. The building system of claim 1, wherein the instructions cause the one or more processors to: store technical detail

information for the piece of building equipment in the one or more storage media; and cause the view of the BIM to include the technical detail information in a particular location within the view of the BIM associated with the graphic representation of the piece of building equipment responsive to the selection.

7. The building system of claim 1, wherein the instructions cause the one or more processors to: generate, based on at least a portion of the plurality of mappings, an alarm for the piece of building equipment based on a plurality of values of the point of the plurality of points mapped to the piece of building equipment by the portion of the plurality of mappings and an alarm rule for the piece of building equipment.

8. The building system of claim 1, wherein the instructions cause the one or more processors to: receive, via the user device, a configuration of an alarm rule, the alarm rule and the configuration defining generation of an alarm for the piece of building equipment; and generate, based on at least a portion of the plurality of mappings, the alarm for the piece of building equipment based on the configuration of the alarm rule.

9. The building system of claim 1, wherein the instructions cause the one or more processors to: retrieve, based on the plurality of mappings, a plurality of values of the point from the one or more storage media responsive to receiving the selection; and generate data causing the interface to include an element comprising a trend for the point based on the plurality of values of the point.

10. The building system of claim 1, wherein the instructions cause the one or more processors to: generate a window responsive to the selection, the window comprising: a graph including a trend line of a plurality of values of the point, the graph comprising a vertical axis indicating the plurality of values and a horizontal axis indicating time; and a time range element providing a selection of a time range from a starting time to an ending time; receive, via the time range element of the window, a particular time range including a particular starting time and a particular ending time; and cause the graph to display the trend line from the particular starting time to the particular ending time.

11. A method comprising: generating, by one or more processing circuits, a plurality of mappings between a plurality of points of a building automation system (BAS) network of a building for a plurality of pieces of building equipment and a plurality of graphic representations of the plurality of pieces of building equipment of a building information model (BIM), wherein the plurality of mappings map a point of the plurality of points of a piece of building equipment of the plurality of pieces of building equipment with a graphic representation of the piece of building equipment of the plurality of graphic representations; causing, by the one or more processing circuits, a user device to display an interface comprising: a graphic element comprising point names of the plurality of points mapped to the plurality of pieces of building equipment, wherein the graphic element comprises a hierarchical representation of the building, the hierarchical representation comprising a plurality of levels, wherein: a first level of the plurality of levels includes an indication of a floor of the building; a second level that depends from the first level includes an indication of the piece of building equipment, wherein the second level depending from the first level indicates that the piece of building equipment is located on the floor; and a third level depending from the second level including an indication of the point, wherein the third level depending from the second level indicates that the piece of building equipment includes the point; and a view of the BIM including at least one of the plurality of graphic representations of the plurality of pieces of building equipment; receiving, by the one or more processing circuits, via the graphic element, a selection of the point of the plurality of points, the point mapped to the graphic representation of the piece of building equipment; and modifying, by the one or more processing circuits, based on the plurality of mappings and the selection, the view of the BIM to display the graphic representation of the piece of building equipment mapped to the point.

12. The method of claim 11, wherein the graphic element comprises a plurality of rows representing the plurality of points, wherein a row of the plurality of rows comprises: a name of the point; and an alarm indicator for the point, the alarm indicator based on values of the point; wherein the method comprises: receiving, by the one or more processing circuits, via the graphic element, the selection of the point of the plurality of points by receiving the selection of the row.

13. The method of claim 11, wherein receiving, by the one or more processing circuits, via the graphic element, the selection of the point of the plurality of points comprises receiving the selection of the third level.

14. The method of claim 11, further comprising: storing, by the one or more processing circuits, technical detail information for the piece of building equipment in one or more storage media; and causing, by the one or more processing circuits, the view of the BIM to include the technical detail information in a particular location within the view of the BIM associated with the graphic representation of the piece of building equipment responsive to the selection.

15. The method of claim 11, further comprising: generating, by the one or more processing circuits, based on at least a portion of the plurality of mappings, an alarm for the piece of building equipment based on a plurality of values of the point of the plurality of points mapped to the piece of building equipment by the portion of the plurality of mappings and an alarm rule for the piece of building equipment.

16. The method of claim 11, further comprising: receiving, by the one or more processing circuits, via the user device, a configuration of an alarm rule, the alarm rule and the configuration defining generation of an alarm for the piece of building equipment; and generating, by the one or more processing circuits, based on at least a portion of the plurality

of mappings, the alarm for the piece of building equipment based on the configuration of the alarm rule.

17. The method of claim 11, further comprising: retrieving, by the one or more processing circuits, based on the plurality of mappings, a plurality of values of the point from one or more storage media responsive to receiving the selection; and generating, by the one or more processing circuits, data causing the interface to include an element comprising a trend for the point based on the plurality of values of the point.

18. The method of claim 11, further comprising: generating, by the one or more processing circuits, a window responsive to the selection, the window comprising: a graph including a trend line of a plurality of values of the point, the graph comprising a vertical axis indicating the plurality of values and a horizontal axis indicating time; and a time range element providing a selection of a time range from a starting time to an ending time; receiving, by the one or more processing circuits, via the time range element of the window, a particular time range including a particular starting time and a particular ending time; and causing, by the one or more processing circuits, the graph to display the trend line from the particular starting time to the particular ending time.

19. One or more storage media having instructions stored thereon that, when executed by one or more processors, cause the one or more processors to: generate a plurality of mappings between a plurality of points of a building automation system (BAS) network of a building for a plurality of pieces of building equipment and a plurality of graphic representations of the plurality of pieces of building equipment of a building information model (BIM), wherein the plurality of mappings map a point of the plurality of points of a piece of building equipment of the plurality of pieces of building equipment with a graphic representation of the piece of building equipment of the plurality of graphic representations; cause a user device to display an interface comprising: a graphic element comprising point names of the plurality of points mapped to the plurality of pieces of building equipment, wherein the graphic element comprises a hierarchical representation of the building, the hierarchical representation comprising a plurality of levels, wherein: a first level of the plurality of levels includes an indication of a floor of the building; a second level that depends from the first level includes an indication of the piece of building equipment, wherein the second level depending from the first level indicates that the piece of building equipment is located on the floor; and a third level depending from the second level including an indication of the point, wherein the third level depending from the second level indicates that the piece of building equipment includes the point; and a view of the BIM including at least one of the plurality of graphic representations of the plurality of pieces of building equipment; receive, via the graphic element, a selection of the point of the plurality of points, the point mapped to the graphic representation of the piece of building equipment; and modify, based on the plurality of mappings and the selection, the view of the BIM to display the graphic representation of the piece of building equipment mapped to the point.

20. The one or more storage media of claim 19, wherein the graphic element comprises a plurality of rows representing the plurality of points, wherein a row of the plurality of rows comprises: a name of the point; and an alarm indicator for the point, the alarm indicator based on values of the point; wherein the instructions cause the one or more processors to: receive, via the graphic element, the selection of the point of the plurality of points by receiving the selection of the row.
