

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405716
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Blohowiak; Aaron Peter et al.

Systems and methods for automatic formatting of images for media assets based on user profile

Abstract

Systems and methods are provided herein for personalizing images that correspond to a media asset identifier by using user profile information. As an example, the television series “Community” has several actors, such as Joel McHale, Chevy Chase, and Ken Jeong. Poster art developed by an editor o50533238_1f “Community” may include an image that portrays each of Joel McHale, Chevy Chase, and Ken Jeong. In order to personalize the image, control circuitry may determine which actor(s) the user prefers, and crop out only those actors in the poster art to create a personalized image. As an example, if the user prefers Joel McHale, control circuitry may crop out the portrayal of Joel McHale and use only that portion of the image to display next to other text describing “Community.”

Inventors: Blohowiak; Aaron Peter (Belmont, CA), Klappert; Walter R. (North Hollywood, CA), Nichols; Michael R. (La Canada Flintridge, CA), Chalouhi; Olivier (Mountain View, CA)

Applicant: Adeia Guides Inc. (San Jose, CA)

Family ID: 57602316

Assignee: Adeia Guides Inc. (San Jose, CA)

Appl. No.: 18/500928

Filed: November 02, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240152260 A1	May. 09, 2024

Related U.S. Application Data

continuation parent-doc US 17949663 20220921 US 11842040 child-doc US 18500928
continuation parent-doc US 16816094 20200311 US 11481095 20221025 child-doc US 17949663
continuation parent-doc US 14752031 20150626 US 10628009 20200421 child-doc US 16816094

Publication Classification

Int. Cl.: **G06F3/04845** (20220101); **G06F3/0481** (20220101); **G06F3/04842** (20220101);
G06F3/14 (20060101); **G06F16/78** (20190101); **G06T11/60** (20060101); **G09G5/00**
(20060101); **G09G5/14** (20060101)

U.S. Cl.:

CPC **G06F3/04845** (20130101); **G06F3/0481** (20130101); **G06F3/04842** (20130101);
G06F3/14 (20130101); **G06F3/1415** (20130101); **G06F16/78** (20190101); **G06T11/60**
(20130101); **G09G5/003** (20130101); **G09G5/14** (20130101); G06T2210/22 (20130101);
G09G2320/08 (20130101)

Field of Classification Search

CPC: G06F (3/04845); G06F (16/78); G06F (3/0481); G06F (3/04842); G06F (3/14); G06F
(3/1415); G06T (11/60); G06T (2210/22); G09G (5/003); G09G (5/14); G09G (2320/08)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5850352	12/1997	Moezzi et al.	N/A	N/A
6239794	12/2000	Yuen et al.	N/A	N/A
6388714	12/2001	Schein et al.	N/A	N/A
6564378	12/2002	Satterfield et al.	N/A	N/A
6756997	12/2003	Ward et al.	N/A	N/A
7165098	12/2006	Boyer et al.	N/A	N/A
7334249	12/2007	Byers	N/A	N/A
7761892	12/2009	Ellis et al.	N/A	N/A
7916894	12/2010	Dhillon et al.	N/A	N/A
8023702	12/2010	Momosaki et al.	N/A	N/A
8046801	12/2010	Ellis et al.	N/A	N/A
8594488	12/2012	Grundmann et al.	N/A	N/A
9591359	12/2016	Blohowiak et al.	N/A	N/A
10628009	12/2019	Blohowiak et al.	N/A	N/A
11481095	12/2021	Blohowiak	N/A	G06F 3/04842
11842040	12/2022	Blohowiak	N/A	G06F 16/78
2002/0083091	12/2001	Pulier et al.	N/A	N/A
2002/0174430	12/2001	Ellis et al.	N/A	N/A
2003/0051256	12/2002	Uesaki et al.	N/A	N/A
2003/0110499	12/2002	Knudson et al.	N/A	N/A
2004/0059705	12/2003	Wittke et al.	N/A	N/A

2005/0078220	12/2004	Sullivan	N/A	N/A
2005/0166224	12/2004	Ficco	N/A	N/A
2005/0251827	12/2004	Ellis et al.	N/A	N/A
2006/0044446	12/2005	Porter et al.	N/A	N/A
2007/0172155	12/2006	Guckenberger	N/A	N/A
2007/0244902	12/2006	Seide	N/A	G06F 16/78
2008/0313233	12/2007	Cohen et al.	N/A	N/A
2009/0022422	12/2008	Sorek	382/284	H04N 1/3876
2009/0049467	12/2008	Robson et al.	N/A	N/A
2009/0066784	12/2008	Stone et al.	N/A	N/A
2009/0106699	12/2008	Kihara et al.	N/A	N/A
2010/0153885	12/2009	Yates	N/A	N/A
2011/0131241	12/2010	Petrou et al.	N/A	N/A
2011/0160886	12/2010	Lee et al.	N/A	N/A
2011/0225610	12/2010	Prieto	N/A	N/A
2011/0321096	12/2010	Landow et al.	N/A	N/A
2012/0213493	12/2011	Luo et al.	N/A	N/A
2012/0218297	12/2011	Ur	N/A	N/A
2012/0308192	12/2011	Chung et al.	N/A	N/A
2013/0016128	12/2012	Bhatt	N/A	N/A
2013/0063561	12/2012	Stephan	N/A	N/A
2013/0254825	12/2012	Mishra	N/A	N/A
2013/0268306	12/2012	Tai et al.	N/A	N/A
2014/0044358	12/2013	Srinivasan	382/190	G06Q 10/10
2014/0086556	12/2013	Yoshida	386/241	H04N 9/79
2014/0164365	12/2013	Graham	N/A	N/A
2014/0172881	12/2013	Petrou et al.	N/A	N/A
2014/0282660	12/2013	Oztascent et al.	N/A	N/A
2015/0213305	12/2014	Sundstrm	N/A	N/A
2015/0264416	12/2014	Heinz et al.	N/A	N/A
2015/0304521	12/2014	Campanelli et al.	N/A	N/A
2015/0317805	12/2014	Kagitani	382/162	G06T 11/001
2015/0326892	12/2014	McCoy et al.	N/A	N/A
2015/0373414	12/2014	Kinoshita	386/282	G06V 40/172
2016/0035347	12/2015	Agarwal et al.	N/A	N/A
2016/0092447	12/2015	Venkataraman et al.	N/A	N/A
2016/0094889	12/2015	Venkataraman et al.	N/A	N/A
2016/0100110	12/2015	Mate et al.	N/A	N/A
2016/0119488	12/2015	Chen et al.	N/A	N/A
2016/0179796	12/2015	Agarwal	N/A	N/A
2016/0378307	12/2015	Blohowiak et al.	N/A	N/A
2016/0378308	12/2015	Blohowiak et al.	N/A	N/A
2016/0381420	12/2015	Blohowiak et al.	N/A	N/A
2017/0238056	12/2016	Greene et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102637255	12/2011	CN	N/A
102822817	12/2011	CN	N/A
103034841	12/2012	CN	N/A

103197931	12/2012	CN	N/A
2003179908	12/2002	JP	N/A
2007174378	12/2006	JP	N/A
2008015854	12/2007	JP	N/A
2008165700	12/2007	JP	N/A
2008271268	12/2007	JP	N/A
2009089065	12/2008	JP	N/A
2009296346	12/2008	JP	N/A
2010103764	12/2009	JP	N/A
2010154342	12/2009	JP	N/A
2012003433	12/2011	JP	N/A
2012044358	12/2011	JP	N/A
2013501975	12/2012	JP	N/A
2014194020	12/2013	WO	N/A
2014194020	12/2013	WO	N/A

OTHER PUBLICATIONS

International Search Report and Written Opinion for PCT/US2016/038897 dated Sep. 12, 2016.
cited by applicant

YouTube video by: Karenzuelalulz; published on Jun. 21, 2009: <https://www.youtube.com/watch?v=MhpTDarr6c8> (examiner printed (Jul. 11, 2017) NPL pdf pp. 1-4; file named YouTube_karenzuelalulz). cited by applicant

Primary Examiner: Chae; Kyu

Attorney, Agent or Firm: Haley Guiliano LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) (1) This is a continuation of U.S. patent application Ser. No. 17/949,663, filed Sep. 21, 2022, which is a continuation of U.S. patent application Ser. No. 16/816,094, filed on Mar. 11, 2020, now U.S. Pat. No. 11,481,095, which is a continuation of U.S. patent application Ser. No. 14/752,031, filed on Jun. 26, 2015, now U.S. Pat. No. 10,628,009. The disclosures of the foregoing applications are hereby incorporated by reference in their entireties.

BACKGROUND

(1) As media guidance applications proliferate and become more ubiquitous, images are used to illustrate media assets that may be of interest to a user. For example, box art or poster art corresponding to a particular movie may be displayed adjacent to text describing that particular movie. This box art or poster art is selected for display based solely on a corresponding media asset, and is not personalized.

SUMMARY

(2) Systems and methods are provided herein for personalizing images that correspond to a media asset identifier by using user profile information. As an example, the television series “Community” has several actors, such as Joel McHale, Chevy Chase, and Ken Jeong. Poster art developed by an editor of “Community” may include an image that portrays each of Joel McHale, Chevy Chase, and Ken Jeong. In order to personalize the image, control circuitry may determine which actor(s) the user prefers, and crop out only those actors in the poster art to create a

personalized image. As an example, if the user prefers Joel McHale, control circuitry may crop out the portrayal of Joel McHale and use only that portion of the image to display next to other text describing “Community.”

(3) To achieve these ends and others, systems and methods are provided herein for selectively generating for display portions of an image based on a user profile. In some aspects, these systems and methods comprise control circuitry identifying an image corresponding to a media asset, where the image comprises a plurality of portions, and where each portion of the plurality of portions comprises a respective entity. For example, control circuitry may identify a poster, picture, box art, and/or the like, that corresponds to a media asset, such as the hit series “Community” starring actors Joel McHale, Chevy Chase, and Ken Jeong. The image identified by control circuitry may include several portions, where each portion includes a respective entity. For example, control circuitry may determine that the image portrays each of Joel McHale, Chevy Chase, and Ken Jeong, and control circuitry may demark each portion that contains each separate actor as a separate portion of the image.

(4) In some embodiments, control circuitry may determine an identity of each respective entity in each respective portion of the plurality of portions. Following the example from above, control circuitry may determine that one portion includes Joel McHale, another portion includes Chevy Chase, and another portion includes Ken Jeong. Control circuitry may make these determinations based on image recognition algorithms, by consulting metadata corresponding to the image, or by any other known mechanism.

(5) In some embodiments, control circuitry may access a user profile from a database. For example, control circuitry may query a remote or local database to access a user profile that corresponds to a present user of a user equipment that control circuitry is implemented in or associated with. Control circuitry may, responsive to the query, receive information from the user profile.

(6) In some embodiments, control circuitry may cross-reference metadata of the user profile with each identity of each respective entity from the image. For example, control circuitry may compare information of the user profile with information corresponding to each entity represented in the image. Following from the example above, control circuitry may cross-reference information indicating user preferences from the user profile against metadata corresponding to each of Joel McHale, Ken Jeong, and Chevy Chase, in an effort to determine which actor(s) the user may prefer. Control circuitry may then identify a preferred entity based on the cross-referencing.

(7) In some embodiments, control circuitry may generate for display the respective portion comprising the preferred entity. For example, control circuitry may crop one or more entities that the user prefers from the original image and display the cropped image in place of the original image. Doing so may cause an image that a user is more likely to prefer to be displayed.

(8) In some embodiments, when control circuitry generates for display the respective portion, control circuitry may crop the image to include less than the entire image and to include the preferred entity. Control circuitry may crop the image by removing portions of the image that do not include the preferred entity. Any known means of image cropping may be used to achieve the objects of these embodiments.

(9) In some embodiments, when control circuitry identifies the preferred entity, control circuitry may identify an entity of the image that the user profile reflects a user associated with the user profile is likely to prefer. For example, control circuitry may determine that a particular user enjoys comedy. Control circuitry may determine that Ken Jeong is an outspoken comedian. Accordingly, control circuitry may identify Ken Jeong as the preferred entity, as Ken Jeong satisfies a characteristic that the user profile indicates the user would enjoy.

(10) In some embodiments, when control circuitry is identifying the preferred entity based on the cross-referencing, control circuitry may identify an affinity of the user with respect to each entity in the image. For example, control circuitry may, based on the user's profile, determine a degree to which a user prefers each entity. The control circuitry may then rank each respective entity (e.g.,

based on the determined degree). Control circuitry may then identify a subset of adjacent portions of the plurality of portions that comprise respective entities associated with a highest combined rank as compared to each other subset of adjacent portions of the plurality of portions. For example, control circuitry may determine that two adjacent entities (e.g., Ken Jeong and Chevy Chase) have a higher combined degree of preference, as compared to two other adjacent entities in the image. Control circuitry may then generate for display the respective portion comprising the preferred entity, where doing so comprises generating for display the subset of the adjacent portions. As an example, control circuitry may crop both the portion containing Ken Jeong, as well as the portion containing Chevy Chase, to create a new image with that contains both entities.

(11) In some embodiments, when control circuitry determines an identity of each respective entity in each respective portion of the plurality of portions, control circuitry may perform facial recognition on each respective entity of the image. For example, control circuitry may identify facial characteristics of each entity and cross-reference those facial characteristics against listings in a database of characteristics of individuals to identify a best guess of who each respective entity corresponds to. In some embodiments, the database that control circuitry compares the facial characteristics against may be a knowledge graph.

(12) In some embodiments, control circuitry may identify a plurality of preferred entities based on the cross-referencing. For example, control circuitry may identify two or more entities in the image that a user may prefer. Following the example from above, if the image is poster art corresponding to the television show “Community,” and each of Chevy Chase, Joel McHale, and Ken Jeong is depicted in the poster art, the control circuitry may determine that the user prefers all of Ken Jeong, Chevy Chase, and Joel McHale. Control circuitry may then generate for display a sufficient amount of the plurality of portions comprising entities of the plurality of preferred entities to satisfy a specified aspect ratio requirement. For example, if a specified aspect ratio requirement can accommodate only two portions, and an amalgamation of portions including representations of Ken Jeong and Joel McHale most closely satisfies the specified aspect ratio requirement, control circuitry may crop the portions including Ken Jeong and Joel McHale and generate for display the cropped image.

(13) In some embodiments, control circuitry may receive a selection by a user of the respective portion, and generate for display the image in response to receiving the selection. For example, if control circuitry receives a selection by the user of a displayed portion of the image, control circuitry may responsively display the full, original image (e.g., along with a page providing additional information about a media asset corresponding to the image).

(14) In some embodiments, control circuitry may recognize textual content in the image, and generate for simultaneous display the textual content with the respective portion comprising the preferred entity. For example, if the original image includes textual content (e.g., the title “Community”), control circuitry may cause that textual content to be superimposed on the respective portion (e.g., a cropped portion including a preferred actor).

(15) In some embodiments, control circuitry may determine characteristics of the preferred entity, and may then determine optimal characteristics for features surrounding the entity in the respective portion corresponding to the preferred entity. Based on the determined optimal characteristics, control circuitry may alter characteristics of the features surrounding the entity to reflect the optimal characteristics. For example, control circuitry may consider the skin tone of the preferred entity, and may then lighten or darken surrounding features of the image, such as the color of the sky or background surrounding the depiction of the preferred entity.

(16) In some aspects, control circuitry may identify an image corresponding to a media asset, where the image comprises a plurality of portions, and where each portion of the plurality of portions comprises a respective entity. For example, control circuitry may identify a poster, picture, box art, and/or the like, that corresponds to a media asset, such as the hit series “Community” starring actors Joel McHale, Chevy Chase, and Ken Jeong. The image identified by control

circuitry may include several portions, where each portion includes a respective entity. For example, control circuitry may determine that the image portrays each of Joel McHale, Chevy Chase, and Ken Jeong, and control circuitry may demark each portion that contains each separate actor as a separate portion of the image.

(17) In some embodiments, control circuitry may determine an identity of each respective entity in each respective portion of the plurality of portions. Following the example from above, control circuitry may determine that one portion includes Joel McHale, another portion includes Chevy Chase, and another portion includes Ken Jeong. Control circuitry may make these determinations based on image recognition algorithms, by consulting metadata corresponding to the image, or by any other known mechanism.

(18) In some embodiments, control circuitry may access a database to determine a level of prevalence of each identity in the media asset. For example, control circuitry may, when accessing the database, identify relative amounts of screen time of particular actors, or relative amounts of frames where an actor is the sole character in a frame. Based on these identifications, control circuitry may determine which respective entity corresponds to a highest level of prevalence (e.g., with respect to the other entities).

(19) In some embodiments, control circuitry may generate for display a respective portion comprising the respective entity that corresponds to the highest level of prevalence. For example, following from the example above, if Joel McHale has more screen time than Chevy Chase and Ken Jeong in the show community, control circuitry may generate for display an image of Joel McHale.

(20) In some embodiments, control circuitry may access a user profile from a database. For example, control circuitry may query a remote or local database to access a user profile that corresponds to a present user of a user equipment that control circuitry is implemented in or associated with. Control circuitry may, responsive to the query, receive information from the user profile.

(21) In some embodiments, control circuitry may cross-reference metadata of the user profile with each identity of each respective entity. For example, control circuitry may compare information of the user profile with information corresponding to each entity represented in the image. Following from the example above, control circuitry may cross-reference information indicating user preferences from the user profile against metadata corresponding to each of Joel McHale, Ken Jeong, and Chevy Chase, in an effort to determine which actor(s) the user may prefer. Control circuitry may then identify a preferred entity based on the cross-referencing.

(22) In some embodiments, control circuitry may rank each respective entity based on the cross-referencing. For example, as discussed above, control circuitry may rank each respective entity based on how likely a user is to prefer that particular entity. Additionally, control circuitry may weight each respective entity based on a respective level of prevalence corresponding to the respective entity. For example, following from the example above, if Joel McHale is more prevalent than Chevy Chase and Ken Jeong because Joel McHale has relatively more screen time in the media asset “Community,” then Joel McHale will have a high weight.

(23) In some embodiments, control circuitry may heuristically combine the rank and weight of each respective entity to determine a combined rank of each respective entity. For example, if control circuitry determines that a user has a strong preference for Ken Jeong, and Ken Jeong has a low weight because he is not so prevalent in the media asset “Community,” and control circuitry determines that a user strongly dislikes Joel McHale, but that Joel McHale has a high prevalence, control circuitry may consider all these factors heuristically to determine a combined rank. Because, in this case, Joel McHale is so strongly disliked, control circuitry may attribute a higher combined weight to Ken Jeong. Control circuitry may then generate for display a respective portion comprising the respective entity that corresponds to the highest combined rank (in this case, an image including Ken Jeong).

(24) In some embodiments, control circuitry may identify a plurality of prevalent entities by determining two or more entities with the highest prevalence levels, relative to each other entity, and generate for display a sufficient amount of the plurality of portions comprising entities of the plurality of preferred entities to satisfy a specified aspect ratio requirement. For example, control circuitry may identify Ken Jeong and Joel McHale as having the two highest prevalence levels (in accordance with any manner described above and below). Control circuitry may identify two identities if a specified aspect ratio requirement can accommodate only two portions. Control circuitry may crop the portions including Ken Jeong and Joel McHale and generate for display the cropped image.

(25) In some embodiments, control circuitry may determine characteristics of the entity that corresponds to the highest level of prevalence, and may then determine optimal characteristics for features surrounding the entity in the respective portion corresponding to the entity that corresponds to the highest level of prevalence. Based on the determined optimal characteristics, control circuitry may alter characteristics of the features surrounding the entity to reflect the optimal characteristics. For example, control circuitry may consider the skin tone of the entity that corresponds to the highest level of prevalence, and may then lighten or darken surrounding features of the image, such as the color of the sky or background surrounding the depiction of the entity corresponding to the highest level of prevalence.

(26) In some embodiments, control circuitry may determine the level of prevalence based on at least one of screen time, amount of time in close-up footage, amount of time in wide shot footage, and amount of time of being the sole character in a frame in the media asset.

(27) In some aspects, control circuitry may identify a plurality of images corresponding to a media asset, where each image of the plurality of images comprises at least one portion, and where each portion comprises a respective entity. For example, control circuitry may identify a poster, picture, box art, and/or the like, that corresponds to a media asset, such as the hit series “Community” starring actors Joel McHale, Chevy Chase, and Ken Jeong. The images identified by control circuitry may include several portions, where each portion includes a respective entity. For example, control circuitry may determine that the image portrays each of Joel McHale, Chevy Chase, and Ken Jeong, and control circuitry may demark each portion that contains each separate actor as a separate portion of the image.

(28) In some embodiments, control circuitry may determine an identity of each respective entity. Following the example from above, control circuitry may determine that one entity represents Joel McHale, another entity represents Chevy Chase, and another entity represents Ken Jeong. Control circuitry may make these determinations based on image recognition algorithms, by consulting metadata corresponding to the image, or by any other known mechanism.

(29) In some embodiments, control circuitry may access a user profile from a database. For example, control circuitry may query a remote or local database to access a user profile that corresponds to a present user of a user equipment that control circuitry is implemented in or associated with. Control circuitry may, responsive to the query, receive information from the user profile.

(30) In some embodiments, control circuitry may cross-reference metadata of the user profile with each identity of each respective entity. For example, control circuitry may compare information of the user profile with information corresponding to each entity. Following from the example above, control circuitry may cross-reference information indicating user preferences from the user profile against metadata corresponding to each of Joel McHale, Ken Jeong, and Chevy Chase, in an effort to determine which actor(s) the user may prefer. Control circuitry may then identify a preferred entity based on the cross-referencing.

(31) In some embodiments, control circuitry may determine an image of the plurality of images where the preferred entity is more prevalent, and may generate for display that image. For example, control circuitry may determine that Ken Jeong is the preferred entity. Control circuitry may

determine that there are three candidates images in the plurality of images, where one includes all of Joel McHale, Ken Jeong, and Chevy Chase, one includes only Ken Jeong, and one includes the entire cast of the media asset “Community.” Control circuitry may determine that the image including only Ken Jeong is the image in which Ken Jeong is most prevalent. Control circuitry may then generate for display the image including Ken Jeong. The display of the image may be generated using any manner discussed above and below with respect to other embodiments.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other objects and advantages of the disclosure will be apparent upon consideration of the following detailed description, taken in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout, and in which:
- (2) FIG. 1 shows an illustrative embodiment of a display screen that may be used to provide media guidance application listings and other media guidance information, in accordance with some embodiments of the disclosure;
- (3) FIG. 2 shows another illustrative embodiment of a display screen that may be used to provide media guidance application listings, in accordance with some embodiments of the disclosure;
- (4) FIG. 3 is a block diagram of an illustrative user equipment (UE) device in accordance with some embodiments of the disclosure;
- (5) FIG. 4 is a block diagram of an illustrative media system in accordance with some embodiments of the disclosure;
- (6) FIG. 5 shows an illustrative embodiment of a user equipment device on which an image, portions of images, media asset identifiers, and other information are displayed, in accordance with some embodiments of the disclosure;
- (7) FIG. 6 is a flowchart of illustrative steps involved in determining which portion of an image to generate for display, in accordance with some embodiments of the disclosure;
- (8) FIG. 7 is a flowchart of illustrative steps involved in determining which portion of an image to generate for display based on a level of prevalence of an identity of an entity in a media asset, in accordance with some embodiments of the disclosure; and
- (9) FIG. 8 is a flowchart of illustrative steps involved in selectively generating for display an image of a plurality of images where a user-preferred entity is most prevalent, in accordance with some embodiments of the disclosure.

DETAILED DESCRIPTION

(10) To achieve these ends and others, systems and methods are provided herein for selectively generating for display portions of an image based on a user profile. In some aspects, these systems and methods comprise control circuitry identifying an image corresponding to a media asset, where the image comprises a plurality of portions, and where each portion of the plurality of portions comprises a respective entity. For example, control circuitry may identify a poster, picture, box art, and/or the like, that corresponds to a media asset, such as the hit series “Community” starring actors Joel McHale, Chevy Chase, and Ken Jeong. The image identified by control circuitry may include several portions, where each portion includes a respective entity. For example, control circuitry may determine that the image portrays each of Joel McHale, Chevy Chase, and Ken Jeong, and control circuitry may demark each portion that contains each separate actor as a separate portion of the image.

(11) In some embodiments, control circuitry may determine an identity of each respective entity in each respective portion of the plurality of portions. Following the example from above, control circuitry may determine that one portion includes Joel McHale, another portion includes Chevy Chase, and another portion includes Ken Jeong. Control circuitry may make these determinations

based on image recognition algorithms, by consulting metadata corresponding to the image, or by any other known mechanism.

(12) In some embodiments, control circuitry may access a user profile from a database. For example, control circuitry may query a remote or local database to access a user profile that corresponds to a present user of a user equipment that control circuitry is implemented in or associated with. Control circuitry may, responsive to the query, receive information of the user profile.

(13) In some embodiments, control circuitry may cross-reference metadata from the user profile with each identity of each respective entity of the image. For example, control circuitry may compare information from the user profile with information corresponding to each entity represented in the image. Following from the example above, control circuitry may cross-reference information indicating user preferences from the user profile against metadata corresponding to each of Joel McHale, Ken Jeong, and Chevy Chase, in an effort to determine which actor(s) the user may prefer. Control circuitry may then identify a preferred entity based on the cross-referencing.

(14) In some embodiments, control circuitry may generate for display the respective portion comprising the preferred entity. For example, control circuitry may crop one or more entities that the user prefers from the original image and display the cropped image in place of the original image. Doing so may cause an image that a user is more likely to prefer to be displayed.

(15) The amount of content available to users in any given content delivery system can be substantial. Consequently, many users desire a form of media guidance through an interface that allows users to efficiently navigate content selections and easily identify content that they may desire. An application that provides such guidance is referred to herein as an interactive media guidance application or, sometimes, a media guidance application or a guidance application.

(16) Interactive media guidance applications may take various forms depending on the content for which they provide guidance. One typical type of media guidance application is an interactive television program guide. Interactive television program guides (sometimes referred to as electronic program guides) are well-known guidance applications that, among other things, allow users to navigate among and locate many types of content or media assets. Interactive media guidance applications may generate graphical user interface screens that enable a user to navigate among, locate and select content. As referred to herein, the terms “media asset” and “content” should be understood to mean an electronically consumable user asset, such as television programming, as well as pay-per-view programs, on-demand programs (as in video-on-demand (VOD) systems), Internet content (e.g., streaming content, downloadable content, Webcasts, etc.), video clips, audio, content information, pictures, rotating images, documents, playlists, websites, articles, books, electronic books, blogs, advertisements, chat sessions, social media, applications, games, and/or any other media or multimedia and/or combination of the same. Guidance applications also allow users to navigate among and locate content. As referred to herein, the term “multimedia” should be understood to mean content that utilizes at least two different content forms described above, for example, text, audio, images, video, or interactivity content forms. Content may be recorded, played, displayed or accessed by user equipment devices, but can also be part of a live performance.

(17) The media guidance application and/or any instructions for performing any of the embodiments discussed herein may be encoded on computer readable media. Computer readable media includes any media capable of storing data. The computer readable media may be transitory, including, but not limited to, propagating electrical or electromagnetic signals, or may be non-transitory including, but not limited to, volatile and non-volatile computer memory or storage devices such as a hard disk, floppy disk, USB drive, DVD, CD, media cards, register memory, processor caches, Random Access Memory (“RAM”), etc.

(18) With the advent of the Internet, mobile computing, and high-speed wireless networks, users

are accessing media on user equipment devices on which they traditionally did not. As referred to herein, the phrase “user equipment device,” “user equipment,” “user device,” “electronic device,” “electronic equipment,” “media equipment device,” or “media device” should be understood to mean any device for accessing the content described above, such as a television, a Smart TV, a set-top box, an integrated receiver decoder (IRD) for handling satellite television, a digital storage device, a digital media receiver (DMR), a digital media adapter (DMA), a streaming media device, a DVD player, a DVD recorder, a connected DVD, a local media server, a BLU-RAY player, a BLU-RAY recorder, a personal computer (PC), a laptop computer, a tablet computer, a WebTV box, a personal computer television (PC/TV), a PC media server, a PC media center, a hand-held computer, a stationary telephone, a personal digital assistant (PDA), a mobile telephone, a portable video player, a portable music player, a portable gaming machine, a smart phone, or any other television equipment, computing equipment, or wireless device, and/or combination of the same. In some embodiments, the user equipment device may have a front facing screen and a rear facing screen, multiple front screens, or multiple angled screens. In some embodiments, the user equipment device may have a front facing camera and/or a rear facing camera. On these user equipment devices, users may be able to navigate among and locate the same content available through a television. Consequently, media guidance may be available on these devices, as well. The guidance provided may be for content available only through a television, for content available only through one or more of other types of user equipment devices, or for content available both through a television and one or more of the other types of user equipment devices. The media guidance applications may be provided as on-line applications (i.e., provided on a web-site), or as stand-alone applications or clients on user equipment devices. Various devices and platforms that may implement media guidance applications are described in more detail below.

(19) One of the functions of the media guidance application is to provide media guidance data to users. As referred to herein, the phrase “media guidance data” or “guidance data” should be understood to mean any data related to content or data used in operating the guidance application. For example, the guidance data may include program information, guidance application settings, user preferences, user profile information, media listings, media-related information (e.g., broadcast times, broadcast channels, titles, descriptions, ratings information (e.g., parental control ratings, critic's ratings, etc.), genre or category information, actor information, logo data for broadcasters' or providers' logos, etc.), media format (e.g., standard definition, high definition, 3D, etc.), advertisement information (e.g., text, images, media clips, etc.), on-demand information, blogs, websites, and any other type of guidance data that is helpful for a user to navigate among and locate desired content selections.

(20) FIGS. 1-2 show illustrative display screens that may be used to provide media guidance data. The display screens shown in FIGS. 1-2 may be implemented on any suitable user equipment device or platform. While the displays of FIGS. 1-2 are illustrated as full screen displays, they may also be fully or partially overlaid over content being displayed. A user may indicate a desire to access content information by selecting a selectable option provided in a display screen (e.g., a menu option, a listings option, an icon, a hyperlink, etc.) or pressing a dedicated button (e.g., a GUIDE button) on a remote control or other user input interface or device. In response to the user's indication, the media guidance application may provide a display screen with media guidance data organized in one of several ways, such as by time and channel in a grid, by time, by channel, by source, by content type, by category (e.g., movies, sports, news, children, or other categories of programming), or other predefined, user-defined, or other organization criteria.

(21) FIG. 1 shows illustrative grid of a program listings display **100** arranged by time and channel that also enables access to different types of content in a single display. Display **100** may include grid **102** with: (1) a column of channel/content type identifiers **104**, where each channel/content type identifier (which is a cell in the column) identifies a different channel or content type available; and (2) a row of time identifiers **106**, where each time identifier (which is a cell in the

row) identifies a time block of programming. Grid **102** also includes cells of program listings, such as program listing **108**, where each listing provides the title of the program provided on the listing's associated channel and time. With a user input device, a user can select program listings by moving highlight region **110**. Information relating to the program listing selected by highlight region **110** may be provided in program information region **112**. Region **112** may include, for example, the program title, the program description, the time the program is provided (if applicable), the channel the program is on (if applicable), the program's rating, and other desired information.

(22) In addition to providing access to linear programming (e.g., content that is scheduled to be transmitted to a plurality of user equipment devices at a predetermined time and is provided according to a schedule), the media guidance application also provides access to non-linear programming (e.g., content accessible to a user equipment device at any time and is not provided according to a schedule). Non-linear programming may include content from different content sources including on-demand content (e.g., VOD), Internet content (e.g., streaming media, downloadable media, etc.), locally stored content (e.g., content stored on any user equipment device described above or other storage device), or other time-independent content. On-demand content may include movies or any other content provided by a particular content provider (e.g., HBO On Demand providing "The Sopranos" and "Curb Your Enthusiasm"). HBO ON DEMAND is a service mark owned by Time Warner Company L.P. et al. and THE SOPRANOS and CURB YOUR ENTHUSIASM are trademarks owned by the Home Box Office, Inc. Internet content may include web events, such as a chat session or Webcast, or content available on-demand as streaming content or downloadable content through an Internet web site or other Internet access (e.g. FTP).

(23) Grid **102** may provide media guidance data for non-linear programming including on-demand listing **114**, recorded content listing **116**, and Internet content listing **118**. A display combining media guidance data for content from different types of content sources is sometimes referred to as a "mixed-media" display. Various permutations of the types of media guidance data that may be displayed that are different than display **100** may be based on user selection or guidance application definition (e.g., a display of only recorded and broadcast listings, only on-demand and broadcast listings, etc.). As illustrated, listings **114**, **116**, and **118** are shown as spanning the entire time block displayed in grid **102** to indicate that selection of these listings may provide access to a display dedicated to on-demand listings, recorded listings, or Internet listings, respectively. In some embodiments, listings for these content types may be included directly in grid **102**. Additional media guidance data may be displayed in response to the user selecting one of the navigational icons **120**. (Pressing an arrow key on a user input device may affect the display in a similar manner as selecting navigational icons **120**.)

(24) Display **100** may also include video region **122**, advertisement **124**, and options region **126**. Video region **122** may allow the user to view and/or preview programs that are currently available, will be available, or were available to the user. The content of video region **122** may correspond to, or be independent from, one of the listings displayed in grid **102**. Grid displays including a video region are sometimes referred to as picture-in-guide (PIG) displays. PIG displays and their functionalities are described in greater detail in Satterfield et al. U.S. Pat. No. 6,564,378, issued May 13, 2003 and Yuen et al. U.S. Pat. No. 6,239,794, issued May 29, 2001, which are hereby incorporated by reference herein in their entireties. PIG displays may be included in other media guidance application display screens of the embodiments described herein.

(25) Advertisement **124** may provide an advertisement for content that, depending on a viewer's access rights (e.g., for subscription programming), is currently available for viewing, will be available for viewing in the future, or may never become available for viewing, and may correspond to or be unrelated to one or more of the content listings in grid **102**. Advertisement **124** may also be for products or services related or unrelated to the content displayed in grid **102**. Advertisement **124** may be selectable and provide further information about content, provide information about a product or a service, enable purchasing of content, a product, or a service,

provide content relating to the advertisement, etc. Advertisement **124** may be targeted based on a user's profile/preferences, monitored user activity, the type of display provided, or on other suitable targeted advertisement bases.

(26) While advertisement **124** is shown as rectangular or banner shaped, advertisements may be provided in any suitable size, shape, and location in a guidance application display. For example, advertisement **124** may be provided as a rectangular shape that is horizontally adjacent to grid **102**. This is sometimes referred to as a panel advertisement. In addition, advertisements may be overlaid over content or a guidance application display or embedded within a display. Advertisements may also include text, images, rotating images, video clips, or other types of content described above. Advertisements may be stored in a user equipment device having a guidance application, in a database connected to the user equipment, in a remote location (including streaming media servers), or on other storage means, or a combination of these locations. Providing advertisements in a media guidance application is discussed in greater detail in, for example, Knudson et al., U.S. Patent Application Publication No. 2003/0110499, filed Jan. 17, 2003; Ward, III et al. U.S. Pat. No. 6,756,997, issued Jun. 29, 2004; and Schein et al. U.S. Pat. No. 6,388,714, issued May 14, 2002, which are hereby incorporated by reference herein in their entireties. It will be appreciated that advertisements may be included in other media guidance application display screens of the embodiments described herein.

(27) Options region **126** may allow the user to access different types of content, media guidance application displays, and/or media guidance application features. Options region **126** may be part of display **100** (and other display screens described herein), or may be invoked by a user by selecting an on-screen option or pressing a dedicated or assignable button on a user input device. The selectable options within options region **126** may concern features related to program listings in grid **102** or may include options available from a main menu display. Features related to program listings may include searching for other air times or ways of receiving a program, recording a program, enabling series recording of a program, setting program and/or channel as a favorite, purchasing a program, or other features. Options available from a main menu display may include search options, VOD options, parental control options, Internet options, cloud-based options, device synchronization options, second screen device options, options to access various types of media guidance data displays, options to subscribe to a premium service, options to edit a user's profile, options to access a browse overlay, or other options.

(28) The media guidance application may be personalized based on a user's preferences. A personalized media guidance application allows a user to customize displays and features to create a personalized "experience" with the media guidance application. This personalized experience may be created by allowing a user to input these customizations and/or by the media guidance application monitoring user activity to determine various user preferences. Users may access their personalized guidance application by logging in or otherwise identifying themselves to the guidance application. Customization of the media guidance application may be made in accordance with a user profile. The customizations may include varying presentation schemes (e.g., color scheme of displays, font size of text, etc.), aspects of content listings displayed (e.g., only HDTV or only 3D programming, user-specified broadcast channels based on favorite channel selections, re-ordering the display of channels, recommended content, etc.), desired recording features (e.g., recording or series recordings for particular users, recording quality, etc.), parental control settings, customized presentation of Internet content (e.g., presentation of social media content, e-mail, electronically delivered articles, etc.) and other desired customizations.

(29) The media guidance application may allow a user to provide user profile information or may automatically compile user profile information. The media guidance application may, for example, monitor the content the user accesses and/or other interactions the user may have with the guidance application. Additionally, the media guidance application may obtain all or part of other user profiles that are related to a particular user (e.g., from other web sites on the Internet the user

accesses, such as www.allrovi.com, from other media guidance applications the user accesses, from other interactive applications the user accesses, from another user equipment device of the user, etc.), and/or obtain information about the user from other sources that the media guidance application may access. As a result, a user can be provided with a unified guidance application experience across the user's different user equipment devices. This type of user experience is described in greater detail below in connection with FIG. 4. Additional personalized media guidance application features are described in greater detail in Ellis et al., U.S. Patent Application Publication No. 2005/0251827, filed Jul. 11, 2005, Boyer et al., U.S. Pat. No. 7,165,098, issued Jan. 16, 2007, and Ellis et al., U.S. Patent Application Publication No. 2002/0174430, filed Feb. 21, 2002, which are hereby incorporated by reference herein in their entireties.

(30) Another display arrangement for providing media guidance is shown in FIG. 2. Video mosaic display **200** includes selectable options **202** for content information organized based on content type, genre, and/or other organization criteria. In display **200**, television listings option **204** is selected, thus providing listings **206**, **208**, **210**, and **212** as broadcast program listings. In display **200** the listings may provide graphical images including cover art, still images from the content, video clip previews, live video from the content, or other types of content that indicate to a user the content being described by the media guidance data in the listing. Each of the graphical listings may also be accompanied by text to provide further information about the content associated with the listing. For example, listing **208** may include more than one portion, including media portion **214** and text portion **216**. Media portion **214** and/or text portion **216** may be selectable to view content in full-screen or to view information related to the content displayed in media portion **214** (e.g., to view listings for the channel that the video is displayed on).

(31) The listings in display **200** are of different sizes (i.e., listing **206** is larger than listings **208**, **210**, and **212**), but if desired, all the listings may be the same size. Listings may be of different sizes or graphically accentuated to indicate degrees of interest to the user or to emphasize certain content, as desired by the content provider or based on user preferences. Various systems and methods for graphically accentuating content listings are discussed in, for example, Yates, U.S. Patent Application Publication No. 2010/0153885, filed Nov. 12, 2009, which is hereby incorporated by reference herein in its entirety.

(32) Users may access content and the media guidance application (and its display screens described above and below) from one or more of their user equipment devices. FIG. 3 shows a generalized embodiment of illustrative user equipment device **300**. More specific implementations of user equipment devices are discussed below in connection with FIG. 4. User equipment device **300** may receive content and data via input/output (hereinafter "I/O") path **302**. I/O path **302** may provide content (e.g., broadcast programming, on-demand programming, Internet content, content available over a local area network (LAN) or wide area network (WAN), and/or other content) and data to control circuitry **304**, which includes processing circuitry **306** and storage **308**. Control circuitry **304** may be used to send and receive commands, requests, and other suitable data using I/O path **302**. I/O path **302** may connect control circuitry **304** (and specifically processing circuitry **306**) to one or more communications paths (described below). I/O functions may be provided by one or more of these communications paths, but are shown as a single path in FIG. 3 to avoid overcomplicating the drawing.

(33) Control circuitry **304** may be based on any suitable processing circuitry such as processing circuitry **306**. As referred to herein, processing circuitry should be understood to mean circuitry based on one or more microprocessors, microcontrollers, digital signal processors, programmable logic devices, field-programmable gate arrays (FPGAs), application-specific integrated circuits (ASICs), etc., and may include a multi-core processor (e.g., dual-core, quad-core, hexa-core, or any suitable number of cores) or supercomputer. In some embodiments, processing circuitry may be distributed across multiple separate processors or processing units, for example, multiple of the same type of processing units (e.g., two Intel Core i7 processors) or multiple different processors

(e.g., an Intel Core i5 processor and an Intel Core i7 processor). In some embodiments, control circuitry **304** executes instructions for a media guidance application stored in memory (i.e., storage **308**). Specifically, control circuitry **304** may be instructed by the media guidance application to perform the functions discussed above and below. For example, the media guidance application may provide instructions to control circuitry **304** to generate the media guidance displays. In some implementations, any action performed by control circuitry **304** may be based on instructions received from the media guidance application.

(34) In client-server based embodiments, control circuitry **304** may include communications circuitry suitable for communicating with a guidance application server or other networks or servers. The instructions for carrying out the above mentioned functionality may be stored on the guidance application server. Communications circuitry may include a cable modem, an integrated services digital network (ISDN) modem, a digital subscriber line (DSL) modem, a telephone modem, Ethernet card, or a wireless modem for communications with other equipment, or any other suitable communications circuitry. Such communications may involve the Internet or any other suitable communications networks or paths (which is described in more detail in connection with FIG. 4). In addition, communications circuitry may include circuitry that enables peer-to-peer communication of user equipment devices, or communication of user equipment devices in locations remote from each other (described in more detail below).

(35) Memory may be an electronic storage device provided as storage **308** that is part of control circuitry **304**. As referred to herein, the phrase “electronic storage device” or “storage device” should be understood to mean any device for storing electronic data, computer software, or firmware, such as random-access memory, read-only memory, hard drives, optical drives, digital video disc (DVD) recorders, compact disc (CD) recorders, BLU-RAY disc (BD) recorders, BLU-RAY 3D disc recorders, digital video recorders (DVR, sometimes called a personal video recorder, or PVR), solid state devices, quantum storage devices, gaming consoles, gaming media, or any other suitable fixed or removable storage devices, and/or any combination of the same. Storage **308** may be used to store various types of content described herein as well as media guidance data described above. Nonvolatile memory may also be used (e.g., to launch a boot-up routine and other instructions). Cloud-based storage, described in relation to FIG. 4, may be used to supplement storage **308** or instead of storage **308**.

(36) Control circuitry **304** may include video generating circuitry and tuning circuitry, such as one or more analog tuners, one or more MPEG-2 decoders or other digital decoding circuitry, high-definition tuners, or any other suitable tuning or video circuits or combinations of such circuits. Encoding circuitry (e.g., for converting over-the-air, analog, or digital signals to MPEG signals for storage) may also be provided. Control circuitry **304** may also include scaler circuitry for upconverting and downconverting content into the preferred output format of the user equipment **300**. Circuitry **304** may also include digital-to-analog converter circuitry and analog-to-digital converter circuitry for converting between digital and analog signals. The tuning and encoding circuitry may be used by the user equipment device to receive and to display, to play, or to record content. The tuning and encoding circuitry may also be used to receive guidance data. The circuitry described herein, including for example, the tuning, video generating, encoding, decoding, encrypting, decrypting, scaler, and analog/digital circuitry, may be implemented using software running on one or more general purpose or specialized processors. Multiple tuners may be provided to handle simultaneous tuning functions (e.g., watch and record functions, picture-in-picture (PIP) functions, multiple-tuner recording, etc.). If storage **308** is provided as a separate device from user equipment **300**, the tuning and encoding circuitry (including multiple tuners) may be associated with storage **308**.

(37) A user may send instructions to control circuitry **304** using user input interface **310**. User input interface **310** may be any suitable user interface, such as a remote control, mouse, trackball, keypad, keyboard, touch screen, touchpad, stylus input, joystick, voice recognition interface, or

other user input interfaces. Display **312** may be provided as a stand-alone device or integrated with other elements of user equipment device **300**. For example, display **312** may be a touchscreen or touch-sensitive display. In such circumstances, user input interface **310** may be integrated with or combined with display **312**. Display **312** may be one or more of a monitor, a television, a liquid crystal display (LCD) for a mobile device, amorphous silicon display, low temperature poly silicon display, electronic ink display, electrophoretic display, active matrix display, electro-wetting display, electrofluidic display, cathode ray tube display, light-emitting diode display, electroluminescent display, plasma display panel, high-performance addressing display, thin-film transistor display, organic light-emitting diode display, surface-conduction electron-emitter display (SED), laser television, carbon nanotubes, quantum dot display, interferometric modulator display, or any other suitable equipment for displaying visual images. In some embodiments, display **312** may be HDTV-capable. In some embodiments, display **312** may be a 3D display, and the interactive media guidance application and any suitable content may be displayed in 3D. A video card or graphics card may generate the output to the display **312**. The video card may offer various functions such as accelerated rendering of 3D scenes and 2D graphics, MPEG-2/MPEG-4 decoding, TV output, or the ability to connect multiple monitors. The video card may be any processing circuitry described above in relation to control circuitry **304**. The video card may be integrated with the control circuitry **304**. Speakers **314** may be provided as integrated with other elements of user equipment device **300** or may be stand-alone units. The audio component of videos and other content displayed on display **312** may be played through speakers **314**. In some embodiments, the audio may be distributed to a receiver (not shown), which processes and outputs the audio via speakers **314**.

(38) The guidance application may be implemented using any suitable architecture. For example, it may be a stand-alone application wholly-implemented on user equipment device **300**. In such an approach, instructions of the application are stored locally (e.g., in storage **308**), and data for use by the application is downloaded on a periodic basis (e.g., from an out-of-band feed, from an Internet resource, or using another suitable approach). Control circuitry **304** may retrieve instructions of the application from storage **308** and process the instructions to generate any of the displays discussed herein. Based on the processed instructions, control circuitry **304** may determine what action to perform when input is received from input interface **310**. For example, movement of a cursor on a display up/down may be indicated by the processed instructions when input interface **310** indicates that an up/down button was selected.

(39) In some embodiments, the media guidance application is a client-server based application. Data for use by a thick or thin client implemented on user equipment device **300** is retrieved on-demand by issuing requests to a server remote to the user equipment device **300**. In one example of a client-server based guidance application, control circuitry **304** runs a web browser that interprets web pages provided by a remote server. For example, the remote server may store the instructions for the application in a storage device. The remote server may process the stored instructions using circuitry (e.g., control circuitry **304**) and generate the displays discussed above and below. The client device may receive the displays generated by the remote server and may display the content of the displays locally on equipment device **300**. This way, the processing of the instructions is performed remotely by the server while the resulting displays are provided locally on equipment device **300**. Equipment device **300** may receive inputs from the user via input interface **310** and transmit those inputs to the remote server for processing and generating the corresponding displays. For example, equipment device **300** may transmit a communication to the remote server indicating that an up/down button was selected via input interface **310**. The remote server may process instructions in accordance with that input and generate a display of the application corresponding to the input (e.g., a display that moves a cursor up/down). The generated display is then transmitted to equipment device **300** for presentation to the user.

(40) In some embodiments, the media guidance application is downloaded and interpreted or

otherwise run by an interpreter or virtual machine (run by control circuitry **304**). In some embodiments, the guidance application may be encoded in the ETV Binary Interchange Format (EBIF), received by control circuitry **304** as part of a suitable feed, and interpreted by a user agent running on control circuitry **304**. For example, the guidance application may be an EBIF application. In some embodiments, the guidance application may be defined by a series of JAVA-based files that are received and run by a local virtual machine or other suitable middleware executed by control circuitry **304**. In some of such embodiments (e.g., those employing MPEG-2 or other digital media encoding schemes), the guidance application may be, for example, encoded and transmitted in an MPEG-2 object carousel with the MPEG audio and video packets of a program.

(41) User equipment device **300** of FIG. **3** can be implemented in system **400** of FIG. **4** as user television equipment **402**, user computer equipment **404**, wireless user communications device **406**, or any other type of user equipment suitable for accessing content, such as a non-portable gaming machine. For simplicity, these devices may be referred to herein collectively as user equipment or user equipment devices, and may be substantially similar to user equipment devices described above. User equipment devices, on which a media guidance application may be implemented, may function as a standalone device or may be part of a network of devices. Various network configurations of devices may be implemented and are discussed in more detail below.

(42) A user equipment device utilizing at least some of the system features described above in connection with FIG. **3** may not be classified solely as user television equipment **402**, user computer equipment **404**, or a wireless user communications device **406**. For example, user television equipment **402** may, like some user computer equipment **404**, be Internet-enabled allowing for access to Internet content, while user computer equipment **404** may, like some television equipment **402**, include a tuner allowing for access to television programming. The media guidance application may have the same layout on various different types of user equipment or may be tailored to the display capabilities of the user equipment. For example, on user computer equipment **404**, the guidance application may be provided as a web site accessed by a web browser. In another example, the guidance application may be scaled down for wireless user communications devices **406**.

(43) In system **400**, there is typically more than one of each type of user equipment device but only one of each is shown in FIG. **4** to avoid overcomplicating the drawing. In addition, each user may utilize more than one type of user equipment device and also more than one of each type of user equipment device.

(44) In some embodiments, a user equipment device (e.g., user television equipment **402**, user computer equipment **404**, wireless user communications device **406**) may be referred to as a “second screen device.” For example, a second screen device may supplement content presented on a first user equipment device. The content presented on the second screen device may be any suitable content that supplements the content presented on the first device. In some embodiments, the second screen device provides an interface for adjusting settings and display preferences of the first device. In some embodiments, the second screen device is configured for interacting with other second screen devices or for interacting with a social network. The second screen device can be located in the same room as the first device, a different room from the first device but in the same house or building, or in a different building from the first device.

(45) The user may also set various settings to maintain consistent media guidance application settings across in-home devices and remote devices. Settings include those described herein, as well as channel and program favorites, programming preferences that the guidance application utilizes to make programming recommendations, display preferences, and other desirable guidance settings. For example, if a user sets a channel as a favorite on, for example, the web site www.allrovi.com on their personal computer at their office, the same channel would appear as a favorite on the user's in-home devices (e.g., user television equipment and user computer equipment) as well as the user's mobile devices, if desired. Therefore, changes made on one user

equipment device can change the guidance experience on another user equipment device, regardless of whether they are the same or a different type of user equipment device. In addition, the changes made may be based on settings input by a user, as well as user activity monitored by the guidance application.

(46) The user equipment devices may be coupled to communications network **414**. Namely, user television equipment **402**, user computer equipment **404**, and wireless user communications device **406** are coupled to communications network **414** via communications paths **408**, **410**, and **412**, respectively. Communications network **414** may be one or more networks including the Internet, a mobile phone network, mobile voice or data network (e.g., a 4G or LTE network), cable network, public switched telephone network, or other types of communications network or combinations of communications networks. Paths **408**, **410**, and **412** may separately or together include one or more communications paths, such as, a satellite path, a fiber-optic path, a cable path, a path that supports Internet communications (e.g., IPTV), free-space connections (e.g., for broadcast or other wireless signals), or any other suitable wired or wireless communications path or combination of such paths. Path **412** is drawn with dotted lines to indicate that in the exemplary embodiment shown in FIG. **4** it is a wireless path and paths **408** and **410** are drawn as solid lines to indicate they are wired paths (although these paths may be wireless paths, if desired). Communications with the user equipment devices may be provided by one or more of these communications paths, but are shown as a single path in FIG. **4** to avoid overcomplicating the drawing.

(47) Although communications paths are not drawn between user equipment devices, these devices may communicate directly with each other via communication paths, such as those described above in connection with paths **408**, **410**, and **412**, as well as other short-range point-to-point communication paths, such as USB cables, IEEE 1394 cables, wireless paths (e.g., Bluetooth, infrared, IEEE 802-11x, etc.), or other short-range communication via wired or wireless paths. BLUETOOTH is a certification mark owned by Bluetooth SIG, INC. The user equipment devices may also communicate with each other directly through an indirect path via communications network **414**.

(48) System **400** includes content source **416** and media guidance data source **418** coupled to communications network **414** via communication paths **420** and **422**, respectively. Paths **420** and **422** may include any of the communication paths described above in connection with paths **408**, **410**, and **412**. Communications with the content source **416** and media guidance data source **418** may be exchanged over one or more communications paths, but are shown as a single path in FIG. **4** to avoid overcomplicating the drawing. In addition, there may be more than one of each of content source **416** and media guidance data source **418**, but only one of each is shown in FIG. **4** to avoid overcomplicating the drawing. (The different types of each of these sources are discussed below.) If desired, content source **416** and media guidance data source **418** may be integrated as one source device. Although communications between sources **416** and **418** with user equipment devices **402**, **404**, and **406** are shown as through communications network **414**, in some embodiments, sources **416** and **418** may communicate directly with user equipment devices **402**, **404**, and **406** via communication paths (not shown) such as those described above in connection with paths **408**, **410**, and **412**.

(49) Content source **416** may include one or more types of content distribution equipment including a television distribution facility, cable system headend, satellite distribution facility, programming sources (e.g., television broadcasters, such as NBC, ABC, HBO, etc.), intermediate distribution facilities and/or servers, Internet providers, on-demand media servers, and other content providers. NBC is a trademark owned by the National Broadcasting Company, Inc., ABC is a trademark owned by the American Broadcasting Company, Inc., and HBO is a trademark owned by the Home Box Office, Inc. Content source **416** may be the originator of content (e.g., a television broadcaster, a Webcast provider, etc.) or may not be the originator of content (e.g., an on-demand content provider, an Internet provider of content of broadcast programs for downloading,

etc.). Content source **416** may include cable sources, satellite providers, on-demand providers, Internet providers, over-the-top content providers, or other providers of content. Content source **416** may also include a remote media server used to store different types of content (including video content selected by a user), in a location remote from any of the user equipment devices. Systems and methods for remote storage of content, and providing remotely stored content to user equipment are discussed in greater detail in connection with Ellis et al., U.S. Pat. No. 7,761,892, issued Jul. 20, 2010, which is hereby incorporated by reference herein in its entirety.

(50) Media guidance data source **418** may provide media guidance data, such as the media guidance data described above. Media guidance data may be provided to the user equipment devices using any suitable approach. In some embodiments, the guidance application may be a stand-alone interactive television program guide that receives program guide data via a data feed (e.g., a continuous feed or trickle feed). Program schedule data and other guidance data may be provided to the user equipment on a television channel sideband, using an in-band digital signal, using an out-of-band digital signal, or by any other suitable data transmission technique. Program schedule data and other media guidance data may be provided to user equipment on multiple analog or digital television channels.

(51) In some embodiments, guidance data from media guidance data source **418** may be provided to users' equipment using a client-server approach. For example, a user equipment device may pull media guidance data from a server, or a server may push media guidance data to a user equipment device. In some embodiments, a guidance application client residing on the user's equipment may initiate sessions with source **418** to obtain guidance data when needed, e.g., when the guidance data is out of date or when the user equipment device receives a request from the user to receive data. Media guidance may be provided to the user equipment with any suitable frequency (e.g., continuously, daily, a user-specified period of time, a system-specified period of time, in response to a request from user equipment, etc.). Media guidance data source **418** may provide user equipment devices **402**, **404**, and **406** the media guidance application itself or software updates for the media guidance application.

(52) In some embodiments, the media guidance data may include viewer data. For example, the viewer data may include current and/or historical user activity information (e.g., what content the user typically watches, what times of day the user watches content, whether the user interacts with a social network, at what times the user interacts with a social network to post information, what types of content the user typically watches (e.g., pay TV or free TV), mood, brain activity information, etc.). The media guidance data may also include subscription data. For example, the subscription data may identify to which sources or services a given user subscribes and/or to which sources or services the given user has previously subscribed but later terminated access (e.g., whether the user subscribes to premium channels, whether the user has added a premium level of services, whether the user has increased Internet speed). In some embodiments, the viewer data and/or the subscription data may identify patterns of a given user for a period of more than one year. The media guidance data may include a model (e.g., a survivor model) used for generating a score that indicates a likelihood a given user will terminate access to a service/source. For example, the media guidance application may process the viewer data with the subscription data using the model to generate a value or score that indicates a likelihood of whether the given user will terminate access to a particular service or source. In particular, a higher score may indicate a higher level of confidence that the user will terminate access to a particular service or source. Based on the score, the media guidance application may generate promotions and advertisements that entice the user to keep the particular service or source indicated by the score as one to which the user will likely terminate access.

(53) Media guidance applications may be, for example, stand-alone applications implemented on user equipment devices. For example, the media guidance application may be implemented as software or a set of executable instructions which may be stored in storage **308**, and executed by

control circuitry **304** of a user equipment device **300**. In some embodiments, media guidance applications may be client-server applications where only a client application resides on the user equipment device, and server application resides on a remote server. For example, media guidance applications may be implemented partially as a client application on control circuitry **304** of user equipment device **300** and partially on a remote server as a server application (e.g., media guidance data source **418**) running on control circuitry of the remote server. When executed by control circuitry of the remote server (such as media guidance data source **418**), the media guidance application may instruct the control circuitry to generate the guidance application displays and transmit the generated displays to the user equipment devices. The server application may instruct the control circuitry of the media guidance data source **418** to transmit data for storage on the user equipment. The client application may instruct control circuitry of the receiving user equipment to generate the guidance application displays.

(54) Content and/or media guidance data delivered to user equipment devices **402**, **404**, and **406** may be over-the-top (OTT) content. OTT content delivery allows Internet-enabled user devices, including any user equipment device described above, to receive content that is transferred over the Internet, including any content described above, in addition to content received over cable or satellite connections. OTT content is delivered via an Internet connection provided by an Internet service provider (ISP), but a third party distributes the content. The ISP may not be responsible for the viewing abilities, copyrights, or redistribution of the content, and may only transfer IP packets provided by the OTT content provider. Examples of OTT content providers include YOUTUBE, NETFLIX, and HULU, which provide audio and video via IP packets. Youtube is a trademark owned by Google Inc., Netflix is a trademark owned by Netflix Inc., and Hulu is a trademark owned by Hulu, LLC. OTT content providers may additionally or alternatively provide media guidance data described above. In addition to content and/or media guidance data, providers of OTT content can distribute media guidance applications (e.g., web-based applications or cloud-based applications), or the content can be displayed by media guidance applications stored on the user equipment device.

(55) Media guidance system **400** is intended to illustrate a number of approaches, or network configurations, by which user equipment devices and sources of content and guidance data may communicate with each other for the purpose of accessing content and providing media guidance. The embodiments described herein may be applied in any one or a subset of these approaches, or in a system employing other approaches for delivering content and providing media guidance. The following four approaches provide specific illustrations of the generalized example of FIG. **4**.

(56) In one approach, user equipment devices may communicate with each other within a home network. User equipment devices can communicate with each other directly via short-range point-to-point communication schemes described above, via indirect paths through a hub or other similar device provided on a home network, or via communications network **414**. Each of the multiple individuals in a single home may operate different user equipment devices on the home network. As a result, it may be desirable for various media guidance information or settings to be communicated between the different user equipment devices. For example, it may be desirable for users to maintain consistent media guidance application settings on different user equipment devices within a home network, as described in greater detail in Ellis et al., U.S. Patent Publication No. 2005/0251827, filed Jul. 11, 2005. Different types of user equipment devices in a home network may also communicate with each other to transmit content. For example, a user may transmit content from user computer equipment to a portable video player or portable music player.

(57) In a second approach, users may have multiple types of user equipment by which they access content and obtain media guidance. For example, some users may have home networks that are accessed by in-home and mobile devices. Users may control in-home devices via a media guidance application implemented on a remote device. For example, users may access an online media guidance application on a website via a personal computer at their office, or a mobile device such

as a PDA or web-enabled mobile telephone. The user may set various settings (e.g., recordings, reminders, or other settings) on the online guidance application to control the user's in-home equipment. The online guide may control the user's equipment directly, or by communicating with a media guidance application on the user's in-home equipment. Various systems and methods for user equipment devices communicating, where the user equipment devices are in locations remote from each other, is discussed in, for example, Ellis et al., U.S. Pat. No. 8,046,801, issued Oct. 25, 2011, which is hereby incorporated by reference herein in its entirety.

(58) In a third approach, users of user equipment devices inside and outside a home can use their media guidance application to communicate directly with content source **416** to access content. Specifically, within a home, users of user television equipment **402** and user computer equipment **404** may access the media guidance application to navigate among and locate desirable content. Users may also access the media guidance application outside of the home using wireless user communications devices **406** to navigate among and locate desirable content.

(59) In a fourth approach, user equipment devices may operate in a cloud computing environment to access cloud services. In a cloud computing environment, various types of computing services for content sharing, storage or distribution (e.g., video sharing sites or social networking sites) are provided by a collection of network-accessible computing and storage resources, referred to as "the cloud." For example, the cloud can include a collection of server computing devices, which may be located centrally or at distributed locations, that provide cloud-based services to various types of users and devices connected via a network such as the Internet via communications network **414**. These cloud resources may include one or more content sources **416** and one or more media guidance data sources **418**. In addition or in the alternative, the remote computing sites may include other user equipment devices, such as user television equipment **402**, user computer equipment **404**, and wireless user communications device **406**. For example, the other user equipment devices may provide access to a stored copy of a video or a streamed video. In such embodiments, user equipment devices may operate in a peer-to-peer manner without communicating with a central server.

(60) The cloud provides access to services, such as content storage, content sharing, or social networking services, among other examples, as well as access to any content described above, for user equipment devices. Services can be provided in the cloud through cloud computing service providers, or through other providers of online services. For example, the cloud-based services can include a content storage service, a content sharing site, a social networking site, or other services via which user-sourced content is distributed for viewing by others on connected devices. These cloud-based services may allow a user equipment device to store content to the cloud and to receive content from the cloud rather than storing content locally and accessing locally-stored content.

(61) A user may use various content capture devices, such as camcorders, digital cameras with video mode, audio recorders, mobile phones, and handheld computing devices, to record content. The user can upload content to a content storage service on the cloud either directly, for example, from user computer equipment **404** or wireless user communications device **406** having content capture feature. Alternatively, the user can first transfer the content to a user equipment device, such as user computer equipment **404**. The user equipment device storing the content uploads the content to the cloud using a data transmission service on communications network **414**. In some embodiments, the user equipment device itself is a cloud resource, and other user equipment devices can access the content directly from the user equipment device on which the user stored the content.

(62) Cloud resources may be accessed by a user equipment device using, for example, a web browser, a media guidance application, a desktop application, a mobile application, and/or any combination of access applications of the same. The user equipment device may be a cloud client that relies on cloud computing for application delivery, or the user equipment device may have some functionality without access to cloud resources. For example, some applications running on

the user equipment device may be cloud applications, i.e., applications delivered as a service over the Internet, while other applications may be stored and run on the user equipment device. In some embodiments, a user device may receive content from multiple cloud resources simultaneously. For example, a user device can stream audio from one cloud resource while downloading content from a second cloud resource. Or a user device can download content from multiple cloud resources for more efficient downloading. In some embodiments, user equipment devices can use cloud resources for processing operations such as the processing operations performed by processing circuitry described in relation to FIG. 3.

(63) FIG. 5 shows an illustrative embodiment of a user equipment device on which an image, portions of images, media asset identifiers, and other information are displayed, in accordance with some embodiments of the disclosure. FIG. 5 depicts user equipment **500** (which may include the functionality of user equipment **402**, **404**, and/or **406**). Control circuitry **304** may cause user equipment **500** to display media asset identifiers **502**, and image portions **504**. Control circuitry **304** may generate for display a given image portion **504** in a manner such that the given image portion **504** corresponds to an adjacent media asset identifier **502**. When control circuitry **304** detects a user selection of a given media asset identifier **502**, control circuitry **304** may cause a display of descriptive information **506** corresponding to the selected given media asset identifier **502**. Additionally, when control circuitry **304** detects a user selection of the given media asset identifier **502**, control circuitry **304** may generate for display image **508** that corresponds to the selected media asset identifier **502**. In some embodiments, image **508** may be a larger image from which image portion **504** was cropped. Any of elements **502**, **504**, **506**, and **508** may be optionally displayed or omitted from the display illustrated in FIG. 5. Furthermore, the manner in which elements **502**, **504**, **506**, and **508** is illustrated are merely illustrative, and these illustrations may be rearranged in any manner.

(64) In some embodiments, control circuitry **304** may identify an image corresponding to a media asset. For example, control circuitry **304** may determine that media asset identifier **502** corresponds to the media asset “Community,” which is a comedy series starring actors Joel McHale, Ken Jeong, and Chevy Chase. Control circuitry **304** may identify an image (e.g., image **508**) that corresponds to the media asset “Community.” Image **508** may be any image associated with “Community,” such as poster art, box art, fan art, a photograph, a frame of a video, or any other image including any actor or identifying information corresponding to the media asset identified by media asset identifier **502**. Control circuitry **304** may identify image **508** by cross-referencing a database (e.g., media guidance data source **418**, accessed by way of communications network **414**) that includes entries corresponding to media asset metadata. Image **508** may include a plurality of portions, where each portion includes a respective entity. For example, image **508** may correspond to the media asset “Community,” and may include depictions of Joel McHale, Chevy Chase, and Ken Jeong. Control circuitry **304** may partition image **508** into portions, where each portion includes an identified entity.

(65) In some embodiments, control circuitry **304** may determine an identity of each respective entity in each respective portion of the plurality of portions. Control circuitry **304** may determine the entity by using any known mechanism. As an example, control circuitry **304** may determine the identity of Chevy Chase in image **508** by accessing metadata corresponding to image **508** and determining therefrom that Chevy Chase is depicted in a certain part of image **508**. As another example, control circuitry **304** may utilize image recognition technology (e.g., facial recognition technology), where control circuitry **304** recognizes unique characteristics of each entity, and then cross-references those unique characteristics against a database (e.g., storage **306**) to find an entity that matches the characteristics. In some embodiments, when determining the identity of an entity of image **508**, control circuitry **304** may consult a knowledge graph and may provide the knowledge graph any metadata associated with a given entity, and/or may provide the knowledge graph with any other data associated with a given entity (such as data gleaned from image

recognition processes, and/or data gleaned from user interaction with images of entities similar to the given entity). Knowledge graphs and their features are described in greater detail in U.S. patent application Ser. No. 14/501,504, filed Sep. 30, 2014, U.S. patent application Ser. No. 14/500,309, filed Sep. 29, 2014, and U.S. patent application Ser. No. 14/448,308, filed Jul. 31, 2014, which are hereby incorporated by reference herein in their entireties.

(66) In some embodiments, control circuitry **304** may access a user profile from a database. For example, control circuitry may access a user profile of a current user of user equipment **500** by retrieving the user profile from a database. The database may be local (e.g., storage **306**) or remote (e.g., media guidance data source **418** or media content source **416**, accessible by way of communications network **414**). The user profile may indicate preferences of the user of user equipment **500**.

(67) In some embodiments, control circuitry **304** may cross-reference metadata of the user profile with each identity of each respective entity depicted in image **508**. In some embodiments, the metadata may comprise preference information corresponding to the user. For example, control circuitry **304** may cross-reference information corresponding to the user's preference for the actor Chevy Chase against the identity of Chevy Chase, as identified by control circuitry **304** above as an entity of image **508**. Control circuitry **304** may responsively identify a preferred entity based on the cross-referencing. For example, control circuitry **304** may determine that of Joel McHale, Chevy Chase, and Ken Jeong depicted in image **508**, where image **508** represents the media asset "Community," the user of user equipment **500** prefers Chevy Chase.

(68) In some embodiments, control circuitry **304** may generate for display the respective portion comprising the preferred entity. For example, the media guidance application illustrated in FIG. 5 may cause image portion **504** that is depicted next to media asset identifier **502** to be a cropped portion of image **508** that includes an entity that the user of user equipment **500** prefers. Following the "Community" example above, control circuitry **304** may crop a portion of image **508** that includes Chevy Chase, but does not include Joel McHale or Ken Jeong, and generate for display that cropped portion as image portion **504**. In this manner, control circuitry **304** may cause the media guidance application running on user equipment **500** to be personalized to a user such that portions of art corresponding to a given media asset identifier **502** are displayed in image **504**, instead of full image **508** which includes entities that the user is not interested in.

(69) In some embodiments, when control circuitry **304** is identifying the preferred entity based on the cross-referencing, control circuitry **304** may identify an affinity of the user with respect to each entity in the image. For example, control circuitry **304** may determine that a user profile reflects that a user really likes Chevy Chase, and may therefore identify a high affinity of the user with respect to Chevy Chase. Control circuitry **304** may identify that a user is indifferent with respect to Joel McHale, and may therefore identify a neutral affinity of the user with respect to Joel McHale. Control circuitry **304** may identify that a user dislikes Ken Jeong, and may therefore identify a negative affinity of the user with respect to Ken Jeong.

(70) In some embodiments, control circuitry **304** may rank each respective affinity. Following from the example above, control circuitry would rank the affinity from "high," to "neutral," to "negative." Accordingly, Chevy Chase would be ranked first, Joel McHale would be ranked second, and Ken Jeong would be ranked third.

(71) Control circuitry **304** may then identify a subset of adjacent portions of the plurality of portions that comprise respective entities associated with the highest combined rank as compared to each other subset of adjacent portions of the plurality of portions of image **508**. For example, image **508** may depict Joel McHale in a left portion of image **508**, Chevy Chase in a middle portion of image **508**, and Ken Jeong in a right portion of image **508**. Control circuitry **304** may determine adjacent entities. For example, Joel McHale and Chevy Chase are entities depicted in adjacent portions, as the left and middle portions of image **508** are adjacent to one another. Similarly, Chevy Chase and Ken Jeong are entities depicted in adjacent portions, as the middle and right portions of

image **508** are adjacent to one another. Control circuitry may combine the rank of each adjacent entity in any known manner, such as averaging the rank of the adjacent entities. For example, the average rank of Joel McHale and Chevy Chase would be 1.5, and the average rank of Chevy Chase and Ken Jeong would be 2.5.

(72) In some embodiments, control circuitry **304** may then generate for display image portion **504** as including the subset of image portions (e.g., the two or more adjacent image portions with the highest combined rank). In some embodiments, control circuitry **304** may perform similar processes using non-adjacent portions of image **508**, where the non-adjacent portions of image **508** that are to be depicted in image portion **504** are stitched together using any known image stitching mechanism.

(73) In some embodiments, control circuitry **304** may identify a plurality of preferred entities based on the cross-referencing. For example, control circuitry may, as discussed above, determine an affinity of the user for each entity of image **508**. Control circuitry **304** may determine a threshold entity, or retrieve a threshold affinity from a database (e.g., storage **308** or media guidance data source **418**). Control circuitry **304** may identify a plurality of preferred entities depicted in image **508** by determining which entities of image **508** correspond to an affinity that equals or exceeds the threshold affinity.

(74) In some embodiments, control circuitry **304** may generate for display a sufficient amount of the plurality of portions comprising entities of the plurality of preferred entities to satisfy a specified aspect ratio requirement. As an example, control circuitry **304** may determine a specified aspect ratio requirement by determining dimensions of image portion **504** that the media guidance application used by user equipment **500** is programmed to display. Control circuitry **304** may determine, that exactly two portions of image **508** are required to satisfy the determined dimensions. Control circuitry **304** may then select two portions for display as image portion **504** to satisfy the specified aspect ratio requirement (e.g., using any manner to select multiple portions described above and below).

(75) In some embodiments, control circuitry **304** may receive a selection by a user of the respective portion of image **508**, and may generate for display image portion **504** in response to receiving the selection. For example, control circuitry **304** may receive a selection or indication from the user that the user prefers Chevy Chase by the user selecting the depiction of Chevy Chase in image **508**. Alternatively, control circuitry **304** may receive this selection by the user describing Chevy Chase as a preferred actor in any known manner without specifically selecting Chevy Chase in image **508** itself. Control circuitry **304** may responsively generate for display image portion **504** including a portion of image **508** including Chevy Chase in response to receiving the selection.

(76) In some embodiments, control circuitry **304** may recognize textual content in image **508**. As an example, image **508** includes the textual content of the title of the media asset “Community.” Control circuitry **304** may recognize that the text “Community” exists in image **508**. Control circuitry **304** may generate for simultaneous display the textual content with the respective portion comprising the preferred entity. For example, control circuitry **304** may, when generating for display image portion **504**, include the textual content “Community” in the generated display of image portion **504**. Control circuitry **304** may maintain the composition of the textual content, or may alter it (e.g., in terms of style, content, size, or any other manner).

(77) In some embodiments, control circuitry **304** may determine that a plurality of images corresponding to a given media asset identifier **502** exist. Control circuitry may determine which image(s) **508** to generate for display by determining an image the user prefers in any manner described above or below with respect to determining which image portion **504** to generate for display. In some embodiments, a preferable image or a stitched set of preferable images may be generated for display where image portion **504** is generated for display, where preferable images or stitched sets of images are determined in any manner described above and below.

(78) In another aspect, control circuitry **304** may selectively generate for display portions of an

image (e.g., image portion **504**). Control circuitry **304** may achieve this end by first identifying an image corresponding to a media asset (e.g., image **508**), where the image comprises a plurality of portions, and wherein each portion of the plurality of portions comprises a respective entity. Control circuitry **304** may perform the identifying in any manner discussed above and below.

(79) In some embodiments, control circuitry **304** may determine an identity of each respective entity in each respective portion of the plurality of portions. Control circuitry **304** may determine the identity in any manner described above and below.

(80) In some embodiments, control circuitry **304** may access a database to determine a level of prevalence of each identity in the media asset. The database may be local to control circuitry **304** (e.g., at storage **308**), or remote to control circuitry **304** (e.g., at media guidance data source **418**, accessed by way of communications network **414**). Control circuitry **304** may, when accessing the database, retrieve information that may be used to determine a level of prevalence of each identity in the media asset. For example, control circuitry **304** may retrieve information relating to screen time, amount of time in close-up footage, amount of time in wide shot footage, an amount of time of being the sole character in a frame for each identity with respect to the media asset. Control circuitry **304** may determine the level of prevalence by comparing any of, or a combination of, these factors, with respect to any given identity. In some embodiments, control circuitry **304** may determine which respective entity corresponds to a highest level of prevalence. For example, after control circuitry **304** has determined a level of prevalence for each identity, control circuitry **304** may determine which respective entity has the highest level of prevalence. For example, following from the “Community” example, Joel McHale has more screen time in “Community” than Chevy Chase, and thus Joel McHale may be assigned a higher level of prevalence than Chevy Chase.

(81) In some embodiments, control circuitry **304** may generate for display a respective portion comprising the respective entity that corresponds to the highest level of prevalence (e.g., at image portion **504** or image **508**). Control circuitry **304** may generate for display the respective portion in any manner described above and below.

(82) In some embodiments, control circuitry **304** may access a user profile from a database, cross-reference metadata of the user profile with each identity of each respective entity, and rank each respective entity based on the cross-referencing. Control circuitry **304** may perform these functions in any manner described above and below.

(83) In some embodiments, control circuitry **304** may weight each respective entity based on a respective level of prevalence corresponding to the respective entity. For example, following from the example above, if Joel McHale is more prevalent than Chevy Chase and Ken Jeong because Joel McHale has relatively more screen time in the media asset “Community,” then control circuitry **304** may assign Joel McHale a high weight.

(84) In some embodiments, control circuitry **304** may heuristically combine the rank and weight of each respective entity to determine a combined rank of each respective entity. For example, if control circuitry **304** determines that a user has a strong preference for Ken Jeong, and Ken Jeong has a low weight because he is not so prevalent in the media asset “Community,” and control circuitry **304** determines that a user strongly dislikes Joel McHale, but that Joel McHale has a high prevalence, control circuitry **304** may consider all these factors heuristically to determine a combined rank. Because, in this case, Joel McHale is so strongly disliked, control circuitry **304** may attribute a higher combined weight to Ken Jeong. Control circuitry **304** may then generate for display (e.g., on display **312** of user equipment **500** at image portion **504**) a respective portion comprising the respective entity that corresponds to the highest combined rank (in this case, an image including Ken Jeong).

(85) In some embodiments, control circuitry **304** may identify a plurality of prevalent entities by determining two or more entities with the highest prevalence levels, relative to each other entity, and generate for display (e.g., on display **312**) a sufficient amount of the plurality of portions comprising entities of the plurality of preferred entities to satisfy a specified aspect ratio

requirement. For example, control circuitry **304** may identify Ken Jeong and Joel McHale as having the two highest prevalence levels (in accordance with any manner described above and below). Control circuitry **304** may identify two identities if a specified aspect ratio requirement can accommodate only two portions. Control circuitry **304** may crop the portions including Ken Jeong and Joel McHale and generate for display the cropped image. The specified aspect ratio may be a height to width ratio or a specified dimension of image portion **504** that control circuitry **304** is required to meet when generating for display an image or image portion.

(86) In some embodiments, control circuitry **304** may determine characteristics of the entity that correspond to the highest level of prevalence, and may then determine optimal characteristics for features surrounding the entity in the respective portion corresponding to the entity that corresponds to the highest level of prevalence. Based on the determined optimal characteristics, control circuitry **304** may alter characteristics of the features surrounding the entity to reflect the optimal characteristics. For example, control circuitry **304** may consider the skin tone of the entity that corresponds to the highest level of prevalence, and may then lighten or darken surrounding features of the image (e.g., image portion **504** or image **508**), such as the color of the sky or background surrounding the depiction of the entity corresponding to the highest level of prevalence.

(87) Any feature described above with respect to any other aspect or embodiment of this disclosure may be implemented when selectively generating for display portion of an image based on level of prevalence.

(88) In some aspects, control circuitry **304** may identify a plurality of images corresponding to a media asset, where each image of the plurality of images comprises at least one portion, and where each portion comprises a respective entity. For example, control circuitry **304** may identify a poster, picture, box art, and/or the like, that corresponds to a media asset, such as the hit series “Community” starring actors Joel McHale, Chevy Chase, and Ken Jeong. The images identified by control circuitry **304** may include several portions, where each portion includes a respective entity. For example, control circuitry **304** may determine that the image (e.g., image **508**) portrays each of Joel McHale, Chevy Chase, and Ken Jeong, and control circuitry **304** may demark each portion that contains each separate actor as a separate portion of the image.

(89) In some embodiments, control circuitry **304** may determine an identity of each respective entity. Following the example from above, control circuitry **304** may determine that one entity represents Joel McHale, another entity represents Chevy Chase, and another entity represents Ken Jeong. Control circuitry **304** may make these determinations based on image recognition algorithms, by consulting metadata corresponding to the image, or by any other known mechanism. Any manner of identifying images and determining an identity of a respective entity described above and is contemplated for use in this aspect.

(90) In some embodiments, control circuitry **304** may access a user profile from a database. For example, control circuitry **304** may query a remote or local database to access a user profile that corresponds to a present user of a user equipment that control circuitry **304** is implemented in or associated with. Control circuitry **304** may, responsive to the query, receive information from the user profile. Any manner of accessing a user profile discussed above and below is contemplated for use in this aspect.

(91) In some embodiments, control circuitry **304** may cross-reference metadata of the user profile with each identity of each respective entity. For example, control circuitry **304** may compare information of the user profile with information corresponding to each entity. Following from the example above, control circuitry **304** may cross-reference information indicating user preferences from the user profile against metadata corresponding to each of Joel McHale, Ken Jeong, and Chevy Chase, in an effort to determine which actor(s) the user may prefer. Control circuitry **304** may then identify a preferred entity based on the cross-referencing. Any manner of cross-referencing metadata of a user profile with an identity of a respective entity, described above and

below, is contemplated for use in this aspect.

(92) In some embodiments, control circuitry **304** may determine an image of the plurality of images where the preferred entity is more prevalent, and may generate for display that image (e.g., at image portion **504** or image **508**). For example, control circuitry **304** may determine that Ken Jeong is the preferred entity. Control circuitry **304** may determine that there are three candidate images in the plurality of images, where one includes all of Joel McHale, Ken Jeong, and Chevy Chase, one includes only Ken Jeong, and one includes the entire cast of the media asset “Community.” Control circuitry **304** may determine that the image including only Ken Jeong is the image in which Ken Jeong is most prevalent. Control circuitry **304** may then generate for display the image including Ken Jeong. The display of the image may be generated using any manner discussed above and below with respect to other embodiments. A determination of prevalence may be made consistent with any discussion of determining a level of prevalence, as discussed above and below. All other embodiments of any aspect described above and below are contemplated as applicable embodiments for this aspect involving selectively generating for display an image of a plurality of images.

(93) FIG. **6** is a flowchart of illustrative steps involved in determining which portion of an image to generate for display. It should be noted that process **600** or any step thereof could be performed on, or provided by, any of the devices shown in FIGS. **3-5**. For example, process **600** may be executed by control circuitry **304** (FIG. **3**) as instructed by control circuitry implemented on user equipment **402**, **404**, and/or **406** (FIG. **4**) in order to determine which portion of an image to generate for display. In addition, one or more steps of process **600** may be incorporated into or combined with one or more steps of any other process or embodiment, such as those described in FIG. **7** and FIG. **8**.

(94) Process **600** begins at **602**, where control circuitry **304** may identify an image corresponding to a media asset, where the image includes *n* portions, and where each portion of the *n* portions comprises a respective entity. For example, control circuitry **304** may determine that media asset identifier **502** corresponds to the media asset “Community,” which is a comedy series starring actors Joel McHale, Ken Jeong, and Chevy Chase. Control circuitry **304** may identify an image (e.g., image **508**) that corresponds to the media asset “Community.” Control circuitry **304** may identify image **508** by cross-referencing a database (e.g., media guidance data source **418**, accessed by way of communications network **414**) that includes entries corresponding to media asset metadata. Image **508** may include a plurality of portions, where each portion includes a respective entity. For example, image **508** may correspond to the media asset “Community,” and may include depictions of Joel McHale, Chevy Chase, and Ken Jeong. Control circuitry **304** may partition image **508** into portions, where each portion includes an identified entity (in this case, *n*=3).

(95) Process **600** may then continue to **604**, where control circuitry **304** may determine an identity of each respective entity in each respective portion of the plurality of portions. Control circuitry **304** may determine the entity by using any known mechanism. As an example, control circuitry **304** may determine the identity of Chevy Chase in image **508** by accessing metadata corresponding to image **508** and determining therefrom that Chevy Chase is depicted in a certain part of image **508**. As another example, control circuitry **304** may utilize image recognition technology (e.g., facial recognition technology), where control circuitry **304** recognizes unique characteristics of each entity, and then cross-references those unique characteristics against a database (e.g., storage **306**) to find an entity that matches the characteristics.

(96) Process **600** may then continue to **606**, where control circuitry **304** may access a user profile from a database. For example, control circuitry may access a user profile of a current user of user equipment **500** by retrieving the user profile from a database. The database may be local (e.g., storage **306**) or remote (e.g., media guidance data source **418** or media content source **416**, accessible by way of communications network **414**). The user profile may indicate preferences of the user of user equipment **500**.

(97) Process **600** may then continue to **608**, where a counter *i* is initialized to 1. Process **600** may then continue to **610**, where control circuitry **304** may cross-reference metadata of the user profile with the identity of the entity in the *i*th portion of image **508**. In some embodiments, the metadata may comprise preference information corresponding to the user. For example, control circuitry **304** may cross-reference information corresponding to the user's preference for the actor Chevy Chase against the identity of Chevy Chase, as identified by control circuitry **304** above as an entity of image **508**.

(98) Process **600** may then continue to **612**, where control circuitry **304** determines whether the counter equals the number of *n* portions in image **508**. If the counter *i* does not equal *n*, then process **600** may loop back to **610** after incrementing counter *i* by one. If the counter *i* does equal *n*, then process **600** may continue to **614**, where control circuitry **304** may identify a preferred entity based on the cross-referencing. For example, control circuitry **304** may determine that of Joel McHale, Chevy Chase, and Ken Jeong depicted in image **508**, where image **508** represents the media asset "Community," the user of user equipment **500** prefers Chevy Chase.

(99) Process **600** may then continue to **616**, where control circuitry **304** may generate for display the respective portion comprising the preferred entity. For example, the media guidance application illustrated in FIG. 5 may cause image portion **504** that is depicted next to media asset identifier **502** to be a cropped portion of image **508** that includes an entity that the user of user equipment **500** prefers. Following the "Community" example above, control circuitry **304** may crop a portion of image **508** that includes Chevy Chase, but does not include Joel McHale or Ken Jeong, and generate for display that cropped portion as image portion **504**. In this manner, control circuitry **304** may cause the media guidance application running on user equipment **500** to be personalized to a user such that portions of art corresponding to a given media asset identifier **502** are displayed in image **504**, instead of full image **508** which includes entities that the user is not interested in.

(100) It is contemplated that the steps or descriptions of FIG. 6 may be used with any other embodiment of this disclosure. In addition, the steps and descriptions described in relation to FIG. 6 may be done in alternative orders or in parallel to further the purposes of this disclosure. For example, each of these steps may be performed in any order or in parallel or substantially simultaneously to reduce lag or increase the speed of the system or method. Furthermore, it should be noted that any of the devices or equipment discussed in relation to FIGS. 3-5 could be used to perform one or more of the steps in FIG. 6.

(101) FIG. 7 is a flowchart of illustrative steps involved in determining which portion of an image to generate for display based on a level of prevalence of an identity of an entity in a media asset, in accordance with some embodiments of the disclosure. It should be noted that process **700** or any step thereof could be performed on, or provided by, any of the devices shown in FIGS. 3-5. For example, process **700** may be executed by control circuitry **304** (FIG. 3) as instructed by control circuitry implemented on user equipment **402**, **404**, and/or **406** (FIG. 4) in order to determine which portion of an image to generate for display. In addition, one or more steps of process **600** may be incorporated into or combined with one or more steps of any other process or embodiment, such as those described in FIG. 6 and FIG. 8.

(102) Process **700** begins at **702**, control circuitry (e.g., control circuitry **304**) may identify an image corresponding to a media asset, where the image comprises a plurality of portions, and where each portion of the plurality of portions comprises a respective entity. For example, control circuitry **304** may determine that media asset identifier **502** corresponds to the media asset "Community," which is a comedy series starring actors Joel McHale, Ken Jeong, and Chevy Chase. Control circuitry **304** may identify an image (e.g., image **508**) that corresponds to the media asset "Community." Control circuitry **304** may identify image **508** by cross-referencing a database (e.g., media guidance data source **418**, accessed by way of communications network **414**)) that includes entries corresponding to media asset metadata. Image **508** may include a plurality of portions, where each portion includes a respective entity. For example, image **508** may correspond to the

media asset “Community,” and may include depictions of Joel McHale, Chevy Chase, and Ken Jeong, which are respective entities of three different portions of image **508**. Process **700** may continue to **704**.

(103) At **704**, control circuitry **304** may determine an identity of each respective entity in each respective portion of the plurality of portions. Control circuitry **304** may determine the entity by using any known mechanism. As an example, control circuitry **304** may determine the identity of Chevy Chase in image **508** by accessing metadata corresponding to image **508** and determining therefrom that Chevy Chase is depicted in a certain part of image **508**. As another example, control circuitry **304** may utilize image recognition technology (e.g., facial recognition technology), where control circuitry **304** recognizes unique characteristics of each entity, and then cross-references those unique characteristics against a database (e.g., storage **306**) to find an entity that matches the characteristics. Process **700** may then continue to **706**.

(104) At **706**, control circuitry **304** may access a database to determine a level of prevalence of each identity in the media asset. Control circuitry **304** may determine the level of prevalence in any manner described above and below, such as by determining an amount of screen time in the media asset for each identity. For example, control circuitry **304** may determine that Joel McHale has 14 minutes of screen time, Ken Jeong has 3 minutes of screen time, and Chevy Chase has 1 minute of screen time, in an episode of “Community.” Process **700** may then continue to **708**.

(105) At **708**, control circuitry **304** may determine which respective entity corresponds to a highest level of prevalence. Control circuitry **304** may do this, for example, by comparing each level of prevalence against one another to determine the largest level of prevalence. Following from the example above regarding screen time, because Joel McHale has the longest amount of screen time in a given episode of “Community,” control circuitry **304** will determine that Joel McHale corresponds to a highest level of prevalence. Process **700** may then continue to **710**.

(106) At **710**, control circuitry **304** may generate for display a respective portion comprising the respective entity that corresponds to the highest level of prevalence. Following from the example above, control circuitry **304** may generate for display (e.g., at image portion **504**) the portion comprising Joel McHale of image **508**.

(107) It is contemplated that the steps or descriptions of FIG. **7** may be used with any other embodiment of this disclosure. In addition, the steps and descriptions described in relation to FIG. **7** may be done in alternative orders or in parallel to further the purposes of this disclosure. For example, each of these steps may be performed in any order or in parallel or substantially simultaneously to reduce lag or increase the speed of the system or method. Furthermore, it should be noted that any of the devices or equipment discussed in relation to FIGS. **3-5** could be used to perform one or more of the steps in FIG. **7**.

(108) FIG. **8** is a flowchart of illustrative steps involved in selectively generating for display an image of a plurality of images where a user-preferred entity is most prevalent, in accordance with some embodiments of the disclosure. It should be noted that process **800** or any step thereof could be performed on, or provided by, any of the devices shown in FIGS. **3-5**. For example, process **800** may be executed by control circuitry **304** (FIG. **3**) as instructed by control circuitry implemented on user equipment **402**, **404**, and/or **406** (FIG. **4**) in order to determine which portion of an image to generate for display. In addition, one or more steps of process **800** may be incorporated into or combined with one or more steps of any other process or embodiment, such as those described in FIG. **6** and FIG. **7**.

(109) Process **800** beings at **802**, where control circuitry (e.g., control circuitry **304**) may identify a plurality of images corresponding to a media asset, where each image of the plurality of images comprises at least one portion, and where each portion comprises a respective entity. For example, control circuitry **304** may identify multiple images corresponding to “Community,” where one image corresponds to Joel McHale, one image corresponds to Chevy Chase, and one image includes all of Joel McHale, Chevy Chase, and Ken Jeong. Process **800** may then continue to **804**.

(110) At **804**, control circuitry **304** may determine an identity of each respective entity. Control circuitry **304** may determine the identity using any manner described above and below, such as image recognition techniques or an analysis of metadata associated with the image to determine the identity. Process **800** may then continue to **806**.

(111) At **806**, control circuitry **304** may access a user profile from a database. Control circuitry **304** may access the user profile in any manner described above and below, such as by accessing a database at media guidance data source **418** by way of communications network **414**. Process **800** may then continue to **808**.

(112) At **808**, control circuitry **304** may cross-reference metadata of the user profile with each identity of each respective identity. The cross-referencing of the metadata of the user profile with each identity of each respective entity may be performed consistent with any manner described above and below. The cross-referencing of metadata with of the user profile with each identity of each respective identity may yield information about a user's preferences with each identity. Process **800** may then continue to **810**.

(113) At **810**, control circuitry **304** may identify a preferred entity based on the cross-referencing. For example, control circuitry **304** may determine that the user prefers supporting cast comedians, such as Chevy Chase, and does not prefer the main character Joel McHale. Process **800** may then continue to **812**.

(114) At **812**, control circuitry **304** may determine an image of the plurality of images where the preferred entity is most prevalent. Following from the example above, control circuitry **304** may determine that there is an image that includes only Chevy Chase, and another image including Chevy Chase, Joel McHale, and Ken Jeong. Control circuitry **304** may determine that the image including only Chevy Chase is an image where Chevy Chase is most prevalent. Process **800** may then continue to **814**, where control circuitry **304** may generate for display the image including only Chevy Chase.

(115) It is contemplated that the steps or descriptions of FIG. **8** may be used with any other embodiment of this disclosure. In addition, the steps and descriptions described in relation to FIG. **8** may be done in alternative orders or in parallel to further the purposes of this disclosure. For example, each of these steps may be performed in any order or in parallel or substantially simultaneously to reduce lag or increase the speed of the system or method. Furthermore, it should be noted that any of the devices or equipment discussed in relation to FIGS. **3-5** could be used to perform one or more of the steps in FIG. **8**.

(116) It will be apparent to those of ordinary skill in the art that methods involved in the present invention may be embodied in a computer program product that includes a computer-usable and/or readable medium. For example, such a computer-usable medium may consist of a read-only memory device, such as a CD-ROM disk or conventional ROM devices, or a random access memory, such as a hard drive device or a computer diskette, having a computer-readable program code stored thereon. It should also be understood that methods, techniques, and processes involved in the present invention may be executed using processing circuitry. For instance, determination which portion of image **508** to generate for display may be performed by processing circuitry, e.g., by processing circuitry **306** of FIG. **3**. The processing circuitry, for instance, may be a general purpose processor, a customized integrated circuit (e.g., an ASIC), or a field-programmable gate array (FPGA) within user equipment **300**, media content source **416**, or media guidance data source **418**. For example, the media asset correspondences as described herein may be stored in, and retrieved from, storage **308** of FIG. **3**, or media guidance data source **418** of FIG. **4**. Furthermore, processing circuitry, or a computer program, may update settings associated with a user, such as user profile preferences, updating the information stored within storage **308** of FIG. **3** or media guidance data source **418** of FIG. **4**.

(117) The processes discussed above are intended to be illustrative and not limiting. One skilled in the art would appreciate that the steps of the processes discussed herein may be omitted, modified,

combined, and/or rearranged, and any additional steps may be performed without departing from the scope of the invention. More generally, the above disclosure is meant to be exemplary and not limiting. Only the claims that follow are meant to set bounds as to what the present invention includes. Furthermore, it should be noted that the features and limitations described in any one embodiment may be applied to any other embodiment herein, and flowcharts or examples relating to one embodiment may be combined with any other embodiment in a suitable manner, done in different orders, or done in parallel. In addition, the systems and methods described herein may be performed in real time. It should also be noted, the systems and/or methods described above may be applied to, or used in accordance with, other systems and/or methods.

Claims

1. A method for selectively generating for display portions of an image, the method comprising: identifying an image corresponding to a requested media asset, wherein the image comprises a plurality of portions, and wherein each portion of the plurality of portions comprises a respective depiction of a person; determining a level of prevalence of each respective person in the requested media asset, wherein the level of prevalence corresponds to a relative amount of time the respective person is present in the requested media asset; determining a target aspect ratio; determining, based on the target aspect ratio, a target number of portions of the plurality of portions; identifying a plurality of selected portions based on the target number of portions and the respective level of prevalence of each person corresponding to the plurality of portions; cropping out each of the plurality of selected portions, wherein at least two of the plurality of selected portions are non-adjacent portions of the plurality of portions; stitching the plurality of selected portions together to generate a stitched image; and generating for display, the stitched image.
2. The method of claim 1, further comprising: determining an identity of each respective person depicted in each respective portion of the plurality of portions by performing facial recognition on each respective depiction of a person of the image.
3. The method of claim 1, further comprising: recognizing textual content in the image; and generating for simultaneous display the textual content with the stitched image.
4. The method of claim 1, further comprising: determining characteristics of persons depicted in the plurality of selected portions; determining, based on the characteristics of the persons, optimal characteristics for features surrounding the persons; and altering characteristics of the features surrounding the persons to reflect the optimal characteristics.
5. The method of claim 1, wherein the level of prevalence of each respective person is determined based on at least one of screen time, amount of time in close-up footage, amount of time in wide shot footage, and amount of time of being a sole character in a frame in the requested media asset.
6. A system for selectively generating for display portions of an image, the system comprising: memory; control circuitry configured to: identify an image, stored in the memory, corresponding to a requested media asset, wherein the image comprises a plurality of portions, and wherein each portion of the plurality of portions comprises a respective depiction of a person; determine a level of prevalence of each respective person in the requested media asset, wherein the level of prevalence corresponds to a relative amount of time the respective person is present in the requested media asset; determine a target aspect ratio; determine, based on the target aspect ratio, a target number of portions of the plurality of portions; identify a plurality of selected portions based on the target number of portions and the respective level of prevalence of each person corresponding to the plurality of portions; crop out each of the plurality of selected portions, wherein at least two of the plurality of selected portions are non-adjacent portions of the plurality of portions; stitch the plurality of selected portions together to generate a stitched image; and generate for display, the stitched image.
7. The system of claim 6, wherein the control circuitry is further configured to determine an

identity of each respective person depicted in each respective portion of the plurality of portions by performing facial recognition on each respective depiction of a person of the image.

8. The system of claim 6, wherein the control circuitry is further configured to: recognize textual content in the image; and generate for simultaneous display the textual content with the stitched image.

9. The system of claim 6, wherein the control circuitry is further configured to: determine characteristics of persons depicted in the plurality of selected portions; determine, based on the characteristics of the persons, optimal characteristics for features surrounding the persons; and alter characteristics of the features surrounding the persons to reflect the optimal characteristics.

10. The system of claim 6, wherein the control circuitry is further configured to determine the level of prevalence of each respective person based on at least one of screen time, amount of time in close-up footage, amount of time in wide shot footage, and amount of time of being a sole character in a frame in the requested media asset.

11. A non-transitory computer-readable medium having instructions encoded thereon, that when executed by control circuitry causes the control circuitry to: identify an image corresponding to a requested media asset, wherein the image comprises a plurality of portions, and wherein each portion of the plurality of portions comprises a respective depiction of a person; determine a level of prevalence of each respective person in the requested media asset, wherein the level of prevalence corresponds to a relative amount of time the respective person is present in the requested media asset; determine a target aspect ratio; determine, based on the target aspect ratio, a target number of portions of the plurality of portions; identify a plurality of selected portions based on the target number of portions and the respective level of prevalence of each person corresponding to the plurality of portions; crop out each of the plurality of selected portions, wherein at least two of the plurality of selected portions are non-adjacent portions of the plurality of portions; stitch the plurality of selected portions together to generate a stitched image; and generate for display, the stitched image.

12. The non-transitory computer-readable medium of claim 11, wherein the instructions further cause control circuitry to determine an identity of each respective person depicted in each respective portion of the plurality of portions by performing facial recognition on each respective depiction of a person of the image.

13. The non-transitory computer-readable medium of claim 11, wherein the instructions further cause control circuitry to: recognize textual content in the image; and generate for simultaneous display the textual content with a subset with the stitched image.

14. The non-transitory computer-readable medium of claim 11, wherein the instructions further cause control circuitry to: determine, based on characteristics of persons depicted in the plurality of selected portions, optimal characteristics for features surrounding the persons; and alter characteristics of the features surrounding the persons to reflect the optimal characteristics.

15. The non-transitory computer-readable medium of claim 11, wherein the instructions further cause control circuitry to determine the level of prevalence of each respective person based on at least one of screen time, amount of time in close-up footage, amount of time in wide shot footage, and amount of time of being a sole character in a frame in the requested media asset.
