

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12406466

Kind Code

B1

Date of Patent

September 02, 2025

Inventor(s)

Sommerlade; Eric et al.

Gaze correction of multi-view images

Abstract

Gaze is corrected by adjusting multi-view images of a head. Image patches containing the left and right eyes of the head are identified and a feature vector is derived from plural local image descriptors of the image patch in at least one image of the multi-view images. A displacement vector field representing a transformation of an image patch is derived, using the derived feature vector to look up reference data comprising reference displacement vector fields associated with possible values of the feature vector produced by machine learning. The multi-view images are adjusted by transforming the image patches containing the left and right eyes of the head in accordance with the derived displacement vector field.

Inventors: Sommerlade; Eric (Oxford, GB), Robinson; Michael G. (Boulder, CO)

Applicant: RealD Spark, LLC (Boulder, CO)

Family ID: 59226845

Assignee: RealD Spark, LLC (Boulder, CO)

Appl. No.: 18/514040

Filed: November 20, 2023

Related U.S. Application Data

continuation parent-doc US 17703039 20220324 US 11854243 child-doc US 18514040
continuation parent-doc US 16937382 20200723 US 11317081 20220426 child-doc US 17703039
continuation parent-doc US 16405415 20190507 US 10750160 20200818 child-doc US 16937382
continuation parent-doc US 15397951 20170104 US 10321123 20190611 child-doc US 16405415
us-provisional-application US 62274897 20160105

Publication Classification

Int. Cl.: **G06F3/01** (20060101); **G06V10/46** (20220101); **G06V10/62** (20220101); **G06V40/18** (20220101); **H04N7/14** (20060101); **H04N7/15** (20060101); **H04N13/344** (20180101); H04N13/117 (20180101)

U.S. Cl.:

CPC **G06V10/62** (20220101); **G06F3/011** (20130101); **G06F3/013** (20130101); **G06V10/462** (20220101); **G06V40/193** (20220101); **H04N7/147** (20130101); **H04N7/15** (20130101); **H04N13/344** (20180501); H04N13/117 (20180501)

Field of Classification Search

CPC: G06V (10/62); G06V (10/462); G06V (40/193); G06F (3/011); G06F (3/013); H04N (7/147); H04N (7/15); H04N (13/344); H04N (13/117)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1128979	12/1914	Hess	N/A	N/A
1970311	12/1933	Ives	N/A	N/A
2133121	12/1937	Stearns	N/A	N/A
2247969	12/1940	Stewart	N/A	N/A
2480178	12/1948	Zinberg	N/A	N/A
2810905	12/1956	Barlow	N/A	N/A
3409351	12/1967	Winnek	N/A	N/A
3715154	12/1972	Bestenreiner	N/A	N/A
4057323	12/1976	Ward	N/A	N/A
4528617	12/1984	Blackington	N/A	N/A
4542958	12/1984	Young	N/A	N/A
4804253	12/1988	Stewart	N/A	N/A
4807978	12/1988	Grinberg et al.	N/A	N/A
4829365	12/1988	Eichenlaub	N/A	N/A
4914553	12/1989	Hamada et al.	N/A	N/A
5050946	12/1990	Hathaway et al.	N/A	N/A
5278608	12/1993	Taylor et al.	N/A	N/A
5347644	12/1993	Sedlmayr	N/A	N/A
5349419	12/1993	Taguchi et al.	N/A	N/A
5459592	12/1994	Shibatani et al.	N/A	N/A
5466926	12/1994	Sasano et al.	N/A	N/A
5499303	12/1995	Hundt et al.	N/A	N/A
5510831	12/1995	Mayhew	N/A	N/A
5528720	12/1995	Winston et al.	N/A	N/A
5581402	12/1995	Taylor	N/A	N/A
5588526	12/1995	Fantone et al.	N/A	N/A
5697006	12/1996	Taguchi et al.	N/A	N/A
5703667	12/1996	Ochiai	N/A	N/A
5727107	12/1997	Umemoto et al.	N/A	N/A
5771066	12/1997	Barnea	N/A	N/A

5796451	12/1997	Kim	N/A	N/A
5808792	12/1997	Woodgate et al.	N/A	N/A
5875055	12/1998	Morishima et al.	N/A	N/A
5896225	12/1998	Chikazawa	N/A	N/A
5903388	12/1998	Sedlmayr	N/A	N/A
5933276	12/1998	Magee	N/A	N/A
5956001	12/1998	Sumida et al.	N/A	N/A
5959664	12/1998	Woodgate	N/A	N/A
5969850	12/1998	Harrold et al.	N/A	N/A
5971559	12/1998	Ishikawa et al.	N/A	N/A
6008484	12/1998	Woodgate et al.	N/A	N/A
6014164	12/1999	Woodgate et al.	N/A	N/A
6023315	12/1999	Harrold et al.	N/A	N/A
6055013	12/1999	Woodgate et al.	N/A	N/A
6061179	12/1999	Inoguchi et al.	N/A	N/A
6061489	12/1999	Ezra et al.	N/A	N/A
6064424	12/1999	Berkel et al.	N/A	N/A
6075557	12/1999	Holliman et al.	N/A	N/A
6094216	12/1999	Taniguchi et al.	N/A	N/A
6108059	12/1999	Yang	N/A	N/A
6118584	12/1999	Berkel et al.	N/A	N/A
6128054	12/1999	Schwarzenberger	N/A	N/A
6172723	12/2000	Inoue et al.	N/A	N/A
6199995	12/2000	Umemoto et al.	N/A	N/A
6224214	12/2000	Martin et al.	N/A	N/A
6232592	12/2000	Sugiyama	N/A	N/A
6256447	12/2000	Laine	N/A	N/A
6262786	12/2000	Perlo et al.	N/A	N/A
6283858	12/2000	Hayes, Jr. et al.	N/A	N/A
6295109	12/2000	Kubo et al.	N/A	N/A
6302541	12/2000	Grossmann	N/A	N/A
6305813	12/2000	Lekson et al.	N/A	N/A
6373637	12/2001	Gulick et al.	N/A	N/A
6377295	12/2001	Woodgate et al.	N/A	N/A
6422713	12/2001	Fohl et al.	N/A	N/A
6456340	12/2001	Margulis	N/A	N/A
6464365	12/2001	Gunn et al.	N/A	N/A
6476850	12/2001	Erbey	N/A	N/A
6556196	12/2002	Blanz et al.	N/A	N/A
6654156	12/2002	Crossland et al.	N/A	N/A
6663254	12/2002	Ohsumi	N/A	N/A
6677980	12/2003	Jeon	N/A	N/A
6724452	12/2003	Takeda et al.	N/A	N/A
6731355	12/2003	Miyashita	N/A	N/A
6736512	12/2003	Balogh	N/A	N/A
6798406	12/2003	Jones et al.	N/A	N/A
6801243	12/2003	Berkel	N/A	N/A
6806898	12/2003	Toyama et al.	N/A	N/A
6816158	12/2003	Lemelson et al.	N/A	N/A
6825985	12/2003	Brown et al.	N/A	N/A

6847488	12/2004	Travis	N/A	N/A
6859240	12/2004	Brown et al.	N/A	N/A
6867828	12/2004	Taira et al.	N/A	N/A
6919892	12/2004	Cheiky et al.	N/A	N/A
6975755	12/2004	Baumberg	N/A	N/A
7001058	12/2005	Inditsky	N/A	N/A
7058252	12/2005	Woodgate et al.	N/A	N/A
7091931	12/2005	Yoon	N/A	N/A
7101048	12/2005	Travis	N/A	N/A
7136031	12/2005	Lee et al.	N/A	N/A
7215391	12/2006	Kuan et al.	N/A	N/A
7215475	12/2006	Woodgate et al.	N/A	N/A
7227567	12/2006	Beck et al.	N/A	N/A
7239293	12/2006	Perlin et al.	N/A	N/A
7365908	12/2007	Dolgoﬀ	N/A	N/A
7375886	12/2007	Lipton et al.	N/A	N/A
7410286	12/2007	Travis	N/A	N/A
7430358	12/2007	Qi et al.	N/A	N/A
7492346	12/2008	Manabe et al.	N/A	N/A
7524053	12/2008	Lipton	N/A	N/A
7528893	12/2008	Schultz et al.	N/A	N/A
7545429	12/2008	Travis	N/A	N/A
7614777	12/2008	Koganezawa et al.	N/A	N/A
7697735	12/2009	Adam et al.	N/A	N/A
7750981	12/2009	Shestak et al.	N/A	N/A
7750982	12/2009	Nelson et al.	N/A	N/A
7771102	12/2009	Iwasaki	N/A	N/A
7798698	12/2009	Segawa	N/A	N/A
7798699	12/2009	Laitinen et al.	N/A	N/A
7826668	12/2009	Zaklika et al.	N/A	N/A
7864253	12/2010	Tajiri	N/A	N/A
8016475	12/2010	Travis	N/A	N/A
8144135	12/2011	Griffin	345/184	G06F 3/0362
8144153	12/2011	Sullivan et al.	N/A	N/A
8199152	12/2011	Sullivan et al.	N/A	N/A
8223296	12/2011	Lee et al.	N/A	N/A
8331615	12/2011	Furukawa et al.	N/A	N/A
8390680	12/2012	Perez et al.	N/A	N/A
8556491	12/2012	Lee	N/A	N/A
8670019	12/2013	Byers	N/A	N/A
8684588	12/2013	Ajichi et al.	N/A	N/A
8760762	12/2013	Kelly et al.	N/A	N/A
8824779	12/2013	Smyth	N/A	N/A
8908008	12/2013	Tan et al.	N/A	N/A
8926112	12/2014	Uchiike et al.	N/A	N/A
8942283	12/2014	Pace	N/A	N/A
8942434	12/2014	Karakotsios et al.	N/A	N/A
9058765	12/2014	Mallick et al.	N/A	N/A
9104908	12/2014	Rogers et al.	N/A	N/A

9197884	12/2014	Lee et al.	N/A	N/A
9224060	12/2014	Ramaswamy	N/A	N/A
9224248	12/2014	Ye et al.	N/A	N/A
9288388	12/2015	Son et al.	N/A	N/A
9300916	12/2015	Breedvelt-Schouten et al.	N/A	N/A
9325939	12/2015	Schultz et al.	N/A	N/A
9338449	12/2015	Rojals et al.	N/A	N/A
9378574	12/2015	Kim et al.	N/A	N/A
9456196	12/2015	Kim et al.	N/A	N/A
9470911	12/2015	Fonte et al.	N/A	N/A
9489739	12/2015	Kruglick	N/A	N/A
9538130	12/2016	Ford et al.	N/A	N/A
9552668	12/2016	Yang et al.	N/A	N/A
9619722	12/2016	Takeda et al.	N/A	N/A
9626564	12/2016	Rao et al.	N/A	N/A
9684953	12/2016	Kuster et al.	N/A	N/A
9710955	12/2016	Kobayashi et al.	N/A	N/A
9740282	12/2016	McInerny	N/A	N/A
9749581	12/2016	Nilsson et al.	N/A	N/A
9824428	12/2016	Zhang et al.	N/A	N/A
9872007	12/2017	Woodgate et al.	N/A	N/A
9986812	12/2017	Yamanashi et al.	N/A	N/A
10043088	12/2017	Odry et al.	N/A	N/A
10067562	12/2017	Teshome et al.	N/A	N/A
10089740	12/2017	Srikanth et al.	N/A	N/A
10169905	12/2018	Bhat et al.	N/A	N/A
10321747	12/2018	Tamura et al.	N/A	N/A
10423830	12/2018	Chalom et al.	N/A	N/A
10664949	12/2019	Chalom et al.	N/A	N/A
10740985	12/2019	Sommerlade et al.	N/A	N/A
10777018	12/2019	Varady et al.	N/A	N/A
10796480	12/2019	Chen et al.	N/A	N/A
11026634	12/2020	Brouwer et al.	N/A	N/A
2001/0001566	12/2000	Moseley et al.	N/A	N/A
2001/0050686	12/2000	Allen	N/A	N/A
2002/0013691	12/2001	Warnes	N/A	N/A
2002/0018299	12/2001	Daniell	N/A	N/A
2002/0113866	12/2001	Taniguchi et al.	N/A	N/A
2003/0117790	12/2002	Lee et al.	N/A	N/A
2003/0133191	12/2002	Morita et al.	N/A	N/A
2003/0137821	12/2002	Gotoh et al.	N/A	N/A
2003/0197779	12/2002	Zhang et al.	N/A	N/A
2003/0218672	12/2002	Zhang et al.	N/A	N/A
2004/0021809	12/2003	Sumiyoshi et al.	N/A	N/A
2004/0042233	12/2003	Suzuki et al.	N/A	N/A
2004/0046709	12/2003	Yoshino	N/A	N/A
2004/0066480	12/2003	Yoshida et al.	N/A	N/A
2004/0108971	12/2003	Waldern et al.	N/A	N/A
2004/0109303	12/2003	Olczak	N/A	N/A

2004/0135741	12/2003	Tomisawa et al.	N/A	N/A
2004/0170011	12/2003	Kim et al.	N/A	N/A
2004/0263968	12/2003	Kobayashi et al.	N/A	N/A
2004/0263969	12/2003	Lipton et al.	N/A	N/A
2005/0007753	12/2004	Hees et al.	N/A	N/A
2005/0053274	12/2004	Mayer et al.	N/A	N/A
2005/0094295	12/2004	Yamashita et al.	N/A	N/A
2005/0104878	12/2004	Kaye et al.	N/A	N/A
2005/0110980	12/2004	Maehara et al.	N/A	N/A
2005/0135116	12/2004	Epstein et al.	N/A	N/A
2005/0180167	12/2004	Hoelen et al.	N/A	N/A
2005/0190180	12/2004	Jin et al.	N/A	N/A
2005/0190345	12/2004	Dubin et al.	N/A	N/A
2005/0237488	12/2004	Yamasaki et al.	N/A	N/A
2005/0254127	12/2004	Evans et al.	N/A	N/A
2005/0264717	12/2004	Chien et al.	N/A	N/A
2005/0276071	12/2004	Sasagawa et al.	N/A	N/A
2005/0280637	12/2004	Ikeda et al.	N/A	N/A
2006/0002678	12/2005	Weber et al.	N/A	N/A
2006/0012845	12/2005	Edwards	N/A	N/A
2006/0056166	12/2005	Yeo et al.	N/A	N/A
2006/0067573	12/2005	Parr	382/154	G06V 40/169
2006/0114664	12/2005	Sakata et al.	N/A	N/A
2006/0132423	12/2005	Travis	N/A	N/A
2006/0139447	12/2005	Unkrich	N/A	N/A
2006/0158729	12/2005	Vissenberg et al.	N/A	N/A
2006/0176912	12/2005	Anikitchev	N/A	N/A
2006/0203200	12/2005	Koide	N/A	N/A
2006/0215129	12/2005	Alasaarela et al.	N/A	N/A
2006/0215244	12/2005	Yosha et al.	N/A	N/A
2006/0221642	12/2005	Daiku	N/A	N/A
2006/0227427	12/2005	Dolgoff	N/A	N/A
2006/0244918	12/2005	Cossairt et al.	N/A	N/A
2006/0250580	12/2005	Silverstein et al.	N/A	N/A
2006/0262376	12/2005	Mather et al.	N/A	N/A
2006/0267040	12/2005	Baek et al.	N/A	N/A
2006/0269213	12/2005	Hwang et al.	N/A	N/A
2006/0284974	12/2005	Lipton et al.	N/A	N/A
2006/0291053	12/2005	Robinson et al.	N/A	N/A
2006/0291243	12/2005	Niioka et al.	N/A	N/A
2007/0008406	12/2006	Shestak et al.	N/A	N/A
2007/0013624	12/2006	Bourhill	N/A	N/A
2007/0019882	12/2006	Tanaka et al.	N/A	N/A
2007/0025680	12/2006	Winston et al.	N/A	N/A
2007/0035706	12/2006	Margulis	N/A	N/A
2007/0035829	12/2006	Woodgate et al.	N/A	N/A
2007/0035964	12/2006	Olczak	N/A	N/A
2007/0081110	12/2006	Lee	N/A	N/A
2007/0085105	12/2006	Beeson et al.	N/A	N/A

2007/0109400	12/2006	Woodgate et al.	N/A	N/A
2007/0109401	12/2006	Lipton et al.	N/A	N/A
2007/0115551	12/2006	Spilman et al.	N/A	N/A
2007/0115552	12/2006	Robinson et al.	N/A	N/A
2007/0153160	12/2006	Lee et al.	N/A	N/A
2007/0188667	12/2006	Schwerdtner	N/A	N/A
2007/0189701	12/2006	Chakmakjian et al.	N/A	N/A
2007/0223252	12/2006	Lee et al.	N/A	N/A
2007/0244606	12/2006	Zhang et al.	N/A	N/A
2007/0279554	12/2006	Kowarz et al.	N/A	N/A
2007/0279727	12/2006	Gandhi et al.	N/A	N/A
2008/0043833	12/2007	Perera et al.	N/A	N/A
2008/0055221	12/2007	Yabuta et al.	N/A	N/A
2008/0079662	12/2007	Saishu et al.	N/A	N/A
2008/0084519	12/2007	Brigham et al.	N/A	N/A
2008/0128728	12/2007	Nemchuk et al.	N/A	N/A
2008/0225205	12/2007	Travis	N/A	N/A
2008/0259012	12/2007	Ferguson	N/A	N/A
2008/0259643	12/2007	Ijzerman et al.	N/A	N/A
2008/0291359	12/2007	Miyashita	N/A	N/A
2008/0297431	12/2007	Yuuki et al.	N/A	N/A
2008/0297459	12/2007	Sugimoto et al.	N/A	N/A
2008/0304282	12/2007	Mi et al.	N/A	N/A
2008/0316303	12/2007	Chiu et al.	N/A	N/A
2008/0316768	12/2007	Travis	N/A	N/A
2009/0016057	12/2008	Rinko	N/A	N/A
2009/0040426	12/2008	Mather et al.	N/A	N/A
2009/0052796	12/2008	Furukawa	382/260	G06T 7/596
2009/0067156	12/2008	Bonnett et al.	N/A	N/A
2009/0109705	12/2008	Pakhchyan et al.	N/A	N/A
2009/0128735	12/2008	Larson et al.	N/A	N/A
2009/0135623	12/2008	Kunimochi	N/A	N/A
2009/0140656	12/2008	Kohashikawa et al.	N/A	N/A
2009/0160757	12/2008	Robinson	N/A	N/A
2009/0167651	12/2008	Minaño et al.	N/A	N/A
2009/0168459	12/2008	Holman et al.	N/A	N/A
2009/0174840	12/2008	Lee et al.	N/A	N/A
2009/0190072	12/2008	Nagata et al.	N/A	N/A
2009/0190079	12/2008	Saitoh	N/A	N/A
2009/0207629	12/2008	Fujiyama et al.	N/A	N/A
2009/0225380	12/2008	Schwerdtner et al.	N/A	N/A
2009/0244072	12/2008	Pugach et al.	N/A	N/A
2009/0278936	12/2008	Pastoor et al.	N/A	N/A
2009/0290203	12/2008	Schwerdtner	N/A	N/A
2009/0315915	12/2008	Dunn et al.	N/A	N/A
2010/0002169	12/2009	Kuramitsu et al.	N/A	N/A
2010/0033558	12/2009	Horie et al.	N/A	N/A
2010/0034987	12/2009	Fujii et al.	N/A	N/A
2010/0040280	12/2009	McKnight	N/A	N/A

2010/0053771	12/2009	Travis et al.	N/A	N/A
2010/0053938	12/2009	Kim et al.	N/A	N/A
2010/0091093	12/2009	Robinson	N/A	N/A
2010/0091254	12/2009	Travis et al.	N/A	N/A
2010/0103649	12/2009	Hamada	N/A	N/A
2010/0165598	12/2009	Chen et al.	N/A	N/A
2010/0177387	12/2009	Travis et al.	N/A	N/A
2010/0182542	12/2009	Nakamoto et al.	N/A	N/A
2010/0188438	12/2009	Kang	N/A	N/A
2010/0188602	12/2009	Feng	N/A	N/A
2010/0214135	12/2009	Bathiche et al.	N/A	N/A
2010/0220260	12/2009	Sugita et al.	N/A	N/A
2010/0231498	12/2009	Large et al.	N/A	N/A
2010/0271838	12/2009	Yamaguchi	N/A	N/A
2010/0277575	12/2009	Ismael et al.	N/A	N/A
2010/0278480	12/2009	Vasylyev	N/A	N/A
2010/0289870	12/2009	Leister	N/A	N/A
2010/0295920	12/2009	McGowan	N/A	N/A
2010/0295930	12/2009	Ezhov	N/A	N/A
2010/0300608	12/2009	Emerton et al.	N/A	N/A
2010/0309296	12/2009	Harrold et al.	N/A	N/A
2010/0321953	12/2009	Coleman et al.	N/A	N/A
2010/0328438	12/2009	Ohyama et al.	N/A	N/A
2011/0013417	12/2010	Saccomanno et al.	N/A	N/A
2011/0019112	12/2010	Dolgoft	N/A	N/A
2011/0032483	12/2010	Hruska et al.	N/A	N/A
2011/0032724	12/2010	Kinoshita	N/A	N/A
2011/0043142	12/2010	Travis et al.	N/A	N/A
2011/0044056	12/2010	Travis et al.	N/A	N/A
2011/0044579	12/2010	Travis et al.	N/A	N/A
2011/0051237	12/2010	Hasegawa et al.	N/A	N/A
2011/0063465	12/2010	Nanu et al.	N/A	N/A
2011/0115997	12/2010	Kim	N/A	N/A
2011/0154266	12/2010	Friend et al.	N/A	N/A
2011/0187635	12/2010	Lee et al.	N/A	N/A
2011/0188120	12/2010	Tabirian et al.	N/A	N/A
2011/0199459	12/2010	Barenbrug et al.	N/A	N/A
2011/0199460	12/2010	Gallagher	N/A	N/A
2011/0211142	12/2010	Kashiwagi et al.	N/A	N/A
2011/0216266	12/2010	Travis	N/A	N/A
2011/0221998	12/2010	Adachi et al.	N/A	N/A
2011/0228183	12/2010	Hamagishi	N/A	N/A
2011/0235359	12/2010	Liu et al.	N/A	N/A
2011/0242150	12/2010	Song et al.	N/A	N/A
2011/0242277	12/2010	Do et al.	N/A	N/A
2011/0242298	12/2010	Bathiche et al.	N/A	N/A
2011/0255303	12/2010	Nichol et al.	N/A	N/A
2011/0267563	12/2010	Shimizu	N/A	N/A
2011/0285927	12/2010	Schultz et al.	N/A	N/A
2011/0286525	12/2010	Kamisli et al.	N/A	N/A

2011/0292321	12/2010	Travis et al.	N/A	N/A
2011/0305374	12/2010	Chou	N/A	N/A
2011/0310232	12/2010	Wilson et al.	N/A	N/A
2012/0002136	12/2011	Nagata et al.	N/A	N/A
2012/0002295	12/2011	Dobschal et al.	N/A	N/A
2012/0008067	12/2011	Mun et al.	N/A	N/A
2012/0013720	12/2011	Kadowaki et al.	N/A	N/A
2012/0056971	12/2011	Kumar et al.	N/A	N/A
2012/0062991	12/2011	Krijn et al.	N/A	N/A
2012/0063166	12/2011	Panagotacos et al.	N/A	N/A
2012/0081920	12/2011	Ie et al.	N/A	N/A
2012/0086776	12/2011	Lo	N/A	N/A
2012/0092435	12/2011	Wohlert	N/A	N/A
2012/0105486	12/2011	Lankford et al.	N/A	N/A
2012/0106193	12/2011	Kim et al.	N/A	N/A
2012/0114201	12/2011	Luisi et al.	N/A	N/A
2012/0127573	12/2011	Robinson et al.	N/A	N/A
2012/0154450	12/2011	Aho et al.	N/A	N/A
2012/0162966	12/2011	Kim et al.	N/A	N/A
2012/0169838	12/2011	Sekine	N/A	N/A
2012/0206050	12/2011	Spero	N/A	N/A
2012/0219180	12/2011	Mehra	N/A	N/A
2012/0223956	12/2011	Saito et al.	N/A	N/A
2012/0236133	12/2011	Gallagher	348/E13.037	G06T 5/50
2012/0243204	12/2011	Robinson	N/A	N/A
2012/0243261	12/2011	Yamamoto et al.	N/A	N/A
2012/0293721	12/2011	Ueyama	N/A	N/A
2012/0314145	12/2011	Robinson	N/A	N/A
2012/0319928	12/2011	Rhodes	N/A	N/A
2012/0327101	12/2011	Blixt et al.	N/A	N/A
2012/0327172	12/2011	El-Saban et al.	N/A	N/A
2013/0070046	12/2012	Wolf et al.	N/A	N/A
2013/0076853	12/2012	Diao	N/A	N/A
2013/0101253	12/2012	Popovich et al.	N/A	N/A
2013/0107340	12/2012	Wong et al.	N/A	N/A
2013/0127861	12/2012	Gollier	N/A	N/A
2013/0135588	12/2012	Popovich et al.	N/A	N/A
2013/0155063	12/2012	Solem et al.	N/A	N/A
2013/0156265	12/2012	Hennessy	N/A	N/A
2013/0163659	12/2012	Sites	N/A	N/A
2013/0169701	12/2012	Whitehead et al.	N/A	N/A
2013/0230136	12/2012	Sakaguchi et al.	N/A	N/A
2013/0235561	12/2012	Etienne et al.	N/A	N/A
2013/0265625	12/2012	Fäcke et al.	N/A	N/A
2013/0294684	12/2012	Lipton et al.	N/A	N/A
2013/0307831	12/2012	Robinson et al.	N/A	N/A
2013/0307946	12/2012	Robinson et al.	N/A	N/A
2013/0308339	12/2012	Woodgate et al.	N/A	N/A
2013/0321599	12/2012	Harrold et al.	N/A	N/A
2013/0328866	12/2012	Woodgate et al.	N/A	N/A

2013/0335821	12/2012	Robinson et al.	N/A	N/A
2014/0002586	12/2013	Nourbakhsh	N/A	N/A
2014/0009508	12/2013	Woodgate et al.	N/A	N/A
2014/0016354	12/2013	Lee et al.	N/A	N/A
2014/0016871	12/2013	Son et al.	N/A	N/A
2014/0022619	12/2013	Woodgate et al.	N/A	N/A
2014/0036361	12/2013	Woodgate et al.	N/A	N/A
2014/0041205	12/2013	Robinson et al.	N/A	N/A
2014/0043323	12/2013	Sumi	N/A	N/A
2014/0098558	12/2013	Vasylyev	N/A	N/A
2014/0126238	12/2013	Kao et al.	N/A	N/A
2014/0153832	12/2013	Kwatra et al.	N/A	N/A
2014/0240344	12/2013	Tomono et al.	N/A	N/A
2014/0240828	12/2013	Robinson et al.	N/A	N/A
2014/0267584	12/2013	Atzpadin et al.	N/A	N/A
2014/0340728	12/2013	Taheri	N/A	N/A
2014/0344718	12/2013	Rapaport et al.	N/A	N/A
2014/0368602	12/2013	Woodgate et al.	N/A	N/A
2015/0077526	12/2014	Kim et al.	N/A	N/A
2015/0116212	12/2014	Freed et al.	N/A	N/A
2015/0177447	12/2014	Woodgate et al.	N/A	N/A
2015/0243035	12/2014	Narasimha et al.	N/A	N/A
2015/0268479	12/2014	Woodgate et al.	N/A	N/A
2015/0269737	12/2014	Lam et al.	N/A	N/A
2015/0334365	12/2014	Tsubaki et al.	N/A	N/A
2015/0339512	12/2014	Son et al.	N/A	N/A
2016/0125227	12/2015	Soare et al.	N/A	N/A
2016/0196465	12/2015	Wu et al.	N/A	N/A
2016/0211001	12/2015	Sun et al.	N/A	N/A
2016/0219258	12/2015	Woodgate et al.	N/A	N/A
2017/0132528	12/2016	Aslan et al.	N/A	N/A
2017/0134720	12/2016	Park et al.	N/A	N/A
2017/0195662	12/2016	Sommerlade et al.	N/A	N/A
2017/0354882	12/2016	Kono et al.	N/A	N/A
2017/0364149	12/2016	Lu et al.	N/A	N/A
2018/0035886	12/2017	Courtemanche et al.	N/A	N/A
2018/0158246	12/2017	Grau et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1142869	12/1996	CN	N/A
1377453	12/2001	CN	N/A
1454329	12/2002	CN	N/A
1466005	12/2003	CN	N/A
1487332	12/2003	CN	N/A
1696788	12/2004	CN	N/A
1826553	12/2005	CN	N/A
1900785	12/2006	CN	N/A
1908753	12/2006	CN	N/A

101029975	12/2006	CN	N/A
101049028	12/2006	CN	N/A
101114080	12/2007	CN	N/A
101142823	12/2007	CN	N/A
101266338	12/2007	CN	N/A
102012742	12/2010	CN	N/A
102147079	12/2010	CN	N/A
103310186	12/2012	CN	N/A
103534748	12/2013	CN	N/A
104951808	12/2014	CN	N/A
0653891	12/1994	EP	N/A
0830984	12/1997	EP	N/A
0860729	12/1997	EP	N/A
0939273	12/1998	EP	N/A
1394593	12/2003	EP	N/A
2219067	12/2009	EP	N/A
2451180	12/2011	EP	N/A
3665553	12/2019	EP	N/A
01198597	12/2000	GB	N/A
2405542	12/2004	GB	N/A
H10142556	12/1997	JP	N/A
2003215705	12/2002	JP	N/A
2005181914	12/2004	JP	N/A
2006010935	12/2005	JP	N/A
2007094035	12/2006	JP	N/A
2007109255	12/2006	JP	N/A
2007273288	12/2006	JP	N/A
2008204874	12/2007	JP	N/A
2010160527	12/2009	JP	N/A
2012060607	12/2011	JP	N/A
2013015619	12/2012	JP	N/A
20090932304	12/2008	KR	N/A
20110006773	12/2010	KR	N/A
20110017918	12/2010	KR	N/A
20120049890	12/2011	KR	N/A
2493601	12/2012	RU	N/A
1994006249	12/1993	WO	N/A
1995020811	12/1994	WO	N/A
1995027915	12/1994	WO	N/A
1998021620	12/1997	WO	N/A
1999011074	12/1998	WO	N/A
2001061241	12/2000	WO	N/A
2007111436	12/2006	WO	N/A
2011020962	12/2010	WO	N/A
2011148366	12/2010	WO	N/A
2012158574	12/2011	WO	N/A
2016132148	12/2015	WO	N/A

OTHER PUBLICATIONS

Lin et al., “Real-time eye-gaze estimation using a low-resolution webcam”, Springer Science + Business Media, LLC, *Multimed Tools Appln* (2013) 65:543-568, published online Aug. 14, 2012. cited by applicant

Lipton, “Stereographics: Developers' Handbook”, *Stereographic Developers Handbook*, Jan. 1, 1997, XP002239311, p. 42-49. cited by applicant

Lipton: “Stereoscopic Composition Lenny Lipton”, Feb. 15, 2009 (Feb. 15, 2009), XP055335930, Retrieved from the Internet: URL:<https://lennylipton.wordpress.com/2009/02/15/stereoscopic-composition/> [retrieved on Jan. 17, 2017]. cited by applicant

Liu et al., “Optical Flow and Principal Component Analysis-Based Motion Detection in Outdoor Videos”, Hindawi Publishing Corporation, *EURASIP Journal on Advances in Signal Processing*, vol. 2010, Article ID 680623, 6 pages. cited by applicant

Lowe, “Distinctive Image Features from Scale-Invariant Keypoints”, *International Journal of Computer Vision* 60 (2), pp. 91-110, 2004. cited by applicant

Lucio et al.: “RGBD Camera Effects”, Aug. 1, 2012 (Aug. 1, 2012), XP055335831, SIBGRAPI—Conference on Graphics, Patterns and Images Retrieved from the Internet: URL:https://www.researchgate.net/profile/Leandro_Cruz/publication/233398182_RGBD_Camera_Effects/links/0912f50a2922010eb2000000.pdf [retrieved on Jan. 17, 2017]. cited by applicant

Luo et al., “Face Location in Wavelet-Based Video Compression for High Perceptual Quality Videoconferencing”, *IEEE Transactions on Circuits and Systems for Video Technology*, Institute of Electrical and Electronics Engineers, US, vol. 6, No. 4, Aug. 1996(Aug. 1996). cited by applicant

Marjanovic, M., “Interlace, Interleave, and Field Dominance,” <http://www.mir.com/DMG/interl.html>, pp. 1-5 (2001). cited by applicant

Marschner et al., “Fundamentals of Computer Graphics.”, A K Peters/CRC Press; 4 edition (Dec. 15, 2015). cited by applicant

McCutchen, “Microsoft Computer Dictionary”, Fourth Edition, Published by Microsoft Press, Redmond, Washington 1999. cited by applicant

Murphy, “Machine Learning A Probabilistic Perspective”, The MIT Press, Cambridge Massachusetts, London England, 2012 Massachusetts Institute of Technology. cited by applicant

Ozuysal et al., “Fast Keypoint recognition in Ten Lines of Code”, *Computer Vision and Pattern Recognition*, pp. 1-8, 2007. cited by applicant

Patil et al., “Expression invariant face recognition using semidecimated DWT, Patch-LDSMT, feature and score level fusion”, *Article in Applied Intelligence*, pp. 1-34, Jun. 2016. cited by applicant

Patil et al., “3-D face recognition: Features, databases, algorithms and challenges”, *Article in Artificial Intelligence Review, An International Science and Engineering Journal*, ISSN 0269-2821, Springer Science + Business Media Dordrecht 2015, 52 pages, Oct. 2015. cited by applicant

Paysan et al. “A 3D Face Model for Pose and Illumination Invariant Face Recognition.”, 6th IEEE International Conference on Advanced Video and Signal based Surveillance (AVSS) for Security, Safety and Monitoring in Smart Environments, 2009. cited by applicant

PCT/RU2016/000118 International Preliminary Report on Patentability dated Sep. 26, 2017. cited by applicant

PCT/RU2016/000118 International search report and written opinion of international searching authority mailed Aug. 25, 2016. cited by applicant

Pisharady et al., “Pose Invariant Face Recognition Using Neuro-Biologically Inspired Features”, *International Journal of Future Computer and Communication*, vol. 1, No. 3, pp. 316-320, Oct. 2012. cited by applicant

Qin et al., “Eye Gaze Correction with a Single Webcam Based on Eye-Replacement”, Springer International Publishing Switzerland ISVC 2015, pp. 599-609, 2015. cited by applicant

Redmon et al., “YOLO9000: Better, Faster, Stronger”, *IEEE/CVPR*, 2017. cited by applicant

Regenbrecht et al., "Mutual Gaze Support in Videoconferencing Reviewed", Article in Communications of the Association for Information Systems, vol. 37, Article 45, 1-27 pages, Nov. 2015. cited by applicant

Ren et al., "Face alignment at 3000 fps via regressing local binary features", CVPR, pp. 1685-1692, 2014. cited by applicant

Saffari et al., "On-line Random Forests", 3rd IEEE ICCV Workshop, On-line Computer Vision, 2009. cited by applicant

Sahoo et al., "Online Deep Learning: Learning Deep Neural Networks on the Fly", School of Information Systems, Singapore Management University (<https://arxiv.org/abs/1711.03705>), 2017, pp. 1-9. cited by applicant

Sang et al., "Pose-Invariant Face Recognition via RGB-D Images", Hindawi Publishing Corporation, Computational Intelligence and Neuroscience, vol. 2016, Article ID 3563758, 9 pages, 2016. cited by applicant

Smith et al., Gaze locking: passive eye contact detection for human-object interaction. In Proceedings of the 26th annual ACM Symposium on User interface software and technology, pp. 271-280, ACM 2013. cited by applicant

Sonka et al., "Image Processing, Analysis, and Machine Vision", Fourth Edition, The University of Iowa, Iowa City, 2008 Cengage Learning, 2015. cited by applicant

Sun et al., "Construction and compression of face models for multi-party videoconferencing with multi-camera", 2013 6th International Congress on Image and Signal Processing (CISP), IEEE, vol. 2, Dec. 16, 2013 (Dec. 16, 2013), pp. 948-952. cited by applicant

Tabiryan et al., "The Promise of Diffractive Waveplates," Optics and Photonics News, vol. 21, Issue 3, pp. 40-45 (Mar. 2010). cited by applicant

Travis, et al. "Backlight for view-sequential autostereo 3D", Microsoft E&DD Applied Sciences, (date unknown), 25 pages. cited by applicant

Travis, et al. "Collimated light from a waveguide for a display," Optics Express, vol. 17, No. 22, pp. 19714-19719 (2009). cited by applicant

Ucar, "Color Face Recognition Based on Steerable Pyramid Transform and Extreme Learning Machines", Hindawi Publishing Corporation, The Scientific World Journal, vol. 2014, Article ID 628494, 15 pages, 2014. cited by applicant

Van Der Hoest, "Eye Contact in Leisure Video Conferencing", Master Erasmus Mundus in Color in Information and Media Technology (CIMET), Gjovik University College, Master Thesis Report, pp. 1-131, Jul. 15, 2012. cited by applicant

Vetterli et al., "Waveletes and Subband Coding", 1995 by Prentice Hall PTR, A Simon and Schuster Company, New Jersey, USA. cited by applicant

Viola and Jones, "Rapid Object Detection using a Boosted Cascade of Simple Features", pp. 1-9 CVPR 2001. cited by applicant

Williams S P et al., "New Computational Control Techniques and Increased Understanding for Stereo 3-D Displays", Proceedings of SPIE, SPIE, US, vol. 1256, Jan. 1, 1990, XP000565512, p. 75, 77, 79. cited by applicant

Wolberg, "Digital Image Warping", Department of Computer Science, Columbia University, New York, IEEE Computer Society Press, Los Alamitos, California, Third Edition 1994, USA, The Institute of Electrical and Electronics Engineers, Inc. cited by applicant

Wolf et al., "An Eye for an Eye: A Single Camera Gaze-Replacement Method", The Blavatnik School of Computer Science Tel-Aviv University, 1-8 pages, 2010. cited by applicant

Wood et al., :GazeDirector: Fully Articulated Eye Gaze Redirection in Video, Univ. of Cambridge, UK, arXiv:1704.08763v1 [cs.CV] Apr. 27, 2017, pp. 1-10. cited by applicant

Wulff et al., "Efficient Sparse-to-Dense Optical Flow Estimation using a Learned Basis and Layers", Max Planck Institute for Intelligent Systems, Tübingen, Germany, pp. 120-130. cited by applicant

Xiong et al., “Supervised descent method and its applications to face alignment”, In Computer Vision Pattern Recognition (CVPR), 2013 IEEE Conference, pp. 532-539. cited by applicant

Yang et al., “Eye Gaze Correction with Stereovision for Video-Teleconferencing”, A. Heyden et al. (Eds.): ECCV 2002, LNCS 2351, pp. 479-494 2002, Springer-Verlag Berlin Heidelberg 2002. cited by applicant

Yang, “Mutli-scale recognition with DAG-CNNs”, ICCV 2015. cited by applicant

Yim et al., “A Gift from Knowledge Distillation: Fast Optimization, Network Minimization and Transfer Learning”, 2017 IEEE Conference on Computer Vision and Pattern Recognition (CVPR), IEEE Computer Society, US, Jul. 21, 2017 (Jul. 21, 2017), pp. 7130-7138. cited by applicant

Yip, “Face and Eye Rectification in Video Conference Using Artificial Neural Network”, IEEE International Conference on Multimedia and Expo, 2005, pp. 690-693. cited by applicant

Zach et al., “A Duality Based Approach for Realtime TV-L1 Optical Flow”, Pattern Recognition (Proc. DAGM), 2007, pp. 214-223. cited by applicant

Zheng et al., “Conditional Random Fields as Recurrent Neural Networks.”, International Conference on Computer Vision (ICCV), 2015. cited by applicant

Zitnick et al., Manipulation of Video Eye Gaze and Head Orientation for Video Teleconferencing, Technical Report MSR-TR-99-26, Microsoft Research, Microsoft Corp., Redmond, WA, Jun. 16, 1999, pp. 1-13. cited by applicant

Bahadur, “Liquid crystals applications and uses,” World Scientific, vol. 1, pp. 178 (1990). cited by applicant

Beato: “Understanding Comfortable stereography”, Dec. 31, 2011 (Dec. 31, 2011), XP055335952, Retrieved from the Internet: URL:[http://64.17.134.112/Affonso Beato/Understanding Comfortable Stereography.html](http://64.17.134.112/Affonso%20Beato/Understanding%20Comfortable%20Stereography.html) [retrieved-on Jan. 17, 2017]. cited by applicant

Braverman: “The 3D Toolbox : News”, Aug. 13, 2010 (Aug. 13, 2010), XP055336081, Retrieved from the Internet: URL:<http://www.dashwood3d.com/blog/the-3d-toolbox/> [retrieved on Jan. 17, 2017]. cited by applicant

Bucila et al., “Model compression”, Proceedings of the Twelfth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining: Aug. 20-23, 2006, Philadelphia, PA USA, New York, NY: ACM Press, 2 Penn Plaza, Suite 701 New York, NY 10121-0701 USA, Aug. 20, 2006 (Aug. 20, 2006), pp. 535-541. cited by applicant

Burt et al., “A Multiresolution Spline with Application to Image Mosaics”, RCA David Sarnoff Research Center, ACM Transactions of Graphics, vol. 2, No. 4, Oct. 1983, pp. 217-236. cited by applicant

Cao et al., “Real-Time High-Fidelity Facial Performance Capture.” ACM Transactions on Graphics (SIGGRAPH 2015). cited by applicant

Cao et al., “Realtime Multi-Person 2D Pose Estimation using Part Affinity Fields.” IEEE/CVPR 2017. cited by applicant

Cham et al., “Analogous View Transfer for Gaze Correction in Video Sequences”, Seventh International Conference on Control, Automation Robotics and Vision (ICARCV'02), Dec. 2002, Singapore, pp. 1415-1420. cited by applicant

Chi et al., “Hybrid Particle and Kalman Filtering for Pupil Tracking in Active IR Illumination Gaze Tracking System”, Hindawi Publishing Corporation, vol. 2014, Article ID 426234, 17 pages, 2014. cited by applicant

Chou et al., “Face-off: Automatic Alteration of Facial Features”, Department of Information Management National Taiwan University of Science and Technology, pp. 1-16, 2012. cited by applicant

CN-201680028919.9—Notification of the 1st Office Action mailed Nov. 4, 2020 of China Patent Office. cited by applicant

CN-201780006239.1—Notification of the 1st Office Action mailed Sep. 30, 2020 of China Patent Office. cited by applicant

CN-201880064948.X Notification of the 1st Office Action of the Chinese Patent Office mailed Apr. 21, 2023. cited by applicant

Cootes et al., “Active Appearance Models”, IEEE Trans. Pattern Analysis and Machine Intelligence, 23(6):681-685, 2001. cited by applicant

Cootes et al., “Active Shape Models—Their Training and Application” Computer Vision and Image Understanding 61(1):38-59 Jan. 1995. cited by applicant

Dalal et al., “Histogram of Oriented Gradients for Human Detection”, Computer Vision and Pattern Recognition, pp. 886-893, 2005. cited by applicant

Dodge et al., “Introduction to Machine Learning and Deep Learning: A Hands-On Starter's Guide”, Copyright 2017-2020 [<https://deeplearningtextbook.org>] Powered by GoDaddy Website Builder. cited by applicant

Drucker et al., “Support Vector Regression Machines”, Advances in Neural Information Processing Systems 9, pp. 155-161, NIPS 1996. cited by applicant

Ekman et al., “Facial Action Coding System: A Technique for the Measurement of Facial Movement.”, Consulting Psychologists Press, Palo Alto, 1978. cited by applicant

EP-17736268.8 European Extended Search Report of European Patent Office dated Jul. 12, 2019. cited by applicant

EP-18844651.2 European Partial Search Report of European Patent Office dated May 3, 2021. cited by applicant

Fleet et al., “Design and Use of Linear Models for Image Motion Analysis”, International Journal of Computer Vision 36(3), 171-193, 2000, 2000 Kluwer Academic Publishers, Manufactured in the Netherlands. cited by applicant

Funes-Mora et al., “Gaze Estimation in the 3D Space Using RGB-D Sensors”, Idiap Research Institute, Switzerland, pp. 1-23, Nov. 13, 2015. cited by applicant

Ganin et al., “DeepWarp: Photorealistic Image Resynthesis for Gaze Manipulation”, Jul. 25, 2016, XP055295123, Retrieved from Internet: URL: <http://arxiv.org/pdf/1607.07215v2.pdf> (retrieved on Jan. 10, 2018). cited by applicant

Gemmell et al., “Gaze Awareness for Video-Conferencing A Software Approach”, IEEE Multimedia, Oct.-Dec. 2000, pp. 1-10. cited by applicant

Giger et al., “Gaze Correction with a Single Webcam”, Proceedings of IEEE ICME 2014 (Chengdu, China, Jul. 14-18, 2014). cited by applicant

Goodfellow et al., “Deep Learning”, The MIT Press Cambridge , Massachusetts, London, England, 2016 Massachusetts Institute of Technology. cited by applicant

Guo et al., “Automatic landmark annotation and dense correspondence registration for 3D human facial images”, BMC Bioinformatics 2013, 14:232, pp. 1-12, 2013. cited by applicant

Hinton et al., “Distilling the Knowledge in a Neural Network”, Corr (Arxiv), vol. 1503.02531v1, Mar. 9, 2015 (Mar. 9, 2015), pp. 1-9. cited by applicant

Hladnik, “Image Compression and Face Recognition: Two Image Processing Applications of Principal Component Analysis”, International Circular of Graphic Education and Research, Issue No. 6 2013, pp. 56-61. cited by applicant

Ho et al., “Gaze Correction Using 3D Video Processing For Videoconferencing”, School of Information and Communications, Gwangju Institute of Science and Technology (GIST), 2015 IEEE ChinaSIP 2015, pp. 496-499. cited by applicant

Ho, “Random Decision Forests”, Proceedings of the 3rd International Conference on Document Analysis and Recognition, Montreal, QC, pp. 278-282, Aug. 14-16, 1995. cited by applicant

Hu et al., A hierarchical dense deformable model for 3D face reconstruction from skull, Article in Multimedia Tools and Applications, Springer Science + Business Media, vol. 64: pp. 345-364, May 2013. cited by applicant

Ian Sexton et al: “Stereoscopic and autostereoscopic display-systems”, —IEEE Signal Processing Magazine, May 1, 1999 (May 1, 1999), pp. 85-99, XP055305471, Retrieved from the Internet:

RL:<http://ieeexplore.ieee.org/iel5/79/16655/00768575.pdf> [retrieved on Sep. 26, 2016]. cited by applicant

International Preliminary Report on Patentability dated Sep. 26, 2017 in International Patent Application No. PCT/RU2016/000118. cited by applicant

International Search Report and Written Opinion dated Apr. 18, 2017 in International Patent Application No. PCT/US17/12203. cited by applicant

International Search Report and Written Opinion dated Aug. 25, 2016 in International Patent Application No. PCT/RU2016/000118. cited by applicant

International Search Report and Written Opinion dated Oct. 16, 2018 in International Patent Application No. PCT/US18/45648. cited by applicant

International search report and written opinion of international searching authority for PCT application PCT/US2018/045648 mailed Oct. 16, 2018. cited by applicant

Jain et al., “Learning Human Pose Estimation Features with Convolutional Networks”, arXiv:1312.7302v6, [cs.CV], pp. 1-11, Apr. 23, 2014. cited by applicant

Jain, “Fundamentals of Digital Image Processing”, Prentice Hall Information and Systems Sciences Series, Thomas Kailath, Series Edition, 1989 by Prentice-Hall, Inc. A Division of Simon & Schuster, New Jersey, USA. cited by applicant

Kalantar, et al. “Backlight Unit With Double Surface Light Emission,” J. Soc. Inf. Display, vol. 12, Issue 4, pp. 379-387 (Dec. 2004). cited by applicant

Kang et al., “Combining random forest with multi-block local binary pattern feature selection for multiclass head pose estimation”, The Department of Electronics Engineering, Ewha W. University, Seoul, Republic of Korea, Plos One, pp. 1-24, Jul. 17, 2017. cited by applicant

Katsigiannis et al., “A GPU based real-time video compression method for video conferencing”, 2013 18th International Conference on Digital Signal Processing (DSP), IEEE, Jul. 2013 (Jul. 2013), pp. 1-6. cited by applicant

Kisku et al., “Multithread Face Recognition in Cloud”, Hindawi Publishing Corporation, Journal of Sensors, vol. 2016, Article ID 2575904, 21 pages, 2016. cited by applicant

Kononenko et al., “Learning to Look Up: Realtime Monocular Gaze Correction Using Machine Learning”, Computer Vision and Pattern Recognition, pp. 4667-4675, 2015. cited by applicant

Kononenko, “Learnable Warping-Based Approach to Image Re-Synthesis with Application to Gaze Redirection”, doctoral thesis, Doctoral Program in Computational and Data Science and Engineering, Moscow 2017. cited by applicant

Languy et al., “Performance comparison of four kinds of flat nonimaging Fresnel lenses made of polycarbonates and polymethyl methacrylate for concentrated photovoltaics”, Optics Letters, 36, pp. 2743-2745. cited by applicant

Liebe et al., “Computer Vision—ECCV 2016”, 14th European Conference, Amsterdam, The Netherlands, Oct. 11-14, 2016, Proceedings, Part II. cited by applicant

Exhibit 1003 “Declaration of L. Karam, PhD” entered Jun. 16, 2023. *Microsoft Corporation v. Reald Spark, LLC*, Case No. IPR2023-01046, U.S. Pat. No. 10,740,985 filed Aug. 7, 2018. cited by applicant

Exhibit 2001 “Declaration of Dr. Eli Saber, PhD” entered Oct. 13, 2023. *Microsoft Corporation v. Reald Spark, LLC*, Case No. IPR2023-01046, U.S. Pat. No. 10,740,985 filed Aug. 7, 2018. cited by applicant

Patent Owner's Preliminary Response to the Petition for Inter Partes Review of U.S. Pat. No. 10,740,985, entered Oct. 13, 2023. *Microsoft Corporation v. Reald Spark, LLC*, Case No. IPR2023-01046, U.S. Pat. No. 10,740,985 filed Aug. 7, 2018. cited by applicant

Patent Owner's Response Pursuant to 37 C.F.R. § 42.120, entered Mar. 15, 2024. *Microsoft Corporation v. Reald Spark, LLC*, Case No. IPR2023-01046, U.S. Pat. No. 10,740,985 filed Aug. 7, 2018. cited by applicant

Petition for Inter Partes Review of U.S. Pat. No. 10,740,985, entered Jun. 16, 2023. *Microsoft*

Primary Examiner: Philippe; Gims S

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

TECHNICAL FIELD

(1) This application relates to the image processing of multi-view images of head, for example a stereoscopic pair of images of a head, having regard to the perceived gaze of the eyes of the head.

BACKGROUND

(2) In many systems, stereoscopic pair of images, or more generally multi-view images, of a head may be captured in one device and displayed on a different device for viewing by an observer. One non-limiting example is a system for performing teleconferencing between two telecommunications devices. In that case, each device may capture a stereoscopic pair of images, or more generally multi-view images, of a head of the observer of that device and transmit it to the other device over a telecommunications network for display and viewing by the observer of the other device.

(3) When a stereoscopic pair of images, or more generally multi-view images, of a head is captured and displayed, the gaze of the head in the displayed stereoscopic pair of images, or more generally multi-view images, may not be directed at the observer. This may be caused for example by the gaze of the head not being directed at the camera system used to capture the stereoscopic pair of images, for example because the user whose head is imaged is observing a display in the same device as the camera system and the camera system is offset above (or below) that display. In that case, the gaze in the displayed images will be perceived to be downwards (or upwards). The human visual system has evolved high sensitivity to gaze during social interaction, using cues gained from the relative position of the iris and white sclera of other observers. As such errors in the perceived gaze are disconcerting. For example in a system for performing teleconferencing, errors in the perceived gaze can create unnatural interactions between the users.

BRIEF SUMMARY

(4) The present disclosure is concerned with an image processing technique for adjusting the stereoscopic pair of images, or more generally multi-view images, of a head to correct the perceived gaze.

(5) According to a first aspect of the present disclosure, there is provided a method of adjusting multi-view images of a head to correct gaze, the method comprising: in each image of the multi-view images, identifying image patches containing the left and right eyes of the head, respectively; in respect of the image patches containing the left eyes of the head in each image of the multi-view images, and also in respect of the image patches containing the right eyes of the head in each image of the multi-view images, performing the steps of: deriving a feature vector from plural local image descriptors of the image patch in at least one image of the multi-view images; and deriving a displacement vector field representing a transformation of an image patch, using the derived feature vector to look up reference data comprising reference displacement vector fields associated with possible values of the feature vector; and adjusting each image of the multi-view images by transforming the image patches containing the left and right eyes of the head in accordance with the

derived displacement vector field.

(6) In this method, image patches containing the left and right eyes of the head are identified and transformed. To derive a displacement vector field that represents the transformation, a feature vector is derived from plural local image descriptors of the image patch in at least one image of the multi-view images and used to look up reference data comprising reference displacement vector fields associated with possible values of the feature vector. The form of the feature vector may be derived in advance from the reference data using machine learning. This method allows the gaze to be corrected, thereby reducing the disconcerting effect of incorrect gaze when the multi-view images are subsequently displayed.

(7) Various approaches to deriving and using displacement vector fields are possible as follows.

(8) In a first approach, displacement vector fields may be derived in respect of the image patches in each image of the multi-view images independently. This allows for correction of gaze, but there is a risk that the displacement vector fields in respect of each image may be inconsistent with each other, with the result that conflicting transformations are performed which can distort the stereoscopic effect and/or reduce the quality of the image.

(9) However, the following alternative approaches overcome this problem.

(10) A second possible approach is as follows. In the second approach, the plural local image descriptors used in the method are plural local image descriptors in both images of the multi-view images. In this case, the reference data comprises reference displacement vector fields for each image of the multi-view images, which reference displacement vector fields are associated with possible values of the feature vector. This allows a displacement vector field to be derived from the reference data for each image of the multi-view images. As such, the derived displacement vector fields for each image of the multi-view images are inherently consistent.

(11) A potential downside of this second approach is that it may require the reference data to be derived from stereoscopic or more generally multi-view imagery, which may be inconvenient to derive. However, the following approaches allow the reference data to be derived from monoscopic imagery.

(12) A third possible approach is as follows. In the third approach, the plural local image descriptors are plural local image descriptors in one image of the multi-view images, and the displacement vector fields are derived as follows. A displacement vector field representing a transformation of the image patch in said one image of the multi-view images is derived, using the derived feature vector to look up reference data comprising reference displacement vector fields associated with possible values of the feature vector. Then, a displacement vector field representing a transformation of the image patch in the other multi-view image or images is derived by transforming the derived displacement vector field representing a transformation of the image patch in said one image of the multi-view images in accordance with an estimate of the optical flow between the image patches in the one image and the other multi-view image or images.

(13) Thus, in the third approach, the displacement vector fields derived in respect of each image are consistent, because only one displacement vector field is derived from the reference data, and the other displacement vector field is derived therefrom using a transformation in accordance with an estimate of the optical flow between the image patches in the images of the multi-view images.

(14) A fourth possible approach is as follows. In the fourth approach, the plural local image descriptors are plural local image descriptors in both images of the multi-view images, and the displacement vector fields are derived as follows. An initial displacement vector field representing a notional transformation of a notional image patch in a notional image having a notional camera location relative to the camera locations of the images of the multi-view images, using the derived feature vector to look up reference data comprising reference displacement vector fields associated with possible values of the feature vector. Then, displacement vector fields representing a transformation of the image patches in each image of the multi-view images are derived by transforming the initial displacement vector field in accordance with an estimate of the optical

flows between the notional image patches in the notional images and the image patches in the images of the multi-view images.

(15) Thus, in the fourth approach, the displacement vector fields derived in respect of each image are consistent, because only one displacement vector field is derived from the reference data, this representing a notional transformation of a notional image patch in a notional image having a notional camera location relative to the camera locations of the images of the multi-view images. The respective displacement vector fields used to transform the two images of the multi-view images are derived therefrom using a transformation in accordance with an estimate of the optical flow between the notional image patches in the notional images and the images of the multi-view images.

(16) A fifth possible approach is as follows. In the fifth approach, displacement vector fields in respect of the image patches in each image of the multi-view images are derived, but then a merged displacement vector field is derived therefrom and used to transform the image patches containing both the left and right eyes of the head. In this case, the displacement vector fields for each image are consistent because they are the same.

(17) The merging may be performed in any suitable manner. For example, the merging may be a simple average or may be an average that is weighted by a confidence value associated with each derived displacement vector field. Such a confidence value may be derived during the machine learning.

(18) According to a second aspect of the present disclosure, there is provided an apparatus configured to perform a similar method to the first aspect of the disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Non-limitative embodiments are illustrated by way of example in the accompanying figures, in which like reference numbers indicate similar parts, and in which:
- (2) FIG. 1 is a schematic perspective view of a device that captures a stereoscopic pair of images;
- (3) FIG. 2 is a schematic perspective view of a device that displays the stereoscopic pair of images;
- (4) FIG. 3 is a flow chart of a method of adjusting a stereoscopic pair of images;
- (5) FIG. 4 is a diagram illustrating the processing of the stereoscopic pair of images in the method of FIG. 3;
- (6) FIG. 5 is a flow chart of a step of extracting an image patch;
- (7) FIG. 6 and FIG. 7 are flow charts of steps of deriving displacement vector fields according to two alternative approaches;
- (8) FIG. 8 and FIG. 9 are flow charts of two alternatives for a step of adjusting an image;
- (9) FIG. 10 is a flow chart of a transformation step within the step of adjusting an image in the methods shown in FIG. 8 and FIG. 9; and
- (10) FIG. 11 is a diagram of a telecommunications system in which the method may be implemented.

DETAILED DESCRIPTION

- (11) FIG. 1 and FIG. 2 illustrate how incorrect gaze is perceived when a stereoscopic pair of images of a head is captured by the device 10 shown in FIG. 1 which will be referred to as the source device 10 and displayed on a different device 20 shown in FIG. 2 which will be referred to as the destination device 20.
- (12) The capture device 10 includes a display 11 and a camera system 12 comprises two cameras 13 used to capture the stereoscopic pair of images of the head of a source observer 14. The source observer 14 views the display 11, along line 15. The cameras 13 of the camera system 12 are offset from the display 11, in this case being above the display 11. Thus, the cameras 13 effectively look

down on the source observer **14** along line **16**.

(13) The display device **20** includes a display **21** which is a stereoscopic display of any known type, for example an autostereoscopic display of any known type. The display **21** displays the stereoscopic pair of images is captured by the capture device **10**. A destination observer **24** views the display **21**. If the destination observer **24** is located in a normal viewing position perpendicular to the center of the display **21**, as shown by the hard outline of the destination observer **24**, then the gaze of the source observer **14** is perceived by the destination observer **24** to be downwards, rather than looking at the destination observer **24**, because the cameras **13** of the source device **10** look down on the source observer **14**.

(14) Although the cameras **13** are above the display **11** in this example, the cameras **13** could in general could be in any location adjacent the display **11**, and the gaze of the source observer **14** perceived by the destination observer **24** would be correspondingly incorrect.

(15) If the destination observer **24** is located in an offset viewing position, as shown by the dotted outline of the destination observer **24** so that the destination observer **24** views the display **21** along line **26**, then the offset of the destination observer **24** creates an additional error in the gaze of the source observer **14** perceived by the destination observer **24**. A similar additional error in the perceived gaze of the source observer **14** occurs if the destination observer **24** is located in the normal viewing position along line **25**, but the stereoscopic pair of images is displayed on the display **25** in a position offset from the center of the display **25**.

(16) A stereoscopic pair of images is an example of multi-view images where there are two images. Although FIG. **1** illustrates an example where the camera system **12** includes two cameras **13** that capture of a stereoscopic pair of images, alternatively the camera system may include more than two cameras **13** that capture more than two multi-view images, in which case similar issues of incorrect perceived gaze exist on display.

(17) FIG. **3** illustrates a method of adjusting multi-view images to correct such errors in the perceived gaze. For simplicity, this method will be described with respect to the adjustment of multi-view images comprising a stereoscopic pair of images. The method may be generalized to multi-view images comprising more than two images, simply by performing the similar processing on a larger number of images.

(18) The method may be performed in an image processor **30**. The image processor **30** may be implemented by a processor executing a suitable computer program or by dedicated hardware or by some combination of software and hardware. Where a computer program is used, the computer program may comprise instructions in any suitable language and may be stored on a computer readable storage medium, which may be of any type, for example: a recording medium which is insertable into a drive of the computing system and which may store information magnetically, optically or opto-magnetically; a fixed recording medium of the computer system such as a hard drive; or a computer memory.

(19) The image processor **30** may be provided in the source device **10**, the destination device **10** or in any other device, for example a server on a telecommunications network, which may be suitable in the case that the source device **10** and the destination device **10** communicate over such a telecommunications network.

(20) The stereoscopic pair of images **31** are captured by the camera system **12**. Although the camera systems **12** is illustrated in FIG. **1** as including two cameras **13**, this is not limitative and more generally the camera system **13** may have the following properties.

(21) The camera system comprises a set of cameras **13**, with at least two cameras **13**. The cameras are typically spaced apart by a distance less than the average human intrapupilar distance. In the alternative that the method is applied to more than two multi-view images, then there are more than two cameras **13**, that is one camera **13** image.

(22) The cameras **13** are spatially related to each other and the display **11**. The spatial relationship between the cameras **13** themselves and between the cameras **13** and the display **11** is known in

advance. Known methods for finding the spatial relationship may be applied, for example a calibration method using a reference image, or specification a priori.

(23) The cameras **13** face in the same direction as the display **11**. Thus, when the source observer **14** is viewing the display **11**, then the cameras **13** face the source observer **14** and the captured stereoscopic pair of images are images of the head of the source observer **14**. The cameras in the camera system can have different fields of view.

(24) The camera system **12** may include cameras **13** having different sensing modalities, including visible light and infrared.

(25) The main output of the camera system **13** is a stereoscopic pair of images **31** which are typically video images output at a video rate. The output of the camera system **13** may also include data representing the spatial relationship between the cameras **13** and the display **11**, the nature of the sensing modalities and internal parameters of the cameras **13** (for example focal length, optical axis) which may be used for angular localization.

(26) The method performed on the stereoscopic pair of images **31** is as follows. To illustrate the method, reference is also made to FIG. **4** which shows an example of the stereoscopic pair of images **31** at various stages of the method.

(27) In step **S1**, the stereoscopic pair of images **31** are analyzed to detect the location of the head and in particular the eyes of the source observer **14** within the stereoscopic pair of images **31**. This is performed by detecting presence of a head, tracking the head, and localizing the eyes of the head. Step **S1** may be performed using a variety of techniques that are known in the art.

(28) One possible technique for detecting the presence of the head is to use Haar feature cascades, for example as disclosed in Viola and Jones, "Rapid Object Detection using a Boosted Cascade of Simple Features", CVPR 2001, pp 1-9 (incorporated herein by reference).

(29) One possible technique for tracking the head is to use the approach of Active Appearance Models to provide the position of the head of the subject, as well as the location of the eyes, for example as disclosed in Cootes et al., "Active shape models-their training and application", Computer Vision and Image Understanding, 61(1): 38-59, January 1995 and in Cootes et al. "Active appearance models", IEEE Trans. Pattern Analysis and Machine Intelligence, 23(6): 681-685, 2001 (incorporated herein by reference).

(30) In step **S1**, typically, a set of individual points ("landmarks") are set to regions of the face, typically the eyes, for example corners of the eye, upper and lower lid locations, etc, thereby localizing the eyes.

(31) In step **S2**, image patches containing the left and right eyes of the head, respectively are identified in each image **31** of the stereoscopic pair. FIG. **4** shows the identified image patches **32** of the right eye in each image **31** (the image patches for the left eye being omitted in FIG. **4** for clarity).

(32) Step **S2** may be performed as shown in FIG. **5**, as follows.

(33) In step **S2-1**, image patches **32** containing the left and right eyes of the head are identified in each image **31** of the stereoscopic pair. This is done by identifying an image patch **39** in each image **31** located around the identified points ("landmarks") corresponding to features of an eye, as shown for example in FIG. **4**.

(34) In step **S2-2**, the image patches **32** identified in step **S2-1** are transformed into a normalized coordinate system, being the same normalized coordinate system as used in the machine learning process which is described further below. The transformation is chosen to align the points ("landmarks") of the eye within the image patch that were identified in step **S1**, with predetermined locations in the normalized coordinate system. The transformation may include translation, rotation and scaling, to appropriate extents to achieve that alignment. The output of step **S2-2** is identified image patches **33** of the right eye in each image in the normalized coordinate system as shown for example in FIG. **4**.

(35) The following steps are performed separately (a) in respect of the image patches containing

the left eyes of the head in each image **31** of the stereoscopic pair, and (b) in respect of the image patches containing the right eyes of the head in each image **31** of the stereoscopic pair. For brevity, the following description will refer merely to image patches and eyes without specifying the left or right eye, but noting the same steps are performed for both left and right eyes.

(36) In step **S3**, a feature vector **34** is derived from plural local image descriptors of an image patch **33** in at least one image **31** of the stereoscopic pair. Depending on the approach and as described further below, this may be an image patch in a single image **31** of the stereoscopic pair or may be both images **31** of the stereoscopic pair. Thus, the local image descriptors are local image descriptors derived in the normalized coordinate system.

(37) The feature vectors **34** are representations of the image patches **33** that are suitable for use in looking up reference data **35** comprising reference displacement vector fields that represent transformations of the image patch and are associated with possible values of the feature vector.

(38) The reference data **35** is obtained and analyzed in advance using a machine learning technique which derives the form of the feature vectors **34** and associates the reference displacement vector fields with the possible values of the feature vector. Accordingly, the machine learning technique will now be described before reverting to the method of FIG. **3**.

(39) The training input to the machine learning technique is two sets of images, which may be stereoscopic pairs of images or monoscopic images, as discussed further below. Each set comprises images of the head of the same group of individuals but captured from cameras in different locations relative to the gaze so that the perceived gaze differs as between them.

(40) The first set are input images, being images of each individual with an incorrect gaze where the error is known a priori. In particular, the images in the first set may be captured by at least one cameras in a known camera location where the gaze of the individual which is in a different known direction. For example in the case of the source device of FIG. **1**, the camera location may be the location of a camera **13** and while the gaze of the imaged individual is towards the center of the display **11**.

(41) The second set are output images, being images of each individual with correct gaze for a predetermined observer location relative to a display location in which the image is to be displayed. In the simplest case, the observer location is a normal viewing position perpendicular to the center of the display location, for example as shown by the hard outline of the destination observer **24** in the case of the destination device **20** of FIG. **2**.

(42) For each image in the two sets, the image is analyzed to detect the location of the head and in particular the eyes using the same technique as used in step **S1** described above, and then image patches containing the left and right eyes of the head, respectively, are identified using the same technique as used in step **S2** described above. The following steps are then performed separately (a) in respect of the image patches containing the left eyes of the head in each image, and (b) in respect of the image patches containing the right eyes of the head in each image. For brevity, the following description will refer merely to image patches and eyes without specifying the left or right eye, but noting the same steps are performed for both left and right eyes.

(43) Each image patch is transformed into the same normalized coordinate system as used in step **S2** described above. As described above, the transformation is chosen to align points (“landmarks”) of the eye with predetermined locations in the normalized coordinate system. The transformation may include translation, rotation and scaling, to appropriate extents to achieve that alignment.

(44) Thus, the image patches input and output images of each individual are aligned in the normalized coordinate system.

(45) From an input and output image of each individual, there is derived a displacement vector field that represents the transformation of the image patch in the input image required to obtain the image patch of the output image, for example as follows. Defining positions in the image patches by (x,y), the displacement vector field **F** is given by

$$F=\{u(x,y),v(x,y)\}$$

where u and v define the horizontal and vertical components of the vector at each position (x,y) .

(46) The displacement vector field F is chosen so that the image patch of the output image $O(x,y)$ is derived from the image patch of the input image $I(x,y)$ as

$$O(x,y)=I(x+u(x,y),y+v(x,y))$$

(47) For image data from more than one camera, the system delivers a displacement vector field for the input image from each camera.

(48) The displacement vector field F for an input and output image of an individual may be derived using a process in which a trial feature vector $F'=\{u',v'\}$ is modified to minimize error, optionally in an iterative process, for example in accordance with:

$$\sum |O(x,y)-I(x+u'(x,y),y+v'(x,y))|=\min!$$

(49) By way of non-limitative example, the displacement vector field F may be derived as disclosed in Kononenko et al., “Learning To Look Up: Realtime Monocular Gaze Correction Using Machine Learning”, Computer Vision and Pattern Recognition, 2015, pp. 4667-4675 (incorporated herein by reference), wherein the displacement vector field F is referred to as a “flow field”.

(50) A machine learning technique is used to obtain a map from the displacement vector field F of each individual to respective feature vectors derived from plural local image descriptors of the image patch of the input image.

(51) The local descriptors capture relevant information of a local part of the image patch of the input image and the set of descriptors usually form a continuous vectorial output.

(52) The local image descriptors input into the machine learning process are of types expected to provide discrimination between different individuals, although the specific local image descriptors are selected and optimized by the machine learning process itself. In general, the local image descriptors may be of any suitable type, some non-limitative examples which may be applied in any combination being as follows.

(53) The local image descriptors may include values of individual pixels or a linear combination thereof. Such a linear combination may be, for example, a difference between the pixels at two points, a kernel derived within a mask at an arbitrary location, or a difference between two kernels at different locations.

(54) The local image descriptors may include distances of a pixel location from the position of an eye point (“landmark”).

(55) The local image descriptors may include SIFT features (Scale-invariant feature transform features), for example as disclosed in Lowe, “Distinctive Image Features from Scale-Invariant Keypoints”, International Journal of Computer Vision 60 (2), pp 91-110 (incorporated herein by reference).

(56) The local image descriptors may include HOG features (Histogram of Oriented Gradients features), for example as disclosed in Dalal et al. “Histograms of Oriented Gradients for Human Detection”, Computer Vision and Pattern Recognition, 2005, pp. 886-893 (incorporated herein by reference).

(57) The derivation of the feature vector from plural local image descriptors depends on the type of machine learning applied.

(58) In a first type of machine learning technique, the feature vector may comprise features that are values derived from the local image descriptors in a discrete space, being binary values or values discretized into more than two possible values. In this case, the machine learning technique associates a reference displacement vector field F derived from the training input with each possible value of the feature vector in the discrete space, so the reference data **35** is essentially a look-up table. This allows a reference displacement vector field F to be simply selected from the reference data **35** on the basis of the feature vector **34** derived in step **S3**, as described below.

(59) In the case that the feature vector comprises features that are binary values derived from the local image descriptors, the feature vector has a binary representation. Such binary values may be derived in various ways from the values of descriptors, for example by comparing the value of a

descriptor with a threshold, comparing the value of two descriptors, or by comparing the distance of a pixel location from the position of an eye point (“landmark”).

(60) Alternatively, the feature vector may comprise features that are discretized values of the local image descriptors. In this case, more than two discrete values of each feature are possible.

(61) Any suitable machine learning technique may be applied, for example using a decision tree, a decision forest, a decision fern or an ensemble or combination thereof.

(62) By way of example, a suitable machine learning technique using a feature vector comprising features that are binary values derived by comparing a set of individual pixels or a linear combination thereof against a threshold, is disclosed in Ozuysal et al. “Fast Keypoint Recognition in Ten Lines of Code”, Computer Vision and Pattern Recognition, 2007, pp. 1-8 (incorporated herein by reference).

(63) By way of further example, a suitable machine learning technique using a distance of a pixel location with the position of an eye landmark is disclosed in Kononenko et al., “Learning To Look Up: Realtime Monocular Gaze Correction Using Machine Learning”, Computer Vision and Pattern Recognition, 2015, pp. 4667-4675 (incorporated herein by reference).

(64) By way of further example, a suitable machine learning technique using a random decision forest is disclosed in Ho, “Random Decision Forests”, Proceedings of the 3rd International Conference on Document Analysis and Recognition, Montreal, QC, 14-16 Aug. 1995, pp. 278-282 (incorporated herein by reference).

(65) In a second type of machine learning technique, the feature vector may comprise features that are discrete values of the local image descriptors in a continuous space. In this case, the machine learning technique associates a reference displacement vector field **F** derived from the training input with possible discrete values of the feature vector in the continuous space. This allows a displacement vector field **F** to be derived from the reference data **35** by interpolation from the reference displacement vector fields based on the relationship between the feature vector **34** derived in step **S3** and the values of the feature vector associated with the reference displacement vector fields.

(66) Any suitable machine learning technique may be applied, for example using support vector regression.

(67) By way of example, a suitable machine learning technique using support vector regression is disclosed in Drucker et al. “Support Vector Regression Machines”, Advances in Neural Information Processing Systems 9, NIPS 1996, 155-161, (incorporated herein by reference). The output of the technique is a continuously varying set of interpolation directions that form part of the reference data **35** and are used in the interpolation.

(68) The machine learning technique, regardless of its type, inherently also derives the form of the feature vectors **34** that is used to derive the reference displacement vector fields **F**. This is the form of the feature vectors **34** that is derived in step **S3**.

(69) Optionally, the output of the machine learning technique may be augmented to provide confidence values associated with derivation of a displacement vector field from the reference data **35**.

(70) In the case that the feature vector comprises features that are values in a discrete space, a confidence value is derived for each reference displacement vector field.

(71) One example of deriving a confidence value is to keep, for each resulting index (value of the feature vector) in the resulting look-up table, a distribution of the corresponding part of the input image in the training data. In this case, the confidence value may be the amount of training data that ended up with the same index, divided by the total number of training data exemplars.

(72) Another example of deriving a confidence value is to fit a Gaussian to the distribution of input images in the training data in each bin indexed, and to use the trace of the covariance matrix around the mean value as the confidence value.

(73) In the case that the feature vector comprises features that are discrete values of the local image

descriptors in a continuous space, the confidence values may be derived according to the machine learning method used. For example, when using support vector regression, the confidence values may be the inverse of the maximum distance to the support vectors.

(74) Where used, the confidence values are stored as part of the reference data.

(75) The description now reverts to the method of FIG. 3.

(76) In step S4, at least one displacement vector field 37 representing a transformation of an image patch is derived by using the feature vector 34 derived in step S3 is to look up the reference data 35. Due to the derivation of the displacement vector field 37 from the reference data 35, the transformation represented thereby corrects the gaze that will be perceived when the stereoscopic pair of images 31 are displayed.

(77) In the case that the feature vector 34 comprises features that are values in a discrete space and the reference displacement vector fields of the reference data 35 comprise a reference displacement vector field associated with each possible value of the feature vector in the discrete space, then the displacement vector field for the image patch is derived by selecting the reference displacement field associated with the actual value of the derived feature vector 34.

(78) In the case that the feature vector 34 comprises features that are discrete values of the local image descriptors in a continuous space, then then the displacement vector field for the image patch is derived by interpolating a displacement vector field from the reference displacement vector fields based on the relationship between the actual value of the derived feature vector 34 and the values of the feature vectors associated with the reference displacement vector fields. In the case that the machine learning technique was support vector regression, This may be done using the interpolation directions that form part of the reference data 35.

(79) Some different approaches to the derivation of the displacement vector field 37 in step S4 will now be described.

(80) In a first approach, in step S4, a displacement vector field 37 is derived in respect of the image patches in each image 31 of the stereoscopic pair independently. This first approach may be applied when the reference data 35 was derived from monoscopic images. This approach provides for correction of gaze, but there is a risk that the displacement vector fields 37 in respect of each image may be inconsistent with each other, with the result that conflicting transformations are subsequently performed which can distort the stereoscopic effect and/or reduce the quality of the image.

(81) Other approaches which overcome this problem are as follows.

(82) In a second possible approach, the plural local image descriptors used in deriving the feature vector 34 in step S3 are plural local image descriptors in both images of the stereoscopic pair. In this case, the reference data 35 similarly comprises pairs of reference displacement vector fields for each image 31 of the stereoscopic image pair, it being the pairs of reference displacement vector fields that are associated with possible values of the feature vector 34.

(83) This second approach allows a pair of displacement vector fields 35 to be derived from the reference data 35, that is one displacement vector field for each image 31 of the stereoscopic pair. As such, the derived displacement vector fields for each image 31 of the stereoscopic pair are inherently consistent since they are derived together from the consistent pairs of reference displacement vector fields in the reference data 35.

(84) The downside of this second approach is that it requires the reference data 35 to be derived from training input to the machine learning technique that is stereoscopic pairs of images. This does not create any technical difficulty, but may create some practical inconvenience as monoscopic imagery is more commonly available. Accordingly, the following approaches may be applied when the reference data 35 is derived from training input to the machine learning technique that is monoscopic images.

(85) In a third possible approach, a feature vector 34 is derived from plural local image descriptors that are plural local image descriptors derived from one image of the stereoscopic pair. In that case,

the displacement vector fields **37** are derived as shown in FIG. **6** as follows.

(86) In step **S4-1**, a first displacement vector field **37** representing a transformation of the image patch in said one image **31** of the stereoscopic pair (which may be either image **31**) is derived. This is done using the derived feature vector **34** to look up the reference data **35**.

(87) In step **S4-2**, a displacement vector field **37** representing a transformation of the image patch in the other image **31** of the stereoscopic pair is derived. This is done by transforming the displacement vector field derived in step **S4-1** in accordance with an estimate of the optical flow between the image patches in the images **31** of the stereoscopic pair.

(88) The optical flow represents the effect of the different camera locations as between the images **31** of the stereoscopic pair. Such an optical flow is known in itself and may be estimated using known techniques for example as disclosed in Zach et al., "A Duality Based Approach for Realtime TV-L1 Optical Flow", Pattern Recognition (Proc. DAGM), 2007, pp. 214-223 (incorporated herein by reference).

(89) By way of example, if the first displacement vector field **37** derived in step **S4-1** is for the left image $L_{sub.o}$, $L_{sub.i}$ (where the subscripts o and i represent the output and input images respectively), and the optical flow to the right image $R_{sub.o}$ is represented by a displacement vector field G given by

$$G=\{s(x,y),t(x,y)\}$$

then the second displacement vector field **37** may be derived in accordance with

$$R_{sub.o}(x,y)=L_{sub.o}(x+s(x,y),y+t(x,y))=L_{sub.i}(x+s+u(x+s,y+t),y+t+v(x+s,y+t))$$

(90) Thus, in the third approach, the displacement vector fields **37** derived in respect of each image **31** of the stereoscopic pair are consistent, because only one displacement vector field is derived from the reference data **35**, and the other displacement vector field is derived therefrom using a transformation which maintains consistency because it is derived in accordance with an estimate of the optical flow between the image patches in the images **31** of the stereoscopic pair.

(91) In a fourth possible approach, a feature vector **34** is derived from plural local image descriptors that are plural local image descriptors derived from both images of the stereoscopic pair. In that case, the displacement vector fields **37** are derived as shown in FIG. **7** as follows.

(92) In step **S4-3**, an initial displacement vector field representing a notional transformation of a notional image patch in a notional image having a notional camera location in a predetermined location relative to the camera locations of the images **31**, in this example between the camera locations of the images **31**. This may be thought of as a Cyclopean eye. This is done using the derived feature vector **34** to look up the reference data **35** which comprises reference displacement vector fields associated with possible values of the feature vector. This means that the reference data **35** is correspondingly structured, but may still be derived from training input that comprises monoscopic images.

(93) In step **S4-4**, a displacement vector fields **37** representing transformations of the image patches in each image **31** of the stereoscopic pair are derived. This is done by transforming the initial displacement vector field derived in step **S4-3** in accordance with an estimate of the optical flow between the notional image patches in the notional images and the image patches in the images **31** of the stereoscopic pair.

(94) The optical flow represents the effect of the different camera locations as between the notional image and the images **31** of the stereoscopic pair. Such an optical flow is known in itself and may be estimated using known techniques for example as disclosed in Zach et al., "A Duality Based Approach for Realtime TV-L1 Optical Flow", Pattern Recognition (Proc. DAGM), 2007, pp. 214-223 (as cited above and incorporated herein by reference).

(95) By way of example, if the optical flow from the left image L to the right image R is represented by a displacement vector field G given by

$$G=\{s(x,y),t(x,y)\}$$

then the transformation deriving the notional image C is given by

$$(96) C(x, y) = R(x - \frac{s(x, y)}{2}, y - \frac{t(x, y)}{2}) = L(x + \frac{s(x, y)}{2}, y + \frac{t(x, y)}{2})$$

(97) Thus, in this example, the initial displacement vector field F derived in step **S4-3** for this notional image C is transformed in step **S4-4** to derive the flow fields $F_{sub.rc}$ and $F_{sub.lc}$ for the right and left images in accordance with

$$(98) F_{rc}(x, y) = \{u(x, y) + \frac{s(x, y)}{2}, v(x, y) + \frac{t(x, y)}{2}\} F_{lc}(x, y) = \{u(x, y) - \frac{s(x, y)}{2}, v(x, y) - \frac{t(x, y)}{2}\}$$

(99) Thus, in the fourth approach, the displacement vector fields **37** derived in respect of each image **31** of the stereoscopic pair are consistent, because only one displacement vector field is derived from the reference data **35**, this representing a notional transformation of a notional image patch in a notional image, and the displacement vector fields for the left and right images are derived therefrom using a transformation which maintains consistency because it is derived in accordance with an estimate of the optical flow between the image patches in the notional image and in the images **31** of the stereoscopic pair.

(100) In step **S5**, each image **31** of the stereoscopic pair is adjusted by transforming the image patches containing the left and right eyes of the head in accordance with the derived displacement vector fields **37**. This produces an adjusted stereoscopic pair of images **38** as shown in FIG. **4**, in which the gaze has been corrected. In particular, the adjustment may be performed using two alternative methods, as follows.

(101) A first method for performing step **S5** is shown in FIG. **8** and performed as follows.

(102) In step **S5-1**, the image patch is transformed in the normalised coordinate system in accordance with the corresponding displacement vector field **37** in respect of the same image, thereby correcting the gaze. As described above, for a displacement vector field F the transformation of the image patch of the input image $I(x, y)$ provides the output image $O(x, y)$ in accordance with

$$O(x, y) = I(x + u(x, y), y + v(x, y))$$

(103) In step **S5-2**, the transformed image patch output from step **S5-1** is transformed out of the normalised coordinate system, back into the original coordinate system of the corresponding image **31**. This is done using the inverse transformation from that applied in step **S2-2**.

(104) In step **S5-3**, the transformed image patch output from step **S5-2** is superimposed on the corresponding image **31**. This may be done with a full replacement within an eye region corresponding to the eye itself, and a smoothed transition between the transformed image patch and the original image **31** over a boundary region around the eye region. The width of the boundary region may be of fixed size or a percentage of the size of the image patch in the original image **31**.

(105) A second method for performing step **S5** is shown in FIG. **9** and performed as follows.

(106) In this second, alternative method, the transformation back into the coordinate system of the corresponding image **31** occurs before the transformation of the image patch in accordance with the transformed displacement vector field F .

(107) In step **S5-4**, the displacement vector field F is transformed out of the normalised coordinate system, back into the original coordinate system of the corresponding image **31**. This is done using the inverse transformation from that applied in step **S2-2**.

(108) In step **S5-5**, the image patch **32** in the coordinate system of the image **31** is transformed in accordance with the displacement vector field F that has been transformed into the same coordinate system in step **S5-4**. As described above, for a displacement vector field F the transformation of the image patch of the input image $I(x, y)$ provides the output image $O(x, y)$ in accordance with

$$O(x, y) = I(x + u(x, y), y + v(x, y))$$

but this is now performed in the coordinate system of the original image **31**.

(109) Step **S5-6** is the same as **S5-3**. Thus, in step **S5-6**, the transformed image patch output from step **S5-5** is superimposed on the corresponding image **31**. This may be done with a full replacement within an eye region corresponding to the eye itself, and a smoothed transition between the transformed image patch and the original image **31** over a boundary region around the eye region. The width of the boundary region may be of fixed size or a percentage of the size of the

image patch in the original image **31**.

(110) The displacement vector fields **37** used in step **S5** will now be discussed.

(111) One option is that the displacement vector fields **37** derived in step **S4** in respect of the left and right images are used directly in step **S5**. That is, the image patch in respect of each image **31** of the stereoscopic patch is transformed in accordance with the displacement vector field **37** in respect of that image **31**. This is appropriate if the displacement vector fields **37** are sufficiently accurate, for example because they have been derived from reference data **35** that is itself derived from stereoscopic imagery in accordance with the second approach described above.

(112) An alternative option in accordance with a fifth approach is that a merged displacement vector field **39** is derived and used. This may be applied in combination with any of the first to fourth approaches discussed above. In this case, step **S5** additionally includes step **S5-a** as shown in FIG. **10** which is performed before step **S5-1** in the first method of FIG. **8** or before step **S5-4** in the second method of FIG. **9**. In step **S5-a**, a merged displacement vector field **39** is derived from the displacement vector fields **37** derived in step **S4** in respect of the image patches in each image **31** of the stereoscopic pair.

(113) The rest of step **S5** is then performed using the merged displacement vector field **39** in respect of each image **31**. That is, in the first method of FIG. **8**, the image patch **33** in respect of each image **31** of the stereoscopic pair is transformed in step **S5-1** of in accordance with the merged displacement vector field **39**. Similarly, in the second method of FIG. **9**, in step **S5-4** the merged displacement vector field **39** is transformed and in step **S5-5** the image patch **33** in respect of each image **31** of the stereoscopic pair is transformed in accordance with that merged displacement vector field **39**.

(114) In this case, the displacement vector fields for each image are consistent because they are the same.

(115) The merging in step **S5-1a** may be performed in any suitable manner.

(116) In one example, the merging in step **S5-1a** may be a simple average of the displacement vector fields **37** derived in step **S4**

(117) In another example, the merging in step **S5-1a** may be an average that is weighted by a confidence value associated with each derived displacement vector field **37**. In this case, confidence values form part of the reference data **35**, in the manner described above, and in step **S4** the confidence values are derived from the reference data **35**, together with the derived displacement vector field **37**.

(118) By way of example, denoting the derived displacement vector field **37** as $F_{sub.i}$, the merged displacement vector field **39** as $F_{sub.avg}$, and the confidence values as $a_{sub.i}$, then the merged displacement vector field **39** may be derived as

$$(119) F_{avg} = \frac{\text{Math. } a_i F_i}{\text{Math. } a_i}$$

(120) In the example described above, gaze is corrected for a destination observer **24** in an observer location that is a normal viewing position perpendicular to the center of the display location, for example as shown by the hard outline of the destination observer **24** in the case of the destination device **20** of FIG. **2**. This is sufficient in many situations. However, there will now be described an optional modification which allows gaze is corrected for a destination observer **24** in a different observer location, for example as shown by the dotted outline of the destination observer **24** in the case of the destination device **20** of FIG. **2**.

(121) In this case, the method further comprises using location data **40** representing the observer location relative to a display location of the stereoscopic pair of images **31**. This location data **40** may be derived in the destination device **20**, for example as described below. In that case, if the method is not performed in the destination device **20**, then the location data **40** is transmitted to the device in which the method is performed.

(122) The relative observer location may take into account the location of the observer with respect to the display **21**. This may be determined using a camera system in the destination device **20** and

an appropriate head tracking module to detect the location of the destination observer **24**.

(123) The relative observer location may assume that the image is displayed centrally on the display **21**. Alternatively, relative observer location may take into account both the location of the observer with respect to the display **21** and the location of the image displayed on the display **21**. In this case, the location of the image displayed on the display **21** may be derived from the display geometry (for example, the position and area of a display window and the size of the display **21**).

(124) To account for different observer locations, the reference data **34** comprises plural sets of reference displacement vector fields, each set being associated with different observer locations. This is achieved by the training input to the machine learning technique comprising plural second sets of output images, each second set being images of each individual with correct gaze for a respective, predetermined observer location relative to a display location in which the image is to be displayed. Thus, in step **S4**, the displacement vector fields **37** are derived by looking up the set of reference displacement vector fields associated with the observer location represented by the location data.

(125) As described above, the method may be implemented in an image processor **30** provided in various different devices. By way of non-limitative example, there will now be described an particular implementation in a telecommunications system which is shown in FIG. **11** and arranged as follows.

(126) In this implementation, the source device **10** and the destination device **10** communicate over such a telecommunications network **50**. For communication over the telecommunications network **50**, the source device **10** includes a telecommunications interface **17** and the destination device **20** includes a telecommunications interface **27**.

(127) In this implementation, the image processor **30** is provided in the source device **10** and is provided with the stereoscopic pair of images directly from the camera system **12**. The telecommunications interface **17** is arranged to transmit the adjusted stereoscopic pair of images **38** over the telecommunications network **50** to the destination device **20** for display thereon.

(128) The destination device **20** includes an image display module **28** that controls the display **26**. The adjusted stereoscopic pair of images **38** are received in the destination device **20** by the telecommunications interface **27** and supplied to the image display module **28** which causes them to be displayed on the display **26**.

(129) The following elements of the destination device **20** are optionally included in the case that the method corrects gaze for a destination observer **24** in an observer location other than a normal viewing position perpendicular to the center of the display location. In this case, the destination device **20** includes a camera system **23** and an observer location module **29**. The camera system **23** captures an image of the destination observer **24**. The observer location module **29** derives the location data **40**. The observer location module **29** includes a head tracking module that uses the output of the camera system **23** to detect the location of the destination observer **24**. The observer location module **29**. Where the relative observer location also takes into account the location of the image displayed on the display **21**, the observer location module **29** obtains the location of the image displayed on the display **21** from the image display module **28**. The telecommunications interface **17** is arranged to transmit the location data **40** over the telecommunications network **50** to the source device **10** for use thereby.

(130) Although the above description refers to a method applied to images supplied from a source device **10** to a destination device **20**, the method may equally be applied to images supplied from in the opposite direction from the destination device **20** to the source device **10**, in which case the destination device **20** effectively becomes the “source device” and the source device **10** effectively becomes the “destination device”. Where images are supplied bi-directionally, the labels “source” and “destination” may be applied to both devices, depending on the direction of communication being considered.

(131) While various embodiments in accordance with the principles disclosed herein have been

described above, it should be understood that they have been presented by way of example only, and not limitation. Thus, the breadth and scope of this disclosure should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with any claims and their equivalents issuing from this disclosure. Furthermore, the above advantages and features are provided in described embodiments, but shall not limit the application of such issued claims to processes and structures accomplishing any or all of the above advantages.

(132) Additionally, the section headings herein are provided for consistency with the suggestions under 37 CFR 1.77 or otherwise to provide organizational cues. These headings shall not limit or characterize the embodiment(s) set out in any claims that may issue from this disclosure.

Specifically and by way of example, although the headings refer to a “Technical Field,” the claims should not be limited by the language chosen under this heading to describe the so-called field.

Further, a description of a technology in the “Background” is not to be construed as an admission that certain technology is prior art to any embodiment(s) in this disclosure. Neither is the

“Summary” to be considered as a characterization of the embodiment(s) set forth in issued claims.

Furthermore, any reference in this disclosure to “invention” in the singular should not be used to argue that there is only a single point of novelty in this disclosure. Multiple embodiments may be set forth according to the limitations of the multiple claims issuing from this disclosure, and such claims accordingly define the embodiment(s), and their equivalents, that are protected thereby. In all instances, the scope of such claims shall be considered on their own merits in light of this disclosure, but should not be constrained by the headings set forth herein.

Claims

1. A method of adjusting multi-view images of a head to modify a perceived gaze, the method comprising: identifying, in each image of the multi-view images, captured image patches including a left image patch containing a left eye of the head and a right image patch containing a right eye of the head; deriving a feature vector from local image descriptors of the right image patch or the left image patch; determining a displacement vector field representing a transformation of the right image patch or the left image patch, based on the derived feature vector, and based on reference data including one or more predefined relationships between displacement vector fields and feature vectors; and adjusting one or more of the multi-view images by transforming one or both of the right image patch and the left image patch based on the determined displacement vector field.
2. The method of claim 1, wherein the multi-view images include images captured substantially contemporaneously with different perspectives of the head, wherein the one or more predefined relationships are based on the different perspectives.
3. The method of claim 1, wherein the multi-view images include images captured substantially contemporaneously from different positions, wherein the one or more predefined relationships are based on the different positions.
4. The method of claim 1, wherein the multi-view images include a stereoscopic pair of images.
5. The method of claim 4, wherein the local image descriptors represent features represented in both images of the stereoscopic pair of images.
6. The method of claim 1, wherein the local image descriptors represent features of a first image of the multi-view images, the operation of determining further comprising: determining the displacement vector field representing a transformation of the right image patch or the left image patch in the first image based on the one or more predefined relationships; and determining a derived displacement vector field representing a transformation of the right image patch or the left image patch in a second image of the multi-view images by transforming the determined displacement vector field based on a determined optical flow between the captured image patches in the first image and the second image.
7. The method of claim 1, wherein the multi-view images include a stereoscopic pair of images and

the local image descriptors represent features of both a first image and a second image of the stereoscopic pair, the operation of determining further comprising: determining an initial displacement vector field representing a notional transformation of a notional image patch in a notional image representing an image captured from a notional camera location relative to camera locations of cameras configured to capture the first image and the second image; and determining derived displacement vector fields representing a transformation of the captured image patches in each of the multi-view images by transforming the initial displacement vector field based on an estimate of optical flows between the notional image patch and the captured image patches.

8. The method of claim 7, wherein the notional camera location is between the camera locations.

9. The method of claim 1, wherein the operation of determining includes determining different displacement vector fields corresponding to each image of the multi-view images and the operation of adjusting includes transforming each image of the multi-view images based on the corresponding determined displacement vector field.

10. The method of claim 1, wherein the displacement vector field is a merged displacement vector field, and the operation of determining includes: determining, based on the one or more predefined relationships, image-specific displacement vector fields, each image-specific displacement vector field corresponding to one of the multi-view images; and deriving the merged displacement vector field from the image-specific displacement vector fields.

11. The method of claim 10, further comprising: associating the image-specific displacement vector fields with corresponding confidence values, wherein the operation of determining the image-specific displacement vector fields includes: deriving a confidence value associated in memory with each of the image-specific displacement vector fields, wherein the merged displacement vector field is an average of the image-specific displacement vector fields weighed by the corresponding confidence values.

12. The method of claim 1, further comprising: accessing location data representing a position of an observer relative to a display viewable by the observer, wherein the operation of adjusting is further based on the location data.

13. The method of claim 1, wherein the local image descriptors are local image descriptors derived in a normalized coordinate system, and the displacement vector field is expressed in the normalized coordinate system.

14. The method of claim 1, wherein the feature vectors are discrete vectors that include discrete values representing the local image descriptors in a discrete space, the one or more predefined relationships include data points that each include one of the displacement vector fields and a corresponding one of the feature vectors in the discrete space, and the operation of determining further includes: selecting, from among the displacement vector fields, the displacement vector field corresponding to the derived feature vector.

15. The method of claim 1, wherein the derived feature vector is one of a plurality of discrete feature vectors that includes discrete values representing the local image descriptors in a continuous space, the one or more predefined relationships include data points that each include one of the displacement vector fields and a corresponding one of the feature vectors in the continuous space, and the operation of determining further includes: interpolating the displacement vector field from values of two or more of the displacement vector fields corresponding to feature vectors surrounding the derived feature vector.

16. The method of claim 1, further comprising: generating an output image based on the operation of adjusting, wherein the output image presents the modified perceived gaze as being normal to the output image at a position of the left eye or the right eye within the output image.

17. The method of claim 1, further comprising: retrieving location data representing a position of an observer relative to a display viewable by the observer; and generating an output image based on the operation of adjusting, wherein the output image presents the modified perceived gaze as being directed from the display to the position of the observer.

18. The method of claim 1, wherein the operation of deriving comprises: generating the feature vector by inputting the local image descriptors into a machine learning model trained based, wherein the machine learning model was trained by.

19. One or more processor-readable storage media embodied with instructions for executing on a computing device a process of adjusting multi-view images of a head to modify a perceived gaze, the process comprising: identifying, in each image of a set of multi-view images, captured image patches including a left image patch containing a left eye of the head and a right image patch containing a right eye of the head; deriving a feature vector from local image descriptors of the right image patch or the left image patch; determining a displacement vector field representing a transformation of the right image patch or the left image patch, based on the derived feature vector, and based on reference data including one or more predefined relationships between displacement vector fields and feature vectors; and adjusting one or more of the multi-view images by transforming one or both of the right image patch and the left image patch based on the determined displacement vector field.

20. A computing device adjusting multi-view images of a head to modify a perceived gaze, the computing device comprising: one or more hardware processors; an image patch identifier executable by the one or more hardware processors and configured to identify, in each image of the multi-view images, captured image patches including a left image patch containing a left eye of the head and a right image patch containing a right eye of the head; a feature vector deriver executable by the one or more hardware processors and configured to derive a feature vector from local image descriptors of the right image patch or the left image patch; a displacement vector field determiner executable by the one or more hardware processors and configured to determine a displacement vector field representing a transformation of the right image patch or the left image patch, based on the derived feature vector, and based on reference data including one or more predefined relationships between displacement vector fields and feature vectors; and an image adjuster executable by the one or more hardware processors and configured to adjust one or more of the multi-view images by transforming one or both of the right image patch and the left image patch based on the determined displacement vector field.
