

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407461
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kubota; Keiichi et al.

Techniques for providing uplink-based mobility

Abstract

Techniques are described for wireless communication. A method for wireless communication at a user equipment (UE) includes identifying, while the UE is in a connected mode with a network, a radio resource configuration of the UE, selecting a dedicated set of resources for the UE or a common set of resources for a plurality of UEs based at least in part on the identified radio resource configuration, and transmitting a pilot signal to the network using the selected set of resources. Methods for wireless communication at a network access device and a network access device controller are also described.

Inventors: Kubota; Keiichi (Tokyo, JP), Horn; Gavin Bernard (La Jolla, CA), Ji; Tingfang (San Diego, CA), Soriaga; Joseph Binamira (San Diego, CA), Azarian Yazdi; Kambiz (San Diego, CA), Tavildar; Saurabha Rangrao (San Francisco, CA)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 59315207

Assignee: QUALCOMM Incorporated (San Diego, CA)

Appl. No.: 18/055575

Filed: November 15, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230072864 A1	Mar. 09, 2023

Related U.S. Application Data

division parent-doc US 17327272 20210521 US 11510122 child-doc US 18055575
division parent-doc US 15192513 20160624 US 11026142 20210601 child-doc US 17327272
us-provisional-application US 62280920 20160120

Publication Classification

Int. Cl.: **H04W36/30** (20090101); **H04L5/00** (20060101); **H04L43/10** (20220101); **H04W36/16** (20090101); **H04W72/0453** (20230101); **H04W76/28** (20180101); H04W36/08 (20090101); H04W36/34 (20090101)

U.S. Cl.:

CPC **H04L5/0048** (20130101); **H04L5/005** (20130101); **H04L5/0051** (20130101); **H04L43/10** (20130101); **H04W36/165** (20130101); **H04W36/304** (20230501); **H04W72/0453** (20130101); **H04W76/28** (20180201); H04W36/087 (20230501); H04W36/34 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6519248	12/2002	Valko	N/A	N/A
8891489	12/2013	Attar et al.	N/A	N/A
10172177	12/2018	Gheorghiu et al.	N/A	N/A
11026142	12/2020	Kubota et al.	N/A	N/A
2009/0028112	12/2008	Attar et al.	N/A	N/A
2010/0067479	12/2009	Choi et al.	N/A	N/A
2010/0118752	12/2009	Suzuki et al.	N/A	N/A
2010/0142492	12/2009	Huschke	370/336	H04B 7/022
2011/0098054	12/2010	Gorokhov et al.	N/A	N/A
2011/0110398	12/2010	Zhang et al.	N/A	N/A
2011/0249558	12/2010	Raaf et al.	N/A	N/A
2011/0292895	12/2010	Wager et al.	N/A	N/A
2012/0113938	12/2011	Larsson et al.	N/A	N/A
2012/0252513	12/2011	Kiyoshima et al.	N/A	N/A
2012/0320847	12/2011	Nam et al.	N/A	N/A
2013/0165122	12/2012	Tanaka	455/436	H04W 36/00692
2013/0188612	12/2012	Dinan	N/A	N/A
2013/0308551	12/2012	Madan et al.	N/A	N/A
2014/0024372	12/2013	Zhao et al.	N/A	N/A
2014/0153536	12/2013	Ouchi et al.	N/A	N/A
2014/0213245	12/2013	Yang et al.	N/A	N/A
2014/0256328	12/2013	Li et al.	N/A	N/A
2014/0274079	12/2013	Li	455/450	H04L 5/0048
2014/0321416	12/2013	Pragada et al.	N/A	N/A
2014/0376482	12/2013	Kim et al.	N/A	N/A
2015/0063253	12/2014	Barbieri et al.	N/A	N/A
2015/0296522	12/2014	Bergstrom et al.	N/A	N/A

2015/0305041	12/2014	Kim	N/A	N/A
2015/0327198	12/2014	Axmon	370/336	H04W 56/0005
2015/0365869	12/2014	Gao	370/230	H04W 36/22
2016/0262074	12/2015	Reial	N/A	H04W 36/302
2017/0034842	12/2016	Xu	N/A	H04W 64/00
2017/0208516	12/2016	Kubota et al.	N/A	N/A
2018/0323917	12/2017	Um et al.	N/A	N/A
2018/0332618	12/2017	Kakishma et al.	N/A	N/A
2020/0314933	12/2019	Tang et al.	N/A	N/A
2021/0274409	12/2020	Kubota et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101986586	12/2010	CN	N/A
102651910	12/2011	CN	N/A
102958095	12/2012	CN	N/A
103220708	12/2012	CN	N/A
103581989	12/2013	CN	N/A
105228238	12/2015	CN	N/A
2011250386	12/2010	JP	N/A
WO2010124241	12/2009	WO	N/A
WO2010124241	12/2009	WO	N/A
WO2013164024	12/2012	WO	N/A
WO-2013177179	12/2012	WO	N/A
WO-2014110758	12/2013	WO	N/A
WO-2014120618	12/2013	WO	N/A
WO2014172270	12/2013	WO	N/A
WO-2015046949	12/2014	WO	N/A

OTHER PUBLICATIONS

Xu-Ming F., et al., “The Evolution and Development of Key Technologies of Mobile Communication Systems for High-Speed Railway”, Journal of Electronics & Information Technology, vol. 37, No. 1, Jan. 15, 2015, 10 Pages. cited by applicant

3GPP TS 36.331: “3rd Generation Partnership Project; Technical Specification Group Radio Access Network; Evolved Universal Terrestrial Radio Access (E-UTRA); Radio Resource Control (RRC); Protocol Specification (Release 10)”, V10.4.0 (Dec. 2011), XP050555028, Dec. 20, 2011, 296 Pages. European Search Report—EP20196978—Search Authority—Munich—Oct. 6, 2020. cited by applicant

European Search Report—EP20196978—Search Authority—Munich—Oct. 6, 2020. cited by applicant

International Preliminary Report on Patentability—PCT/US2017/013963, The International Bureau of WIPO—Geneva, Switzerland, May 22, 2018. cited by applicant

International Search Report and Written Opinion—PCT/US2017/013963—ISA/EPO—Jun. 12, 2017. cited by applicant

International Search Report and Written Opinion—PCT/US2017/013963—ISA/EPO—Sep. 13, 2017. cited by applicant

ISA/EPO, Partial International Search Report of the International Searching Authority, International App. No. PCT/US2017/013963, Apr. 21, 2017, European Patent Office, Rijswijk, NL, 18 Pages. cited by applicant

Nam Y-H., et al., “Evolution of Reference Signals for LTE-Advanced Systems”, IEEE Communications Magazine, IEEE Service Center, Piscataway, NJ, Feb. 9, 2012, 7 pages, vol. 50, No. 2, XP011417049, Feb. 1, 2012, ISSN: 0163-6804, DOI: 10.1109/MCOM.2012.6146492. cited by applicant

NTT Docomo, et al., “RRC_Connected DRX and Dedicated UL Resources”, 3GPP TSG RAN WG2 #60bis, 3GPP Draft, R2-080462, Sevilla, Spain, Jan. 14-18, 2008, 2 Pages, Jan. 8, 2008, XP050138308. cited by applicant

Qualcomm Europe: “RAN Level ”Keep-Alive“ Signalling”, 3GPP TSG-RAN WG2 Meeting #61-bis, R2-081551 (re-submission of R2-081096), Shenzhen, China, Mar. 31-Apr. 4, 2008, 3 Pages, Mar. 25, 2008, XP050139287. cited by applicant

Qualcomm Incorporated, et al., “NR RRC States Definition”, 3GPP TSG-RAN WG2 Meeting #94, R2-164095, Nanjing, China May 23-27, 2016, pp. 1-4. cited by applicant

Qualcomm Incorporated, et al., “RRC States for NR”, 3GPP TSG-RAN WG2 Meeting #93bis, R2-162742, Dubrovnik, Croatia Apr. 11-15, 2016, pp. 1-4. cited by applicant

Qualcomm Incorporated: “Reduction of RRC Signalling,” 3GPP TSG-SA1#56, S1-113305, Dublin, EI, Aug. 8, 2011-Aug. 12, 2011, 1 page. cited by applicant

Taiwan Search Report—TW106101507—TIPO—Jan. 15, 2021. cited by applicant

Zhang J., et al., “Mobility Enhancement and Performance Evaluation for 5G Ultra Dense Networks”, IEEE Wireless Communications and Networking Conference (WCNC), Track 3: Mobile and Wireless Networks, Mar. 9, 2015, XP032786398, DOI: 10.1109/WCNC.2015.7127740 [retrieved on Jun. 17, 2015], pp. 1793-1798. cited by applicant

Primary Examiner: Van; Jenkey

Attorney, Agent or Firm: QUALCOMM IP DEPT.

Background/Summary

CROSS REFERENCES (1) The present application is a Divisional of U.S. patent application Ser. No. 17/327,272 by Kubota, et al., entitled “Techniques For Providing Uplink-Based Mobility” filed May 21, 2021, which is a Divisional of U.S. patent application Ser. No. 15/192,513 by Kubota et al., entitled “Techniques For Providing Uplink-Based Mobility” filed Jun. 24, 2016, which claims priority to U.S. Provisional Patent Application No. 62/280,920 by Kubota et al., entitled “Techniques for Providing User Equipment-Centric Mobility,” filed Jan. 20, 2016. All of said applications are assigned to the assignee hereof, and are expressly incorporated by reference herein as if fully set forth below and for all applicable purposes.

BACKGROUND

Field of the Disclosure

(1) The present disclosure, for example, relates to wireless communication systems, and more particularly to techniques for providing uplink-based mobility.

Description of Related Art

(2) Wireless communication systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on. These systems may be multiple-access systems capable of supporting communication with multiple users by sharing the available system resources (e.g., time, frequency, and power). Examples of such multiple-access systems include code-division multiple access (CDMA) systems, time-division multiple access (TDMA) systems, frequency-division multiple access (FDMA) systems, and orthogonal frequency-division multiple access (OFDMA) systems.

(3) In some examples, a wireless multiple-access communication system may include a number of base stations, each simultaneously supporting communication for multiple communication devices, otherwise known as UEs. In a Long-Term Evolution (LTE) or LTE-Advanced (LTE-A) network, a set of one or more base stations may define an eNodeB (eNB). In other examples (e.g., in a next generation or 5G network), a wireless multiple access communication system may include a number of distributed units (e.g., edge units (EUs), edge nodes (ENs), radio heads (RHs), smart radio heads (SRHs), transmission and reception points (TRPs), etc.) in communication with a number of central units (e.g., central nodes (CNs), access node controllers (ANCs), etc.), where a set of one or more distributed units, in communication with a central unit, may define an access node (e.g., a new radio base station (NR BS), a new radio node-B (NR NB), a network node, etc.). A base station or DU may communicate with a set of UEs on downlink channels (e.g., for transmissions from a base station or to a UE) and uplink channels (e.g., for transmissions from a UE to a base station or distributed unit).

(4) Some next generation or 5G networks may support an uplink-based medium access control (MAC) layer. In these networks, a UE may transmit a pilot signal (e.g., a reference signal) for network access devices (e.g., distributed units) to receive and measure. Based on measurements of the pilot signal by one or more network access devices, the network may identify a serving cell (or serving distributed unit) for the UE. As the UE moves within the network, the network may make at least some mobility decisions for the UE (e.g., decisions to initiate a handover of the UE from one serving cell to another serving cell) transparently to the UE (e.g., without notifying the UE of the mobility decision, or without involving the UE in the mobility decision).

SUMMARY

(5) The present disclosure, for example, relates to techniques for providing uplink-based mobility, which in some examples may be referred to as user equipment (UE) centric mobility. In accordance with the described techniques, a network may provide a common set of resources (e.g., one or more component carriers or channels of a radio frequency spectrum band, one or more sub-carriers of a radio frequency spectrum band, one or more resource blocks of a subframe, one or more durations of time, periodic time increments between resource availability, etc.) that any UE may use to transmit a pilot signal to the network. The network may also allocate a dedicated set of resources to each of one or more UEs. Upon initially accessing the network, a UE may transmit a pilot signal to the network using the common set of resources. After accessing the network, the UE may continue to transmit a pilot signal to the network using the common set of resources (e.g., if the UE is relatively inactive, traffic between the UE and the network is relatively low, etc.); or, when a dedicated set of resources has been allocated to the UE, the UE may transmit a pilot signal to the network using the dedicated set of resources instead of the common set of resources. In some cases, a dedicated set of resources may be allocated to an active UE (e.g., a UE having a higher level of traffic to transmit/receive to/from the network), and the UE may be configured to use the dedicated set of resources when the dedicated set of resources is available. In other cases, the UE may determine when or whether to use the dedicated set of resources. In some examples, procedures for handling UE mobility may vary, depending on whether a UE is operating in a radio resource configuration associated with transmitting pilots using a dedicated set of resources to transmit a pilot signal or operating in a radio resource configuration associated with transmitting pilots using a common set of resources to transmit a pilot signal.

(6) A method for wireless communication at a UE is described. The method may include: identifying, while the UE is in a connected mode with a network, a radio resource configuration of the UE; selecting a dedicated set of resources for the UE or a common set of resources for a plurality of UEs based at least in part on the identified radio resource configuration; and transmitting a pilot signal to the network using the selected set of resources.

(7) An apparatus for wireless communication at a UE is described. The apparatus may include a processor and memory in electronic communication with the processor. The processor and the

memory may be configured to: identify, while the UE is in a connected mode with a network, a radio resource configuration of the UE; select a dedicated set of resources for the UE or a common set of resources for a plurality of UEs based at least in part on the identified radio resource configuration; and transmit a pilot signal to the network using the selected set of resources.

(8) An apparatus for wireless communication at a UE is described. The apparatus may include: means for identifying, while the UE is in a connected mode with a network, a radio resource configuration of the UE; means for selecting a dedicated set of resources for the UE or a common set of resources for a plurality of UEs based at least in part on the identified radio resource configuration; and means for transmitting a pilot signal to the network using the selected set of resources.

(9) A non-transitory computer-readable medium storing computer-executable code for wireless communication at a UE is described. The code may be executable by a processor to: identify, while the UE is in a connected mode with a network, a radio resource configuration of the UE; select a dedicated set of resources for the UE or a common set of resources for a plurality of UEs based at least in part on the identified radio resource configuration; and transmit a pilot signal to the network using the selected set of resources.

(10) In some examples of the method, apparatuses, or non-transitory computer-readable medium, the identified radio resource configuration of the UE may include a radio resource control (RRC) configuration.

(11) In some examples of the method, apparatuses, or non-transitory computer-readable medium, the identified radio resource configuration of the UE comprises an RRC dedicated state or an RRC common state.

(12) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: identifying a serving cell for the UE based at least in part on a keep alive signal received from the serving cell for the UE, the keep alive signal based at least in part on the pilot signal.

(13) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: receiving the keep alive signal using the selected set of resources.

(14) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: receiving an allocation of the common set of resources in at least one of: a synchronization signal, or system information, or a unicast message, or a combination thereof.

(15) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: identifying an allocation of the common set of resources based at least in part on a type of the UE.

(16) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: receiving an allocation of the dedicated set of resources in at least one of: a unicast message, or a timing of the unicast message, or a combination thereof.

(17) In some examples of the method, apparatuses, or non-transitory computer-readable medium, the pilot signal may be transmitted periodically based at least in part on a discontinuous reception (DRX) configuration of the UE or a discontinuous transmission (DTX) configuration of the UE.

(18) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: identifying a zone in which the UE is located; and configuring the pilot signal based at least in part on the identified zone.

(19) In some examples of the method, apparatuses, or non-transitory computer-readable medium, the dedicated set of resources may be associated with a more granular periodicity than the common set of resources.

(20) A method for wireless communication at a network access device is described. The method

may include: identifying at least one dedicated set of resources for at least one UE in a first set of UEs, wherein the network access device is a member of a monitoring set of network access devices for each UE in the first set of UEs; measuring a first set of pilot signals received from the first set of UEs on the at least one dedicated set of resources, and a second set of pilot signals received from a second set of UEs using a common set of resources; and identifying, based at least in part on measurements of the first set of pilot signals and the second set of pilot signals, a third set of UEs for which the network access device operates as a serving cell.

(21) An apparatus for wireless communication at a network access device is described. The method may include a processor and memory in electronic communication with the processor. The processor and the memory may be configured to: identify at least one dedicated set of resources for at least one UE in a first set of UEs, wherein the network access device is a member of a monitoring set of network access devices for each UE in the first set of UEs; measure a first set of pilot signals received from the first set of UEs on the at least one dedicated set of resources, and a second set of pilot signals received from a second set of UEs using a common set of resources; and identify, based at least in part on measurements of the first set of pilot signals and the second set of pilot signals, a third set of UEs for which the network access device operates as a serving cell.

(22) Another apparatus for wireless communication at a network access device is described. The apparatus may include: means for identifying at least one dedicated set of resources for at least one UE in a first set of UEs, wherein the network access device is a member of a monitoring set of network access devices for each UE in the first set of UEs; means for measuring a first set of pilot signals received from the first set of UEs on the at least one dedicated set of resources, and a second set of pilot signals received from a second set of UEs using a common set of resources; and means for identifying, based at least in part on measurements of the first set of pilot signals and the second set of pilot signals, a third set of UEs for which the network access device operates as a serving cell.

(23) A non-transitory computer-readable medium storing computer-executable code for wireless communication at a network access device is described. The code may be executable by a processor to: identify at least one dedicated set of resources for at least one UE in a first set of UEs, wherein the network access device is a member of a monitoring set of network access devices for each UE in the first set of UEs; measure a first set of pilot signals received from the first set of UEs on the at least one dedicated set of resources, and a second set of pilot signals received from a second set of UEs using a common set of resources; and identify, based at least in part on measurements of the first set of pilot signals and the second set of pilot signals, a third set of UEs for which the network access device operates as a serving cell.

(24) In some examples of the method, apparatuses, or non-transitory computer-readable medium, the third set of UEs may include at least one UE in the first set of UEs, or at least one UE in the second set of UEs, or a combination thereof.

(25) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: transmitting a dedicated keep alive signal to each UE that is a member of both the first set of UEs and the third set of UEs, or transmitting a common keep alive signal to each UE that is a member of both the second set of UEs and the third set of UEs, or a combination thereof.

(26) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: determining whether a pilot signal received from a UE on the common set of resources satisfies at least one threshold; and transmitting a keep alive signal to the UE, using the common set of resources, upon determining the pilot signal satisfies the at least one threshold.

(27) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: receiving, from another network access device, a reconfiguration message for a UE that is a member of both the first set of UEs and the

third set of UEs, the reconfiguration message identifying a reconfigured dedicated set of resources to be used, by the UE, after a handover of the UE from the network access device to a different network access device; and forwarding the reconfiguration message to the UE.

(28) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: receiving, from another network access device, a reconfiguration message for a UE that is being handed over to the network access device, the reconfiguration message identifying a reconfigured dedicated set of resources to be used, by the UE, after a handover of the UE to the network access device; forwarding the reconfiguration message to the UE; and adding the UE to the first set of UEs and the third set of UEs.

(29) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: receiving a reconfiguration complete message from a UE which has been handed over to the network access device; and forwarding the reconfiguration complete message to another network access device.

(30) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: transmitting at least one of the measurements of the first set of pilot signals or at least one of the measurements of the second set of pilot signals to another network access device; and receiving, from the other network access device, updates to the third set of UEs.

(31) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: selecting the at least one of the measurements of the first set of pilot signals or the at least one of the measurements of the second set of pilot signals based at least in part on a periodic measurement reporting criteria or an event-driven measurement reporting criteria.

(32) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: receiving additional measurements of the first set of pilot signals or the second set of pilot signals from at least one other network access device, wherein the identifying the third set of UEs is based at least in part on the additional measurements.

(33) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: receiving, from another network access device, an update to the first set of UEs.

(34) In some examples of the method, apparatuses, or non-transitory computer-readable medium, the network access device includes a distributed unit.

(35) A method for wireless communication is described. The method may include: receiving, from each cell of a plurality of cells, measurements of a first set of pilot signals transmitted by a first set of UEs operating with a first radio resource configuration while connected to a network, and of a second set of pilot signals transmitted by a second set of UEs operating with a second radio resource configuration while connected to the network; identifying, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the measurements, a serving cell for the respective UE; identifying, for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals transmitted by the respective UE; and indicating, to each cell, a first set of UEs for which the respective cell is a serving cell, and a second set of UEs for which the respective cell is a member of a monitoring set of cells.

(36) An apparatus for wireless communication is described. The apparatus may include a processor and memory in electronic communication with the processor. The processor and the memory may be configured to: receive, from each cell of a plurality of cells, measurements of a first set of pilot signals transmitted by a first set of UEs operating with a first radio resource configuration while connected to a network, and of a second set of pilot signals transmitted by a second set of UEs operating with a second radio resource configuration while connected to the network; identify, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the

measurements, a serving cell for the respective UE; identify, for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals transmitted by the respective UE; and indicate, to each cell, a first set of UEs for which the respective cell is a serving cell, and a second set of UEs for which the respective cell is a member of a monitoring set of cells.

(37) Another apparatus for wireless communication is described. The apparatus may include: means for receiving, from each cell of a plurality of cells, measurements of a first set of pilot signals transmitted by a first set of UEs operating with a first radio resource configuration while connected to a network, and of a second set of pilot signals transmitted by a second set of UEs operating with a second radio resource configuration while connected to the network; means for identifying, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the measurements, a serving cell for the respective UE; means for identifying, for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals transmitted by the respective UE; and means for indicating, to each cell, a first set of UEs for which the respective cell is a serving cell, and a second set of UEs for which the respective cell is a member of a monitoring set of cells.

(38) A non-transitory computer-readable medium storing computer-executable code for wireless communication is described. The code may be executable by a processor to: receive, from each cell of a plurality of cells, measurements of a first set of pilot signals transmitted by a first set of UEs operating with a first radio resource configuration while connected to a network, and of a second set of pilot signals transmitted by a second set of UEs operating with a second radio resource configuration while connected to the network; identify, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the measurements, a serving cell for the respective UE; identify, for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals transmitted by the respective UE; and indicate, to each cell, a first set of UEs for which the respective cell is a serving cell, and a second set of UEs for which the respective cell is a member of a monitoring set of cells.

(39) In some examples of the method, apparatuses, or non-transitory computer-readable medium, the first radio resource configuration may be associated with transmitting pilot signals using a dedicated set of resources, and the second radio resource configuration may be associated with transmitting pilot signals using a common set of resources.

(40) In some examples of the method, apparatuses, or non-transitory computer-readable medium, the first radio resource configuration, or the second radio resource configuration, or both comprises a RRC configuration.

(41) Some examples of the method, apparatuses, or non-transitory computer-readable medium may include operations, features, means, or instructions for: identifying a change in a serving cell for a UE in the first set of UEs; and initiating a serving cell change procedure for the UE upon identifying the change in the serving cell.

(42) In some examples of the method, apparatuses, or non-transitory computer-readable medium, initiating the serving cell change procedure may include operations, features, means, or instructions for: transmitting to the UE, through a source serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message identifying a dedicated set of resources to be used, by the UE, after a handover of the UE to a target serving cell.

(43) In some examples of the method, apparatuses, or non-transitory computer-readable medium, initiating the serving cell change procedure may include operations, features, means, or instructions for: transmitting to the UE, through a target serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message identifying a dedicated set of resources to be used, by the UE, after a handover of the UE to the target serving cell.

(44) In some examples of the method, apparatuses, or non-transitory computer-readable medium, identifying a monitoring set of cells to monitor for pilot signals transmitted by a UE may be based at least in part on: measurements of at least one pilot signal transmitted by the UE, or a location of

the identified serving cell for the UE, or a combination thereof.

(45) The foregoing has outlined rather broadly the techniques and technical advantages of examples according to the disclosure in order that the detailed description that follows may be better understood. Additional techniques and advantages will be described hereinafter. The conception and specific examples disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present disclosure. Such equivalent constructions do not depart from the scope of the appended claims. Characteristics of the concepts disclosed herein, both their organization and method of operation, together with associated advantages will be better understood from the following description when considered in connection with the accompanying figures. Each of the figures is provided for the purpose of illustration and description, and not as a definition of the limits of the claims.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) A further understanding of the nature and advantages of the methods, apparatuses, and non-transitory computer readable medium associated with the present invention may be realized by reference to the following drawings. In the appended figures, similar components or functions may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

(2) FIG. 1 illustrates an example of a wireless communication system that supports uplink-based mobility, in accordance with various aspects of the disclosure;

(3) FIG. 2 shows an example of a timeline of operations that may be performed in a network that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(4) FIG. 3 illustrates an example of a wireless communication system that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(5) FIG. 4 illustrates an example of a wireless communication system that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(6) FIG. 5 illustrates a diagram showing examples for implementing a communications protocol stack that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(7) FIGS. 6-9 show examples of communication flows that support uplink-based mobility, in accordance with various aspects of the present disclosure;

(8) FIG. 10 shows a block diagram of an apparatus that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(9) FIG. 11 shows a block diagram of a UE wireless communication manager that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(10) FIG. 12 shows a block diagram of an apparatus that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(11) FIG. 13 shows a block diagram of a transmit/receive communication manager that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(12) FIG. 14 shows a block diagram of an apparatus that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(13) FIG. 15 shows a block diagram of an access node communication manager that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(14) FIG. 16 shows a block diagram of a UE that supports uplink-based mobility, in accordance

with various aspects of the present disclosure;

(15) FIGS. **17** and **18** show block diagrams of network access devices that support uplink-based mobility, in accordance with various aspects of the present disclosure;

(16) FIG. **19** is a block diagram of a multiple-input multiple-output (MIMO) communication system that supports uplink-based mobility, in accordance with various aspects of the present disclosure;

(17) FIGS. **20** and **21** show flow charts illustrating examples of methods that support uplink-based mobility at a UE, in accordance with various aspects of the present disclosure; and

(18) FIGS. **22-26** show flow charts illustrating examples of methods that support uplink-based mobility at a network access device, in accordance with various aspects of the present disclosure.

DETAILED DESCRIPTION

(19) Techniques are described in which uplink-based mobility is provided. The techniques may enable a UE to operate in various radio resource configurations, including a configuration associated with transmitting pilots using a dedicated set of resources (e.g., a radio resource control (RRC) dedicated state, etc.) or a configuration associated with transmitting pilots using a common set of resources (e.g., an RRC common state, etc.). When operating in the RRC dedicated state, the UE may select a dedicated set of resources for transmitting a pilot signal to a network. When operating in the RRC common state, the UE may select a common set of resources for transmitting a pilot signal to the network. In either case, a pilot signal transmitted by the UE may be received by one or more network access devices, such as an access node (AN), or a distributed unit (DU), or portions thereof. Each receiving network access device may be configured to receive and measure pilot signals transmitted on the common set of resources, and also receive and measure pilot signals transmitted on dedicated sets of resources allocated to the UEs for which the network access device is a member of a monitoring set of network access devices for the UE. One or more of the receiving network access devices, or a central unit (CU) to which receiving network access device(s) transmit the measurements of the pilot signals, may use the measurements to identify serving cells for the UEs, or to initiate a change of serving cell for one or more of the UEs.

(20) The following description provides examples, and is not limiting of the scope, applicability, or examples set forth in the claims. Changes may be made in the function and arrangement of elements discussed without departing from the scope of the disclosure. Various examples may omit, substitute, or add various procedures or components as appropriate. For instance, the methods described may be performed in an order different from that described, and various steps may be added, omitted, or combined. Also, features described with respect to some examples may be combined in some other examples.

(21) FIG. **1** illustrates an example of a wireless communication system **100** that supports uplink-based mobility, in accordance with various aspects of the disclosure. The wireless communication system **100** may include network access devices **105**, which may include ANs **105-a**, CUs **105-b**, and/or DUs **105-c**. Each of the ANs **105-a** may be an example of a new radio base station (NR BS), a new radio Node-B (NR NB), a network node (NN), or the like. Each of the CUs **105-b** may be an example of a central node (CN), an access node controller (ANC), or the like. Each of the DUs **105-c** may be an example of an edge node (EN), an edge unit (EU), a radio head (RH), a smart radio head (SRH), a transmission and reception point (TRP), or the like. The wireless communication system **100** may also include UEs **115**, and a core network **130**. The core network **130** may provide user authentication, access authorization, tracking, Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. At least some of the network access devices **105** (e.g., ANs **105-a**, CUs **105-b**, etc.) may interface with the core network **130** through backhaul links **132** (e.g., S1, S2, etc.) and may perform radio configuration and scheduling for communication with the UEs **115**.

(22) In various examples, CUs **105-b** may communicate, either directly or indirectly (e.g., through core network **130**), with each other over backhaul links **134** (e.g., X1, X2, etc.), which may be

wired or wireless communication links. Each CU **105-b** may also communicate with a number of UEs **115** through a number of distributed network access devices, such as DUs **105-c**. A DU **105-c** may include, for example, radio frequency (RF) components (e.g., at least one transceiver) and a modem. In some configurations of the wireless communication system **100**, functionality of a CU **105-b** may be provided by a DU **105-c** or distributed across the DUs **105-c** of an AN **105-a**. In some configurations of the wireless communication system **100**, DUs **105-c** may be replaced with base stations, and CUs **105-b** may be replaced by base station controllers (or links to the core network **130**).

(23) The CUs **105-b** may wirelessly communicate with the UEs **115** via one or more DUs **105-c**, with each DU **105-c** having one or more antennas. Each of the DUs **105-c** may provide communication coverage for a respective geographic coverage area **110-b**, and may provide one or more remote transceivers associated with a CU **105-b**. In some examples an AN **105-a** may be associated with a geographic coverage area, such as geographic coverage area **110-a**, which may be formed from a collection of geographic coverage areas **110-b** associated with DUs **105-c** of the AN **105-a** where applicable. A DU **105-c** may perform many of the functions of a LTE/LTE-A base station. In some examples, a CU **105-b** may be implemented in distributed form, with a portion of the CU **105-b** being provided in each DU **105-c**. The geographic coverage areas **110-a** for an AN **105-a** or geographic coverage areas **110-b** for a DU **105-c** may be divided into sectors making up only a portion of the coverage area (not shown). In some examples, the network access devices **105** may be replaced with alternative network access devices, such as base transceiver stations, radio base stations, access points, radio transceivers, NodeBs, eNodeBs (eNBs), Home NodeBs, Home eNodeBs, NR BSs, NR NBs, etc. The wireless communication system **100** may include DUs **105-c** (or base stations or other network access devices) of different types (e.g., macro cell and/or small cell network access devices). The geographic coverage areas **110-a** of the ANs **105-a** or the geographic coverage areas **110-b** of the DUs **105-c** or other network access devices may overlap. In some examples, different network access devices **105** may be associated with different radio access technologies.

(24) In various examples, the wireless communication system **100** may include a 5G network, an LTE/LTE-A network, or combinations thereof. The wireless communication system **100** may in some cases be a heterogeneous network, in which different types of ANs provide coverage for various geographical regions. For example, each AN **105-a** or DU **105-c** may provide communication coverage for a macro cell, a small cell, and/or other types of cell. The term “cell” can be used to describe a network access device **105** (e.g. an AN **105-a**, a centralized network access device such as CU **105-b**, a distributed network access device such as DU **105-c**, etc.), a carrier or component carrier associated with a network access device **105**, or a coverage area (e.g., sector, etc.) of a carrier or network access device, depending on context.

(25) A macro cell may cover a relatively large geographic area (e.g., several kilometers in radius) and may allow unrestricted access by UEs **115** with service subscriptions with a network provider. A small cell may include a lower-powered DU or base station, as compared with a macro cell, and may operate in the same or different frequency band(s) as macro cells. Small cells may include pico cells, femto cells, and micro cells according to various examples. A pico cell may cover a relatively smaller geographic area and may allow unrestricted access by UEs **115** with service subscriptions with a network provider. A femto cell also may cover a relatively small geographic area (e.g., a home) and may provide restricted access by UEs **115** having an association with the femto cell (e.g., UEs in a closed subscriber group (CSG), UEs for users in the home, and the like). An AN for a macro cell may be referred to as a macro AN (e.g., a macro eNB, etc.). An AN for a small cell may be referred to as a small cell AN, a pico AN, a femto AN, or a home AN (e.g., a small cell eNB, a pico eNB, a femto eNB, a home eNB, etc.). An AN may support one or multiple (e.g., two, three, four, and the like) cells (e.g., component carriers).

(26) The wireless communication system **100** may support synchronous or asynchronous operation.

For synchronous operation, the ANs **105-a** and/or DUs **105-c** may have similar frame timing, and transmissions from different ANs **105-a** and/or DUs **105-c** may be approximately aligned in time. For asynchronous operation, the ANs **105-a** and/or DUs **105-c** may have different frame timings, and transmissions from different ANs **105-a** and/or DUs **105-c** may not be aligned in time. The techniques described herein may be used for either synchronous or asynchronous operations.

(27) The communication networks that may accommodate some of the various disclosed examples may be packet-based networks that operate according to a layered protocol stack. In the user plane, communications at the bearer or Packet Data Convergence Protocol (PDCP) layer may be IP-based. A Radio Link Control (RLC) layer may in some cases perform packet segmentation and reassembly to communicate over logical channels. A Medium Access Control (MAC) layer may perform priority handling and multiplexing of logical channels into transport channels. The MAC layer may also use Hybrid ARQ (HARM) to provide retransmission at the MAC layer to improve link efficiency. In the control plane, the Radio Resource Control (RRC) protocol layer may provide establishment, configuration, and maintenance of an RRC connection between a UE **115** and a DU **105-c**, a CU **105-b**, an AN **105-a**, or core network **130** supporting radio bearers for user plane data. At the Physical (PHY) layer, transport channels may be mapped to physical channels.

(28) The UEs **115** may be dispersed throughout the wireless communication system **100**, and each UE **115** may be stationary or mobile. A UE **115** may also include or be referred to by those skilled in the art as a mobile station, a subscriber station, a mobile unit, a subscriber unit, a wireless unit, a remote unit, a mobile device, a wireless device, a wireless communications device, a remote device, a mobile subscriber station, an access terminal, a mobile terminal, a wireless terminal, a remote terminal, a handset, a user agent, a mobile client, a client, or some other suitable terminology. A UE **115** may be a cellular phone, a personal digital assistant (PDA), a wireless modem, a wireless communication device, a handheld device, a tablet computer, a laptop computer, a cordless phone, a wireless local loop (WLL) station, an Internet of Everything (IoE) device, or other electronic device having a wireless communication interface. A UE may be able to communicate with various types of ANs **105-a**, DUs **105-c**, base stations, access points, or other network access devices, including macro ANs, small cell ANs, relay base stations, and the like. A UE may also be able to communicate directly with other UEs (e.g., using a peer-to-peer (P2P) protocol).

(29) The communication links **125** shown in wireless communication system **100** may include uplink (UL) channels from a UE **115** to a DU **105-c** or an AN **105-a**, and/or downlink (DL) channels, from a DU **105-c** or an AN **105-a** to a UE **115**. The downlink channels may also be called forward link channels, while the uplink channels may also be called reverse link channels.

(30) One or more of the UEs **115** may include a UE wireless communication manager **1020**. In some examples, the UE wireless communication manager **1020** may be used to identify, while the UE **115** is in a connected mode with a network defined by the wireless communication system **100**, a radio resource configuration of the UE **115**. In some examples identifying the radio resource configuration of the UE **115** may include identifying if the UE is operating with a radio resource configuration associated with transmitting pilots using a dedicated set of resources (e.g., an RRC dedicated state, etc.) or a common set of resources (e.g. an RRC common state, etc.). The UE wireless communication manager **1020** may also be used to select a dedicated set of resources or a common set of resources for the UE **115** based at least in part on the identified radio resource configuration, and to transmit a pilot signal to the network (e.g., to a DU **105-c**, an AN **105-a**, etc.) using the selected set of resources. In some examples, the UE wireless communication manager **1020** may be an example of the UE wireless communication manager **1020** described with reference to FIG. **10**, **11**, **16**, or **19**.

(31) One or more of the network access devices **105** (e.g., one or more ANs **105-a**, one or more DUs **105-c**, etc.) may include a transmit/receive communication manager **1220**. In some examples, the transmit/receive communication manager **1220** may be used to identify at least one dedicated

set of resources for at least one UE in a first set of UEs. The network access device **105** including the transmit/receive communication manager **1220** may be a member of a monitoring set of network access devices **105** for each UE in the first set of UEs. The transmit/receive communication manager **1220** may also be used to measure a first set of pilot signals received from the first set of UEs using a dedicated set of resources, and a second set of pilot signals received from a second set of UEs using a common set of resources. The transmit/receive communication manager **1220** may subsequently identify, based at least in part on measurements of the first set of pilot signals and the second set of pilot signals, a third set of UEs for which the network access device **105** operates as a serving cell. In some examples, the transmit/receive communication manager **1220** may be an example of aspects of transmit/receive communication managers **1220** described with reference to FIG. **12**, **13**, **17**, or **19**.

(32) One or more of the network access devices **105** (e.g., one or more ANs **105-a**, one or more CUs **105-b**, etc.) may include an access node communication manager **1420**. In some examples, the access node communication manager **1420** may be used to receive, from each cell of a plurality of cells, measurements of a first set of pilot signals transmitted by a first set of user UEs operating with a first radio resource configuration while connected to a network (e.g., a network defined by the wireless communication system **100**), and of a second set of pilot signals transmitted by a second set of UEs operating with a second radio resource configuration while connected to the network. The first radio resource configuration may be associated with UEs transmitting pilot signals using a dedicated set of resources (e.g., an RRC dedicated state), and the second radio resource configuration may be associated with UEs transmitting pilot signals using a common set of resources (e.g., an RRC common state). The access node communication manager **1420** may also be used to identify, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the measurements, a serving cell for the respective UE. The access node communication manager **1420** may also be used to identify, for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals transmitted by the respective UE. In some examples the access node communication manager **1420** may indicate, to each cell, a first set of UEs for which the respective cell is a serving cell, and a second set of UEs for which the respective cell is a member of a monitoring set of cells. In some examples, the access node communication manager **1420** may be an example of access node communication managers **1420** described with reference to FIG. **14**, **15**, **18**, or **19**.

(33) Each communication link **125** may include one or more carriers, where each carrier may be a signal made up of multiple sub-carriers or tones (e.g., waveform signals of different frequencies) modulated according to one or more radio access technologies. Each modulated signal may be sent on a different sub-carrier and may carry control information (e.g., reference signals, control channels, etc.), overhead information, user data, etc. The communication links **125** may transmit bidirectional communications using Frequency Division Duplexing (FDD) techniques (e.g., using paired spectrum resources) or Time Division Duplexing (TDD) techniques (e.g., using unpaired spectrum resources). Frame structures for FDD (e.g., frame structure type **1**) and TDD (e.g., frame structure type **2**) may be defined.

(34) In some examples of the wireless communication system **100**, the ANs **105-a**, DUs **105-c** and/or UEs **115** may include multiple antennas for employing antenna diversity schemes to improve communication quality and reliability between ANs **105-a**, DUs **105-c**, and UEs **115**. Additionally or alternatively, ANs **105-a**, DUs **105-c** and/or UEs **115** may employ multiple-input multiple-output (MIMO) techniques that may take advantage of multi-path environments to transmit multiple spatial layers carrying the same or different coded data. In some examples two or more DUs **105-c** may be configured in cooperation to support directional transmission and/or reception techniques, such as techniques associated with beamforming of transmissions by multiple DUs **105-c** for directional transmission and/or precoding of signals received at multiple DUs **105-c** for directional reception.

(35) The wireless communication system **100** may support operation on multiple cells or carriers, a feature which may be referred to as carrier aggregation (CA) or multi-carrier operation. A carrier may also be referred to as a component carrier (CC), a layer, a channel, etc. The terms “carrier,” “component carrier,” “cell,” and “channel” may be used interchangeably herein. A UE **115** may be configured with multiple downlink CCs and one or more uplink CCs for carrier aggregation. Carrier aggregation may be used with both FDD and TDD component carriers.

(36) FIG. 2 shows an example of a timeline **200** of operations that may be performed in a network that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The operations may be performed by a network access device **105-d** (e.g., an AN **105-a**, a CU **105-b**, a DU **105-c**, etc.) and a UE **115-a** that is served by the network access device **105**. In some examples, the serving network access device **105-d** may be a distributed network access device, and may be an example of aspects of one or more of the DUs **105-c** described with reference to FIG. 1. The UE **115-a** may be an example of aspects of one or more of the UEs **115** described with reference to FIG. 1.

(37) As shown in timeline **200**, the serving network access device **105-d** may broadcast a synchronization signal **205**. The synchronization signal **205** may be common (e.g., not cell-specific, not UE-specific, etc.) to a plurality of cells within a network, and may be broadcast from the plurality of cells (e.g., from a plurality of DUs) in a single frequency network (SFN) manner. The synchronization signal **205** need not include a cell identifier. In some examples, the synchronization signal **205** may be a periodic signal. In various examples, the synchronization signal **205** may have a relatively short duration or may be transmitted relatively infrequently. For example, the synchronization signal **205** may have a duration of one symbol and be transmitted once every ten seconds. In other examples, the synchronization signal **205** may be transmitted more frequently, such as once per radio frame. In some examples, the synchronization signal **205** may carry several bits of information, such as 4-6 bits of information. In some examples, the synchronization signal **205** may include system information request (e.g., system information block (SIB) request) configuration information. The system information request configuration information may, in some examples, include at least one of an indication of a SIB request bandwidth, an indication of a SIB request timing (e.g., slot/symbol timing), or network access barring information (e.g., an indication of times when UEs of particular types may not transmit a SIB request). In some examples, the synchronization signal **205** may be more dynamic, and may be broadcast on a synchronization channel with guard, for example.

(38) The UE **115-a** may receive the synchronization signal **205** and acquire a timing of the network based on the synchronization signal **205**. In response to acquiring the timing of the network, the UE **115-a** may transmit a pilot signal (or UE chirp) **210**. The pilot signal **210** may be concurrently receivable by the plurality of cells (e.g., a plurality of DUs) within the network. In some examples, the cells within a “zone” of cells may be synchronized so that the UE **115-a** does not need to transmit multiple pilot signals and the cells within the zone may all receive the same pilot signal. In some examples, the pilot signal **210** may include a spatial signature (e.g., a sounding reference signal (SRS)). A DU may in some cases have a large uplink spatial multiplexing capacity for receiving the SRS. In some examples, the pilot signal **210** may be transmitted in a SIB request occasion (or set of common resources) indicated by system information request configuration information received with the synchronization signal. In some examples, the pilot signal **210** may be transmitted with a pre-determined random sequence or a random sequence generated by the UE **115-a**, which random sequence may be usable by the network (e.g., a DU) to temporarily identify the UE **115-a** during initial acquisition.

(39) Following transmission of an instance of the pilot signal **210**, the UE **115-a** may listen for a transmission from the network (e.g., a transmission, from a DU, of on-demand system information for the UE **115-a**, an uplink allocation for the UE **115-a**, a power control message for the UE **115-a**, or a timing advance message for the UE **115-a**). In some examples, the UE **115-a** may listen for

transmissions during a listening window **215**. When the UE **115-a** does not receive a transmission during the listening window **215**, the UE **115-a** may transition a receiver of the UE **115-a** to a low power or OFF state until a next listening window **215**, which may conserve power.

(40) One or more network access devices **105** (e.g., ANs **105-a**, DUs **105-c**, etc.) may receive the pilot signal **210** and measure the pilot signal **210** for purposes of initial access to the network. A serving cell for the UE **115-a** may be selected by one or more of the receiving network access devices **105**, or by a CU **105-b** in communication with the receiving network access devices **105**, based at least in part on the measurements of the pilot signal **210**. For example, each of a number of receiving DUs **105-c** may measure the signal strength or power (P.sub.PS) of the pilot signal (PS) **210**, and a serving DU (or serving cell) for the UE **115-a** may be selected based on a function such as:

$$\text{serving cell} = \text{argmax}(P.\text{sub.PS.sub.i})$$

where P.sub.PS.sub.i is the measured power of a serving cell i, and where the serving cell selected for the UE **115-a** is the serving cell that receives the pilot signal **210** at a greatest power. Serving cell selection is therefore handled (at least primarily) on the network side, and the number of measurements performed by the UE **115-a**, or processes managed by the UE **115-a**, may be reduced.

(41) When the network has information to transmit to the UE **115-a**, indicated by data arrival **220**, the serving network access device **105-d** for the UE may transmit a unicast paging signal **225** to the UE **115-a**. In some examples, the unicast paging signal **225** may be transmitted with on-demand system information for the UE **115-a** (e.g., an on-demand SIB or MIB), an uplink allocation for the UE **115-a**, a power control message for the UE **115-a**, or a timing advance message for the UE **115-a**. In some examples, the network access device **105-d** may initiate communication with a plurality of UEs using a multicast paging signal. Following receipt of a paging signal (e.g., the unicast paging signal **225**), the UE **115-a** may in some examples increase the duration of its current listening window **215**, and in some examples may transmit a radio resource control (RRC) connection request **230** to its serving network access device **105-d**. In some cases, the serving network access device **105-d** may transmit additional connection setup information **235** to the UE **115-a**, or perform additional contention resolution procedures, following receipt of the connection request **230**.

(42) When the UE **115-a** has information to transmit to the network, the UE **115-a** may transmit a scheduling request (SR) with one or more instances of the pilot signal **210**. In response to receiving the pilot signal **210** or the scheduling request, the serving network access device **105-d** may transmit on-demand system information (e.g., an on-demand system information block (SIB) or master information block (MIB)) to the UE. The serving network access device **105-d** may also transmit an uplink allocation (e.g., an uplink grant) for the UE **115-a**, or may transmit a power control message or a timing advance message for the UE **115-a**. In some examples, the system information, uplink allocation, power control message, or timing advance message may be transmitted to the UE **115-a** in a same downlink transmission. In some examples, the uplink allocation may be spatially multiplexed.

(43) When system information is transmitted from a network access device **105** to a number of UEs **115** on-demand (e.g., when needed for an uplink or downlink transmission between the DU and one or more of the UEs), the network access device **105-d** may reduce or eliminate periodic broadcasts of system information, which may conserve power. On the UE side, a UE **115** may conserve power by not listening for system information broadcasts, and instead only listening for on-demand system information transmissions.

(44) In some examples of the timeline **200** shown in FIG. 2, different synchronization signals may be transmitted for different constellations (e.g., different groups of cells, nodes, or base stations of the network, or different groups of cells, nodes, or DUs belonging to different networks).

(45) In the timeline **200** of operations performed in FIG. 2, the UE **115-a** does not need to measure

signals received from its serving cell or neighboring cells and report the measurements to the network. Instead, the network measures a pilot signal transmitted by the UE **115-a** and makes mobility decisions for the UE **115-a**. This framework offloads at least some of the processing burden pertaining to UE mobility decisions from the UE **115-a** to the network, and may help to conserve both resources and power at the UE **115-a**. This framework may also help the network to save power by omitting the continuous transmission of reference signals for the UE **115-a** to measure.

(46) During initial access, a UE **115** may transmit a pilot signal using a common set of resources. After initial access, a UE **115** may in some cases be allocated a dedicated set of resources. After entering a RRC connected state with the network, a UE **115** may operate with a radio resource configuration associated with transmitting pilot signals using a common set of resources or a dedicated set of resources. In some examples, the UE **115** may select an RRC dedicated state when the UE **115** has been allocated a dedicated set of resources, and select a RRC common state when the UE **115** has not been allocated a dedicated set of resources.

(47) When operating in the RRC common state, the UE **115** may transmit a pilot signal on the common set of resources. When operating in the RRC dedicated state, the UE **115** may transmit a pilot signal on the dedicated set of resources. A pilot signal transmitted on the common set of resources may be measured by all of the cells (e.g., ANs **105-a**, DUs **105-c**, etc.) that receive the pilot signal, and measurement reports including the measurements may be transmitted to a CU **105-b** or shared with other cells for the purpose of making a mobility decision for the UE **115**. A pilot signal transmitted on the dedicated set of resources may be measured by a set of cells included in a monitoring set of cells for the UE **115**. For example, a CU **105-b** may initially determine a monitoring set of DUs **105-c** to include neighbors of a serving DU **105-c** for the UE **115** (e.g., based on measurements or operations and maintenance (O&M) information). In some examples, the network (e.g., a AN **105-a**, a CU **105-b**, etc.) may identify the cells of a monitoring set of cells for a UE based at least in part on measurements of at least one pilot signal transmitted by the UE, or a location of the serving cell for the UE **115**, or a combination thereof. The network may configure the set of monitoring cells to monitor a specific uplink reference signal from the UE **115**, and may report the measured results of the received uplink reference signal (e.g. to a CU **105-b**). The network may also update the monitoring set of cells upon UE mobility (e.g., upon a change in DUs **105-c** included in a neighbor set of DUs **105-c**).

(48) When a UE **115** operates in an RRC common state, a UE identity (e.g., a System Architecture Evolution (SAE) temporary mobile subscriber identity (S-TMSI)) alone may be maintained by the network for the UE **115**, and the common set of resources may be used for data transfer and pilot/keep alive signal transmission. In some examples, small data transmissions may be made to/from a UE **115** operating in an RRC common state, and the UE **115** may transition to the RRC dedicated state for larger data transmissions. A discontinuous reception (DRX) cycle or discontinuous transmission (DTX) cycle associated with an RRC common state may, in some examples, be several minutes or hours long. When a UE **115** operates in the RRC dedicated state, a set of dedicated resources and a radio network temporary identifier (RNTI) may be allocated to the UE **115**. The dedicated resources may be allocated by just one DU **105-c** (e.g., a serving DU **105-c**), and similar resources may be allocated to other UEs **115** by other DUs **105-c**. A DRX cycle or DTX cycle associated with an RRC dedicated state may, in some examples, may be relatively short (or up to the maximum duration dictated by service requirements). Regardless of whether a UE **115** operates with a radio resource configuration associated with transmission of pilot signals using a common or dedicated set of resources, the network may maintain a UE context for the UE **115** and consider the UE **115** to be in a RRC connected mode.

(49) The network access devices **105** of a monitoring set for a UE **115** may in some examples, transmit a measurement report for a pilot signal of the UE **115** based on a periodic measurement reporting criteria and/or an event-driven measurement reporting criteria. A periodic measurement

reporting criteria may indicate, for example, that a measurement report should be transmitted to a CU **105-b** for every pilot signal, for every nth pilot signal, or at periodic time intervals. An event-driven measurement reporting criteria may indicate, for example, that a measurement report should be transmitted upon the occurrence of one or more events, such as a determination that a signal strength or signal quality of a pilot signal no longer satisfies a threshold signal strength or threshold signal quality.

(50) In some examples, the serving network access device **105** for a UE **115** may transmit a keep alive signal **240** to the UE **115**. The keep alive signal **240** may be transmitted in response to receiving a pilot signal **210** from the UE **115**. When a pilot signal **210** is received by the serving network access device **105** using a common set of resources, the keep alive signal **240** may be transmitted to the UE **115** using the common set of resources. When a pilot signal **210** is received by the serving network access device **105** using a dedicated set of resources, the keep alive signal **240** may be transmitted to the UE **115** using the dedicated set of resources. In some examples, a keep alive signal **240** may carry power control information or timing advance information.

(51) FIG. 3 illustrates an example of a wireless communication system **300** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The wireless communication system **300** may include a number of zones (including, e.g., a first zone **305-a** (Zone 1), a second zone **305-b** (Zone 2), and a third zone **305-c** (Zone 3)). A number of UEs, including UE **115-b**, may move within or between the zones.

(52) As described with reference to FIG. 2, a zone may include multiple cells, and the cells within a zone may be synchronized (e.g., the cells may share the same timing). Wireless communication system **300** may include examples of both non-overlapping zones (e.g., the first zone **305-a** and the second zone **305-b**) and overlapping zones (e.g., the first zone **305-a** and the third zone **305-c**). In some examples, the first zone **305-a** and the second zone **305-b** may each include one or more macro cells, micro cells, or pico cells, and the third zone **305-c** may include one or more femto cells.

(53) By way of example, the UE **115-b** is shown to be located in the first zone **305-a**. If the UE **115-b** is operating with a radio resource configuration associated with transmitting pilot signals using a common set of resources, such as an RRC common state, the UE **115-b** may transmit a pilot signal using a common set of resources, as described with reference to FIG. 2. Cells (e.g., ANs **105-a**, DUs **105-c**, etc.) within the first zone **305-a** may monitor the common set of resources for a pilot signal from the UE **115-b**. If the UE **115-b** is operating with a radio resource configuration associated with transmitting pilot signals using a dedicated set of resource, such as an RRC dedicated state, the UE **115-b** may transmit a pilot signal using a dedicated set of resources, as described with reference to FIG. 2. Cells of a monitoring set of cells established for the UE **115-b** within the first zone **305-a** (e.g., a first cell **310-a**, a second cell **310-b**, and a third cell **310-c**) may monitor the dedicated set of resources for the pilot signal of the UE **115-b**.

(54) FIG. 4 illustrates an example of a wireless communication system **400** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The wireless communication system **400** may include a number of access networks, including, for example, a first access node **105-a-1** and a second access node **105-a-2**. In some examples, one or more of the access nodes **405** may define a zone, such as one of the zones **305** described with reference to FIG. 3. Each of the access nodes **405** may interface with a core network **130-a**, which may be an example of aspects of the core network **130** described with reference to FIG. 1. In some examples, the core network **130-a** may include a mobility management entity (MME) **410** or a serving gateway (SGW) (e.g., a MME or SGW for a next generation or 5G network).

(55) Each of the access nodes **405** may include a CU **105-b** and a number of DUs **105-c**. For example, the first access node **105-a-1** may include a CU **105-b-1**, a first DU **105-c-1**, a second DU **105-c-2**, and a third DU **105-c-3**. By way of example, a UE **115-c** is shown to communicate with the first DU **105-c-1**. Other UEs (not shown) may communicate with the first DU **105-c-1** or with

other DUs. The UE **115-c** may be handed over from one serving DU (e.g., the first DU **105-c-1**) to another serving DU as it moves within the wireless communication system **400**. The CU **105-b-1**, first DU **105-c-1**, second DU **105-c-2**, third DU **105-c-3**, and UE **115-c** may be examples of aspects of the CUs **105-b**, DUs **105-c**, or UEs **115** described with reference to FIGS. **1** through **3**. Communications between access nodes **405** (e.g., between CUs **105-b**) may in some examples be conducted over a X2 interface.

(56) Each CU **105-b** within the wireless communication system **400** (including the CU **105-b-1**) may terminate a connection to the core network **130-a** for all of the DUs within an access network (e.g., via a S1-MME interface and a S1-U (user) interface). For example, the CU **105-b-1** may terminate a connection to the core network **130-a** for the first DU **105-c-1**, the second DU **105-c-2**, and the third DU **105-c-3**. The CU **105-b-1** may also coordinate actions between or including multiple DUs. For example, the CU **105-b-1** may coordinate intra-access network handovers of a UE **115** from one DU **105-c** to another DU **105-c**. The CU **105-b-1** may also coordinate RRC layer and user (U)-plane PDCP layer communications for the first access node **105-a-1**.

(57) Each DU **105-c** within the wireless communication system **400** may serve traffic between a set of UEs **115** for which the DU **105-c** operates as a serving node and a CU **105-b** with which the DU **105-c** is associated. For example, the first DU **105-c-1** may serve traffic between a set of UEs **115**, including the UE **115-c**, and the CU **105-b-1**. The first DU **105-c-1** may also monitor for pilot signals received over a common set of resources (e.g., from UEs operating in a RRC common state) and dedicated sets of resources (e.g., from UEs operating in a RRC dedicated state). The pilot signals may be measured and used by the first DU **105-c-1**, another DU, or the CU **105-b-1** to make UE mobility decisions (e.g., mobility decisions for the UE **115-c**). The first DU **105-c-1** may also perform PHY layer processing (e.g., the reception and measurement of pilot signals, and the transmission of measurement reports to the CU **105-b-1**) and control/user (C/U) plane processing below the PDCP layer.

(58) In some examples, the functions of an access node **405** may be split between a CU **105-b** and DUs **105-c** as shown in FIG. **4**. In other examples, the functions performed by a CU **105-b** may be moved to one or more DUs **105-c**, and the DUs **105-c** may communicate with each other and with the core network **130-a**.

(59) FIG. **5** illustrates a diagram **500** showing examples for implementing a communications protocol stack that supports uplink-based mobility, in accordance with various aspects of the present disclosure. For example, diagram **500** illustrates a communications protocol stack including an RRC layer **510**, a PDCP layer **515**, an RLC layer **520**, a MAC layer **525**, and a PHY layer **530**. In various examples the layers of a protocol stack may be implemented as separate modules of software, portions of a processor or ASIC, portions of non-collocated devices connected by a communications link, or various combinations thereof. Collocated and non-collocated implementations may be used, for example, in a protocol stack for a network access device **105** or a UE **115**.

(60) A first option **505-a** shows a split implementation of a protocol stack, in which implementation of the protocol stack is split between a centralized network access device **105** (e.g., CU **105-b-2**) and a distributed network access device **105** (e.g., DU **105-c-4**). In the first option **505-a**, an RRC layer **510** and a PDCP layer **515** may be implemented by the CU **105-b-2**, and an RLC layer **520**, a MAC layer **525**, and a PHY layer **530** may be implemented by the DU **105-c-4**. In various examples the CU **105-b-2** and the DU **105-c-4** may be collocated or non-collocated. The first option **505-a** may be useful in a macro cell, micro cell, or pico cell deployment.

(61) A second option **505-b** shows a unified implementation of a protocol stack, in which the protocol stack is implemented in a single network access device **105** (e.g., AN **105-a-3**). In the second option **505-b**, the RRC layer **510**, the PDCP layer **515**, the RLC layer **520**, the MAC layer **525**, and the PHY layer **530** may each be implemented by the AN **105-a-3**. The second option **505-b** may be useful in a femto cell deployment.

(62) Regardless of whether a network access device implements part or all of a protocol stack, a UE **115-d** may implement an entire protocol stack (e.g., the RRC layer **510**, the PDCP layer **515**, the RLC layer **520**, the MAC layer **525**, and the PHY layer **530**).

(63) FIGS. **6** and **7** provide examples of UE, DU, and CU behaviors when a UE **115** operates in a RRC common state.

(64) FIG. **6** shows an example of a communication flow **600** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. As shown, communication flow **600** includes communication between a UE **115-e**, a first DU **105-c-5**, a second DU **105-c-6**, and a CU **105-b-3**. The UE **115-e** may be an example of aspects of the UEs **115** described with reference to FIGS. **1** through **5**; the first DU **105-c-5** and the second DU **105-c-6** may be examples of aspects of the DUs **105-c** described with reference to FIGS. **1** through **5**; and the CU **105-b-3** may be an example of aspects of the CUs **105-b** (e.g., centralized network access devices **105**) described with reference to FIGS. **1** through **5**. Each of the first DU **105-c-5** and the second DU **105-c-6** may operate in a common zone or overlapping zones, and may be associated with the CU **105-b-3**. The communication flow **600** may commence with the UE **115-e** operating with a radio resource configuration associated with transmitting pilot signals using a common set of resources (e.g., an RRC common state), and with the first DU **105-c-5** operating as a serving DU for the UE **115-e**.

(65) Because the UE **115-e** is operating with a radio resource configuration associated with transmitting pilot signals using a common set of resources, each of the first DU **105-c-5** and the second DU **105-c-6** (and all other DUs, or all other DUs within the zone or overlapping of zones in which the UE **115-e** operates) may monitor for pilot signals transmitted by the UE **115-e**. At **605**, the UE **115-e** may transmit a pilot signal using a common set of resources while within the coverage area of the first DU **105-c-5** but not within the coverage area of the second DU **105-c-6**. In some examples, the pilot signal may be configured according to an RRC_COMMON pilot signal configuration. In some examples, the UE **115-e** may receive an allocation of the common set of resources (including, for example, the RRC_COMMON pilot signal configuration) in a synchronization signal, in system information (e.g., a SIB, etc.), in a unicast message (e.g., on-demand system information by way of a MAC control element, an RRC message, a PHY message, a physical downlink control channel (PDCCH) command, etc.), or a combination thereof. In some examples, the UE **115-e** may identify the allocation of the common set of resources based at least in part on a type of the UE **115-e** (e.g., different common sets of resources may be allocated for different types of UEs). In some examples, the pilot signal may identify the UE **115-e** (e.g., the pilot signal may include an identifier of the UE **115-e**).

(66) The pilot signal transmitted by the UE **115-e** at **605** may be received and measured by the first DU **105-c-5**. In some examples, the first DU **105-c-5** may measure a signal strength or signal quality (e.g., signal-to-noise ratio (SNR), signal-to-interference-plus-noise ratio (SINR), etc.) of the pilot signal. The first DU **105-c-5** may forward a measurement report including one or more measurements of the pilot signal (e.g., a measurement report including the signal strength or signal quality of the pilot signal) to the CU **105-b-3** at **610**.

(67) The CU **105-b-3** may determine, based on the measurement report received from the first DU **105-c-5** at **610**, that the first DU **105-c-5** should remain the serving DU for the UE **115-e**.

(68) At **615**, the first DU **105-c-5** may transmit a keep alive signal to the UE **115-e** on a common set of resources (e.g., on a same frequency band, a same component carrier, a same set of subcarrier(s), a same set of resource block(s), and/or a same channel as the common set of resources on which the pilot signal is transmitted at **605**). In some examples, transmitting the keep alive signal may be based at least in part on the pilot signal transmitted at **605** (e.g., the keep alive signal may be transmitted to the UE **115-e** in response to the first DU **105-c-5** receiving the pilot signal). In some examples, the keep alive signal transmitted at **615** may be transmitted before the measurement report is transmitted at **610**.

(69) At **620**, the UE **115-e** may move into the coverage area of the second DU **105-c-6**, while

remaining in the coverage area of the first DU **105-c-5**.

(70) At **625**, the UE **115-e** may transmit another pilot signal on the common set of resources (e.g., on a same frequency band, a same component carrier, a same set of subcarrier(s), a same set of resource block(s), and/or a same channel as the common set of resources on which the pilot signal is transmitted at **605**). The pilot signal transmitted by the UE **115-e** at **625** may be received and measured by both the first DU **105-c-5** and the second DU **105-c-6**. The first DU **105-c-5** may forward a measurement report to the CU **105-b-3** at **630**, and the second DU **105-c-6** may forward a measurement report to the CU **105-b-3** at **635**.

(71) The CU **105-b-3** may determine, based on the measurement reports received from the first DU **105-c-5** and the second DU **105-c-6** at **625** and **630**, that the first DU **105-c-5** should remain the serving DU for the UE **115-e**. In other examples, the CU **105-b-3** may determine to initiate a handover of the UE **115-e** from the first DU **105-c-5** to the second DU **105-c-6** (or to another DU).

(72) At **640**, the first DU **105-c-5** may transmit another keep alive signal to the UE **115-e** using a common set of resources (e.g., on a same frequency band, a same component carrier, a same set of subcarrier(s), a same set of resource block(s), and/or a same channel as the common set of resources on which the pilot signal is transmitted at **605**). In some examples, transmitting the keep alive signal may be based at least in part on the pilot signal transmitted at **625**. In some examples, the keep alive signal transmitted at **640** may be transmitted before the measurement report is transmitted at **630** or **635**. The second DU **105-c-6** may not transmit a keep alive signal to the UE **115-e** because the second DU **105-c-6** is not the serving DU for the UE **115-e**.

(73) FIG. 7 shows an example of a communication flow **700** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. As shown, communication flow **700** includes communication between a UE **115-f**, a first DU **105-c-7**, a second DU **105-c-8**, and a CU **105-b-4**. The UE **115-f** may be an example of aspects of the UEs **115** described with reference to FIGS. 1 through 6; the first DU **105-c-7** and the second DU **105-c-8** may be examples of aspects of the DUs **105-c** described with reference to FIGS. 1 through 6; and the CU **105-b-4** may be an example of aspects of the CUs **105-b** described with reference to FIGS. 1 through 6. Each of the first DU **105-c-7** and the second DU **105-c-8** may operate in a common zone or overlapping zones, and may be associated with the CU **105-b-4**. The communication flow **700** may commence with the UE **115-f** operating with a radio resource configuration associated with transmitting pilot signals using a common set of resources (e.g., an RRC common state), and with the first DU **105-c-7** operating as a serving DU for the UE **115-f**.

(74) Because the UE **115-f** is operating with a configuration associated with transmitting pilot signals using a common set of resources, each of the first DU **105-c-7** and the second DU **105-c-8** (and all other DUs, or all other DUs within the zone in which the UE **115-f** operates) may monitor for pilot signals transmitted by the UE **115-f**. At **705**, the UE **115-f** may transmit a pilot signal using a common set of resources while within the coverage area of the first DU **105-c-7** and the second DU **105-c-8**. In some examples, the pilot signal may be configured according to a RRC_COMMON pilot signal configuration. In some examples, the UE **115-f** may receive an allocation of the common set of resources (including, for example, the RRC_COMMON pilot signal configuration) in a synchronization signal, in system information (e.g., a SIB), in a unicast message (e.g., on-demand system information by way of a MAC control element, an RRC message, a PHY message, a PDCCH command, etc.), or a combination thereof. In some examples, the UE **115-f** may identify the allocation of the common set of resources based at least in part on a type of the UE **115-f** (e.g., different common sets of resources may be allocated for different types of UEs). In some examples, the pilot signal may identify the UE **115-f** (e.g., the pilot signal may include an identifier of the UE **115-f**).

(75) The pilot signal transmitted by the UE **115-f** at **705** may be received and measured by both the first DU **105-c-7** and the second DU **105-c-8**. In some examples, each of the first DU **105-c-7** and the second DU **105-c-8** may measure a signal strength or signal quality of the pilot signal. The first

DU **105-c-7** may forward a measurement report including one or more measurements of the pilot signal (e.g., a measurement report including the signal strength or signal quality of the pilot signal) to the CU **105-b-4** at **710**. The second DU **105-c-8** may forward a measurement report including one or more measurements of the pilot signal (e.g., a measurement report including the signal strength or signal quality of the pilot signal) to the CU **105-b-4** at **715**.

(76) The CU **105-b-4** may determine at **720**, based on the measurement reports received from the first DU **105-c-7** and the second DU **105-c-8**, that the second DU **105-c-8** would be a preferred serving DU for the UE **115-f**, and may initiate a serving cell change procedure (e.g., a handover of the UE **115-f** from the first DU **105-c-7** to the second DU **105-c-8**).

(77) At **725**, the CU **105-b-4** may transmit, to the second DU **105-c-8**, a request for the second DU **105-c-8** to operate as a serving DU (or cell) for the UE **115-f**, which UE **115-f** is operating in a RRC common state. At **730**, the second DU **105-c-8** may acknowledge receipt of the request transmitted at **725**.

(78) At **735**, the second DU **105-c-8** may transmit a keep alive signal to the UE **115-f** on common resources (e.g., on a same frequency band, a same component carrier, a same set of subcarrier(s), a same set of resource block(s), and/or a same channel as the common set of resources on which the pilot signal is transmitted at **705**). In some examples, transmitting the keep alive signal may be based at least in part on the pilot signal transmitted at **705** (e.g., the keep alive signal may be transmitted to the UE **115-f** in response to the first DU **105-c-7** receiving and measuring the pilot signal and transmitting a measurement report to the CU **105-b-4**, and in response to the CU **105-b-4** identifying the second DU **105-c-8** as a serving DU for the UE **115-f**). In some examples, the first DU **105-c-7** may refrain from transmitting a keep alive signal to the UE **115-f** after receipt of the pilot signal at **705**, because measurement of the pilot signal by the first DU **105-c-7** indicates a strength of the pilot signal is below a threshold (e.g., too weak).

(79) At **740**, the CU **105-b-4** may transmit, to the first DU **105-c-7**, a request for the first DU **105-c-7** to release any serving DU resources allocated for the UE **115-f**. At **745**, the first DU **105-c-7** may acknowledge receipt of the request transmitted at **740**.

(80) In the communication flow **700**, the handover of the UE **115-f** from the first DU **105-c-7** to the second DU **105-c-8** may be transparent to the UE **115-f**. That is, the network side **750** (e.g., the CU **105-b-4**, the first DU **105-c-7**, and second DU **105-c-8**) may initiate and complete the handover without involving the UE **115-f**, and may signal completion of the handover by transmitting a keep alive signal to the UE **115-f** from the second DU **105-c-8** instead of the first DU **105-c-7**. The keep alive signal transmitted by the second DU **105-c-8** (or the first DU **105-c-7**) may or may not identify the second DU **105-c-8** (or the first DU **105-c-7**) to the UE **115-f**.

(81) In an alternative examples of the communication flow **700**, the second DU **105-c-8** may transmit a keep alive signal to the UE **115-f** prior to receiving the request at **725** (i.e., prior to receiving the request to operate as a serving DU (or cell) for the UE **115-f**). More generally, a DU **105-c** (including, for example, the first DU **105-c-7** and/or the second DU **105-c-4**) may transmit a keep alive signal to the UE **115-f**, regardless of whether the DU **105-c** is the current serving DU for the UE **115-f**. In these examples, the CU **105-b-4** may configure DUs **105-c** to transmit keep alive signals to UEs **115** in an event driven manner. For example, a DU **105-c** may be configured to transmit a keep alive signal to a UE **115** upon: 1) receiving a pilot signal from the UE **115** using a common set of resources, and 2) determining that the pilot signal satisfies one or more thresholds. The threshold(s) may include a received signal received power (RSRP) threshold, a received signal received quality (RSRQ) threshold, etc. Upon a DU **105-c** determining that an RSRP or RSRQ of the pilot signal satisfies (e.g., exceeds) a respective RSRP threshold or RSRQ threshold, the DU **105-c** may transmit a keep alive signal to the UE **115** using the common set of resources.

(82) Configuring only serving DUs **105-c** to transmit keep alive signals guarantees that a UE **115** receives a keep alive signal from only one DU **105-c**. However, such a configuration incurs signaling overhead and can delay keep alive signal transmission (which may cause a UE **115** to stay

awake for a longer period of time, and thus increase UE power consumption) or necessitate tighter backhaul requirements (e.g., a lower latency backhaul). Configuring all DUs **105-c** to transmit keep alive signals to UEs **115**, upon certain criteria being met, can mitigate the issues associated with transmitting keep alive signals only from serving DUs **105-c**.

(83) FIGS. **8** and **9** provide examples of UE, DU, and CU behaviors when a UE **115** operates in a radio resource configuration associated with transmitting pilot signals using a dedicated set of resources.

(84) FIG. **8** shows an example of a communication flow **800** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. As shown, communication flow **800** includes communication between a UE **115-g**, a first DU **105-c-9**, a second DU **105-c-10**, and a CU **105-b-5**. The UE **115-g** may be an example of aspects of the UEs **115** described with reference to FIGS. **1** through **7**; the first DU **105-c-9** and the second DU **105-c-10** may be examples of aspects of the DUs **105-c** described with reference to FIGS. **1** through **7**; and the CU **105-b-5** may be an example of aspects of the CUs **105-b** described with reference to FIGS. **1** through **7**. Each of the first DU **105-c-9** and the second DU **105-c-10** may operate in a common zone or overlapping zones, and may be associated with the CU **105-b-5**. The communication flow **800** may commence with the UE **115-g** operating with a radio resource configuration associated with transmitting pilot symbols using a dedicated set of resources (e.g., an RRC dedicated state), and with the first DU **105-c-9** operating as a serving DU (or serving cell) for the UE **115-g**.

(85) Because the UE **115-g** is operating with a radio resource configuration associated with transmitting pilot signals using a dedicated set of resources, only DUs that the network-side **850** (e.g., the CU **105-b-5**) has identified as members of a monitoring set (e.g., a monitoring set of cells, network access devices **105**, DUs **105-c**, etc.) may monitor for pilot signals transmitted by the UE **115-g**, and DUs **105-c** that are members of the monitoring set may monitor a dedicated set of resources for pilot signals transmitted by the UE **115-g**. The communication flow **800** may commence with the first DU **105-c-9** being a member of the monitoring set of DUs for the UE **115-g**, and second DU **105-c-10** not being a member of the monitoring set. In some examples, the DUs of the monitoring set of DUs for the UE **115-g** may be identified based at least in part on measurements of at least one pilot signal transmitted by the UE **115-g**, or a location of the identified serving DU (or cell) for the UE **115-g**, or a combination thereof.

(86) At **805**, the UE **115-g** may transmit a pilot signal using a dedicated set of resources while within the coverage area of the first DU **105-c-9** and the second DU **105-c-10**. In some examples, the pilot signal may be configured according to a RRC_DEDICATED pilot signal configuration. In some examples, the UE **115-g** may receive an allocation of the dedicated set of resources (including, for example, the RRC_DEDICATED pilot signal configuration) in a unicast message (e.g., on-demand system information by way of a MAC control element, an RRC message, a PHY message, a PDCCH command, etc.), or in a timing of the unicast message, or a combination thereof. In some examples, the pilot signal may identify the UE **115-g** (e.g., explicitly, because the pilot signal includes an identifier of the UE **115-g**, or implicitly, because the pilot signal is transmitted on a set of resources dedicated to the UE **115-g**).

(87) The pilot signal transmitted by the UE **115-g** at **805** may be received and measured by the first DU **105-c-9**. In some examples, the first DU **105-c-9** may measure a signal strength or signal quality of the pilot signal. In some examples, the first DU **105-c-9** may additionally determine whether the signal strength or signal quality of the pilot signal satisfies a threshold signal strength or signal quality. The first DU **105-c-9** may forward a measurement report including one or more measurements of the pilot signal (e.g., a measurement report including the signal strength, the signal quality, an indication of whether the signal strength satisfies the threshold signal strength, or an indication of whether the signal quality satisfies the threshold signal quality) to the CU **105-b-3** at **810**. The pilot signal transmitted by the UE **115-g** at **805** may also be received by the second DU **105-c-10**, but because the second DU **105-c-10** is not a member of the monitoring set for the UE

115-g, the second DU **105-c-10** may ignore the pilot signal.

(88) The CU **105-b-5** may determine, based on the measurement report received from the first DU **105-c-9** at **810**, that the UE **115-g** has moved and/or may be better served by a different serving DU. At **815**, and based on its determination regarding the pilot signal transmitted by the UE **115-g** (or the assessment of the pilot signal made by the first DU **105-c-9**), the CU **105-b-5** may update the monitoring set of DUs for the UE **115-g**. For example, the CU **105-b-5** may add the second DU **105-c-10** to the monitoring set of DUs for the UE **115-g**. The second DU **105-c-10** may be a neighbor of the first DU **105-c-9**.

(89) At **820**, the CU **105-b-5** may transmit, to the second DU **105-c-10**, an indication that the second DU **105-c-10** is a member of the monitoring set of DUs for the UE **115-g**. The indication may include, for example, a measurement configuration (e.g., an indication of a dedicated set of resources on which the UE **115-g** may transmit pilot signals). At **825**, the second DU **105-c-10** may acknowledge receipt of the indication transmitted at **820**.

(90) At **830**, the first DU **105-c-9** may transmit a keep alive signal to the UE **115-g** on dedicated resources (e.g., on a same frequency band, a same component carrier, a same set of subcarrier(s), a same set of resource block(s), and/or a same channel as the dedicated set of resources on which the pilot signal is transmitted at **805**). In some examples, transmitting the keep alive signal may be based at least in part on the pilot signal transmitted at **805** (e.g., the keep alive signal may be transmitted to the UE **115-g** in response to the first DU **105-c-9** receiving the pilot signal). In some examples, the keep alive signal transmitted at **830** may be transmitted before the measurement report is transmitted at **810**.

(91) At **835**, the UE **115-g** may transmit another pilot signal on the dedicated set of resources (e.g., on a same frequency band, a same component carrier, a same set of subcarrier(s), a same set of resource block(s), and/or a same channel as the dedicated set of resources on which the pilot signal is transmitted at **805**). The pilot signal transmitted by the UE **115-g** at **835** may be received and measured by both the first DU **105-c-9** and the second DU **105-c-10**. The first DU **105-c-9** may forward a measurement report to the CU **105-b-5** at **840**, and the second DU **105-c-10** may forward a measurement report to the CU **105-b-5** at **845**.

(92) The CU **105-b-5** may determine, based on the measurement reports received from the first DU **105-c-9** and the second DU **105-c-10** at **840** and **845**, that the first DU **105-c-9** should remain the serving DU for the UE **115-g**. In other examples, the CU **105-b-5** may determine to initiate a handover of the UE **115-g** from the first DU **105-c-9** to the second DU **105-c-10** (or to another DU **105-c**).

(93) In some examples of the communication flow **800**, a DU that is a member of the monitoring set of DUs for the UE **115-g** may only transmit a measurement report to the CU **105-b-5** under certain conditions. For example, a DU may transmit a measurement report based at least in part on a periodic measurement reporting criteria and/or an event-driven measurement reporting criteria. A periodic measurement reporting criteria may indicate, for example, that a measurement report should be transmitted to the CU **105-b-5** for every pilot signal, for every nth pilot signal, or at periodic time intervals. An event-driven measurement reporting criteria may indicate, for example, that a measurement report should be transmitted upon the occurrence of one or more events, such as a determination that a signal strength or signal quality of a pilot signal no longer satisfies a threshold signal strength or threshold signal quality. In some examples, a periodic measurement reporting criteria or event-driven measurement reporting criteria may be included in an indication such as the indication transmitted at **820**.

(94) The communication flow **800** illustrates an addition of a radio to the monitoring set of DUs for the UE **115-g**. A DU may also be removed from the monitoring set of DUs for the UE **115-g**. Removal of a DU from the monitoring set of DUs may also be based on the measurement of one or more pilot signals transmitted by the UE **115-g**, the locations of DUs, etc. In some examples, an update to the monitoring set of DUs for the UE **115-g** may be initiated in combination with a

change in the serving DU for the UE **115-g**.

(95) FIG. **9** shows an example of a communication flow **900** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. As shown, communication flow **900** includes communication between a UE **115-h**, a first DU **105-c-11**, a second DU **105-c-12**, and a CU **105-b-6**. The UE **115-h** may be an example of aspects of the UEs **115** described with reference to FIGS. **1** through **8**; the first DU **105-c-11** and the second DU **105-c-12** may be examples of aspects of the DUs **105-c** described with reference to FIGS. **1** through **8**; and the CU **105-b-6** may be an example of aspects of the CUs **105-b** described with reference to FIGS. **1** through **8**. Each of the first DU **105-c-11** and the second DU **105-c-12** may operate in a common zone or overlapping zones, and may be associated with the CU **105-b-6**. The communication flow **900** may commence with the UE **115-h** operating with a radio resource configuration associated with transmitting pilot signals using a dedicated set of resources (e.g., an RRC dedicated state), and with the first DU **105-c-11** operating as a serving DU (or serving cell) for the UE **115-h**.

(96) Because the UE **115-h** is operating with a radio resource configuration associated with transmitting pilot signals using a dedicated set of resources, only DUs that the network **960** (e.g., the CU **105-b-6**) has identified as members of a monitoring set (e.g., a monitoring of cells or network access devices or DUs) may monitor for pilot signals transmitted by the UE **115-h**, and the DUs that are members of the monitoring set may monitor a dedicated set of resources for pilot signals transmitted by the UE **115-h**. The communication flow **900** may commence with the first DU **105-c-11** and the second DU **105-c-12** being members of the monitoring set of DUs for the UE **115-h**. In some examples, the DUs of the monitoring set of DUs for the UE **115-h** may be identified based at least in part on measurements of at least one pilot signal transmitted by the UE **115-h**, or a location of the identified serving DU (or cell) for the UE **115-h**, or a combination thereof.

(97) At **905**, the UE **115-h** may transmit a pilot signal using a dedicated set of resources while within the coverage area of the first DU **105-c-11** and the second DU **105-c-12**. In some examples, the pilot signal may be configured according to a RRC_DEDICATED pilot signal configuration. In some examples, the UE **115-h** may receive an allocation of the dedicated set of resources (including, for example, the RRC_DEDICATED pilot signal configuration) in a unicast message (e.g., on-demand system information by way of a MAC control element, an RRC message, a PHY message, a PDCCH command, etc.), or a timing of the unicast message, or a combination thereof. In some examples, the pilot signal may identify the UE **115-h** (e.g., explicitly, because the pilot signal includes an identifier of the UE **115-h**, or implicitly, because the pilot signal is transmitted on a set of resources dedicated to the UE **115-h**).

(98) The pilot signal transmitted by the UE **115-h** at **905** may be received and measured by both the first DU **105-c-11** and the second DU **105-c-12**. In some examples, each of the first DU **105-c-11** and the second DU **105-c-12** may measure a signal strength or signal quality of the pilot signal. In some examples, the first DU **105-c-11** or the second DU **105-c-12** may additionally determine whether the signal strength or signal quality of the pilot signal satisfies a threshold signal strength or signal quality. The first DU **105-c-11** may forward a measurement report including one or more measurements of the pilot signal (e.g., a measurement report including the signal strength, the signal quality, an indication of whether the signal strength satisfies the threshold signal strength, or an indication of whether the signal quality satisfies the threshold signal quality) to the CU **105-b-6** at **910**, and the second DU **105-c-12** may forward a measurement report to the CU **105-b-6** at **915**.

(99) The CU **105-b-6** may determine at **920**, based on the measurement reports received from the first DU **105-c-11** and the second DU **105-c-12**, that the second DU **105-c-12** would be a preferred serving DU (or serving cell) for the UE **115-h**, and may initiate a serving cell change procedure (e.g., a handover of the UE **115-h** from the first DU **105-c-11** to the second DU **105-c-12**).

(100) At **925**, the CU **105-b-6** may transmit, to the second DU **105-c-12** (e.g., the target serving cell), a request for the second DU **105-c-12** to operate as a serving DU for the UE **115-h**, which UE **115-h** is operating in a RRC dedicated state. At **930**, the second DU **105-c-12** may acknowledge the

request transmitted at **925**.

(101) At **935**, the CU **105-b-6** may transmit, to the first DU **105-c-11** (e.g., the source serving cell), a reconfiguration message for the UE **115-h**. The RRC reconfiguration message may identify a dedicated set of resources to be used by the UE **115-h** after a handover of the UE **115-h** to the second DU **105-c-12**. In various examples the reconfiguration message may include an RRC message, a MAC CE, a PHY message a PDCCH command, or a combination thereof. The first DU **105-c-11** may forward the RRC reconfiguration message to the UE **115-h** (e.g., in a handover command), and thereby trigger a handover procedure at the UE **115-h**. The UE **115-h** may then perform a handover procedure according to the handover command and/or RRC reconfiguration message.

(102) Upon completing the handover procedure, the UE **115-h** may transmit a reconfiguration complete message to the second DU **105-c-12** at **940**, and the second DU **105-c-12** may forward the reconfiguration complete message to the CU **105-b-6** at **945**.

(103) At **950**, the CU **105-b-6** may transmit, to the first DU **105-c-11**, a request for the first DU **105-c-11** to release any serving DU resources allocated for the UE **115-h**. At **955**, the first DU **105-c-11** may acknowledge receipt of the request transmitted at **950**.

(104) In the communication flow **900**, the handover of the UE **115-h** from the first DU **105-c-11** to the second DU **105-c-12** is not transparent to the UE **115-h**. That is, the network side (e.g., the CU **105-b-6**, the first DU **105-c-11**, and/or the second DU **105-c-12**) may initiate and complete the handover with involvement of the UE **115-h**. However, compared to a handover of a UE in a LTE/LTE-A network, for example, the handover of the UE **115-h** from the first DU **105-c-11** to the second DU **105-c-12** does not require the UE **115-h** to transmit a measurement report based on signals received from its serving cell or neighboring cells, and does not require the UE **115-h** to transmit an LTE/LTE-A Handover Message 1, 2, or 3.

(105) Although not shown in FIG. **9**, the serving DU for the UE **115-h** may respond to pilot signals transmitted by the UE **115-h** with keep alive signals, as described, for example, with reference to FIG. **8**.

(106) In a variation of the communication flow **900**, the CU **105-b-6** may transmit the reconfiguration message to the second DU **105-c-12** (e.g., the target serving cell), and the second DU **105-c-12** may forward the reconfiguration message to the UE **115-h** (e.g., in a handover command).

(107) FIG. **10** shows a block diagram **1000** of an apparatus **1015** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The apparatus **1015** may be an example of aspects of one or more of the UEs **115** described with reference to FIGS. **1** through **9**. The apparatus **1015** may also be or include a processor. The apparatus **1015** may include a receiver **1010**, a UE wireless communication manager **1020-a**, and a transmitter **1030**. Each of these components may be in communication with each other.

(108) The components of the apparatus **1015** may, individually or collectively, be implemented using one or more application-specific integrated circuits (ASICs) adapted to perform some or all of the applicable functions in hardware. Alternatively, the functions may be performed by one or more other processing units (or cores), on one or more integrated circuits. In some other examples, other types of integrated circuits may be used (e.g., Structured/Platform ASICs, Field Programmable Gate Arrays (FPGAs), a System-on-Chip (SoC), and/or other types of Semi-Custom ICs), which may be programmed in any manner known in the art. The functions of each component may also be implemented, in whole or in part, with instructions embodied in a memory, formatted to be executed by one or more general or application-specific processors.

(109) In some examples, the receiver **1010** may include at least one radio frequency (RF) receiver, such as at least one RF receiver operable to receive transmissions over one or more radio frequency spectrum bands. In some examples, the receiver **1010** may include an array of antennas. In some examples, the one or more radio frequency spectrum bands may be used for LTE/LTE-A or 5G

communications, as described, for example, with reference to FIGS. 1 through 9. The receiver **1010** may be used to receive various types of data or control signals (e.g., transmissions) over one or more communication links (or channels) of a wireless communication system, such as one or more communication links (or channels) of the wireless communication system **100**, **300**, or **400** described with reference to FIG. 1, 3, or 4. In some examples, the receiver **1010** may also or alternatively include one or more wired receivers.

(110) In some examples, the transmitter **1030** may include at least one RF transmitter, such as at least one RF transmitter operable to transmit over one or more radio frequency spectrum bands. In some examples, the transmitter **1030** may include an array of antennas. In some examples, the one or more radio frequency spectrum bands may be used for LTE/LTE-A or 5G communications, as described, for example, with reference to FIGS. 1 through 9. The transmitter **1030** may be used to transmit various types of data or control signals (e.g., transmissions) over one or more communication links (or channels) of a wireless communication system, such as one or more communication links (or channels) of the wireless communication system **100**, **300**, or **400** described with reference to FIG. 1, 3, or 4. In some examples, the transmitter **1030** may also or alternatively include one or more wired transmitters.

(111) In some examples, the UE wireless communication manager **1020-a** may be used to manage one or more aspects of wireless communication for the apparatus **1015**. In some examples, part of the UE wireless communication manager **1020-a** may be incorporated into or shared with the receiver **1010** or the transmitter **1030**. In some examples, the UE wireless communication manager **1020-a** may be an example of aspects of the UE wireless communication manager **1020** described with reference to FIG. 1. The UE wireless communication manager **1020-a** may include a radio resource configuration identifier **1035**, a resource selector **1040**, or a pilot signal transmission manager **1045**.

(112) In some examples, the radio resource configuration identifier **1035** may be used to identify, while a UE including the apparatus **1015** is in a connected mode with a network, a radio resource configuration of the UE. In some examples the radio resource configuration identifier **1035** may identify if a UE is operating in an RRC dedicated state or an RRC common state.

(113) In some examples, the resource selector **1040** may be used to select a dedicated set of resources or a common set of resources for the UE based at least in part on the identified radio resource configuration. In some examples, the dedicated set of resources may be associated with a more granular periodicity than the common set of resources.

(114) In some examples, the pilot signal transmission manager **1045** may be used to transmit (e.g., in cooperation with the transmitter **1030**) a pilot signal to the network using the selected set of resources. In some examples, the pilot signal may be transmitted periodically based at least in part on a DTX configuration or a DRX configuration of the UE.

(115) FIG. 11 shows a block diagram **1100** of a UE wireless communication manager **1020-b** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The UE wireless communication manager **1020-b** may be an example of aspects of UE wireless communication managers **1020** described with reference to FIG. 1 or 10.

(116) The components of the UE wireless communication manager **1020-b** may, individually or collectively, be implemented using one or more ASICs adapted to perform some or all of the applicable functions in hardware. Alternatively, the functions may be performed by one or more other processing units (or cores), on one or more integrated circuits. In some other examples, other types of integrated circuits may be used (e.g., Structured/Platform ASICs, FPGAs, a SoC, and/or other types of Semi-Custom ICs), which may be programmed in any manner known in the art. The functions of each component may also be implemented, in whole or in part, with instructions embodied in a memory, formatted to be executed by one or more general or application-specific processors.

(117) In some examples, the UE wireless communication manager **1020-b** may be used to manage

one or more aspects of wireless communication for a UE or apparatus, such as one of the UEs **115** described with reference to FIGS. **1** through **9**, or apparatus **1015** described with reference to FIG. **10**. In some examples, part of the UE wireless communication manager **1020-b** may be incorporated into or shared with a receiver or a transmitter (e.g., a receiver **1010** or a transmitter **1030** described with reference to FIG. **10**). In some examples, the UE wireless communication manager **1020-b** may include a common resource manager **1105**, a dedicated resource manager **1110**, a radio resource configuration identifier **1035-a**, a resource selector **1040-a**, a zone identifier **1115**, a pilot signal transmission manager **1045-a**, a pilot signal configurator **1120**, a keep alive signal processor **1125**, or a serving cell identifier **1130**.

(118) In some examples, the common resource manager **1105** may be used to receive (e.g., in cooperation with a receiver) an allocation of a common set of resources. In some examples, the allocation of the common set of resources may be received in at least one of a synchronization signal, system information (e.g., a SIB), a unicast message (e.g., on-demand system information by way of a MAC control element, an RRC message, a PHY message, a PDCCH command, etc.), or a combination thereof. In some examples, the allocation of the common set of resources may be identified based at least in part on a type of a UE in which the UE wireless communication manager **1020-b** is included.

(119) In some examples, the dedicated resource manager **1110** may be used to receive (e.g., in cooperation with a receiver) an allocation of a dedicated set of resources in at least one of a unicast message (e.g., on-demand system information by way of a MAC control element, an RRC message, a PHY message, a PDCCH command, etc.), a timing of a unicast message, or a combination thereof.

(120) In some examples, the radio resource configuration identifier **1035-a** may be used to identify, while the UE is in a connected mode with a network, a radio resource configuration of the UE. In some examples the radio resource configuration identifier **1035-a** may identify if the UE is operating in a RRC dedicated state or a RRC common state.

(121) In some examples, the resource selector **1040-a** may be used to select a dedicated set of resources for the UE or a common set of resources for a plurality of UEs based at least in part on the identified state. In some examples, the dedicated set of resources may be associated with a more granular periodicity than the common set of resources.

(122) In some examples, the zone identifier **1115** may be used to identify a zone in which the UE is located.

(123) In some examples, the pilot signal transmission manager **1045-a** may be used to transmit (e.g., in cooperation with a transmitter) a pilot signal to the network using the selected set of resources. In some examples, the pilot signal may be transmitted periodically based at least in part on a DTX configuration or a DRX configuration of the UE. In some examples, the pilot signal transmission manager **1045-a** may include a pilot signal configurator **1120**. The pilot signal configurator **1120** may be used to configure a pilot signal based at least in part on the identified zone.

(124) The keep alive signal processor **1125** may be used to receive (e.g., in cooperation with a receiver) a keep alive signal using the selected set of resources. The keep alive signal may be received from a serving cell for the UE and may be based at least in part on the pilot signal (e.g., a network access device may identify itself or another network access device as the serving cell for the UE based at least in part on one or more measurements of the pilot signal).

(125) The serving cell identifier **1130** may be used to identify the serving cell for the UE based at least in part on the keep alive signal.

(126) FIG. **12** shows a block diagram **1200** of an apparatus **1205** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The apparatus **1205** may be an example of aspects of one or more of the network access devices **105** (e.g., ANs **105-a**, DUs **105-c**, etc.) described with reference to FIGS. **1** through **9**. The apparatus **1205** may also be or

include a processor. The apparatus **1205** may include a receiver **1210**, a transmit/receive communication manager **1220-a**, or a transmitter **1230**. Each of these components may be in communication with each other.

(127) The components of the apparatus **1205** may, individually or collectively, be implemented using one or more ASICs adapted to perform some or all of the applicable functions in hardware. Alternatively, the functions may be performed by one or more other processing units (or cores), on one or more integrated circuits. In some other examples, other types of integrated circuits may be used (e.g., Structured/Platform ASICs, FPGAs, a SoC, and/or other types of Semi-Custom ICs), which may be programmed in any manner known in the art. The functions of each component may also be implemented, in whole or in part, with instructions embodied in a memory, formatted to be executed by one or more general or application-specific processors.

(128) In some examples, the receiver **1210** may include at least one RF receiver, such as at least one RF receiver operable to receive transmissions over one or more radio frequency spectrum bands. In some examples, the receiver **1210** may include an array of antennas. In some examples, the one or more radio frequency spectrum bands may be used for LTE/LTE-A or 5G communications, as described, for example, with reference to FIGS. **1** through **9**. The receiver **1210** may be used to receive various types of data or control signals (e.g., transmissions) over one or more communication links (or channels) of a wireless communication system, such as one or more communication links (or channels) of the wireless communication system **100**, **300**, or **400** described with reference to FIG. **1**, **3**, or **4**. In some examples, the receiver **1210** may also or alternatively include one or more wired receivers.

(129) In some examples, the transmitter **1230** may include at least one RF transmitter, such as at least one RF transmitter operable to transmit over one or more radio frequency spectrum bands. In some examples, the transmitter **1230** may include an array of antennas. In some examples, the one or more radio frequency spectrum bands may be used for LTE/LTE-A or 5G communications, as described, for example, with reference to FIGS. **1** through **9**. The transmitter **1230** may be used to transmit various types of data or control signals (e.g., transmissions) over one or more communication links (or channels) of a wireless communication system, such as one or more communication links (or channels) of the wireless communication system **100**, **300**, or **400** described with reference to FIG. **1**, **3**, or **4**. In some examples, the transmitter **1230** may also or alternatively include one or more wired transmitters.

(130) In some examples, the transmit/receive communication manager **1220-a** may be used to manage one or more aspects of wireless communication for the apparatus **1205**. In some examples, part of the transmit/receive communication manager **1220-a** may be incorporated into or shared with the receiver **1210** or the transmitter **1230**. In some examples, the transmit/receive communication manager **1220-a** may be an example of aspects of the transmit/receive communication manager **1220** described with reference to FIG. **1**.

(131) The apparatus **1205** may be included in a network access device **105** that is a member of a monitoring set of network access devices for each UE in a set of UEs. As UEs move within a network, the transmit/receive communication manager **1220-a** may receive updates to the set of UEs. In some examples, the updates may be received from an access node controller. In some examples, the transmit/receive communication manager **1220-a** may include a resource identifier **1235**, a pilot signal measurer **1240**, or a serving cell identifier **1245**.

(132) The resource identifier **1235** may be used to identify a common set of resources or a dedicated set of resources for UEs in communication with the apparatus **1205**.

(133) The pilot signal measurer **1240** may be used to measure pilot signals received from UEs on at least one dedicated set of resources, and pilot signals received from UEs using a common set of resources.

(134) The serving cell identifier **1245** may be used to identify, based at least in part on pilot signal measurements, a set of UEs for which the network access device operates as a serving cell. In

various examples, the set of UEs may include a UE configured to transmit pilot signals using a dedicated set of resources, a UE configured to transmit pilot signals using a common set of resources, or a combination thereof.

(135) FIG. **13** shows a block diagram **1300** of a transmit/receive communication manager **1220-b** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The transmit/receive communication manager **1220-b** may be an example of aspects of transmit/receive communication managers **1220** described with reference to FIG. **1** or **12**.

(136) The components of the transmit/receive communication manager **1220-b** may, individually or collectively, be implemented using one or more ASICs adapted to perform some or all of the applicable functions in hardware. Alternatively, the functions may be performed by one or more other processing units (or cores), on one or more integrated circuits. In some other examples, other types of integrated circuits may be used (e.g., Structured/Platform ASICs, FPGAs, a SoC, and/or other types of Semi-Custom ICs), which may be programmed in any manner known in the art. The functions of each component may also be implemented, in whole or in part, with instructions embodied in a memory, formatted to be executed by one or more general or application-specific processors.

(137) In some examples, the transmit/receive communication manager **1220-b** may be used to manage one or more aspects of wireless communication for a network access device or apparatus, such as one of the network access devices **105** described with reference to FIGS. **1** through **9**, or the apparatus **1205** described with reference to FIG. **12**. In some examples, part of the transmit/receive communication manager **1220-b** may be incorporated into or shared with a receiver or a transmitter (e.g., the receiver **1210** or the transmitter **1230** described with reference to FIG. **12**).

(138) The transmit/receive communication manager **1220-b** may be included in a network access device **105** (e.g., an AN **105-a**, a DU **105-c**, etc.) that is a member of a monitoring set of network access devices for each UE in a set of UEs. As UEs move within a network, the transmit/receive communication manager **1220-b** may receive updates to the set of UEs. In some examples, the updates may be received from a CU **105-b**. In some examples, the transmit/receive communication manager **1220-b** may include a resource identifier **1235-a**, a pilot signal measurer **1240-a**, an measurement reporting manager **1315**, a serving cell identifier **1245-a**, a keep alive signal manager **1305**, or a UE reconfiguration manager **1310**.

(139) The resource identifier **1235-a** may be used to identify a common set of resources or a dedicated set of resources for UEs in communication with the transmit/receive communication manager **1220-b**.

(140) The pilot signal measurer **1240-a** may be used to measure pilot signals received from UEs on the at least one dedicated set of resources, and pilot signals received from UEs using a common set of resources.

(141) The measurement reporting manager **1315** may be used to transmit (e.g., in cooperation with a transmitter) measurements of pilot signals to a CU. In some examples, measurements may be selected based at least in part on periodic measurement reporting criteria or event-driven measurement reporting criteria.

(142) The serving cell identifier **1245-a** may be used to identify, based at least in part on pilot signal measurements, a set of UEs for which the network access device operates as a serving cell. In various examples, the set of UEs may include a UE configured to transmit pilot signals using a dedicated set of resources, a UE configured to transmit pilot signals using a common set of resources, or a combination thereof. In some examples, the serving cell identifier **1245-a** may receive additional measurements of pilot signals from at least one other network access device (e.g., when the transmit/receive communication manager **1220-b** is included in a DU, the serving cell identifier **1245-a** may receive measurements from other DUs). When additional measurements are received by the serving cell identifier **1245-a**, the serving cell identifier **1245-a** may identify the

set of UEs based at least in part on the measurements made by the pilot signal measurer **1240-a** and the additional measurements. In some examples, the serving cell identifier **1245-a** may receive updates to the set of UEs from the CU. Thus, the serving cell identifier **1245-a** may be configured to identify the UEs included in the set of UEs locally, at the transmit/receive communication manager **1220-b**, and/or the serving cell identifier **1245-a** may be configured to receive remote identifications of UEs to be included in the third set of UEs.

(143) The keep alive signal manager **1305** may be used to transmit (e.g., in cooperation with a transmitter) a dedicated keep alive signal to each UE that is a member of both the first set of UEs and the third set of UEs. The keep alive signal manager **1305** may also or alternatively be used to transmit a common keep alive signal to each UE that is a member of both the second set of UEs and the third set of UEs.

(144) In some examples, the UE reconfiguration manager **1310** may be used to receive (e.g., in cooperation with a receiver), from another network access device (e.g., a CU **105-b**), a reconfiguration message for a UE. In these examples, the reconfiguration message may identify a reconfigured dedicated set of resources to be used, by the UE, after a handover of the UE from the network access device to a different network access device. The UE reconfiguration manager **1310** may also be used to receive, from an access node controller, a reconfiguration message for a UE that is being handed over to the network access device. In these examples, the reconfiguration message may identify a reconfigured dedicated set of resources to be used, by the UE, after a handover of the UE to the network access device, and the UE reconfiguration manager **1310** may add the UE to a set of UEs configured to transmit pilot signals using a dedicated set of resources, or a set of UEs for which a network access device including the transmit/receive communication manager **1220-b** is a serving network access device. The UE reconfiguration manager **1310** may also be used to forward the reconfiguration message to the UE.

(145) In some examples, the UE reconfiguration manager **1310** may be used to receive (e.g., in cooperation with a receiver) a reconfiguration complete message from a UE which has been handed over to the network access device that includes the transmit/receive communication manager **1220-b**. The UE reconfiguration manager **1310** may also be used to add a UE to a set of UEs for which a network access device including the transmit/receive communication manager **1220-b** is a serving network access device, and/or to forward the reconfiguration complete message to an access node controller.

(146) FIG. **14** shows a block diagram **1400** of an apparatus **1405** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The apparatus **1405** may be an example of aspects of one or more of the network access devices **105** (e.g., ANs **105-a**, CUs **105-b**, etc.) described with reference to FIGS. **1** through **9**. The apparatus **1405** may also be or include a processor. The apparatus **1405** may include a receiver **1410**, a access node communication manager **1420-a**, or a transmitter **1430**. Each of these components may be in communication with each other.

(147) The components of the apparatus **1405** may, individually or collectively, be implemented using one or more ASICs adapted to perform some or all of the applicable functions in hardware. Alternatively, the functions may be performed by one or more other processing units (or cores), on one or more integrated circuits. In some other examples, other types of integrated circuits may be used (e.g., Structured/Platform ASICs, FPGAs, a SoC, and/or other types of Semi-Custom ICs), which may be programmed in any manner known in the art. The functions of each component may also be implemented, in whole or in part, with instructions embodied in a memory, formatted to be executed by one or more general or application-specific processors.

(148) In some examples, the receiver **1410** may include at least one RF receiver, such as at least one RF receiver operable to receive transmissions over one or more radio frequency spectrum bands. In some examples, the receiver **1410** may include an array of antennas. In some examples, the one or more radio frequency spectrum bands may be used for LTE/LTE-A or 5G

communications, as described, for example, with reference to FIGS. 1 through 9. The receiver **1410** may be used to receive various types of data or control signals (i.e., transmissions) over one or more communication links (or channels) of a wireless communication system, such as one or more communication links (or channels) of the wireless communication system **100**, **300**, or **400** described with reference to FIG. 1, 3, or 4. In some examples, the receiver **1410** may also or alternatively include one or more wired receivers.

(149) In some examples, the transmitter **1430** may include at least one RF transmitter, such as at least one RF transmitter operable to transmit over one or more radio frequency spectrum bands. In some examples, the transmitter **1430** may include an array of antennas. In some examples, the one or more radio frequency spectrum bands may be used for LTE/LTE-A or 5G communications, as described, for example, with reference to FIGS. 1 through 9. The transmitter **1430** may be used to transmit various types of data or control signals (i.e., transmissions) over one or more communication links (or channels) of a wireless communication system, such as one or more communication links (or channels) of the wireless communication system **100**, **300**, or **400** described with reference to FIG. 1, 3, or 4. In some examples, the transmitter **1430** may also or alternatively include one or more wired transmitters.

(150) In some examples, the access node communication manager **1420-a** may be used to manage one or more aspects of wireless communication for the apparatus **1405**. In some examples, part of the access node communication manager **1420-a** may be incorporated into or shared with the receiver **1410** or the transmitter **1430**. In some examples, the access node communication manager **1420-a** may be an example of aspects of the access node communication manager **1420** described with reference to FIG. 1. In some examples, the access node communication manager **1420-a** may include a measurement manager **1435**, a serving cell identifier **1440**, a monitoring set identifier **1445**, or a cell membership manager **1450**.

(151) The measurement manager **1435** may be used to receive measurements from each cell of a plurality of cells. The measurements may include measurements of a first set of pilot signals transmitted by a first set of UEs operating with a radio resource configuration associated with transmitting pilot signals using a dedicated set of resources while connected to a network, and measurements of a second set of pilot signals transmitted by a second set of UEs operating with a radio resource configuration associated with transmitting pilot signals using a common set of resources while connected to the network.

(152) The serving cell identifier **1440** may be used to identify, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the measurements, a serving cell for the UE.

(153) The monitoring set identifier **1445** may be used to identify monitoring sets of cells to monitor for pilot signals transmitted by UEs. In some examples, a monitoring set of cells to monitor for pilot signals transmitted by a UE may be identified based at least in part on measurements of at least one pilot signal transmitted by the UE, or a location of the identified serving cell for the UE, or a combination thereof.

(154) The cell membership manager **1450** may be used to indicate, to each cell, a set of UEs for which the cell is a serving cell, and a set of UEs for which the cell is a member of a monitoring set of cells for the UE.

(155) FIG. 15 shows a block diagram **1500** of an access node communication manager **1420-b** for use in wireless communication, in accordance with various aspects of the present disclosure. The access node communication manager **1420-b** may be an example of aspects of the access node communication manager **1420** described with reference to FIG. 1 or 14.

(156) The components of the access node communication manager **1420-b** may, individually or collectively, be implemented using one or more ASICs adapted to perform some or all of the applicable functions in hardware. Alternatively, the functions may be performed by one or more other processing units (or cores), on one or more integrated circuits. In some other examples, other

types of integrated circuits may be used (e.g., Structured/Platform ASICs, FPGAs, a SoC, and/or other types of Semi-Custom ICs), which may be programmed in any manner known in the art. The functions of each component may also be implemented, in whole or in part, with instructions embodied in a memory, formatted to be executed by one or more general or application-specific processors.

(157) In some examples, the access node communication manager **1420-b** may be used to manage one or more aspects of wireless communication for a network access device or apparatus, such as one of the network access devices **105** described with reference to FIGS. **1** through **9**, or apparatus **1405** described with reference to FIG. **14**. In some examples, part of the access node communication manager **1420-b** may be incorporated into or shared with a receiver or a transmitter (e.g., the receiver **1410** or the transmitter **1430** described with reference to FIG. **14**). In some examples, the access node communication manager **1420-b** may include a measurement manager **1435-a**, a serving cell identifier **1440-a**, a monitoring set identifier **1445-a**, or a cell membership manager **1450-a**.

(158) The measurement manager **1435-a** may be used to receive measurements from each cell of a plurality of cells. The measurements may include measurements of a first set of pilot signals transmitted by a first set of UEs operating with a radio resource configuration associated with transmitting pilot signals using a dedicated set of resources while connected to a network, and measurements of a second set of pilot signals transmitted by a second set of UEs operating with a radio resource configuration associated with transmitting pilot signals using a common set of resources while connected to the network.

(159) The serving cell identifier **1440-a** may be used to identify, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the measurements, a serving cell for the UE. In some examples, the serving cell identifier **1440-a** may include a serving cell change manager **1505**. The serving cell change manager **1505** may be used to identify a change in a serving cell for a UE in the first set of UEs, and initiate a serving cell change procedure for the UE upon identifying the change in the serving cell. In some examples, initiating the serving cell change procedure may include transmitting to the UE, through a source serving cell for the UE, a reconfiguration message for the UE. In some examples, initiating the serving cell change procedure may include transmitting to the UE, through a target serving cell for the UE, a reconfiguration message for the UE. The RRC reconfiguration message may identify a dedicated set of resources to be used, by the UE, after a handover of the UE to a target serving cell.

(160) The monitoring set identifier **1445-a** may be used to identify monitoring sets of cells to monitor for pilot signals transmitted by UEs. In some examples, a monitoring set of cells to monitor for pilot signals transmitted by a UE may be identified based at least in part on measurements of at least one pilot signal transmitted by the UE, or a location of the identified serving cell for the UE, or a combination thereof.

(161) The cell membership manager **1450-a** may be used to indicate, to each cell, a set of UEs for which the cell is a serving cell, and a set of UEs for which the cell is a member of a monitoring set of cells for the UE.

(162) FIG. **16** shows a block diagram **1600** of a UE **115-i** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The UE **115-i** may be included or be part of a personal computer (e.g., a laptop computer, a netbook computer, a tablet computer, etc.), a cellular telephone, a PDA, a DVR, an internet appliance, a gaming console, an e-reader, a vehicle, a home appliance, a lighting or alarm control system, etc. The UE **115-i** may, in some examples, have an internal power supply (not shown), such as a small battery, to facilitate mobile operation. In some examples, the UE **115-i** may be an example of aspects of one or more of the UEs **115** described with reference to FIGS. **1** through **9**, or the apparatus **1015** described with reference to FIG. **10**. The UE **115-i** may be configured to implement at least some of the UE or apparatus techniques and functions described with reference to FIGS. **1** through **11**.

(163) The UE **115-i** may include a processor **1610**, a memory **1620**, at least one transceiver (represented by transceiver(s) **1630**), at least one antenna (represented by antenna(s) **1640**), or a UE wireless communication manager **1020-c**. Each of these components may be in communication with each other, directly or indirectly, over one or more buses **1635**.

(164) The memory **1620** may include random access memory (RAM) or read-only memory (ROM). The memory **1620** may store computer-readable, computer-executable code **1625** containing instructions that are configured to, when executed, cause the processor **1610** to perform various functions described herein related to wireless communication, including, for example, at least some of the UE techniques and functions described with reference to FIGS. **1** through **11**. Alternatively, the computer-executable code **1625** may not be directly executable by the processor **1610** but be configured to cause the UE **115-i** (e.g., when compiled and executed) to perform various of the functions described herein.

(165) The processor **1610** may include an intelligent hardware device (e.g., a central processing unit (CPU), a microcontroller, an ASIC, etc.). The processor **1610** may process information received through the transceiver(s) **1630** or information to be sent to the transceiver(s) **1630** for transmission through the antenna(s) **1640**. The processor **1610** may handle, alone or in connection with the UE wireless communication manager **1020-c**, various aspects of communicating over (or managing communications over) one or more radio frequency spectrum bands.

(166) The transceiver(s) **1630** may include a modem configured to modulate packets and provide the modulated packets to the antenna(s) **1640** for transmission, and to demodulate packets received from the antenna(s) **1640**. The transceiver(s) **1630** may, in some examples, be implemented as one or more transmitters and one or more separate receivers. The transceiver(s) **1630** may support communications in one or more radio frequency spectrum bands. The transceiver(s) **1630** may be configured to communicate bi-directionally, via the antenna(s) **1640**, with one or more of the network access devices **105** (e.g., one or more ANs **105-a**, one or more DUs **105-c**, etc.) described with reference to FIGS. **1** through **9**, or one or more of the apparatuses **1205** or **1405** described with reference to FIG. **12** or **14**. While the UE **115-i** may include a single antenna, there may be examples in which the UE **115-i** may include multiple antennas **1640**.

(167) The UE wireless communication manager **1020-c** may be configured to perform or control some or all of the UE or apparatus techniques or functions described with reference to FIGS. **1** through **11** related to wireless communication over one or more radio frequency spectrum bands. The UE wireless communication manager **1020-c**, or portions of it, may include a processor, or some or all of the functions of the UE wireless communication manager **1020-c** may be performed by the processor **1610** or in connection with the processor **1610**. In some examples, the UE wireless communication manager **1020-c** may be an example of the UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, or **11**.

(168) FIG. **17** shows a block diagram **1700** of a network access device **105-e** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. In some examples, the network access device **105-w** may be an example of aspects of one or more of the ANs **105-a** or DUs **105-c** described with reference to FIGS. **1** through **9**, or the apparatus **1205** described with reference to FIG. **12**. The network access device **105-e** may be configured to implement at least some of the network access device, DU or apparatus techniques and functions described with reference to FIG. **1-9**, **12**, or **13**.

(169) The network access device **105-e** may include a processor **1710**, a memory **1720**, at least one transceiver (represented by transceiver(s) **1730**), at least one antenna (represented by antenna(s) **1740**), or a transmit/receive communication manager **1220-c**. Each of these components may be in communication with each other, directly or indirectly, over one or more buses **1735**.

(170) The memory **1720** may include RAM or ROM. The memory **1720** may store computer-readable, computer-executable code **1725** containing instructions that are configured to, when executed, cause the processor **1710** to perform various functions described herein related to

wireless communication, including, for example, at least some of the network access device, DU, or apparatus techniques and functions described with reference to FIGS. 1 through 13.

Alternatively, the computer-executable code 1725 may not be directly executable by the processor 1710 but be configured to cause the network access device 105-e (e.g., when compiled and executed) to perform various of the functions described herein.

(171) The processor 1710 may include an intelligent hardware device (e.g., a CPU, a microcontroller, an ASIC, etc.) The processor 1710 may process information received through the transceiver(s) 1730 or information to be sent to the transceiver(s) 1730 for transmission through the antenna(s) 1740. The processor 1710 may handle, alone or in connection with the transmit/receive communication manager 1220-c, various aspects of communicating over (or managing communications over) one or more radio frequency spectrum bands.

(172) The transceiver(s) 1730 may include a modem configured to modulate packets and provide the modulated packets to the antenna(s) 1740 for transmission, and to demodulate packets received from the antenna(s) 1740. The transceiver(s) 1730 may, in some examples, be implemented as one or more transmitters and one or more separate receivers. The transceiver(s) 1730 may support communications in one or more radio frequency spectrum bands. The transceiver(s) 1730 may be configured to communicate bi-directionally, via the antenna(s) 1740, with one or more of the UEs 115 described with reference to FIGS. 1 through 9, or apparatus 1015 described with reference to FIG. 10. While the network access device 105-e may include a single antenna, there may be examples in which the network access device 105-e may include multiple antennas 1740.

(173) The transmit/receive communication manager 1220-c may be configured to perform or control some or all of the network access device, DU, or apparatus techniques or functions described with reference to FIG. 1-9, 12, or 13 related to wireless communication over one or more radio frequency spectrum bands. The transmit/receive communication manager 1220-c may also be used to manage communications with a CU associated with the network access device 105-w. The communications with the CU may be over wired or wireless communication links, for example, depending on implementation. The transmit/receive communication manager 1220-c, or portions of it, may include a processor, or some or all of the functions of the transmit/receive communication manager 1220-c may be performed by the processor 1710 or in connection with the processor 1710. In some examples, the transmit/receive communication manager 1220-c may be an example of the transmit/receive communication manager 1220 described with reference to FIG. 1, 12, or 13.

(174) FIG. 18 shows a block diagram 1800 of a network access device 105-f that supports uplink-based mobility, in accordance with various aspects of the present disclosure. In some examples, the network access device 105-f may be an example of aspects of one or more of the ANs 105-a or CUs 105-b described with reference to FIGS. 1 through 9, or the apparatus 1405 described with reference to FIG. 14. The network access device 105-f may be configured to implement or facilitate at least some of the network access device, CU, or apparatus techniques and functions described with reference to FIG. 1-9, 14, or 15.

(175) The CU 105-f may include a processor 1810, a memory 1820, or a access node communication manager 1420-c. Each of these components may be in communication with each other, directly or indirectly, over one or more buses 1835.

(176) The memory 1820 may include RAM or ROM. The memory 1820 may store computer-readable, computer-executable code 1825 containing instructions that are configured to, when executed, cause the processor 1810 to perform various functions described herein related to wireless communication, including, for example, at least some of the network access device, CU, or apparatus techniques and functions described with reference to FIG. 1-9, 14, or 15. Alternatively, the computer-executable code 1825 may not be directly executable by the processor 1810 but be configured to cause the network access device 105-f (e.g., when compiled and executed) to perform various of the functions described herein.

(177) The processor 1810 may include an intelligent hardware device (e.g., a CPU, a

microcontroller, an ASIC, etc.). The processor **1810** may process information received through the access node communication manager **1420-c** from a core network **130-b**, or from one or more other network access devices **105** (e.g., from one or more DUs, such as DU **105-c-13** or DU **105-c-14**, or from one or more other CUs **105-b**). The processor **1810** may also process information to be sent to the access node communication manager **1420-c**, for transmission to the core network **130-b** or to one or more other network access devices **105** (e.g., to one or more DUs, such as DU **105-c-13** or DU **105-c-14**, or to one or more other CUs **105-b**). The processor **1810** may handle, alone or in connection with the access node communication manager **1420-c**, various aspects of communicating over (or managing communications over) one or more radio frequency spectrum bands.

(178) The access node communication manager **1420-c** may be configured to perform or control some or all of the techniques or functions described with reference to FIG. **1-9, 14**, or **15** related to wireless communication over one or more radio frequency spectrum bands. The access node communication manager **1420-c** may also be used to manage communications with a network (e.g., the core network **130-b**), one or more DUs (e.g., DU **105-c-13** or DU **105-c-14**), or one or more other CUs **105-b**. The communications with the network, DUs, or other CUs may be over wired or wireless communication links, for example, depending on implementation. The access node communication manager **1420-c**, or portions of it, may include a processor, or some or all of the functions of the access node communication manager **1420-c** may be performed by the processor **1810** or in connection with the processor **1810**. In some examples, the access node communication manager **1420-c** may be an example of the access node communication manager **1420** described with reference to FIG. **1, 14**, or **15**.

(179) FIG. **19** is a block diagram of a MIMO communication system **1900** that supports uplink-based mobility, in accordance with various aspects of the present disclosure. The MIMO communication system **1900** may include a network access device **105-g** and a UE **115-j**. The MIMO communication system **1900** may illustrate aspects of the wireless communication system **100, 300**, or **400** shown in FIG. **1, 3**, or **4**. In some examples, the network access device **105-g** may be an example of one or more aspects of a network access device (e.g., an AN **105-a**, a CU **105-b**, a DU **105-c**, or a base station), such as one of the network access devices **105** described with reference to FIGS. **1** through **9**, or the apparatuses **1205** or **1405** described with reference to FIG. **12** or **14**. The network access device **105-g** may be equipped with antennas **1934-a** through **1934-x**, and the UE **115-j** may be equipped with antennas **1952-a** through **1952-n**. In the MIMO communication system **1900**, the network access device **105-g** may be able to send data over multiple communication links at the same time. Each communication link may be called a “layer” and the “rank” of the communication link may indicate the number of layers used for communication. For example, in a 2×2 MIMO communications system where network access device **105-g** transmits two “layers,” the rank of the communication link between the network access device **105-g** and the UE **115-j** is two.

(180) At the network access device **105-g**, a transmit processor **1920** may receive data from a data source. The transmit processor **1920** may process the data. The transmit processor **1920** may also generate control symbols and/or reference symbols. A transmit (Tx) MIMO processor **1930** may perform spatial processing (e.g., precoding) on data symbols, control symbols, and/or reference symbols, if applicable, and may provide output symbol streams to the transmit modulator/demodulators (Mod/Demod) **1932-a** through **1932-x**. Each modulator/demodulator **1932** may process a respective output symbol stream (e.g., for OFDM, etc.) to obtain an output sample stream. Each modulator/demodulator **1932** may further process (e.g., convert to analog, amplify, filter, and upconvert) the output sample stream to obtain a DL signal. In one example, DL signals from modulator/demodulators **1932-a** through **1932-x** may be transmitted via the antennas **1934-a** through **1934-x**, respectively.

(181) At the UE **115-j**, the antennas **1952-a** through **1952-n** may receive the DL signals from the

network access device **105-g** and may provide the received signals to the modulator/demodulators **1954-a** through **1954-n**, respectively. Each modulator/demodulator **1954** may condition (e.g., filter, amplify, downconvert, and digitize) a respective received signal to obtain input samples. Each modulator/demodulator **1954** may further process the input samples (e.g., for OFDM, etc.) to obtain received symbols. A MIMO detector **1956** may obtain received symbols from all the modulator/demodulators **1954-a** through **1954-n**, perform MIMO detection on the received symbols, if applicable, and provide detected symbols. A receive processor **1958** may process (e.g., demodulate, deinterleave, and decode) the detected symbols, providing decoded data for the UE **115-j** to a data output, and provide decoded control information to a processor **1980**, or memory **1982**.

(182) The processor **1980** may in some cases execute stored instructions to instantiate a UE wireless communication manager **1020-d**. In some examples, the UE wireless communication manager **1020-d** may include components of, or may be used to perform functions of the UE wireless communication managers **1020** described with reference to FIG. **1**, **10**, **11**, or **16**.

(183) On the uplink (UL), at the UE **115-j**, a transmit processor **1964** may receive and process data from a data source. The transmit processor **1964** may also generate reference symbols for a reference signal. The symbols from the transmit processor **1964** may be precoded by a transmit MIMO processor **1966** if applicable, further processed by the modulator/demodulators **1954-a** through **1954-n** (e.g., for SC-FDMA, etc.), and be transmitted to the network access device **105-g** in accordance with the transmission parameters received from the network access device **105-g**. At the network access device **105-g**, the UL signals from the UE **115-j** may be received by the antennas **1934**, processed by the modulator/demodulators **1932**, detected by a MIMO detector **1936** if applicable, and further processed by a receive processor **1938**. The receive processor **1938** may provide decoded data to a data output and to the processor **1940** and/or memory **1942**. In some examples the processor **1940** may execute stored instructions to instantiate a transmit/receive communication manager **1220-d**. The transmit/receive communication manager **1220-d** may include components of, or may be used to perform functions of the transmit/receive communication managers **1220** described with reference to FIG. **1**, **12**, **13**, or **17**. In some examples the processor **1940** may execute stored instructions to instantiate an access node communication manager **1420-d**. The access node communication manager **1420-d** may include components of, or may be used to perform functions of the access node communication managers **1420** described with reference to FIG. **1**, **14,15**, or **18**.

(184) The components of the UE **115-j** may, individually or collectively, be implemented with one or more ASICs adapted to perform some or all of the applicable functions in hardware. Each of the noted modules may be a means for performing one or more functions related to operation of the MIMO communication system **1900**. Similarly, the components of the network access device **105-g** may, individually or collectively, be implemented with one or more ASICs adapted to perform some or all of the applicable functions in hardware. Each of the noted components may be a means for performing one or more functions related to operation of the MIMO communication system **1900**.

(185) FIG. **20** shows a flow chart illustrating an example of a method **2000** that supports uplink-based mobility at a UE **115**, in accordance with various aspects of the present disclosure. For clarity, the method **2000** is described below with reference to aspects of one or more of the UEs **115** described with reference to FIGS. **1** through **9**, **16**, or **19**, or the apparatus **1015** described with reference to FIGS. **10**, or the UE wireless communication managers **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**. In some examples, a UE may execute one or more sets of codes to control the functional elements of the UE to perform the functions described below. Additionally or alternatively, the UE may perform one or more of the functions described below using special-purpose hardware.

(186) At block **2005**, the method **2000** may include identifying, while the UE is in a connected

mode with a network, a radio resource configuration of the UE. Operations at block **2005** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a radio resource configuration identifier **1035** described with reference to FIG. **10** or **11**.

(187) At block **2010**, the method **2000** may include selecting a dedicated set of resources for the UE or a common set of resources for a plurality of UEs based at least in part on the identified radio resource configuration. In some examples, the dedicated set of resources may be associated with a more granular periodicity than the common set of resources. Operations at block **2010** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a resource selector **1040** described with reference to FIG. **10** or **11**.

(188) At block **2015**, the method **2000** may include transmitting a pilot signal to the network using the selected set of resources. In some examples, the pilot signal may be transmitted periodically based at least in part on a DTX or DRX configuration of the UE. Operations at block **2015** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a pilot signal transmission manager **1045** described with reference to FIG. **10** or **11**.

(189) Thus, the method **2000** may provide for wireless communication. It should be noted that the method **2000** is just one implementation and that the operations of the method **2000** may be rearranged or otherwise modified such that other implementations are possible.

(190) FIG. **21** shows a flow chart illustrating an example of a method **2100** that supports uplink-based mobility at a UE **115**, in accordance with various aspects of the present disclosure. For clarity, the method **2100** is described below with reference to aspects of one or more of the UEs **115** described with reference to FIGS. **1** through **9**, **16**, or **19**, or the apparatus **1015** described with reference to FIG. **10**, or a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**. In some examples, a UE may execute one or more sets of codes to control the functional elements of the UE to perform the functions described below. Additionally or alternatively, the UE may perform one or more of the functions described below using special-purpose hardware.

(191) At block **2105**, the method **2100** may optionally include receiving an allocation of a common set of resources. In some examples, the allocation of the common set of resources may be received in at least one of a synchronization signal, system information (e.g., a SIB), a unicast message (e.g., on-demand system information by way of a MAC control element, an RRC message, a PHY message, a PDCCH command, etc.), or a combination thereof. In some examples, the allocation of the common set of resources may be identified based at least in part on a type of the UE. Operations at block **2105** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a common resource manager **1105** described with reference to FIG. **11**.

(192) At block **2110**, the method **2100** may optionally include receiving an allocation of a dedicated set of resources in at least one of a unicast message, a timing of a unicast message, or a combination thereof. Operations at block **2110** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a dedicated resource manager **1110** described with reference to FIG. **11**.

(193) At block **2115**, the method **2100** may include identifying, while the UE is in a connected mode with a network, a radio resource configuration of the UE. Operations at block **2115** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a radio resource configuration identifier **1035** described with reference to FIG. **10** or **11**.

(194) At block **2120**, the method **2100** may include selecting the dedicated set of resources for the UE or the common set of resources for a plurality of UEs based at least in part on the identified radio resource configuration. In some examples, the dedicated set of resources may be associated

with a more granular periodicity than the common set of resources. Operations at block **2120** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a resource selector **1040** described with reference to FIG. **10** or **11**.

(195) At block **2125**, the method **2100** may optionally include identifying a zone in which the UE is located. Operations at block **2125** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a zone identifier **1115** described with reference to FIG. **11**.

(196) At block **2130**, the method **2100** may optionally include configuring a pilot signal based at least in part on the identified zone. Operations at block **2130** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, a pilot signal transmission manager **1045** described with reference to FIG. **10** or **11**, or a pilot signal configurator **1120** described with reference to FIG. **11**.

(197) At block **2135**, the method **2100** may include transmitting the pilot signal to the network using the selected set of resources. In some examples, the pilot signal may be transmitted periodically based at least in part on a DTX or DRX configuration of the UE. Operations at block **2135** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a pilot signal transmission manager **1045** described with reference to FIG. **10** or **11**.

(198) At block **2140**, the method **2100** may optionally include receiving a keep alive signal using the selected set of resources. The keep alive signal may be received from a serving cell for the UE and may be based at least in part on the pilot signal (e.g., a network access device may identify itself or another network access device as the serving cell for the UE based at least in part on one or more measurements of the pilot signal). Operations at block **2140** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a keep alive signal processor **1125** described with reference to FIG. **11**.

(199) At block **2145**, the method **2100** may optionally include identifying the serving cell for the UE based at least in part on the keep alive signal. Operations at block **2145** may be performed using a UE wireless communication manager **1020** described with reference to FIG. **1**, **10**, **11**, **16**, or **19**, or a serving cell identifier **1130** described with reference to FIG. **11**.

(200) Thus, the method **2100** may provide for wireless communication. It should be noted that the method **2100** is just one implementation and that the operations of the method **2100** may be rearranged or otherwise modified such that other implementations are possible. In some examples, aspects of the methods **2000** and **2100** described with reference to FIGS. **20** and **21** may be combined.

(201) FIG. **22** shows a flow chart illustrating an example of a method **2200** that supports uplink-based mobility at a network access device **105**, in accordance with various aspects of the present disclosure. For clarity, the method **2200** is described below with reference to aspects of one or more of the network access devices **105** (e.g., an AN **105-a**, a DU **105-c**, etc.) described with reference to FIG. **1-9**, **17**, **18**, or **19**, or the apparatus **1205** described with reference to FIG. **12**, or the transmit/receive communication managers **1220** described with reference to FIG. **1**, **12**, **13**, **17**, **18**, or **19**. In some examples, the method **2200** may be performed by a DU. In some examples, a network access device **105** may execute one or more sets of codes to control the functional elements of the network access device **105** to perform the functions described below. Additionally or alternatively, the network access device **105** may perform one or more of the functions described below using special-purpose hardware.

(202) At block **2205**, the method **2200** may include identifying at least one dedicated set of resources for at least one UE in a first set of UEs. The network access device may be a member of a monitoring set of network access devices for each UE in the first set of UEs. As UEs move within a network, the network access device may receive updates to the first set of UEs. In some examples, the updates may be received from a CU **105-b**. Operations at block **2205** may be performed using a

transmit/receive communication manager **1220** described with reference to FIG. 1, 12, 13, 17, or 19, or a resource identifier **1235** described with reference to FIG. 12 or 13.

(203) At block **2210**, the method **2200** may include measuring a first set of pilot signals received from the first set of UEs on the at least one dedicated set of resources, and a second set of pilot signals received from a second set of UEs using a common set of resources. Operations at block **2210** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. 1, 12, 13, 17, or 19, or a pilot signal measurer **1240** described with reference to FIG. 12 or 13.

(204) At block **2215**, the method **2200** may include identifying, based at least in part on measurements of the first set of pilot signals and the second set of pilot signals, a third set of UEs for which the network access device operates as a serving cell. In some examples, the third set of UEs may include at least one UE in the first set of UEs, or at least one UE in the second set of UEs, or a combination thereof. Operations at block **2215** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. 1, 12, 13, 17, or 19, or a serving cell identifier **1245** described with reference to FIG. 12 or 13.

(205) Thus, the method **2200** may provide for wireless communication. It should be noted that the method **2200** is just one implementation and that the operations of the method **2200** may be rearranged or otherwise modified such that other implementations are possible.

(206) FIG. 23 shows a flow chart illustrating an example of a method **2300** that supports uplink-based mobility at a network access device **105**, in accordance with various aspects of the present disclosure. For clarity, the method **2300** is described below with reference to aspects of one or more of the network access devices **105** (e.g., ANs **105-a**, DUs **105-c**, etc.) described with reference to FIG. 1-9, 17, 18, or 19, or the apparatus **1205** described with reference to FIG. 12, or the transmit/receive communication manager **1220** described with reference to FIG. 1, 12, 13, 17, or 19. In some examples, the method **2300** may be performed by a DU **105-c**. In some examples, a network access device **105** may execute one or more sets of codes to control the functional elements of the network access device **105** to perform the functions described below. Additionally or alternatively, the network access device **105** may perform one or more of the functions described below using special-purpose hardware.

(207) At block **2305**, the method **2300** may include identifying at least one dedicated set of resources for at least one UE in a first set of UEs. The network access device may be a member of a monitoring set of network access devices for each UE in the first set of UEs. As UEs move within a network, the network access device may receive updates to the first set of UEs. In some examples, the updates may be received from another network access device (e.g., a CU **105-b**). Operations at block **2305** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. 1, 12, 13, 17, or 19, or a resource identifier **1235** described with reference to FIG. 12 or 13.

(208) At block **2310**, the method **2300** may include measuring a first set of pilot signals received from the first set of UEs on the at least one dedicated set of resources, and a second set of pilot signals received from a second set of UEs using a common set of resources. Operations at block **2310** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. 1, 12, 13, 17, or 19, or a pilot signal measurer **1240** described with reference to FIG. 12 or 13.

(209) At block **2315**, the method **2300** may include identifying, based at least in part on measurements of the first set of pilot signals and the second set of pilot signals, a third set of UEs for which the network access device operates as a serving cell. In some examples, the third set of UEs may include at least one UE in the first set of UEs, or at least one UE in the second set of UEs, or a combination thereof. Operations at block **2315** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. 1, 12, 13, 17, or 19, or a serving cell identifier **1245** described with reference to FIG. 12 or 13.

(210) At block **2320**, the method **2300** may optionally include receiving additional measurements of the first set of pilot signals or the second set of pilot signals from at least one other network access device. When additional measurements are received at block **2320**, the third set of UEs may be further identified, at block **2315**, based at least in part on the additional measurements received at block **2320**. Operations at block **2320** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**, or a serving cell identifier **1245** described with reference to FIG. **12** or **13**.

(211) At block **2325**, the method **2300** may optionally include transmitting a dedicated keep alive signal to each UE that is a member of both the first set of UEs and the third set of UEs, or transmitting a common keep alive signal to each UE that is a member of both the second set of UEs and the third set of UEs, or a combination thereof. Operations at block **2325** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**, or a keep alive signal manager **1305** described with reference to FIG. **13**.

(212) At block **2330**, the method **2300** may optionally include receiving, from another network access device (e.g., a CU **105-b**), a reconfiguration message for a UE that is a member of both the first set of UEs and the third set of UEs. The reconfiguration message may identify a reconfigured dedicated set of resources to be used, by the UE, after a handover of the UE from the network access device to another network access device. Alternatively, at block **2330**, the method **2300** may optionally include receiving, from another network access device (e.g., a CU **105-b**), a reconfiguration message for a UE that is being handed over to the network access device. In this alternative example, the reconfiguration message may identify a reconfigured dedicated set of resources to be used, by the UE, after a handover of the UE to the network access device, and the UE may be added to the first set of UEs and the third set of UEs. At block **2335**, the method **2300** may optionally include forwarding the reconfiguration message to the UE. Operations at block **2330** or **2335** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**, or a UE reconfiguration manager **1310** described with reference to FIG. **13**.

(213) At block **2340**, the method **2300** may optionally include receiving a reconfiguration complete message from a UE which has been handed over to the network access device. At block **2345**, the method **2300** may optionally include forwarding the reconfiguration complete message to another network access device (e.g., a CU **105-b**). Operations at block **2340** or **2345** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**, or a UE reconfiguration manager **1310** described with reference to FIG. **13**.

(214) Thus, the method **2300** may provide for wireless communication. It should be noted that the method **2300** is just one implementation and that the operations of the method **2300** may be rearranged or otherwise modified such that other implementations are possible.

(215) FIG. **24** shows a flow chart illustrating an example of a method **2400** that supports uplink-based mobility at a network access device **105**, in accordance with various aspects of the present disclosure. For clarity, the method **2400** is described below with reference to aspects of one or more of the network access devices **105** (e.g., ANs **105-a**, DUs **105-c**, etc.) described with reference to FIG. **1-9**, **17**, **18**, or **19**, or the apparatus **1205** described with reference to FIG. **12**, or the transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**. In some examples, the method **2400** may be performed by a DU **105-c**. In some examples, a network access device **105** may execute one or more sets of codes to control the functional elements of the network access device **105** to perform the functions described below. Additionally or alternatively, the network access device **105** may perform one or more of the functions described below using special-purpose hardware.

(216) At block **2405**, the method **2400** may include identifying at least one dedicated set of resources for at least one UE in a first set of UEs. The network access device may be a member of a monitoring set of network access devices for each UE in the first set of UEs. As UEs move within a

network, the network access device may receive updates to the first set of UEs. In some examples, the updates may be received from another network access device (e.g., a CU **105-b**). Operations at block **2405** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**, or resource identifier **1235** described with reference to FIG. **12** or **13**.

(217) At block **2410**, the method **2400** may include measuring a first set of pilot signals received from the first set of UEs on the at least one dedicated set of resources, and a second set of pilot signals received from a second set of UEs using a common set of resources. Operations at block **2410** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**, or a pilot signal measurer **1240** described with reference to FIG. **12** or **13**.

(218) At block **2415**, the method **2400** may include transmitting at least one of the measurements of the first set of pilot signals or at least one of the measurements of the second set of pilot signals to another network access device (e.g., a CU **105-b**). In some examples, the at least one of the measurements of the first set of pilot signals or the at least one of the measurements of the second set of pilot signals may be selected based at least in part on a periodic measurement reporting criteria or an event-driven measurement reporting criteria. Operations at block **2415** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**, or a measurement reporting manager **1315** described with reference to FIG. **13**.

(219) At block **2420**, the method **2400** may include receiving, from the other network access device (e.g., the CU **105-b**), updates to the third set of UEs. At block **2425**, the method **2400** may include identifying, based at least in part on measurements of the first set of pilot signals and the second set of pilot signals, a third set of UEs for which the network access device operates as a serving cell. In some examples, the third set of UEs may include at least one of: at least one UE in the first set of UEs, at least one UE in the second set of UEs, or a combination thereof. In some examples, the operation(s) at block **2425** may include receiving, from the access node controller, updates to the third set of UEs. Thus, in some examples, part or all of the third set of UEs may be identified remotely, and the operation(s) at block **2425** may include receiving these remote identifications. Operations at block **2425** may be performed using a transmit/receive communication manager **1220** described with reference to FIG. **1**, **12**, **13**, **17**, or **19**, or a serving cell identifier **1245** described with reference to FIG. **12** or **13**.

(220) Thus, the method **2400** may provide for wireless communication. It should be noted that the method **2400** is just one implementation and that the operations of the method **2400** may be rearranged or otherwise modified such that other implementations are possible. In some examples, aspects of the methods **2300** and **2400** described with reference to FIGS. **23** and **24** may be combined.

(221) FIG. **25** shows a flow chart illustrating an example of a method **2500** that supports uplink-based mobility at a network access device **105**, in accordance with various aspects of the present disclosure. For clarity, the method **2500** is described below with reference to aspects of one or more of the network access devices **105** (e.g., ANs **105-a**, CUs **105-b**, etc.) described with reference to FIG. **1-9**, **17**, **18**, or **19**, or the apparatus **1405** described with reference to FIG. **14**, or the access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**. In some examples, the method **2500** may be performed by a CU **105-b**. In some examples, a network access device **105** may execute one or more sets of codes to control the functional elements of the network access device **105** to perform the functions described below. Additionally or alternatively, the network access device **105** may perform one or more of the functions described below using special-purpose hardware.

(222) At block **2505**, the method **2500** may include receiving measurements from each cell of a plurality of cells. The measurements may include measurements of a first set of pilot signals transmitted by a first set of UEs operating with a first radio resource configuration while connected

to a network, and measurements of a second set of pilot signals transmitted by a second set of UEs operating with a second radio resource configuration while connected to the network. Operations at block **2505** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, or a measurement manager **1435** described with reference to FIG. **14** or **15**.

(223) At block **2510**, the method **2500** may include identifying, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the measurements, a serving cell for the respective UE. Operations at block **2510** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, or a serving cell identifier **1440** described with reference to FIG. **14** or **15**.

(224) At block **2515**, the method **2500** may include identifying, for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals transmitted by the respective UE. In some examples, a monitoring set of cells to monitor for pilot signals transmitted by a UE may be identified based at least in part on measurements of at least one pilot signal transmitted by the UE, or a location of the identified serving cell for the UE, or a combination thereof. Operations at block **2515** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, or a monitoring set identifier **1445** described with reference to FIG. **14** or **15**.

(225) At block **2520**, the method **2500** may include indicating, to each cell, a first set of UEs for which the respective cell is a serving cell, and a second set of UEs for which the respective cell is a member of a monitoring set of cells for the UE. Operations at block **2520** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, or a cell membership manager **1450** described with reference to FIG. **14** or **15**.

(226) Thus, the method **2500** may provide for wireless communication. It should be noted that the method **2500** is just one implementation and that the operations of the method **2500** may be rearranged or otherwise modified such that other implementations are possible.

(227) FIG. **26** shows a flow chart illustrating an example of a method **2600** that supports uplink-based mobility at a network access device **105**, in accordance with various aspects of the present disclosure. For clarity, the method **2600** is described below with reference to aspects of one or more of the network access devices **105** (e.g., ANs **105-a**, CUs **105-b**, etc.) described with reference to FIG. **1-9**, **17**, **18**, or **19**, or the apparatus **1405** described with reference to FIG. **14**, or the access node communication managers **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**. In some examples, the method **2600** may be performed by a CU **105-b**. In some examples, a network access device **105** may execute one or more sets of codes to control the functional elements of the network access device **105** to perform the functions described below. Additionally or alternatively, the network access device **105** may perform one or more of the functions described below using special-purpose hardware.

(228) At block **2605**, the method **2600** may include receiving measurements from each cell of a plurality of cells. The measurements may include measurements of a first set of pilot signals transmitted by a first set of UEs operating with a first radio resource configuration while connected to a network, and measurements of a second set of pilot signals transmitted by a second set of UEs operating with a second radio resource configuration while connected to the network. Operations at block **2605** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, or a measurement manager **1435** described with reference to FIG. **14** or **15**.

(229) At block **2610**, the method **2600** may include identifying, for each UE in the first set of UEs and each UE in the second set of UEs, based at least in part on the measurements, a serving cell for the respective UE. Operations at block **2610** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, or a serving cell identifier **1440** described with reference to FIG. **14** or **15**.

(230) At block **2615**, the method **2600** may include identifying, for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals transmitted by the respective UE. In some examples, a monitoring set of cells to monitor for pilot signals transmitted by a UE may be identified based at least in part on measurements of at least one pilot signal transmitted by the UE, or a location of the identified serving cell for the UE, or a combination thereof. Operations at block **2615** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, or a monitoring set identifier **1445** described with reference to FIG. **14** or **15**.

(231) At block **2620**, the method **2600** may include indicating, to each cell, a first set of UEs for which the respective cell is a serving cell, and a second set of UEs for which the respective cell is a member of a monitoring set of cells for the UE. Operations at block **2620** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, or a cell membership manager **1450** described with reference to FIG. **14** or **15**.

(232) At block **2625**, the method **2600** may include identifying a change in a serving cell for a UE in the first set of UEs. At block **2630**, the method **2600** may include initiating a serving cell change procedure for the UE upon identifying the change in the serving cell. In some examples, initiating the serving cell change procedure may include transmitting to the UE, through a source serving cell for the UE, a reconfiguration message for the UE. In some examples, initiating the serving cell change procedure may include transmitting to the UE, through a target serving cell for the UE, a reconfiguration message for the UE. The RRC reconfiguration message may identify a dedicated set of resources to be used, by the UE, after a handover of the UE to a target serving cell. Operations at block **2625** or **2630** may be performed using an access node communication manager **1420** described with reference to FIG. **1**, **14**, **15**, **18**, or **19**, a serving cell identifier **1440** described with reference to FIG. **14** or **15**, or a serving cell change manager **1505** described with reference to FIG. **15**.

(233) Thus, the method **2600** may provide for wireless communication. It should be noted that the method **2600** is just one implementation and that the operations of the method **2600** may be rearranged or otherwise modified such that other implementations are possible. In some examples, aspects of the methods **2500** and **2600** described with reference to FIGS. **25** and **26** may be combined.

(234) Techniques described herein may be used for various wireless communication systems such as CDMA, TDMA, FDMA, OFDMA, SC-FDMA, and other systems. The terms “system” and “network” are often used interchangeably. A CDMA system may implement a radio technology such as CDMA2000, Universal Terrestrial Radio Access (UTRA), etc. CDMA2000 covers IS-2000, IS-95, and IS-856 standards. IS-2000 Releases 0 and A may be referred to as CDMA2000 1×, 1×, etc. IS-856 (TIA-856) may be referred to as CDMA2000 1×EV-DO, High Rate Packet Data (HRPD), etc. UTRA includes Wideband CDMA (WCDMA) and other variants of CDMA. A TDMA system may implement a radio technology such as Global System for Mobile Communications (GSM). An OFDMA system may implement a radio technology such as Ultra Mobile Broadband (UMB), Evolved UTRA (E-UTRA), Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM™, etc. UTRA and E-UTRA are part of Universal Mobile Telecommunication System (UMTS). 3GPP LTE and LTE-A are new releases of UMTS that use E-UTRA. UTRA, E-UTRA, UMTS, LTE, LTE-A, and GSM are described in documents from an organization named 3GPP. CDMA2000 and UMB are described in documents from an organization named “3rd Generation Partnership Project 2” (3GPP2). The techniques described herein may be used for the systems and radio technologies mentioned above as well as other systems and radio technologies, including cellular (e.g., LTE) communications over an unlicensed or shared bandwidth. The description above, however, describes an LTE/LTE-A system for purposes of example, and LTE terminology is used in much of the description above, although the techniques are applicable beyond LTE/LTE-A applications.

(235) The detailed description set forth above in connection with the appended drawings describes examples and does not represent all of the examples that may be implemented or that are within the scope of the claims. The terms “example” and “exemplary,” when used in this description, mean “serving as an example, instance, or illustration,” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some instances, well-known structures and apparatuses are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

(236) As used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an exemplary step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

(237) Information and signals may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the above description may be represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

(238) The various illustrative blocks and components described in connection with the disclosure herein may be implemented or performed with a general-purpose processor, a digital signal processor (DSP), an ASIC, an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices, e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration.

(239) The functions described herein may be implemented in hardware, software executed by a processor, firmware, or any combination thereof. If implemented in software executed by a processor, the functions may be stored on or transmitted over as one or more instructions or code on a computer-readable medium. Other examples and implementations are within the scope and spirit of the disclosure and appended claims. For example, due to the nature of software, functions described above can be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Components implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations. As used herein, including in the claims, the term “or,” when used in a list of two or more items, means that any one of the listed items can be employed by itself, or any combination of two or more of the listed items can be employed. For example, if a composition is described as containing components A, B, or C, the composition can contain A alone; B alone; C alone; A and B in combination; A and C in combination; B and C in combination; or A, B, and C in combination. Also, as used herein, including in the claims, “or” as used in a list of items (for example, a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates a disjunctive list such that, for example, a list of “at least one of A, B, or C” means A or B or C or AB or AC or BC or ABC (i.e., A and B and C).

(240) Computer-readable media includes both computer storage media and communication media including any medium that facilitates transfer of a computer program from one place to another. A storage medium may be any available medium that can be accessed by a general purpose or special purpose computer. By way of example, and not limitation, computer-readable media can comprise RAM, ROM, EEPROM, flash memory, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to carry or store

desired program code means in the form of instructions or data structures and that can be accessed by a general-purpose or special-purpose computer, or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of medium. Disk and disc, as used herein, include compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above are also included within the scope of computer-readable media.

(241) The previous description of the disclosure is provided to enable a person skilled in the art to make or use the disclosure. Various modifications to the disclosure will be readily apparent to those skilled in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not to be limited to the examples and designs described herein but is to be accorded the broadest scope consistent with the principles and novel techniques disclosed herein.

Claims

1. A method for wireless communication, comprising: receiving, from each cell of a plurality of cells, measurements of a first set of pilot signals corresponding to a first set of user equipments (UEs) operating with a first radio resource configuration while connected to a network, and of a second set of pilot signals corresponding to a second set of UEs operating with a second radio resource configuration while connected to the network, wherein for each UE in the first set of UEs and each UE in the second set of UEs, a serving cell for the respective UE is determined based at least in part on the measurements, and wherein for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals corresponds to the respective UE; and indicating, to each cell, each UE for which the respective cell is determined to be a serving cell, and each UE for which the respective cell is a member of a monitoring set of cells.
2. The method of claim 1, wherein the first radio resource configuration is associated with transmitting pilot signals using a dedicated set of resources, and the second radio resource configuration is associated with transmitting pilot signals using a common set of resources.
3. The method of claim 1, wherein the first radio resource configuration, or the second radio resource configuration, or both comprises a radio resource control (RRC) configuration.
4. The method of claim 1, further comprising: initiating a serving cell change procedure for a UE in the first set of UEs based at least in part on the measurements of the first set of pilot signals.
5. The method of claim 4, wherein initiating the serving cell change procedure comprises: transmitting to the UE, through a source serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message indicative of a dedicated set of resources to be used, by the UE, after a handover of the UE to a target serving cell.
6. The method of claim 4, wherein initiating the serving cell change procedure comprises: transmitting to the UE, through a target serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message indicative of a dedicated set of resources to be used, by the UE, after a handover of the UE to the target serving cell.
7. The method of claim 1, wherein the monitoring set of cells to monitor for pilot signals corresponding to the respective UE is based at least in part on: measurements of at least one pilot signal corresponding to the respective UE, or a location of the determined serving cell for the respective UE, or a combination thereof.
8. An apparatus for wireless communication, comprising: a processor; and memory coupled with

the processor, the processor configured to: receive, from each cell of a plurality of cells, measurements of a first set of pilot signals corresponding to a first set of user equipments (UEs) operating with a first radio resource configuration while connected to a network, and of a second set of pilot signals corresponding to a second set of UEs operating with a second radio resource configuration while connected to the network, wherein for each UE in the first set of UEs and each UE in the second set of UEs, a serving cell for the respective UE is determined based at least in part on the measurements, and wherein for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals corresponds to the respective UE; and indicate, to each cell, each UE for which the respective cell is determined to be a serving cell, and each UE for which the respective cell is a member of a monitoring set of cells.

9. The apparatus of claim 8, wherein the first radio resource configuration is associated with transmitting pilot signals using a dedicated set of resources, and the second radio resource configuration is associated with transmitting pilot signals using a common set of resources.

10. The apparatus of claim 8, wherein the first radio resource configuration, or the second radio resource configuration, or both comprises a radio resource control (RRC) configuration.

11. The apparatus of claim 8, wherein the processor is configured to: initiate a serving cell change procedure for a UE based at least in part on the measurements of the first set of pilot signals.

12. The apparatus of claim 11, wherein, for initiating the serving cell change procedure, the processor is configured to: transmit to the UE, through a source serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message indicative of a dedicated set of resources to be used, by the UE, after a handover of the UE to a target serving cell.

13. The apparatus of claim 11, wherein, for initiating the serving cell change procedure, the processor is configured to: transmit to the UE, through a target serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message indicative of a dedicated set of resources to be used, by the UE, after a handover of the UE to the target serving cell.

14. The apparatus of claim 8, wherein the monitoring set of cells to monitor for pilot signals corresponding to the respective UE is based at least in part on: measurements of at least one pilot signal corresponding to the respective UE, or a location of the determined serving cell for the respective UE, or a combination thereof.

15. An apparatus for wireless communication, comprising: means for receiving, from each cell of a plurality of cells, measurements of a first set of pilot signals corresponding to a first set of user equipments (UEs) operating with a first radio resource configuration while connected to a network, and of a second set of pilot signals corresponding to a second set of UEs operating with a second radio resource configuration while connected to the network, wherein for each UE in the first set of UEs and each UE in the second set of UEs, a serving cell for the respective UE is determined based at least in part on the measurements, and wherein for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals corresponds to the respective UE; and means for indicating, to each cell, each UE for which the respective cell is determined to be a serving cell, and each UE for which the respective cell is a member of a monitoring set of cells.

16. The apparatus of claim 15, wherein the first radio resource configuration is associated with transmitting pilot signals using a dedicated set of resources, and the second radio resource configuration is associated with transmitting pilot signals using a common set of resources.

17. The apparatus of claim 15, wherein the first radio resource configuration, or the second radio resource configuration, or both comprises a radio resource control (RRC) configuration.

18. The apparatus of claim 15, further comprising: means for initiating a serving cell change procedure for a UE in the first set of UEs based at least in part on the measurements of the first set of pilot signals.

19. The apparatus of claim 18, wherein the means for initiating the serving cell change procedure comprise: means for transmitting to the UE, through a source serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message indicative of a dedicated set of

resources to be used, by the UE, after a handover of the UE to a target serving cell.

20. The apparatus of claim 18, wherein the means for initiating the serving cell change procedure comprise: means for transmitting to the UE, through a target serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message indicative of a dedicated set of resources to be used, by the UE, after a handover of the UE to the target serving cell.

21. The apparatus of claim 15, wherein the monitoring set of cells to monitor for pilot signals corresponding to the respective UE is based at least in part on: measurements of at least one pilot signal corresponding to the respective UE, or a location of the determined serving cell for the respective UE, or a combination thereof.

22. A non-transitory computer-readable medium storing code for wireless communication, the code comprising instructions executable by a processor to: receive, from each cell of a plurality of cells, measurements of a first set of pilot signals corresponding to a first set of user equipments (UEs) operating with a first radio resource configuration while connected to a network, and of a second set of pilot signals corresponding to a second set of UEs operating with a second radio resource configuration while connected to the network, wherein for each UE in the first set of UEs and each UE in the second set of UEs, a serving cell for the respective UE is determined based at least in part on the measurements, and wherein for each UE in the first set of UEs, a monitoring set of cells to monitor for pilot signals corresponds to the respective UE; and indicate, to each cell, each UE for which the respective cell is determined to be a serving cell, and each UE for which the respective cell is a member of a monitoring set of cells.

23. The non-transitory computer-readable medium of claim 22, wherein the first radio resource configuration is associated with transmitting pilot signals using a dedicated set of resources, and the second radio resource configuration is associated with transmitting pilot signals using a common set of resources.

24. The non-transitory computer-readable medium of claim 22, wherein the first radio resource configuration, or the second radio resource configuration, or both comprises a radio resource control (RRC) configuration.

25. The non-transitory computer-readable medium of claim 22, wherein the instructions are further executable by the processor to: initiate a serving cell change procedure for a UE based at least in part on the measurements of the first set of pilot signals.

26. The non-transitory computer-readable medium of claim 25, wherein the instructions to initiate the serving cell change procedure are executable by the processor to: transmit to the UE, through a source serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message indicative of a dedicated set of resources to be used, by the UE, after a handover of the UE to a target serving cell.

27. The non-transitory computer-readable medium of claim 25, wherein the instructions to initiate the serving cell change procedure are executable by the processor to: transmit to the UE, through a target serving cell for the UE, a reconfiguration message for the UE, the reconfiguration message indicative of a dedicated set of resources to be used, by the UE, after a handover of the UE to the target serving cell.

28. The non-transitory computer-readable medium of claim 22, wherein the monitoring set of cells to monitor for pilot signals corresponding to the respective UE is based at least in part on: measurements of at least one pilot signal corresponding to the UE, or a location of the determined serving cell for the UE, or a combination thereof.
