

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407920
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Li; Dong Charles

Image modification based on objects of interest

Abstract

In various example embodiments, a system and method for modifying images are presented. The system receives a user interface selection initiating an image capture and detects a first image capture parameter. The system identifies an object of interest within a field of view of an image capture device and identifies a set of object characteristics of the object of interest. The system generates a parameter notification indicating a suggested modification of the first image capture parameter based on one or more object characteristics of the set of object characteristics. The system causes presentation of the parameter notification at the image capture device.

Inventors:	Li; Dong Charles (Sunnyvale, CA)
Applicant:	eBay Inc. (San Jose, CA)
Family ID:	60089867
Assignee:	eBay Inc. (San Jose, CA)
Appl. No.:	18/652366
Filed:	May 01, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240284040 A1	Aug. 22, 2024

Related U.S. Application Data

continuation parent-doc US 17705178 20220325 US 12022185 child-doc US 18652366
continuation parent-doc US 17011627 20200903 US 11330167 20220510 child-doc US 17705178
continuation parent-doc US 16406920 20190508 US 10805524 20201013 child-doc US 17011627
continuation parent-doc US 15136388 20160422 US 10432849 child-doc US 16406920

Publication Classification

Int. Cl.: **H04N23/60** (20230101); **H04N9/64** (20230101); **H04N23/62** (20230101); **H04N23/63** (20230101); **H04N23/88** (20230101); H04N23/69 (20230101)

U.S. Cl.:

CPC **H04N23/64** (20230101); **H04N9/646** (20130101); **H04N23/62** (20230101); **H04N23/633** (20230101); **H04N23/88** (20230101); H04N23/632 (20230101); H04N23/69 (20230101)

Field of Classification Search

CPC: H04N (23/64); H04N (9/646); H04N (23/62); H04N (23/633); H04N (23/88); H04N (23/632); H04N (23/69)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7409145	12/2007	Antoun et al.	N/A	N/A
7805066	12/2009	Wexler et al.	N/A	N/A
9473687	12/2015	Luk et al.	N/A	N/A
9704231	12/2016	Kulewski et al.	N/A	N/A
9875515	12/2017	Karppanen	N/A	N/A
10432849	12/2018	Li	N/A	N/A
10805524	12/2019	Li	N/A	N/A
11330167	12/2021	Dong	N/A	N/A
12022185	12/2023	Li	N/A	N/A
2003/0067551	12/2002	Venturino et al.	N/A	N/A
2004/0201699	12/2003	Parulski et al.	N/A	N/A
2005/0207615	12/2004	Stach	N/A	N/A
2007/0120979	12/2006	Zhang et al.	N/A	N/A
2007/0180482	12/2006	Frink et al.	N/A	N/A
2007/0206108	12/2006	Nozawa	N/A	N/A
2007/0286482	12/2006	Au	382/173	G06T 7/254
2009/0061971	12/2008	Weitzner et al.	N/A	N/A
2009/0136082	12/2008	Zandifar et al.	N/A	N/A
2009/0256933	12/2008	Mizukami	N/A	N/A
2012/0069212	12/2011	Imai	N/A	N/A
2012/0113307	12/2011	Watanabe et al.	N/A	N/A
2013/0329995	12/2012	Webb et al.	N/A	N/A
2014/0032406	12/2013	Roach	705/42	G06Q 20/042
2014/0285428	12/2013	Holz	N/A	N/A
2014/0285522	12/2013	Kim et al.	N/A	N/A
2015/0085145	12/2014	Sinha et al.	N/A	N/A
2015/0130981	12/2014	Hagiwara	N/A	N/A
2015/0262011	12/2014	Keat et al.	N/A	N/A
2015/0264273	12/2014	Feder et al.	N/A	N/A
2015/0339905	12/2014	Stevens et al.	N/A	N/A

2015/0358549	12/2014	Cho et al.	N/A	N/A
2015/0373257	12/2014	Shirakawa	N/A	N/A
2016/0182816	12/2015	Luk et al.	N/A	N/A
2016/0224857	12/2015	Zhang et al.	N/A	N/A
2017/0310884	12/2016	Li	N/A	N/A
2019/0268534	12/2018	Li	N/A	N/A
2020/0404168	12/2019	Li	N/A	N/A
2022/0279117	12/2021	Li	N/A	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 15/136,388, , “Corrected Notice Of Allowability received for U.S. Appl. No. 15/136,388, mailed on Aug. 27, 2019”, Aug. 27, 2019, 4 pages. cited by applicant

U.S. Appl. No. 15/136,388, , “First Action Pre-Interview Summary received for U.S. Appl. No. 15/136,388, mailed on Apr. 21, 2017”, Apr. 21, 2017, 6 pages. cited by applicant

U.S. Appl. No. 15/136,388, , “Notice of Allowance received for U.S. Appl. No. 15/136,388, mailed on Jan. 14, 2019”, Jan. 14, 2019, 7 pages. cited by applicant

U.S. Appl. No. 15/136,388, , “Notice Of Allowance received for U.S. Appl. No. 15/136,388, mailed on May 3, 2019”, May 3, 2019, 7 pages. cited by applicant

U.S. Appl. No. 16/406,920, , “Advisory Action Received for U.S. Appl. No. 16/406,920, mailed on Apr. 22, 2020”, Apr. 22, 2020, 3 pages. cited by applicant

U.S. Appl. No. 16/406,920, , “Corrected Notice Of Allowability received for U.S. Appl. No. 16/406,920, mailed on Aug. 3, 2020”, Aug. 3, 2020, 4 pages. cited by applicant

U.S. Appl. No. 16/406,920, , “Final Office Action Received for U.S. Appl. No. 16/406,920, mailed on Jan. 24, 2020”, Jan. 24, 2020, 15 pages. cited by applicant

U.S. Appl. No. 16/406,920, , “Non-Final Office Action received for U.S. Appl. No. 16/406,920, mailed on Jul. 11, 2019”, Jul. 11, 2019, 14 pages. cited by applicant

U.S. Appl. No. 16/406,920, , “Notice Of Allowance received for U.S. Appl. No. 16/406,920, mailed on Jun. 4, 2020”, Jun. 4, 2020, 7 pages. cited by applicant

U.S. Appl. No. 17/011,627, , “Corrected Notice Of Allowability received for U.S. Appl. No. 17/011,627, mailed on Apr. 26, 2022”, Apr. 26, 2022, 8 pages. cited by applicant

U.S. Appl. No. 17/011,627, , “Non-final Office Action received for U.S. Appl. No. 17/011,627, mailed on Sep. 2, 2021”, Sep. 2, 2021, 8 pages. cited by applicant

U.S. Appl. No. 17/011,627, , “Notice of Allowance Received for U.S. Appl. No. 17/011,627, mailed on Jan. 3, 2022”, Jan. 3, 2022, 7 pages. cited by applicant

U.S. Appl. No. 17/705,178, , “Final Office Action”, U.S. Appl. No. 17/705,178, May 10, 2023, 12 pages. cited by applicant

U.S. Appl. No. 17/705,178, , “Non-Final Office Action”, U.S. Appl. No. 17/705,178, Sep. 14, 2023, 20 pages. cited by applicant

U.S. Appl. No. 17/705,178, , “Non-Final Office Action Received for U.S. Appl. No. 17/705,178, mailed on Oct. 27, 2022”, Oct. 27, 2022, 12 pages. cited by applicant

U.S. Appl. No. 17/705,178, , “Notice of Allowance”, U.S. Appl. No. 17/705,178, Mar. 19, 2024, 19 pages. cited by applicant

Aguilar, , “Gadget Hacks”, Retrieved from the Internet URL: <<https://galaxy-note-3.gadgethacks.com/how-to/get-lenovos-exclusive-super-camera-apps-your-galaxy-note-3-0150388/>>, Jan. 21, 2014, 9 pages. cited by applicant

Primary Examiner: Dagnew; Mekonnen D

Attorney, Agent or Firm: FIG. 1 Patents

Background/Summary

RELATED APPLICATIONS (1) This application is a continuation of and claims priority to U.S. patent application Ser. No. 17/705,178, filed Mar. 25, 2022, entitled “Image Modification Based on Objects of Interest,” which is a continuation of and claims priority to U.S. patent application Ser. No. 17/011,627, filed Sep. 3, 2020, entitled “Image Modification Based on Objects of Interest,” now U.S. Pat. No. 11,330,167, issued May 10, 2022, which is a continuation of and claims priority to U.S. patent application Ser. No. 16/406,920, filed May 8, 2019, entitled “Image Modification Based on Objects of Interest,” now U.S. Pat. No. 10,805,524, issued Oct. 13, 2020, which is a continuation of and claims priority to U.S. patent application Ser. No. 15/136,388 filed Apr. 22, 2016, entitled “Image Modification Based on Objects of Interest,” now U.S. Pat. No. 10,432,849, issued Oct. 1, 2019, the entire disclosure of which is hereby incorporated by reference herein in its entirety.

BACKGROUND/SUMMARY

Technical Field

(1) Embodiments of the present disclosure relate generally to image capture and, more particularly, but not by way of limitation, to modifying images and image capture parameters for accurate portrayal of an image subject.

BACKGROUND

(2) Conventionally, image capture devices provide image capture modes and image effects to provide artistic changes to an image captured by the image capture device. The artistic changes are often made to exaggerate portions of the image and reduce accuracy. Image capture modes are often provided to a user prior to capture of an image such that the image capture device is placed into an image capture mode with specified settings prior to capture of the image. Image capture modes are often independent of context or rely on a user to correctly select the image capture mode appropriate for a context or subject of the image. Image effects are often provided after capture of the image. Image effects are often provided regardless of context of the image.

Description

DESCRIPTION

Brief Description of the Drawings

- (1) Various ones of the appended drawings merely illustrate example embodiments of the present disclosure and cannot be considered as limiting its scope.
- (2) FIG. 1 is a block diagram illustrating a networked system, according to some example embodiments.
- (3) FIG. 2 is a block diagram of an example image modification system, according to various embodiments.
- (4) FIG. 3 is a flow chart illustrating an example method, according to various embodiments.
- (5) FIG. 4 is an example user interface diagram illustrating a user interface screen including a field of view, according to various embodiments.
- (6) FIG. 5 is an example user interface diagram illustrating a user interface screen including a parameter notification, according to various embodiments.
- (7) FIG. 6 is an example user interface diagram illustrating a modified image, according to various embodiments.
- (8) FIG. 7 is a flow chart illustrating an example method, according to various embodiments.
- (9) FIG. 8 is a flow chart illustrating an example method, according to various embodiments.
- (10) FIG. 9 is an example user interface diagram illustrating a set of preview images, according to

various embodiments.

(11) FIG. 10 is a flow chart illustrating an example method, according to various embodiments.

(12) FIG. 11 is a flow chart illustrating an example method, according to various embodiments.

(13) FIG. 12 is an example user interface diagram illustrating a position notification, according to various embodiments.

(14) FIG. 13 is a flow chart illustrating an example method, according to various embodiments.

(15) FIG. 14 is a block diagram illustrating an example of a software architecture that may be installed on a machine, according to some example embodiments.

(16) FIG. 15 illustrates a diagrammatic representation of a machine in the form of a computer system within which a set of instructions may be executed for causing the machine to perform any one or more of the methodologies discussed herein, according to an example embodiment.

(17) The headings provided herein are merely for convenience and do not necessarily affect the scope or meaning of the terms used.

DETAILED DESCRIPTION

(18) The description that follows includes systems, methods, techniques, instruction sequences, and computing machine program products that embody illustrative embodiments of the disclosure. In the following description, for the purposes of explanation, numerous specific details are set forth in order to provide an understanding of various embodiments of the inventive subject matter. It will be evident, however, to those skilled in the art, that embodiments of the inventive subject matter may be practiced without these specific details. In general, well-known instruction instances, protocols, structures, and techniques are not necessarily shown in detail.

(19) In various example embodiments, methods and systems for an image modification are presented. Users capturing images for publication are often not skilled photographers. Captured images in amateur or hobbyist publications may not appear as clear or accurate as those professionally photographed and provided in large scale or professional publications. For example, an image captured by an amateur or hobbyist may not offer sharp focus, accurate contrast, and accurate white balance. Imbalances in image capture characteristics such as focus, contrast, white balance, color saturation, and other characteristics may lower interest in a publication, reduce user interaction with the publication, and lead to dissatisfaction with an item underlying the publication.

(20) Embodiments of the present disclosure describe systems and methods for an image capture and modification system to enable users to capture quality and accurate images. The image capture and modification system may dynamically change or suggest changes to image capture modes, image capture parameters, and image composition elements to ensure accurate and sharp representation of objects depicted within a captured image.

(21) In some embodiments, the image capture and modification system determines image capture modes, image capture parameters, and image composition elements based on objects detected within a field of view of an image capture device. For example, the image capture and modification system may determine one or more objects within a field of view, determine colors of the objects, and determine relative contrasts among the colors. The image capture and modification system may then automatically adjust an image capture mode and image capture parameters (e.g., white balance, color saturation, International Standards Organization (ISO) speeds, and focus points or values). The image capture and modification system may also generate and present suggestions for changes in a composition of the objects within the field of view. For example, the image capture and modification system may generate and present instructions suggesting a change of a color or type of a background positioned behind an object of interest within the field of view. In some instances, suggestions generated and presented by the image capture and modification system may include suggested manual changes to image capture modes or image capture parameters of the image capture device.

(22) In some embodiments, the image capture and modification system may dynamically change or suggest changes to image capture modes, image capture parameters, and image composition

elements based on network-accessible publications including images depicting objects of interest similar to those within the field of view of the image capture device. To ensure accurate and sharp representation of objects depicted within a captured image, the image capture and modification system may perform object detection methods to determine a type, class, or specific object within the field of view of the image capture device. Upon determining information about the object, the image capture and modification system may perform a search on one or more databases or systems via a network to identify publications including images of objects similar to that present within the field of view. From the images depicting similar objects, the image capture and modification system may identify image capture modes, image capture parameters, or image composition values or characteristics of the images depicting similar objects. The image capture and modification system may then dynamically modify or generate and present suggestions for modifications to the image capture mode, the image capture parameters, or the image composition of the image capture device prior to capture of the image. The publications containing images depicting similar objects may be example images on a product or manufacturer web page, images for particular products on an auction or other commerce website, an instructional website such as a school website or a website for a photography course, or any other suitable publications.

(23) With reference to FIG. 1, an example embodiment of a high-level client-server-based network architecture **100** is shown. A networked system **102**, in the example forms of a network-based marketplace or payment system, provides server-side functionality via a network **104** (e.g., the Internet or a wide area network (WAN)) to one or more client devices **110**. FIG. 1 illustrates, for example, a web client **112** (e.g., a browser, such as the Internet Explorer® browser developed by Microsoft® Corporation of Redmond, Wash. State), an application **114**, a programmatic client **116**, and an image modification system **150** executing on the client device **110**. In some embodiments, the image modification system **150** may be entirely included in the client device **110**. In some instances, a portion of the image modification system **150** resides at the client device **110** and a portion of the image modification system **150** resides on a publication system **142**.

(24) The client device **110** may comprise, but is not limited to, a mobile phone, a desktop computer, a laptop, a portable digital assistant (PDA), a smartphone, a tablet, an ultra book, a netbook, a laptop, a multi-processor system, microprocessor-based or programmable consumer electronics, a game console, a set-top box, or any other communication device that a user may utilize to access the networked system **102**. In some embodiments, the client device **110** may comprise a display component (not shown) to display information (e.g., in the form of user interfaces). In further embodiments, the client device **110** may comprise one or more of touch screens, accelerometers, gyroscopes, cameras, microphones, global positioning system (GPS) devices, and so forth. The client device **110** may be a device of a user that is used to perform a transaction involving digital items within the networked system **102**. In one embodiment, the networked system **102** is a network-based marketplace that responds to requests for product listings, publishes publications comprising item listings of products available on the network-based marketplace, and manages payments for these marketplace transactions. One or more users **106** may be a person, a machine, or other means of interacting with the client device **110**. In some embodiments, the user **106** is not part of the network architecture **100**, but may interact with the network architecture **100** via the client device **110** or another means. For example, one or more portions of the network **104** may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a WAN, a wireless WAN (WWAN), a metropolitan area network (MAN), a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a cellular telephone network, a wireless network, a WiFi network, a WiMax network, another type of network, or a combination of two or more such networks.

(25) Each of the client devices **110** may include one or more applications **114** (also referred to as “apps”) such as, but not limited to, a web browser, a messaging application, an electronic mail (email) application, an e-commerce site application (also referred to as a marketplace application),

and the like. In some embodiments, if the e-commerce site application is included in a given one of the client devices **110**, then this application **114** is configured to locally provide the user interface and at least some of the functionalities of an e-commerce site, with the application **114** configured to communicate with the networked system **102**, on an as-needed basis, for data and/or processing capabilities not locally available (e.g., to access a database of items available for sale, to authenticate a user **106**, to verify a method of payment, etc.). Conversely, if the e-commerce site application is not included in the client device **110**, the client device **110** may use its web browser to access the e-commerce site (or a variant thereof) hosted on the networked system **102**.

(26) One or more users **106** may be a person, a machine, or other means of interacting with the client device **110**. In example embodiments, the user **106** is not part of the network architecture **100**, but may interact with the network architecture **100** via the client device **110** or other means. For instance, the user **106** provides input (e.g., touch screen input or alphanumeric input) to the client device **110** and the input is communicated to the networked system **102** via the network **104**. In this instance, the networked system **102**, in response to receiving the input from the user **106**, communicates information to the client device **110** via the network **104** to be presented to the user **106**. In this way, the user **106** can interact with the networked system **102** using the client device **110**.

(27) An application program interface (API) server **120** and a web server **122** are coupled to, and provide programmatic and web interfaces respectively to, one or more application servers **140**. The application servers **140** may host one or more publication systems **142** and payment systems **144**, each of which may comprise one or more components or applications and each of which may be embodied as hardware, software, firmware, or any combination thereof. The application servers **140** are, in turn, shown to be coupled to one or more database servers **124** that facilitate access to one or more information storage repositories or database(s) **126**. In an example embodiment, the databases **126** are storage devices that store information to be posted (e.g., publications or listings) to the publication system **142**. The databases **126** may also store digital item information, in accordance with example embodiments.

(28) Additionally, a third party application **132**, executing on third party server(s) **130**, is shown as having programmatic access to the networked system **102** via the programmatic interface provided by the API server **120**. For example, the third party application **132**, utilizing information retrieved from the networked system **102**, supports one or more features or functions on a website hosted by a third party. The third party website, for example, provides one or more promotional, marketplace, or payment functions that are supported by the relevant applications of the networked system **102**.

(29) The one or more publication systems **142** may provide a number of publication functions and services to users **106** that access the networked system **102**. The payment systems **144** may likewise provide a number of functions to perform or facilitate payments and transactions. While the publication system **142** and payment system **144** are shown in FIG. 1 to both form part of the networked system **102**, it will be appreciated that, in alternative embodiments, each system **142** and **144** may form part of a payment service that is separate and distinct from the networked system **102**. In some embodiments, the payment system **144** may form part of the publication system **142**.

(30) The image modification system **150** may provide functionality operable to perform various modifications to image capture modes and image parameters. The image modification system **150** may provide functionality operable to generate and present suggested instructions to guide manipulation of image capture publications, image parameters, and image composition. In some embodiments, the modifications performed by the image modification system **150** may be based on aspects of objects and backgrounds within a field of view of an image capture device, image characteristics of images depicting similar objects and published on the one or more publication systems **142**, or any other suitable information. For example, the image modification system **150** accesses publications and identifies images, image characteristics (e.g., image metadata), and descriptions within the publications. In some instances, portions of the image modification system

150 which identify images within publications on the one or more publication systems **142** may be stored at and part of the publication systems **142**. In some example embodiments, as referenced above and described in more detail below, the image modification system **150** may reside entirely on the client device **110**. In these embodiments, the client device **110** may query the one or more publication systems **142** or query an internal data structure to identify the publications and the images within the publications. The image modification system **150** may modify image parameters or image capture modes and generate and present suggestions for changes to image composition based on information gleaned from the publications. In some example embodiments, the image modification system **150** analyzes objects of interest, backgrounds, image capture parameters, and ambient characteristics to determine and perform modifications to one or more of an image capture mode and an image capture parameter. The image modification system **150** may also generate and cause presentation of suggestions and instructions for modification to image composition within the field of view of the image capture device based on the object of interest, backgrounds, and ambient characteristics.

(31) Further, while the client-server-based network architecture **100** shown in FIG. **1** employs a client-server architecture, the present inventive subject matter is of course not limited to such an architecture, and could equally well find application in a distributed, or peer-to-peer, architecture system, for example. The various publication system **142**, payment system **144**, and image modification system **150** could also be implemented as standalone software programs, which do not necessarily have networking capabilities.

(32) The web client **112** may access the various publication and payment systems **142** and **144** via the web interface supported by the web server **122**. Similarly, the programmatic client **116** accesses the various services and functions provided by the publication and payment systems **142** and **144** via the programmatic interface provided by the API server **120**. The programmatic client **116** may, for example, be a seller application (e.g., the Turbo Lister application developed by eBay® Inc., of San Jose, Calif.) to enable sellers to author and manage listings on the networked system **102** in an offline manner, and to perform batch-mode communications between the programmatic client **116** and the networked system **102**.

(33) Additionally, a third party application(s) **132**, executing on a third party server(s) **130**, is shown as having programmatic access to the networked system **102** via the programmatic interface provided by the API server **120**. For example, the third party application **132**, utilizing information retrieved from the networked system **102**, may support one or more features or functions on a website hosted by a third party. The third party website may, for example, provide one or more promotional, marketplace, or payment functions that are supported by the relevant applications of the networked system **102**.

(34) FIG. **2** is a block diagram illustrating components of the image modification system **150**, according to some example embodiments. The image modification system **150** is shown as including a receiver component **210**, a parameter component **220**, an identification component **230**, a characteristic component **240**, a notification component **250**, a presentation component **260**, a capture component **270**, a modification component **280**, and an authentication component **290**, all configured to communicate with one another (e.g., via a bus, shared memory, or a switch). Any one or more of the components described herein may be implemented using hardware (e.g., one or more processors of a machine) or a combination of hardware and software. For example, any component described herein may configure a processor (e.g., among one or more processors of a machine) to perform operations for which that component is designed. Moreover, any two or more of these components may be combined into a single component, and the functions described herein for a single component may be subdivided among multiple components. Furthermore, according to various example embodiments, components described herein as being implemented within a single machine, database(s) **126**, or device (e.g., client device **110**) may be distributed across multiple machines, database(s) **126**, or devices.

(35) The receiver component **210** receives a user interface selection (e.g., selection of a user interface element presented at a display device) initiating an image capture operation. The receiver component **210** may access publications within the client device **110** or in the one or more publication systems **142**. The receiver component **210** may access publications by direct access to a data structure or non-transitory processor-readable storage medium. The receiver component **210** may also access publications on a remote computing system, server, or database via a network connection.

(36) The parameter component **220** detects image capture parameters for an image capture device associated with the client device **110** and the objects and background within the field of view. The parameter component **220** may detect a setting or parameter of the image capture device, a lens arrangement, a color temperature, a white balance, a contrast setting, a filter setting, a focus element, an image capture mode, or any other suitable parameters of the image capture device. In some embodiments, the parameter component **220** determines parameters of image composition elements for the field of view. For example, the parameter component **220** may determine contrast values between portions of a background and an object of interest within the field of view. The parameter component **220** may also determine that various parameters are below or exceed threshold values.

(37) The identification component **230** identifies objects of interest within the field of view of the image capture device associated with the client device **110**. The identification component **230** may identify the objects of interest by parsing identifying information for the object of interest within a publication (e.g., a draft of a publication generated for inclusion in the one or more publication systems **142**). In some embodiments, the identification component **230** identifies objects of interest based on characteristics of the object of interest within the field of view of the image capture device associated with the client device **110**. The identification component **230** may identify the object of interest using one or more images or object recognition techniques. For example, the identification component **230** may use edge detection, object recognition, rigid point detection, shape recognition, or any other operation or set of operations configured to identify an object or a type or class of object within a field of view or an image.

(38) The characteristic component **240** identifies sets of characteristics for the image modification system **150**. In some instances, the characteristic component **240** identifies sets of object characteristics for an object within a field of view of the image capture device associated with the client device **110**. The characteristic component **240** may also identify characteristics of the image capture device and values or characteristics of image capture parameters used by the image capture device. In some instances, the set of characteristics includes color values, color temperatures, sizes, dimensions, contrast values, ISO speeds, shutter speeds, focus points, focal length values, pixel dimensions, and other characteristics.

(39) The notification component **250** generates notifications for the image modification system **150**. In some embodiments, the notification component **250** generates parameter notifications including suggested changes in parameters. In some instances, where the image modification system **150** dynamically and automatically changes image capture modes, the notification component **250** generates indications or alerts of the changes implemented by the image modification system **150**.

(40) The presentation component **260** causes presentation of various aspects of the image modification system **150**, including instructions, suggestions, parameter notifications, and modified images. In some embodiments, the presentation component **260** causes presentation of a field of view of an image capture device associated with the client device **110**. In some instances, the presentation component **260** causes presentation by transmitting data indicative of the images, notifications, fields of view, suggestions, or instructions to the client device **110**. In some instances, the presentation component **260** is implemented within the publication system **142** in the context of a web application, a server based application, or a client-side application **114** (e.g., all or a portion

of an application stored on the client device **110**).

(41) FIG. **3** is a flow chart of operations of the image modification system **150** in performing a method **300** of identifying and generating a set of modified images for a publication on a network-based publication system, according to some example embodiments. Operations in the method **300** may be performed by the image modification system **150**, using components described above with respect to FIG. **2**.

(42) In operation **310**, the receiver component **210** receives a user interface selection initiating an image capture. As shown in FIG. **4**, the user interface selection may represent a user interaction with a user interface element **410**. The receiver component **210** may receive the user interface selection from a user interface presented on an image capture device. In some embodiments, the user interface selection may be an interaction with an input device of the image capture device. For example, the user interface selection may be a tap (e.g., a temporary finger contact) on a touch screen, a press of a physical button (e.g., a button, a switch, a toggle, a wheel), a mouse click, or pressing a key on a keyboard (e.g., a physical keyboard or a virtual keyboard) to indicate a command. In some instances, in order to initiate an image capture, in response to the user interface selection, the image capture device opens or otherwise initiates an image capture application. In some embodiments, the user interface selection may be received within a user interface of an application for generating publications for storage and provision by the publication system **142**. In these embodiments, the initiation of the image capture may include changing modes within the publication generation application to an image capture mode, temporarily switching from the publication generation application to an image capture application (e.g., performed automatically by the image capture device and reverting back to the publication generation application after capture of an image), or any other suitable manner of initiating a set of image capture operations.

(43) In operation **320**, the parameter component **220** detects a first image capture parameter. The parameter component **220** may detect the first image capture parameter as a setting or parameter of the image capture device or a camera or lens arrangement of the image capture device. The first image capture parameter may be an adjustable setting or parameter of the image capture device (e.g., a parameter adjustable in either hardware or software associated with the image capture device). The first image capture parameter may be a white balance, a color temperature setting, a contrast setting, a color filter setting, a lens effect setting, a focus setting, or a mode (e.g., indoors, sunny day, night, or candlelight) setting indicating a predetermined arrangement of parameter values for the image capture device. Although described with respect to specified parameters or settings, it should be understood that the first image capture parameter may be any parameter which may be modified for the image capture device prior to or during an image capture process.

(44) The first image capture parameter may be detected in response to operation **310**. In some instances, the parameter component **220** detects the first image capture parameter by accessing one or more settings of the image capture device, one or more parameter of software associated with the image capture device, one or more parameter of an image sensor associated with the image capture device, one or more parameter of a lens associated with the image capture device, combinations thereof, or any other parameter or setting. The parameter component **220** may detect the first image capture parameter by accessing metadata for hardware (e.g., the lens or the image sensor) associated with the image capture device or metadata for the software associated with the image capture device. In some embodiments, the metadata may be static (e.g., hardware configuration data) associated with the image capture device. In some instances, the metadata is dynamic, generated or otherwise set upon initiation of the operation **310**.

(45) In operation **330**, the identification component **230** identifies an object of interest within a field of view of the image capture device. As shown in FIG. **4**, the object of interest **420** may be identified and highlighted with an interest element **430**. The interest element **430** may be a user interface element generated to highlight, point to, encompass, or otherwise indicate the object of interest **420**. The identification component **230** may identify the object of interest **420** based on any

suitable operations. For example, the identification component **230** may identify the object of interest **420** based on one or more focus operations, one or more object recognition (e.g., pattern matching) operations, one or more edge detection operations, or any other suitable method. By way of further example, in some instances, the identification component **230** may identify an object of interest based on a position of the object of interest within a field of view of the image capture device. In these embodiments, an object positioned proximate to a center of the field of view may be prioritized as the object of interest. In some example embodiments, the identification component **230** may generate an object notification highlighting or outlining an identified object of interest. The object notification may request confirmation of the object of interest based on selection of the object of interest through a user interaction with a graphical user interface causing presentation of the object notification. In some instances, the identification component **230** identifies the object of interest and may receive a user interface selection indicating a change in the object of interest to identify a different object of interest within the field of view.

(46) As referenced above, the identification component **230** may also identify an object of interest based on edge detection of objects or portions of objects within the field of view. The identification component **230** may identify one or more edges within the field of view and perform one or more focus operations to sharpen at least a portion of the one or more edges. Once the edges have been sharpened, the identification component **230** may identify the object of interest based on the object's position within the field of view, completeness of the edges of the object (e.g., edges forming a completed perimeter), contrast between the object and a background, or any other suitable operations. In identifying the object of interest based on contrast, the identification component **230** may select the object of interest based on a comparison of the edges, and one or more colors within the edges, to a background within the field of view. This comparison of the edges and colors to the background may identify the object of interest based on a contrast of the edges and the colors exceeding a predetermined contrast threshold with respect to the background.

(47) In some instances, the presentation component **260** causes presentation of the field of view of the image capture device and enables selection of the object of interest based on a user interface interaction (e.g., clicking on an area of the field of view which contains the object of interest). The identification component **230** may identify a preliminary object of interest and the notification component **250** may generate a user interface element to highlight, delimit, encompass, or point to the preliminary object of interest. The selection of the object of interest within the field of view, by a user interaction with a user interface, may cause confirmation of the preliminary object of interest or change a designation of the object of interest to another portion of the field of view.

(48) In operation **340**, the characteristic component **240** identifies a set of object characteristics of the object of interest. In some embodiments, the set of object characteristics includes a color value (e.g., a set of color values, a single color value, or an average color value), a color temperature, a size, a set of dimensions, and a contrast value between the object of interest (e.g., at least a portion of the object of interest) and a background positioned behind or surrounding the object of interest. The characteristic component **240** may identify the set of object characteristics by extracting or retrieving values present in the field of view of the image capture device. For example, the characteristic component **240** may identify color values and color temperatures based on color values or color temperature values for pixels identified within the object of interest. The contrast value may be identified by the characteristic component **240** based on comparison of the color values of one or more pixels representing the object of interest with color values of one or more pixels representing the background. In some embodiments, the characteristic component **240** may determine estimated dimensions or the size of the object of interest based on pixel measurements extending between pixels identified as representing at least a portion of the object of interest in order to define boundaries of the object of interest to identify contrast values between the object of interest and the background.

(49) In operation **350**, the notification component **250** generates a parameter notification indicating

a suggested modification of the first image capture parameter. The notification component **250** may generate the parameter notification based on the set of object characteristics of the object of interest and the first image capture parameter. In some example embodiments, to generate the parameter notifications, the notification component **250** determines a number and type of potential notifications based on the object characteristics included in the set of object characteristics and one or more parameter values included in the first image capture parameter. For example, based on the set of object characteristics and the first image capture parameter, the notification component **250** may identify a contrast value between the object of interest and the background, a size or dimension of the object of interest, a white balance for the image capture device, and a focus value for the image capture device as types of parameters for a potential notification. Each of the object characteristics and the first image capture parameter may correspond to a potential notification. In response to identifying the number and type of potential notifications, the notification component **250** identifies values associated with each of the object characteristics and the first image parameter and determines whether the value is suitable for the image. Where the value is unsuitable for an image, the notification component **250** generates a parameter notification for that object characteristic or the image parameter. For example, where a portion of the object of interest extends outside the field of view, the notification component **250** may identify the dimensions of the object of interest as exceeding the field of view and select a parameter notification for the object characteristic (e.g., the dimension of the object of interest). By way of a further example, where the object characteristic is a contrast value between the object of interest and the background and the image capture parameter is a white balance, the notification component **250** identifies whether the contrast value is within an acceptable range (e.g., exceeds a predetermined threshold contrast) and generates a parameter notification for adjustment of the white balance to cause a change in the contrast value, modifying the contrast value to be within the acceptable range or below a predetermined threshold.

(50) As shown in FIG. 5, the parameter notification **510** may include instructions **520** and a user interface element **530** for executing the instructions **520**. The modification of the first image capture parameter may cause one or more of the set of object characteristics to change within an image captured by the image capture device. The parameter notification **510** may include one or more user interface elements selectable to modify the first image capture parameter. In some embodiments, the notification component **250** generates the parameter notification **510** as indicating a suggested change in a white balance of the image capture device. The notification component **250** may indicate the suggested change by inserting a white balance value in the parameter notification **510** and generating the parameter notification **510** as a pop-up or overlay window to be displayed over a presentation of the field of view of the image capture device.

(51) In some instances, the notification component **250** indicates the suggested change by inserting the white balance value and generating the user interface element **530**. The user interface element **530** may be a white balance adjustment element. In these embodiments, the white balance adjustment element may be a text entry field, a slider, a wheel, or another suitable data entry element. The white balance adjustment element may be initially set to a current white balance. In some instances, the suggested white balance value may be generated and included in the parameter notification **510** as a position on the white balance adjustment element (e.g., a tick mark for a position on the slider or the wheel).

(52) The notification component **250** may generate the parameter notification **510** in response to receiving one or more values associated with the set of object characteristics from the characteristic component **240**. In these embodiments, one or more of the characteristic component **240** and the notification component **250** may determine that an object characteristic value of the set of object characteristics is below a predetermined characteristic threshold or is unexpected or incorrect. The object characteristic value may be associated with and affected by the first image capture parameter. For example, as described above, the object characteristic may be a color of the object

of interest and the first image capture parameter may be a current white balance of the image capture device. Based on the object of interest and one or more objects, colors, or color temperatures within the field of view of the image capture device, the characteristic component **240** may determine that the white balance is below a predetermined white balance value (e.g., the predetermined characteristic threshold) configured to accurately depict colors (e.g., object characteristics) within the field of view in a captured image. For example, one or more of the contrast, the color, or the color temperatures may have a value different than an expected value, based on an existing publication, image, or product. The characteristic component **240** may determine a change in white balance value resulting in a modification of the contrast, color, or color temperature to match the expected value. Where the white balance value is below the predetermined white balance value, the characteristic component **240** may pass to the notification component **250** the predetermined white balance value, an indication of a corrected white balance value (e.g., a white balance value to accurately depict the colors in a captured image), or an amount of white balance value adjustment (e.g., an amount by which the white balance value should be increased or decreased). In some instances, the notification component **250** may be passed values for each of the object characteristics of the set of object characteristics and determine whether any of the object characteristics fall below specified or determined thresholds, warranting a change and generation of a notification.

(53) In operation **360**, the presentation component **260** causes presentation of the parameter notification. As shown in FIG. 5, the parameter notification **510** may be presented within the depiction of the field of view of the image capture device. The parameter notification **510** may be presented as an overlay; in a distinct portion of the field of view, such that the parameter notification **510** does not obstruct the object of interest; in a window; or in any other suitable manner. The presentation component **260** may cause presentation by rendering the parameter notification **510** on an output device associated with the image capture device. In some instances, the presentation component **260** may cause presentation by transmitting data indicative of the parameter notification **510** to an output device which is connected to the image capture device by a wired or wireless connection. The data may be transmitted via wired or wireless network (e.g., the network **104**).

(54) In operation **370**, the image modification system **150** captures an image and formats the image for publication on the publication system **142**. As shown in FIG. 6, the image **610** may be formatted and presented within the field of view as modified by the image modification system **150**. The image modification system **150** may capture the image based on receiving a change in one or more parameter values. For example, after receiving the change in the first image capture parameter via the white balance adjustment element, the image modification system **150** may enable selection of an image capture element. The selection may be enabled by activating a user interface element, such as by rendering the user interface element, enabling selection (e.g., removing an overlay or a grayed out status) of the user interface element, or any other suitable user interface enablement operations. Upon receiving selection of the image capture element, the image capture device may capture the image of the object of interest within the field of view.

(55) In some embodiments, the operation **370** may be performed by the capture component **270** using a series of sub-operations. The capture component **270** may receive a capture selection indicating interaction with the image capture element to cause capture of an image by the image capture device. For example, the capture component **270** may receive a click of a camera button on the user interface.

(56) The identification component **230** may determine dimensions of the captured image. After the image is captured, the identification component **230** may determine the dimension of the captured image as the total pixel count of the image (e.g., eight megapixels (MP)), the pixel height and width (e.g., 3264 pixels by 2448 pixels), the translated height and width in physical units of measurement (e.g., inches or centimeters), or any other suitable dimensions. The identification

component **230** may determine the dimensions based on metadata associated with the captured image, image data from the captured image, or characteristics of a file into which the captured image has been stored.

(57) In response to determining the dimensions of the captured image, the identification component **230** may determine whether the dimensions of the captured image exceeds a predetermined dimension threshold. The predetermined dimension threshold may be a predetermined length and a predetermined width for images, a diagonal measurement for an image, a predetermined pixel count, or any other suitable dimension for an image. Where the predetermined dimension threshold is exceeded, the modification component **280** may modify the dimensions of the captured image to be within the predetermined dimension threshold and generate a modified image. The modification component **280** may modify dimensions of the captured image while maintaining an aspect ratio for the captured image. In some embodiments, the publication system **142** or an application (e.g., website or smartphone application) associated with the publication system **142** may include a threshold for dimensions of images included in a publication stored within the publication system **142**. For example, the threshold may be a three MP threshold indicating that images in a specified publication may be displayed in the application when sized below three MP. The modification component **280** may reduce the dimensions of the captured image to meet or fall below the predetermined dimension threshold. The modification component **280** may perform any suitable image reduction technique to reduce the dimensions of the captured image. In some instances, the modification component **280** may select from a set of image reduction techniques to prioritize image reduction having the least reduction in image quality, accuracy, or color representation of the available image reduction techniques.

(58) FIG. 7 is a flow chart of operations of a method **700** of the image modification system **150** in performing the operations **340** and **350** for modifying image capture device settings to generate accurate images, according to various example embodiments of the present disclosure. The method **700**, depicted in FIG. 7, may be performed by the image modification system **150** using components described above with respect to FIG. 2.

(59) In operation **710**, the receiver component **210** accesses a publication within the image capture device. The receiver component **210** may access the publication in the image capture device based on an association with the object of interest. The association between the publication and the object of interest may be determined from the image or may be determined based on user interaction with the image capture device.

(60) Where the association between the publication and the object of interest is determined from the image, the identification component **230** may identify the set of object characteristics, as described above. The set of object characteristics may include identifying information. For example, the set of object characteristics identified by the identification component **230** may include a name, a description, a serial number, or other identifying information visible on the surface of the object of interest. The identification component **230** may parse the identifying information from the field of view of the image capture device using text recognition operations. Once identifying information has been determined by the identification component **230**, the receiver component **210** may receive the identifying information and access the publication based on a match between one or more portions of the identifying information and a publication or portion of a publication stored on the image capture device. In some embodiments, the receiver component **210** may attempt to match publications which are listed as pending, incomplete, or in a draft state.

(61) Where the association between the publication and the object of interest is indicated based on user interaction with the image capture device, the image capture device may initially be set in a publication generation mode. In the publication generation mode, a publication may be opened in an editable format. Data may be entered into the publication to generate or modify the publication. The publication generation mode may be provided with an image capture element. The image

capture element may be a selectable user interface element that, when selected, causes the image capture device to access the image modification system **150**. In these embodiments, the receiver component **210** may access the publication in order to retrieve identifying or descriptive information.

(62) In operation **720**, the identification component **230** parses the publication to identify text description associated with the object of interest. Once the text description is accessed, the identification component **230** accesses or extracts identifying and descriptive information from the publication. The identification component **230** may use predetermined keywords or values to parse the publication for description information. For example, the identification component **230** may identify text within portions of the publication which have predetermined titles or metadata tags. In these instances, the identification component **230** may parse the publication for section titles (e.g., title, description, size, color, or item specifics). The identification component **230** may also parse the publication for predetermined keywords of a set of descriptive or identifying keywords. For example, the identification component **230** may be provided with a list of colors, dimensions, textures, item types (e.g., car, shirt, or smartphone) and parse the description for words matching the predetermined keywords or semantically related thereto.

(63) In operation **730**, the identification component **230** identifies the set of object characteristics from the text description within the publication. The identification component **230** may extract color information, dimension information, item type information, and information capable of identifying the object of interest (e.g., serial numbers, titles, or manufacturers). The identification component **230** may incorporate the extracted data into the set of object characteristics for use in the method **300** described above.

(64) In operation **740**, the receiver component **210** accesses a set of publications within the publication system **142**. The receiver component **210** may access portions of the descriptive information to access the set of publications of the publication system **142** to identify publications representing items or objects similar to the object being described in the publication being generated. The operation **740** may be performed prior to or after an image has been captured. In some embodiments, the operation **740** may be performed while the image capture device is in the publication generation mode. In these embodiments, the operation **740** may be performed in response to a publication being generated and provided with descriptive information.

(65) In operation **750**, the identification component **230** identifies a set of image parameters for images within the set of publications. The identification component **230** may parse the set of publications within the publication system **142** to identify images within the set of publications. The identification component **230** may then identify image parameters associated with the images of the set of publications. The set of image parameters may be identified from metadata associated with the set of publications, image metadata associated with the images, or description data stored within the set of publications. The set of image parameters may include image dimensions, contrast values, color values, white balance values, a color temperature value, or any other suitable parameters used by an image capture device in capturing or processing an image.

(66) In operation **760**, the notification component **250** determines one or more of the image parameters to include in the parameter notification. The notification component **250** may determine the one or more image parameters to include based on the set of image parameters or based on the publications. Where the notification component **250** determines the one or more image parameters for inclusion based on the image parameters, the notification component **250**, alone or in conjunction with one or more other components described herein, may determine an accuracy value for the image parameters associated with each of the publications of the set of publications. The notification component **250** may include the one or more image parameters determined to have the highest accuracy value. Determination of accuracy values will be described in more detail below with respect to FIG. **13**.

(67) Where the notification component **250** determines the one or more image parameters for

inclusion based on the publications of the set of publications, the notification component **250** may determine one or more favorability characteristics of the set of publications. In some embodiments, the favorability characteristics include one or more of a number of page views for the publication, a frequency of views for a specified period of time, a set of ratings for the publication, or other characteristics. In some instances, where the publication is an item listing being offered for sale on a website, the favorability characteristics may also include a sale price of the item, a number of watchers (e.g., users saving the publication into a watch list for later viewing), a number of bids, a number of sales where the publication represents a plurality of items, a feedback score, or any other suitable characteristic. The notification component **250** may include the one or more image parameters of the publication having the highest number of favorability characteristics, a higher favorability score generated from the favorability characteristics, or an indication of the highest accuracy for the images included within the publication. For example, the notification component **250** may determine a number of comments or ratings for the publication or the user associated with the publication relating to the accuracy of the images (e.g., the item being as pictured or described). The notification component **250** may then use the publication which has the greatest number of comments or ratings related to accuracy.

(68) FIG. **8** is a flow chart of operations of a method **800** of the image modification system **150** in performing the operation **350** for modifying image capture device settings to generate accurate images, according to various example embodiments of the present disclosure. The method **800**, depicted in FIG. **8**, may be performed by the image modification system **150**, using components described above with respect to FIG. **2**.

(69) In operation **810**, the notification component **250** generates a set of preview images. As shown in FIG. **9**, the set of preview images **910** may be generated with differing parameter values and presented proximate to one another. Each preview image of the set of preview images may be generated with a different image capture parameter of the set of image capture parameters. In some instances, the set of preview images may be positioned in an ordered manner based on the image capture parameters. For example, in some instances, the notification component **250** may generate six preview images in a grid pattern having three columns and two rows of images. The notification component **250** may arrange the set of preview images such that an image in a first column and a first row has a white balance value (e.g., an image capture parameter) having the lowest value. Each image may have a progressively higher white balance value (e.g., image capture parameter) such that the preview image positioned in the third column of the second row has the highest value for the white balance (e.g., image capture parameter).

(70) In operation **820**, the notification component **250** generates a set of image capture representations indicating image capture parameters of the set of image capture parameters. As shown in FIG. **9**, the set of image capture representations **920** may be presented proximate to a preview image generated using the image capture parameter. The image capture representations may be a set of numbers indicating a single image capture parameter or a plurality of image capture values. For example, the set of image capture representations may be a numerical value for the white balance used in generating the preview image. The image capture representations may also be a set of sliders, a set of wheels or dials, or any other suitable representation. In some embodiments, one or more of the set of image capture representations may be overlaid on the preview image to which the image capture representation or representations correspond. In these embodiments, the image capture representation may be positioned on the preview image in a position such that the object of interest remains unobstructed. In some instances, the image capture representations may be positioned in a separate portion of a notification represented by a differing portion of a display device.

(71) In operation **830**, the notification component **250** associates the set of preview images with the set of image capture representations, with each preview image including an image capture representation indicating the image capture parameter used to generate the preview image. The

association of a preview image with an image capture representation or set of image capture representations may cause the notification component **250** to present the image capture representation proximate to or within a border of the preview image with which it is associated.

(72) FIG. **10** is a flow chart of operations of the image modification system **150** in performing a method **1000** of identifying and generating a set of modified images for publication on a network-based publication system, according to some example embodiments. The operations depicted in FIG. **10** may be performed by the image modification system **150**, using components described above with respect to FIG. **2**. In some instances, as shown in FIG. **10**, the method **1000** may be performed as a part of the methods **300** or **700** or may be performed as a set of sub-operations of one or more of the operations described in the methods **300** and **700**.

(73) In operation **1010**, the identification component **230** identifies a background behind the object of interest. In some instances, the operation **1010** may be performed after one or more of the operation **330** or **340**, where the object of interest and the object characteristics have been identified. The background may be identified as a portion of the field of view which surrounds the object of interest, in whole or in part. The identification component **230** may identify the background using edge detection operations, shape detection operations, color identification operations, or any other recognition operations suitable to identify the background.

(74) In operation **1020**, the parameter component **220** determines a contrast value between at least a portion of the object of interest and at least a portion of the background. In some embodiments, the parameter component **220** determines one or more of a hue, a tint, a saturation, and a luminance value for each of the background and the object of interest. The parameter component **220** then determines a contrast value between the object of interest and the background. The contrast value may be a numerical or graphical representation of the contrast between colors or other values of the object of interest and the background.

(75) In operation **1030**, the parameter component **220** determines that a minimum contrast threshold exceeds the contrast value. For example, the contrast value may be below the minimum contrast threshold. The minimum contrast threshold may represent a numerical or graphical value at which colors or other values of the object of interest become indistinguishable or otherwise unsuitable with respect to the background or other values of the object of interest. The parameter component **220** may determine that the minimum contrast threshold exceeds the contrast value by comparing values (e.g., numerical or graphical) of the contrast value and the minimum contrast threshold. In some instances, the parameter component **220** may perform one or more image analysis techniques (e.g., edge detection, shape detection, or color detection) to determine whether the minimum contrast threshold exceeds the contrast value. For example, where the minimum contrast threshold exceeds the contrast value, one or more edges of the object of interest may not be distinguishable within the field of view or a captured image.

(76) In operation **1040**, the notification component **250** generates an image notification indicating a suggested modification to the background behind the object of interest. Operation **1040** may be performed in response to the parameter component **220** determining the contrast value is below the minimum contrast threshold. In some instances, the suggested modification may indicate a change in one or more image capture parameters. The suggested modification may indicate a change in the background. For example, the notification component **250** may generate text instructing the user to replace the current background with a differing background.

(77) In some embodiments, the operation **1040** may comprise a set of sub-operations. In some instances, in performing the operation **1040**, the identification component **230** identifies a color of the background. The color may be identified by a color value for pixels of the background, a hue value, a saturation value, a luminance value, combinations thereof, or any other suitable value. In some instances the identification component **230** identifies the color of the background by parsing pixels, of the field of view or the captured image, associated with the background and extracting color values of the pixels.

(78) The identification component **230** may then identify an alternate color. The alternate color may have a contrast value in relation to the object of interest which exceeds the minimum contrast threshold. For example, where the object of interest is primarily dark blue and the background is black, dark brown, or dark blue, the identification component **230** may identify yellow, light gray, beige, or another suitable alternate color having a higher contrast with the object of interest. In some instances, the identification component **230** may determine a plurality of colors for the object of interest and identify the alternate color such that differentiation among the plurality of colors and between the plurality of colors and the background has a suitable contrast value.

(79) The notification component **250** may then generate an indication of the alternate color as the suggested modification to the background. The notification component **250** may generate text suggesting that a background of the alternate color be positioned under or behind the object of interest. In some embodiments, in addition to the text, the notification component **250** may generate one or more color block (e.g., rectangular, oblong, square, or circular) with user interface elements matching the alternate color or a set of alternate colors to enable visual confirmation of an alternate color corresponding to the suggestion.

(80) In operation **1050**, the presentation component **260** causes presentation of the image notification at the image capture device. The presentation component **260** may cause presentation by rendering the notification as a window (e.g., a pop up or overlay) over the captured image, the preview image, or the field of view of the image capture device represented on the display device. In some instances, the presentation component **260** may transmit data representing the image notification to a client device for rendering on the display device for the user.

(81) FIG. **11** is a flow chart of operations of the image modification system **150** in performing operations of a method **1100** of identifying and generating a set of modified images for a publication on the publication system **142**, according to various example embodiments. Shown in FIG. **11** is a set of operations which may be performed as part of the method **300** or **700** or as a set of sub-operations of one or more of the operations described in the method **300** or **700**.

(82) In operation **1110**, the identification component **230** determines a position of the object of interest within the field of view of the image capture device. In some instances, the identification component **230** determines the position of the object of interest as a position within the field of view of the image capture device. The identification component **230** may determine the position of the object of interest based on a distance of one or more portions of the object of interest from one or more edges of the field of view. For example, the position may be determined by calculating a pixel distance or other distance from one or more edges (e.g., the one or more portions of the object of interest) to the one or more edges of the field of view. The identification component **230** may determine the position based on one or more pixels representing the object of interest. The identification component **230** may also determine the position based on a grid determined for the field of view. For example, the identification component **230** may partition the field of view of the image capture device into a set of boxes in a grid pattern. The position of the object of interest may be determined as one or more specified boxes in which pixels representing the object of interest are located.

(83) In some embodiments, the identification component **230** may perform the operation **1110** using one or more sub-operations. In some instances, in operation **1112**, the identification component **230** identifies at least a portion of a perimeter of the object of interest within the field of view of the image capture device. The identification component **230** may perform one or more object recognition operations to identify the portion of the perimeter. In some embodiments, the identification component **230** determines a position of the object of interest (e.g., a position of the perimeter) using edge matching techniques (e.g., edge detection, Canny edge detection), grayscale matching, gradient matching, interpretation trees, pose consistency, pose clustering, invariance, geometric hashing, scale-invariant feature transform, speed up robust features, or genetic algorithms. In some instances, the identification component **230** determines edges or other features

of the object of interest and identifies the position within the field of view of the image capture device. Edges of the object of interest identified by the identification component **230** may form the perimeter or portion of the perimeter of the object of interest.

(84) In operation **1114**, the identification component **230** determines whether a portion of the perimeter of the object of interest extends beyond the field of view of the image capture device. Once the object of interest is identified, the identification component **230** may determine the position of the object of interest as described above. For each of the edges of the object of interest, the identification component **230** determines whether a portion of the edge intersects an edge of the field of view. Where an edge of the object of interest intersects an edge of the field of view, the identification component **230** identifies the edge as extending beyond the field of view. After determining that the perimeter of the object of interest extends beyond the field of view, the identification component **230** determines the position of the object of interest, as described above. In some instances, based on the edges of the object of interest and the portion of the perimeter extending beyond the field of view, the identification component **230** determines that a portion of the object of interest is outside of the field of view.

(85) In operation **1120**, the notification component **250** generates a position notification indicating a suggested modification to the position of the object of interest within the field of view of the image capture device. As shown in FIG. **12**, the position notification **1210** may be generated with instructions **1220** suggesting a modification of the position of the object of interest **1230**. The position notification includes one or more user interface elements indicating a suggested position of the object of interest. The notification component **250** may generate a user interface element such as a dialog box, a window, or a text overlay. The user interface element may include a textual or graphical representation indicating that a portion of the object of interest is outside of the field of view. In some embodiments, the user interface element includes a movement direction for the object of interest, indicating a direction in which the object of interest or the image capture device should be moved to position the object of interest within the field of view of the image capture device. The movement direction may be a relative direction in terms of the image capture device (e.g., right, left, up, or down). In some instances, where portions of the perimeter of the object of interest extend out of the field of view at more than one edge of the field of view, the movement direction may indicate a zoom direction (e.g., zoom out) or relative direction of the image capture device (e.g., move back) sufficient to decrease the apparent size of the object of interest to orient the perimeter of the object of interest within the field of view of the image capture device.

(86) In some embodiments, the position notification includes a graphical indication of the perimeter or a portion of the perimeter. The position notification may also include a graphical indication of a portion of the edge of the field of view intersecting the edge of the object of interest. For example, the position notification may include a highlighted outline of the perimeter of the object of interest and a highlighted portion of the edge of the field of view intersected by the perimeter of the object of interest.

(87) In operation **1130**, the presentation component **260** causes presentation of the position notification at the image capture device. The presentation component **260** may cause presentation of the position notification by rendering the position notification on a display device (e.g., an output device, a screen, or a touch screen) of the image capture device, associated with the image capture device, or in communication with the image capture device. For example, where the image capture device is a mobile computing device, such as a mobile telephone, the presentation component **260** may render the position notification on a touch screen of the mobile computing device. In some instances, the position notification is rendered on the display device in combination with a representation of the field of view (e.g., a preview image or a cached image). The position notification may be presented as an overlay depicted on the representation of the field of view, such as an overlay or window.

(88) FIG. **13** is a flow chart of operations of the image modification system **150** in performing a

method **1300** of modifying publications within the publication system **142**, according to some example embodiments. Operations of the method **1300** may be performed by the image modification system **150**, using components described above with respect to FIG. 2.

(89) In operation **1310**, in response to capturing the image, the authentication component **290** determines one or more image characteristics modified prior to capture of the image. The image characteristics may be a contrast, a color temperature, or any other suitable image characteristic. The image characteristics may be modified based on the characteristics of the object of interest and may have been modified based on a notification generated by the image modification system **150**, as described above.

(90) In operation **1320**, the authentication component **290** determines a contrast value between the object of interest and the background depicted within the image. The contrast value may be determined as described with respect to the operation **340**. In some instances, the contrast value may be an image characteristic modified by the image modification system **150**.

(91) In operation **1330**, the authentication component **290** determines one or more image characteristics of images within a set of publications on the publication system **142**. In some instances, where the image modification system **150** modifies captured images or image characteristics based on a publication associated with the object of interest, the authentication component **290** identifies the set of publications stored on the database **126** of the publication system **142**. The authentication component **290** may identify the set of publications based on a search of the database **126**, generated from keywords associated with the object of interest and contained in the publication, stored on the image capture device, or otherwise associated with the object of interest. The set of publications identified by the authentication component **290** may be publications which depict and describe objects of interest similar to the object of interest in the captured image modified by the image modification system **150**.

(92) The authentication component **290** determines the one or more image characteristics by parsing data and metadata for the images contained in the identified set of publications. The one or more image characteristics may be included within the images or within metadata describing the images. For example, the authentication component **290** may determine the one or more image characteristics as a color temperature and a contrast value between an object of interest depicted within an image and a background positioned behind the object of interest. The contrast value may be determined based on pixel values for the object of interest in the image and the background, and the color temperature may be included within image metadata.

(93) In operation **1340**, the authentication component **290** determines an accuracy value for the captured image. The accuracy value may be determined based on the one or more image characteristics of the images contained within the set of publications identified by the authentication component **290**. For example, where each publication of the set of publications contains a color temperature and a contrast value between the background and an object of interest, the authentication component **290** may determine an average color temperature value for the color temperatures of the set of publications and an average contrast value for the contrast values of the set of publications. The accuracy value may be a difference between the one or more image characteristics of the captured image and the averaged one or more image characteristics of the set of publications. For example, the authentication component **290** may determine a color temperature difference between the average color temperature value and the color temperature of the captured image and a contrast difference between the average contrast value and the contrast value for the captured image. In these instances, where the accuracy value is lower, the one or more image characteristics of the captured image are similar to the one or more image characteristics of the set of publications. Although an example has been described in which a lower value indicates accuracy, it should be understood that the accuracy value may be calculated in a manner that yields a higher value for comparatively more accurate image characteristics.

(94) In operation **1350**, based on the accuracy value, the authentication component **290** generates

an accuracy watermark and modifies the captured image to include the accuracy watermark. The authentication component **290** may generate the accuracy watermark where the accuracy value exceeds an accuracy threshold. In some instances, the accuracy threshold may be a predetermined accuracy value below which the one or more image characteristics of the captured image are accurate with respect to the set of publications. In these instances, exceeding the accuracy threshold indicates that the accuracy value is lower than the accuracy threshold. In embodiments where a higher accuracy value indicates a more accurate captured image, exceeding the accuracy threshold may occur where the accuracy value is greater than the accuracy threshold. The accuracy watermark may be a visible graphical representation generated and incorporated into the captured image, generating a modified captured image. In some instances, the accuracy watermark may be generated as metadata associated with the captured image. Where the accuracy watermark is metadata, the accuracy watermark may be included in preexisting metadata describing the captured image, or generated as separate metadata to be associated with the captured image. Inclusion of the accuracy watermark depicted within a captured image or stored in metadata associated with a captured image, may indicate that the settings and parameters with which the image was captured generate a captured image which is an accurate representation of the characteristics (e.g., size, colors, and color temperatures) of the object of interest within the captured image. In this way, the accuracy watermark may indicate to an observer that the object of interest is accurately portrayed in the captured image as it would appear in person. The accuracy watermark may also indicate that no image filters were used in generating the captured image which would cause the object of interest to appear differently in the captured image than in person.

(95) According to various example embodiments, one or more of the methodologies described herein may facilitate modifying image capture modes and image capture parameters to generate accurate images based on identified objects of interest within a field of view of an image capture device. One or more methodologies described herein may also generate and cause presentation of instructions or suggestions to guide a user in modifying image capture modes, image capture parameters, or image composition elements to generate accurate images based on the identified objects. Methodologies described herein may also facilitate modification, automatically or manually, of the image capture modes, image capture parameters, and image composition based on similarities to images included in network-based publications having a determined qualitative and quantitative value. Accordingly, one or more of the methodologies described herein may have the effect of allowing a user to generate quality, accurate images which are supported by an objective accuracy assessment for use in online publications and other transmission or publication.

(96) As a result, one or more of the methodologies described herein may reduce or eliminate a need for certain efforts or resources that otherwise would be involved in determining and setting image capture modes, image capture parameters, and image composition to generate accurate depictions of objects within an image. Efforts expended by a user in identifying and replicating accurate images based on network-based publications are reduced, and accuracy may be more quantitatively determined based on the image parameters not presented to the user (e.g., stored in metadata or hidden from the user) when viewing network-based publications. Examples of computing resources which may be reduced by the presented methodologies of the present disclosure include processor cycles, network traffic, memory usage, data storage capacity, power consumption, and cooling capacity. Specifically, computing resources used by machines, being directed by interactions of a user, to search for network-based publications and images or to recapture inaccurate images may be reduced or eliminated.

Modules, Components, and Logic

(97) Certain embodiments are described herein as including logic or a number of components, modules, or mechanisms. Components may constitute either software components (e.g., code embodied on a machine-readable medium) or hardware components. A “hardware component” is a tangible unit capable of performing certain operations and may be configured or arranged in a

certain physical manner. In various example embodiments, one or more computer systems (e.g., a standalone computer system, a client computer system, or a server computer system) or one or more hardware components of a computer system (e.g., a processor or a group of processors) may be configured by software (e.g., an application or application portion) as a hardware component that operates to perform certain operations as described herein.

(98) In some embodiments, a hardware component may be implemented mechanically, electronically, or any suitable combination thereof. For example, a hardware component may include dedicated circuitry or logic that is permanently configured to perform certain operations. For example, a hardware component may be a special-purpose processor, such as a Field-Programmable Gate Array (FPGA) or an Application Specific Integrated Circuit (ASIC). A hardware component may also include programmable logic or circuitry that is temporarily configured by software to perform certain operations. For example, a hardware component may include software executed by a general-purpose processor or other programmable processor. Once configured by such software, hardware components become specific machines (or specific components of a machine) uniquely tailored to perform the configured functions and are no longer general-purpose processors. It will be appreciated that the decision to implement a hardware component mechanically, in dedicated and permanently configured circuitry, or in temporarily configured circuitry (e.g., configured by software) may be driven by cost and time considerations.

(99) Accordingly, the phrase “hardware component” should be understood to encompass a tangible entity, be that an entity that is physically constructed, permanently configured (e.g., hardwired), or temporarily configured (e.g., programmed) to operate in a certain manner or to perform certain operations described herein. As used herein, “hardware-implemented component” refers to a hardware component. Considering embodiments in which hardware components are temporarily configured (e.g., programmed), each of the hardware components need not be configured or instantiated at any one instance in time. For example, where a hardware component comprises a general-purpose processor configured by software to become a special-purpose processor, the general-purpose processor may be configured as respectively different special-purpose processors (e.g., comprising different hardware components) at different times. Software accordingly configures a particular processor or processors, for example, to constitute a particular hardware component at one instance of time and to constitute a different hardware component at a different instance of time.

(100) Hardware components can provide information to, and receive information from, other hardware components. Accordingly, the described hardware components may be regarded as being communicatively coupled. Where multiple hardware components exist contemporaneously, communications may be achieved through signal transmission (e.g., over appropriate circuits and buses) between or among two or more of the hardware components. In embodiments in which multiple hardware components are configured or instantiated at different times, communications between such hardware components may be achieved, for example, through the storage and retrieval of information in memory structures to which the multiple hardware components have access. For example, one hardware component may perform an operation and store the output of that operation in a memory device to which it is communicatively coupled. A further hardware component may then, at a later time, access the memory device to retrieve and process the stored output. Hardware components may also initiate communications with input or output devices, and can operate on a resource (e.g., a collection of information).

(101) The various operations of example methods described herein may be performed, at least partially, by one or more processors that are temporarily configured (e.g., by software) or permanently configured to perform the relevant operations. Whether temporarily or permanently configured, such processors may constitute processor-implemented components that operate to perform one or more operations or functions described herein. As used herein, “processor-implemented component” refers to a hardware component implemented using one or more

processors.

(102) Similarly, the methods described herein may be at least partially processor-implemented, with a particular processor or processors being an example of hardware. For example, at least some of the operations of a method may be performed by one or more processors or processor-implemented components. Moreover, the one or more processors may also operate to support performance of the relevant operations in a “cloud computing” environment or as a “software as a service” (SaaS). For example, at least some of the operations may be performed by a group of computers (as examples of machines including processors), with these operations being accessible via a network (e.g., the Internet) and via one or more appropriate interfaces (e.g., an Application Program Interface (API)).

(103) The performance of certain of the operations may be distributed among the processors, not only residing within a single machine, but deployed across a number of machines. In some example embodiments, the processors or processor-implemented components may be located in a single geographic location (e.g., within a home environment, an office environment, or a server farm). In other example embodiments, the processors or processor-implemented components may be distributed across a number of geographic locations.

Machine and Software Architecture

(104) The components, methods, applications, and so forth described in conjunction with FIGS. 2-13 are implemented in some embodiments in the context of a machine and an associated software architecture. In various embodiments, the components, methods, applications, and so forth described above are implemented in the context of a plurality of machines, distributed across and communicating via a network, and one or more associated software architectures. The sections below describe representative software architecture(s) and machine (e.g., hardware) architecture(s) that are suitable for use with the disclosed embodiments.

(105) Software architectures are used in conjunction with hardware architectures to create devices and machines tailored to particular purposes. For example, a particular hardware architecture coupled with a particular software architecture will create a mobile device, such as a mobile phone, tablet device, or so forth. A slightly different hardware and software architecture may yield a smart device for use in the “internet of things,” while yet another combination produces a server computer for use within a cloud computing architecture. Not all combinations of such software and hardware architectures are presented here, as those of skill in the art can readily understand how to implement the inventive subject matter in different contexts from the disclosure contained herein.

Software Architecture

(106) FIG. 14 is a block diagram 1400 illustrating a representative software architecture 1402, which may be used in conjunction with various hardware architectures herein described. FIG. 14 is merely a non-limiting example of a software architecture, and it will be appreciated that many other architectures may be implemented to facilitate the functionality described herein. The software architecture 1402 may be executing on hardware such as a machine 1500 of FIG. 15 that includes, among other things, processors 1510, memory/storage 1530, and I/O components 1550. A representative hardware layer 1404 is illustrated and can represent, for example, the machine 1500 of FIG. 15. The representative hardware layer 1404 comprises one or more processing units 1406 having associated executable instructions 1408. The executable instructions 1408 represent the executable instructions of the software architecture 1402, including implementation of the methods, components, and so forth of FIGS. 2-13. The hardware layer 1404 also includes memory and/or storage components 1410, which also have the executable instructions 1408. The hardware layer 1404 may also comprise other hardware 1412 which represents any other hardware of the hardware layer 1404, such as the other hardware illustrated as part of the machine 1500.

(107) In the example architecture of FIG. 14, the software architecture 1402 may be conceptualized as a stack of layers where each layer provides particular functionality. For example, the software architecture 1402 may include layers such as an operating system 1414, libraries 1416,

frameworks/middleware **1418**, applications **1420**, and a presentation layer **1444**. Operationally, the applications **1420** and/or other components within the layers may invoke application programming interface (API) calls **1424** through the software stack and receive a response, returned values, and so forth illustrated as messages **1426** in response to the API calls **1424**. The layers illustrated are representative in nature, and not all software architectures have all layers. For example, some mobile or special purpose operating systems may not provide a frameworks/middleware layer **1418**, while others may provide such a layer. Other software architectures may include additional or different layers.

(108) The operating system **1414** may manage hardware resources and provide common services. The operating system **1414** may include, for example, a kernel **1428**, services **1430**, and drivers **1432**. The kernel **1428** may act as an abstraction layer between the hardware and the other software layers. For example, the kernel **1428** may be responsible for memory management, processor management (e.g., scheduling), component management, networking, security settings, and so on. The services **1430** may provide other common services for the other software layers. The drivers **1432** may be responsible for controlling or interfacing with the underlying hardware. For instance, the drivers **1432** may include display drivers, camera drivers, Bluetooth® drivers, flash memory drivers, serial communication drivers (e.g., Universal Serial Bus (USB) drivers), Wi-Fi® drivers, audio drivers, power management drivers, and so forth depending on the hardware configuration.

(109) The libraries **1416** may provide a common infrastructure that may be utilized by the applications **1420** and/or other components and/or layers. The libraries **1416** typically provide functionality that allows other software components to perform tasks in an easier fashion than to interface directly with the underlying operating system **1414** functionality (e.g., kernel **1428**, services **1430**, and/or drivers **1432**). The libraries **1416** may include system **1434** libraries (e.g., C standard library) that may provide functions such as memory allocation functions, string manipulation functions, mathematic functions, and the like. In addition, the libraries **1416** may include API libraries **1436** such as media libraries (e.g., libraries to support presentation and manipulation of various media formats such as MPEG4, H.264, MP3, AAC, AMR, JPG, PNG), graphics libraries (e.g., an OpenGL framework that may be used to render 2D and 3D graphic content on a display), database libraries (e.g., SQLite that may provide various relational database functions), web libraries (e.g., WebKit that may provide web browsing functionality), and the like. The libraries **1416** may also include a wide variety of other libraries **1438** to provide many other APIs to the applications **1420** and other software components/modules.

(110) The frameworks **1418** (also sometimes referred to as middleware) may provide a higher-level common infrastructure that may be utilized by the applications **1420** and/or other software components/modules. For example, the frameworks **1418** may provide various graphic user interface (GUI) functions, high-level resource management, high-level location services, and so forth. The frameworks **1418** may provide a broad spectrum of other APIs that may be utilized by the applications **1420** and/or other software components/modules, some of which may be specific to a particular operating system or platform. In some example embodiments, image modification components **1419** (e.g., one or more components of the image modification system **150**) may be implemented at least in part within the middleware/frameworks **1418**. For example, in some instances, at least a portion of the presentation component **260**, providing graphic and non-graphic user interface functions, may be implemented in the middleware/frameworks **1418**. Similarly, in some example embodiments, portions of one or more of the receiver component **210**, the parameter component **220**, the identification component **230**, and the characteristic component **240** may be implemented in the middleware/frameworks **1418**.

(111) The applications **1420** include built-in applications **1440**, third party applications **1442**, and/or image modification components **1443** (e.g., user facing portions of one or more of the components of the image modification system **150**). Examples of representative built-in applications **1440** may include, but are not limited to, a contacts application, a browser application,

a book reader application, a location application, a media application, a messaging application, and/or a game application. The third party applications **1442** may include any of the built-in applications as well as a broad assortment of other applications. In a specific example, the third party application **1442** (e.g., an application developed using the Android™ or iOS™ software development kit (SDK) by an entity other than the vendor of the particular platform) may be mobile software running on a mobile operating system such as iOS™, Android™, Windows® Phone, or other mobile operating systems. In this example, the third party application **1442** may invoke the API calls **1424** provided by the mobile operating system such as the operating system **1414** to facilitate functionality described herein. In various example embodiments, the user facing portions of the image modification components **1443** may include one or more components or portions of components described with respect to FIG. 2. For example, in some instances, portions of the receiver component **210**, the parameter component **220**, the identification component **230**, the notification component **250**, and the presentation component **260** associated with user interface elements (e.g., data entry and data output functions) may be implemented in the form of an application of the image modification components **1443**.

(112) The applications **1420** may utilize built-in operating system functions (e.g., kernel **1428**, services **1430**, and/or drivers **1432**), libraries (e.g., system libraries **1434**, API libraries **1436**, and other libraries **1438**), and frameworks/middleware **1418** to create user interfaces to interact with users of the system. Alternatively, or additionally, in some systems interactions with a user may occur through a presentation layer, such as the presentation layer **1444**. In these systems, the application/module “logic” can be separated from the aspects of the application/module that interact with a user.

(113) Some software architectures utilize virtual machines. In the example of FIG. 14, this is illustrated by a virtual machine **1448**. A virtual machine creates a software environment where applications/modules can execute as if they were executing on a hardware machine (such as the machine **1500** of FIG. 15, for example). A virtual machine is hosted by a host operating system (e.g., operating system **1414** in FIG. 14) and typically, although not always, has a virtual machine monitor **1446**, which manages the operation of the virtual machine as well as the interface with the host operating system (e.g., operating system **1414**). A software architecture executes within the virtual machine **1448** such as an operating system **1450**, libraries **1452**, frameworks/middleware **1454**, applications **1456**, and/or a presentation layer **1458**. These layers of software architecture executing within the virtual machine **1448** can be the same as corresponding layers previously described or may be different.

Example Machine Architecture and Machine-Readable Medium

(114) FIG. 15 is a block diagram illustrating components of a machine **1500**, according to some example embodiments, able to read instructions (e.g., processor executable instructions) from a machine-readable medium (e.g., a non-transitory machine-readable storage medium) and perform any one or more of the methodologies discussed herein. Specifically, FIG. 15 shows a diagrammatic representation of the machine **1500** in the example form of a computer system, within which instructions **1516** (e.g., software, a program, an application, an applet, an app, or other executable code) for causing the machine **1500** to perform any one or more of the methodologies discussed herein may be executed. For example, the instructions **1516** may cause the machine **1500** to execute the flow diagrams of FIGS. 3, 7-8, 10-11, and 13. Additionally, or alternatively, the instructions **1516** may implement the receiver component **210**, the parameter component **220**, the identification component **230**, the characteristic component **240**, the notification component **250**, and the presentation component **260** of FIGS. 2-13, and so forth. The instructions **1516** transform the general, non-programmed machine into a particular machine programmed to carry out the described and illustrated functions in the manner described.

(115) In alternative embodiments, the machine **1500** operates as a standalone device or may be coupled (e.g., networked) to other machines in a networked system. In a networked deployment,

the machine **1500** may operate in the capacity of a server machine or a client machine in a server-client network environment, or as a peer machine in a peer-to-peer (or distributed) network environment. The machine **1500** may comprise, but not be limited to, a server computer, a client computer, a personal computer (PC), a tablet computer, a laptop computer, a netbook, a set-top box (STB), an entertainment media system, a web appliance, a network router, a network switch, a network bridge, or any machine capable of executing the instructions **1516**, sequentially or otherwise, that specify actions to be taken by the machine **1500**. In some example embodiments, in the networked deployment, one or more machines may implement at least a portion of the components described above. The one or more machines interacting with the machine **1500** may comprise, but not be limited to, a personal digital assistant (PDA), an entertainment media system, a cellular telephone, a smartphone, a mobile device, a wearable device (e.g., a smart watch), a smart home device (e.g., a smart appliance), and other smart devices. Further, while only a single machine **1500** is illustrated, the term “machine” shall also be taken to include a collection of machines **1500** that individually or jointly execute the instructions **1516** to perform any one or more of the methodologies discussed herein.

(116) The machine **1500** may include processors **1510**, memory/storage **1530**, and I/O components **1550**, which may be configured to communicate with each other such as via a bus **1502**. In an example embodiment, the processors **1510** (e.g., a Central Processing Unit (CPU), a Reduced Instruction Set Computing (RISC) processor, a Complex Instruction Set Computing (CISC) processor, a Graphics Processing Unit (GPU), a Digital Signal Processor (DSP), an ASIC, a Radio-Frequency Integrated Circuit (RFIC), another processor, or any suitable combination thereof) may include, for example, a processor **1512** and a processor **1514** that may execute the instructions **1516**. The term “processor” is intended to include multi-core processors that may comprise two or more independent processors (sometimes referred to as “cores”) that may execute instructions contemporaneously. Although FIG. **15** shows multiple processors, the machine **1500** may include a single processor with a single core, a single processor with multiple cores (e.g., a multi-core processor), multiple processors with a single core, multiple processors with multiples cores, or any combination thereof.

(117) The memory/storage **1530** may include a memory **1532**, such as a main memory, or other memory storage, and a storage unit **1536**, both accessible to the processors **1510** such as via the bus **1502**. The storage unit **1536** and memory **1532** store the instructions **1516** embodying any one or more of the methodologies or functions described herein. The instructions **1516** may also reside, completely or partially, within the memory **1532**, within the storage unit **1536**, within at least one of the processors **1510** (e.g., within the processor's cache memory), or any suitable combination thereof, during execution thereof by the machine **1500**. Accordingly, the memory **1532**, the storage unit **1536**, and the memory of the processors **1510** are examples of machine-readable media.

(118) As used herein, “machine-readable medium” means a device able to store instructions and data temporarily or permanently and may include, but is not limited to, random-access memory (RAM), read-only memory (ROM), buffer memory, flash memory, optical media, magnetic media, cache memory, other types of storage (e.g., Erasable Programmable Read-Only Memory (EEPROM)), and/or any suitable combination thereof. The term “machine-readable medium” should be taken to include a single medium or multiple media (e.g., a centralized or distributed database, or associated caches and servers) able to store the instructions **1516**. The term “machine-readable medium” shall also be taken to include any medium, or combination of multiple media, that is capable of storing instructions (e.g., instructions **1516**) for execution by a machine (e.g., machine **1500**), such that the instructions, when executed by one or more processors of the machine (e.g., processors **1510**), cause the machine to perform any one or more of the methodologies described herein. Accordingly, a “machine-readable medium” refers to a single storage apparatus or device, as well as “cloud-based” storage systems or storage networks that include multiple storage apparatus or devices. The term “machine-readable medium” excludes signals per se.

(119) The I/O components **1550** may include a wide variety of components to receive input, provide output, produce output, transmit information, exchange information, capture measurements, and so on. The specific I/O components **1550** that are included in a particular machine will depend on the type of machine. For example, portable machines such as mobile phones will likely include a touch input device or other such input mechanisms, while a headless server machine will likely not include such a touch input device. It will be appreciated that the I/O components **1550** may include many other components that are not shown in FIG. 15. The I/O components **1550** are grouped according to functionality merely for simplifying the following discussion and the grouping is in no way limiting. In various example embodiments, the I/O components **1550** may include output components **1552** and input components **1554**. The output components **1552** may include visual components (e.g., a display such as a plasma display panel (PDP), a light emitting diode (LED) display, a liquid crystal display (LCD), a projector, or a cathode ray tube (CRT)), acoustic components (e.g., speakers), haptic components (e.g., a vibratory motor, resistance mechanisms), other signal generators, and so forth. The input components **1554** may include alphanumeric input components (e.g., a keyboard, a touch screen configured to receive alphanumeric input, a photo-optical keyboard, or other alphanumeric input components), point based input components (e.g., a mouse, a touchpad, a trackball, a joystick, a motion sensor, or other pointing instruments), tactile input components (e.g., a physical button, a touch screen that provides location and/or force of touches or touch gestures, or other tactile input components), audio input components (e.g., a microphone), and the like.

(120) In further example embodiments, the I/O components **1550** may include biometric components **1556**, motion components **1558**, environmental components **1560**, or position components **1562** among a wide array of other components. For example, the biometric components **1556** may include components to detect expressions (e.g., hand expressions, facial expressions, vocal expressions, body gestures, or eye tracking), measure biosignals (e.g., blood pressure, heart rate, body temperature, perspiration, or brain waves), identify a person (e.g., voice identification, retinal identification, facial identification, fingerprint identification, or electroencephalogram based identification), and the like. The motion components **1558** may include acceleration sensor components (e.g., accelerometer), gravitation sensor components, rotation sensor components (e.g., gyroscope), and so forth. The environmental components **1560** may include, for example, illumination sensor components (e.g., photometer), temperature sensor components (e.g., one or more thermometers that detect ambient temperature), humidity sensor components, pressure sensor components (e.g., barometer), acoustic sensor components (e.g., one or more microphones that detect background noise), proximity sensor components (e.g., infrared sensors that detect nearby objects), gas sensors (e.g., gas detection sensors to detect concentrations of hazardous gases for safety or to measure pollutants in the atmosphere), or other components that may provide indications, measurements, or signals corresponding to a surrounding physical environment. The position components **1562** may include location sensor components (e.g., a Global Position System (GPS) receiver component), altitude sensor components (e.g., altimeters or barometers that detect air pressure from which altitude may be derived), orientation sensor components (e.g., magnetometers), and the like.

(121) Communication may be implemented using a wide variety of technologies. The I/O components **1550** may include communication components **1564** operable to couple the machine **1500** to a network **1580** or devices **1570** via a coupling **1582** and a coupling **1572** respectively. For example, the communication components **1564** may include a network interface component or other suitable device to interface with the network **1580**. In further examples, the communication components **1564** may include wired communication components, wireless communication components, cellular communication components, Near Field Communication (NFC) components, Bluetooth® components (e.g., Bluetooth® Low Energy), Wi-Fi® components, and other communication components to provide communication via other modalities. The devices **1570** may

be another machine or any of a wide variety of peripheral devices (e.g., a peripheral device coupled via a USB).

(122) Moreover, the communication components **1564** may detect identifiers or include components operable to detect identifiers. For example, the communication components **1564** may include Radio Frequency Identification (RFID) tag reader components, NFC smart tag detection components, optical reader components (e.g., an optical sensor to detect one-dimensional bar codes such as Universal Product Code (UPC) bar code, multi-dimensional bar codes such as Quick Response (QR) code, Aztec code, Data Matrix, Dataglyph, MaxiCode, PDF417, Ultra Code, UCC RSS-2D bar code, and other optical codes), or acoustic detection components (e.g., microphones to identify tagged audio signals). In addition, a variety of information may be derived via the communication components **1564**, such as location via Internet Protocol (IP) geolocation, location via Wi-Fi® signal triangulation, location via detecting an NFC beacon signal that may indicate a particular location, and so forth.

Transmission Medium

(123) In various example embodiments, one or more portions of the network **1580** may be an ad hoc network, an intranet, an extranet, a virtual private network (VPN), a local area network (LAN), a wireless LAN (WLAN), a wide area network (WAN), a wireless WAN (WWAN), a metropolitan area network (MAN), the Internet, a portion of the Internet, a portion of the Public Switched Telephone Network (PSTN), a plain old telephone service (POTS) network, a cellular telephone network, a wireless network, a Wi-Fi® network, another type of network, or a combination of two or more such networks. For example, the network **1580** or a portion of the network **1580** may include a wireless or cellular network and the coupling **1582** may be a Code Division Multiple Access (CDMA) connection, a Global System for Mobile communications (GSM) connection, or another type of cellular or wireless coupling. In this example, the coupling **1582** may implement any of a variety of types of data transfer technology, such as Single Carrier Radio Transmission Technology (1xRTT), Evolution-Data Optimized (EVDO) technology, General Packet Radio Service (GPRS) technology, Enhanced Data rates for GSM Evolution (EDGE) technology, third Generation Partnership Project (3GPP) including 3G, fourth generation wireless (4G) networks, Universal Mobile Telecommunications System (UMTS), High Speed Packet Access (HSPA), Worldwide Interoperability for Microwave Access (WiMAX), Long Term Evolution (LTE) standard, others defined by various standard-setting organizations, other long range protocols, or other data transfer technology.

(124) The instructions **1516** may be transmitted or received over the network **1580** using a transmission medium via a network interface device (e.g., a network interface component included in the communication components **1564**) and utilizing any one of a number of well-known transfer protocols (e.g., hypertext transfer protocol (HTTP)). Similarly, the instructions **1516** may be transmitted or received using a transmission medium via the coupling **1572** (e.g., a peer-to-peer coupling) to the devices **1570**. The term “transmission medium” shall be taken to include any intangible medium that is capable of storing, encoding, or carrying the instructions **1516** for execution by the machine **1500**, and includes digital or analog communications signals or other intangible media to facilitate communication of such software.

Language

(125) Throughout this specification, plural instances may implement components, operations, or structures described as a single instance. Although individual operations of one or more methods are illustrated and described as separate operations, one or more of the individual operations may be performed concurrently, and nothing requires that the operations be performed in the order illustrated. Structures and functionality presented as separate components in example configurations may be implemented as a combined structure or component. Similarly, structures and functionality presented as a single component may be implemented as separate components. These and other variations, modifications, additions, and improvements fall within the scope of the

subject matter herein.

(126) Although an overview of the inventive subject matter has been described with reference to specific example embodiments, various modifications and changes may be made to these embodiments without departing from the broader scope of embodiments of the present disclosure. Such embodiments of the inventive subject matter may be referred to herein, individually or collectively, by the term “invention” merely for convenience and without intending to voluntarily limit the scope of this application to any single disclosure or inventive concept if more than one is, in fact, disclosed.

(127) The embodiments illustrated herein are described in sufficient detail to enable those skilled in the art to practice the teachings disclosed. Other embodiments may be used and derived therefrom, such that structural and logical substitutions and changes may be made without departing from the scope of this disclosure. The Detailed Description, therefore, is not to be taken in a limiting sense, and the scope of various embodiments is defined only by the appended claims, along with the full range of equivalents to which such claims are entitled.

(128) As used herein, the term “or” may be construed in either an inclusive or exclusive sense. Moreover, plural instances may be provided for resources, operations, or structures described herein as a single instance. Additionally, boundaries between various resources, operations, components, engines, and data stores are somewhat arbitrary, and particular operations are illustrated in a context of specific illustrative configurations. Other allocations of functionality are envisioned and may fall within a scope of various embodiments of the present disclosure. In general, structures and functionality presented as separate resources in the example configurations may be implemented as a combined structure or resource. Similarly, structures and functionality presented as a single resource may be implemented as separate resources. These and other variations, modifications, additions, and improvements fall within a scope of embodiments of the present disclosure as represented by the appended claims. The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense.

Claims

1. A method comprising: receiving an image for a product listing of a network-based marketplace; identifying an object and a background depicted in the image; identifying an additional image corresponding to an additional product listing for a product related to the object by performing a search of the network-based marketplace; identifying a characteristic of the background depicted in the image that is different from a characteristic of a background depicted in the additional image by comparing the image and the additional image; and causing presentation of instructions to change the background depicted in the image based on the characteristic of the background depicted in the additional image.
2. The method of claim 1, wherein identifying the object depicted in the image includes detecting edges of the object.
3. The method of claim 1, further comprising identifying the characteristic of the background depicted in the image based on determining a contrast value between a color of the background depicted in the image and a color of the object depicted in the image.
4. The method of claim 3, further comprising determining whether the contrast value between the color of the background depicted in the image and the color of the object depicted in the image meets a threshold contrast value.
5. The method of claim 1, wherein the instructions to change the background depicted in the image indicate an edit to a color of the background depicted in the image.
6. The method of claim 1, wherein the instructions to change the background depicted in the image indicate a change to a position of the object relative to a portion of the background depicted in the image.

7. The method of claim 1, wherein the characteristic of the background depicted in the image and the characteristic of the background depicted in the additional image comprise a white balance value, a color saturation value, a color temperature value, or a combination thereof.
8. The method of claim 1, further comprising generating a preview image including the object and an edited background based on the instructions to change the background depicted in the image.
9. The method of claim 1, wherein identifying the background depicted in the image includes parsing pixels corresponding to the object depicted in the image.
10. A system, comprising: at least one processor; and a memory storing instructions which, when executed by the at least one processor, cause the at least one processor to perform operations including: receiving an image for a product listing of a network-based marketplace; identifying an object and a background depicted in the image; identifying an additional image corresponding to an additional product listing for a product related to the object by performing a search of the network-based marketplace; identifying a characteristic of the background depicted in the image that is different from a characteristic of a background depicted in the additional image by comparing the image and the additional image; and causing presentation of instructions to change the background depicted in the image based on the characteristic of the background depicted in the additional image.
11. The system of claim 10, wherein identifying the object depicted in the image includes detecting edges of the object.
12. The system of claim 10, the operations further including identifying the characteristic of the background depicted in the image based on determining a contrast value between a color of the background depicted in the image and a color of the object depicted in the image.
13. The system of claim 12, wherein identifying the characteristic of the background is based on determining whether the contrast value between the color of the background depicted in the image and the color of the object depicted in the image meets a threshold contrast value.
14. The system of claim 10, wherein the instructions to change the background depicted in the image indicate an edit to a color of the background depicted in the image.
15. The system of claim 10, wherein the characteristic of the background depicted in the image and the characteristic of the background depicted in the additional image include a white balance value, a color saturation value, a color temperature value, or a combination thereof.
16. The system of claim 10, wherein the operations further include generating a preview image including the object and an edited background based on the instructions to change the background depicted in the image.
17. One or more non-transitory machine-readable storage media storing instructions, which when executed by at least one processor, cause the at least one processor to perform operations comprising: receiving an image for a product listing of a network-based marketplace; identifying an object and a background depicted in the image; identifying an additional image corresponding to an additional product listing for a product related to the object by performing a search of the network-based marketplace; identifying a characteristic of the background depicted in the image that is different from a characteristic of a background depicted in the additional image by comparing the image and the additional image; and causing presentation of instructions to change the background depicted in the image based on the characteristic of the background depicted in the additional image.
18. The one or more non-transitory machine-readable storage media of claim 17, wherein identifying the object depicted in the image includes detecting edges of the object.
19. The one or more non-transitory machine-readable storage media of claim 17, wherein the operations further include identifying the characteristic of the background depicted in the image based on determining a contrast value between a color of the background depicted in the image and a color of the object depicted in the image.
20. The one or more non-transitory machine-readable storage media of claim 19, wherein

identifying the characteristic of the background is based on determining whether the contrast value between the color of the background depicted in the image and the color of the object depicted in the image meets a threshold contrast value.
