

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281057

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Block; Ueyn L. et al.

CONCENTRIC ARCHITECTURE FOR OPTICAL SENSING

Abstract

An electronic device including optical sensing with a concentric architecture and methods for operation thereof is disclosed. The concentric architecture can include light detector(s) arranged in a concentric manner around light emitter(s). In some examples, at least one light emitter can be located in the center of the device, and each light detector can be located the same separation distance from the light emitter. Each light detector can be arranged such that the separation distance from the centrally located light emitter can be greater than the separation distance from another light emitter. Examples of the disclosure further include a selective transparent layer overlaying the light detector(s). The selective transparent layer can include section(s) transparent to a first wavelength range and non-transparent to a second wavelength ranges. In some examples, the selective transparent layer can further include section(s) transparent to the second wavelength range.

Inventors: Block; Ueyn L. (Menlo Park, CA), Shao; Guocheng (San Jose, CA), Hiromi; Itaru L. (Cupertino, CA), Charbonneau-LeFort; Mathieu (San Jose, CA), Harrison-Noonan; Tobias J. (San Francisco, CA)

Applicant: Apple Inc. (Cupertino, CA)

Family ID: 63686144

Appl. No.: 19/219543

Filed: May 27, 2025

Related U.S. Application Data

parent US continuation 18808815 20240819 parent-grant-document US 12318178 child US 19219543

parent US continuation 17675399 20220218 parent-grant-document US 12064224 child US 18808815

parent US continuation 16126970 20180910 parent-grant-document US 11266320 child US

Publication Classification

Int. Cl.: **A61B5/024** (20060101); **A61B5/00** (20060101); **A61B5/026** (20060101); **A61B5/0295** (20060101); **A61B5/1455** (20060101); **H01L25/16** (20230101); **H10F55/20** (20250101); **H10F77/40** (20250101)

U.S. Cl.:

CPC **A61B5/02433** (20130101); **A61B5/02438** (20130101); **A61B5/0261** (20130101); **A61B5/0295** (20130101); **A61B5/14551** (20130101); **A61B5/681** (20130101); **H01L25/167** (20130101); **H10F55/20** (20250101); **H10F77/413** (20250101); **A61B2562/0238** (20130101); **A61B2562/0242** (20130101); **A61B2562/046** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of U.S. patent application Ser. No. 18/808,815, filed Aug. 19, 2024, which is a continuation of U.S. patent application Ser. No. 17/675,399, filed Feb. 18, 2022, now issued U.S. Pat. No. 12,064,224, which is a continuation of U.S. patent application Ser. No. 16/126,970, filed Sep. 10, 2018, now issued U.S. Pat. No. 11,266,320, which claims the benefit of U.S. Provisional Patent Application No. 62/563,594, filed Sep. 26, 2017, the entire disclosures of which are incorporated herein by reference in their entirety.

FIELD

[0002] This relates generally to architectures for optical sensing. More particularly, the disclosure relates to architectures for an optical sensing unit including a plurality of light detectors arranged in a concentric manner around a plurality of light emitters.

BACKGROUND

[0003] A photoplethysmogram (PPG) signal can be measured by optical sensing systems to derive corresponding physiological signals (e.g., pulse rate). In a basic form, the optical sensing systems can employ a light emitter that emits light through an aperture and/or window into the user's tissue. In addition, a light detector can be included to receive light through an aperture and/or window. The light received by the light detector can be light that has returned (e.g., reflected or scattered) and exited the tissue. In some instances, optical losses due to one or more components in the system may affect the determination of the user's physiological information.

SUMMARY

[0004] This disclosure relates to an electronic device configured for optical sensing having a concentric architecture and methods for operation thereof. The concentric architecture can include a plurality of light detectors arranged in a concentric manner around a plurality of light emitters. The plurality of light emitters can include a plurality of first light emitters emitting at a first wavelength range (e.g., visible wavelengths) and one or more second light emitters emitting at a second wavelength range (e.g., infrared wavelengths). In some examples, at least one second light emitter can be located in the center of the device, and each light detector can be located the same separation distance from the at least one second light emitter. Each light detector can be arranged such that the separation distance from the centrally located second light emitter can be greater than the separation distance from a first light emitter.

[0005] Examples of the disclosure further include a selective transparent layer overlaying the plurality of light detectors. The selective transparent layer can include a plurality of first sections transparent to a second wavelength range (e.g., infrared wavelengths) and non-transparent to a first wavelength ranges (e.g., visible wavelengths). The selective transparent layer can further include a plurality of second sections transparent to the second wavelength range. In some examples, a Fresnel lens can be located in a corresponding region of the first and second light emitters. The Fresnel lens can include a plurality of regions, such as a first region and a second region. The first region can be located in the field of view(s) of the first light emitter(s), and the second region can be located in the field of view(s) of the second light emitter(s). The plurality of regions of the Fresnel lens may have different optical (e.g., percent transmission, amount of collimation, etc.) properties.

[0006] Methods for operating the optical sensing unit can include associating the plurality of light detectors to one or more channels. Each light emitter is sequentially activated to emit light, and the one or more channels can further sequentially measure light from the given light emitter. In some examples, the association of the one or more channels can be dynamically changed. For example, during a first time, all of the plurality of light detectors can be associated to a single channel. The system can dynamically change, during a second time, to the plurality of light detectors being associated to multiple channels. In some examples, the device can be configured to perform multiple measurement types (e.g., primary and secondary measurements) as part of a sampling procedure, where the primary measurements can include readings using a first set of operating conditions of the PPG sensor unit, and the secondary measurements can use a different second set of operating conditions of the PPG sensor unit. The single channel can be used for the primary measurements, and the multiple channels can be used for the secondary measurements, for example.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] FIGS. 1A-1C illustrate systems in which examples of the disclosure can be implemented.

[0008] FIG. 2A illustrates a top view of an exemplary electronic device including a concentric architecture for optical sensing according to examples of the disclosure.

[0009] FIG. 2B illustrates the cross-sectional view of FIG. 2A along line 1-11 according to examples of the disclosure.

[0010] FIG. 2C illustrates a top view of an exemplary concentric architecture including a selective transparent layer overlaid according to examples of the disclosure.

[0011] FIG. 2D illustrates an enlarged view of an exemplary selective transparent layer overlaying a single light detector according to examples of the disclosure.

[0012] FIG. 2E illustrates a cross-sectional view of an exemplary electronic device including a concentric architecture and a retroreflector according to examples of the disclosure.

[0013] FIG. 2F illustrates a cross-sectional view of an exemplary electronic device including a concentric architecture, a retroreflector, and an opaque mask according to examples of the disclosure.

[0014] FIG. 2G-2H illustrate cross-sectional and top views, respectively, of an exemplary electronic device including a lens with multiple regions according to examples of the disclosure.

[0015] FIG. 3 illustrates an exemplary process flow using a binning technique for one or more channels according to examples of the disclosure.

[0016] FIGS. 4A-4E illustrate exemplary associations of the light detectors to channels according to examples of the disclosure.

[0017] FIG. 5 illustrates an exemplary block diagram of a computing system comprising light

emitters and light detectors for measuring a signal associated with a user's physiological state according to examples of the disclosure.

[0018] FIG. 6 illustrates an exemplary configuration in which an electronic device is connected to a host according to examples of the disclosure.

DETAILED DESCRIPTION

[0019] In the following description of examples, reference is made to the accompanying drawings in which it is shown by way of illustration specific examples that can be practiced. It is to be understood that other examples can be used and structural changes can be made without departing from the scope of the various examples. Numerous specific details are set forth in order to provide a thorough understanding of one or more aspects and/or features described or referenced herein. It will be apparent, however, to one skilled in the art, that one or more aspects and/or features described or referenced herein may be practiced without some or all of these specific details. In other instances, well-known process steps and/or structures have not been described in detail in order to not obscure some of the aspects and/or features described or referenced herein.

[0020] A photoplethysmographic (PPG) signal can be measured by an optical sensing system to derive corresponding physiological signals (e.g., pulse rate). Such optical sensing systems can be designed to be sensitive to changes in a user's tissue that can result from fluctuations in the amount or volume of blood or blood oxygen in the vasculature of the user. In a basic form, optical sensing systems can employ a light emitter or light emitter that emits light through an aperture and/or window into the user's tissue. The system can further include a light detector to receive return light (i.e., light that has reflected and/or scattered and exited the tissue) through the same or another aperture and/or window. The PPG signal is the amplitude of return light that is modulated with volumetric change in blood volume in the tissue. The light emitters and light emitters in the optical sensing system can be arranged in a concentric architecture.

[0021] This disclosure relates to an electronic device configured for optical sensing having a concentric architecture and methods for operation thereof. The concentric architecture can include a plurality of light detectors arranged in a concentric manner around a plurality of light emitters. The plurality of light emitters can include a plurality of first light emitters emitting at a first wavelength range (e.g., visible wavelengths) and one or more second light emitters emitting at a second wavelength range (e.g., infrared wavelengths). In some examples, at least one second light emitter can be located in the center of the device, and each light detector can be located the same separation distance from the at least one second light emitter. Each light detector can be arranged such that the separation distance from the centrally located second light emitter can be greater than the separation distance from a first light emitter.

[0022] Examples of the disclosure further include a selective transparent layer overlaying the plurality of light detectors. The selective transparent layer can include a plurality of first sections transparent to a second wavelength range (e.g., infrared wavelengths) and at least partially non-transparent to a first wavelength ranges (e.g., visible wavelengths). The selective transparent layer can further include a plurality of second sections transparent to the second wavelength range. In some examples, a Fresnel lens can be located in a corresponding region of the first and second light emitters. The Fresnel lens can include a plurality of regions, such as a first region and a second region. The first region can be located in the field of view(s) of the first light emitter(s), and the second region can be located in the field of view(s) of the second light emitter(s). The plurality of regions of the Fresnel lens may have different optical (e.g., percent transmission, amount of collimation, etc.) properties.

[0023] Methods for operating the optical sensing unit can include associating the plurality of light detectors to one or more channels. Each light emitter is sequentially activated to emit light, and the one or more channels can further sequentially measure light from the given light emitter. In some examples, the association of the one or more channels can be dynamically changed. For example, during a first time, all of the plurality of light detectors can be associated to a single channel. The

system can dynamically change, during a second time, to the plurality of light detectors being associated to multiple channels. In some examples, the device can be configured to perform multiple measurement types (e.g., primary and secondary measurements) as part of a sampling procedure, where the primary measurements can include readings using a first set of operating conditions of the PPG sensor unit, and the secondary measurements can use a different second set of operating conditions of the PPG sensor unit. The single channel can be used for the primary measurements, and the multiple channels can be used for the secondary measurements, for example.

[0024] Representative applications of the apparatus and methods according to the present disclosure are described in this section. These examples are being provided solely to add context and aid in the understanding of the described examples. It will thus be apparent to one skilled in the art that the described examples may be practiced without some or all of the specific details. Other applications are possible, such that the following examples should not be taken as limiting.

[0025] FIGS. **1A-1C** illustrate systems in which examples of the disclosure can be implemented. FIG. **1A** illustrates an exemplary mobile telephone **136** that can include a touch screen **124**. FIG. **1B** illustrates an exemplary media player **140** that can include a touch screen **126**. FIG. **1C** illustrates an exemplary wearable device **144** that can include a touch screen **128** and can be attached to a user using a strap **146**. The systems of FIGS. **1A-1C** can utilize the optical layers, the optical films, the lenses, the window systems, the concentric architecture, and/or methods for detecting a PPG signal as will be disclosed.

Exemplary Configuration of the Optical Sensing Unit

[0026] FIG. **2A** illustrates a top view of an exemplary electronic device including a concentric architecture for optical sensing according to examples of the disclosure. The top view in FIG. **2A** can be viewed as the underside of wearable device **144** of FIG. **1C**, for example. Further, the top view in FIG. **2A** includes a partial top view of device without a selective transparent layer (discussed below) overlaid.

[0027] Device **200** can include a plurality of light detectors **204A, 204B, 204C, 204D, 204E, 204F, 204G, and 204H** (collectively referred to as plurality of light detectors **204**); a plurality of first light emitters **206A, 206B, 206C, and 206D** (collectively referred to as plurality of first light emitters **206**); and a plurality of second light emitters **208A and 208B** (collectively referred to as plurality of second light emitters **208**). The device **200** can be situated such that the plurality of light detectors **204**, the plurality of first light emitters **206**, and second light emitter **208** are proximate to the user's skin. For example, the device **200** can be held in a user's hand or strapped to a user's wrist, among other possibilities.

[0028] The device can include a plurality of regions such as the center region **209** and the peripheral region **205**. The center region **209** can be separated from the peripheral region **205** by an optical isolation (e.g., optical isolation **216**), where the peripheral region **205** can be located closer to the edges (e.g., edge **201C**) of the device **200** than the center region **209**. For example, the center region **209** can include a plurality of light emitters (e.g., first light emitters **206** and second light emitters **208**). In some examples, the plurality of first light emitters **206** can be located closer to the peripheral region than at least one second light emitter **208** (e.g., second light emitter **208A**). In some examples, at least one second light emitter **208** (e.g., second light emitter **208A**) can be located in the center of the center region **209**. In some examples, the plurality of first light emitters **206** can be configured to emit a different range(s) of wavelengths (e.g., green wavelengths) than the second light emitter(s) **208** (e.g., second light emitters can be configured to emit infrared wavelengths). The peripheral region **205** can partially or entirely surround the center region **209**.

[0029] In some examples, the separation distances and locations of the light detectors and light emitters can be optimized for different types of measurements (e.g., primary and secondary measurements). For example, the second light emitter **208A** can be located in the center of device **200** and can be configured to emit infrared light for detecting one type of information. The center

of device **200** can be such that the distances from second light emitter **208A** to the edges of device **200** along the same direction (e.g., left-to-right and/or top-to-bottom) are the same. For example, the distance from the top edge **201A** of the device and second light emitter **208A** can be the same as the distance from the bottom edge **201B** of the device. The distance from the left edge **201C** of the device and second light emitter **208A** can be the same as the distance from the right edge **201D** of the device. Optionally, device **200** can include second light emitter **208B** also used for detecting the same type of information as the second light emitter **208A**.

[0030] The plurality of first light emitters **206** can be placed closer to the peripheral region **205**. For example, the plurality of first light emitters **206** can include four light emitters: first light emitter **206A**, first light emitter **206B**, first light emitter **206C**, and first light emitter **206D**, which can be arranged to form a square, rectangle, quadrilateral, or the like. For example, the plurality of first light emitters **206** can be arranged in a square where the separation distances between first light emitter **206A** and first light emitter **206B**, between first light emitter **206B** and first light emitter **206C**, between first light emitter **206C** and first light emitter **206D**, and between first light emitter **206D** and first light emitter **206A** can be the same. In some examples, the separation distances between each first light emitter **206** and the center second light emitter **208A** can be the same. Although the figure illustrates the plurality of first light emitters **206** as located the same separation distance from optical isolation **216**, examples of the disclosure can include the light emitters being separated at varying distances. Further, examples of the disclosure are not limited to the light emitters located in a square-like arrangement, and pairs of first and second light emitters are not limited to having the same separation distances.

[0031] The peripheral region **205** can be located around (partially or entirely) the center region **209**. The plurality of light detectors **204** can be radially arranged in the peripheral region **205**. In some examples, a radial arrangement can include the plurality of light detectors **204** as oriented with an angle of a given edge dependent on the location in the peripheral region **205**, where each light detector **204** has the same or similar shape. For example, an angle of a top edge **214** (e.g., edge of the light detector closest to the edges of the device) of light detector **204A** and light detector **204E** can be at 0° . Top edge **214** of light detector **204B** and/or light detector **204F** can be 45° relative to the top edge **214** of light detector **204A** and/or light detector **204E**. Top edge **214** of light detector **204D** and/or light detector **204H** can be -45° relative to the top edge **214** of light detector **204A** and/or light detector **204E**. Top edge **214** of light detector **204C** and/or light detector **204G** can be 90° or -90° relative to top edge **214** of light detector **204A** and/or light detector **204E**. In this manner, the top edges **214** of two or more light detectors **204** can have different angles of orientation.

[0032] The relative arrangement of the light emitters and light detectors can be such that the distance (i.e., separation distance D.sub.2) between a first light emitter **206** (e.g., first light emitter **206A**) and its closest light detector **204** (e.g., light detector **204A**) can be less than the distance (i.e., separation distance D.sub.1) between a second light emitter **208** (e.g., second light emitter **208A**) and the same light detector **204**. In instances, the first light emitter **206A** can be a LED that emits visible light (e.g., green light) that has a separation distance D.sub.2 to one light detector **204A** that is shorter than the separation distances to the other light detectors, such as the light detectors **204B-204H**. The term “separation distance” means the distance measured from the center of one component to the center of the other component. In some examples, the separation distance between a first light emitter **206** and its closest neighboring light detectors **204** can be the same. Additionally, the distance (e.g., separation distance D.sub.3) between the same closest first light emitter **206** (e.g., first light emitter **206A**) and another light detector (e.g., light detector **204E**) can be greater than both the separation distance D.sub.1 and the separation distance D.sub.2, as illustrated in the figure.

[0033] In some examples, the second light emitter **208A** can be an infrared light emitter configured for one type of measurement, and the first light emitter **206A** can be a visible (e.g., green

wavelengths) light emitter configured for another type of measurement. In some examples, the light detectors associated with the separation distance $D_{sub.1}$ and the separation distance $D_{sub.3}$ can have the same angle of orientation. For example, the light detector **204A** and the light detector **204E** can both have a top edge **214** orientated at 0° .

[0034] In some examples, each light detector can be configured such that an edge “aligns” with a light emitter. For example, the center of the first light emitter **206A** can be along the same y-plane as the center of the light detector **204A**. In this manner, the separation distance $D_{sub.2}$ between centers of a first light emitter (e.g., the first light emitter **206A**) and its closest light detector (e.g., light detector **204A**) is less than the separation distances between the center of the same first light emitter and others of the plurality of light detectors **204**.

[0035] In other examples, the first light emitter **206A** can be located between the edges of adjacent light detectors **204A** and **204H**, as shown in FIG. 2C. That is, the radial angle of first light emitter **206A** can be the same as the radial angle of the edges of light detector **204A** and light detector **204H**. In this manner, the separation distances between the center of a light emitter (e.g., first light emitter **206A**) and the center of its two closest light detectors (e.g., light detector **204A** and **204H** and/or two adjacent light detectors) can be the same. Although the figure illustrates eight light detectors **204** and four first light emitters **206**, examples of the disclosure can include any number of light detectors and any number of light emitters. Further, although the figure illustrates the light detectors **204** as having rectangular-shaped detection areas and the light emitters as having square-shared emitting areas, examples of the disclosure can include any shape.

[0036] The device **200** can include one or more components for enhanced optical collection, signal generation, and/or reduced noise. FIG. 2B illustrates the cross-sectional view of FIG. 2A along line **1-11**. The one or more components can include optical isolation **216**, optical film **240**, and Fresnel lens **242**. To prevent or reduce optical crosstalk between the plurality of light detectors **204** and the plurality of first light emitters **206**, optical isolation **216** can be a wall located between the plurality of light detectors **204** and the plurality of first light emitters **206**. The optical isolation **216** can thereby define the cavity of the light emitters, separate from the cavity or cavities of the light detectors. The optical isolation **216** can be located in the center region **209** and/or in the peripheral region **205**. In some examples, the optical isolation **216** located in center region **209** can include the same material (or be formed from a continuous piece of material) as included in the optical isolation **216** located in peripheral region **205**. In some instances, the optical isolation **216** can be a concentric ring. In some examples, the optical isolation **216** may be different from other types of isolation that may be included in the device. Optical isolation **216** may collectively form at least two cavities which the light emitters and light sensors may be located within. Other types of isolation may include, but are not limited to, optical, electrical, and/or mechanical isolation of the optical sensing system from other components (e.g., a display or a touch screen) included in the device.

[0037] The optical film **240** can be a film configured for light restriction (discussed in detail below). The optical film **240** can at least partially overlay the section of window **203** corresponding to light passing through to at least one light detector **204**. In some examples, device **200** can include one section of optical film **240** disposed over each light detector **204**. The optical film **240** can have other arrangements such as being attached to a window, being disposed on a window, being disposed on a detector, and the like. In some examples, a single (e.g., ring-shaped) optical film **240** can be disposed over a plurality (including all) of light detectors **204**. In some examples, the edges of optical film **240** can extend to (e.g., contact) the optical isolation **216**.

[0038] The Fresnel lens **242** can be a lens configured to direct and/or focus light emitted by the light emitters. The Fresnel lens **242** can at least partially overlay the section of window **203** corresponding to light passing through from the plurality of first light emitters **206** and/or the second light emitter(s) **208**. That is, the Fresnel lens **242** can be located in the field of view of the plurality of first light emitters **206** and the field of view of the plurality of second light emitters

208. The Fresnel lens **242** can be configured for one or more targeted types of measurements. In some examples, the Fresnel lens **242** can be configured for obscuration of the light emitters. For example, the features of the Fresnel lens **242** can be based on achieving optimal measurements associated with the second light emitter **208** and associated with the plurality of first light emitters **206**, while also reducing the visibility of the light emitters.

[0039] Additionally, device **200** can include one or more layers for reducing visibility of other components. Opaque mask **219** can be configured to reduce visibility optical isolation **216** and/or the edge of optical film **240** by being opaque at one or more wavelengths (e.g., the wavelengths being measured by the device). In some examples, a portion of opaque mask **219** can extend past the walls of the cavities (e.g., created by optical isolation **216**). In some examples, the opaque mask **219** and the optical isolation **216** can include the same materials and/or functions (e.g., act as an optical isolation and/or cosmetic layer). At least one end of the opaque mask **219** and/or the optical isolation **216** can be located at or in close proximity to the internal surface (i.e., surface furthest from the exterior surface of the housing of device **200**) of window **203**. The device **200** further can include an adhesive **215** configured to adhere one or more components (e.g., optical film **240**, opaque mask **219**, etc.) to the window **203**.

[0040] FIG. 2C illustrates a top view of the concentric architecture including the selective transparent layer overlaid according to examples of the disclosure. FIG. 2D illustrates an enlarged view of the selective transparent layer overlaying a single light detector according to examples of the disclosure. A selective transparent layer **210** can be located in a peripheral region (e.g., peripheral region **205** illustrated in FIG. 2A). The selective transparent layer **210** can be configured to conceal routing traces and the contact pads **212** and/or edges of the plurality of light detectors **204**. In this manner, the selective transparent layer **210** can be located between the optical film **240** and the adhesive **215**. The selective transparent layer **210** can include one or more first sections **211A** of material that is at least partially transparent to a second wavelength range (e.g., infrared wavelengths) of light, wherein the transparency can be configured to allow light to reach the plurality of light detectors **204** for, e.g., a secondary measurement. The selective transparent layer **210** can also include one or more second sections **211B** overlaying a central portion of each light detector **204** to allow light of a first wavelength range (e.g., visible wavelengths) to reach the plurality of light detectors **204** for, e.g., a primary measurements. The one or more second sections **211B** overlaying the central portion can include material transparent to the second wavelength range or may be omitted material (e.g., an opening). In some instances, the one or more second sections **211B** can also be transparent to the first wavelength range.

[0041] In some examples, the first section(s) **211A** can be partially transparent (i.e., partially blocks) a first wavelength range and fully transparent to a second wavelength range.

[0042] The selective transparent layer **210** can be located anywhere in the field of view of the plurality of light detectors **204**. For example, the selective transparent layer **210** can be located between the optical film **240** and the window **203**. Examples of the disclosure can include the selective transparent layer **210** as being a layer separate from the windows **203**. In other instances, the selective transparent layer **210** can be formed in the window **203**.

[0043] In some examples, the device can include one or more components configured to redirect light that may not include physiological information, thereby preventing the unwanted light from reaching the light detector. FIG. 2E illustrates a cross-sectional view of an exemplary electronic device including a concentric architecture and a retroreflector according to examples of the disclosure. The device **200** can include a retroreflector **233** located proximate to the optical isolation **216**. In some instances, the retroreflector **233** may be implemented as a component of the optical sensing unit. The retroreflector **233** can replace the opaque mask **219** illustrated in FIG. 2C and can be located between the center region **209** (including the first light emitters **206** and the second light emitters **208**) and the peripheral region **205** (including the light detectors **204**). The retroreflector **233** may be a ring or an arc that is located around the center region **209**.

Alternatively, the retroreflector **233** can be located in one or more sections of the ring, while an opaque mask (e.g., opaque mask **219**) can be located in one or more other sections of the ring. In some examples, one or more sections of the ring may not include a retroreflector **233** or an opaque mask **219**.

[0044] The retroreflector **233** can be a component capable of reflecting light back along a direction that is parallel or nearly parallel to, but opposite in direction from its origin, irrespective of the angle of incidence. For example, light from the light emitters **206** may reflect off an interface (e.g., the outer surface, which may be the surface opposite the retroreflector **233**) of the window **203**. The light may reach the light detector **204** without interacting with the sample, and thus may not include physiological information. Instead of allowing the light to reach the light detector **204**, the retroreflector **233** may reflect the light back to the interface (e.g., in the direction away from the light detector **204**).

[0045] In some examples, the retroreflector can include one or more features having properties (e.g., 20 degrees, 60 degrees, 90 degrees, etc.) configured to selectively reflect light within a range of angles of incidence. In some examples, the one or more features can reflect light back in the same direction that is not parallel or nearly parallel to the incident light. In some examples, the retroreflector **233** may be wavelength independent, where a wide range of wavelengths can be reflected back.

[0046] In some instances, the device **200** can include both a retroreflector **233** and an opaque mask **219**, as illustrated in FIG. 2F. The retroreflector **233** can be located closer to the light emitters **206** and **208** (and/or light detector **204C**) than the opaque mask **219**. The opaque mask **219** can further help to prevent unwanted light from reaching the light detector **204** by including a material that can absorb the light rays that reflect off the one or more interfaces of the window **203**. In some examples, as illustrated in the FIGS. 2E-2F, the retroreflector **233** and/or the opaque mask **219** can have a larger width (e.g., can overhang) than the optical isolation **216**, which can reduce the cross-talk between the light emitters **206** and **208** and the light detectors **204**. In some examples, the opaque mask **219** can have a smaller width than the retroreflector **233**. Additionally or alternatively, the retroreflector **233** and/or the opaque mask **219** can include one or more materials (e.g., black ink) that conceal underlying components (e.g., optical isolation **216**) from the user's eyes.

[0047] In some examples, the device **200** can include a lens having multiple regions. FIG. 2G-2H illustrate cross-sectional and top views, respectively, of an exemplary electronic device including a lens with multiple regions according to examples of the disclosure. The device **200** can include lens region **242A** and lens regions **242B** (collectively referred to as lens **242**). The different lens regions can have different optical and/or physical properties. For example, the lens region **242A** can be a Fresnel lens that overlays (i.e., located in the field of view of) the second light emitter **208A**. The lens regions **242A** can include a plurality of features (e.g., ridges) for focusing (e.g., collimating the light emitted by the second light emitter **208A**). The lens regions **242B** can overlay at least two of the plurality of first light emitters **206**. The lens regions **242B** can include one or more other features (e.g., prisms) for controlling the light emitted by the plurality of first light emitters **206**.

[0048] In some instances, the lens **242** can be a layer separate from the windows **203**. In other examples, the lens **242** can be formed as a part of (i.e., inseparable from) the windows **203**.

[0049] In instances where the second light emitter(s) **208** emit a second light having a second wavelength, such as infrared light, and the first light emitters **206** emit a first light having a first wavelength, such as visible (e.g., green) light, the properties of the second light may differ from the first light. For example, the second light may have a lower signal intensities (or signal-to-noise ratio (SNR)), and the lens region **242A** (associated with the second light) may have one or more properties for enhancing the relative signals or SNR.

Exemplary Operation of the Sensing Unit

[0050] The sensing unit can be operated using one or more binning techniques. FIG. 3 illustrates an exemplary process flow using a binning technique for one or more channels according to examples

of the disclosure. One or more light detectors (e.g., all of the plurality of light detectors **204**) can be associated with one or more channels (step **352** of process **350**). In some examples, the channels can be dynamically changed based on the selected light emitter (step **353** of process **350**). In some examples, the channels can be dynamically changed based on the spacing.

[0051] For a given channel, one or more light emitters (e.g., second light emitter **208A**) can emit light (e.g., infrared light) (step **354** of process **350**). A portion of the light can be absorbed by the user's skin, vasculature, and/or blood, and a portion of the light can return to the light detectors. The light detector(s) associated with the given channel can measure the return light and can generate one or more signals indicative of the measured return light (step **356** of process **350**). The signals in the channel may be read out and processed (e.g., summed) together, for example, to produce a channel signal (step **358** of process **350**). The process can measure channels sequentially or concurrently. In the scenarios where the channels are measured sequentially, the process can be repeated for other channels until some or all channels are measured for a given light emitter. In some examples, multiple (including all) channels may be readout simultaneously, where signals within the same channel are processed separately from signals from other channels. Another light emitter (e.g., first light emitter **206A**) can be selected for the measurements (step **364** and step **366** of process **350**). Measuring multiple light emitters can allow the system to measure multiple regions of the user's skin for enhanced measurement accuracy. From the binned signals, the physiological information can be determined (step **368** of process **350**).

[0052] Examples of the disclosure can include a single channel wherein some (including all) of the light detectors are associated with the single channel. With a single channel, all the signals from all of the plurality of light detectors can be processed together. The single channel association can allow higher total signal collection, which can increase the SNR for the light emitter **408A**. Examples of the disclosure can further include each light detector associated with a unique channel. For example, the system can be configured with eight light detectors and eight channels. In this manner, the signal from each light detector can be processed separately.

[0053] Additionally or alternatively, the system can be configured with other associations. FIGS. **4A-4E** illustrate exemplary associations of the light detectors to channels according to examples of the disclosure. FIG. **4A** illustrates two channels, where light detectors (e.g., light detector **404A**, light detector **404B**, light detector **404C**, and light detector **404D**) located on one side of the device can be associated with a first channel **420**, and light detectors (e.g., light detector **404E**, light detector **404F**, light detector **404G**, and light detector **404H**) located on the other side of the device can be associated with a second channel **421**. The unique relationships between each light emitter relative to the channels can lead to different information. Generally, the signal information may include a higher signal intensity for shorter separation distances between a light emitter and a light detector. When one light emitter is emitting light (i.e., activated), the signal information measured by each channel may be the same. For example, when light emitter **406A** is emitting light, the light can be detected by all of the light detectors associated with a given channel. Channel **420** and channel **421** can include high signal information from light detector **404A** and light detector **404H**, respectively, along with low signal information from light detector **404D** and light detector **404E**, respectively. When another light emitter is emitting light, the signal information measured by each channel may differ. For example, when light emitter **406B** is emitting light, channel **420** may include high signal information from light detector **404B** and light detector **404C**, along with moderate signal information from light detector **404A** and light detector **404D**. Channel **421** may include low signal information from light detector **404E**, light detector **404H**, light detector **404F**, and light detector **404G**. In this manner, the same light detectors can measure different sets of signals depending on which light emitter is activated.

[0054] Although the figure illustrates one channel as including the light detectors located on the right side and the other channel as including the light detectors located on the left side, examples of the disclosure can include the same number (e.g., two) of channels, but the associations including

different light detectors. For example, the channel **420** can include the light detector **404C**, the light detector **404D**, the light detector **404E**, and the light detector **404F**, while the channel **421** can include the light detector **404G**, the light detector **404H**, the light detector **404A**, and the light detector **404B** (not shown). In some examples, the channel associations can be based on the relative location of the light emitter.

[0055] FIG. **4B** illustrates four channels according to examples of the disclosure. Each channel can include two adjacent light detectors with an emitter having the same separation distance relative to the centers of the light detectors. For example, the channel **422** can include the light detector **404A** and the light detector **404H**; the channel **423** can include the light detector **404B** and the light detector **404C**; the channel **424** can include the light detector **404D** and the light detector **404E**; and the channel **425** can include the light detector **404F** and the light detector **404G**. The unique relationships between each light emitter relative to the channels can lead to different information. For example, the signal from the channel **422** can include different information than the channel **424** when the light emitter **406A** is activated. With a higher number of channels (e.g., relative to the two channel association illustrated in FIG. **4A**), localization of the measurement region on the user's skin can be enhanced, thereby increasing the SNR for the measurements. The localization of a measurement region can refer to the amount of information in the signal that is from the region proximate to a given light detector(s).

[0056] FIG. **4C** illustrates two channels, wherein the channels may be non-uniformly allocated. In some instances, the number of light detectors associated with each channel can differ. For example, the channel **426** can include six light detectors (e.g., the light detector **404C**, the light detector **404D**, the light detector **404E**, the light detector **404F**, the light detector **404G**, and the light detector **404H**), and the channel **427** can include two light detectors (e.g., the light detector **404A** and the light detector **404B**). The system can be configured such that signals from one channel may be utilized for one type of information, and the signals from the other channel may be utilized for another type of information. For example, the channel **427** may have increased localization of a targeted measurement region on the user's skin and can be used for determining the user's physiological information. With decreased localization, channel **426** can be used for off-wrist detection and/or ambient light sensing. The signal from channel **426** can, for example, interrupt or be used for adjusting measurements associated with channel **427**. As another example, channel **426** can have a larger sampling area than channel **427**. The light detectors can be associated with a certain channel based on the signal quality.

[0057] FIG. **4D** illustrates multiple channels, where at least one channel includes non-neighboring light detectors according to examples of the disclosure. Channel **428** can include a first set of neighboring light detectors **404A** and **404H** and a second set of neighboring light detectors **404D** and **404E**, where the first set can be spatially separated (i.e., non-adjacent) along the concentric arrangement from the second set by at least one other (i.e., not included in the same channel) light detector. Channel **429** can include a first set of neighboring light detectors **404B** and **404C** and a second set of neighboring light detectors **404F** and **404G**, where the first set can be spatially separated from the second set by at least one other light detector. That is, one or more of the first and second channels can include two sets of adjacent light detectors (e.g., a first set can include light detector **404A** and light detector **404H**), where the two sets can be non-adjacent (e.g., a second set can include light detector **404D** and light detector **404E**, where the second set can be non-adjacent to the first set). The first and second channels can have one or more different light detectors (e.g., light detector **404G** may not be included in both first and second channels).

[0058] In this channel association, one set of light detectors can measure pulsatile information, while the other set of light detectors can measure non-pulsatile (e.g., dark) information. For example, when light emitter **406A** is activated, pulsatile information for channel **428** can be generated by light detector **404A** and light detector **404H**, but may not be generated by light detector **404D** and light detector **404E**. Which light detector(s) measures pulsatile information for a

given channel may depend on the activated light emitter. For example, pulsatile information for the channel **428** may not be measured by the light detector **404A** and the light detector **404H** when another light emitter (e.g., light emitter **406B**) is activated; the another light emitter may be one that is not proximate to the respective light detector(s). Instead, the light detector **404D** and the light detector **404E** may generate pulsatile information when the light emitter **406B** is activated.

[0059] In this manner, the same channel can effectively be used to measure different locations. For example, the light emitter **406A** and the light emitter **406D** can be assigned to the same channel **428**. Signals measured by a first one or more light detectors **404** in the channel may measure useful information when one light emitter is active, while a second one or more light detectors **404** in the same channel may not. Subsequently, the detectors that measure useful information (e.g., included in the determination of physiological information) may differ when another light emitter is active.

[0060] FIG. **4E** illustrates three channels, where each channel may include different levels of signal information. The first association can include two sets of adjacent light detector, the two sets being non-adjacent (as discussed in the context of FIG. **4D**), while the second association can include one or more light detectors adjacent to at least one light detector in the first association (e.g., light detector **404G** can be adjacent to light detector **404H**). For example, channel **430** can include the light detector **404A**, the light detector **404H**, the light detector **404D**, and the light detector **404E**. Channel **431** can include the light detector **404B** and the light detector **404G**; and channel **432** can include the light detector **404C** and the light detector **404F**. With light emitter **406A** activated, the channel **430** may include the highest level of pulsatile signal information, channel **431** may include a moderate level, and channel **432** may include the lowest level. With light emitter **406B** or light emitter **406D** activated, the channel **431** and the channel **432** may include the highest level of pulsatile signal information, and the channel **430** may include the lowest level. With light emitter **406C** activated, the channel **430** may include the highest level of pulsatile information, the channel **432** may include a moderate level, and the channel **431** may include the lowest level.

[0061] In some examples, the binning and channel associations may be dynamically changed without user interaction. The channel association can be based on the mode of operation. For example, when the system is in a first measurement operation mode, the system can be configured with a single channel including all eight light detectors. When the system switches to a second measurement operation mode, the system can dynamically switch to multiple (e.g., two, three, four, etc.) channels (e.g., as illustrated FIGS. **4A-4E**).

[0062] In some examples, the system can switch to a certain channel association based on the measured signal information. For example, if the system is configured with two channels, as illustrated in FIG. **4A** and the channel **420** generates higher pulsatile signal information after a certain number of measurements than the channel **421**, the system may switch to the channel association shown in FIG. **4C**. If, after the channel association switch, the higher pulsatile signal information is associated with the channel **427**, the system may determine that one or more regions on the user's skin (e.g., localized in close proximity to the channel **427**) may be most optimal for the given user. In this manner, the system can be tailored to the user, user conditions (e.g., one or more materials, such as the user's sleeve, inadvertently blocking optical components), and/or environmental conditions (e.g., higher levels of ambient light incident on one or more light detectors).

[0063] The above discussed channel associations can be implemented in post-processing where one or more (including all) of the light detectors can be hardwired together. Examples of the disclosure can further include one or more switches for dynamically switching which light detectors are electrically coupled (e.g., hardwired) together. Additionally or alternatively, one or more light detectors and/or channels may be deactivated. For example, if the system determines that the channel **427** (illustrated in FIG. **4C**) includes the highest level of pulsatile information, the system may deactivate light detectors (e.g., light detector **404C**, light detector **404D**, light detector **404E**, light detector **404F**, light detector **404G**, and light detector **404H**) included in another channel, such

as channel **426**, to save power.

[0064] FIG. **5** illustrates an exemplary block diagram of a computing system comprising the concentric architecture for optical sensing according to examples of the disclosure. Computing system **500** can correspond to any of the computing devices illustrated in FIGS. **1A-1C**. Computing system **500** can include a processor **510** configured to execute instructions and to carry out operations associated with computing system **500**. For example, using instructions retrieved from memory, processor **510** can control the reception and manipulation of input and output data between components of computing system **500**. Processor **510** can be a single-chip processor or can be implemented with multiple components.

[0065] In some examples, processor **510** together with an operating system can operate to execute computer code and produce and use data. The computer code and data can reside within a program storage block **502** that can be operatively coupled to processor **510**. Program storage block **502** can generally provide a place to hold data that is being used by computing system **500**. Program storage block **502** can be any non-transitory computer-readable storage medium (excluding signals), and can store, for example, history and/or pattern data relating to PPG signal and perfusion index values measured by one or more light detectors such as light detectors **504**. By way of example, program storage block **502** can include Read-Only Memory (ROM) **518**, Random-Access Memory (RAM) **522**, hard disk drive **508** and/or the like. The computer code and data could also reside on a removable storage medium and loaded or installed onto the computing system **500** when needed. Removable storage mediums include, for example, CD-ROM, DVD-ROM, Universal Serial Bus (USB), Secure Digital (SD), Compact Flash (CF), Memory Stick, Multi-Media Card (MMC) and a network component.

[0066] Computing system **500** can also include an input/output (I/O) controller **512** that can be operatively coupled to processor **510**, or it can be a separate component as shown. I/O controller **512** can be configured to control interactions with one or more I/O devices. I/O controller **512** can operate by exchanging data between processor **510** and the I/O devices that desire to communicate with processor **510**. The I/O devices and I/O controller **512** can communicate through a data link. The data link can be a one-way link or a two-way link. In some cases, I/O devices can be connected to I/O controller **512** through wireless connections. By way of example, a data link can correspond to PS/2, USB, Firewire, IR, RF, Bluetooth or the like.

[0067] Computing system **500** can include a display device **524** that can be operatively coupled to processor **510**. Display device **524** can be a separate component (peripheral device) or can be integrated with processor **510** and program storage block **502** to form a desktop computer (e.g., all-in-one machine), a laptop, handheld or tablet computing device of the like. Display device **524** can be configured to display a graphical user interface (GUI) including perhaps a pointer or cursor as well as other information to the user. By way of example, display device **524** can be any type of display including a liquid crystal display (LCD), an electroluminescent display (ELD), a field emission display (FED), a light emitting diode display (LED), an organic light emitting diode display (OLED) or the like.

[0068] Display device **524** can be coupled to display controller **526** that can be coupled to processor **510**. Processor **510** can send raw data to display controller **526**, and display controller **526** can send signals to display device **524**. Data can include voltage levels for a plurality of pixels in display device **524** to project an image. In some examples, processor **510** can be configured to process the raw data.

[0069] Computing system **500** can also include a touch screen **530** that can be operatively coupled to processor **510**. Touch screen **530** can be a combination of sensing device **532** and display device **524**, where the sensing device **532** can be a transparent panel that is positioned in front of display device **524** or integrated with display device **524**. In some cases, touch screen **530** can recognize touches and the position and magnitude of touches on its surface. Touch screen **530** can report the touches to processor **510**, and processor **510** can interpret the touches in accordance with its

programming. For example, processor **510** can perform tap and event gesture parsing and can initiate a wake of the device or powering on one or more components in accordance with a particular touch.

[0070] Touch screen **530** can be coupled to a touch controller **540** that can acquire data from touch screen **530** and can supply the acquired data to processor **510**. In some cases, touch controller **540** can be configured to send raw data to processor **510**, and processor **510** can process the raw data. For example, processor **510** can receive data from touch controller **540** and can determine how to interpret the data. The data can include the coordinates of a touch as well as pressure exerted. In some examples, touch controller **540** can be configured to process raw data itself. That is, touch controller **540** can read signals from sensing points **534** located on sensing device **532** and can turn the signals into data that the processor **510** can understand.

[0071] Touch controller **540** can include one or more microcontrollers such as microcontroller **542**, each of which can monitor one or more sensing points **534**. Microcontroller **542** can, for example, correspond to an application specific integrated circuit (ASIC), which works with firmware to monitor the signals from sensing device **532**, process the monitored signals, and report this information to processor **510**.

[0072] One or both display controller **526** and touch controller **540** can perform filtering and/or conversion processes. Filtering processes can be implemented to reduce a busy data stream to prevent processor **510** from being overloaded with redundant or non-essential data. The conversion processes can be implemented to adjust the raw data before sending or reporting them to processor **510**.

[0073] In some examples, sensing device **532** can be based on capacitance. When two electrically conductive members come close to one another without actually touching, their electric fields can interact to form a capacitance. The first electrically conductive member can be one or more of the sensing points **534**, and the second electrically conductive member can be an object **590** such as a finger. As object **590** approaches the surface of touch screen **530**, a capacitance can form between object **590** and one or more sensing points **534** in close proximity to object **590**. By detecting changes in capacitance at each of the sensing points **534** and noting the position of sensing points **534**, touch controller **540** can recognize multiple objects, and determine the location, pressure, direction, speed, and acceleration of object **590** as it moves across the touch screen **530**. For example, touch controller **540** can determine whether the sensed touch is a finger, tap, or an object covering the surface.

[0074] Sensing device **532** can be based on self-capacitance or mutual capacitance. In self-capacitance, each of the sensing points **534** can be provided by an individually charged electrode. As object **590** approaches the surface of the touch screen **530**, the object can capacitively couple to those electrodes in close proximity to object **590**, thereby stealing charge away from the electrodes. The amount of charge in each of the electrodes can be measured by the touch controller **540** to determine the position of one or more objects when they touch or hover over the touch screen **530**. In mutual capacitance, sensing device **532** can include a two layer grid of spatially separated lines or wires (not shown), although other configurations are possible. The upper layer can include lines in rows, while the lower layer can include lines in columns (e.g., orthogonal). Sensing points **534** can be provided at the intersections of the rows and columns. During operation, the rows can be charged, and the charge can capacitively couple from the rows to the columns. As object **590** approaches the surface of the touch screen **530**, object **590** can capacitively couple to the rows in close proximity to object **590**, thereby reducing the charge coupling between the rows and columns. The amount of charge in each of the columns can be measured by touch controller **540** to determine the position of multiple objects when they touch the touch screen **530**.

[0075] Computing system **500** can also include one or more light emitters such as light emitters **506** and one or more light detectors such as light detectors **504** proximate to skin **520** of a user. Light emitters **506** can be configured to generate light, and light detectors **504** can be configured to

measure the return. Light detectors **504** can send measured raw data to processor **510**, and processor **510** can perform noise and/or artifact cancelation to determine the PPG signal and/or perfusion index. Processor **510** can dynamically activate light emitters and/or light detectors based on an application, user skin type, and usage conditions. In some examples, some light emitters and/or light detectors can be activated, while other light emitters and/or light detectors can be deactivated to conserve power, for example. In some examples, processor **510** can store the raw data and/or processed information in a ROM **518** or RAM **522** for historical tracking or for future diagnostic purposes.

[0076] In some examples, the light detectors can measure light information and a processor can determine a PPG signal and/or perfusion index from the return light. Processing of the light information can be performed on the device as well. In some examples, processing of light information need not be performed on the device itself. FIG. **6** illustrates an exemplary configuration in which an electronic device is connected to a host according to examples of the disclosure. Host **610** can be any device external to device **600** including, but not limited to, any of the systems illustrated in FIGS. **1A-1C** or a server. Device **600** can be connected to host **610** through communications link **620**. Communications link **620** can be any connection including, but not limited to, a wireless connection and a wired connection. Exemplary wireless connections include Wi-Fi, Bluetooth, Wireless Direct and Infrared. Exemplary wired connections include Universal Serial Bus (USB), FireWire, Thunderbolt, or any connection requiring a physical cable.

[0077] In operation, instead of processing light information from the light detectors on the device **600** itself, device **600** can send raw data **630** measured from the light detectors over communications link **620** to host **610**. Host **610** can receive raw data **630**, and host **610** can process the light information. Processing the light information can include canceling or reducing any noise due to artifacts and determining physiological signals such as a user's heart rate. Host **610** can include algorithms or calibration procedures to account for differences in a user's characteristics affecting PPG signal and perfusion index. Additionally, host **610** can include storage or memory for tracking a PPG signal and perfusion index history for diagnostic purposes. Host **610** can send the processed result **640** or related information back to device **600**. Based on the processed result **640**, device **600** can notify the user or adjust its operation accordingly. By offloading the processing and/or storage of the light information, device **600** can conserve space and power-enabling device **600** to remain small and portable, as space that could otherwise be required for processing logic can be freed up on the device.

[0078] As discussed above, aspects in of the present technology include the gathering and use of physiological information. The technology may be implemented along with technologies that involve gathering personal data that relates to the user's health and/or uniquely identifies or can be used to contact or locate a specific person. Such personal data can include demographic data, date of birth, location-based data, telephone numbers, email addresses, home addresses, and data or records relating to a user's health or level of fitness (e.g., vital signs measurements, medication information, exercise information, etc.).

[0079] The present disclosure recognizes that a user's personal data, including physiological information, such as data generated and used by the present technology, can be used to the benefit of users. For example, a user's heart rate may allow a user to track or otherwise gain insights about their health or fitness levels.

[0080] The present disclosure contemplates that the entities responsible for the collection, analysis, disclosure, transfer, storage, or other use of such personal data will comply with well-established privacy policies and/or privacy practices. In particular, such entities should implement and consistently use privacy policies and practices that are generally recognized as meeting or exceeding industry or governmental requirements for maintaining personal information data private and secure. Such policies should be easily accessible by users, and should be updated as the collection and/or use of data changes. Personal information from users should be collected for

legitimate and reasonable uses of the entity and not shared or sold outside of those legitimate uses. Further, such collection/sharing should require receipt of the informed consent of the users. Additionally, such entities should consider taking any needed steps for safeguarding and securing access to such personal information data and ensuring that others with access to the personal information data adhere to their privacy policies and procedures. Further, such entities can subject themselves to evaluation by third parties to certify their adherence to widely accepted privacy policies and practices. The policies and practices may be adapted depending on the geographic region and/or the particular type and nature of personal data being collected and used.

[0081] Despite the foregoing, the present disclosure also contemplates embodiments in which users selectively block the collection of, use of, or access to, personal data, including physiological information. For example, a user may be able to disable hardware and/or software elements that collect physiological information. Further, the present disclosure contemplates that hardware and/or software elements can be provided to prevent or block access to personal data that has already been collected. Specifically, users can select to remove, disable, or restrict access to certain health-related applications collecting users' personal health or fitness data.

[0082] A device is disclosed. In some examples, the device comprises: an optical sensing unit comprising: a center region including: a plurality of first light emitters configured to emit first light paths having first wavelengths; one or more second light emitters configured to emit second light paths having second wavelengths, different from the first wavelengths, wherein the plurality of first light emitters is located closer to a peripheral region than the one or more second light emitters; and the peripheral region located around the center region, the peripheral region including: a plurality of light detectors configured to detect the first light paths and the second light paths, wherein the plurality of light detectors is oriented in a concentric arrangement. Additionally or alternatively, the device comprises: a lens including a plurality of regions, the plurality of regions including: a first region overlaying the plurality of first light emitters; and a second region overlaying the one or more second light emitters, wherein optical properties of the first region differ from optical properties of the second region. Additionally or alternatively, in some examples, a center of each light detector is located a first separation distance away from at least one of the one or more second light emitters. Additionally or alternatively, in some examples, each light detector is located a first separation distance from one of the one or more second light emitters and a second separation distance from one of the plurality of first light emitters, wherein the first separation distance is greater than the second separation distance. Additionally or alternatively, in some examples, another light detector is located a third separation distance from the one of the plurality of first light emitters, wherein the third separation distance is greater than the first separation distance, the second separation distance, or both. Additionally or alternatively, in some examples, each of the plurality of first light emitters is located at a radial angle relative to a center of the center region, and edges of two of the plurality of light detectors are located at the radial angle relative to the center of the center region. Additionally or alternatively, in some examples, each of the first light emitters is located such that a separation distance between the respective first light emitter and one of the plurality of light detectors is the same as the separation distance between the respective first light emitter and others of the plurality of light detectors, wherein the one of the plurality of light detectors and the other of the plurality of light detectors are adjacent light detectors. Additionally or alternatively, in some examples, the device further comprises: an optical isolation located between the plurality of first and second light emitters and the plurality of light detectors. Additionally or alternatively, the optical isolation is ring-shaped. Additionally or alternatively, in some examples, walls of the optical isolation define one or more cavities, wherein the plurality of first light emitters and the one or more second light emitters are located in a cavity separate from the plurality of light detectors. Additionally or alternatively, in some examples, the device further comprises: a retroreflector located between the center region and the peripheral region, wherein the retroreflector is configured to reflect light in a direction away from at least one of the plurality of

detectors. Additionally or alternatively, in some examples, the device further comprises: one or more windows located proximate to the center region and the peripheral region; and an opaque mask located between the center region and the peripheral region, wherein the opaque mask is configured to absorb light reflecting off an interface of the one or more windows. Additionally or alternatively, in some examples, the device further comprises: a selective transparent layer located in the peripheral region, the selective transparent layer including a plurality of first sections and a plurality of second sections, wherein the plurality of first sections overlays one or more first portions of the peripheral region and the plurality of second sections overlays one or more second portions of the peripheral region, the one or more second portions overlay the plurality of light detectors. Additionally or alternatively, in some examples, the plurality of first sections includes material that is partially transparent to the first wavelengths and transparent to the second wavelengths. Additionally or alternatively, in some examples, the plurality of second sections excludes material. Additionally or alternatively, in some examples, the selective transparent layer is ring-shaped. Additionally or alternatively, in some examples, the device further comprises: a Fresnel lens located in the center region overlaying the plurality of first light emitters and the one or more second light emitters; and one or more optical film sections located in the peripheral region overlaying the plurality of light detectors, wherein the one or more optical film sections are configured to restrict light passing through the peripheral region. Additionally or alternatively, in some examples, the first wavelengths include one or more visible wavelengths, and the second wavelengths include one or more infrared wavelengths. Additionally or alternatively, in some examples, the first region of the lens is a Fresnel lens, and the second region of the lens includes a plurality of prisms.

[0083] A method for operating a device is disclosed. The method comprises: associating a plurality of light detectors to a plurality of channels during a first time; for each light emitter: emitting light from the respective light emitter; measuring at least a portion of the emitted light by the one or more channels; and selecting and changing to another association such that at least one of the plurality of light detectors is associated with a different channel during a second time, the selected another association based on one or more of the measurements. Additionally or alternatively, in some examples, the association during the first time or the second time includes each channel having adjacent light detectors. Additionally or alternatively, in some examples, the association during the first time or the second time includes each channel having a first set of one or more of the plurality of light detectors and a second set of one or more of the plurality of light detectors, the first set spatially separated from the second set. Additionally or alternatively, in some examples, the method further comprises: determining a physiological information using the measurement from the first set when one light emitter is emitting and using the measurement from the second set when another light emitter is emitting. Additionally or alternatively, in some examples, one association includes a single channel including all of the plurality of light detectors and another association includes multiple channels. Additionally or alternatively, in some examples, signals from the one association are used for primary measurement information, and signals from the other association are used for secondary measurement information. Additionally or alternatively, in some examples, the association during the first time includes two sets of adjacent light detectors, the two sets being non-adjacent. Additionally or alternatively, in some examples, at least one of the plurality of light detectors included in one of the plurality of channels during the first time is included in the same one of the plurality of channels during the second time.

[0084] Although the disclosed examples have been fully described with reference to the accompanying drawings, it is to be noted that various changes and modifications will become apparent to those skilled in the art. Such changes and modifications are to be understood as being included within the scope of the disclosed examples as defined by the appended claims.

Claims

1. A wearable electronic device comprising: a device housing; a strap attached to the device housing and configured to retain the device housing on a user's wrist; a processor positioned within the device housing; and an optical sensing unit positioned at least partially within the device housing and comprising: a central region; a peripheral region surrounding the central region; a first light emitter positioned in the central region and configured to emit first light in a first wavelength range; a second light emitter positioned in the central region and configured to emit second light in a second wavelength range that is different from the first wavelength range; a set of light detectors positioned in the peripheral region and configured to detect the first light and the second light, the set of light detectors at least partially surrounding the first light emitter and the second light emitter; and a selective transparent layer positioned in the peripheral region and comprising: a first section positioned over a light detector of the set of light detectors and transparent to the second wavelength range; and a second section surrounding the first section, the second section at least partially transparent to the first wavelength range and opaque to the second wavelength range.
2. The wearable electronic device of claim 1, wherein: the first section of the selective transparent layer is one of a set of first sections; each of the set of first sections is positioned over a respective light detector of the set of light detectors; and the second section surrounds each of the set of first sections.
3. The wearable electronic device of claim 1, wherein: the first wavelength range comprises infrared wavelengths; and the second wavelength range comprises visible light wavelengths.
4. The wearable electronic device of claim 1, wherein: the first section is at least partially transparent to the first wavelength range; and the second section is fully transparent to the first wavelength range.
5. The wearable electronic device of claim 1, wherein the first section is an open portion of the selective transparent layer.
6. The wearable electronic device of claim 1, wherein: the wearable electronic device further comprises a window positioned over the central region and the peripheral region of the optical sensing unit, the window defining a portion of an exterior surface of the wearable electronic device; and the selective transparent layer is positioned along an interior surface of the window opposite the exterior surface.
7. The wearable electronic device of claim 1, wherein: the optical sensing unit further comprises: a first wall that extends around the central region between the central region and the peripheral region; and a second wall that extends around the peripheral region; the first light emitter and the second light emitter are positioned in a first cavity at least partially defined by the first wall; and the set of light detectors is positioned in a second cavity that is at least partially defined by the first wall and the second wall and that extends around the first cavity.
8. The wearable electronic device of claim 7, wherein: the optical sensing unit further comprises an optical isolation configured to at least partially enclose the first light emitter, the second light emitter, and the set of light detectors; and the first wall, the second wall, the first cavity, and the second cavity cooperatively form the optical isolation.
9. The wearable electronic device of claim 7, wherein: the wearable electronic device further comprises a window positioned over the central region and the peripheral region of the optical sensing unit, the window defining a portion of an exterior surface of the wearable electronic device; and the optical sensing unit further comprises: a lens positioned between the first cavity and the window; an optical film positioned between the second cavity and the window; a first opaque mask positioned between the first wall and the window and extending around the central region; and a second opaque mask positioned between the second wall and the window.
10. A wearable electronic device, comprising: a device housing defining an opening; a processor

positioned within the device housing; a window positioned over the opening and defining a portion of an exterior surface of the wearable electronic device; an optical sensing unit positioned beneath the window and comprising: a central region; a first light emitter positioned in the central region and configured to emit first light in a first wavelength range; a set of second light emitters arranged around the first light emitter and configured to emit second light in a second wavelength range that is different from the first wavelength range; a set of light detectors arranged around the set of second light emitters and configured to detect the first light and the second light; and a selective transparent layer positioned between the set of light detectors and the window and comprising: a set of first sections, each of the set of first sections positioned over a respective light detector of the set of light detectors and at least partially transparent to the second wavelength range; and a second section surrounding each of the set of first sections, the second section transparent to the first wavelength range and at least partially non-transparent to the second wavelength range.

11. The wearable electronic device of claim 10, wherein the optical sensing unit further comprises a wall positioned between the set of second light emitters and the set of light detectors and extending around the first light emitter and the set of second light emitters.

12. The wearable electronic device of claim 11, wherein: the optical sensing unit further comprises a lens positioned between the window and the first light emitter and the set of second light emitters; and the wall extends around the lens.

13. The wearable electronic device of claim 11, wherein the optical sensing unit further comprises an opaque mask positioned between the wall and the window.

14. The wearable electronic device of claim 13, wherein: the wall is a first wall; the opaque mask is a first opaque mask; and the optical sensing unit further comprises: a second wall extending around the set of light detectors; and a second opaque mask positioned between the second wall and the window.

15. The wearable electronic device of claim 11, wherein: the wall is a first wall; and the optical sensing unit further comprises: a second wall extending around the set of light detectors; and an optical film positioned between the set of light detectors and the window and between the first wall and the second wall.

16. The wearable electronic device of claim 10, wherein: the first wavelength range comprises infrared wavelengths; and the second wavelength range comprises visible light wavelengths.

17. An optical sensing unit for a wearable electronic device comprising: an optical isolation comprising: a first wall extending around and at least partially defining a first cavity; a second wall extending around the first wall and at least partially defining a second cavity between the first wall and the second wall; a first light emitter positioned in the first cavity and configured to emit first light in a first wavelength range; a second light emitter positioned in the first cavity and configured to emit second light in a second wavelength range different from the first wavelength range; a set of light detectors positioned in the second cavity of the optical sensing unit and configured to detect the first light and the second light; and a selective transparent layer positioned over the second cavity and comprising: a first section that is transparent to the second wavelength range; and a second section surrounding the first section, the second section at least partially transparent to the first wavelength range and opaque to the second wavelength range.

18. The optical sensing unit of claim 17, further comprising: a Fresnel lens positioned over the first light emitter; and a prism positioned over the second light emitter.

19. The optical sensing unit of claim 17, wherein: the second light emitter is one of a set of second light emitters; and the set of second light emitters is arranged around the first light emitter.

20. The optical sensing unit of claim 19, wherein: the optical sensing unit further comprises: a first lens region positioned over the first light emitter and comprising a Fresnel lens; and a second lens region positioned over the set of second light emitters and comprising a set of prisms, each prism of the set of prisms positioned over a respective second light emitter of the set of second light emitters.

