

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284040

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

JO; Yong Joo

OPTICAL SYSTEM

Abstract

An optical system includes a first lens having refractive power; a second lens having refractive power, both surfaces thereof being convex in a paraxial region; a third lens having refractive power and having an object-side surface that is convex in the paraxial region; a fourth lens having refractive power; a fifth lens having refractive power and having an image-side surface that is concave in the paraxial region; and a sixth lens having refractive power, wherein the first to sixth lenses are sequentially disposed from an object side, and when an Abbe number of the first lens is v_1 and an Abbe number of the second lens is v_2 , $|v_1 - v_2| < 10$ is satisfied, whereby an aberration improvement effect can be increased, and high resolution in images captured thereby can be realized while an amount of light incident through the lenses to an image sensor can be increased.

Inventors: JO; Yong Joo (Suwon-si, KR)

Applicant: Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008629030

Assignee: Samsung Electro-Mechanics Co., Ltd. (Suwon-si, KR)

Appl. No.: 19/220434

Filed: May 28, 2025

Foreign Application Priority Data

KR 10-2014-0156332

Nov. 11, 2014

Related U.S. Application Data

parent US continuation 16990417 20200811 PENDING child US 19220434

parent US continuation 14679428 20150406 parent-grant-document US 10778922 child US 16990417

Publication Classification

Int. Cl.: G02B13/00 (20060101); G02B5/00 (20060101); G02B9/62 (20060101)

U.S. Cl.:

CPC G02B5/005 (20130101); G02B9/62 (20130101); G02B13/0045 (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of application Ser. No. 16/990,417 filed on Aug. 11, 2020, which is a continuation of application Ser. No. 14/679,428 filed on Apr. 6, 2015, now U.S. Pat. No. 10,778,922 issued on Sep. 15, 2020, and claims the benefit under 35 USC 119(a) of Korean Patent Application No. 10-2014-0156332 filed on Nov. 11, 2014, in the Korean Intellectual Property Office, the entire disclosures of which are incorporated herein by reference for all purposes.

BACKGROUND

1. Field

[0002] The present disclosure relates to an optical system.

2. Description of Related Art

[0003] Mobile communications terminals may include camera modules to allow users to make video calls and to capture still and moving images. In addition, as the degree of functionality of the camera modules included in the mobile communications terminals has gradually increased, a demand exists for the camera modules for the mobile communications terminals to include high levels of resolution and high degrees of performance.

[0004] However, as a result of an existing trend of reducing a size and weight of the mobile communications terminals, limitations exists in configuring camera modules to have high levels of resolution and high degrees of performance.

[0005] In order to overcome the limitations in resolution and performance of existing camera modules, an optical system is needed in which an aberration effect is improved, and an amount of light incident through lenses to an image sensor increases to improve resolution of an image or images being captured.

SUMMARY

[0006] This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

[0007] In accordance with an illustrative example, there is provided an optical system, including a first lens; a second lens comprising an object-side surface and an image-side surface, both being convex in a paraxial region; a third lens comprising an object-side surface that is convex in the paraxial region; a fourth lens; a fifth lens comprising an image-side surface that is concave in the paraxial region; and a sixth lens, wherein the first to sixth lenses are sequentially disposed from an object side to an image side, and wherein, v_1 , an Abbe number of the first lens, and, v_2 , an Abbe number of the second lens satisfy $|v_1 - v_2| < 10$.

[0008] The optical system may also include a stop disposed between the second and third lenses, wherein, SD , a radius of the stop and, f , an overall focal length of the optical system including the first to sixth lenses satisfy $SD/f < 0.4$.

[0009] The optical system may also include r_9 , a radius of curvature of an object-side surface of the

fifth lens and, r_{10} , a radius of curvature of the image-side surface of the fifth lens may satisfy r_{10} , $-30 < (r_9 - r_{10}) / (r_9 + r_{10}) < 3$.

[0010] The optical system may also include an image sensor converting an image incident through the first to sixth lenses into an electrical signal, wherein TTL is a distance from an object-side surface of the first lens to an imaging surface of the image sensor and f is an overall focal length of the optical system including the first to sixth lenses satisfying $TTL/f < 1.35$.

[0011] The optical system may also include f , an overall focal length of the optical system including the first to sixth lenses and, f_1 , a focal length of the first lens that satisfy $0.4 < f/f_1 < 0.7$.

[0012] The optical system may also include f , an overall focal length of the optical system including the first to sixth lenses and, f_2 , a focal length of the second lens that satisfy $1.0 < f/f_2 < 1.3$.

[0013] The optical system may also include f , an overall focal length of the optical system including the first to sixth lenses and, f_3 , a focal length of the third lens that satisfy $1.0 < f/f_3 < 1.2$.

[0014] The optical system may also include f , an overall focal length of the optical system including the first to sixth lenses and, f_4 , a focal length of the fourth lens that satisfy $0.2 < f/f_4 < 0.4$.

[0015] The optical system may also include f , an overall focal length of the optical system including the first to sixth lenses and, f_5 , a focal length of the fifth lens that satisfy $0.01 < |f/f_5| < 0.07$.

[0016] The optical system may also include f , an overall focal length of the optical system including the first to sixth lenses and, f_6 , a focal length of the sixth lens that satisfy $0.4 < f/f_6 < 0.6$.

[0017] The optical system may also include f_1 , a focal length of the first lens and, f_2 , a focal length of the second lens that satisfy $1.9 < f_1/f_2 < 2.1$.

[0018] The optical system may also include f_4 , a focal length of the fourth lens and, f_5 , a focal length of the fifth lens that satisfy $4.0 < f_5/f_4 < 15$.

[0019] The optical system may also include f , an overall focal length of the optical system including the first to sixth lenses, f_1 , a focal length of the first lens, and, f_2 , a focal length of the second lens that satisfy $1.5 < f/f_1 + f/f_2 < 2.0$.

[0020] The optical system may also include f , an overall focal length of the optical system including the first to sixth lenses, f_5 , a focal length of the fifth lens, and, f_6 , a focal length of the sixth lens that satisfy $0.4 < |f/f_5| + |f/f_6| < 0.6$.

[0021] The optical system may also include v_3 , an Abbe number of the third lens that satisfies $v_1 - v_3 > 30$.

[0022] The optical system may also include v_3 , an Abbe number of the third lens that satisfies $v_2 - v_3 > 30$.

[0023] The first lens may have a positive refractive power.

[0024] An object-side surface of the first lens may be convex in the paraxial region.

[0025] An image-side surface of the first lens may be concave in the paraxial region.

[0026] The second lens may be a positive refractive power.

[0027] An absolute value of a radius of curvature of an object-side surface of the second lens in the paraxial region may be smaller than an absolute value of a radius of curvature of an image-side surface of the second lens in the paraxial region.

[0028] The third lens may be a negative refractive power.

[0029] An image-side surface of the third lens may be concave in the paraxial region.

[0030] The fourth lens may be a positive refractive power.

[0031] An object-side surface of the fourth lens may be concave in the paraxial region.

[0032] An image-side surface of the fourth lens may be convex in the paraxial region.

[0033] The fifth lens may be a negative refractive power.

[0034] An object-side surface of the fifth lens may be concave in the paraxial region.

[0035] Among the first to sixth lenses, the fifth lens may have a largest absolute value of a focal length.

[0036] An absolute value of a radius of curvature of the image-side surface of the fifth lens in the

paraxial region may be larger than an absolute value of a radius of curvature of an object-side surface of the fifth lens in the paraxial region.

[0037] The fifth lens may have at least one inflection point on at least one of an object-side surface and the image-side surface thereof.

[0038] The sixth lens may have a negative refractive power.

[0039] An object-side surface of the sixth lens may be convex in the paraxial region.

[0040] An image-side surface of the sixth lens may be concave in the paraxial region.

[0041] A radius of curvature of an image-side surface of the sixth lens in the paraxial region may be smaller than a radius of curvature of an object-side surface of the sixth lens in the paraxial region.

[0042] The sixth lens may have at least one inflection point on at least one of an object-side surface and an image-side surface thereof.

[0043] At least one of an object-side surface and an image-side surface of each of the first to sixth lenses may be aspherical.

[0044] In accordance with another aspect, there is provided an optical system, including lenses sequentially arranged from an object side to an image side, wherein a fifth lens of the lenses comprises an object-side surface and an image-side surface, both being concave in a paraxial region, a sixth lens of the lenses comprises an image-side surface that is concave in the paraxial region, and an absolute difference between an Abbe number of a first lens and an Abbe number of a second lens is less than 10.

[0045] At least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens, and an absolute value of a radius of curvature of a second surface of the fifth lens in the paraxial region may be larger than an absolute value of a radius of curvature of the first surface of the fifth lens in the paraxial region.

[0046] A radius of curvature of a second surface of the sixth lens in the paraxial region may be smaller than a radius of curvature of a first surface of the sixth lens in the paraxial region.

[0047] In accordance with another aspect, there is provided an optical system, including lenses sequentially arranged from an object side to an image side, wherein a first lens of the lenses comprises an object-side surface that is convex in a paraxial region, a second lens of the lenses comprises an object-side surface that is convex in the paraxial region, a fifth lens of the lenses comprises an image-side surface that is concave in the paraxial region, and an absolute difference between an Abbe number of the first lens and an Abbe number of the second lens is less than 10.

[0048] At least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens, and an absolute value of a radius of curvature of a second surface of the fifth lens in the paraxial region is larger than an absolute value of a radius of curvature of the first surface of the fifth lens in the paraxial region.

[0049] In accordance with a further aspect, there is provided an optical system including lenses sequentially arranged from an object side to an image side, wherein a first lens of the lenses has a meniscus shape and comprises an object-side surface that is convex in a paraxial region and an image-side surface that is concave in the paraxial region, a second lens of the lenses comprises an object-side and image-side surfaces, each being convex in the paraxial region, and an absolute difference between an Abbe number of the first lens and an Abbe number of the second lens is less than 10.

[0050] A third lens of the lenses may include an object-side surface that is convex in the paraxial region and an image-side surface that is concave in the paraxial region, a fourth lens of the lenses may include an object-side surface that is concave in the paraxial region and an image-side surface that is convex in the paraxial region, a fifth lens of the lenses may include an object-side surface and an image-side surface, both being concave in the paraxial region, and a sixth lens of the lenses may include an object-side surface that is convex in the paraxial region and an image-side surface that is concave in the paraxial region.

[0051] The first, the second, and the fourth lenses may have a positive refractive power, and the

third, the fifth and the sixth lenses may have a negative refractive power.

[0052] At least one inflection point is formed on at least one of the first and second surfaces of the fifth lens, and an absolute value of a radius of curvature of a second surface of the fifth lens in the paraxial region may be larger than an absolute value of a radius of curvature of the first surface of the fifth lens in the paraxial region.

[0053] The third, the fourth, and the sixth lenses may have a meniscus shape, and a radius of curvature of a second surface of the sixth lens in the paraxial region may be smaller than a radius of curvature of a first surface of the sixth lens in the paraxial region.

[0054] An absolute value of a radius of curvature of a first surface of the second lens in the paraxial region may be smaller than an absolute value of a radius of curvature of a second surface of the second lens in the paraxial region.

[0055] Other features and aspects will be apparent from the following detailed description, the drawings, and the claims.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0056] These and/or other aspects will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings in which:

[0057] FIG. 1 is a configuration diagram of an optical system, according to a first embodiment;

[0058] FIG. 2 is graphs having curves representing aberration characteristics of the optical system illustrated in FIG. 1;

[0059] FIG. 3 is a table illustrating respective characteristics of lenses in the optical system illustrated in FIG. 1;

[0060] FIG. 4 is a table illustrating respective aspherical surface coefficients of lenses in the optical system illustrated in FIG. 1;

[0061] FIG. 5 is a configuration diagram of an optical system, according to a second embodiment;

[0062] FIG. 6 is graphs having curves representing aberration characteristics of the optical system illustrated in FIG. 5;

[0063] FIG. 7 is a table illustrating respective characteristics of lenses in the optical system illustrated in FIG. 5;

[0064] FIG. 8 is a table illustrating respective aspherical surface coefficients of lenses in the optical system illustrated in FIG. 5;

[0065] FIG. 9 is a configuration diagram of an optical system, according to a third embodiment;

[0066] FIG. 10 is graphs having curves representing aberration characteristics of the optical system illustrated in FIG. 9;

[0067] FIG. 11 is a table illustrating respective characteristics of lenses in the optical system illustrated in FIG. 9;

[0068] FIG. 12 is a table illustrating respective aspherical surface coefficients of lenses in the optical system illustrated in FIG. 9;

[0069] FIG. 13 is a configuration diagram of an optical system, according to a fourth embodiment;

[0070] FIG. 14 is graphs having curves representing aberration characteristics of the optical system illustrated in FIG. 13;

[0071] FIG. 15 is a table illustrating respective characteristics of lenses in the optical system illustrated in FIG. 13;

[0072] FIG. 16 is a table illustrating respective aspherical surface coefficients of lenses in the optical system illustrated in FIG. 13;

[0073] FIG. 17 is a configuration diagram of an optical system, according to a fifth embodiment;

[0074] FIG. 18 is graphs having curves representing aberration characteristics of the optical system illustrated in FIG. 17;

[0075] FIG. 19 is a table illustrating respective characteristics of lenses in the optical system illustrated in FIG. 17; and

[0076] FIG. 20 is a table illustrating respective aspherical surface coefficients of lenses in the optical system illustrated in FIG. 17.

[0077] Throughout the drawings and the detailed description, unless otherwise described, the same drawing reference numerals will be understood to refer to the same elements, features, and structures. The relative size and depiction of these elements may be exaggerated for clarity, illustration, and convenience.

DETAILED DESCRIPTION

[0078] The following detailed description is provided to assist the reader in gaining a comprehensive understanding of the methods, apparatuses, and/or systems described herein. However, various changes, modifications, and equivalents of the methods, apparatuses, and/or methods described herein will be apparent to one of ordinary skill in the art. For example, the sequences of operations described herein are merely examples, and are not limited to those set forth herein, but may be changed as will be apparent to one of ordinary skill in the art, with the exception of operations necessarily occurring in a certain order. Also, descriptions of functions and constructions that are well known to one of ordinary skill in the art may be omitted for increased clarity and conciseness.

[0079] Throughout the drawings and the detailed description, the same reference numerals refer to the same elements. The drawings may not be to scale, and the relative size, proportions, and depiction of elements in the drawings may be exaggerated for clarity, illustration, and convenience.

[0080] The features described herein may be embodied in different forms, and are not to be construed as being limited to the examples described herein. Rather, the examples described herein have been provided so that this disclosure will be thorough and complete, and will convey the full scope of the disclosure to one of ordinary skill in the art.

[0081] It will be understood that, although the terms first, second, third, etc., may be used herein to describe various lenses, these lenses should not be limited by these terms. These terms are only used to distinguish one lens from another lens. These terms do not necessarily imply a specific order or arrangement of the lenses. Thus, a first lens discussed below could be termed a second lens without departing from the teachings description of the various embodiments.

[0082] In the following lens configuration diagrams, thicknesses, sizes, and shapes of lenses may be exaggerated for clarity. Particularly, the shapes of spherical surfaces and aspherical surfaces, as illustrated in the lens configuration diagrams, are only illustrated by way of example, but are not limited to those illustrated in the drawings.

[0083] In some configurations, lenses included in lens modules are formed of plastic or polycarbonate, a material lighter than glass. In other configurations, some of the lenses included in the modules are formed of plastic or polycarbonate, and other lenses may be formed of glass. According to some configurations, a lens module may include five or more lenses in order to achieve high levels of resolution in images being captured.

[0084] In accordance with an illustrative configuration, a first lens refers to a lens closest to an object, while a sixth lens refers to a lens closest to an imaging surface.

[0085] Further, a surface of each lens closest to an object is referred to as a first surface or an object-side surface, and a surface of each lens closest to an imaging surface is referred to as a second surface or an image-side surface. Further, all numerical values of radii of curvature, thicknesses, and other parameters of the lenses are represented in millimeters (mm).

[0086] In addition, a paraxial region refers to a very narrow region in the vicinity of an optical axis. Paraxial region or space region near an axis is where the angle α between rays and optical axis is so small that $\sin \alpha$ and $\tan \alpha$ can be replaced with sufficient accuracy by the angle α .

[0087] In accordance with an illustrative example, the embodiments described of the optical system include six lenses. However, a person of ordinary skill in the relevant art will appreciate that the number of lenses in the optical system may vary, for example, between two to five lenses, while achieving the various results and benefits described hereinbelow.

[0088] In one example, the optical system includes a first lens, a second lens, a third lens, a fourth lens, a fifth lens, and a sixth lens.

[0089] However, the optical system is not limited to include lenses and may further include other components, if necessary. For example, the optical system may include a stop to control an amount of light. In addition, the optical system may further include an infrared cut-off filter filtering infrared light. Further, the optical system may further include an image sensor converting an image of a subject incident thereon into electrical signals. Further, the optical system may further include a gap maintaining member to adjust a gap between lenses.

[0090] The first through sixth lenses configuring the optical system, according to an embodiment, are formed of materials including glass, plastic or other similar types of polycarbonate materials. In another embodiment, at least one of the first through sixth lenses is formed of a material different from the materials forming the other first through sixth lenses.

[0091] In addition, at least one of the first to sixth lenses may have an aspherical object-side or image-side surface. Alternatively, each of the first to sixth lenses may have at least one aspherical object-side or image-side surface.

[0092] That is, at least one of first and second surfaces of the first to sixth lenses may be aspherical. In one example, the aspherical surfaces of the first to sixth lenses may be represented by the following Equation 1:

[00001]
$$Z = \frac{cY^2}{1 + \sqrt{1 - (1 + K)c^2Y^2}} + AY^4 + BY^6 + CY^8 + DY^{10} + EY^{12} + FY^{14} + \dots \text{Math.} \quad (1)$$

[0093] In this equation, c is curvature (the inverse of a radius of curvature) at an apex of the lens, K is a conic constant, and Y is a distance from a certain point on the aspherical surface of the lens to an optical axis in a direction perpendicular to the optical axis. In addition, constants A to F refer to aspherical surface coefficients. In addition, Z is a distance between the certain point on the aspherical surface at the distance Y and a tangential plane meeting the apex of the aspherical surface of the lens.

[0094] Each of the first through sixth lenses has a refractive power, either negative or positive. For instance, in one configuration, from the object side towards the image side, the first lens has a positive refractive power, the second lens has a positive refractive power, the third lens has a negative refractive power, the fourth lens has a positive refractive power, the fifth lens has a negative refractive power, and the sixth lens has a negative refractive power. A person of ordinary skill in the relevant art will appreciate that each of the first and sixth lenses may be configured in an opposite refractive power from the configuration described above. For example, in an alternative configuration, the first lens has a positive refractive power, the second lens has a positive refractive power, the third lens has a negative refractive power, the fourth lens has a negative refractive power, the fifth lens has a positive refractive power, and the sixth lens has a negative refractive power.

[0095] The optical system configured as described above improves optical performance through aberration improvement. In addition, an increased amount of light is incident through the lenses to the image sensor while images captured thereby have high levels of resolution.

[0096] The optical system according to embodiments satisfies Conditional Expression 1.

[00002]
$$v_1 - v_2 < 10 \quad (\text{ConditionalExpression1})$$

[0097] Here, v_1 is an Abbe number of the first lens, and v_2 is an Abbe number of the second lens.

[0098] The optical system according to embodiments satisfies Conditional Expression 2.

[00003]
$$SD/f < 0.4 \quad (\text{ConditionalExpression2})$$

[0099] Here, SD is a radius of the stop, and f is an overall focal length of the optical system.

[0100] The optical system according to embodiments satisfies Conditional Expression 3.

[00004] $-30 < (r_9 - r_{10}) / (r_9 + r_{10}) < 3$ (ConditionalExpression3)

[0101] Here, r₉ is a radius of curvature of an object-side surface of the fifth lens, and r₁₀ is a radius of curvature of an image-side surface of the fifth lens.

[0102] The optical system according to embodiments satisfies Conditional Expression 4.

[00005] $TTL / f < 1.35$ (ConditionalExpression4)

[0103] Here, TTL is a distance from an object-side surface of the first lens to an imaging surface of the image sensor, and f is the overall focal length of the optical system.

[0104] The optical system according to embodiments satisfies Conditional Expression 5.

[00006] $0.4 < f / f_1 < 0.7$ (ConditionalExpression5)

[0105] Here, f is the overall focal length of the optical system, and f₁ is a focal length of the first lens.

[0106] The optical system according to embodiments satisfies Conditional Expression 6.

[00007] $1. < f / f_2 < 1.3$ (ConditionalExpression6)

[0107] Here, f is the overall focal length of the optical system, and f₂ is a focal length of the second lens.

[0108] The optical system according to embodiments satisfies Conditional Expression 7.

[00008] $1. < f / f_3 < 1.2$ (ConditionalExpression7)

[0109] Here, f is the overall focal length of the optical system, and f₃ is a focal length of the third lens.

[0110] The optical system according to embodiments satisfies Conditional Expression 8.

[00009] $0.2 < f / f_4 < 0.4$ (ConditionalExpression8)

[0111] Here, f is the overall focal length of the optical system, and f₄ is a focal length of the fourth lens.

[0112] The optical system according to embodiments satisfies Conditional Expression 9.

[00010] $0.01 < f / f_5 < 0.07$ (ConditionalExpression9)

[0113] Here, f is the overall focal length of the optical system, and f₅ is a focal length of the fifth lens.

[0114] The optical system according to embodiments satisfies Conditional Expression 10.

[00011] $0.4 < f / f_6 < 0.6$ (ConditionalExpression10)

[0115] Here, f is the overall focal length of the optical system, and f₆ is a focal length of the sixth lens.

[0116] The optical system according to embodiments satisfies Conditional Expression 11.

[00012] $1.9 < f_1 / f_2 < 2.1$ (ConditionalExpression11)

[0117] Here, f₁ is the focal length of the first lens, and f₂ is the focal length of the second lens.

[0118] The optical system according to embodiments satisfies Conditional Expression 12.

[00013] $4 < f_5 / f_4 < 15$ (ConditionalExpression12)

[0119] Here, f₅ is the focal length of the fifth lens, and f₄ is the focal length of the fourth lens.

[0120] The optical system according to embodiments satisfies Conditional Expression 13.

[00014] $1.5 < f / f_1 + f / f_2 < 2.0$ (ConditionalExpression13)

[0121] Here, f is the overall focal length of the optical system, f₁ is the focal length of the first lens, and f₂ is the focal length of the second lens.

[0122] The optical system according to embodiments satisfies Conditional Expression 14.

[00015] $0.4 < f / f_5 + f / f_6 < 0.6$ (ConditionalExpression14)

[0123] Here, f is the overall focal length of the optical system, f₅ is the focal length of the fifth

lens, and f_6 is the focal length of the sixth lens.

[0124] The optical system according to embodiments satisfies Conditional Expression 15.

[00016] $v_1 - v_3 > 30$ (ConditionalExpression15)

[0125] Here, v_1 is the Abbe number of the first lens, and v_3 is an Abbe number of the third lens.

[0126] The optical system according to embodiments satisfies Conditional Expression 16.

[00017] $v_2 - v_3 > 30$ (ConditionalExpression16)

[0127] Here, v_2 is the Abbe number of the second lens, and v_3 is the Abbe number of the third lens.

[0128] Next, the first to sixth lenses configuring the optical system, according to various embodiments will be described.

[0129] The first lens includes a positive refractive power. In addition, the first lens has a meniscus shape with an object-side surface being convex. For example, a first surface of the first lens is convex in the paraxial region, and a second surface of the first lens is concave in the paraxial region.

[0130] At least one of the first and second surfaces of the first lens is aspherical. In an example, both surfaces of the first lens may be aspherical. In another example, neither of the first and second surfaces are aspherical.

[0131] The second lens has a positive refractive power. In addition, the second lens has two convex surfaces. For example, first and second surfaces of the second lens may be convex in the paraxial region.

[0132] At least one of the first and second surfaces of the second lens is aspherical. For example, both surfaces of the second lens are aspherical. In another example, neither of the first and second surfaces of the second lens are aspherical.

[0133] In addition, in one configuration, an absolute value of a radius of curvature of an object-side surface of the second lens in the paraxial region is smaller than an absolute value of a radius of curvature of an image-side surface of the second lens in the paraxial region.

[0134] The third lens has a negative refractive power. In addition, the third lens has a meniscus shape of which an object-side surface is convex. In an example, a first surface of the third lens is convex in the paraxial region, and a second surface of the third lens may be concave in the paraxial region. In an alternative configuration, the first surface of the third lens is substantially flat.

[0135] At least one of the first and second surfaces of the third lens is aspherical. For example, both surfaces of the third lens are aspherical. In another example, neither surface of the third lens is aspherical.

[0136] The fourth lens has a positive refractive power. In one configuration, the fourth lens has a meniscus shape of which an image-side surface is convex. A first surface of the fourth lens is concave in the paraxial region, and a second surface of the fourth lens is convex in the paraxial region.

[0137] At least one of the first and second surfaces of the fourth lens is aspherical. For example, both surfaces of the fourth lens are aspherical. In another example, neither surface of the fourth lens is aspherical.

[0138] The fifth lens has a negative refractive power. In addition, both surfaces of the fifth lens are concave. For instance, the first and second surfaces of the fifth lens are concave in the paraxial region. In another illustrative configuration, the first surface of the fifth lens is concave in the paraxial region and end portions thereof are substantially flat and the second surface of the fifth lens is convex in the paraxial region.

[0139] In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the fifth lens. For example, the first surface of the fifth lens is concave in the paraxial region and becomes convex at an edge thereof. In addition, the second surface of the fifth lens is concave in the paraxial region and becomes convex at an edge thereof.

[0140] Further, an absolute value of a radius of curvature of an image-side surface of the fifth lens

in the paraxial region may be larger than an absolute value of a radius of curvature of an object-side surface of the fifth lens in the paraxial region.

[0141] The sixth lens has negative refractive power. In addition, the sixth lens may have a meniscus shape of which an object-side surface is convex. For example, a first surface of the sixth lens is convex in the paraxial region, and a second surface of the sixth lens is concave in the paraxial region.

[0142] At least one of the first and second surfaces of the sixth lens is aspherical. For example, both surfaces of the sixth lens are aspherical. In another example, neither surface of the sixth lens is aspherical.

[0143] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the sixth lens. For example, the first surface of the sixth lens is convex in the paraxial region and becomes concave at an edge thereof. In addition, the second surface of the sixth lens is concave in the paraxial region and becomes convex at an edge thereof.

[0144] Furthermore, a radius of curvature of an image-side surface of the sixth lens in the paraxial region is smaller than a radius of curvature of an object-side surface of the sixth lens in the paraxial region.

[0145] In one embodiment, among the first to sixth lenses, the fifth lens has the largest absolute value of a focal length.

[0146] Also, in one embodiment, each of the first to sixth lenses may be separate lenses configured as described above. A distance between lenses may vary. In another embodiment, at least one of the first to sixth lenses may be operatively connected or in contact with another one of the first to sixth lenses.

[0147] In a further alternative embodiment, two or more of the lenses of the first to sixth lenses may be configured as a group and in operative connection or contact with another lens. For instance, the first, second, and third lenses may be in contact with each other as a first group lens, while the fourth, fifth, and sixth lenses are configured separate from each other and from the first group lens. In the alternative, the first, second, and third lenses may be in contact with each other as a first group lens, the fourth and the fifth lenses may be in contact with each other as a second group lens, and the sixth lens is configured separate from the first and second group lenses.

[0148] In the optical system configured as described above, of the first through sixth lenses perform an aberration correction function, whereby aberration performance is improved and high resolution in images captured thereby may be realized while an amount of light incident through the lenses to the image sensor is increased.

[0149] An optical system according to a first embodiment will be described with reference to FIGS. 1 through 4.

[0150] The optical system according to the first embodiment includes a first lens **110**, a second lens **120**, a third lens **130**, a fourth lens **140**, a fifth lens **150**, and a sixth lens **160**. The optical system also includes a stop, an infrared cut-off filter **170**, and an image sensor **180**. As illustrated in Table 1, a focal length (f1) of the first lens **110** is 7.781 mm, a focal length (f2) of the second lens **120** is 3.996 mm, a focal length (f3) of the third lens **130** is -4.095 mm, a focal length (f4) of the fourth lens **140** is 16.346 mm, a focal length (f5) of the fifth lens **150** is -67.58 mm, a focal length (f6) of the sixth lens **160** is -9.268 mm, and an overall focal length (f) of the optical system is 4.685 mm. Also, TTL, a distance from an object-side surface of the first lens **110** to an imaging surface of the image sensor **180** is 5.5. Further, Fno, which indicates how much light can pass through the lens, is 2.2. Fno is inversely proportional to the focal length of the lens and directly proportional to the diameter of the effective aperture of the lens. For a given focal length, the larger the aperture of the lens the smaller the Fno and a brighter image is produced.

TABLE-US-00001 TABLE 1 Fno 2.2 TTL 5.5 f 4.685 f1 7.781 f2 3.996 f3 -4.095 f4 16.346 f5 -67.58 f6 -9.268 Stop/f 0.363 TTL/f 1.174 $(r9 - r10)/(r9 + r10)$ -1.777

[0151] For this example, respective characteristics, such as radii of curvature, thicknesses,

refractive indices, and Abbe numbers of lenses are illustrated in FIG. 3.

[0152] In the first embodiment, the first lens **110** has a positive refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the first lens **110** is convex in the paraxial region, and a second surface of the first lens **110** is concave in the paraxial region.

[0153] The second lens **120** has a positive refractive power, and both surfaces thereof are convex. For example, the first and second surfaces of the second lens **120** are convex in the paraxial region.

[0154] In addition, an absolute value of a radius of curvature of the first surface of the second lens **120** in the paraxial region is smaller than an absolute value of a radius of curvature of the second surface of the second lens **120** in the paraxial region.

[0155] The third lens **130** has a negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the third lens **130** is convex in the paraxial region, and a second surface of the third lens **130** is concave in the paraxial region.

[0156] The fourth lens **140** has a positive refractive power, and has a meniscus shape of an image-side surface is convex. For example, a first surface of the fourth lens **140** is concave in the paraxial region, and a second surface of the fourth lens **140** is convex in the paraxial region.

[0157] The fifth lens **150** has a negative refractive power and both surfaces thereof are concave. For example, first and second surfaces of the fifth lens **150** are concave in the paraxial region.

[0158] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the fifth lens **150**.

[0159] In addition, an absolute value of a radius of curvature of the second surface of the fifth lens **150** in the paraxial region is larger than an absolute value of a radius of curvature of the first surface of the fifth lens **150** in the paraxial region.

[0160] The sixth lens **160** has a negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the sixth lens **160** is convex in the paraxial region, and a second surface of the sixth lens **160** is concave in the paraxial region.

[0161] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the sixth lens **160**.

[0162] In addition, a radius of curvature of the second surface of the sixth lens **160** in the paraxial region is smaller than a radius of curvature of the first surface of the sixth lens **160** in the paraxial region.

[0163] Although FIG. 1 illustrates the sixth lens **160** to be in contact to the infrared cut-off filter **170**, the sixth lens **160** may be placed at a distance from the infrared cut-off filter **170**. In an alternative embodiment, the infrared cut-off filter **170** may be shaped to mirror the image-side surface or the second surface of the sixth lens **160**, thereby forming an integral part of the sixth lens **160**.

[0164] In accordance with an embodiment, the respective surfaces of the first to sixth lenses **110** to **160** have aspherical coefficients as illustrated in FIG. 4. However, a person of ordinary skill in the art will appreciate that some variation in the aspherical coefficients may exist without departing from the results and benefits of the present first embodiment.

[0165] In addition, among the first to sixth lenses **110** to **160**, the fifth lens **150** has the largest absolute value of a focal length.

[0166] In addition, the stop is disposed between the second lens **120** and the third lens **130**. In an alternative configuration, the stop may be disposed on an object side of the first lens **110**, closest to the object side of the optical system. In a further alternative configuration, the stop may be disposed on the object side of the first lens **110** and is aligned along an axis perpendicular to an axial point of the object-side surface of the first lens **110**.

[0167] In addition, the optical system configured as described above has aberration characteristics illustrated in FIG. 2. However, a person of ordinary skill in the art will appreciate that some variation in the aberration characteristics may exist without departing from the results and benefits

of the present first embodiment.

[0168] An optical system, according to a second embodiment, will be described with reference to FIGS. 5 through 8.

[0169] The optical system, according to the second embodiment, includes a first lens **210**, a second lens **220**, a third lens **230**, a fourth lens **240**, a fifth lens **250**, and a sixth lens **260**. The optical system further includes a stop, an infrared cut-off filter **270**, and an image sensor **280**.

[0170] As illustrated in Table 2, a focal length (f1) of the first lens **210** may be 7.817 mm, a focal length (f2) of the second lens **220** may be 3.991 mm, a focal length (f3) of the third lens **230** may be -4.14 mm, a focal length (f4) of the fourth lens **240** may be 15.395 mm, a focal length (f5) of the fifth lens **250** may be -89.394 mm, a focal length (f6) of the sixth lens **260** may be -8.772 mm, and an overall focal length (f) of the optical system may be 4.589 mm. Also, TTL, a distance from an object-side surface of the first lens **210** to an imaging surface of the image sensor **280** is 5.40021. Further, Fno is 2.1.

TABLE-US-00002 TABLE 2 Fno 2.1 TTL 5.40021 f 4.589 f1 7.817 f2 3.991 f3 -4.14 f4 15.395 f5 -89.394 f6 -8.772 Stop/f 0.363 TTL/f 1.177 (r9 - r10)/(r9 + r10) -2.37

[0171] In this example, respective characteristics, such as radii of curvature, thicknesses, refractive indices, and Abbe numbers of lenses are illustrated in FIG. 7.

[0172] In the second embodiment, the first lens **210** has a positive refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the first lens **210** is convex in the paraxial region, and a second surface of the first lens **210** is concave in the paraxial region.

[0173] The second lens **220** has a positive refractive power, and both surfaces thereof are convex. For example, first and second surfaces of the second lens **220** are convex in the paraxial region.

[0174] In addition, an absolute value of a radius of curvature of the first surface of the second lens **220** in the paraxial region is smaller than an absolute value of a radius of curvature of the second surface of the second lens **220** in the paraxial region.

[0175] The third lens **230** has a negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the third lens **230** is convex in the paraxial region, and a second surface of the third lens **230** is concave in the paraxial region.

[0176] The fourth lens **240** has a positive refractive power, and has a meniscus shape of which an image-side surface is convex. For example, a first surface of the fourth lens **240** is concave in the paraxial region, and a second surface of the fourth lens **240** is convex in the paraxial region.

[0177] The fifth lens **250** has a negative refractive power, and both surfaces thereof are concave. For example, first and second surfaces of the fifth lens **250** are concave in the paraxial region.

[0178] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the fifth lens **250**.

[0179] In addition, an absolute value of a radius of curvature of the second surface of the fifth lens **250** in the paraxial region is larger than an absolute value of a radius of curvature of the first surface of the fifth lens **250** in the paraxial region.

[0180] The sixth lens **260** has a negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the sixth lens **260** is convex in the paraxial region, and a second surface of the sixth lens **260** is concave in the paraxial region.

[0181] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the sixth lens **260**.

[0182] In addition, a radius of curvature of the second surface of the sixth lens **260** in the paraxial region is smaller than a radius of curvature of the first surface of the sixth lens **260** in the paraxial region.

[0183] Although FIG. 5 illustrates the sixth lens **260** to be in contact to the infrared cut-off filter **270**, the sixth lens **260** may be placed at a distance from the infrared cut-off filter **270**. In an alternative embodiment, the infrared cut-off filter **270** may be shaped to mirror the image-side

surface or the second surface of the sixth lens **260**, thereby forming an integral part of the sixth lens **260**.

[0184] In accordance with an embodiment, the respective surfaces of the first to sixth lenses **210** to **260** have aspherical coefficients as illustrated in FIG. **8**. However, a person of ordinary skill in the art will appreciate that some variation in the aspherical coefficients may exist without departing from the results and benefits of the present second embodiment.

[0185] In addition, among the first to sixth lenses **210** to **260**, the fifth lens **250** has the largest absolute value of a focal length.

[0186] In addition, the stop is disposed between the second lens **220** and the third lens **230**. In an alternative configuration, the stop may be disposed on an object side of the first lens **210**, closest to the object side of the optical system. In a further alternative configuration, the stop may be disposed on the object side of the first lens **210** and is aligned along an axis perpendicular to an axial point of the object-side surface of the first lens **210**.

[0187] In addition, the optical system configured as described above has aberration characteristics illustrated in FIG. **6**. However, a person of ordinary skill in the art will appreciate that some variation in the aberration characteristics may exist without departing from the results and benefits of the present second embodiment.

[0188] An optical system according to a third embodiment will be described with reference to FIGS. **9** through **12**.

[0189] The optical system according to the third embodiment includes a first lens **310**, a second lens **320**, a third lens **330**, a fourth lens **340**, a fifth lens **350**, and a sixth lens **360**. The optical system further includes a stop, an infrared cut-off filter **370**, and an image sensor **380**.

[0190] As illustrated in Table 3, a focal length (f_1) of the first lens **310** is 8.245 mm, a focal length (f_2) of the second lens **320** is 3.967 mm, a focal length (f_3) of the third lens **330** is -4.126 mm, a focal length (f_4) of the fourth lens **340** is 14.899 mm, a focal length (f_5) of the fifth lens **350** is -143.125 mm, a focal length (f_6) of the sixth lens **360** is -9.144 mm, and an overall focal length (f) of the optical system is 4.541 mm. Also, TTL, a distance from an object-side surface of the first lens **310** to an imaging surface of the image sensor **380** is 4.541. Further, F_{no} , which indicates how much light can pass through the lens, is 2.0.

TABLE-US-00003 TABLE 3 F_{no} 2 TTL 5.4 f 4.541 f_1 8.245 f_2 3.967 f_3 -4.126 f_4 14.899 f_5 -143.125 f_6 -9.144 Stop/ f 0.385 TTL/ f 1.189 $(r_9 - r_{10})/(r_9 + r_{10})$ -13.422

[0191] In this example, respective characteristics, such as radii of curvature, thicknesses, refractive indices, and Abbe numbers of lenses are illustrated in FIG. **11**.

[0192] In the third embodiment, the first lens **310** has a positive refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the first lens **310** is convex in the paraxial region, and a second surface of the first lens **310** is concave in the paraxial region.

[0193] The second lens **320** has a positive refractive power, and both surfaces thereof may be convex. For example, first and second surfaces of the second lens **320** are convex in the paraxial region.

[0194] In addition, an absolute value of a radius of curvature of the first surface of the second lens **320** in the paraxial region is smaller than an absolute value of a radius of curvature of the second surface of the second lens **320** in the paraxial region.

[0195] The third lens **330** has a negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the third lens **330** is convex in the paraxial region, and a second surface of the third lens **330** is concave in the paraxial region.

[0196] The fourth lens **340** has a positive refractive power, and has a meniscus shape of which an image-side surface is convex. For example, a first surface of the fourth lens **340** is concave in the paraxial region, and a second surface of the fourth lens **340** is convex in the paraxial region.

[0197] The fifth lens **350** has a negative refractive power, and both surfaces thereof are concave.

For example, first and second surfaces of the fifth lens **350** are concave in the paraxial region. [0198] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the fifth lens **350**.

[0199] In addition, an absolute value of a radius of curvature of the second surface of the fifth lens **350** in the paraxial region is larger than an absolute value of a radius of curvature of the first surface of the fifth lens **350** in the paraxial region.

[0200] The sixth lens **360** has a negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the sixth lens **360** is convex in the paraxial region, and a second surface of the sixth lens **360** is concave in the paraxial region.

[0201] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the sixth lens **360**.

[0202] In addition, a radius of curvature of the second surface of the sixth lens **360** in the paraxial region is smaller than a radius of curvature of the first surface of the sixth lens **360** in the paraxial region. Although FIG. **9** illustrates the sixth lens **360** to be in contact to the infrared cut-off filter **370**, the sixth lens **360** may be placed at a distance from the infrared cut-off filter **370**. In an alternative embodiment, the infrared cut-off filter **370** may be shaped to mirror the image-side surface or the second surface of the sixth lens **360**, thereby forming an integral part of the sixth lens **360**.

[0203] Meanwhile, the respective surfaces of the first to sixth lenses **310** to **360** have aspherical coefficients as illustrated in FIG. **12**. However, a person of ordinary skill in the art will appreciate that some variation in the aspherical coefficients may exist without departing from the results and benefits of the present third embodiment.

[0204] In addition, among the first to sixth lenses **310** to **360**, the fifth lens **350** has the largest absolute value of a focal length.

[0205] In addition, the stop is disposed between the second lens **320** and the third lens **330**. In an alternative configuration, the stop may be disposed on an object side of the first lens **310**, closest to the object side of the optical system. In a further alternative configuration, the stop may be disposed on the object side of the first lens **310** and is aligned along an axis perpendicular to an axial point of the object-side surface of the first lens **310**.

[0206] In addition, the optical system configured as described above has aberration characteristics as illustrated in FIG. **10**. However, a person of ordinary skill in the art will appreciate that some variation in the aberration characteristics may exist without departing from the results and benefits of the present third embodiment.

[0207] An optical system according to a fourth embodiment will be described with reference to FIGS. **13** through **16**.

[0208] The optical system according to the fourth embodiment includes a first lens **410**, a second lens **420**, a third lens **430**, a fourth lens **440**, a fifth lens **450**, and a sixth lens **460**. The optical system also includes a stop, an infrared cut-off filter **470**, and an image sensor **480**.

[0209] As illustrated in Table 4, a focal length (f_1) of the first lens **410** is 8.034 mm, a focal length (f_2) of the second lens **420** is 3.996 mm, a focal length (f_3) of the third lens **430** is -4.163 mm, a focal length (f_4) of the fourth lens **440** is 16.369 mm, a focal length (f_5) of the fifth lens **450** is -237.166 mm, a focal length (f_6) of the sixth lens **460** is -9.251 mm, and an overall focal length (f) of the optical system is 4.526 mm. Also, TTL, a distance from an object-side surface of the first lens **410** to an imaging surface of the image sensor **480** is 4.526. Further, F_{no} , which indicates how much light can pass through the lens, is 2.2.

TABLE-US-00004 TABLE 4 F_{no} 2.2 TTL 5.4 f 4.526 f_1 8.034 f_2 3.996 f_3 -4.163 f_4 16.369 f_5 -237.166 f_6 -9.251 Stop/ f 0.386 TTL/ f 1.193 $(r_9 - r_{10})/(r_9 + r_{10})$ 1.877

[0210] In this example, respective characteristics, such as radii of curvature, thicknesses, refractive indices, and Abbe numbers of lenses are illustrated in FIG. **15**.

[0211] In the fourth embodiment, the first lens **410** has a positive refractive power, and has a

meniscus shape of which an object-side surface is convex. For example, a first surface of the first lens **410** is convex in the paraxial region, and a second surface of the first lens **410** is concave in the paraxial region.

[0212] The second lens **420** has a positive refractive power, and both surfaces thereof are convex. For example, first and second surfaces of the second lens **420** are convex in the paraxial region.

[0213] In addition, an absolute value of a radius of curvature of the first surface of the second lens **420** in the paraxial region is smaller than an absolute value of a radius of curvature of the second surface of the second lens **420** in the paraxial region.

[0214] The third lens **430** has a negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the third lens **430** is convex in the paraxial region, and a second surface of the third lens **430** is concave in the paraxial region.

[0215] The fourth lens **440** has a positive refractive power, and has a meniscus shape of which an image-side surface is convex. For example, a first surface of the fourth lens **440** is concave in the paraxial region, and a second surface of the fourth lens **440** is convex in the paraxial region.

[0216] The fifth lens **450** has a negative refractive power and both surfaces thereof are concave. For example, first and second surfaces of the fifth lens **450** are concave in the paraxial region.

[0217] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the fifth lens **450**.

[0218] In addition, an absolute value of a radius of curvature of the second surface of the fifth lens **450** in the paraxial region is larger than an absolute value of a radius of curvature of the first surface of the fifth lens **450** in the paraxial region.

[0219] The sixth lens **460** has negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the sixth lens **460** is convex in the paraxial region, and a second surface of the sixth lens **460** is concave in the paraxial region.

[0220] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the sixth lens **460**.

[0221] In addition, a radius of curvature of the second surface of the sixth lens **460** in the paraxial region is smaller than a radius of curvature of the first surface of the sixth lens **460** in the paraxial region. Although FIG. 13 illustrates the sixth lens **460** to be in contact to the infrared cut-off filter **470**, the sixth lens **460** may be placed at a distance from the infrared cut-off filter **470**. In an alternative embodiment, the infrared cut-off filter **470** may be shaped to mirror the image-side surface or the second surface of the sixth lens **460**, thereby forming an integral part of the sixth lens **460**.

[0222] Furthermore, the respective surfaces of the first to sixth lenses **410** to **460** have aspherical coefficients as illustrated in FIG. 16. However, a person of ordinary skill in the art will appreciate that some variation in the aspherical coefficients may exist without departing from the results and benefits of the present third embodiment.

[0223] In addition, among the first to sixth lenses **410** to **460**, the fifth lens **450** has the largest absolute value of a focal length.

[0224] In addition, the stop is disposed between the second lens **420** and the third lens **430**. In an alternative configuration, the stop may be disposed on an object side of the first lens **410**, closest to the object side of the optical system. In a further alternative configuration, the stop may be disposed on the object side of the first lens **410** and is aligned along an axis perpendicular to an axial point of the object-side surface of the first lens **410**.

[0225] In addition, the optical system configured as described above has aberration characteristics illustrated in FIG. 14. However, a person of ordinary skill in the art will appreciate that some variation in the aberration characteristics may exist without departing from the results and benefits of the present third embodiment.

[0226] An optical system according to a fifth embodiment in the present disclosure will be described with reference to FIGS. 17 through 20.

[0227] The optical system according to the fifth embodiment includes a first lens **510**, a second lens **520**, a third lens **530**, a fourth lens **540**, a fifth lens **550**, and a sixth lens **560**. The optical system also includes a stop, an infrared cut-off filter **570**, and an image sensor **580**.

[0228] As illustrated in Table 5, a focal length (f_1) of the first lens **510** is 8.112 mm, a focal length (f_2) of the second lens **520** is 3.989 mm, a focal length (f_3) of the third lens **530** is -4.165 mm, a focal length (f_4) of the fourth lens **540** is 15.535 mm, a focal length (f_5) of the fifth lens **550** is -153.086 mm, a focal length (f_6) of the sixth lens **560** is -9.084 mm, and an overall focal length (f) of the optical system is 4.514 mm. Also, TTL, a distance from an object-side surface of the first lens **510** to an imaging surface of the image sensor **580** is 5.4. Further, F_{no} , which indicates how much light can pass through the lens, is 1.95.

TABLE-US-00005 TABLE 5 F_{no} 1.95 TTL 5.4 f 4.514 f_1 8.112 f_2 3.989 f_3 -4.165 f_4 15.535 f_5 -153.086 f_6 -9.084 Stop/ f 0.3466 TTL/ f 1.196 $(r_9 - r_{10})/(r_9 + r_{10})$ 1.022

[0229] In this example, respective characteristics, such as radii of curvature, thicknesses, refractive indices, and Abbe numbers of lenses are illustrated in FIG. **19**.

[0230] In the fifth embodiment, the first lens **510** has a positive refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the first lens **510** is convex in the paraxial region, and a second surface of the first lens **510** is concave in the paraxial region.

[0231] The second lens **520** has a positive refractive power and both surfaces thereof are convex. For example, first and second surfaces of the second lens **520** are convex in the paraxial region.

[0232] In addition, an absolute value of a radius of curvature of the first surface of the second lens **520** in the paraxial region is smaller than an absolute value of a radius of curvature of the second surface of the second lens **520** in the paraxial region.

[0233] The third lens **530** has a negative refractive power and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the third lens **530** is convex in the paraxial region, and a second surface of the third lens **530** is concave in the paraxial region.

[0234] The fourth lens **540** has a positive refractive power, and has a meniscus shape of which an image-side surface is convex. For example, a first surface of the fourth lens **540** is concave in the paraxial region, and a second surface of the fourth lens **540** is convex in the paraxial region.

[0235] The fifth lens **550** has a negative refractive power, and both surfaces thereof are concave. For example, first and second surfaces of the fifth lens **550** are concave in the paraxial region.

[0236] In addition, at least one inflection point is formed on at least one of the first and second surfaces of the fifth lens **550**.

[0237] In addition, an absolute value of a radius of curvature of the second surface of the fifth lens **550** in the paraxial region is larger than an absolute value of a radius of curvature of the first surface of the fifth lens **550** in the paraxial region.

[0238] The sixth lens **560** has a negative refractive power, and has a meniscus shape of which an object-side surface is convex. For example, a first surface of the sixth lens **560** is convex in the paraxial region, and a second surface of the sixth lens **560** is concave in the paraxial region.

[0239] In addition, at least one inflection point may be formed on at least one of the first and second surfaces of the sixth lens **560**.

[0240] In addition, a radius of curvature of the second surface of the sixth lens **560** in the paraxial region is smaller than a radius of curvature of the first surface of the sixth lens **560** in the paraxial region. Although FIG. **17** illustrates the sixth lens **560** to be in contact to the infrared cut-off filter **570**, the sixth lens **560** may be placed at a distance from the infrared cut-off filter **570**. In an alternative embodiment, the infrared cut-off filter **570** may be shaped to mirror the image-side surface or the second surface of the sixth lens **560**, thereby forming an integral part of the sixth lens **560**.

[0241] Meanwhile, the respective surfaces of the first to sixth lenses **510** to **560** have aspherical coefficients as illustrated in FIG. **20**. However, a person of ordinary skill in the art will appreciate

that some variation in the aspherical coefficients may exist without departing from the results and benefits of the present third embodiment.

[0242] In addition, among the first to sixth lenses **510** to **560**, the fifth lens **550** has the largest absolute value of a focal length.

[0243] In addition, the stop is disposed between the second lens **520** and the third lens **530**. In an alternative configuration, the stop may be disposed on an object side of the first lens **510**, closest to the object side of the optical system. In a further alternative configuration, the stop may be disposed on the object side of the first lens **510** and is aligned along an axis perpendicular to an axial point of the object-side surface of the first lens **510**.

[0244] In addition, the optical system configured as described above has aberration characteristics illustrated in FIG. **18**. However, a person of ordinary skill in the art will appreciate that some variation in the aberration characteristics may exist without departing from the results and benefits of the present third embodiment.

[0245] As set forth above, in an optical system, according to embodiments, an aberration improvement effect is increased, and an increased amount of light is incident through lenses to an image sensor while images captured thereby have high levels of resolution.

[0246] While this disclosure includes specific examples, it will be apparent to one of ordinary skill in the art that various changes in form and details may be made in these examples without departing from the spirit and scope of the claims and their equivalents. The examples described herein are to be considered in a descriptive sense only, and not for purposes of limitation. Descriptions of features or aspects in each example are to be considered as being applicable to similar features or aspects in other examples. Suitable results may be achieved if the described techniques are performed in a different order, and/or if components in a described system, architecture, device, or circuit are combined in a different manner and/or replaced or supplemented by other components or their equivalents. Therefore, the scope of the disclosure is defined not by the detailed description, but by the claims and their equivalents, and all variations within the scope of the claims and their equivalents are to be construed as being included in the disclosure.

Claims

1. An optical system comprising: a first lens having a positive refractive power, a convex object-side surface in a paraxial region thereof, and a concave image-side surface in a paraxial region thereof; a second lens having a positive refractive power, a convex object-side surface in a paraxial region thereof, and a convex image-side surface in a paraxial region thereof; a third lens having a negative refractive power; a fourth lens having a refractive power; a fifth lens having a refractive power and a concave image-side surface in a paraxial region thereof; and a sixth lens having a negative refractive power, a convex object-side surface in a paraxial region thereof, and a concave image-side surface in a paraxial region thereof, wherein the first to sixth lenses are sequentially disposed in ascending numerical order along an optical axis of the optical system from an object side of the optical system toward an imaging surface of an image sensor, the optical system has a total of six lenses, $0.01 < |f/f_5| < 0.07$ is satisfied, where f is an overall focal length of the optical system, and f_5 is a focal length of the fifth lens, $0.4 < |f/f_6| < 0.6$ is satisfied, where f_6 is a focal length of the sixth lens, and $0.4 < |f/f_5| + |f/f_6| < 0.6$ is satisfied.
2. The optical system of claim 1, further comprising a stop disposed between the second and third lenses, wherein $SD/f < 0.4$ is satisfied, where SD is a radius of the stop.
3. The optical system of claim 1, wherein $|v_1 - v_2| < 10$ is satisfied, where v_1 is an Abbe number of the first lens, and v_2 is an Abbe number of the second lens.
4. The optical system of claim 1, wherein $v_1 - v_3 > 30$ is satisfied, where v_1 is an Abbe number of the first lens, and v_3 is an Abbe number of the third lens.
5. The optical system of claim 1, wherein $v_2 - v_3 > 30$ is satisfied, where v_2 is an Abbe number of

the second lens, and v_3 is an Abbe number of the third lens.

6. The optical system of claim 1, wherein $-30 < (r_9 - r_{10}) / (r_9 + r_{10}) < 3$ is satisfied, where r_9 is a radius of curvature of an object-side surface of the fifth lens at the optical axis, and r_{10} is a radius of curvature of the image-side surface of the fifth lens at the optical axis.
 7. The optical system of claim 1, wherein $TTL/f < 1.35$ is satisfied, where TTL is a distance along the optical axis from the object-side surface of the first lens to the imaging surface of the image sensor.
 8. The optical system of claim 1, wherein $0.4 < f/f_1 < 0.7$ is satisfied, where f_1 is a focal length of the first lens.
 9. The optical system of claim 1, wherein $1.0 < f/f_2 < 1.3$ is satisfied, where f_2 is a focal length of the second lens.
 10. The optical system of claim 1, wherein $1.0 < |f/f_3| < 1.2$ is satisfied, where f_3 is a focal length of the third lens.
 11. The optical system of claim 1, wherein $0.2 < f/f_4 < 0.4$ is satisfied, where f_4 is a focal length of the fourth lens.
 12. The optical system of claim 1, wherein $1.9 < f_1/f_2 < 2.1$ is satisfied, where f_1 is a focal length of the first lens, and f_2 is a focal length of the second lens.
 13. The optical system of claim 1, wherein $4.0 < |f_5/f_4| < 15$ is satisfied, where f_4 is a focal length of the fourth lens.
 14. The optical system of claim 1, wherein $1.5 < f/f_1 + f/f_2 < 2.0$ is satisfied, where f_1 is a focal length of the first lens, and f_2 is a focal length of the second lens.
 15. The optical system of claim 1, wherein an absolute value of a radius of curvature of the object-side surface of the second lens at the optical axis is less than an absolute value of a radius of curvature of the image-side surface of the second lens at the optical axis, an absolute value of a radius of curvature of the image-side surface of the fifth lens at the optical axis is greater than an absolute value of a radius of curvature of an object-side surface of the fifth lens at the optical axis, and a radius of curvature of the image-side surface of the sixth lens at the optical axis is less than a radius of curvature of the object-side surface of the sixth lens at the optical axis.
 16. The optical system of claim 1, wherein the third lens has a convex object-side surface in a paraxial region thereof, and a concave image-side surface in a paraxial region thereof.
 17. The optical system of claim 1, wherein the fourth lens has a positive refractive power, a concave object-side surface in a paraxial region thereof, and a convex image-side surface in a paraxial region thereof.
 18. The optical system of claim 1, wherein the fifth lens has a negative refractive power, and a concave object-side surface in a paraxial region thereof.
 19. The optical system of claim 1, wherein among the first to sixth lenses, the fifth lens has a greatest absolute value of a focal length.
 20. The optical system of claim 1, wherein the fifth lens has at least one inflection point on at either one or both of an object-side surface and the image-side surface thereof, and the sixth lens has at least one inflection point on either one or both of the object-side surface and the image-side surface thereof.
-