

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12409572
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Nakada; Youhei et al.

Safety vision device, and safety vision system

Abstract

A robot decelerates or stops, without using an area sensor, when a worker enters a robot operating area. The safety vision device includes a human three-dimensional skeleton estimation model, a robot three-dimensional skeleton estimation model, an input unit for inputting a two-dimensional image of a worker and a robot captured by an external camera, and a distance and a tilt between the camera and the robot, an estimation unit that inputs, to the models, the two-dimensional image and the distance and tilt, to estimate three-dimensional joint point data indicating the three-dimensional coordinate values of the position of a joint point of the worker, and the angles of a plurality of joint axes included in the robot, and an approach determination unit that calculates a worker area and a robot area, and outputs an instruction to decelerate or stop the robot, depending on the degree of overlap of the areas.

Inventors:	Nakada; Youhei (Yamanashi, JP), Motodaka; Takeshi (Tokyo, JP)
Applicant:	FANUC CORPORATION (Yamanashi, JP)
Family ID:	82159718
Assignee:	FANUC CORPORATION (Yamanashi, JP)
Appl. No.:	18/038807
Filed (or PCT Filed):	December 14, 2021
PCT No.:	PCT/JP2021/046118
PCT Pub. No.:	WO2022/138340
PCT Pub. Date:	June 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230415363 A1	Dec. 28, 2023

Foreign Application Priority Data

JP 2020-211721 Dec. 21, 2020

Publication Classification

Int. Cl.: B25J19/06 (20060101); G06T7/246 (20170101); G06T7/62 (20170101); G06T7/80 (20170101)

U.S. Cl.:

CPC B25J19/061 (20130101); G06T7/251 (20170101); G06T7/62 (20170101); G06T7/80 (20170101); G06T2207/30196 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10929654	12/2020	Iqbal	N/A	G06N 3/08
12182197	12/2023	Yoshida	N/A	G06F 16/532
2015/0294496	12/2014	Medasani	345/420	G06T 15/205
2019/0105779	12/2018	Einav	N/A	B25J 9/1689
2019/0134819	12/2018	Okahara	N/A	B25J 13/088
2019/0217472	12/2018	Nakasu	N/A	B25J 9/1676
2020/0331155	12/2019	Vu	N/A	B25J 19/06
2021/0065430	12/2020	Le Floch	N/A	G06T 7/564
2024/0033910	12/2023	Nakada	N/A	B25J 9/1605
2024/0303859	12/2023	Nakamura	N/A	G06T 7/251

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101511550	12/2008	CN	N/A
104476544	12/2014	CN	N/A
108527370	12/2017	CN	N/A
110480634	12/2018	CN	N/A
111372735	12/2019	CN	N/A
2004-243427	12/2003	JP	N/A
2020-93373	12/2019	JP	N/A
20200036088	12/2019	KR	N/A

OTHER PUBLICATIONS

International Search Report issued Mar. 1, 2022 in corresponding International Application No. PCT/JP2021/046118. cited by applicant

Naoki Kato, "Investigation of the latest papers on computer vision 3D Human Pose Estimation", URL:<https://engineering.dena.com/blog/2019/12/cv-papers-19-3d-human-pose-estimation/>,

Primary Examiner: Tran; Khoi H

Assistant Examiner: Estevez; Dairon

Attorney, Agent or Firm: Wenderoth, Lind & Ponack, L.L.P.

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a safety vision device and a safety vision system.

BACKGROUND ART

(2) There is known a technology in which, when there is a possibility that a worker, who is a safety monitoring target, enters a motion area of a robot, the motion area of the robot is set around the worker, and safe motion control, emergency stop control and the like, of the robot are performed when the robot enters the motion area. See, for example, Patent Document 1. Patent Document 1: Japanese Unexamined Patent Application, Publication No. 2004-243427

DISCLOSURE OF THE INVENTION

Problems to be Solved by the Invention

(3) In the conventional technology, in order to detect that the worker has entered the motion area of the robot, an area sensor or the like is used. However, since it is necessary to install the area sensor near the robot, motions and movements of the worker and the robot are restricted.

(4) Therefore, it is desired to, when the worker enters the motion area of the robot, cause the robot to decelerate or stop without using an area sensor.

Means for Solving the Problems

(5) (1) An aspect of a safety vision device of the present disclosure comprising: a human three-dimensional skeleton estimation model receiving input of a two-dimensional image of a human, and outputting three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points of the human; a robot three-dimensional skeleton estimation model receiving input of a two-dimensional image of a robot, and a distance and a tilt between a camera that has captured the two-dimensional image of the robot and the robot, and outputting angles of a plurality of joint axes included in the robot; an input unit configured to input a two-dimensional image of a worker and the robot captured by an external camera, and a distance and a tilt between the external camera and the robot; an estimation unit configured to input the two-dimensional image, and the distance and tilt between the external camera and the robot, which have been inputted by the input unit, to the human three-dimensional skeleton estimation model and the robot three-dimensional skeleton estimation model, and estimate three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points of the worker and the angles of the plurality of joint axes included in the robot; and an approach determination unit configured to calculate an area indicating a range of the worker and an area indicating a range of the robot, based on the three-dimensional joint point data and the angles of the plurality of joint axes, and output an instruction to decelerate or stop the robot according to a degree of overlap between the calculated areas of the worker and the robot.

(6) (2) An aspect of the safety vision system of the present disclosure comprising a robot; a camera; and the safety vision device of (1).

(7) According to an aspect, it is possible to, when a worker enters a motion area of a robot, cause the robot to decelerate or stop without using an area sensor.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a functional block diagram showing a functional configuration example of a safety vision system according to one embodiment;
- (2) FIG. 2 is a diagram showing an example of a relationship between a two-dimensional skeleton estimation model and a joint angle estimation model as a robot three-dimensional skeleton estimation model;
- (3) FIG. 3 is a diagram showing an example of positions of joint points of a worker estimated by an estimation unit;
- (4) FIG. 4 is a diagram showing an example of an area of a robot;
- (5) FIG. 5 is a flowchart illustrating a determination process of a safety vision device;
- (6) FIG. 6 is a diagram showing an example of a configuration of the safety vision system;
- (7) FIG. 7 is a functional block diagram showing a functional configuration example of a machine learning device;
- (8) FIG. 8A is a diagram showing an example of a frame image in which the angle of a joint axis J4 is 90 degrees;
- (9) FIG. 8B is a diagram showing an example of a frame image in which the angle of the joint axis J4 is -90 degrees;
- (10) FIG. 9 is a diagram showing an example for increasing the number of pieces of training data;
- (11) FIG. 10 is a diagram showing an example of coordinate values of joint axes on normalized XY coordinates;
- (12) FIG. 11 is a diagram showing an example of feature maps of joint axes of the robot;
- (13) FIG. 12 is a diagram showing an example of comparison between a frame image and an output result of the two-dimensional estimation model; and
- (14) FIG. 13 is a diagram showing an example of the joint angle estimation model.

PREFERRED MODE FOR CARRYING OUT THE INVENTION

(15) One embodiment of the present disclosure will be described below using diagrams.

One Embodiment

(16) FIG. 1 is a functional block diagram showing a functional configuration example of a safety vision system according to one embodiment. As shown in FIG. 1, a safety vision system 1 includes a robot 10, a safety vision device 20, and a camera 40.

(17) The robot 10, the safety vision device 20, and the camera 40 as an external camera may be mutually connected via a network not shown such as a wireless LAN (local area network), Wi-Fi (registered trademark), and a mobile phone network conforming to a standard such as 4G or 5G. In this case, the robot 10, the safety vision device 20, and the camera 40 include communication units not shown for mutually performing communication via such connection. Though it has been described that the robot 10 and the safety vision device 20 perform data transmission/reception via the communication units not shown, data transmission/reception may be performed via a robot control device (not shown) that controls motions of the robot 10.

(18) <Robot 10>

(19) The robot 10 is, for example, an industrial robot or the like that is well known to one skilled in the art, and drives movable members (not shown) of the robot 10 by driving a servomotor not shown that is arranged for each of a plurality of joint axes not shown, which are included in the robot 10, based on a drive instruction from the robot control device (not shown).

(20) Though the robot **10** will be described below as a 6-axis vertically articulated robot having six joint axes **J1** to **J6**, the robot **10** may be a vertically articulated robot other than the six-axis one and may be a horizontally articulated robot, a parallel link robot, or the like.

(21) <Camera **40**>

(22) The camera **40** as an external camera is, for example, a digital camera or the like and is installed being fixed to a wall or a pillar in a factory or the like in which the robot **10** is arranged so that the robot **10** and a worker U, who is a user carrying the safety vision device **20** described later, can be photographed. The camera **40** may be a camera mounted on a smartphone, a tablet terminal, AR (augmented reality) glasses, MR (mixed reality) glasses or the like.

(23) The camera **40** photographs the robot **10** and the worker U at a predetermined frame rate (for example, 30 frames/s) to generate a frame image which is a two-dimensional image projected on a plane vertical to the optical axis of the camera **40**. The camera **40** outputs the generated frame image to the safety vision device **20**. The frame image generated by the camera **40** may be a visible light image such as an RGB color image or a gray-scale image.

(24) It is assumed that the robot coordinate system of the robot **10** and the camera coordinate system of the camera **40** are associated in the world coordinate system by calibration performed in advance.

(25) <Safety Vision Device **20**>

(26) The safety vision device **20** is, for example, a smartphone, a tablet terminal, AR (augmented reality) glasses, or MR (mixed reality) glasses.

(27) As shown in FIG. 1, the safety vision device **20** includes a control unit **21**, a communication unit **22**, and a storage unit **23**. The control unit **21** includes a three-dimensional object recognition unit **211**, a self-position estimation unit **212**, an input unit **213**, an estimation unit **214**, an approach determination unit **215**, and a notification unit **216**.

(28) The communication unit **22** is a communication control device to perform data transmission/reception with a network such as a wireless LAN (local area network), Wi-Fi (registered trademark), and a mobile phone network conforming to a standard such as 4G or 5G. For example, the communication unit **22** may directly communicate with the camera **40** or may communicate with the robot **10** via the robot control device (not shown) that controls motions of the robot **10**.

(29) The storage unit **23** is, for example, a ROM (read-only memory) or an HDD (hard disk drive) and stores a system program, a safety vision application program, and the like executed by the control unit **21** described later. Further, the storage unit **23** may store a human three-dimensional skeleton estimation model **231** described later, a robot three-dimensional skeleton estimation model **232** configured with a two-dimensional skeleton estimation model **2321** and a joint angle estimation model **2322** described later, and three-dimensional recognition model data **233**.

(30) <Human Three-Dimensional Skeleton Estimation Model **231**>

(31) The human three-dimensional skeleton estimation model **231** is a trained model that is generated by a machine learning device not shown executing supervised learning, using training data configured with input data of frame images of video of an arbitrary person acquired from a dataset such as Human 3.6M (<http://vision.imar.ro/human3.6m/description.php>) and label data of three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points of the arbitrary person annotated in the frame images in advance, based on a deep learning model, for example, used for a well-known 3D pose estimation method (for example, <https://engineer.dena.com/posts/2019.12/cv-papers-19-3d-human-pose-estimation/>).

(32) <Robot Three-Dimensional Skeleton Estimation Model **232**>

(33) As shown in FIG. 2 the robot three-dimensional skeleton estimation model **232** is configured with the two-dimensional skeleton estimation model **2321** and the joint angle estimation model **2322**.

(34) FIG. 2 is a diagram showing an example of a relationship between the two-dimensional

skeleton estimation model **2321** and the joint angle estimation model **2322** as the robot three-dimensional skeleton estimation model **232**.

(35) As shown in FIG. 2, the two-dimensional skeleton estimation model **2321** is a CNN (convolutional neural network) that receives input of a frame image of the robot **10** captured by the camera **40** and outputs a two-dimensional posture of pixel coordinates indicating positions of the centers of the joint axes **J1** to **J6** of the robot **10** in the frame image.

(36) The two-dimensional skeleton estimation model **2321** is generated by the machine learning device not shown executing supervised learning, using training data configured with input data of frame images of the robot **10** in various postures captured by the camera **40** and label data of values of two-dimensional coordinates (pixel coordinates) indicating positions of the centers of the joint axes **J1** to **J6** in each frame image at the time when the frame image was captured, for example, based on a deep learning model used for a well-known markerless animal tracking tool (for example, DeepLabCut) or the like.

(37) The joint angle estimation model **2322** is a neural network or the like that receives input of the distance and tilt between the camera **40** and the robot **10**, and the two-dimensional posture of the pixel coordinates indicating the positions of the centers of the joint axes **J1** to **J6** of the robot **10** outputted from the two-dimensional skeleton estimation model **2321** and normalized with the width and height of the frame image, with the joint axis **J1**, which is a base link of the robot **10**, as the origin, and outputs angles of the joint axes **J1** to **J6** of the robot **10**.

(38) The joint angle estimation model **2322** is generated by the machine learning device not shown executing supervised learning, for example, using training data configured with input data including distances and tilts between the camera **40** and the robot **10**, and two-dimensional postures indicating normalized positions of the centers of the joint axes **J1** to **J6**, and label data of angles of the joint axes **J1** to **J6** of the robot **10** at the time when frame images were captured.

(39) Details of the machine learning device for generating the robot three-dimensional skeleton estimation model **232** (the two-dimensional skeleton estimation model **2321** and the joint angle estimation model **2322**) will be described later.

(40) <Three-Dimensional Recognition Model Data **233**>

(41) In the three-dimensional recognition model data **233**, for example, feature values such as an edge quantity extracted from each of a plurality of frame images of the robot **10** are stored as a three-dimensional recognition model, the plurality of frame images having been captured by the camera **40** in advance by changing the posture and direction of the robot **10**. Further, in the three-dimensional recognition model data **233**, three-dimensional coordinate values of the origin of the robot coordinate system of the robot **10** in the world coordinate system (hereinafter also referred to as “the robot origin”) at the time when the frame image of each of the three-dimensional recognition models was captured, and information indicating a direction of each of the X, Y, and Z axes of the robot coordinate system in the world coordinate system may be stored in association with the three-dimensional recognition model.

(42) <Control Unit **21**>

(43) The control unit **21** includes a CPU (central processing unit), a ROM, a RAM, a CMOS (complementary metal-oxide-semiconductor) memory and the like, and these are configured being mutually communicable via a bus and are well-known to one skilled in the art.

(44) The CPU is a processor that performs overall control of the safety vision device **20**. The CPU reads out the system program and the safety vision application program stored in the ROM via the bus, and controls the whole safety vision device **20** according to the system program and the safety vision application program. Thereby, as shown in FIG. 1, the control unit **21** is configured to realize the functions of the three-dimensional object recognition unit **211**, the self-position estimation unit **212**, the input unit **213**, the estimation unit **214**, the approach determination unit **215**, and the notification unit **216**. In the RAM, various kinds of data such as temporary calculation data and display data are stored. The CMOS memory is backed up by a battery not shown and is configured

as a nonvolatile memory in which a storage state is kept even when the safety vision device **20** is powered off.

(45) <Three-Dimensional Object Recognition Unit **211**>

(46) The three-dimensional object recognition unit **211** acquires a frame image of the robot **10** captured by the camera **40**, for example, via the communication unit **22**. The three-dimensional object recognition unit **211** extracts feature values such as an edge quantity from the frame image of the robot **10** captured by the camera **40**, for example, using a well-known robot three-dimensional coordinate recognition method. Here, as for the well-known method, see, for example, “https://linx.jp/product/mvtec/halcon/feature/3d_vision.html”.

(47) The three-dimensional object recognition unit **211** performs matching between the extracted feature values and the feature values of the three-dimensional recognition models stored in the three-dimensional recognition model data **233**. Based on a result of the matching, the three-dimensional object recognition unit **211** acquires, for example, three-dimensional coordinate values of the robot origin in the world coordinate system and information indicating the direction of each of the X, Y, and Z axes of the robot coordinate system in a three-dimensional recognition model with the highest matching degree.

(48) <Self-Position Estimation Unit **212**>

(49) The self-position estimation unit **212** acquires three-dimensional coordinate values of the origin of the camera coordinate system of the camera **40** in the world coordinate system (hereinafter also referred to as “the three-dimensional coordinate values of the camera **40**”, for example, using a well-known self-position estimation method. Based on the acquired three-dimensional coordinate values of the camera **40** and the acquired three-dimensional coordinate values of the robot origin, an information acquisition unit **301** calculates the distance and tilt between the camera **40** and the robot **10**.

(50) Since the robot **10** and the camera **40** are fixedly arranged in a factory, the self-position estimation unit **212** may calculate, when the safety vision application program is started, the three-dimensional coordinate values of the robot origin and the three-dimensional coordinate values of the camera **40** in the world coordinate system, and the distance and tilt between the camera **40** and the robot **10** only once and store them into the storage unit **23**.

(51) <Input Unit **213**>

(52) The input unit **213** inputs a frame image of the worker U and the robot **10** captured by the camera **40**, and the distance and tilt between the camera **40** and the robot **10** calculated by the self-position estimation unit **212**.

(53) <Estimation Unit **214**>

(54) The estimation unit **214** inputs the frame image of the worker U and the robot **10**, and the distance and tilt between the camera **40** and the robot **10**, which have been inputted by the input unit **213**, to the human three-dimensional skeleton estimation model **231** and the robot three-dimensional skeleton estimation model **232**.

(55) Specifically, the estimation unit **214** estimates three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points of the worker U in the inputted frame image, from the output of the human three-dimensional skeleton estimation model **231**.

(56) FIG. 3 is a diagram showing an example of the positions of the joint points of the worker U estimated by the estimation unit **214**.

(57) As shown in FIG. 3, the joint points of the worker U estimated by the estimation unit **214** are indicated, for example, by black points.

(58) Further, the estimation unit **214** estimates angles of the joint axes J1 to J6 of the robot **10** in the inputted frame image, from the output of the robot three-dimensional skeleton estimation model **232**.

(59) As described above, the estimation unit **214** normalizes pixel coordinates of positions of the centers of the joint axes J1 to J6 outputted from the two-dimensional skeleton estimation model

2321 and inputs the pixel coordinates to the joint angle estimation model **2322**. Further, the estimation unit **214** may be adapted to set each confidence degree $c_{sub.i}$ of a two-dimensional posture outputted from the two-dimensional skeleton estimation model **2321** to “1” when the confidence degree $c_{sub.i}$ is 0.5 or above and to “0” when the confidence degree $c_{sub.i}$ is below 0.5.

(60) If a part of the worker **U** is hidden by the robot **10** in the frame image inputted by the input unit **213**, the estimation unit **214** may estimate three-dimensional joint point data of the worker **U** in the frame image in which the part of the worker **U** is hidden by the robot **10**, using time-series data of three-dimensional joint point data of the worker **U** estimated from a plurality of chronologically consecutive frame images before the frame image, in which the whole worker **U** and the whole robot **10** are photographed.

(61) Or alternatively, if a part of the robot **10** is hidden by the worker **U** in the frame image inputted by the input unit **213**, the estimation unit **214** may estimate angles of the joint axes **J1** to **J6** of the robot **10** in the frame image in which the part of the robot **10** is hidden by the worker **U**, using time-series data of angles of the joint axes **J1** to **J6** of the robot **10** estimated from a plurality of chronologically consecutive frame images before the frame image, in which the whole worker **U** and the whole robot **10** are photographed.

(62) <Approach Determination Unit **215**>

(63) The approach determination unit **215** calculates an area indicating a range of the worker **U** and an area indicating a range of the robot **10**, based on the three-dimensional joint point data of the worker **U** and the angles of the joint axes **J1** to **J6** of the robot **10** estimated by the estimation unit **214**, and outputs an instruction to decelerate or stop the robot **10**, to the robot control device (not shown) according to a degree of overlap between the calculated areas of the worker **U** and the robot **10**.

(64) Specifically, by arranging the joint points of the worker **U** in the three-dimensional space of the world coordinate system, for example, based on the three-dimensional joint point data of the worker **U** estimated by the estimation unit **214**, and connecting the joint points with straight lines, the approach determination unit **215** generates a skeleton of the worker **U**. By adding a shape such as a rectangular parallelepiped with a length, a depth, and a height that are set in advance, to each straight line of the generated skeleton, the approach determination unit **215** calculates the area indicating the range of the worker **U**.

(65) Further, the approach determination unit **215** solves forward kinematics from the angles of the joint axes **J1** to **J6** estimated by the estimation unit **214**, using a DH (Denavit-Hartenberg) parameter table defined in advance, to calculate three-dimensional coordinate values of the positions of the centers of the joint axes **J1** to **J6**. Then, by arranging the calculated positions of the centers of the joint axes **J1** to **J6** of the robot **10** in the three-dimensional space of the world coordinate system, the approach determination unit **215** generates a skeleton of the robot **10**. By adding a shape such as a rectangular parallelepiped with a length, a depth, and a height that are set in advance, to each link of the generated skeleton of the robot **10**, the approach determination unit **215** calculates the area indicating the range of the robot **10**.

(66) The DH parameter table is created in advance, for example, based on the specifications of the robot **10** and stored into the storage unit **23**.

(67) FIG. 4 is a diagram showing an example of the area of the robot **10**. The area of the robot **10** shown in FIG. 4 is configured with two areas **R1** and **R2** with different sizes. That is, the length, depth, and height of the area **R1** are set larger than the length, depth, and height of the area **R2**.

(68) The approach determination unit **215** determines whether the calculated area of the worker **U** in the world coordinate system overlaps with the area **R1** or the area **R2** of the robot **10**. If the area of the worker **U** overlaps only with the area **R1** of the robot **10**, the approach determination unit **215** determines that there is time before the worker **U** and the robot **10** collide, and causes the motion of the robot **10** to decelerate by outputting a deceleration instruction to the robot control

device (not shown).

(69) If the area of the worker U also overlaps with the area R2 of the robot **10**, the approach determination unit **215** determines that there is a danger that the worker U and the robot **10** immediately collide, and causes the motion of the robot **10** to stop by outputting a stop instruction to the robot control device (not shown).

(70) By providing the two areas R1 and R2 with different sizes as the area of the robot **10** as described above, the approach determination unit **215** can appropriately determine which of the deceleration instruction or the stop instruction is to be outputted.

(71) <Notification Unit **216**>

(72) If the approach determination unit **215** outputs the deceleration or stop instruction, the notification unit **216** outputs a warning sound via a speaker (not shown) included in the safety vision device **20**.

(73) The notification unit **216** may display a message indicating a warning to a display device (not shown) such as an LCD (liquid crystal display) included in the safety vision device **20**.

(74) <Determination Process of Safety Vision Device **20**>

(75) Next, an operation related to a determination process of the safety vision device **20** according to the present embodiment will be described.

(76) FIG. 5 is a flowchart illustrating the determination process of the safety vision device **20**. The flow shown here is repeatedly executed while the safety vision device **20** is executing the safety vision application program.

(77) At Step S1, the three-dimensional object recognition unit **211** acquires a frame image of the worker U and the robot **10** captured by the camera **40** at a predetermined frame rate.

(78) At Step S2, the three-dimensional object recognition unit **211** acquires three-dimensional coordinate values of the robot origin in the world coordinate system, and information indicating a direction of each of the X, Y, and Z axes of the robot coordinate system, based on the frame image acquired at Step S1 and the three-dimensional recognition model data **233**.

(79) At Step S3, the self-position estimation unit **212** acquires three-dimensional coordinate values of the camera **40** in the world coordinate system, based on the frame image acquired at Step S1.

(80) At Step S4, the self-position estimation unit **212** calculates the distance and tilt between the camera **40** and the robot **10**, based on the three-dimensional coordinate values of the camera **40** acquired at Step S3 and the three-dimensional coordinate values of the robot origin of the robot **10** acquired at Step S2.

(81) At Step S5, the input unit **213** inputs the frame image acquired at Step S1 and the distance and tilt between the camera **40** and the robot **10** calculated at Step S4.

(82) At Step S6, by inputting the frame image inputted at Step S5 to the human three-dimensional skeleton estimation model **231**, the estimation unit **214** estimates three-dimensional joint point data indicating three-dimensional coordinate values of positions of the joint points of the worker U in the inputted frame image. Further, by inputting the frame image, and the distance and tilt between the camera **40** and the robot **10**, which have been inputted at Step S2, to the robot three-dimensional skeleton estimation model **232**, the estimation unit **214** estimates angles of the joint axes J1 to J6 of the robot **10** at the time when the inputted frame image was captured.

(83) At Step S7, the approach determination unit **215** calculates an area indicating the range of the worker U, based on the three-dimensional joint point data of the worker U estimated at Step S6. Further, the approach determination unit **215** calculates areas R1 and R2 of the robot **10**, based on the angles of the joint axes J1 to J6 of the robot **10** estimated at Step S6.

(84) At Step S8, the approach determination unit **215** determines whether the area of the worker U calculated at Step S7 overlaps with the area R1 of the robot **10** calculated at Step S7 or not. If the area of the worker U overlaps with the area R1 of the robot **10**, the process proceeds to Step S9. On the other hand, if the area of the worker U does not overlap with the area R1 of the robot **10**, the safety vision device **20** ends the determination process.

(85) At Step S9, the approach determination unit **215** determines whether the area of the worker U calculated at Step S7 overlaps with the area R2 of the robot **10** calculated at Step S7 or not. If the area of the worker U overlaps with the area R2 of the robot **10**, the process proceeds to Step S10. On the other hand, if the area of the worker U does not overlap with the area R2 of the robot **10**, the process proceeds to Step S11.

(86) At Step S10, the approach determination unit **215** outputs a stop instruction to the robot control device (not shown).

(87) At Step S11, the approach determination unit **215** outputs a deceleration instruction to the robot control device (not shown).

(88) At Step S12, the notification unit **216** outputs a warning sound via the speaker (not shown) of the safety vision device **20**.

(89) According to the above, by inputting a frame image in which the worker U and the robot **10** are photographed, and the distance and tilt between the camera **40** and the robot **10** to the human three-dimensional skeleton estimation model **231** and the robot three-dimensional skeleton estimation model **232** as a trained model, the safety vision device **20** according to the one embodiment estimates three-dimensional joint point data indicating three-dimensional coordinate values of positions of the joint points of the worker U and angles of the joint axes J1 to J6 of the robot **10**. The safety vision device **20** calculates an area indicating the range of the worker U based on the estimated three-dimensional joint point data, and calculates areas R1 and R2 indicating the range of the robot **10** based on the angles of the joint axes J1 to J6. The safety vision device **20** determines whether or not the area of the worker U overlaps with the area R1 or R2 of the robot **10**, and outputs a deceleration or stop instruction to the robot control device (not shown).

(90) Thereby, it is possible for the safety vision device **20** to, when the worker U enters the motion area of the robot **10**, cause the robot **10** to decelerate or stop without using an area sensor.

(91) The safety vision device **20** has been described above. The machine learning device for generating the robot three-dimensional skeleton estimation model **232** will be described.

(92) FIG. 7 is a functional block diagram showing a functional configuration example of a machine learning device **30**.

(93) As shown in FIG. 7, the machine learning device **30** includes an information acquisition unit **301**, a two-dimensional posture acquisition unit **302**, an input data acquisition unit **303**, a label acquisition unit **304**, a learning unit **305**, and a storage unit **306**.

(94) In the description below, the machine learning device **30** acquires, as training data, only such pieces of data that are acquired at a timing when all the pieces of data can be synchronized. For example, if the camera **40** captures frame images at 30 frames/s, the period with which angles of the plurality of joint axes included in the robot **10** can be acquired is 100 milliseconds, and other data can be immediately acquired, then the machine learning device **30** acquires training data with a predetermined period that enables synchronization, such as 100 milliseconds.

(95) <Storage Unit **306**>

(96) The storage unit **306** is a RAM (random access memory) or the like, and stores input data acquired by the input data acquisition unit **303** described later, label data acquired by the label acquisition unit **304** described later, learned models constructed by the learning unit **305** described later, and the like. Further, the storage unit **306** may store three-dimensional recognition model data **3061**.

(97) The three-dimensional recognition model data **3061** is similar, for example, to the three-dimensional recognition model data **233** of the safety vision device **20**, and description thereof will be omitted.

(98) <Information Acquisition Unit **301**>

(99) The information acquisition unit **301** acquires a frame image of the robot **10** captured by the camera **40**, for example, via a communication unit not shown. The information acquisition unit **301** acquires three-dimensional coordinate values of the robot origin in the world coordinate system and

information indicating a direction of each of the X, Y, and Z axes of the robot coordinate system from the acquired frame image, for example, similarly to the three-dimensional object recognition unit **211** of the safety vision device **20**.

(100) Further, the information acquisition unit **301** may be adapted to acquire three-dimensional coordinate values of the camera **40** in the world coordinate system, and calculate the distance and tilt between the camera **40** and the robot **10** based on the acquired three-dimensional coordinate values of the camera **40** and the acquired three-dimensional coordinate values of the robot origin, similarly to the self-position estimation unit **212** of the safety vision device **20**.

(101) <Two-Dimensional Posture Acquisition Unit **302**>

(102) The two-dimensional posture acquisition unit **302** transmits a request to the robot **10** with the above-described predetermined period that enables synchronization, such as 100 milliseconds, for example, via the communication unit not shown to acquire angles of the joint axes **J1** to **J6** of the robot **10** at the time when the frame image acquired by the information acquisition unit **301** was captured.

(103) Then, the two-dimensional posture acquisition unit **302** solves forward kinematics from the acquired angles of the joint axes **J1** to **J6**, for example, using a DH parameter table defined in advance, to calculate three-dimensional coordinate values of positions of the centers of the joint axes **J1** to **J6** and calculate a three-dimensional posture of the robot **10** in the world coordinate system. The DH parameter table is created in advance, for example, based on the specifications of the robot **10** and is stored into the storage unit **306**.

(104) Further, the two-dimensional posture acquisition unit **302** arranges the positions of the centers of the joint axes **J1** to **J6** of the robot **10** calculated by the forward kinematics in the three-dimensional space of the world coordinate system, for example, using a well-known method for projection to a two-dimensional plane, and generates two-dimensional coordinates (pixel coordinates) ($x_{sub.i}, y_{sub.i}$) of the positions of the centers of the joint axes **J1** to **J6** as a two-dimensional posture of the robot **10**, by projecting, from the point of view of the camera **40** decided by the distance and tilt between the camera **40** and the robot **10** calculated by the information acquisition unit **301**, onto a projection plane decided by the distance and tilt between the camera **40** and the robot **10**. Here, i is an integer from 1 to 6.

(105) As shown in FIGS. **8A** and **8B**, there may be a case where a joint axis is hidden in a frame image, depending on a posture of the robot **10** and a photographing direction.

(106) FIG. **8A** is a diagram showing an example of a frame image in which the angle of the joint axis **J4** is 90 degrees. FIG. **8B** is a diagram showing an example of a frame image in which the angle of the joint axis **J4** is -90 degrees.

(107) In the frame image of FIG. **8A**, the joint axis **J6** is hidden and not seen. In the frame image of FIG. **8B**, the joint axis **J6** is seen.

(108) Therefore, the two-dimensional posture acquisition unit **302** connects adjacent joint axes of the robot **10** with a line segment, and defines a thickness for each line segment with a link width of the robot **10** set in advance. The two-dimensional posture acquisition unit **302** determines whether there is another joint axis on each line segment or not, based on a three-dimensional posture of the robot **10** calculated by forward kinematics and an optical axis direction of the camera **40** decided by the distance and tilt between the camera **40** and the robot **10**. In a case like FIG. **8A** where that another joint axis J_i exists on a side opposite to the camera **40** side in the depth direction, relative to a line segment, the two-dimensional posture acquisition unit **302** sets the confidence degree $c_{sub.i}$ of that other joint axis J_i (the joint axis **J6** in FIG. **8A**) to "0". In a case like FIG. **8B** where that other joint axis J_i exists on the camera **40** side relative to the line segment, the two-dimensional posture acquisition unit **302** sets the confidence degree $c_{sub.i}$ of that other joint axis J_i (the joint axis **J6** in FIG. **8B**) to "1".

(109) That is, the two-dimensional posture acquisition unit **302** may include, for the two-dimensional coordinates (pixel coordinates) ($x_{sub.i}, y_{sub.i}$) of the projected positions of the

centers of the joint axes J1 to J6, the confidence degrees c.sub.i indicating whether the joint axes J1 to J6 are shown or not, respectively, in a frame image, into the two-dimensional posture of the robot 10.

(110) As for training data for performing supervised learning in the machine learning device 30, it is desirable that many pieces of training data are prepared.

(111) FIG. 9 is a diagram showing an example for increasing the number of pieces of training data.

(112) As shown in FIG. 9, for example, in order to increase the number of pieces of training data, the two-dimensional posture acquisition unit 302 randomly gives a distance and a tilt between the camera 40 and the robot 10 to cause a three-dimensional posture of the robot 10 calculated by forward kinematics to rotate. The two-dimensional posture acquisition unit 302 may generate many two-dimensional postures of the robot 10, by projecting the rotated three-dimensional posture of the robot 10 to a two-dimensional plane decided by the randomly given distance and tilt.

(113) <Input Data Acquisition Unit 303>

(114) The input data acquisition unit 303 acquires frame images of video of an arbitrary person from a dataset such as Human 3.6M, as input data, for example, via the communication unit not shown in order to generate the human three-dimensional skeleton estimation model 231 described above. Further, the input data acquisition unit 303 acquires frame images from the camera 40, and distances and tilts between the camera 40 and the robot 10 at the time when the frame images were captured, which have been acquired from the information acquisition unit 301, as input data in order to generate the robot three-dimensional skeleton estimation model 232. The input data acquisition unit 303 stores the acquired input data into the storage unit 306.

(115) At the time of generating the joint angle estimation model 232 configuring the robot three-dimensional skeleton estimation model 232, the input data acquisition unit 303 may convert the two-dimensional coordinates (pixel coordinates) (x.sub.i,y.sub.i) of the positions of the centers of the joint axes J1 to J6 included in the two-dimensional posture generated by the two-dimensional posture acquisition unit 302 to values of XY coordinates that have been normalized to satisfy $-1 < X < 1$ by being divided by the width of the frame image and satisfy $-1 < Y < 1$ by being divided by the height of the frame image, with the joint axis J1, which is a base link of the robot 10, as the origin, as shown in FIG. 10.

(116) <Label Acquisition Unit 304>

(117) The label acquisition unit 304 acquires three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points in the camera coordinate system that have been annotated in advance in each of the frame images of the arbitrary person described above as label data (correct answer data), from the above-described dataset such as Human 3.6M, for example, via the communication unit not shown in order to generate the human three-dimensional skeleton estimation model 231 described above. The label acquisition unit 304 may convert the camera coordinate system of the three-dimensional joint point data to the world coordinate system.

(118) Further, the label acquisition unit 304 acquires angles of the joint axes J1 to J6 of the robot 10 at the time when frame images were captured with the above-stated predetermined period that enables synchronization, such as 100 milliseconds, and two-dimensional postures indicating positions of the centers of the joint axes J1 to J6 of the robot 10 in the frame images, from the two-dimensional posture acquisition unit 302 as label data (correct answer data) in order to generate the robot three-dimensional skeleton estimation model 232 described above. The label acquisition unit 304 stores the acquired label data into the storage unit 306.

(119) <Learning Unit 305>

(120) The learning unit 305 accepts pairs configured with the input data and labels described above, as training data. By performing supervised learning using the accepted training data, the learning unit 305 constructs the human three-dimensional skeleton estimation model 231 and the robot three-dimensional skeleton estimation model 232, which is configured with the two-dimensional skeleton estimation model 2321 and the joint angle estimation model 2322.

(121) Then, the learning unit **305** provides the constructed human three-dimensional skeleton estimation model **231** and robot three-dimensional skeleton estimation model **232**, which is configured with the two-dimensional skeleton estimation model **2321** and the joint angle estimation model **2322**, for the safety vision device **20**.

(122) Description will be made below on construction of the two-dimensional skeleton estimation model **2321** and the joint angle estimation model **2322** configuring the robot three-dimensional skeleton estimation model **232**.

(123) <Two-Dimensional Skeleton Estimation Model **2321**>

(124) For example, as described above, based on a deep learning model used for a well-known markerless animal tracking tool (for example, DeepLabCut) or the like, the learning unit **305** performs supervised learning using training data configured with input data of frame images of the robot **10** captured by the camera **40** and labels of two-dimensional postures indicating positions of the centers of the joint axes **J1** to **J6** at the time when the frame images were captured, and generates the two-dimensional skeleton estimation model **2321** which receives input of a frame image of the worker **U** and the robot **10** captured by the camera **40**, and outputs a two-dimensional posture of pixel coordinates indicating positions of the centers of the joint axes **J1** to **J6** of the robot **10** in the captured frame image.

(125) Specifically, the two-dimensional skeleton estimation model **2321** is constructed based on a CNN (convolutional neural network) which is a neural network.

(126) The convolutional neural network has a structure provided with a convolutional layer, a pooling layer, a fully connected layer, and an output layer.

(127) In the convolutional layer, a predetermined parameter filter is applied to an inputted frame image in order to perform feature extraction such as edge extraction. The predetermined parameter of the filter corresponds to the weight of the neural network, and is learned by repeating forward propagation and back propagation.

(128) In the pooling layer, the image outputted from the convolutional layer is blurred in order to allow position misalignment of the robot **10**. Thereby, even if the position of the robot **10** fluctuates, the robot **10** can be regarded as the identical object.

(129) By combining these convolutional layer and pooling layer, feature values can be extracted from the frame image.

(130) In the fully connected layer, pieces of image data of feature parts that have been taken out through the convolutional layer and the pooling layer are combined to be one node, and a feature map of values converted by an activation function, that is, a feature map of confidence degrees is outputted.

(131) FIG. **11** is a diagram showing an example of feature maps of the joint axes **J1** to **J6** of the robot **10**.

(132) As shown in FIG. **11**, in each of the feature maps of the joint axes **J1** to **J6**, the value of the confidence degree $c_{sub.i}$ is indicated within a range of 0 to 1. For a cell closer to the position of the center of a joint axis, a value closer to “1” is obtained. For a cell farther away from the position of the center of a joint axis, a value closer to “0” is obtained.

(133) In the output layer, the row, column, and confidence degree (maximum) of a cell at which the confidence degree is the maximum value, in each of the feature maps of the joint axes **J1** to **J6**, which are the output from the fully connected layer, is outputted. In a case where the frame image is convoluted to become $1/N$ in the convolutional layer, the row and column of each cell is increased by N times in the output layer, and pixel coordinates indicating the position of the center of each of the joint axes **J1** to **J6** in the frame image are set (N is an integer equal to or larger than 1).

(134) FIG. **12** is a diagram showing an example of comparison between a frame image and an output result of the two-dimensional skeleton estimation model **2321**.

(135) <Joint Angle Estimation Model **2322**>

(136) The learning unit **305** performs supervised learning, for example, using training data configured with input data including distances and tilts between the camera **40** and the robot **10**, and two-dimensional postures indicating the above-stated normalized positions of the centers of the joint axes **J1** to **J6**, and label data of angles of the joint axes **J1** to **J6** of the robot **10** at the time when frame images were captured, to generate the joint angle estimation model **2322**.

(137) Though the learning unit **305** normalizes the two-dimensional posture of the joint axes **J1** to **J6** outputted from the two-dimensional skeleton estimation model **2321**, the two-dimensional skeleton estimation model **2321** may be generated such that a normalized two-dimensional posture is outputted from the two-dimensional skeleton estimation model **2321**.

(138) FIG. **13** is a diagram showing an example of the joint angle estimation model **2322**. Here, as the joint angle estimation model **2322**, a multilayer neural network is exemplified in which two-dimensional posture data indicating positions of the joint axes **J1** to **J6** outputted from the two-dimensional skeleton estimation model **2321** and normalized, and the distance and tilt between the camera **40** and the robot **10** are the input layer, and angles of the joint axes **J1** to **J6** are the output layer, as shown in FIG. **13**. The two-dimensional posture is indicated by $(x_{sub.i}, y_{sub.i}, c_{sub.i})$ including the coordinates $(x_{sub.i}, y_{sub.i})$, which indicate normalized positions of the centers of the joint axes **J1** to **J6**, and confidence degrees $c_{sub.i}$, which is set to “1” if the confidence degree outputted from the two-dimensional skeleton estimation model **2321** is 0.5 or above, or set to “0” if the confidence degree is below 0.5.

(139) Further, “inclination R_x of X axis”, “inclination R_y of Y axis”, and “inclination R_z of Z axis” are a rotation angle around the X axis, a rotation angle around the Y axis, and a rotation angle around the Z axis, between the camera **40** and the robot **10** in the world coordinate system that are calculated based on three-dimensional coordinate values of the camera **40** in the world coordinate system and three-dimensional coordinate values of the robot origin of the robot **10** in the world coordinate system.

(140) The learning unit **305** may be adapted to, if acquiring new training data after constructing a trained model configured with the two-dimensional skeleton estimation model **2321** and the joint angle estimation model **2322**, update the robot three-dimensional skeleton estimation model **232** configured with the two-dimensional skeleton estimation model **2321** and the joint angle estimation model **2322** which has been once constructed, by further performing supervised learning for the robot three-dimensional skeleton estimation model **232** configured with the two-dimensional skeleton estimation model **2321** and the joint angle estimation model **2322**.

(141) By doing so, training data can be automatically obtained from regular photographing of the robot **10**, and, therefore, the accuracy of estimating angles of the joint axes **J1** to **J6** of the robot **10** can be increased on the daily basis.

(142) The supervised learning described above may be performed as online learning, batch learning, or mini-batch learning.

(143) The online learning is a learning method in which, each time a frame image of the robot **10** is captured, and training data is created, supervised learning is immediately performed.

(144) The batch learning is a learning method in which, while capturing of a frame image of the robot **10** and creation of training data are repeated, a plurality of pieces of training data corresponding to the repetition are collected, and supervised learning is performed using all the collected pieces of training data. The mini-batch learning is an intermediate learning method between the online learning and the batch learning, in which supervised learning is performed each time some pieces of training data have been collected.

(145) By the machine learning device described above, the robot three-dimensional skeleton estimation model **232** provided in the safety vision device **20** can be generated.

(146) One embodiment has been described above. The safety vision device **20**, however, is not limited to the above embodiment, and modifications, improvements and the like within a range that the object can be achieved are included.

Modification Example 1

(147) In the above embodiment, the safety vision device **20** calculates one area for the worker U. However, the present invention is not limited thereto. For example, the safety vision device **20** may calculate two areas RU1 and RU2 with different sizes for the worker U similarly to the areas R1 and R2 of the robot **10**. It is assumed that the length, depth, and height of the area RU1 are set larger than the length, depth, and height of the area RU2.

(148) The safety vision device **20** may be adapted to, for example, when the area RU1 of the worker U overlaps with the area R1 of the robot **10**, when the area RU2 of the worker U overlaps with the area R1 of the robot **10**, or when the area RU1 of the worker U overlaps with the area R2 of the robot **10**, output an instruction to decelerate the robot **10**, to the robot control device (not shown).

(149) The safety vision device **20** may be adapted to, when the smallest area RU2 of the worker U overlaps with the area R2 of the robot **10**, output an instruction to stop the robot **10**, to the robot control device (not shown).

(150) Though the number of the areas of each of the worker U and the robot **10** is assumed to be one or two, three or more areas may be set.

(151) By doing so, the safety vision device **20** can avoid collision between the worker U and the robot **10** more precisely.

Modification Example 2

(152) For example, in the above embodiment, the safety vision device **20** estimates three-dimensional joint point data of the worker U and angles of the joint axes J1 to J6 of the robot **10** from a frame image of the worker U and the robot **10**, and the distance and tilt between the camera **40** and the robot **10**, which have been inputted, using the human three-dimensional skeleton estimation model **231** and the robot three-dimensional skeleton estimation model **232**. However, the present invention is not limited thereto. For example, as shown in FIG. 6, a server **50** may store the human three-dimensional skeleton estimation model **231** and the robot three-dimensional skeleton estimation model **232**, and share the human three-dimensional skeleton estimation model **231** and the robot three-dimensional skeleton estimation model **232** with m safety vision devices **20A(1)** to **20A(m)** connected to the server **50** via a network **60** (m is an integer equal to or larger than 2). Thereby, even when a new robot and a new safety vision device are arranged, the human three-dimensional skeleton estimation model **231** and the robot three-dimensional skeleton estimation model **232** can be applied.

(153) Each of robots **10A(1)** to **10A(m)** corresponds to the robot **10** of FIG. 1. Each of the safety vision devices **20A(1)** to **20A(m)** corresponds to the safety vision device **20** of FIG. 1.

(154) Each function included in the safety vision device **20** in the one embodiment can be realized by hardware, software, or a combination thereof. Here, being realized by software means being realized by a computer reading and executing a program.

(155) Each component included in the safety vision device **20** can be realized by hardware including an electronic circuit and the like, software, or a combination thereof. In the case of being realized by software, a program configuring the software is installed into a computer. The program may be recorded in a removable medium and distributed to a user or may be distributed by being downloaded to the user's computer via a network. In the case of being configured with hardware, a part or all of functions of each component included in the above devices can be configured with an integrated circuit (IC), for example, an ASIC (application specific integrated circuit), a gate array, an FPGA (field programmable gate array), a CPLD (complex programmable logic device), or the like.

(156) The program can be supplied to the computer by being stored in any of various types of non-transitory computer-readable media. The non-transitory computer-readable media include various types of tangible storage media. Examples of the non-transitory computer-readable media include a magnetic recording medium (for example, a flexible disk, a magnetic tape, or a hard disk drive), a

magneto-optical recording medium (for example, a magneto-optical disk), a CD-ROM (read-only memory), a CD-R, a CD-R/W, a semiconductor memory (for example, a mask ROM and a PROM (programmable ROM)), an EPROM (Erasable PROM), a flash ROM, and a RAM). The program may be supplied to the computer by any of various types of transitory computer-readable media. Examples of the transitory computer-readable media include an electrical signal, an optical signal and an electromagnetic wave. The transitory computer-readable media can supply the program to the computer via a wired communication path such as an electrical wire and an optical fibers, or a wireless communication path.

(157) Steps describing the program recorded in a recording medium include not only processes that are performed chronologically in that order but also processes that are not necessarily performed chronologically but are executed in parallel or individually.

(158) In other words, the safety vision device and safety vision system of the present disclosure can take many different embodiments having the following configurations.

(159) (1) A safety vision device **20** of the present disclosure includes: a human three-dimensional skeleton estimation model **231** receiving input of a two-dimensional image of a human, and outputting three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points of the human; a robot three-dimensional skeleton estimation model **232** receiving input of a two-dimensional image of a robot **10**, and a distance and a tilt between a camera **40** that has captured the two-dimensional image of the robot **10** and the robot **10**, and outputting angles of a plurality of joint axes **J1** to **J6** included in the robot **10**; an input unit **213** configured to input a two-dimensional image of a worker U and the robot **10** captured by the external camera **40**, and a distance and a tilt between the external camera **40** and the robot **10**; an estimation unit **214** configured to input the two-dimensional image, and the distance and tilt between the external camera **40** and the robot **10**, which have been inputted by the input unit **213**, to the human three-dimensional skeleton estimation model **231** and the robot three-dimensional skeleton estimation model **232** to estimate three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points of the worker U and the angles of the plurality of joint axes **J1** to **J6** included in the robot **10**; and an approach determination unit **215** configured to calculate an area indicating a range of the worker U and areas **R1** and **R2** indicating a range of the robot **10**, based on the three-dimensional joint point data and the angles of the plurality of joint axes **J1** to **J6**, and outputting an instruction to decelerate or stop the robot **10** according to a degree of overlap between the area of the worker U and the areas **R1**, **R2** of the robot **10** that have been calculated.

(160) According to this safety vision device **20**, it is possible to, when a worker enters the motion area of a robot, cause the robot to decelerate or stop without using an area sensor.

(161) (2) In the safety vision device **20** according to (1), the two-dimensional image may be a frame image captured by the camera **40** at a predetermined frame rate.

(162) By doing so, the safety vision device **20** can continuously track motions of the worker U and the robot **10**.

(163) (3) The safety vision device **20** according to (1) or (2) may further include a notification unit **216** configured to output a warning sound when the approach determination unit **215** outputs the deceleration or stop instruction.

(164) By doing so, the safety vision device **20** can give a warning to the worker U.

(165) (4) In the safety vision device **20** according to any of (1) to (3), the human three-dimensional skeleton estimation model **231** and the robot three-dimensional skeleton estimation model **232** may be provided in a server **50** connected to be accessible from the safety vision device **20** via a network **60**.

(166) By doing so, the safety vision device **20** can apply a trained model even when a new robot and a new safety vision device are arranged.

(167) (5) A safety vision system **1** of the present disclosure includes the robot **10**, the camera **40**

and the safety vision device **20** according to any of (1) to (4).

(168) This safety vision system **1** have effects similar to (1) to (4).

EXPLANATION OF REFERENCE NUMERALS

(169) **1** Safety vision system **10** Robot **20** Safety vision device **21** Control unit **211** Three-dimensional object recognition unit **212** Self-position estimation unit **213** Input unit **214** Estimation unit **215** Approach determination unit **216** Notification unit **22** Communication unit **23** Storage unit **231** Human three-dimensional skeleton estimation model **232** Robot three-dimensional skeleton estimation model **2321** Two-dimensional skeleton estimation model **2322** Joint angle estimation model **30** Machine learning device **301** Information acquisition unit **302** Two-dimensional posture acquisition unit **303** Input data acquisition unit **304** Label acquisition unit **305** Learning unit **306** Storage unit **40** Camera **50** Server **60** Network

Claims

1. A safety vision device comprising: a human three-dimensional skeleton estimation model as a learned model based on a supervised learning receiving input of a two-dimensional image of a human, and outputting three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points of the human; a two-dimensional skeleton estimation model as a learned model based on a supervised learning receiving input of a two-dimensional image of a robot captured by a camera and outputting a two-dimensional posture of pixel coordinates indicating positions of the centers of the joint axes of the robot in the two-dimensional image when the two-dimensional image is captured; a robot three-dimensional skeleton estimation model as a learned model based on a supervised learning receiving input of the two-dimensional posture of pixel coordinates of the robot, and a distance and a tilt between the camera that has captured the two-dimensional image of the robot and the robot, and outputting angles of a plurality of joint axes included in the robot; an input unit configured to input a two-dimensional image of a worker and the robot captured by an external camera, and a distance and a tilt between the external camera and the robot; an estimation unit configured to input the two-dimensional image of the worker which have been inputted by the input unit to the human three-dimensional skeleton estimation model and estimate the three-dimensional joint point data indicating three-dimensional coordinate values of positions of joint points of the worker, the estimation unit further configured to input the two-dimensional image of a robot captured by the camera to the two-dimensional skeleton estimation model and estimate a two-dimensional posture of pixel coordinates indicating positions of the centers of the joint axes of the robot in the two-dimensional image, the estimation unit further configured to input the distance and tilt between the external camera and the robot, which have been inputted by the input unit, and the two-dimensional posture of pixel coordinates indicating positions of the centers of the joint axes of the robot to the robot three-dimensional skeleton estimation model, and estimate the angles of the plurality of joint axes included in the robot; and an approach determination unit configured to calculate an area indicating a range of the worker by adding a shape having a length, depth, and height set in advance for each straight line of the skeleton generated based on the three-dimensional joint point data of the worker, and an area indicating a range of the robot by adding a shape having a length, depth, and height set in advance to each link of the skeleton generated based on the three-dimensional joint point data and the angles of the plurality of joint axes, and output an instruction to decelerate or stop the robot according to a degree of overlap between the calculated areas of the worker and the robot.
2. The safety vision device according to claim 1, wherein the two-dimensional image is a frame image captured by the camera at a predetermined frame rate.
3. The safety vision device according to claim 1, further comprising a notification unit configured to output a warning sound when the approach determination unit outputs the deceleration or stop instruction.

4. The safety vision device according to claim 1, wherein the human three-dimensional skeleton estimation model and the robot three-dimensional skeleton estimation model are provided in a server connected to be accessible from the safety vision device via a network.
 5. A safety vision system comprising: a robot; a camera; and the safety vision device according to claim 1.
-