

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12410967
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lim; Suhyeong et al.

Door opening device and refrigerator having the same

Abstract

A door opening device for opening a drawer type door of a refrigerator includes: a handle lever rotatably assembled with a door cap and including a rotating and pressing portion; a transfer lever positioned behind the handle lever to rotate by the handle lever, and including a sliding surface inclined such that the rotating and pressing portion slidingly moves according to a rotation of the handle lever; and a slider assembled with a rear portion of the transfer lever in such a way as to be linearly movable, and configured to linearly move toward a rear direction according to a rotation of the transfer lever to press the main body, thereby opening the drawer type door.

Inventors: Lim; Suhyeong (Suwon-si, KR), Kang; Changgu (Suwon-si, KR), Jeong; Hyunsung (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 86897415

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 17/968390

Filed: October 18, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230204278 A1	Jun. 29, 2023

Foreign Application Priority Data

KR	10-2021-0185790	Dec. 23, 2021
----	-----------------	---------------

Related U.S. Application Data

Publication Classification

Int. Cl.: **F25D23/02** (20060101); **E05B1/00** (20060101); **E05B17/00** (20060101); **E05F11/54** (20060101); **F25D25/02** (20060101); F25D11/02 (20060101)

U.S. Cl.:

CPC **F25D23/028** (20130101); **F25D25/025** (20130101); E05B17/0033 (20130101); E05F11/54 (20130101); E05Y2900/31 (20130101); F25D11/02 (20130101); F25D23/02 (20130101); F25D23/021 (20130101)

Field of Classification Search

CPC: F25D (23/028); F25D (25/025); F25D (23/021); E05Y (2900/31); E05F (11/54); E05B (17/0033)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7984955	12/2010	Jung	312/319.2	F25D 23/028
8328301	12/2011	Lee	292/336.3	E05B 17/0033
9127879	12/2014	Hwang	N/A	F25D 23/00
9506685	12/2015	Park	N/A	F25D 23/028
9897368	12/2017	Lee	N/A	F25D 23/028
10527342	12/2019	Park	N/A	E05F 11/54
2009/0205357	12/2008	Lim et al.	N/A	N/A
2012/0280608	12/2011	Park	49/460	E05B 1/0015
2013/0270990	12/2012	Park	312/405	F25D 23/028
2014/0319989	12/2013	Hwang	312/405	F25D 23/028
2015/0292793	12/2014	Bischoff et al.	N/A	N/A
2017/0336131	12/2016	Lee	N/A	E05F 11/10
2019/0024965	12/2018	Park	N/A	F25D 23/028

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
105466101	12/2015	CN	N/A
2 299 213	12/2010	EP	N/A
2 653 810	12/2012	EP	N/A
2004-116842	12/2003	JP	N/A
10-0182734	12/1998	KR	N/A
10-2011-0064720	12/2010	KR	N/A
10-2013-0053921	12/2012	KR	N/A
10-2013-0116738	12/2012	KR	N/A
10-1510759	12/2014	KR	N/A

10-1528729	12/2014	KR	N/A
10-2017-0129541	12/2016	KR	N/A
10-1897275	12/2017	KR	N/A

OTHER PUBLICATIONS

International Search Report dated Jan. 10, 2023 in International Patent Application No.

PCT/KR2022/013538 (3 pages; 3 pages English translation). cited by applicant

PCT/ISA/237 dated Jan. 10, 2023 in International Patent Application. No. PCT/KR2022/013538 (4 pages). cited by applicant

Extended European Search Report dated Dec. 9, 2024 for European Application No. 22911509.2. cited by applicant

Primary Examiner: Wright; Kimberley S

Attorney, Agent or Firm: STAAS & HALSEY LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is continuation application, under 35 USC § 111(a) of International Application No. PCT/KR2022/013538, filed on Sep. 8, 2022, which claims priority to Korean Patent Application No. 10-2021-0185790, filed on Dec. 23, 2021 in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

(1) The disclosure relates to a refrigerator having an improved door opening device for opening a drawer type door with a recess type handle.

2. Description of the Related Art

(2) A refrigerator is an appliance that includes a main body having a storage room and a cool air supply system for supplying cool air to the storage room to keep food fresh. The storage room includes a refrigerating room that is maintained at temperature of about 0° C. to about 5° C. to keep food refrigerated, and a freezing room that is maintained at temperature of about 0° C. to about -30° C. to keep food frozen. On the front side of the main body, a door is provided to open or close the storage room. The door is rotatably provided on the front side of the main body to open or close the storage room. Also, the door is provided as a drawer type door to open or close the storage room.

(3) The drawer type door for opening or closing the storage room includes a handle which a user grips to push the drawer type door in or take the drawer type door out. The handle may be a recess type.

(4) The storage room that is opened or closed by the drawer type door having the recess type handle stores different amounts of food therein according to the capacity. In the case in which the storage room stores a large amount of food, a user who grips the handle to take out the drawer type door should apply great strength. That is, a user should apply great strength to open the drawer type door being in a closed state in an operation of opening the drawer type door.

(5) To enable a user to easily open the drawer type door, the drawer type door includes a door opening device for opening the drawer type door. By gripping the recess type handle of the drawer type door being in a closed state to operate the door opening device, the drawer type door opens by a certain gap and a user can easily open the drawer type door without applying great strength.

(6) The door opening device includes a lever which a user can press while gripping the handle, and a slider operating by the lever to open the drawer type door. In a refrigerator having a structure capable of replacing a front panel of a drawer type door, the front panel needs to have a thin thickness due to a structure for assembling the front panel. To reduce the thickness of the front panel, a moving distance of the slider needs to be long compared to an operation of the lever pressed by a user. That is, a moving distance of the slider needs to be maximally long with a minimum operation of the lever within a thin thickness of the front panel.

(7) Also, exposure of the door opening device that operates by being gripped by a user to the outside leads to damage in appearance, and accordingly, the door opening device needs to be prevented from being exposed.

SUMMARY

(8) A refrigerator according to an embodiment of the disclosure includes: a main body; a storage room formed inside the main body and having an opening formed along a front side of the main body; a drawer type door couplable with the main body and slideable along the storage room, to open or close the opening of the storage room, the drawer type door including a door cap having a handle pocket; and a door opening device connectable with a portion of the door cap, and configured to open the drawer type door, wherein the door opening device includes: a handle lever connectable with the door cap, and including a rotating and pressing portion; a transfer lever positioned behind the handle lever and rotatable by the handle lever, the transfer lever including a sliding surface inclined such that the rotating and pressing portion slides according to a rotation of the handle lever; and a slider connectable with a rear portion of the transfer lever in such a way as to be linearly movable, and configured to linearly move toward a rear direction according to a rotation of the transfer lever to press the main body, and thereby open the drawer type door.

(9) A door bracket may be connectable with a center portion of a lower end of the door cap, and the door opening device may be connectable with the door bracket.

(10) The door bracket may include a handle lever assembling portion to which the handle lever is rotatably connectable, a slider assembling portion with which the slider is connectable to in such a way as to be linearly movable, and a transfer lever assembling hole connectable to the transfer lever.

(11) The slider assembling portion may include a guide protrusion configured to guide the slider to linearly move, and an opening of the slider assembling portion configured to enable the slider to linearly move to press the main body.

(12) The door opening device may further include an elastic member of which one end is supported on the transfer lever and an other end is supported on the door bracket, the elastic member configured to return the handle lever to an original position upon removal of a force applied to the handle lever after the transfer lever rotates by the handle lever.

(13) The door cap may include a first opening configured to expose a portion of the handle lever to the handle pocket, and a second opening formed at a location corresponding to the opening of the door bracket and configured to enable the slider to linearly move to open the drawer type door.

(14) The handle lever may include a bracket of which a portion is exposed to the handle pocket, a reinforcing member connectable with the bracket and configured to reinforce the bracket, and a handle lever rotation shaft fixed to the reinforcing member and configured to enable the handle lever to be rotatably connectable with the door cap.

(15) The bracket may include a grip portion exposed to the handle pocket, a plurality of catching hooks with which the reinforcing member is assembled, and the rotating and pressing portion being in contact with the sliding surface of the transfer lever.

(16) An end of the rotating and pressing portion, which is in contact with the sliding surface, may be in a shape of a cylinder to be in linear contact with the sliding surface.

(17) The slider may include a guide rail guided by the guide protrusion, a pushed portion configured to be pushed by the transfer lever to enable the slider to linearly move toward the main

body, and a pressing portion configured to press the main body through the opening of the slider assembling portion upon a linear movement of the slider toward the main body to open the drawer type door.

(18) The transfer lever may further include a transfer lever rotation shaft fixable to the transfer lever assembling hole, a rotation hole rotatably fixable to the transfer lever rotation shaft, a push portion configured to push the slider, and a first support protrusion on which the one end of the elastic member is supported, and the door bracket may further include a second support protrusion on which the other end of the elastic member is supported.

(19) A center of the handle lever, a center of the transfer lever, and a center of the slider may be aligned along an axis.

(20) The slider and the transfer lever may be provided at a left side and a right side of the door bracket with respect to a center of the door bracket.

(21) The rotating and pressing portion of the handle lever may be provided as a pair of pieces to correspond to the transfer lever.

(22) A center of the rotating and pressing portion, a center of the transfer lever, and a center of the slider may be aligned along an axis.

(23) Also, a refrigerator according to an embodiment of the disclosure includes: a main body; a storage room formed inside the main body, wherein a front side of the storage room opens; a drawer type door slidably coupled with the main body and configured to open or close the storage room; and a door opening device assembled with the drawer type door and configured to open the drawer type door, wherein the drawer type door includes: a door cap assembled with an upper portion of the drawer type door, wherein a handle pocket is formed in the door cap; and a door bracket with which the door opening device is assembled, the door bracket assembled with a lower end of the door cap and configured to prevent the door opening device from being exposed to outside.

(24) The door opening device may include: a handle lever rotatably assembled with the door bracket and including a rotating and pressing portion; a slider configured to linearly move by the handle lever to open the drawer type door; and a transfer lever assembled with the door bracket and configured to rotate by the handle lever to push the slider.

(25) The transfer lever may include a sliding surface inclined such that the rotating and pressing portion slidably moves; and a push portion configured to push the slider, wherein, according to a rotation of the handle lever, the rotating and pressing portion slidably moves along the sliding surface to rotate the transfer lever.

(26) An end of the rotating and pressing portion, which is in contact with the sliding surface, may be in a shape of a cylinder to be in linear contact with the sliding surface.

(27) Also, in a door opening device for opening a drawer type door, according to an embodiment of the disclosure, the drawer type door includes: a door cap assembled with an upper portion of the drawer type door, wherein a handle pocket is formed in the door cap; and a door bracket assembled with a lower end of the door cap, wherein the door opening device is assembled with the door bracket, the door opening device includes: a handle lever rotatably assembled with the door bracket; a transfer lever positioned behind the handle lever and assembled with the door bracket to rotate by the handle lever; and a slider configured to linearly move toward a rear direction by the transfer lever, thereby opening the drawer type door, and a contact surface of the transfer lever, which the handle lever contacts, is inclined such that the handle lever slidably moves along the contact surface of the transfer lever according to a rotation of the handle lever.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The above and other aspects, features, and advantages of certain embodiments of the present disclosure will become apparent from the following description taken in conjunction with the accompanying drawings of which:
- (2) FIG. 1 is a perspective view of a refrigerator according to an embodiment of the disclosure;
- (3) FIG. 2 shows a door opening device installed in a drawer type door according to an embodiment of the disclosure;
- (4) FIG. 3 is a top view of a drawer type door according to an embodiment of the disclosure;
- (5) FIG. 4 shows a state in which a door cap is assembled with an upper portion of a drawer type door according to an embodiment of the disclosure, and a door opening device is assembled with a lower portion of the door cap;
- (6) FIG. 5 shows a state in which a door opening device according to an embodiment of the disclosure is assembled with a door bracket;
- (7) FIG. 6 is an exploded perspective view of a handle lever according to an embodiment of the disclosure;
- (8) FIG. 7 shows a state in which a handle lever rotation shaft according to an embodiment of the disclosure is fixed to a reinforcing member;
- (9) FIG. 8 shows a state in which a reinforcing member according to an embodiment of the disclosure is assembled with a bracket;
- (10) FIG. 9 shows a state in which a reinforcing member according to an embodiment of the disclosure is assembled with a bracket and then coupled with the bracket by a coupling member;
- (11) FIG. 10 shows a state in which a handle lever according to an embodiment of the disclosure is assembled with a door bracket;
- (12) FIG. 11 shows a state in which a slider according to an embodiment of the disclosure is assembled with a door bracket;
- (13) FIG. 12 shows a state in which a transfer lever and an elastic member according to an embodiment of the disclosure are assembled with a door bracket;
- (14) FIG. 13 shows a state in which a door bracket assembled with a door opening device according to an embodiment of the disclosure is assembled with a lower end of a door cap;
- (15) FIG. 14 shows a state in which centers of a handle lever, a transfer lever, and a slider, according to an embodiment of the disclosure, are aligned on the same line;
- (16) FIG. 15 shows a closed state of a drawer type door assembled with a door opening device according to an embodiment of the disclosure;
- (17) FIG. 16 is a cross-sectional view of a door opening device in a closed state of a drawer type door according to an embodiment of the disclosure;
- (18) FIG. 17 is a cross-sectional view showing an initial operation of a door opening device according to a rotation of a handle lever according to an embodiment of the disclosure;
- (19) FIG. 18 is a cross-sectional view showing a full operation of a door opening device according to a rotation of a handle lever according to an embodiment of the disclosure;
- (20) FIG. 19 is a cross-sectional view showing an open state of a drawer type door according to a full operation of a door opening device according to an embodiment of the disclosure;
- (21) FIG. 20 shows a drawer type door assembled with a door opening device including two sliders according to an embodiment of the disclosure;
- (22) FIG. 21 shows a state in which the door opening device shown in FIG. 20 is assembled with a door bracket;
- (23) FIG. 22 shows a state in which a door bracket assembled with a door opening device according to an embodiment of the disclosure is assembled with a lower end of a door cap; and
- (24) FIG. 23 shows a state in which centers of a rotating and pressing portion, a transfer lever, and a slider, according to an embodiment of the disclosure, are aligned on the same line.

DETAILED DESCRIPTION

- (25) Configurations illustrated in the embodiments and the drawings described in the present specification are only the preferred embodiments of the disclosure, and thus it is to be understood that various modified examples, which may replace the embodiments and the drawings described in the present specification, are possible when filing the present application.
- (26) Also, like reference numerals or symbols denoted in the drawings of the present specification represent members or components that perform the substantially same functions.
- (27) Also, the terms used in the present specification are merely used to describe embodiments, and are not intended to limit and/or restrict the disclosure. An expression used in the singular encompasses the expression of the plural, unless it has a clearly different meaning in the context. In the present specification, it is to be understood that the terms such as “comprising”, “including” or “having”, etc., are intended to indicate the existence of the features, numbers, steps, operations, components, parts, or combinations thereof disclosed in the specification, and are not intended to preclude the possibility that one or more other features, numbers, steps, operations, components, parts, or combinations thereof may exist or may be added.
- (28) Also, it will be understood that, although the terms including ordinal numbers, such as “first”, “second”, etc., may be used herein to describe various components, these components should not be limited by these terms. These terms are only used to distinguish one component from another. For example, a first component could be termed a second component, and, similarly, a second component could be termed a first component, without departing from the scope of the present disclosure. As used herein, the term “and/or” includes any and all combinations of one or more of associated listed items.
- (29) In the following description, the terms “front end”, “rear end”, “upper portion”, “lower portion”, “front surface”, “rear surface”, “upper end”, “lower end”, etc. are defined based on the drawings, and the shapes and positions of the corresponding components are not limited by the terms.
- (30) Throughout the disclosure, the expression “at least one of a, b or c” indicates only a, only b, only c, both a and b, both a and c, both b and c, all of a, b, and c, or variations thereof.
- (31) Therefore, it is an aspect of the disclosure to provide a door opening device that is operable within a small space and prevented from being exposed to outside, and a refrigerator having the door opening device.
- (32) Additional aspects of the disclosure will be set forth in part in the description which follows and, in part, will be obvious from the description, or may be learned by practice of the disclosure.
- (33) Hereinafter, embodiments of the disclosure will be described in detail with reference to the accompanying drawings.
- (34) FIG. 1 is a perspective view of a refrigerator according to an embodiment of the disclosure.
- (35) As shown in FIG. 1, a refrigerator may include a main body **10**, a storage room **20** formed inside the main body **10** and provided as a plurality of rooms of which front sides open, and a door **30** for opening or closing an open front side of the storage room **20**.
- (36) The main body **10** may include an inner case **11** forming the storage room **20**, and an outer case **13** forming an outer appearance. An insulation **15** may be foamed between the inner case **11** and the outer case **13** and inside the door **30** to prevent cool air from leaking out of the storage room **20** (see FIG. 14).
- (37) The main body **10** may include a cool air supplier for supplying cool air to the storage room **20**. The cool air supplier may include a compressor (not shown), a condenser (not shown), an expansion valve (not shown), an evaporator (not shown), a blower fan (not shown), a cool air duct (not shown), etc.
- (38) In a rear, lower portion of the main body **10**, a machine room (not shown) in which the compressor for compressing a refrigerant and the condenser for condensing the compressed refrigerant are installed may be provided.

(39) The evaporator for generating cool air, the blower fan for blowing cool air generated by the evaporator to inside of the storage room **20**, and the cool air duct for guiding cool air generated by the evaporator to the storage room **20** may be positioned on a rear wall of the storage room **20**. A plurality of evaporators, a plurality of blower fans, and a plurality of cool air ducts may be configured to independently supply cool air to the storage room **20**.

(40) The storage room **20** may be partitioned into a plurality of storage rooms by a partition wall **17**. The storage room **20** may be divided into an upper room **21**, a middle room **23**, and a lower room **25** in an up-down direction by the partition wall **17**. The upper room **21**, the middle room **23**, and the lower room **25** may keep food refrigerated or frozen as necessary.

(41) In the upper room **21**, a plurality of shelves **27** may be provided to partition the upper room **21** into a plurality of spaces. In the upper room **21**, a plurality of storage containers **28** for storing food, etc. may be provided.

(42) The door **30** may include a side-by-side type door **31** rotatably coupled with the main body **10** to open or close the upper room **21**. The side-by-side type door **31** may include a recess type handle **32** that a user grips to open or close the side-by-side type door **31**. On a rear surface of the side-by-side type door **31**, a plurality of door guards **33** for accommodating food, etc. may be installed.

(43) The door **30** may include a drawer type door **40** that is slidably movable with respect to the main body **10** to open or close the middle room **23** and the lower room **25** independently. The drawer type door **40** may include a handle pocket **51** as a recess type handle that a user grips to open or close the drawer type door **40**. The drawer type door **40** may include a storage box for storing food, etc. therein.

(44) The middle room **23** and the lower room **25**, which are opened or closed by the drawer type door **40**, may have different capacities. In the drawings, the lower room **25** is shown to have a larger capacity than the middle room **23**, although not limited thereto. In the drawer type door **40** for opening or closing the lower room **25** having the larger capacity among drawer type doors **40** for opening or closing the middle room **23** and the lower room **25**, a door opening device **100** for opening the drawer type door **40** may be provided. The reason may be because greater strength is required to open the drawer type door **40** for opening or closing the lower room **25** having the larger capacity than that required to open the drawer type door **40** for opening or closing the middle room **23** having a smaller capacity. In the drawing, the door opening device **100** is shown to be provided only in the drawer type door **40** for opening or closing the lower room **25**, although not limited thereto. That is, the door opening device **100** may be also provided in the drawer type door **40** for opening or closing the middle room **23**. A configuration of the drawer type door **40** equipped with the door opening device **100** will be described below.

(45) The drawer type doors **40** may be slidably inserted into or taken out of the middle room **23** and the lower room **25** by a sliding device **70**. One sides of the sliding device **70** for slidably moving the drawer type doors **40** may be respectively coupled with both inner side walls of the middle room **23** and the lower room **25** in which the drawer type doors **40** are respectively accommodated, and the other sides of the sliding device **70** may be respectively coupled with both side surfaces of the drawer type doors **40**.

(46) FIG. 2 shows a door opening device installed in a drawer type door according to an embodiment of the disclosure. FIG. 3 is a top view of a drawer type door according to an embodiment of the disclosure. FIG. 4 shows a state in which a door cap is assembled with an upper portion of a drawer type door according to an embodiment of the disclosure, and a door opening device is assembled with a lower portion of the door cap.

(47) As shown in FIGS. 2 to 4, the door opening device **100** may be provided in the drawer type door **40**. The drawer type door **40** may include a door cap **50** assembled with an upper portion of the drawer type door **40**. The door cap **50** may include a handle pocket **51** which is a recess type handle. The handle pocket **51** may be formed in a shape of a downward depressed groove to enable a user to grip to open the drawer type door **40**. The door opening device **100** may be assembled

with a lower portion of the door cap **50**. The door opening device **100** may be assembled with the lower portion of the handle pocket **51** to be prevented from being exposed to outside. Because the door opening device **100** is prevented from being exposed to the outside, the drawer type door **40** that opens or closes the lower room **25** may have the same outer appearance as the drawer type door **40** that opens or closes the middle room **23** and does not include the door opening device **100**, as seen from in front of the refrigerator. Therefore, the drawer type door **40** for opening or closing the middle room **23** and the drawer type door **40** for opening or closing the lower room **25** may give a sense of unity, which leads to an improvement of the outer appearance (see FIG. 1).

(48) The door cap **50** may include a first opening **53** for exposing a portion of a handle lever **110** which will be described below to the hand pocket **51**. The first opening **53** may be formed in a front portion of walls forming the handle pocket **51**. A user may grip the handle pocket **51** and press the portion of the handle lever **110** exposed through the first opening **53**. The portion of the handle lever **110** exposed through the first opening **53** may be a grip portion **121**.

(49) The door cap **50** may include a second opening **55** formed at a location corresponding to an opening **63b** of a door bracket **60** which will be described below. A portion of a slider **150** which will be described below may be exposed to outside of the drawer type door **40** through the second opening **55**. The slider **150** exposed to the outside of the drawer type door **40** through the second opening **55** may move toward a rear direction, that is, toward the main body **10** by the handle lever **110** to press the main body **10**. The second opening **55** will be described in detail together with the door bracket **60**, below.

(50) The door opening device **100** may be assembled with the door bracket **60**. The door bracket **60** may be assembled with a center portion of a lower end of the door cap **50**. That is, the door opening device **100** may be assembled with the door bracket **60** and then assembled with the center portion of the lower end of the door cap **50**. The door opening device **100** may be assembled with the lower end of the door cap **50** to be prevented from being exposed to the outside. The door opening device **100** may be positioned such that only the grip portion **121** being a portion of the handle lever **110** is exposed to the outside through the first opening **53** and the remaining portion of the door opening device **100** is prevented from being exposed to the outside.

(51) FIG. 5 shows a state in which a door opening device according to an embodiment of the disclosure is assembled with a door bracket. FIG. 6 is an exploded perspective view of a handle lever according to an embodiment of the disclosure.

(52) As shown in FIGS. 5 and 6, the door opening device **100** may be assembled with the door bracket **60**. The door opening device **100** may include the handle lever **110** rotatably assembled with the door bracket **60**. The handle lever **110** may rotate by being gripped and pressed by a user. The handle lever **110** may rotate to rotate a transfer lever **160** which will be described below.

(53) The door bracket **60** may include a handle lever assembling portion **61** with which the handle lever **110** is assembled. The handle lever **110** may be rotatably assembled with the handle lever assembling portion **61** of the door bracket **60**. The handle lever assembling portion **61** may be formed in a depressed shape in which a portion of the handle lever **110** is accommodated. The handle lever assembling portion **61** may include a plurality of fixing hooks **61a** to which a handle lever rotation shaft **140** is rotatably fixed (see FIG. 10).

(54) The door bracket **60** may include a slider assembling portion **63** with which the slider **150** is assembled. The slider **150** may be assembled with the slider assembling portion **63** of the door bracket **60** in such a way as to be linearly movable with respect to the slider assembling portion **63**. The slider assembling portion **63** may include a guide protrusion **63a** guiding the slider **150** to linearly move. The slider assembling portion **63** may include the opening **63b** to enable the slider **150** to linearly move toward the rear direction and thus press the main body **10** (see FIG. 1).

(55) The door bracket **60** may include a transfer lever assembling hole **65** with which the transfer lever **160** is assembled. A transfer lever rotation shaft **161** of the transfer lever **160** may be fixed to the transfer lever assembling hole **65**. The transfer lever **160** may be rotatably fixed to the transfer

lever rotation shaft **161**.

(56) The handle lever **110** may include a bracket **120**. The bracket **120** may include the grip portion **121** exposed to the handle pocket **51** through the first opening **53** formed in the door cap **50**. The grip portion **121** may be exposed to the outside through the handle pocket **51** such that a user presses the grip portion **121** while gripping the handle pocket **51**. As a result of pressing of the grip portion **121** by the user, the handle lever **110** may rotate (see FIG. 3).

(57) The bracket **120** may include a plurality of catching hooks **123** with which a reinforcing member **130** is assembled. The plurality of catching hooks **123** may include a plurality of first catching hooks **123a** and a plurality of second catching hooks **123b**. The plurality of first catching hooks **123a** may be formed in an upper portion of the bracket **120**. The plurality of second catching hooks **123b** may be formed in a lower portion of the bracket **120**. The plurality of first catching hooks **123a** may be caught by a plurality of catching grooves of the reinforcing member **130** which will be described below and fixed. The plurality of second catching hooks **123b** may be caught by a plurality of catching holes **135** of the reinforcing member **130** and fixed.

(58) The bracket **120** may include a first coupling hole **125** through which the reinforcing member **130** is coupled with the bracket **120** by a coupling member S after the reinforcing member **130** is assembled with the bracket **120**. The first coupling hole **125** may be formed at a location corresponding to a second coupling hole **137** formed in the reinforcing member **130**. By coupling the coupling member S with the second coupling hole **137** of the reinforcing member **130** and the first coupling hole **125** of the bracket **120**, the reinforcing member **130** may be coupled with the bracket **120**.

(59) The bracket **120** may include a rotating and pressing portion **127** pressing the transfer lever **160**. The rotating and pressing portion **127** may be in contact with a sliding surface **163** of the transfer lever **160** which will be described below. One end of the rotating and pressing portion **127**, which is in contact with the sliding surface **163**, may be in a shape of a cylinder. The end of the rotating and pressing portion **127**, which is in a shape of a cylinder, may be in linear contact with the sliding surface **163**. According to a rotation of the handle lever **110**, the rotating and pressing portion **127** may slidably move along the sliding surface **163** to rotate the transfer lever **160** (see FIG. 15).

(60) The handle lever **110** may include the reinforcing member **130**. The reinforcing member **130** may be coupled with the bracket **120** to reinforce stiffness of the bracket **120**. The reinforcing member **130** may include a fixing portion **131** to which the handle lever rotation shaft **140** is fixed. The handle lever rotation shaft **140** may be inserted into and fixed to the fixing portion **131**.

(61) The reinforcing member **130** may include a plurality of catching grooves **133** and a plurality of catching holes **135** with which the plurality of catching hooks **123** of the bracket **120** are assembled. The plurality of first catching hooks **123a** among the plurality of catching hooks **123** may be assembled with the plurality of catching grooves **133** by being caught by the plurality of catching grooves **133**. The plurality of second catching hooks **123b** among the plurality of catching hooks **123** may be assembled with the plurality of catching holes **135** by being caught by the plurality of catching holes **135**.

(62) The reinforcing member **130** may include a second coupling hole **137** to enable the reinforcing member **130** to be coupled with the bracket **120** by a coupling member S. The second coupling hole **137** may be formed at a location corresponding to the first coupling hole **125** formed in the bracket **120**. The coupling member S may be coupled with the second coupling hole **137** of the reinforcing member **130** and the first coupling hole **125** of the bracket **120** to couple the reinforcing member **130** with the bracket **120**.

(63) The handle lever **110** may include the handle lever rotation shaft **140**. The handle lever rotation shaft **140** may be inserted into and fixed to the fixing portion **131** of the reinforcing member **130**. The handle lever rotation shaft **140** may be rotatably fixed to a fixing hook **61a** (which will be described below) of the door bracket **60**. The handle lever **110** may be rotatably

assembled with the door bracket **60** by the handle lever rotation shaft **140**. The handle lever **110** may rotate on the handle lever rotation shaft **140**.

(64) The door opening device **100** may include the slider **150** assembled with the door bracket **60** in such a way to be linearly movable with respect to the door bracket **60**. As a result of pressing and rotating of the handle lever **110** by a user, the transfer lever **160** may rotate by the handle lever **110**, and the slider **150** may linearly move by the rotating transfer lever **160** to press the main body **10**. According to pressing of the main body **10** by the slider **150**, the drawer type door **40** may open (see FIG. 1).

(65) The slider **150** may include a guide rail **151** that is guided by the guide protrusion **63a** of the door bracket **60**. A pair of guide rails **151** may be respectively formed at both side surfaces of the slider **151**. The guide rail **151** may be guided by the guide protrusion **63a**, and thus, the slider **150** may move linearly.

(66) The slider **150** may include a pushed portion **153** that is pushed by the transfer lever **160**. The pushed portion **153** may be provided in a rear end of the slider **150** to be in contact with the transfer lever **160**. According to a rotation of the transfer lever **160** by the handle lever **110**, the transfer lever **160** may push the pushed portion **153** to cause the slider **150** to linearly move toward the rear direction. That is, the slider **150** may move linearly toward the main body **10** (see FIG. 1).

(67) The slider **150** may include a pressing portion **155** that moves linearly toward the rear direction to press the main body **10** (see FIG. 1). The pressing portion **155** may be provided at a front end of the slider **150**. According to pushing of the pushed portion **153** by the transfer lever **160**, the slider **150** may move linearly toward the rear direction, and thus, the pressing portion **155** may press the main body **10** (see FIG. 1) through the opening **63b** formed in the door bracket **60**. The opening **63b** may be formed at a location corresponding to the second opening **55** of the door cap **50**. Accordingly, the pressing portion **155** may press the main body **10** (see FIG. 1) through the opening **63b** of the door bracket **60** and the second opening **55** of the door cap **50**.

(68) The door opening device **100** may include the transfer lever **160** assembled with the door bracket **60** and rotating with respect to the door bracket **60**. The transfer lever **160** may be positioned between the handle lever **110** and the slider **150**. According to a rotation of the handle lever **110**, the transfer lever **160** may rotate by the handle lever **110**, and according to the rotation of the transfer lever **160**, the slider **150** may move linearly by the transfer lever **160** to press the main body **10** (see FIG. 1).

(69) The transfer lever **160** may include the transfer lever rotation shaft **161** assembled with the transfer lever assembling hole **65** of the door bracket **60**. After the transfer lever rotation shaft **161** is assembled with the transfer lever assembling hole **65**, the transfer lever rotation shaft **161** may be fixed by the coupling member S. The transfer lever **160** may be rotatably fixed to the transfer lever rotation shaft **161**.

(70) The transfer lever **160** may include a rotation hole **162** rotatably fixed to the transfer lever rotation shaft **161**. The transfer lever rotation hole **161** may be rotatably fixed to the transfer lever rotation shaft **161**, and thus, the transfer lever **160** may rotate on the transfer lever rotation shaft **161**.

(71) The transfer lever **160** may include the sliding surface **163** inclined such that the rotating and pressing portion **127** of the handle lever **110** slidably moves on the sliding surface **163**. The sliding surface **163** may be a contact surface being in contact with the rotating and pressing portion **127** of the handle lever **110**. According to a rotation of the handle lever **110**, the rotating and pressing portion **127** may slidably move along the sliding surface **163** to rotate the transfer lever **160**. The end of the rotating and pressing portion **127** may be in a shape of a cylinder to be in linear contact with the sliding surface **163**. Because the end of the rotating and pressing portion **127** is in linear contact with the sliding surface **163** and the rotating and pressing portion **127** slidably moves along the inclined sliding surface **163** according to a rotation of the handle lever **110** to rotate the transfer lever **160**, an angle by which the transfer lever **160** rotates may be greater than an angle by

which the handle lever **110** rotates. Accordingly, although the handle lever **110** rotates by a small angle, the slider **150** may move to a long distance by the transfer lever **160** rotating by a great angle (see FIG. 15).

(72) The transfer lever **160** may include a push portion **165** that is in contact with the slider **150** to push the slider **150**. According to a rotation of the transfer lever **160** by the handle lever **110**, the push portion **165** may push the pushed portion **153** of the slider **150** to cause the slider **150** to linearly move toward the main body **10** (see FIG. 1).

(73) The transfer lever **160** may include a first support protrusion **167** (see FIG. 15) supporting one end of an elastic member **170**. The transfer lever **160** may compress the elastic member **170** according to a rotation of the first support protrusion **167** (see FIG. 15) in a direction toward the second support protrusion **67** of the door bracket **60**, and by a compressive force of the elastic member **170**, the first support protrusion **167** (see FIG. 15) may rotate in an opposite direction of the direction toward the second support protrusion **67** of the door bracket **60**.

(74) The door opening device **100** may include the elastic member **170** of which one end is supported on the transfer lever **160** and the other end is supported on the door bracket **60**. The elastic member **170** may be a spring. The transfer lever **160** may include a first support protrusion **167** (see FIG. 15) supporting the one end of the elastic member **170**. The door bracket **60** may include a second support protrusion **67** supporting the other end of the elastic member **170**. The elastic member **170** may be positioned between the transfer lever **160** and the door bracket **60**. As a result of pressing and rotating of the handle lever **110** by a user, the transfer lever **160** may rotate by the handle lever **110** to compress the elastic member **170**. Upon removal of a force applied to the handle lever **110** in the compressed state of the elastic member **170**, the transfer lever **160** may rotate in an opposite direction of a direction in which the force has been applied to the handle lever **110** by the compressive force of the elastic member **170**. According to the rotation of the transfer lever **160**, the handle lever **110** may rotate by the transfer lever **160** to return to an original position before the force is applied to the handle lever **110**.

(75) FIG. 7 shows a state in which a handle lever rotation shaft according to an embodiment of the disclosure is fixed to a reinforcing member. FIG. 8 shows a state in which a reinforcing member according to an embodiment of the disclosure is assembled with a bracket. FIG. 9 shows a state in which a reinforcing member according to an embodiment of the disclosure is assembled with a bracket and then coupled with the bracket by a coupling member.

(76) As shown in FIG. 7, the handle lever rotation shaft **140** may be inserted into and fixed to the fixing portion **131** of the reinforcing member **130**.

(77) After the handle lever rotation shaft **140** is fixed to the fixing portion **131** of the reinforcing member **130**, the reinforcing member **130** may be assembled with the bracket **120**, as shown in FIG. 8. To assemble the reinforcing member **130** with the bracket **120**, the plurality of first catching hooks **123a** among the plurality of catching hooks **123** formed in the bracket **120** may be inserted into and fixed to the plurality of catching grooves **133** of the reinforcing member **130**. The plurality of first catching hooks **123a** of the bracket **120** may be formed in the upper portion of the bracket **120** and the plurality of catching grooves **133** of the reinforcing member **130** may be formed in an upper portion of the reinforcing member **130**. After the plurality of first catching hooks **123a** are fixed to the plurality of catching grooves **133**, the reinforcing member **130** may rotate.

(78) By rotating the reinforcing member **130**, the plurality of second catching hooks **123b** of the bracket **120** may be fixed to the plurality of catching holes **135** of the reinforcing member **130**, as shown in FIG. 9. According to the fixing of the plurality of catching hooks **123b** of the bracket **120** to the plurality of catching holes **135** of the reinforcing member **130**, the first coupling hole **125** of the bracket **120** may be aligned with the second coupling hole **137** of the reinforcing member **130**. After the plurality of second catching hooks **123b** of the bracket **120** are fixed to the plurality of catching holes **135** of the reinforcing member **130**, a coupling member S may be coupled with the second coupling hole **137** and the first coupling hole **125**, thereby assembling the reinforcing

member **130** with the bracket **120**.

(79) FIG. **10** shows a state in which a handle lever according to an embodiment of the disclosure is assembled with a door bracket. FIG. **11** shows a state in which a slider according to an embodiment of the disclosure is assembled with a door bracket. FIG. **12** shows a state in which a transfer lever and an elastic member according to an embodiment of the disclosure are assembled with a door bracket.

(80) As shown in FIG. **10**, the handle lever **110** may be assembled with the door bracket **60**. The handle lever **110** may be rotatably assembled with the handle lever assembling portion **61** of the door bracket **60**. The handle lever rotation shaft **140** may be rotatably fixed to the plurality of fixing hooks **61a** of the handle lever assembling portion **61**.

(81) After the handle lever **110** is assembled with the door bracket **60**, the slider **150** may be assembled with the door bracket **60**, as shown in FIG. **11**. The slider **150** may be assembled with the slider assembling portion **63** of the door bracket **60** in such a way as to be linearly movable with respect to the slider assembling portion **63**. The slider **150** may be assembled such that the guide rail **151** is guided by the guide protrusion **63a** of the door bracket **60** to linearly move.

(82) After the slider **150** is assembled with the door bracket **60**, as shown in FIG. **12**, one end of the elastic member **170** may be supported on the first support protrusion **167** (see FIG. **15**) of the transfer lever **160**, and the other end of the elastic member **170** may be supported on the second support protrusion **67** of the door bracket **60**. Because both ends of the elastic member **170** are supported on the transfer lever **160** and the door bracket **60**, the transfer lever **160** may be positioned such that the rotation hole **162** of the transfer lever **160** is positioned in the transfer lever assembling hole **65** of the door bracket **60**. After the transfer lever **160** is positioned such that the rotation hole **162** is positioned in the transfer lever assembling hole **65**, the transfer lever rotation shaft **161** may be inserted into the transfer lever assembling hole **65** and the rotation hole **162**. After the transfer lever rotation shaft **161** is inserted into the transfer lever assembling hole **65** and the rotation hole **162**, the transfer lever rotation shaft **161** may be fixed to the transfer lever assembling hole **65** by a coupling member S. After the transfer lever rotation shaft **161** is fixed to the transfer lever assembling hole **65**, the transfer lever **160** may rotate on the transfer lever rotation shaft **161**.

(83) FIG. **13** shows a state in which a door bracket assembled with a door opening device according to an embodiment of the disclosure is assembled with a lower end of a door cap.

(84) As shown in FIG. **13**, the door bracket **60** assembled with the door opening device **100** may be assembled with the lower end of the door cap **50**. The door bracket **60** may be assembled with the center portion of the lower end of the door cap **50**. The door bracket **60** may be assembled with a lower end of the handle pocket **51** of the door cap **50**. Because the door bracket **60** is assembled with the lower end of the handle pocket **51**, the door opening device **100** may be prevented from being exposed to the outside. Because the door opening device **100** is prevented from being exposed, the drawer type door **40** that opens or closes the lower room **25** may have the same outer appearance as the drawer type door **40** that opens or closes the middle room **23** and does not include the door opening device **100**, as seen from in front of the refrigerator. Therefore, the drawer type door **40** for opening or closing the middle room **23** and the drawer type door **40** for opening or closing the lower room **25** may give a sense of unity, which leads to an improvement of the outer appearance (see FIG. **1**).

(85) In the door bracket **60**, a first assembling hole **69** may be formed to assemble the door bracket **60** with the door cap **50**. In the door cap **50**, a second assembling hole **57** with which the first assembling hole **69** of the door bracket **60** is assembled may be formed. The door bracket **60** may be assembled with the door cap **50** by a coupling member S that is coupled with the first assembling hole **69** and the second assembling hole **57**.

(86) FIG. **14** shows a state in which centers of a handle lever, a transfer lever, and a slider, according to an embodiment of the disclosure, are aligned on the same line.

(87) As shown in FIG. **14**, centers of the handle lever **110**, the transfer lever **160**, and the slider **150**

may be aligned on the same line. Because the centers of the handle lever **110**, the transfer lever **160**, and the slider **150** are aligned on a straight line, a moving distance of the slider **150** may be prevented from being reduced by bending of the handle lever **110**.

(88) FIG. **15** shows a closed state of a drawer type door assembled with a door opening device according to an embodiment of the disclosure. FIG. **16** is a cross sectional view of a door opening device in a closed state of a drawer type door according to an embodiment of the disclosure. FIG. **17** is a cross-sectional view showing an initial operation of a door opening device according to a rotation of a handle lever according to an embodiment of the disclosure. FIG. **18** is a cross-sectional view showing a full operation of a door opening device according to a rotation of a handle lever according to an embodiment of the disclosure. FIG. **19** is a cross sectional view showing an open state of a drawer type door according to a full operation of a door opening device according to an embodiment of the disclosure.

(89) As shown in FIGS. **15** and **16**, in a closed state of the drawer type door **40**, the pressing portion **155** of the slider **150** may be in contact with the main body **10**. In this case, the pressing portion **155** of the slider **150** may be in contact with the main body **10** without pressing the main body **10**. That is, the transfer lever **160** may have rotated to the maximum in a counterclockwise direction on the transfer lever rotation shaft **161** by an elastic force of the elastic member **170**. Because the transfer lever **160** has rotated to the maximum in the counterclockwise direction on the transfer lever rotation shaft **161**, the pressing portion **155** of the slider **150** may be in contact with the main body **10** without pressing the main body **10**.

(90) As shown in FIG. **17**, upon pressing of the handle lever **110** by a user, the handle lever **110** may rotate in the counterclockwise direction on the handle lever rotation shaft **140**. As a result of the rotation in counterclockwise direction of the handle lever **110** on the handle lever rotation shaft **140**, the rotating and pressing portion **127** of the handle lever **110** may slidably move along the sliding surface **163** of the transfer lever **160**. According to the sliding movement of the rotating and pressing portion **127** along the inclined sliding surface **163**, the transfer lever **160** may rotate in a clockwise direction on the transfer lever rotation shaft **161**. According to the rotation in clockwise direction of the transfer lever **160** on the transfer lever rotation shaft **161**, the push portion **165** of the transfer lever **160** may push the pushed portion **153** of the slider **150**.

(91) As shown in FIGS. **18** and **19**, upon full pressing of the handle lever **110** by a user, the handle lever **110** may rotate by an angle of $A1$ in the counterclockwise direction on the handle lever rotation shaft **140**. At this time, the handle lever **110** may move by a distance of $D1$ toward the front direction from a position of the handle lever **110** before the handle lever **110** rotates.

(92) As a result of the rotation in counterclockwise direction of the handle lever **110** on the handle lever rotation shaft **140**, the rotating and pressing portion **127** of the handle lever **110** may slidably move up to an end of the sliding surface **163** of the transfer lever **160** along the sliding surface **163**. The end of the rotating and pressing portion **127** may be in a shape of a cylinder to be in linear contact with the sliding surface **163**. Because the end of the rotating and pressing portion **127**, being in linear contact with the sliding surface **163**, moves along the sliding surface **163** to rotate the transfer lever **160**, the transfer lever **160** may rotate to a greater angle than the handle lever **110**. That is, the transfer lever **160** may rotate by an angle of $A2$ in the clockwise direction on the transfer lever rotation shaft **161**. The angle of $A2$ by which the transfer lever **160** rotates may be greater than the angle of $A1$ by which the handle lever **110** rotates.

(93) As a result of the rotation in clockwise direction by the angle of $A2$ of the transfer lever **160** on the transfer lever rotation shaft **161**, the push portion **165** of the transfer lever **160** may push the pushed portion **153** of the slider **150** to cause the slider **150** to linearly move in a direction toward the main body **10**. At this time, the slider **150** may move by a distance of $D2$ toward the main body **10**. The distance of $D2$ by which the slider **150** moves may be greater than the distance of $D1$ by which the handle lever **110** moves. According to the linear movement of the slider **150** toward the main body **10**, the pressing portion **155** may press the main body **10**. According to the pressing of

the main body **10** by the slider **150**, the drawer type door **40** may move toward the front direction to open. That is, the drawer type door **40** may move in a direction away from the main body **10** to open. According to the rotation in clockwise direction of the transfer lever **160** on the transfer lever rotation shaft **161**, the elastic member **170** may be compressed.

(94) As described above, because, according to a rotation of the handle lever **110**, the rotating and pressing portion **127** of the handle lever **110**, being in a shape of a cylinder, slidably moves along the inclined sliding surface **163** of the transfer lever **160** to rotate the transfer lever **160**, the transfer lever **160** may rotate by the angle of $A2$ that is greater than the angle of $A1$ by which the handle lever **110** rotates. Also, the slider **150** may move by the distance of $D2$ that is greater than the distance of $D1$ by which the handle lever **110** moves. That is, because an operation of the slider **150** is maximized with a minimal operation of the handle lever **110**, the door opening device **100** may be efficiently used within a small space.

(95) FIG. **20** shows a drawer type door assembled with a door opening device including two sliders according to an embodiment of the disclosure. FIG. **21** shows a state in which the door opening device shown in FIG. **20** is assembled with a door bracket.

(96) As shown in FIGS. **20** and **21**, sliders **150** may be provided respectively at left and right sides of the door bracket **60** with respect to a center of the door bracket **60**. That is, a pair of sliders **150** may be provided. Because the pair of sliders **150** is provided, a pair of transfer levers **160** may be provided to move the sliders **150**. Because the pair of sliders **150** and the pair of transfer levers **160** are provided, a pair of rotating and pressing portions **127** of the handle lever **110** may be provided to correspond to the pair of sliders **150** and the pair of transfer levers **160**. Also, a pair of elastic members **170** may be provided. Also, to correspond to a pair of door opening devices **100**, some components of the door bracket **60**, with which the door opening devices **100** are assembled, may also be provided as a pair of pieces. Also, to linearly move the sliders **150**, a pair of second openings **55** may be formed in the door cap **50**. As described above, although some of components of the door opening device **100** are provided as a pair of pieces, the other components may be the same as those of the door opening device **100** shown in FIG. **5**. That is, although some components of the door opening device **100** are provided as a pair of pieces, the remaining components may be the same as those described above.

(97) As described above, because the pair of sliders **150** is provided, the door opening device **100** may operate more stably to open the drawer type door **40**. That is, because the pair of sliders **150** presses the main body **10**, the drawer type door **40** may open stably without failure.

(98) FIG. **22** shows a state in which a door bracket assembled with a door opening device according to an embodiment of the disclosure is assembled with a lower end of a door cap.

(99) As shown in FIG. **22**, except that some components of the door opening device **100** are provided as a pair of components and thus some components of the door bracket **60** are provided as a pair of components, the remaining components may be the same as those by which the door bracket **60** shown in FIG. **13** is assembled with the lower end of the door cap **50**.

(100) FIG. **23** shows a state in which centers of a rotating and pressing portion, a transfer lever, and a slider, according to an embodiment of the disclosure, are aligned on the same line.

(101) As shown in FIG. **3**, centers of the rotating and pressing portion **127**, the transfer lever **160**, and the slider **150** may be aligned on the same line. Because the centers of the rotating and pressing portion **127**, the transfer lever **160**, and the slider **150** are positioned on a straight line, a moving distance of the slider **150** may be prevented from being reduced by bending of the handle lever **110**.

(102) According to the embodiments of the disclosure, the door opening device for opening the drawer type door with the recess type handle may operate efficiently even within a small space.

(103) Also, the door opening device may be prevented from being exposed to the outside, resulting in an improvement of appearance.

(104) While the above descriptions about the door opening device and the refrigerator having the same, given with reference to the accompanying drawings, are based on specific shapes and

directions, various modifications and changes may be made by those of skilled in the art, and such various modification and changes should be interpreted to be included in the scope of rights of the disclosure.

Claims

1. A refrigerator comprising: a main body; a storage room formed inside the main body and having an opening formed along a front side of the main body; a drawer type door couplable with the main body and slideable along the storage room to open or close the opening of the storage room, the drawer type door including a door cap having a handle pocket; and a door opening device connectable with a portion of the door cap, and configured to open the drawer type door, wherein the door opening device includes: a handle lever connectable with the door cap so as to be rotatable, and including: a rotating and pressing portion, and a grip portion exposed in the handle pocket in a direction facing a rear of the drawer type door, and configured to be pressed into the drawer type door to rotate the handle lever in a first rotation direction, a transfer lever positioned behind the handle lever and rotatable by rotation of the handle lever, the transfer lever including a sliding surface inclined such that, when the handle lever is rotated in the first rotation direction, the rotating and pressing portion slides along the sliding surface to rotate the transfer lever in a second rotation direction that is opposite to the first rotation direction, and a slider connectable with a rear portion of the transfer lever in such a way as to be linearly movable, and configured to linearly move toward a rear direction according to the rotation of the transfer lever in the second rotation direction to press the main body, and thereby open the drawer type door, and wherein the handle lever includes: a bracket of which a portion is exposed to the handle pocket, a reinforcing member connectable with the bracket and configured to reinforce the bracket, and a handle lever rotation shaft fixed to the reinforcing member and configured to enable the handle lever to be rotatably connectable with the door cap.
2. The refrigerator of claim 1, wherein a door bracket is connectable with a center portion of a lower end of the door cap, and the door opening device is connectable with the door bracket.
3. The refrigerator of claim 2, wherein the door bracket includes: a handle lever assembling portion to which the handle lever is rotatably connectable, a slider assembling portion with which the slider is connectable to in such a way as to be linearly movable, and a transfer lever assembling hole connectable to the transfer lever.
4. The refrigerator of claim 3, wherein the slider assembling portion includes a guide protrusion configured to guide the slider to linearly move, and an opening of the slider assembling portion configured to enable the slider to linearly move to press the main body.
5. The refrigerator of claim 4, wherein the door opening device includes an elastic member having a first end supported on the transfer lever, and a second end supported on the door bracket, the elastic member configured to return the handle lever to an original position upon removal of a force applied to the handle lever after the transfer lever is rotated by the handle lever.
6. The refrigerator of claim 5, wherein the door cap includes: a first opening configured to expose a portion of the handle lever to the handle pocket, and a second opening formed at a location corresponding to the opening of the door bracket and configured to enable the slider to linearly move to open the drawer type door.
7. The refrigerator of claim 1, wherein the bracket includes: the grip portion exposed to the handle pocket, a plurality of catching hooks with which the reinforcing member is assembled to the bracket.
8. The refrigerator of claim 1, wherein an end of the rotating and pressing portion is in a shape of a cylinder to be in linear contact with the sliding surface.
9. The refrigerator of claim 4, wherein the slider includes: a guide rail guided by the guide protrusion, a pushed portion configured to be pushed by the transfer lever to linearly move the

slider toward the main body, and a pressing portion configured to press the main body through the opening of the slider assembling portion upon a linear movement of the slider toward the main body to open the drawer type door.

10. The refrigerator of claim 5, wherein the transfer lever includes: a transfer lever rotation shaft fixable to the transfer lever assembling hole, a rotation hole rotatably fixable to the transfer lever rotation shaft, a push portion configured to push the slider, and a first support protrusion on which the first end of the elastic member is supported, and wherein the door bracket includes a second support protrusion on which the second end of the elastic member is supported.

11. The refrigerator of claim 1, wherein a center of the handle lever, a center of the transfer lever, and a center of the slider are aligned along an axis.

12. The refrigerator of claim 3, wherein the slider and the transfer lever are provided at a left side and a right side of the door bracket with respect to a center of the door bracket.

13. The refrigerator of claim 12, wherein the rotating and pressing portion of the handle lever is provided as a pair of pieces to correspond to the transfer lever.

14. The refrigerator of claim 13, wherein a center of the rotating and pressing portion, a center of the transfer lever, and a center of the slider are aligned along an axis.
