

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412576
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Yae; Seong Soo

Vehicle and control method thereof

Abstract

A voice recognition apparatus for use in a vehicle may include: a user interface configured to receive a command from a user; a memory configured to store data about a voice recognition usage history of the user; and a processor configured to change a voice recognition guide mode to one of a plurality of modes divided according to a degree of detail of a voice recognition guide based on the voice recognition usage history. Corresponding methods for controlling a voice recognition apparatus for use in a vehicle are disclosed.

Inventors:	Yae; Seong Soo (Gyeonggi-do, KR)
Applicant:	Hyundai Motor Company (Seoul, KR); Kia Corporation (Seoul, KR)
Family ID:	86693660
Assignee:	Hyundai Motor Company (Seoul, KR); Kia Corporation (Seoul, KR)
Appl. No.:	18/074870
Filed:	December 05, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230206917 A1	Jun. 29, 2023

Foreign Application Priority Data

KR	10-2021-0187750	Dec. 24, 2021
----	-----------------	---------------

Publication Classification

Int. Cl.: G10L15/22 (20060101); B60K35/00 (20240101); B60K35/10 (20240101); G10L25/78 (20130101)

U.S. Cl.:

CPC **G10L15/22** (20130101); **B60K35/00** (20130101); **G10L25/78** (20130101); B60K35/10 (20240101); B60K2360/148 (20240101); G10L2015/223 (20130101)

Field of Classification Search

CPC: G10L (15/22); G10L (25/78); G10L (2015/223); G10L (15/30); B60K (35/00); B60K (35/10); B60K (2360/148); G06F (3/167); B60W (40/08); B60W (50/08); B60W (2040/089); B60W (2050/0005)

USPC: 704/270

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2007/0094033	12/2006	Nagashima et al.	N/A	N/A
2011/0276329	12/2010	Ayabe et al.	N/A	N/A
2018/0204570	12/2017	Puranik	N/A	H04N 21/41422
2019/0147862	12/2018	Lu et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2001296890	12/2000	JP	N/A
2004258233	12/2003	JP	N/A
2006197298	12/2005	JP	N/A
201122748	12/2010	JP	N/A
2004258233	12/2003	KR	G10L 15/28
20180081933	12/2017	KR	B60R 16/0373

Primary Examiner: Goins; Davetta W

Assistant Examiner: Solaiman; Fouzia Hye

Attorney, Agent or Firm: Fox Rothschild LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application claims under 35 U.S.C. § 119 the benefit of Korean Patent Application No. 10-2021-0187750, filed on Dec. 24, 2021, in the Korean Intellectual Property Office, the entire contents of which are incorporated herein by reference.

BACKGROUND

1. Technical Field

(2) The disclosure relates to a vehicle and a control method thereof that may automatically set a voice prompt provided for a voice recognition usage guide according to a user's proficiency level.

2. Background

(3) A vehicle refers to a machine travelling on a road or rail to move to a destination. In general, a

vehicle is capable of moving by rotation of one or more wheels mounted on a vehicle body. Such a vehicle may include a three-wheeled or four-wheeled automobile, a two-wheeled vehicle such as a motorcycle, heavy construction equipment, a bicycle, or a train running on a railway.

(4) Recently, a vehicle is equipped with a variety of devices for user convenience or fun of driving. For example, a device capable of recognizing a user's voice and performing various operations such as making a call, searching for a destination, etc., in response to the recognized voice may be installed inside a vehicle.

(5) Such devices may include a terminal device such as a smartphone, an instrument panel, a navigation device, a head unit, and the like.

SUMMARY

(6) An aspect of the disclosure provides a vehicle and a control method thereof that may automatically set a voice recognition guide mode based on a user's voice recognition usage history.

(7) Additional aspects of the disclosure will be set forth in part in the description which follows and, in part, will be obvious from the description, or may be learned by practice of the disclosure.

(8) According to an embodiment of the disclosure, there is provided a voice recognition apparatus for use in a vehicle. The apparatus may include: a user interface configured to receive a command from a user; a memory storage configured to store data, the data comprising a voice recognition usage history of the user; and a processor configured to change a voice recognition guide mode, the voice recognition guide mode being chosen from a plurality of voice recognition guide modes according to a degree of detail of a voice recognition guide based on the voice recognition usage history.

(9) The plurality of modes include a first mode and a second mode, and if the first mode is changed to the second mode, the degree of detail of the voice recognition guide is increased.

(10) The processor is configured to change the voice recognition guide mode from the second mode to the first mode, if: a number of successful voice recognition commands of the user is accumulated more than a reference number of times for the same command.

(11) The processor is configured to change the voice recognition guide mode to the second mode, if the voice recognition guide mode is in the first mode and a voice recognition fails.

(12) The processor is configured to determine that the voice recognition fails, if the user does not utter a command for a period of time greater than a reference period of time or the user inputs a command of another domain.

(13) The processor is configured to determine that the voice recognition fails, if the user utters a single sound, and thereafter the command is input after a reference period of time.

(14) If the first mode is changed to the second mode due to a failure of a voice recognition, and thereafter the voice recognition is successful by the user inputting a same command before the voice recognition guide ends, the processor is further configured to change the voice recognition guide mode to the first mode.

(15) The processor is further configured to change the voice recognition guide mode from the first mode to the second mode, if the user does not use the vehicle for a time period greater than a reference number of days.

(16) If the voice recognition guide mode is changed from the first mode to the second mode, and then a voice recognition is successful by the user inputting a same command before the voice recognition guide ends, the processor is configured to change the voice recognition guide mode to the first mode.

(17) According to an embodiment of the disclosure, there is provided a control method of a voice recognition apparatus for use in a vehicle, the control method including: receiving a command from a user; storing data about a voice recognition usage history of the user; and changing a voice recognition guide mode chosen from a plurality of voice recognition guide modes according to a degree of detail of a voice recognition guide based on the voice recognition usage history.

(18) The plurality of modes include a first mode and a second mode, and if the first mode is

changed to the second mode, the degree of detail of the voice recognition guide is increased.

(19) The changing of the voice recognition guide mode step changes the voice recognition guide mode from the second mode to the first mode, if: a number of successful voice recognition commands of the user is accumulated more than a reference number of times for the same command.

(20) The changing of the voice recognition guide mode step changes the voice recognition guide mode to the second mode, if the voice recognition guide mode is the first mode and a voice recognition fails.

(21) The changing of the voice recognition guide mode step determines that the voice recognition fails, if the user does not utter a command for a period of time greater than a reference period of time or the user inputs a command of another domain.

(22) The changing of the voice recognition guide mode determines that the voice recognition fails, if the user utters a single sound, and thereafter the command is input after a reference period of time.

(23) If the first mode is changed to the second mode due to a failure of a voice recognition, and thereafter the voice recognition is successful by the user inputting a same command before the voice recognition guide ends, the changing of the voice recognition guide mode changes the voice recognition guide mode to the first mode.

(24) The changing of the voice recognition guide mode step changes the voice recognition guide mode from the first mode to the second mode, if the user does not use the vehicle for a time period greater than a reference number of days.

(25) If the voice recognition guide mode is changed from the first mode to the second mode, and then a voice recognition is successful by the user inputting a same command before the voice recognition guide ends, the changing of the voice recognition guide mode changes the voice recognition guide mode to the first mode.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) These and/or other aspects of the disclosure will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings of which:

(2) FIG. 1 is a control block diagram illustrating a vehicle according to an embodiment;

(3) FIG. 2 is a detailed control block diagram illustrating constituent components controllable by voice recognition in a vehicle according to an embodiment;

(4) FIG. 3 is a detailed control block diagram illustrating a memory of a vehicle according to an embodiment;

(5) FIG. 4 is a detailed control block diagram illustrating a processor of a vehicle according to an embodiment;

(6) FIG. 5 illustrates examples of each variable in a vehicle according to an embodiment;

(7) FIG. 6 is a diagram illustrating a difference between when the disclosure is applied to a vehicle according to an embodiment and when the disclosure is not applied to a vehicle according to an embodiment;

(8) FIGS. 7 and 8 are flowcharts illustrating operations of updating a prompt cancel count (PCc) in a vehicle according to an embodiment;

(9) FIG. 9 is a flowchart illustrating operations of updating a voice prompt count (VPc) and a voice prompt (VP) in a vehicle according to an embodiment;

(10) FIGS. 10 and 11 are flowcharts illustrating operations of updating a PCc, VPc, and VP in a vehicle according to an embodiment; and

(11) FIG. 12 is a flowchart illustrating operations of updating a VPc in a vehicle according to an embodiment, when the vehicle has not been used for a long time.

DETAILED DESCRIPTION

(12) The embodiments set forth herein and illustrated in the configuration of the disclosure are only preferred embodiments, so it should be understood that they may be replaced with various equivalents and modifications at the time of the disclosure.

(13) Like reference numerals throughout the specification denote like elements. Also, this specification does not describe all the elements according to embodiments of the disclosure.

(14) It is to be understood that the singular forms are intended to include the plural forms as well, unless the context clearly dictates otherwise. It will be further understood that the terms “include”, “comprise” and/or “have” when used in this specification, specify the presence of stated features, integers, stages, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, stages, operations, elements, components, and/or groups thereof.

(15) Also, the terms including ordinal numbers like “first” and “second” may be used to explain various components, but the components are not limited by the terms and the terms are only for the purpose of distinguishing a component from another. For example, without departing from the technical spirit or essential features of the disclosure, a first element may be referred to as a second element, and also a second element may be referred to as a first element. Description shall be understood as to include any and all combinations of one or more of the associated items when the items are described by using the conjunctive term “~ and/or ~”, or the like.

(16) Also, the terms such as “part”, “device”, “block”, “member”, “module”, and the like may refer to a unit for processing at least one function or act. For example, the terms may refer to at least process processed by at least one hardware, such as field-programmable gate array (FPGA)/application specific integrated circuit (ASIC), software stored in a memory **300** or a processor **200**.

(17) Reference numerals used for method stages are just used for convenience of explanation, but not to limit an order of the stages. Thus, unless the context clearly dictates otherwise, the written order may be practiced otherwise.

(18) The disclosed embodiments may be embodied in the form of a recording medium storing instructions executable by a computer. The instructions may be stored in the form of program code and, when executed by the processor **200**, may generate a program module to perform the operations of the disclosed embodiments. The recording medium may be embodied as a computer-readable recording medium.

(19) The computer-readable recording medium includes all kinds of recording media in which instructions which may be decoded by a computer are stored, for example, in read only memory (ROM), random access memory (RAM), magnetic tapes, magnetic disks, flash memory **300**, optical recording medium, and the like.

(20) Hereinafter, embodiments of a vehicle **100** and a control method thereof according to an aspect of the disclosure will be described in detail with reference to the accompanying drawings.

(21) FIG. 1 is a control block diagram illustrating the vehicle **100** according to an embodiment.

(22) Referring to FIG. 1, the vehicle **100** includes a memory **300** that transitory or non-transitory stores usage history information required for voice recognition, a user interface **400** including an inputter **401** and an outputter **403**, a communicator **500** that performs wired/wireless communication with internal and external devices, and a processor **200** that controls the above-described constituent components.

(23) Also, the vehicle **100** may wirelessly communicate with an external server **600** by controlling the communicator **500** by the processor **200**.

(24) The memory **300** may be used to store an image around the vehicle **100** photographed by a camera provided in the vehicle **100** in units of frames. Also, the memory **300** may be used to store

wireless charger information received through the communicator **500** from an external terminal.

(25) The memory **300** may include a volatile memory **300** such as a static random access memory (S-RAM) and dynamic random access memory (D-RAM), and a non-volatile memory **300** such as a read only memory (ROM), an erasable programmable read only memory (EPROM), and the like. The memory **300** may include one memory element or a plurality of memory elements.

(26) As described with reference to FIG. **3** below, the memory **300** may include a guide prompt database (DB) **301** and a domain/command DB **302**.

(27) The user interface **400** may include the inputter **401** and the outputter **403**. The inputter **401** may receive a command related to a control of the vehicle **100** from a user and transmit the command to the processor **200**. The outputter **403** may display a voice recognition guide.

(28) The user interface **400** may include an audio video navigation (AVN) display. According to the embodiment, however, the inputter **401** receiving the command from the user and the outputter **403** displaying the voice recognition guide are not limited to the AVN display.

(29) Although the user interface **400** is not the AVN display, as long as the user may input a command through the inputter **401** and check the voice recognition guide through the outputter **403**, types of the inputter **401** and the outputter **403** are not limited.

(30) For example, the inputter **401** may be an automotive voice recognition system by including a voice inputter **402**, and the outputter **403** may be a speaker that outputs a sound inside the vehicle **100** by including a voice outputter **404**.

(31) When the user utters a command, the automotive voice recognition system may analyze the input command, determine a domain corresponding to the command, and perform an operation.

(32) Accordingly, when the inputter **401** is the automotive voice recognition system, the user may control the vehicle **100** by voice.

(33) Specifically, the voice inputter **402** may be used for an electronic system for controlling the vehicle **100**, controlling an air conditioning system of the vehicle **100** or inputting a destination in a navigation device through voice recognition.

(34) Also, the voice outputter **404** may display information indicating a state of the vehicle **100**, information for guiding a setting of the vehicle **100**, a navigation screen, multimedia content, or information related to driving.

(35) The communicator **500** may communicate with another vehicle or the external server **600** through a wireless communication base station, and include a wireless communicator **501** and a wired communicator **502**.

(36) For example, the communicator **500** may use communication methods of the second generation (2G) such as time division multiple access (TDMA), code division multiple access (CDMA), etc., communication methods of the third generation (3G) such as a wide code division multiple access (WCDMA), code division multiple access 2000 (CDMA 2000), wireless broadband (Wibro), world interoperability for microwave access (WiMAX), etc., and communication methods of the fourth generation (4G) such as long-term evolution (LTE), Wibro evolution, etc. The communicator **500** may also use the fifth generation (5G) communication method.

(37) The communicator **500** may include at least one constituent component enabling communication with an external device, for example, at least one of a short-range communication module **108**, the wired communicator **502** or the wireless communicator **501**.

(38) The short-range communication module **108** may include a variety of short-range communication modules that transmit and receive signals in a short distance using a wireless communication network, such as a Bluetooth module, infrared communication module, radio frequency identification (RFID) communication module, wireless local access network (WLAN) communication module, near-field communication (NFC) communication module, Zigbee communication module, and the like.

(39) The wired communicator **502** may include various wired communicators such as a controller area network (CAN) communication module, local area network (LAN) module, wide area network

(WAN) module, value added network (VAN) module, or the like, and also include various cable communication modules such as a universal serial bus (USB), high definition multimedia interface (HDMI), digital visual interface (DVI), recommended standard 232 (RS-232), power line communication, plain old telephone service (POTS), or the like.

(40) The wireless communicator **501** may include wireless communicators that support a variety of communication methods such as a radio data system-traffic message channel (RDS-TMC), digital multimedia broadcasting (DMB), Wifi module, Wibro module, as well as global system for mobile communication (GSM), CDMA, WCDMA, universal mobile telecommunications system (UMTS), TDMA, LTE, and the like.

(41) The wireless communicator **501** may include a wireless communication interface including a receiver and an antenna for receiving user login information. Also, the wireless communicator **501** may further include a signal conversion module for demodulating an analog wireless signal, received through the wireless communication interface, into a digital control signal.

(42) When the user login information is received from the server **600**, the communicator **500** may transmit corresponding data to the processor **200**. Also, the communicator **500** may receive a control signal that requests the user login information from the processor **200** and transmit the control signal to the server **600**.

(43) The processor **200** may receive a command from the user and automatically change a voice recognition guide mode based on a voice recognition usage history of the user by controlling the memory **300**, the user interface **400** and the communicator **50**.

(44) Specifically, the processor **200** may control the communicator **500** to transmit the user login information to the external server **600** and receive voice recognition usage history information from the server **600**. Accordingly, a voice recognition guide may be set and provided differently for each command.

(45) The voice recognition usage history information received by the processor **200** from the server **600** may include domain information x, command information y, information about a start prompt (SP), information about a prompt cancel count (PCc), information about a voice prompt count (VPc) and information about a voice prompt (VP).

(46) The processor **200** may determine how familiar the user is with each command by using variables such as the SP, the PCc, the VPc and the VP.

(47) For instance, when the user stops a voice recognition guide and attempts a voice recognition while the voice recognition guide is being performed, the processor **200** may determine that the user is familiar with the voice recognition guide for a corresponding command.

(48) When the voice recognition is successful after stopping the voice recognition guide and attempting the voice recognition and a prompt cancel count (PCc) reaches more than a reference value by increasing the PCc, the processor **200** may change the voice recognition guide mode from a 'detailed guide' to a 'simple guide' or a 'simple guide' to a 'no guide'.

(49) As described above, the 'detailed guide' may correspond to a first mode, the 'simple guide' may correspond to a second mode and the 'no guide' may correspond to a third mode, respectively.

(50) According to an embodiment, the vehicle **100** automatically changes the voice recognition guide mode by determining whether the user is familiar with a command, thereby may provide an optimal voice recognition guide by providing a minimized guide for a familiar command and providing a detailed guide for an unfamiliar command.

(51) A method of determining whether the user is familiar with each command by the processor **200** is described in detail with reference to the accompanying drawings below.

(52) FIG. 2 is a detailed control block diagram illustrating constituent components controllable by voice recognition in the vehicle **100** according to an embodiment.

(53) The constituent components illustrated in FIG. 2 may be constituent components of the vehicle **100** that may be controlled by the processor **200** through voice recognition. The processor **200** may receive a command from a user through voice recognition and control the constituent components

described below.

(54) A navigation device **101** may include a location determination part **102** for determining a location of the vehicle **100**. The location determination part **102** may measure the location of the vehicle **100**. For example, the location determination part **102** may obtain location data using a global navigation satellite system (GNSS). Here, the GNSS includes a navigation system capable of calculating a location of a receiving terminal using a radio signal received from a satellite. For example, the GNSS may include navigation systems such as global positioning system (GPS), Galileo, global orbiting navigation satellite system (GLONASS), COMPASS, Indian regional navigational satellite system (IRNSS), Quasi-Zenith satellite system (QZSS), and the like. The processor **200** may control the navigation device **101** through voice recognition, and also input, change and cancel a destination.

(55) A head unit **103** refers to a device capable of performing operations of radio reception, radio frequency setting, sound reproduction, and various control operations related thereto. For example, the head unit **103** or a radio receiving device may be installed on a center fascia provided in a center of a dashboard. The processor **200** may control the head unit **103** through voice recognition to control radio or sound reproduction.

(56) A data input/output module **109** is provided to enable the vehicle **100** to perform wired communication with an external terminal such as a smartphone or a tablet computer. The vehicle **100** is communicatively connected with an external device through at least one cable connected to the data input/output module **109** and a connector of the data input/output module **109**. For instance, the data input/output module **109** may include a USB connector, and also at least one of various interface connectors such as a HDMI connector or Thunderbolt connector. The data input/output module **109** may be installed in at least one of a center fascia, gear box or console box as per a designer's selection.

(57) Also, at least one of an external photographing part **110** or an internal photographing part **111** may be further installed inside the vehicle **100**. The external photographing part **110** photographs an image of an outside of the vehicle **100**, for example, a front of the vehicle **100**, and the internal photographing part **111** photographs an image of an inside of the vehicle **100**. At least one of the external photographing part **110** or the internal photographing part **111** may be mounted on a dashboard or a lower side of an upper frame of vehicle body. In this case, at least one of the external photographing part **110** or the internal photographing part **111** may be mounted around a rear-view mirror of the vehicle **100**.

(58) At least one of the external photographing part **110** or the internal photographing part **111** may be implemented using a camera device including a charge coupled device (CCD), a complementary metal-oxide semiconductor (CMOS), or the like. The external photographing part **110** and the internal photographing part **111** may output an image signal corresponding to the photographed image.

(59) The processor **200** may control the external photographing part **110** and the internal photographing part **111** to photograph an inside or outside of the vehicle **100** through voice recognition.

(60) The voice outputter **404** for outputting a voice may be installed inside the vehicle **100**. The voice outputter **404** may be implemented using a speaker device. For example, the speaker device may be mounted on various locations that may be considered by a designer such as a dashboard and/or rear shelf, etc. The voice outputter **404** may also include a speaker device provided in the navigation device **101**.

(61) In addition, the voice inputter **402** capable of receiving a voice uttered by at least one of the driver or a passenger may be mounted inside the vehicle **100**. The voice inputter **402** may be implemented using a microphone. The voice inputter **402** may be mounted at a location where a voice of at least one of the driver or the passenger may be properly received, for example, a location such as at least one area under the upper frame of the vehicle body.

(62) Also, an air conditioning device **104** that cools or heats air inside the vehicle **100** may be provided in an engine room or a space between the engine room and dashboard. A discharge port for discharging the air cooled or heated by the air conditioning device **104** may be provided inside the vehicle **100**. The discharge port may be mounted on a dashboard, console box, and the like.

(63) The processor **200** may control the air conditioning device **104** to adjust a temperature of the vehicle **100** through voice recognition.

(64) In addition, a display for visually providing the driver or the passenger with various information may be mounted inside the vehicle **100**. Here, the various information may include information related to the vehicle **100**.

(65) For example, the various information may include at least one of information about the vehicle **100** that a designer intends to provide, such as a speed of the vehicle **100**, engine speed, engine temperature, the remaining amount of coolant, whether an engine oil is insufficient, and/or whether various systems installed in the vehicle **100** operate normally.

(66) For example, the display may be implemented using a display mounted on the navigation device **101** or an instrument panel installed on a dashboard located in front of a steering wheel and providing various information about the vehicle **100**, and the like.

(67) The inputter **401** may receive a command from the driver or the passenger according to an operation of the driver or the passenger, and transmit a signal corresponding to the command to the processor **200**. For example, the inputter **401** may be mounted on a center fascia, steering wheel, gear box, overhead console, trim of a door **136** and/or console box, etc. The inputter **401** may also be implemented using a touch screen of the navigation device **101**.

(68) In addition, various lighting devices may be further mounted inside the vehicle **100**. The processor **200** may control a color or brightness of an internal lighting device through voice recognition.

(69) As described with reference to FIG. **1**, a module for performing wireless communication, e.g., at least one of a mobile communication module or the short-range communication module **108** may be further mounted on the vehicle **100** according to an embodiment. The processor **200** may transmit a command input by voice recognition to the server **600** through the communicator **500**.

(70) The mobile communication module is provided to transmit and receive data with another device located in a remote place, e.g., at least one of the server **600** or a terminal device. The vehicle **100** may access the World Wide Web (www) by using the mobile communication module, thereby may be provided with various external information such as news, information around the vehicle **100**, weather information, and the like.

(71) The mobile communication module may be implemented using a predetermined mobile communication technology. For example, the mobile communication module may be implemented using at least one communication technology that may be considered by a designer and based on a mobile communication standard such as the third generation partnership project (3GPP), 3GPP2, WiMAX, or the like.

(72) For example, the mobile communication standard may include the GSM, enhanced data GSM environment (EDGE), WCDMA, CDMA, TDMA, and the like.

(73) The short-range communication module **108** may be provided to wirelessly communicate with a device located in a short distance, e.g., a smartphone, tablet computer, laptop, and the like. The vehicle **100** may be paired with the device located in a short distance using the short-range communication module **108**.

(74) According to an embodiment, the short-range communication module **108** is communicatively provided using a predetermined short-range communication technology. For instance, the short-range communication module **108** may communicate with an external device using Bluetooth, Bluetooth low energy, CAN communication, Wi-Fi, Wi-Fi direct, WiMAX, ultra-wideband (UWB), Zigbee, infrared data association (IrDA), NFC, and the like.

(75) For example, the mobile communication module and the short-range communication module

108 may be embedded in the navigation device **101** or the head unit **103**, or installed on a board mounted in a space between an engine room and a dashboard. According to embodiments, at least one of the mobile communication module or the short-range communication module **108** may be manufactured as a separate device, and in this case, at least one of the mobile communication module or the short-range communication module **108** may be mounted on a terminal of the data input/output module **109** to perform communication between the vehicle **100** and an external device.

(76) Referring to FIG. 2, the vehicle **100** may include at least one sensor **190**, and the processor **200** may display a value output from the at least one sensor **190** based on user's voice recognition.

(77) For example, the sensor **190** may include at least one of a fuel sensor **121**, a coolant sensor **122**, an engine temperature sensor **123**, an engine speed sensor **124**, an engine oil sensor **125**, a system sensor **126**, a window opening sensor **127**, a door opening sensor **128**, and a tire pressure sensor **129**.

(78) The fuel sensor **121** measures a remaining fuel amount in a fuel tank **130** and outputs information about the remaining fuel amount. The coolant sensor **122** measures a remaining coolant amount in a coolant tank **131** and outputs information about the remaining coolant amount. The engine temperature sensor **123** measures a temperature of an engine **132** and outputs information about the measured temperature and the engine speed sensor **124** measures a rotation number of the engine **132** and outputs corresponding information.

(79) Also, the engine oil sensor **125** is provided to measure a remaining engine oil in an engine oil tank and output information about the remaining engine oil.

(80) The system sensor **126** is provided to detect whether various systems **140** required for an operation of the vehicle **100** are normally operated. Here, for example, the system **140** may include at least one of an anti-lock brake system (ABS) **141** for adjusting a brake hydraulic pressure, a traction control system (TCS) **142**, an anti-spin regular (ASR) **143**, a vehicle dynamic control (VDC) **144**, an electronic stability program (ESP) **145** and a vehicle stability management (VSM) **146**. In addition to the above, the system sensor **126** may detect whether various systems for controlling an operation of each constituent component related to driving of the vehicle **100** are normally operated. The system sensor **126** may be provided separately for each of the above-described systems.

(81) The window opening sensor **127** may detect whether a window **134** is open. For example, the window opening sensor **127** may be implemented using a window driving part **135** such as an encoder connected to a motor, and also implemented using various optical sensor **190** or a pressure sensor **190**.

(82) The door opening sensor **128** may detect whether the door **136** is open. The door opening sensor **128** may be implemented using the pressure sensor **190** or a switch element connected according to a closure of the door **136**.

(83) The tire pressure sensor **129** is provided to measure a pressure of a tire **137** surrounding a wheel, and for example, may be implemented using a piezoelectric sensor **190** or a capacitive sensor **190**.

(84) In addition to the above-described sensors, the vehicle **100** may further include a variety of sensors **190** for a corresponding purpose. For example, the vehicle **100** may further include a sensor **190** for measuring contamination or damage of a predetermined filter.

(85) Information, output from the above-described navigation device **101**, head unit **103**, air-conditioning device **104**, inputter **401**, mobile communication part **106**, internal interface **107** such as the short-range communication module **108** or the data input/output module **109**, external photographing part **110**, internal photographing part **111**, at least one sensor **190**, voice inputter **402**, voice outputter **404** or an instrument panel, may be an object to be controlled by the processor **200**.

(86) The processor **200** and the memory **300** are electrically connected to each other to transmit and

receive data. Also, at least one of the navigation device **101**, head unit **103**, air-conditioning device **104**, inputter **401**, mobile communication part **106**, internal interface **107** such as the short-range communication module **108** or the data input/output module **109**, external photographing part **110**, internal photographing part **111**, sensor **190**, voice inputter **402**, voice outputter **404** or instrument panel may be provided to transmit data to at least one of the processor **200** or the memory **300**, and/or receive data or a control signal from at least one of the processor **200** or the memory **300** through a wire or cable in the vehicle **100**, or through wireless communication network.

(87) FIG. **3** is a detailed control block diagram illustrating the memory **300** of the vehicle **100** according to an embodiment.

(88) Referring to FIG. **3**, the memory **300** may include the guide prompt DB **301** and the domain/command DB **302**.

(89) The DB may refer to a set of data stored under a predetermined standard, and data may be stored in each table in the DB.

(90) The DB may store related information in a single table and maintain a plurality of tables, thereby may store data systematically. For example, a domain required for voice recognition as a single attribute and a command as another attribute may be stored in one table.

(91) The guide prompt DB stores and databases guide prompt content for each voice recognition stage.

(92) In the guide prompt DB, the content of the guidance prompt may be stored in the form of a wave, which is a waveform audio format, and the fixed word may be stored in the form of text.

(93) Accordingly, the processor **200** may access the guide prompt DB and utilize the variable vocabulary and fixed vocabulary. Specifically, the processor **200** may include a text-to-voice (TTS).

(94) The TTS may refer to a technology of converting written text into human voice. The TTS may segment and store a human voice recorded in advance into a predetermined phonetic unit, and when text is input, find and combine pieces of voice that match a sentence of the text in a database.

(95) As such, the processor **200** may output the variable vocabulary and fixed vocabulary stored in the guide prompt DB as a voice using the TTS. Accordingly, the processor **200** may display a guide prompt to a user for each domain/command recognition stage.

(96) The domain/command DB is a usage history database that stores how familiar the user is with each domain/command without recognition failure, as a variable.

(97) The domain/command DB may include a command required for controlling the vehicle **100** and a domain corresponding to a control area of the command.

(98) Also, the domain/command DB may store variables such as a start prompt (SP), a PCc, a VPc, and a VP.

(99) In this instance, the SP refers to a guide when an initial voice recognition starts, the VP refers to a guide mode after the initial voice recognition, and the PCc refers to the number of times that the user stops a voice recognition guide and voice recognition is successful. Also, the VPc is a temporary variable displayed as 1 when a voice recognition fails in an expert mode among first modes.

(100) The domain/command DB may provide the above variables to the processor **200** and the processor **200** may change a voice recognition guide mode depending on the variables, which is described in detail later.

(101) FIG. **4** is a detailed control block diagram illustrating a processor of a vehicle according to an embodiment.

(102) Referring to FIG. **4**, the processor **200** may determine a wake-up through push-to-talk (PTT) as a voice recognition start signal **210**.

(103) When the voice recognition start signal **210** is received, the processor **200** may change a microphone of the inputter **401** to an input-enabled state. Afterwards, when a user inputs a command through the microphone of the inputter **401**, the command may be analyzed through a

voice processing part **220**.

(104) The voice processing part **220** may divide and extract the input command into a domain and a command.

(105) Specifically, with respect to a method of analyzing a voice, when the user utters the user's voice, the uttered voice is input through the inputter **401**. The inputter **401** may output an electrical signal corresponding to the uttered voice and the output electrical signal may be transmitted to the processor **200**.

(106) The voice processing part **220** of the processor **200** may perform voice recognition based on the received electrical signal. Specifically, the processor **200** may first detect a voice section from the received electrical signal. Here, the voice section refers to a section where a voice uttered by the user exists or is highly likely to exist.

(107) When the voice section is detected, the processor **200** may remove and/or alleviate noise existing in the voice section. The processor **200** may use at least one filter for removing the noise in the voice section. A process for noise removal may be omitted depending on embodiments.

(108) Afterwards, the processor **200** may extract a voice characteristic from the voice section. In this instance, the processor **200** may extract the voice characteristic from the voice section in a feature vector form, using at least one of a linear prediction coefficient (LPC), Cepstrum, Mel frequency cepstral coefficient (MFCC), or filter bank energy.

(109) In response to the voice characteristic extraction, the processor **200** may determine a pattern corresponding to the extracted voice characteristic. For example, the processor **200** may determine the pattern for the voice characteristic using a predetermined acoustic model previously defined.

(110) The acoustic model may be obtained by modeling a signal characteristic of voice. The processor **200** may determine the pattern for the voice characteristic by acquiring a frequency pattern having a similar or the same frequency pattern to that of human voice using the above-described acoustic model. Accordingly, a vocabulary such as a predetermined word, syllable, or short phrase may be recognized from the voice input through the inputter **401**.

(111) The processor **200** may recognize a sentence, or the like, by performing language processing by further using a predetermined language model, when required. The language model may be generated based on human languages, grammars, etc., in order to determine a linguistic order of recognized words, syllables, or phrases. Accordingly, the processor **200** may recognize the sentence corresponding to the voice.

(112) The processor **200** may obtain a result of voice recognition through at least one of the pattern determination or language processing, and determine an operation requested or commanded by the user through user's voice according to the voice recognition result.

(113) The voice processing part **220** of the processor **200** may determine whether the user is familiar with voice recognition for a specific command. Specifically, the voice processing part **220** may determine that the user is familiar with voice recognition for a specific command, when the user utters the command before a voice recognition guide ends and the voice recognition is successful.

(114) That is, because the voice recognition is successfully performed without listening to the voice recognition guide to the end, it may be determined that the user is familiar with voice recognition for the corresponding command.

(115) When the voice recognition is successful and it is determined that the user is familiar with voice recognition for the corresponding command, as described above, the processor **200** may increase a PCc by 1.

(116) The processor **200** may not change a voice recognition guide mode until the PCc is increased to 3, which is a predetermined reference value, in order to secure a reliability of a familiarity level of the user for the command.

(117) Afterwards, when the PCc becomes 3, the processor **200** may determine that the user is familiar with the corresponding command, and increase a VP value by 1.

(118) The processor **200** may determine as a 'detailed guide' when a current VP value is 1, a 'simple guide' when the current VP value is 2, and a 'no guide' when the current VP value is 3, and proceed a guide prompt corresponding thereto.

(119) That is, when it is determined that user is familiar with the corresponding command and the VP value is increased by 1, the processor **200** may guide by changing the 'detailed guide' to the 'simple guide' or the 'simple guide' to the 'no guide'.

(120) In this instance, the processor **200** may divide the voice recognition guide mode into a first mode and a second mode according to a degree of detail of the voice recognition guide. The first and second modes may include the 'detailed guide', 'simple guide', and 'no guide'.

(121) Also, in the degree of detail of the voice recognition guide, guiding all commands required for voice recognition to the user may be defined as being the most detailed, and displaying only a beep sound without guiding the command may be defined as being the least detailed.

(122) Accordingly, for instance, in a domain of 'call', 'say your name' may be the 'detailed guide', 'name' may be the 'simple guide', and outputting only beep sound without any guide may correspond to 'no guide'.

(123) In this instance, when the detailed guide is the second mode, the simple guide may be the first mode, and when the simple guide is the second mode, the 'no guide' may be the first mode, and also a degree of guide is not limited.

(124) The processor **200** may determine that voice recognition fails when a command is not input for more than 4 seconds after the user starts using voice recognition for a specific command.

(125) Also, when a command is not input for more than 2 seconds after the user utters a single sound following a start of voice recognition for a specific command, the processor **200** may determine that voice recognition fails, because the user hesitated due to unfamiliarity with the specific command.

(126) When it is determined that the voice recognition fails as described above, the processor **200** may decrease the VP value of the corresponding command by 1.

(127) That is, when it is determined that the voice recognition fails and the VP value is decreased by 1, the processor **200** may guide by changing the 'simple guide' to 'detailed guide' or the 'no guide' to the 'simple guide'.

(128) As such, through the determination on the user's familiarity with the command, when it is determined that the user is familiar with the command, the processor **200** may minimize the guide, and when it is determined that the user is not familiar with the command, the processor **200** may provide detailed guide. Accordingly, a convenience of user who uses voice recognition may be improved.

(129) A guide prompt controller **230** of the processor **200** may display a voice recognition guide mode changed according to the changed VP value.

(130) For example, when the VP value is 1, that is, in the 'detailed guide', input methods of all commands required for voice recognition may be guided.

(131) Specifically, in the domain of 'call', all of 'say a command', 'say your name' and 'which number to call' may be guided.

(132) When the VP value is 2, i.e., in the 'simple guide', input methods of minimum commands required for voice recognition may be guided.

(133) Specifically, in the domain of 'call', only 'command', 'name' and 'representative number' may be controlled to be simply guided.

(134) When the VP value is 0, i.e., in the 'no guide', the guide as to the input methods required for voice recognition may be omitted.

(135) Specifically, in the domain of 'call', the processor **200** may control so that only a beep sound is output without a guide and a call connection to a desired number is made.

(136) The processor **200** does not physically include the voice processing part **220** and the guide prompt controller **230**, and the voice processing part **220** and the guide prompt controller **230** may

be the names given to functions of a controller for convenience of description.

(137) FIG. 5 illustrates examples of each variable in a vehicle according to an embodiment.

(138) Referring to FIG. 5, each command may have a PCc, a VP, and a VPc for each domain.

(139) The VP corresponds to a guide mode. VP values (command 1:2, command 2:3, command 3:3) of frequently used and familiar call domain commands are mostly greater than VP values (command 1:1, command 2:1, command 3:3) of vehicle setting domain commands which are not used frequently and familiar.

(140) Specifically, with respect to the call domain commands, because a command of “call” has a VP value of 2, ‘simple guide’ may be provided. For example, guidance may be made with a simple word of “command”.

(141) Also, because a command of “call by name” is an expert mode that a user is very familiar with, guidance may be omitted. That is, when voice recognition with “call” is successful according to the guide of “command”, the user may input “call by name” immediately after a beep sound, without a guide of “what item to make a call?”.

(142) FIG. 6 is a diagram illustrating a difference between when the disclosure is applied to the vehicle **100** according to an embodiment and when the disclosure is not applied to the vehicle **100** according to an embodiment.

(143) As described with reference to FIG. 5, the processor **200** may minimize a guide as to a command determined as being familiar to a user.

(144) Accordingly, conventionally, guidance may be completed through the voice signal start signal **210** (stage 1), “say a command” (stage 2), a beep sound (stage 3), “call” (stage 4), “say a name” (stage 5), a beep sound (stage 6), “call Hong Gil-Dong” (stage 7), “which number to call?” (stage 8), a beep sound (stage 9), and “an office” (stage 10).

(145) However, even when a user frequently uses a corresponding command and is familiar with the command, providing all the guides may increase a response time, causing inconvenience to the user, distracting while driving and causing an accident.

(146) Therefore, according to an embodiment, when it is determined that all commands of call domain are familiar to the user, the vehicle **100** may complete the guide through the voice signal start signal (stage 1), a beep sound (stage 2), “call” (stage 3), a beep sound (stage 4), “call Hong Gil-Dong” (stage 5), a beep sound (stage 6) and “an office” (stage 7).

(147) That is, unnecessary guide processes may be reduced based on a user's command usage history, thereby may shorten a response time and improve user's convenience.

(148) FIGS. 7 and 8 are flowcharts illustrating operations of updating a PCc in the vehicle **100** according to an embodiment.

(149) Referring to FIGS. 7 and 8 together, the processor **200** may update a PCc in an initial state where a user starts using voice recognition.

(150) When the voice recognition start signal **210** is received (**700**), the processor **200** may start a start prompt (SP) that provides a guide to receive a first command from the user (**710**). The SP is not limited, as long as it is a means to induce the user to input a command, such as “say a command”.

(151) The processor **200** may determine whether the user utters a command even though a voice recognition guide is not finished, i.e., when a guide is cancelled while providing the SP (**720**). Afterwards, the processor **200** may determine that the user is familiar with the corresponding command when voice recognition is successful (**721**).

(152) That is, because the voice recognition is successful for the corresponding command without listening to the voice recognition guide for the command to the end, it may be determined that the user accurately recognizes a command to be required to be input and is familiar with the command.

(153) When it is determined that the voice recognition is successful and the user is familiar with the command (Yes in operation **730**), the processor **200** may increase the PCc by 1 (**740**).

(154) Afterwards, the processor **200** may determine whether a VPc value is 1 (**750**).

(155) The processor **200** may determine whether the PCc is 3 which is a predetermined reference value (**760**), in order to secure a reliability of a familiarity level of the user for the command. The processor **200** may not change a voice recognition guide mode until the PCc is increased to 3 (No in operation **760**).

(156) When the VPc value is 1 (Yes in operation **750**), the processor **200** may determine that the recognition of the command fails in an expert mode where command usage is familiar for the user, set the VPc value as 0 (**770**), and change to a first mode by decreasing a VP value by 1 to reduce a degree of detail of guide (**780**).

(157) That is, when the recognition of the command fails in the expert mode, which indicates that the user temporarily forgets the command despite the user's familiarity with the corresponding command, the processor **200** may change to the first mode by decreasing the VP value by 1 without accumulation of PCc, in order to reduce the degree of detail of guide.

(158) Afterwards, the processor **200** may store the changed PCc in a domain/command DB (**790**), and when a same command is used later, may guide by reflecting a usage history.

(159) The processor **200** may guide a domain/command in the changed voice recognition guide mode (**800**).

(160) When the user listens to the voice recognition guide to the end, which indicates that the user is not familiar with the command, the processor **200** may confirm whether the user utters a voice command without changing the PCc (**810**).

(161) FIG. **9** is a flowchart illustrating operations of updating a VPc and a VP in the vehicle **100** according to an embodiment.

(162) Referring to FIG. **9**, the processor **200** may confirm whether a voice command is uttered (**900**). When the voice command is uttered (Yes in operation **900**), the processor **200** may determine whether voice recognition is successful (**930**). When it is determined that the voice recognition is successful (Yes in operation **930**), the processor **200** may display a guide corresponding to a domain and command (**960**).

(163) When a user has not uttered the voice command (No in operation **900**) or it is determined that the voice recognition fails due to utterance of another command (No in operation **930**), the processor **200** may determine whether a VPc value is 1 (**910**).

(164) When the VPc value is 1 (Yes in operation **910**), the processor **200** may determine that the voice recognition fails in an expert mode where the user is very familiar with a command.

(165) That is, when the VPc value is 1, which indicates that the voice recognition fails in the expert mode, the processor **200** may change the VPc value to 0 (**940**).

(166) When the VPc value is not 1 (No in operation **910**), the processor **200** may confirm whether a current guide mode is the expert mode (**920**), and when the current guide mode is the expert mode (Yes in operation **920**), the processor **200** may change the VPc value to 1 and determine that the user temporarily forgets the command in the expert mode (**950**).

(167) Afterwards, because the voice recognition fails, the processor **200** may decrease a VP value by 1 to increase a degree of detail of voice recognition guide (**970**).

(168) Next, the processor **200** may store the changed PCc in a domain/command DB (**980**).

(169) FIGS. **10** and **11** are flowcharts illustrating operations of updating a PCc, a VPc, and a VP in the vehicle **100** according to an embodiment.

(170) Referring to FIGS. **10** and **11** together, the processor **200** may update a PCc, a VPc, and a VP after an initial state following a start of voice recognition.

(171) The processor **200** may determine whether a user utters a command even though a voice recognition guide is not finished, that is, when a guide is cancelled during a domain/command guide (**1000**). Afterwards, the processor **200** may determine that the user is familiar with the corresponding command when voice recognition is successful (**1010**).

(172) That is, because the voice recognition is successful without listening to the voice recognition guide to the end, which indicates that the user accurately recognizes a command to be required to

be input, and thus it may be determined that the user is familiar with the corresponding command. (173) When it is determined that the voice recognition is successful and the user is familiar with the corresponding command as described above (Yes in operation **1010**), the processor **200** may increase the PCc by 1 (**1020**).

(174) Next, the processor **200** may determine whether a VPc value is 1 (**1030**).

(175) The processor **200** may determine whether the PCc is 3 which is a predetermined reference value (**1040**), in order to secure a reliability of a familiarity level of the user for the command. The processor **200** may not change a voice recognition guide mode until the PCc is increased to 3 (No in operation **1040**).

(176) When the VPc value is 1 (Yes in operation **1030**), the processor **200** may determine that the recognition of the command fails in an expert mode where command usage is familiar for the user, set the VPc value as 0 (**1050**), and change to a first mode by decreasing a VP value by 1 to reduce a degree of detail of guide (**1060**).

(177) That is, when the recognition of the command fails in the expert mode, which indicates that the user temporarily forgets the command despite the user's familiarity with the corresponding command, the processor **200** may change to the first mode by decreasing the VP value by 1 without accumulation of PCc, in order to reduce the degree of detail of guide.

(178) Afterwards, the processor **200** may store the changed PCc in the domain/command DB (**1070**), and when a same command is used later, may guide by reflecting a usage history.

(179) The processor **200** may guide a domain/command in the changed voice recognition guide mode (**1080**).

(180) When the user listens to the voice recognition guide to the end, which indicates that the user is not familiar with the command, the processor **200** may confirm whether the user utters a voice command without changing the PCc (**1090**).

(181) Afterwards, the processor **200** may determine whether the voice command is uttered (**1100**). When the voice command is uttered (Yes in operation **1100**), the processor **200** may determine whether voice recognition is successful (**1110**). When it is determined that the voice recognition is successful (Yes in operation **1110**), the processor **200** may display a guide corresponding to a domain and command (**1170**).

(182) When the user has not uttered the voice command (No in operation **1100**) or it is determined that the voice recognition fails due to utterance of another command (No in operation **1110**), the processor **200** may determine whether a VPc value is 1 (**1120**).

(183) When the VPc value is 1 (Yes in operation **1120**), the processor **200** may determine that the voice recognition fails in the expert mode where the user is very familiar with a command.

(184) That is, when the VPc value is 1, which indicates that the voice recognition fails in the expert mode, the processor **200** may change the VPc value to 0 (**1130**).

(185) When the VPc value is not 1 (No in operation **1120**), the processor **200** may change the VPc value to 1 and determine that the user temporarily forgets the command in the expert mode (**1140**).

(186) Afterwards, because the voice recognition fails, the processor **200** may set the VP value by 1 to increase the degree of detail of voice recognition guide (**1150**).

(187) Next, the processor **200** may store the changed PCc in the domain/command DB (**1160**).

(188) FIG. **12** is a flowchart illustrating operations of updating a VPc in the vehicle **100** according to an embodiment, when the vehicle has not been used for a long time.

(189) Referring to FIG. **12**, the processor **200** may control the communicator **500** to transmit user login information to the server **600** in order to recognize a user with a user account (**1200**).

Afterwards, the processor **200** may transmit information about voice recognition usage history of the user corresponding to the user login information from the server **600**.

(190) The processor **200** may determine whether 30 days have elapsed since the logged-in user got off the vehicle **100** (**1210**). When 30 days have elapsed (Yes in operation **1210**), the processor **200** may set all VPc values to 1 (**1220**).

(191) When the user has not used the vehicle **100** for more than 30 days, because the user may temporarily forget how to use voice recognition, the processor **200** may set VPc values of all domains/commands to 1. Afterwards, when the user stops a voice recognition guide and the voice recognition is successful with respect to a command, the processor **200** may change to a first mode by decreasing a VP value by 1 without accumulation of the PCc to reduce a degree of detail of guide.

(192) Referring back to FIG. **1**, the processor **200** may receive an input for user login information through the inputter **401** and transmit the user login information to the server **600**. The server **600** may transmit information about voice recognition usage history of the logged-in user to the vehicle **100**.

(193) In the vehicle **100** according to an embodiment, the processor **200** may manage all databases for each user, and because each user has a different familiarity level with each command, values of all variables may vary for each user.

(194) The processor **200** may manage the database for each user and determine a familiarity level for each command based on a usage history. Accordingly, the processor **200** may improve a usability of voice recognition by reducing a guide prompt for a familiar command and providing a detailed guide prompt for a command used for the first time or a command not frequently used.

(195) Detailed embodiments of a control method of the vehicle **100** are the same as those of the vehicle **100** described above, a description thereof is omitted.

(196) As is apparent from the above, according to the embodiments of the disclosure, the vehicle and the control method thereof can determine how familiar a user of the vehicle is with each command, set a simple guide prompt for a familiar command and set a detailed guide prompt for a unfamiliar command, thereby may improve a usability of voice recognition.

(197) Although embodiments have been described for illustrative purposes, those skilled in the art will appreciate that various modifications, additions and substitutions are possible, without departing from the scope and spirit of the disclosure. Therefore, embodiments have not been described for limiting purposes.

Claims

1. A voice recognition apparatus for use in a vehicle, comprising: a user interface configured to receive a command from a user; a memory storage configured to store data, the data comprising a voice recognition usage history of the user; and a processor configured to automatically change a voice recognition guide mode, the voice recognition guide mode being chosen from a plurality of voice recognition guide modes according to a degree of detail of a voice recognition guide based on the voice recognition usage history, wherein the plurality of modes include a first mode and a second mode, and if the first mode is changed to the second mode, the degree of detail of the voice recognition guide is increased, and wherein the processor is further configured to change the voice recognition guide mode from the first mode to the second mode if the user does not use the vehicle for a time period greater than a reference number of days.
2. The voice recognition apparatus of claim 1, wherein the processor is configured to change the voice recognition guide mode from the second mode to the first mode if: a number of successful voice recognition commands of the user is accumulated more than a reference number of times for the same command.
3. The voice recognition apparatus of claim 1, wherein the processor is configured to change the voice recognition guide mode to the second mode if the voice recognition guide mode is in the first mode and a voice recognition fails.
4. The voice recognition apparatus of claim 3, wherein the processor is configured to determine that the voice recognition fails if the user does not utter a command for a period of time greater than a reference period of time or the user inputs a command of another domain.

5. The voice recognition apparatus of claim 3, wherein the processor is configured to determine that the voice recognition fails if the user utters a single sound, and thereafter the command is input after a reference period of time.
 6. The voice recognition apparatus of claim 1, wherein, if the first mode is changed to the second mode due to a failure of a voice recognition, and thereafter the voice recognition is successful by the user inputting a same command before the voice recognition guide ends, the processor is further configured to change the voice recognition guide mode to the first mode.
 7. The voice recognition apparatus of claim 1, wherein, if the voice recognition guide mode is changed from the first mode to the second mode, and then a voice recognition is successful by the user inputting a same command before the voice recognition guide ends, the processor is configured to change the voice recognition guide mode to the first mode.
 8. The voice recognition apparatus of claim 1, further comprising the vehicle.
 9. A control method of a voice recognition apparatus for use in a vehicle, the control method comprising: receiving a command from a user; storing data about a voice recognition usage history of the user; and automatically changing a voice recognition guide mode chosen from a plurality of voice recognition guide modes according to a degree of detail of a voice recognition guide based on the voice recognition usage history, wherein the plurality of modes include a first mode and a second mode, and if the first mode is changed to the second mode, the degree of detail of the voice recognition guide is increased, and wherein the changing of the voice recognition guide mode changes the voice recognition guide mode from the first mode to the second mode if the user does not use the vehicle for a time period greater than a reference number of days.
 10. The control method of claim 9, wherein the changing of the voice recognition guide mode step changes the voice recognition guide mode from the second mode to the first mode if: a number of successful voice recognition commands of the user is accumulated more than a reference number of times for the same command.
 11. The control method of claim 9, wherein the changing of the voice recognition guide mode step changes the voice recognition guide mode to the second mode if the voice recognition guide mode is in the first mode and a voice recognition fails.
 12. The control method of claim 11, wherein the changing of the voice recognition guide mode step determines that the voice recognition fails if the user does not utter a command for a period of time greater than a reference period of time or the user inputs a command of another domain.
 13. The control method claim 11, wherein the changing of the voice recognition guide mode determines that the voice recognition fails if the user utters a single sound, and thereafter the command is input after a reference period of time.
 14. The control method of claim 9, wherein, if the first mode is changed to the second mode due to a failure of a voice recognition, and thereafter the voice recognition is successful by the user inputting a same command before the voice recognition guide ends, the changing of the voice recognition guide mode step changes the voice recognition guide mode to the first mode.
 15. The control method of claim 9, wherein, i the voice recognition guide mode is changed from the first mode to the second mode, and then a voice recognition is successful by the user inputting a same command before the voice recognition guide ends, the changing of the voice recognition guide mode changes the voice recognition guide mode to the first mode.
-