

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12413050
B2
September 09, 2025
Shi; Zhimin et al.

Multi-color visible light source including integrated VCSELs and integrated photonic cavities

Abstract

A visible light source includes a substrate, a vertical-cavity surface-emitting laser including an active semiconductor region configured to emit infrared light and a first reflector configured to reflect the infrared light emitted by the active semiconductor region, a second reflector configured to reflect the infrared light and form a vertical cavity for the infrared light with the first reflector, and one or more micro-resonators configured to receive the infrared light and generate visible light in one or more colors using the infrared light through optical parametric oscillation. The visible light source also includes one or more output couplers configured to couple the visible light in one or more colors from the one or more micro-resonators into free space or into a photonic integrated circuit.

Inventors: Shi; Zhimin (Bellevue, WA), Scheller; Maik Andre (Redmond, WA), Valentine; Gareth (Kirkland, WA), Bonar; James Ronald (Redmond, WA)

Applicant: Meta Platforms Technologies, LLC (Menlo Park, CA)

Family ID: 83694510

Assignee: Meta Platforms Technologies, LLC (Menlo Park, CA)

Appl. No.: 17/344744

Filed: June 10, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220345220 A1	Oct. 27, 2022

Related U.S. Application Data

us-provisional-application US 63179913 20210426

Publication Classification

Int. Cl.: H01S5/42 (20060101); G02F1/35 (20060101); G02F1/39 (20060101); H01S3/108 (20060101); H01S5/00 (20060101); H01S5/026 (20060101); H01S5/04 (20060101); H01S5/11 (20210101); H01S5/14 (20060101); H01S5/183 (20060101); H01S5/50 (20060101); H04B10/116 (20130101)

U.S. Cl.:

CPC H01S5/423 (20130101); G02F1/3536 (20130101); G02F1/39 (20130101); H01S3/1083 (20130101); H01S5/0064 (20130101); H01S5/0261 (20130101); H01S5/041 (20130101); H01S5/11 (20210101); H01S5/141 (20130101); H01S5/142 (20130101); H01S5/18355 (20130101); H01S5/18377 (20130101); H01S5/5054 (20130101); H04B10/116 (20130101);

Field of Classification Search

CPC: H01S (5/423); H01S (3/1083); H01S (5/0261); H01S (5/041); H01S (5/11); H01S (5/141); H01S (5/142); H01S (5/18355); H01S (5/18377); H01S (5/5054); G02F (1/3536); G02F (1/39); H04B (10/116); G02B (2027/0178)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9991669	12/2017	Hirose et al.	N/A	N/A
11749964	12/2022	Scheller et al.	N/A	N/A
12126140	12/2023	Aoki et al.	N/A	N/A
2006/0078027	12/2005	Kim	N/A	N/A
2011/0148328	12/2010	Joseph et al.	N/A	N/A
2011/0158278	12/2010	Koch	N/A	N/A
2019/0371777	12/2018	Iguchi	N/A	H01L 24/29
2021/0080804	12/2020	Liscidini	N/A	G02F 1/39
2021/0408761	12/2020	Scheller et al.	N/A	N/A
2022/0344905	12/2021	Halbritter et al.	N/A	N/A
2022/0344907	12/2021	Shi et al.	N/A	N/A
2023/0198224	12/2022	Kurosaka et al.	N/A	N/A
2024/0045305	12/2023	Antognini et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101849334	12/2009	CN	H01S 5/065

OTHER PUBLICATIONS

Machine translation of CN101849334A (Year: 2010). cited by examiner
International Search Report and Written Opinion for International Application No. PCT/US2022/026078, mailed Jul. 29, 2022, 13 pages. cited by applicant
International Search Report and Written Opinion for International Application No. PCT/US2022/026236, mailed Jul. 28, 2022, 12 pages. cited by applicant

Lu X., et al., “Milliwatt-Threshold Visible-Telecom Optical Parametric Oscillation using Silicon Nanophotonics,” *Optica*, vol. 6, No. 12, Dec. 2019, pp. 1535-1541. cited by applicant

Lu X., et al., “On-Chip Optical Parametric Oscillation into the Visible: Generating Red, Orange, Yellow, and Green from a Near-Infrared Pump,” *Optica*, vol. 7, No. 10, Oct. 20, 2020, pp. 1417-1425. cited by applicant

Stern B., et al., “Battery-Operated Integrated Frequency Comb Generator,” *Nature*, vol. 562, No. 7727, Oct. 8, 2018, pp. 401-405. cited by applicant

Stothard D.J.M., et al., “Relaxation-Oscillation-Free Continuous-Wave Optical Parametric Oscillator Pumped Internal to a Semiconductor Disk Laser,” *Lasers and Electro-Optics, 2009 and 2009 Conference on Quantum Electronics and Laser Science Conference*, Jun. 2, 2009, 2 pages. cited by applicant

Final Office Action mailed Aug. 2, 2024 for U.S. Appl. No. 17/344,738, filed Jun. 10, 2021, 13 pages. cited by applicant

Non-Final Office Action mailed Mar. 20, 2024 for U.S. Appl. No. 17/344,738, filed Jun. 10, 2021, 13 pages. cited by applicant

Notice of Allowance mailed Nov. 14, 2024 for U.S. Appl. No. 17/344,738, filed Jun. 10, 2021, 9 pages. cited by applicant

Notice of Allowance mailed Feb. 18, 2025 for U.S. Appl. No. 17/344,738, filed Jun. 10, 2021, 10 pages. cited by applicant

Primary Examiner: Zhang; Yuanda

Attorney, Agent or Firm: Greenberg Traurig, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This patent application claims benefit of and priority to U.S. Provisional Patent Application Ser. No. 63/179,913, filed Apr. 26, 2021, entitled “VISIBLE LIGHT SOURCE INCLUDING INTEGRATED VCSELS AND INTEGRATED PHOTONIC CAVITIES,” the disclosure of which is hereby incorporated by reference in its entirety for all purposes. The following two U.S. patent applications (including this one) are being filed concurrently, and the entire disclosure of the other application is incorporated by reference into this application for all purposes: U.S. patent application Ser. No. 17/344,738, filed Jun. 10, 2021, entitled “VISIBLE LIGHT SOURCE INCLUDING INTEGRATED VCSELS AND INTEGRATED PHOTONIC CAVITIES”; and U.S. patent application Ser. No. 17/344,744, filed Jun. 10, 2021, entitled “MULTI-COLOR VISIBLE LIGHT SOURCE INCLUDING INTEGRATED VCSELS AND INTEGRATED PHOTONIC CAVITIES.”

BACKGROUND

(1) Semiconductor light-emitting devices, such as light-emitting diodes (LEDs), micro-LEDs, resonant cavity LEDs (RCLEDs), vertical-cavity surface-emitting lasers (VCSELS), and vertical external cavity surface emitting lasers (VECSELS), convert electrical energy into optical energy, and offer many benefits over other light sources, such as reduced size, improved durability, and increased efficiency and brightness. Semiconductor light-emitting devices can be used as light sources in many display systems, such as televisions, computer monitors, laptop computers, tablets, smartphones, projection systems, and wearable electronic devices. For example, micro-LEDs or VCSELS that emit light of different colors (e.g., red, green, and blue) can be used to form the sub-pixels of a display panel in a display system, such as a near-eye display system. Micro-LEDs, VCSELS, and other semiconductor light-emitting devices can also be deployed in various sensor

systems, such as systems for depth sensing, three-dimensional sensing, object tracking (e.g., hand tracking or face tracking), and the like.

SUMMARY

(2) This disclosure relates generally to visible light sources. More specifically, and without limitation, this disclosure relates to integrated vertical-cavity surface-emitting lasers (VCSELs) pumped visible light sources including optical resonators configured to generate visible light through optical parametric oscillation (OPO). Visible light sources disclosed herein may be used in, for example, backlight unit (BLU) displays and active display panels. Various inventive embodiments are described herein, including devices, components, systems, methods, structures, materials, processes, and the like.

(3) According to certain embodiments, a visible light source may include a substrate; a first reflector and a second reflector on the substrate, where the first reflector and the second reflector are configured to reflect infrared light and are arranged vertically to form a vertical cavity; an active region in the vertical cavity and configured to emit infrared light; a micro-resonator on the substrate and configured to receive the infrared light emitted by the active region and generate visible light through optical parametric oscillation; and an output coupler configured to couple the visible light generated in the micro-resonator out of the micro-resonator.

(4) According to certain embodiments, a visible light source array may include a CMOS backplane including drive circuits formed thereon, and an array of visible light sources formed on a substrate and bonded to the CMOS backplane directly or indirectly. Each visible light source in the array of visible light sources is individually addressable by the drive circuits and comprises: a first reflector and a second reflector configured to reflect infrared light and form a vertical cavity; an active region in the vertical cavity and configured to emit infrared light; a micro-resonator configured to receive the infrared light emitted by the active region and generate visible light through optical parametric oscillation; and an output coupler configured to couple the visible light generated in the micro-resonator out of the micro-resonator.

(5) According to certain embodiments, a visible light source may include a substrate; a vertical-cavity surface-emitting laser on the substrate and comprising an active semiconductor region configured to emit infrared light and a first reflector configured to reflect the infrared light emitted by the active semiconductor region; a second reflector configured to reflect the infrared light, the first reflector and the second reflector forming a vertical cavity for the infrared light; one or more micro-resonators on the substrate and configured to receive the infrared light and generate visible light in one or more colors using the infrared light through optical parametric oscillation; and one or more output couplers configured to couple the visible light in one or more colors from the one or more micro-resonators into free space or into a photonic integrated circuit.

(6) According to certain embodiments, a visible light source array may include a substrate including drive circuits formed thereon; and a die or a wafer bonded to the drive circuits directly or indirectly. The die or wafer may include an array of visible light sources formed thereon. Each visible light source in the array of visible light sources is individually addressable by the drive circuits and comprises: a vertical cavity formed by a first reflector and a second reflector, the first reflector and the second reflector configured to reflect infrared light; an active region in the vertical cavity and configured to emit infrared light; one or more micro-resonators configured to receive the infrared light and generate visible light in one or more colors using the infrared light through optical parametric oscillation; and one or more output couplers configured to couple the visible light in one or more colors from the one or more micro-resonators into free space or one or more waveguides.

(7) According to certain embodiments, a visible light source array may include a substrate including drive circuits formed thereon, and a die or a wafer bonded to the drive circuits directly or indirectly. The die or wafer may include an array of visible light sources formed thereon. Each visible light source in the array of visible light sources is individually addressable by the drive

circuits and comprises: a vertical cavity formed by a first reflector and a second reflector, the first reflector and the second reflector configured to reflect infrared light; an active region in the vertical cavity and configured to emit infrared light; a micro-resonator configured to receive the infrared light and generate visible light using the infrared light through optical parametric oscillation; and an output couplers configured to couple the visible light in from the micro-resonator into free space or a waveguide. A first micro-resonator in a first visible light source of the visible light source array and a second micro-resonator in a second visible light source of the visible light source array may have different sizes, different shapes, different materials, or a combination thereof, and are configured to generate visible light of different colors.

(8) This summary is neither intended to identify key or essential features of the claimed subject matter, nor is it intended to be used in isolation to determine the scope of the claimed subject matter. The subject matter should be understood by reference to appropriate portions of the entire specification of this disclosure, any or all drawings, and each claim. The foregoing, together with other features and examples, will be described in more detail below in the following specification, claims, and accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Illustrative embodiments are described in detail below with reference to the following figures.

(2) FIG. 1 is a simplified block diagram of an example of an artificial reality system environment including a near-eye display according to certain embodiments.

(3) FIG. 2 is a perspective view of an example of a near-eye display in the form of a head-mounted display (HMD) device for implementing some of the examples disclosed herein.

(4) FIG. 3 is a perspective view of an example of a near-eye display in the form of a pair of glasses for implementing some of the examples disclosed herein.

(5) FIG. 4 illustrates an example of an optical see-through augmented reality system including a waveguide display according to certain embodiments.

(6) FIG. 5A illustrates an example of a near-eye display device including a waveguide display according to certain embodiments. FIG. 5B illustrates an example of a near-eye display device including a waveguide display according to certain embodiments.

(7) FIG. 6 illustrates an example of an image source assembly in an augmented reality system according to certain embodiments.

(8) FIG. 7A illustrates an example of a vertical-cavity surface-emitting laser (VCSEL).

(9) FIG. 7B illustrates an example of a tunable VCSEL according to certain embodiments.

(10) FIGS. 8A and 8B illustrate an example of generating a higher frequency light signal using lower frequency pump light through degenerate four-wave mixing. FIG. 8C illustrates multiple longitudinal resonant modes of an example of a micro-resonator.

(11) FIG. 9A shows a cross-sectional view of an example of a coupling structure configured to vertically couple light generated in an optical resonator out of the optical resonator according to certain embodiments. FIG. 9B shows a top view of the example of the coupling structure of FIG. 9A according to certain embodiments. FIG. 9C illustrates a top view of an example of a structure configured to couple light generated in an optical resonator into an output waveguide according to certain embodiments. FIG. 9D illustrates a top view of another example of a structure configured to couple light generated in an optical resonator into an output waveguide according to certain embodiments.

(12) FIGS. 10A and 10B illustrate an example of a visible light source including a micro-resonator in a vertical cavity and directly pumped by an infrared light VCSEL in the vertical cavity according to certain embodiments, where visible light generated in the micro-resonator is vertically coupled

out of the vertical cavity.

(13) FIG. 11A illustrates an example of a visible light source including a micro-resonator outside of a vertical cavity and directly pumped by an infrared light VCSEL according to certain embodiments. FIG. 11B illustrates a top view of the example of visible light source of FIG. 11A.

(14) FIGS. 12A and 12B illustrate an example of a visible light source including a micro-resonator pumped by an infrared light VCSEL according to certain embodiments, where the infrared light is coupled into the micro-resonator through an input coupling structure and a waveguide on a same layer as the micro-resonator.

(15) FIGS. 12C and 12D illustrate an example of a visible light source including a micro-resonator pumped by an infrared light VCSEL according to certain embodiments, where the infrared light is coupled into the micro-resonator through an input coupling structure and a waveguide on a different vertical layer from the micro-resonator.

(16) FIG. 13A illustrates an example of a visible light source including a micro-resonator pumped by an infrared light VCSEL in a vertical cavity according to certain embodiments, where the infrared light is coupled into the micro-resonator through an input coupling structure in the vertical cavity and a waveguide on a same vertical layer as the micro-resonator. FIG. 13B illustrates a top view of the example of the visible light source of FIG. 13A.

(17) FIG. 13C illustrates an example of a visible light source including a micro-resonator pumped by an infrared light VCSEL in a vertical cavity according to certain embodiments, where the infrared light is coupled into the micro-resonator through an input coupling structure in the vertical cavity and a waveguide on a different vertical layer as the micro-resonator. FIG. 13D illustrates a top view of the example of the visible light source of FIG. 13C.

(18) FIG. 14A illustrates an example of an array of visible light sources configured to emit visible light of different colors according to certain embodiments, where each visible light source in the array includes a micro-resonator in a vertical cavity and directly pumped by an infrared light VCSEL in the vertical cavity, and the visible light generated in the micro-resonator is vertically coupled out of the vertical cavity. FIGS. 14B and 14C illustrate top views of examples of the array of visible light sources of FIG. 14A.

(19) FIG. 15A illustrates an example of an array of visible light sources according to certain embodiments, where each visible light source in the array is configured to generate visible light of different colors. FIG. 15B illustrates a top view of the example of the array of visible light sources of FIG. 15A.

(20) FIG. 16A illustrates an example of an array of visible light sources according to certain embodiments, where each visible light source is configured to emit visible light in multiple colors and the respective intensity of the visible light in each color is individually controllable.

(21) FIG. 16B illustrates a top view of the example of the array of visible light sources of FIG. 16A.

(22) FIG. 17A illustrates an example of a visible light source that is tunable to emit visible light of different colors according to certain embodiments. FIG. 17B illustrates a top view of the example of the array of visible light sources of FIG. 17A. FIGS. 17C and 17D illustrate an example of generating visible light of different colors by tuning the visible light source of FIGS. 17A and 17B.

(23) FIG. 18A illustrates an example of an array of visible light sources according to certain embodiments, where each visible light source is tunable to emit visible light in one or more colors and the respective intensity of the visible light in each color is individually controllable. FIG. 18B illustrates a top view of the example of the array of visible light sources of FIG. 18A.

(24) FIG. 19 is a simplified block diagram of an electronic system of an example of a near-eye display according to certain embodiments.

(25) The figures depict embodiments of the present disclosure for purposes of illustration only. One skilled in the art will readily recognize from the following description that alternative embodiments of the structures and methods illustrated may be employed without departing from the principles, or

benefits touted, of this disclosure.

(26) In the appended figures, similar components and/or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If only the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label.

DETAILED DESCRIPTION

(27) This disclosure relates generally to visible light sources. More specifically, and without limitation, this disclosure relates to integrated vertical-cavity surface-emitting lasers (VCSELs) pumped visible light sources including optical resonators configured to generate visible light using infrared through optical parametric oscillation (OPO). Various inventive embodiments are described herein, including devices, systems, components, wafers, dice, methods, structures, materials, processes, and the like.

(28) Semiconductor light-emitting devices may be used in many optical systems, such as display systems and sensor systems. For example, in some display systems, visible display light emitted from a visible light source (e.g., a diode laser array or a micro-light-emitting diode (micro-LED) array) may be directed projected to user's eyes. In waveguide display systems, visible display light emitted from a visible light source may be coupled into a display (e.g., a waveguide display) for delivering images to a viewer's eyes. The overall efficiency $\eta_{\text{sub.tot}}$ of a waveguide display system may be determined by $\eta_{\text{sub.tot}} = \eta_{\text{sub.EQE}} \times \eta_{\text{sub.in}} \times \eta_{\text{sub.out}}$, where $\eta_{\text{sub.EQE}}$ is the external quantum efficiency (EQE) of the light source (e.g., a laser or micro-LED) and may be proportional to a product of the carrier (e.g., electron) injection efficiency, the internal quantum efficiency, and the light extraction efficiency (LEE). $\eta_{\text{sub.in}}$ is the in-coupling efficiency of the visible display light from the light source into the waveguide. $\eta_{\text{sub.out}}$ is the out-coupling efficiency of the visible display light from the waveguide towards the viewer's eye. To improve, for example, the brightness, resolution, and efficiency of an optical system (e.g., a display system), visible light source arrays with small pixel pitches (e.g., less than about 20 or about 10 μm), high brightness, high dynamic range, controllable emission direction, individual addressability, large color Gamut, and manufacture scalability are generally desired.

(29) However, it can be challenging to make such visible light sources. For example, LEDs and organic LEDs (OLEDs) may have fundamental limitations in brightness. It can be very difficult to make VCSELs with high efficiencies for some visible colors (e.g., green). It can be even more challenging to manufacture visible-light laser sources for multiple colors on a same chip or wafer. Furthermore, current visible light source architectures may typically have large footprints and may not be suitable for individually addressable high-density source array for high resolution display. Integration of III-V semiconductor devices with photonic integrated circuits (PICs) can pose additional manufacturing challenges.

(30) According to certain embodiments, a visible light source may include an VCSEL that may emit light in the near-infrared (NIR) or other infrared (IR) band with a high efficiency. The NIR light may be generally referred to as IR light hereinafter. The visible light source may also include a micro-resonator that may convert the IR light into visible light due to degenerate four-wave mixing (a third order nonlinear optical process also referred to as Optical Parametric Oscillation (OPO)) within the micro-resonator. In some embodiments, the micro-resonator may be positioned inside or outside the VCSEL cavity and aligned with the VCSEL, where the IR light emitted by the VCSEL may be coupled into the micro-resonator directly or by a coupling structure (e.g., a grating coupler or nano-resonators). In some embodiments, the IR light emitted by the VCSEL may be coupled into a waveguide by a coupling structure (e.g., a grating coupler or nano-resonators) and may then be coupled from the waveguide into the micro-resonator, for example, through a waveguide coupler. The micro-resonator may include, for example, a micro-ring resonator, a

photonic crystal point defect cavity, a photonic crystal ring (line-defect) cavity, a plasmonic resonator, and the like. Visible light generated by the degenerate four-wave mixing in the micro-resonator may be coupled out of the micro-resonator into a waveguide through side coupling or into free space through vertical coupling by coupling structures (e.g., gratings, or dielectric or metallic scatterers placed in the vicinity of the micro-resonator).

(31) In some embodiments, a device may include an array of visible light sources, where the visible light sources may emit visible light of different colors, such as red, blue, and green. In one example, each visible light source may include one micro-resonator, and the micro-resonators (and/or the VCSELs) in some visible light sources may be different from the micro-resonators (and/or the VCSELs) in some other visible light sources, such that different visible light sources may emit light of different colors. In some embodiments, each visible light source in the array of visible light source may be configured to, or may be configurable to, emit light of different colors. In one example, each visible light source of the array of visible light sources may include a pump VCSEL and multiple micro-resonators (e.g., arranged vertically) having different parameters, where each of the multiple micro-resonators may be configured to generate visible light of a different color, and, in some embodiments, each micro-resonator of the multiple micro-resonators may be tuned (e.g., by a thermal-optic or electro-optic tuner) to independently adjust the intensity of the corresponding visible light generated by the micro-resonator. In some embodiments, a visible light source in the array of visible light sources may include a pump VCSEL that has a tunable cavity and can be tuned to emit pump light having different wavelengths, and the visible light source may also include a micro-resonator having multiple resonant modes and thus can generate visible light of different colors using the pump light having different wavelengths.

(32) Techniques disclosed herein may achieve performance needed for display applications. For example, because of the vertical configuration of each visible light source and the compactness of the arrangement of the visible light source array, a small-pitch, multi-color pixelated array may be achieved, which can be used as a backlight unit (BLU) with local dimming capability for liquid crystal displays (LCDs), or can be used as an active display panel. The polarization of the output light from the visible light source is highly controllable, for example, by the design of the output coupling structures (e.g., gratings, scatterers, etc.). The structure of the visible light source can be designed to generate light at any visible wavelength using the OPO process, and thus can be used to provide International Telecommunication Union (ITU) Recommendation BT.2020 (Rec. 2020) color gamut or an even larger gamut by producing more than 3 primary colors. The direct electronic control of each visible light source can provide individual addressability, high contrast, and fast response. The integration of the pump light and the OPO components provides an overall compact, low profile, planar structure suitable for AR/VR applications. When side coupling is used, the visible light sources disclosed herein can also be used to provide red, green, and blue light to other on-chip photonic integrated circuits.

(33) In addition, visible light sources disclosed herein can have scalable manufacturability. For example, visible light sources disclosed herein can be manufactured using established integration techniques for integrating (e.g., bonding) near-infrared (NIR) VCSELs with SiN, SiC, AlN, LiNbO₃, or SiON materials for photonic integrated circuits. Visible light sources disclosed herein use VCSEL structures that are suitable for substrate lift-off to enable integration. The pixelated arrays can be fabricated at a scalable, wafer level, including the fabrication of VCSELs and PIC devices, the bonding, or the like.

(34) As used herein, visible light may refer to light that is visible to human eyes, such as light with a wavelength between about 400 nm and about 750 nm. Infrared light may refer generally to light with a wavelength greater than about 750 nm. Near-infrared (NIR) light may refer to IR light with a wavelength between, for example, about 750 nm and about 2500 nm.

(35) The visible light sources described herein may be used in conjunction with various technologies, such as an artificial reality system. An artificial reality system, such as a head-

mounted display (HMD) or heads-up display (HUD) system, generally includes a display configured to present artificial images that depict objects in a virtual environment. The display may present virtual objects or combine images of real objects with virtual objects, as in virtual reality (VR), augmented reality (AR), or mixed reality (MR) applications. For example, in an AR system, a user may view both displayed images of virtual objects (e.g., computer-generated images (CGIs)) and the surrounding environment by, for example, seeing through transparent display glasses or lenses (often referred to as optical see-through) or viewing displayed images of the surrounding environment captured by a camera (often referred to as video see-through). In some AR systems, the artificial images may be presented to users using an LED-based display subsystem.

(36) In the following description, for the purposes of explanation, specific details are set forth in order to provide a thorough understanding of examples of the disclosure. However, it will be apparent that various examples may be practiced without these specific details. For example, devices, systems, structures, assemblies, methods, and other components may be shown as components in block diagram form in order not to obscure the examples in unnecessary detail. In other instances, well-known devices, processes, systems, structures, and techniques may be shown without necessary detail in order to avoid obscuring the examples. The figures and description are not intended to be restrictive. The terms and expressions that have been employed in this disclosure are used as terms of description and not of limitation, and there is no intention in the use of such terms and expressions of excluding any equivalents of the features shown and described or portions thereof. The word “example” is used herein to mean “serving as an example, instance, or illustration.” Any embodiment or design described herein as “example” is not necessarily to be construed as preferred or advantageous over other embodiments or designs.

(37) FIG. 1 is a simplified block diagram of an example of an artificial reality system environment **100** including a near-eye display **120** in accordance with certain embodiments. Artificial reality system environment **100** shown in FIG. 1 may include near-eye display **120**, an optional external imaging device **150**, and an optional input/output interface **140**, each of which may be coupled to an optional console **110**. While FIG. 1 shows an example of artificial reality system environment **100** including one near-eye display **120**, one external imaging device **150**, and one input/output interface **140**, any number of these components may be included in artificial reality system environment **100**, or any of the components may be omitted. For example, there may be multiple near-eye displays **120** monitored by one or more external imaging devices **150** in communication with console **110**. In some configurations, artificial reality system environment **100** may not include external imaging device **150**, optional input/output interface **140**, and optional console **110**. In alternative configurations, different or additional components may be included in artificial reality system environment **100**.

(38) Near-eye display **120** may be a head-mounted display that presents content to a user. Examples of content presented by near-eye display **120** include one or more of images, videos, audio, or any combination thereof. In some embodiments, audio may be presented via an external device (e.g., speakers and/or headphones) that receives audio information from near-eye display **120**, console **110**, or both, and presents audio data based on the audio information. Near-eye display **120** may include one or more rigid bodies, which may be rigidly or non-rigidly coupled to each other. A rigid coupling between rigid bodies may cause the coupled rigid bodies to act as a single rigid entity. A non-rigid coupling between rigid bodies may allow the rigid bodies to move relative to each other. In various embodiments, near-eye display **120** may be implemented in any suitable form-factor, including a pair of glasses. Some embodiments of near-eye display **120** are further described below with respect to FIGS. 2 and 3. Additionally, in various embodiments, the functionality described herein may be used in a headset that combines images of an environment external to near-eye display **120** and artificial reality content (e.g., computer-generated images). Therefore, near-eye display **120** may augment images of a physical, real-world environment external to near-eye display **120** with generated content (e.g., images, video, sound, etc.) to present an augmented

reality to a user.

(39) In various embodiments, near-eye display **120** may include one or more of display electronics **122**, display optics **124**, and an eye-tracking unit **130**. In some embodiments, near-eye display **120** may also include one or more locators **126**, one or more position sensors **128**, and an inertial measurement unit (IMU) **132**. Near-eye display **120** may omit any of eye-tracking unit **130**, locators **126**, position sensors **128**, and IMU **132**, or include additional elements in various embodiments. Additionally, in some embodiments, near-eye display **120** may include elements combining the function of various elements described in conjunction with FIG. 1.

(40) Display electronics **122** may display or facilitate the display of images to the user according to data received from, for example, console **110**. In various embodiments, display electronics **122** may include one or more display panels, such as a liquid crystal display (LCD), an organic light-emitting diode (OLED) display, an inorganic light-emitting diode (ILED) display, a micro light-emitting diode (μ LED) display, an active-matrix OLED display (AMOLED), a transparent OLED display (TOLED), or some other displays. For example, in one implementation of near-eye display **120**, display electronics **122** may include a front TOLED panel, a rear display panel, and an optical component (e.g., an attenuator, polarizer, or diffractive or spectral film) between the front and rear display panels. Display electronics **122** may include pixels to emit light of a predominant color such as red, green, blue, white, or yellow. In some implementations, display electronics **122** may display a three-dimensional (3D) image through stereoscopic effects produced by two-dimensional panels to create a subjective perception of image depth. For example, display electronics **122** may include a left display and a right display positioned in front of a user's left eye and right eye, respectively. The left and right displays may present copies of an image shifted horizontally relative to each other to create a stereoscopic effect (i.e., a perception of image depth by a user viewing the image).

(41) In certain embodiments, display optics **124** may display image content optically (e.g., using optical waveguides and couplers) or magnify image light received from display electronics **122**, correct optical errors associated with the image light, and present the corrected image light to a user of near-eye display **120**. In various embodiments, display optics **124** may include one or more optical elements, such as, for example, a substrate, optical waveguides, an aperture, a Fresnel lens, a convex lens, a concave lens, a filter, input/output couplers, or any other suitable optical elements that may affect image light emitted from display electronics **122**. Display optics **124** may include a combination of different optical elements as well as mechanical couplings to maintain relative spacing and orientation of the optical elements in the combination. One or more optical elements in display optics **124** may have an optical coating, such as an anti-reflective coating, a reflective coating, a filtering coating, or a combination of different optical coatings.

(42) Magnification of the image light by display optics **124** may allow display electronics **122** to be physically smaller, weigh less, and consume less power than larger displays. Additionally, magnification may increase a field of view of the displayed content. The amount of magnification of image light by display optics **124** may be changed by adjusting, adding, or removing optical elements from display optics **124**. In some embodiments, display optics **124** may project displayed images to one or more image planes that may be further away from the user's eyes than near-eye display **120**.

(43) Display optics **124** may also be designed to correct one or more types of optical errors, such as two-dimensional optical errors, three-dimensional optical errors, or any combination thereof. Two-dimensional errors may include optical aberrations that occur in two dimensions. Example types of two-dimensional errors may include barrel distortion, pincushion distortion, longitudinal chromatic aberration, and transverse chromatic aberration. Three-dimensional errors may include optical errors that occur in three dimensions. Example types of three-dimensional errors may include spherical aberration, comatic aberration, field curvature, and astigmatism.

(44) Locators **126** may be objects located in specific positions on near-eye display **120** relative to

one another and relative to a reference point on near-eye display **120**. In some implementations, console **110** may identify locators **126** in images captured by external imaging device **150** to determine the artificial reality headset's position, orientation, or both. A locator **126** may be an LED, a corner cube reflector, a reflective marker, a type of light source that contrasts with an environment in which near-eye display **120** operates, or any combination thereof. In embodiments where locators **126** are active components (e.g., LEDs or other types of light-emitting devices), locators **126** may emit light in the visible band (e.g., about 380 nm to 750 nm), in the infrared (IR) band (e.g., about 750 nm to 1 mm), in the ultraviolet band (e.g., about 10 nm to about 380 nm), in another portion of the electromagnetic spectrum, or in any combination of portions of the electromagnetic spectrum.

(45) External imaging device **150** may include one or more cameras, one or more video cameras, any other device capable of capturing images including one or more of locators **126**, or any combination thereof. Additionally, external imaging device **150** may include one or more filters (e.g., to increase signal to noise ratio). External imaging device **150** may be configured to detect light emitted or reflected from locators **126** in a field of view of external imaging device **150**. In embodiments where locators **126** include passive elements (e.g., retroreflectors), external imaging device **150** may include a light source that illuminates some or all of locators **126**, which may retro-reflect the light to the light source in external imaging device **150**. Slow calibration data may be communicated from external imaging device **150** to console **110**, and external imaging device **150** may receive one or more calibration parameters from console **110** to adjust one or more imaging parameters (e.g., focal length, focus, frame rate, sensor temperature, shutter speed, aperture, etc.).

(46) Position sensors **128** may generate one or more measurement signals in response to motion of near-eye display **120**. Examples of position sensors **128** may include accelerometers, gyroscopes, magnetometers, other motion-detecting or error-correcting sensors, or any combination thereof. For example, in some embodiments, position sensors **128** may include multiple accelerometers to measure translational motion (e.g., forward/back, up/down, or left/right) and multiple gyroscopes to measure rotational motion (e.g., pitch, yaw, or roll). In some embodiments, various position sensors may be oriented orthogonally to each other.

(47) IMU **132** may be an electronic device that generates fast calibration data based on measurement signals received from one or more of position sensors **128**. Position sensors **128** may be located external to IMU **132**, internal to IMU **132**, or any combination thereof. Based on the one or more measurement signals from one or more position sensors **128**, IMU **132** may generate fast calibration data indicating an estimated position of near-eye display **120** relative to an initial position of near-eye display **120**. For example, IMU **132** may integrate measurement signals received from accelerometers over time to estimate a velocity vector and integrate the velocity vector over time to determine an estimated position of a reference point on near-eye display **120**. Alternatively, IMU **132** may provide the sampled measurement signals to console **110**, which may determine the fast calibration data. While the reference point may generally be defined as a point in space, in various embodiments, the reference point may also be defined as a point within near-eye display **120** (e.g., a center of IMU **132**).

(48) Eye-tracking unit **130** may include one or more eye-tracking systems. Eye tracking may refer to determining an eye's position, including orientation and location of the eye, relative to near-eye display **120**. An eye-tracking system may include an imaging system to image one or more eyes and may optionally include a light emitter, which may generate light that is directed to an eye such that light reflected by the eye may be captured by the imaging system. For example, eye-tracking unit **130** may include a non-coherent or coherent light source (e.g., a laser diode) emitting light in the visible spectrum or infrared spectrum, and a camera capturing the light reflected by the user's eye. As another example, eye-tracking unit **130** may capture reflected radio waves emitted by a miniature radar unit. Eye-tracking unit **130** may use low-power light emitters that emit light at

frequencies and intensities that would not injure the eye or cause physical discomfort. Eye-tracking unit **130** may be arranged to increase contrast in images of an eye captured by eye-tracking unit **130** while reducing the overall power consumed by eye-tracking unit **130** (e.g., reducing power consumed by a light emitter and an imaging system included in eye-tracking unit **130**). For example, in some implementations, eye-tracking unit **130** may consume less than 100 milliwatts of power.

(49) Near-eye display **120** may use the orientation of the eye to, e.g., determine an inter-pupillary distance (IPD) of the user, determine gaze direction, introduce depth cues (e.g., blur image outside of the user's main line of sight), collect heuristics on the user interaction in the VR media (e.g., time spent on any particular subject, object, or frame as a function of exposed stimuli), some other functions that are based in part on the orientation of at least one of the user's eyes, or any combination thereof. Because the orientation may be determined for both eyes of the user, eye-tracking unit **130** may be able to determine where the user is looking. For example, determining a direction of a user's gaze may include determining a point of convergence based on the determined orientations of the user's left and right eyes. A point of convergence may be the point where the two foveal axes of the user's eyes intersect. The direction of the user's gaze may be the direction of a line passing through the point of convergence and the mid-point between the pupils of the user's eyes.

(50) Input/output interface **140** may be a device that allows a user to send action requests to console **110**. An action request may be a request to perform a particular action. For example, an action request may be to start or to end an application or to perform a particular action within the application. Input/output interface **140** may include one or more input devices. Example input devices may include a keyboard, a mouse, a game controller, a glove, a button, a touch screen, or any other suitable device for receiving action requests and communicating the received action requests to console **110**. An action request received by the input/output interface **140** may be communicated to console **110**, which may perform an action corresponding to the requested action. In some embodiments, input/output interface **140** may provide haptic feedback to the user in accordance with instructions received from console **110**. For example, input/output interface **140** may provide haptic feedback when an action request is received, or when console **110** has performed a requested action and communicates instructions to input/output interface **140**. In some embodiments, external imaging device **150** may be used to track input/output interface **140**, such as tracking the location or position of a controller (which may include, for example, an IR light source) or a hand of the user to determine the motion of the user. In some embodiments, near-eye display **120** may include one or more imaging devices to track input/output interface **140**, such as tracking the location or position of a controller or a hand of the user to determine the motion of the user.

(51) Console **110** may provide content to near-eye display **120** for presentation to the user in accordance with information received from one or more of external imaging device **150**, near-eye display **120**, and input/output interface **140**. In the example shown in FIG. 1, console **110** may include an application store **112**, a headset tracking module **114**, an artificial reality engine **116**, and an eye-tracking module **118**. Some embodiments of console **110** may include different or additional modules than those described in conjunction with FIG. 1. Functions further described below may be distributed among components of console **110** in a different manner than is described here.

(52) In some embodiments, console **110** may include a processor and a non-transitory computer-readable storage medium storing instructions executable by the processor. The processor may include multiple processing units executing instructions in parallel. The non-transitory computer-readable storage medium may be any memory, such as a hard disk drive, a removable memory, or a solid-state drive (e.g., flash memory or dynamic random access memory (DRAM)). In various embodiments, the modules of console **110** described in conjunction with FIG. 1 may be encoded as instructions in the non-transitory computer-readable storage medium that, when executed by the

processor, cause the processor to perform the functions further described below.

(53) Application store **112** may store one or more applications for execution by console **110**. An application may include a group of instructions that, when executed by a processor, generates content for presentation to the user. Content generated by an application may be in response to inputs received from the user via movement of the user's eyes or inputs received from the input/output interface **140**. Examples of the applications may include gaming applications, conferencing applications, video playback application, or other suitable applications.

(54) Headset tracking module **114** may track movements of near-eye display **120** using slow calibration information from external imaging device **150**. For example, headset tracking module **114** may determine positions of a reference point of near-eye display **120** using observed locators from the slow calibration information and a model of near-eye display **120**. Headset tracking module **114** may also determine positions of a reference point of near-eye display **120** using position information from the fast calibration information. Additionally, in some embodiments, headset tracking module **114** may use portions of the fast calibration information, the slow calibration information, or any combination thereof, to predict a future location of near-eye display **120**. Headset tracking module **114** may provide the estimated or predicted future position of near-eye display **120** to artificial reality engine **116**.

(55) Artificial reality engine **116** may execute applications within artificial reality system environment **100** and receive position information of near-eye display **120**, acceleration information of near-eye display **120**, velocity information of near-eye display **120**, predicted future positions of near-eye display **120**, or any combination thereof from headset tracking module **114**. Artificial reality engine **116** may also receive estimated eye position and orientation information from eye-tracking module **118**. Based on the received information, artificial reality engine **116** may determine content to provide to near-eye display **120** for presentation to the user. For example, if the received information indicates that the user has looked to the left, artificial reality engine **116** may generate content for near-eye display **120** that mirrors the user's eye movement in a virtual environment. Additionally, artificial reality engine **116** may perform an action within an application executing on console **110** in response to an action request received from input/output interface **140**, and provide feedback to the user indicating that the action has been performed. The feedback may be visual or audible feedback via near-eye display **120** or haptic feedback via input/output interface **140**.

(56) Eye-tracking module **118** may receive eye-tracking data from eye-tracking unit **130** and determine the position of the user's eye based on the eye tracking data. The position of the eye may include an eye's orientation, location, or both relative to near-eye display **120** or any element thereof. Because the eye's axes of rotation change as a function of the eye's location in its socket, determining the eye's location in its socket may allow eye-tracking module **118** to more accurately determine the eye's orientation.

(57) FIG. 2 is a perspective view of an example of a near-eye display in the form of an HMD device **200** for implementing some of the examples disclosed herein. HMD device **200** may be a part of, e.g., a VR system, an AR system, an MR system, or any combination thereof. HMD device **200** may include a body **220** and a head strap **230**. FIG. 2 shows a bottom side **223**, a front side **225**, and a left side **227** of body **220** in the perspective view. Head strap **230** may have an adjustable or extendible length. There may be a sufficient space between body **220** and head strap **230** of HMD device **200** for allowing a user to mount HMD device **200** onto the user's head. In various embodiments, HMD device **200** may include additional, fewer, or different components. For example, in some embodiments, HMD device **200** may include eyeglass temples and temple tips as shown in, for example, FIG. 3 below, rather than head strap **230**.

(58) HMD device **200** may present to a user media including virtual and/or augmented views of a physical, real-world environment with computer-generated elements. Examples of the media presented by HMD device **200** may include images (e.g., two-dimensional (2D) or three-

dimensional (3D) images), videos (e.g., 2D or 3D videos), audio, or any combination thereof. The images and videos may be presented to each eye of the user by one or more display assemblies (not shown in FIG. 2) enclosed in body **220** of HMD device **200**. In various embodiments, the one or more display assemblies may include a single electronic display panel or multiple electronic display panels (e.g., one display panel for each eye of the user). Examples of the electronic display panel(s) may include, for example, an LCD, an OLED display, an ILED display, a μ LED display, an AMOLED, a TOLED, some other display, or any combination thereof. HMD device **200** may include two eye box regions.

(59) In some implementations, HMD device **200** may include various sensors (not shown), such as depth sensors, motion sensors, position sensors, and eye tracking sensors. Some of these sensors may use a structured light pattern for sensing. In some implementations, HMD device **200** may include an input/output interface for communicating with a console. In some implementations, HMD device **200** may include a virtual reality engine (not shown) that can execute applications within HMD device **200** and receive depth information, position information, acceleration information, velocity information, predicted future positions, or any combination thereof of HMD device **200** from the various sensors. In some implementations, the information received by the virtual reality engine may be used for producing a signal (e.g., display instructions) to the one or more display assemblies. In some implementations, HMD device **200** may include locators (not shown, such as locators **126**) located in fixed positions on body **220** relative to one another and relative to a reference point. Each of the locators may emit light that is detectable by an external imaging device.

(60) FIG. 3 is a perspective view of an example of a near-eye display **300** in the form of a pair of glasses for implementing some of the examples disclosed herein. Near-eye display **300** may be a specific implementation of near-eye display **120** of FIG. 1, and may be configured to operate as a virtual reality display, an augmented reality display, and/or a mixed reality display. Near-eye display **300** may include a frame **305** and a display **310**. Display **310** may be configured to present content to a user. In some embodiments, display **310** may include display electronics and/or display optics. For example, as described above with respect to near-eye display **120** of FIG. 1, display **310** may include an LCD display panel, an LED display panel, or an optical display panel (e.g., a waveguide display assembly).

(61) Near-eye display **300** may further include various sensors **350a**, **350b**, **350c**, **350d**, and **350e** on or within frame **305**. In some embodiments, sensors **350a-350e** may include one or more depth sensors, motion sensors, position sensors, inertial sensors, or ambient light sensors. In some embodiments, sensors **350a-350e** may include one or more image sensors configured to generate image data representing different fields of views in different directions. In some embodiments, sensors **350a-350e** may be used as input devices to control or influence the displayed content of near-eye display **300**, and/or to provide an interactive VR/AR/MR experience to a user of near-eye display **300**. In some embodiments, sensors **350a-350e** may also be used for stereoscopic imaging.

(62) In some embodiments, near-eye display **300** may further include one or more illuminators **330** to project light into the physical environment. The projected light may be associated with different frequency bands (e.g., visible light, infra-red light, ultra-violet light, etc.), and may serve various purposes. For example, illuminator(s) **330** may project light in a dark environment (or in an environment with low intensity of infra-red light, ultra-violet light, etc.) to assist sensors **350a-350e** in capturing images of different objects within the dark environment. In some embodiments, illuminator(s) **330** may be used to project certain light patterns onto the objects within the environment. In some embodiments, illuminator(s) **330** may be used as locators, such as locators **126** described above with respect to FIG. 1.

(63) In some embodiments, near-eye display **300** may also include a high-resolution camera **340**. Camera **340** may capture images of the physical environment in the field of view. The captured images may be processed, for example, by a virtual reality engine (e.g., artificial reality engine **116**

of FIG. 1) to add virtual objects to the captured images or modify physical objects in the captured images, and the processed images may be displayed to the user by display 310 for AR or MR applications.

(64) FIG. 4 illustrates an example of an optical see-through augmented reality system 400 including a waveguide display according to certain embodiments. Augmented reality system 400 may include a projector 410 and a combiner 415. Projector 410 may include a light source or image source 412 and projector optics 414. In some embodiments, light source or image source 412 may include one or more micro-LED devices described above. In some embodiments, image source 412 may include a plurality of pixels that displays virtual objects, such as an LCD display panel or an LED display panel. In some embodiments, image source 412 may include a light source that generates coherent or partially coherent light. For example, image source 412 may include a laser diode, a vertical-cavity surface-emitting laser, an LED, and/or a micro-LED described above. In some embodiments, image source 412 may include a plurality of light sources (e.g., an array of micro-LEDs described above), each emitting a monochromatic image light corresponding to a primary color (e.g., red, green, or blue). In some embodiments, image source 412 may include three two-dimensional arrays of micro-LEDs, where each two-dimensional array of micro-LEDs may include micro-LEDs configured to emit light of a primary color (e.g., red, green, or blue). In some embodiments, image source 412 may include an optical pattern generator, such as a spatial light modulator. Projector optics 414 may include one or more optical components that can condition the light from image source 412, such as expanding, collimating, scanning, or projecting light from image source 412 to combiner 415. The one or more optical components may include, for example, one or more lenses, liquid lenses, mirrors, apertures, and/or gratings. For example, in some embodiments, image source 412 may include one or more one-dimensional arrays or elongated two-dimensional arrays of micro-LEDs, and projector optics 414 may include one or more one-dimensional scanners (e.g., micro-mirrors or prisms) configured to scan the one-dimensional arrays or elongated two-dimensional arrays of micro-LEDs to generate image frames. In some embodiments, projector optics 414 may include a liquid lens (e.g., a liquid crystal lens) with a plurality of electrodes that allows scanning of the light from image source 412.

(65) Combiner 415 may include an input coupler 430 for coupling light from projector 410 into a substrate 420 of combiner 415. Combiner 415 may transmit at least 50% of light in a first wavelength range and reflect at least 25% of light in a second wavelength range. For example, the first wavelength range may be visible light from about 400 nm to about 650 nm, and the second wavelength range may be in the infrared band, for example, from about 800 nm to about 1000 nm. Input coupler 430 may include a volume holographic grating, a diffractive optical element (DOE) (e.g., a surface-relief grating), a slanted surface of substrate 420, or a refractive coupler (e.g., a wedge or a prism). For example, input coupler 430 may include a reflective volume Bragg grating or a transmissive volume Bragg grating. Input coupler 430 may have a coupling efficiency of greater than 30%, 50%, 75%, 90%, or higher for visible light. Light coupled into substrate 420 may propagate within substrate 420 through, for example, total internal reflection (TIR). Substrate 420 may be in the form of a lens or a pair of eyeglasses. Substrate 420 may have a flat or a curved surface, and may include one or more types of dielectric materials, such as glass, quartz, plastic, polymer, poly(methyl methacrylate) (PMMA), crystal, or ceramic. A thickness of the substrate may range from, for example, less than about 1 mm to about 10 mm or more. Substrate 420 may be transparent to visible light.

(66) Substrate 420 may include or may be coupled to a plurality of output couplers 440, each configured to extract at least a portion of the light guided by and propagating within substrate 420 from substrate 420, and direct extracted light 460 to an eyepiece 495 where an eye 490 of the user of augmented reality system 400 may be located when augmented reality system 400 is in use. The plurality of output couplers 440 may replicate the exit pupil to increase the size of eyepiece 495 such that the displayed image is visible in a larger area. As input coupler 430, output couplers 440 may

include grating couplers (e.g., volume holographic gratings or surface-relief gratings), other diffraction optical elements, prisms, etc. For example, output couplers **440** may include reflective volume Bragg gratings or transmissive volume Bragg gratings. Output couplers **440** may have different coupling (e.g., diffraction) efficiencies at different locations. Substrate **420** may also allow light **450** from the environment in front of combiner **415** to pass through with little or no loss. Output couplers **440** may also allow light **450** to pass through with little loss. For example, in some implementations, output couplers **440** may have a very low diffraction efficiency for light **450** such that light **450** may be refracted or otherwise pass through output couplers **440** with little loss, and thus may have a higher intensity than extracted light **460**. In some implementations, output couplers **440** may have a high diffraction efficiency for light **450** and may diffract light **450** in certain desired directions (i.e., diffraction angles) with little loss. As a result, the user may be able to view combined images of the environment in front of combiner **415** and images of virtual objects projected by projector **410**.

(67) FIG. 5A illustrates an example of a near-eye display (NED) device **500** including a waveguide display **530** according to certain embodiments. NED device **500** may be an example of near-eye display **120**, augmented reality system **400**, or another type of display device. NED device **500** may include a light source **510**, projection optics **520**, and waveguide display **530**. Light source **510** may include multiple panels of light emitters for different colors, such as a panel of red light emitters **512**, a panel of green light emitters **514**, and a panel of blue light emitters **516**. The red light emitters **512** are organized into an array; the green light emitters **514** are organized into an array; and the blue light emitters **516** are organized into an array. The dimensions and pitches of light emitters in light source **510** may be small. For example, each light emitter may have a diameter less than 2 μm (e.g., about 1.2 μm) and the pitch may be less than 2 μm (e.g., about 1.5 μm). As such, the number of light emitters in each red light emitters **512**, green light emitters **514**, and blue light emitters **516** can be equal to or greater than the number of pixels in a display image, such as 960×720, 1280×720, 1440×1080, 1920×1080, 2160×1080, or 2560×1080 pixels. Thus, a display image may be generated simultaneously by light source **510**. A scanning element may not be used in NED device **500**.

(68) Before reaching waveguide display **530**, the light emitted by light source **510** may be conditioned by projection optics **520**, which may include a lens array. Projection optics **520** may collimate or focus the light emitted by light source **510** to waveguide display **530**, which may include a coupler **532** for coupling the light emitted by light source **510** into waveguide display **530**. The light coupled into waveguide display **530** may propagate within waveguide display **530** through, for example, total internal reflection as described above with respect to FIG. 4. Coupler **532** may also couple portions of the light propagating within waveguide display **530** out of waveguide display **530** and towards user's eye **590**.

(69) FIG. 5B illustrates an example of a near-eye display (NED) device **550** including a waveguide display **580** according to certain embodiments. In some embodiments, NED device **550** may use a scanning mirror **570** to project light from a light source **540** to an image field where a user's eye **590** may be located. NED device **550** may be an example of near-eye display **120**, augmented reality system **400**, or another type of display device. Light source **540** may include one or more rows or one or more columns of light emitters of different colors, such as multiple rows of red light emitters **542**, multiple rows of green light emitters **544**, and multiple rows of blue light emitters **546**. For example, red light emitters **542**, green light emitters **544**, and blue light emitters **546** may each include N rows, each row including, for example, 2560 light emitters (pixels). The red light emitters **542** are organized into an array; the green light emitters **544** are organized into an array; and the blue light emitters **546** are organized into an array. In some embodiments, light source **540** may include a single line of light emitters for each color. In some embodiments, light source **540** may include multiple columns of light emitters for each of red, green, and blue colors, where each column may include, for example, 1080 light emitters. In some embodiments, the dimensions

and/or pitches of the light emitters in light source **540** may be relatively large (e.g., about 3-5 μm) and thus light source **540** may not include sufficient light emitters for simultaneously generating a full display image. For example, the number of light emitters for a single color may be fewer than the number of pixels (e.g., 2560 $\times$ 1080 pixels) in a display image. The light emitted by light source **540** may be a set of collimated or diverging beams of light.

(70) Before reaching scanning mirror **570**, the light emitted by light source **540** may be conditioned by various optical devices, such as collimating lenses or a freeform optical element **560**. Freeform optical element **560** may include, for example, a multi-facet prism or another light folding element that may direct the light emitted by light source **540** towards scanning mirror **570**, such as changing the propagation direction of the light emitted by light source **540** by, for example, about 90° or larger. In some embodiments, freeform optical element **560** may be rotatable to scan the light. Scanning mirror **570** and/or freeform optical element **560** may reflect and project the light emitted by light source **540** to waveguide display **580**, which may include a coupler **582** for coupling the light emitted by light source **540** into waveguide display **580**. The light coupled into waveguide display **580** may propagate within waveguide display **580** through, for example, total internal reflection as described above with respect to FIG. 4. Coupler **582** may also couple portions of the light propagating within waveguide display **580** out of waveguide display **580** and towards user's eye **590**.

(71) Scanning mirror **570** may include a micro-electro-mechanical system (MEMS) mirror or any other suitable mirrors. Scanning mirror **570** may rotate to scan in one or two dimensions. As scanning mirror **570** rotates, the light emitted by light source **540** may be directed to a different area of waveguide display **580** such that a full display image may be projected onto waveguide display **580** and directed to user's eye **590** by waveguide display **580** in each scanning cycle. For example, in embodiments where light source **540** includes light emitters for all pixels in one or more rows or columns, scanning mirror **570** may be rotated in the column or row direction (e.g., x or y direction) to scan an image. In embodiments where light source **540** includes light emitters for some but not all pixels in one or more rows or columns, scanning mirror **570** may be rotated in both the row and column directions (e.g., both x and y directions) to project a display image (e.g., using a raster-type scanning pattern).

(72) NED device **550** may operate in predefined display periods. A display period (e.g., display cycle) may refer to a duration of time in which a full image is scanned or projected. For example, a display period may be a reciprocal of the desired frame rate. In NED device **550** that includes scanning mirror **570**, the display period may also be referred to as a scanning period or scanning cycle. The light generation by light source **540** may be synchronized with the rotation of scanning mirror **570**. For example, each scanning cycle may include multiple scanning steps, where light source **540** may generate a different light pattern in each respective scanning step.

(73) In each scanning cycle, as scanning mirror **570** rotates, a display image may be projected onto waveguide display **580** and user's eye **590**. The actual color value and light intensity (e.g., brightness) of a given pixel location of the display image may be an average of the light beams of the three colors (e.g., red, green, and blue) illuminating the pixel location during the scanning period. After completing a scanning period, scanning mirror **570** may revert back to the initial position to project light for the first few rows of the next display image or may rotate in a reverse direction or scan pattern to project light for the next display image, where a new set of driving signals may be fed to light source **540**. The same process may be repeated as scanning mirror **570** rotates in each scanning cycle. As such, different images may be projected to user's eye **590** in different scanning cycles.

(74) FIG. 6 illustrates an example of an image source assembly **610** in a near-eye display system **600** according to certain embodiments. Image source assembly **610** may include, for example, a display panel **640** that may generate display images to be projected to the user's eyes, and a projector **650** that may project the display images generated by display panel **640** to a waveguide

display as described above with respect to FIGS. 4-5B. Display panel **640** may include a light source **642** and a driver circuit **644** for light source **642**. Light source **642** may include, for example, light source **510** or **540**. Projector **650** may include, for example, freeform optical element **560**, scanning mirror **570**, and/or projection optics **520** described above. Near-eye display system **600** may also include a controller **620** that synchronously controls light source **642** and projector **650** (e.g., scanning mirror **570**). Image source assembly **610** may generate and output an image light to a waveguide display (not shown in FIG. 6), such as waveguide display **530** or **580**. As described above, the waveguide display may receive the image light at one or more input-coupling elements, and guide the received image light to one or more output-coupling elements. The input and output coupling elements may include, for example, a diffraction grating, a holographic grating, a prism, or any combination thereof. The input-coupling element may be chosen such that total internal reflection occurs with the waveguide display. The output-coupling element may couple portions of the total internally reflected image light out of the waveguide display.

(75) As described above, light source **642** may include a plurality of light emitters arranged in an array or a matrix. Each light emitter may emit monochromatic light, such as red light, blue light, green light, infra-red light, or the like. While RGB colors are often discussed in this disclosure, embodiments described herein are not limited to using red, green, and blue as primary colors. Other colors can also be used as the primary colors of near-eye display system **600**. In some embodiments, a display panel in accordance with an embodiment may use more than three primary colors. Each pixel in light source **642** may include three subpixels that include a red light source, a green light source, and a blue light source, where each light source may include, for example, a laser (e.g., a VCSEL), a micro-LED, a resonant cavity LED (RCLED), or the like. In some embodiments, the light source may include a semiconductor light source, such as a semiconductor laser or a semiconductor LED. A semiconductor LED generally includes an active light-emitting layer within multiple layers of semiconductor materials. The multiple layers of semiconductor materials may include different compound materials or a same base material with different dopants and/or different doping densities. For example, the multiple layers of semiconductor materials may include an n-type material layer, an active region that may include hetero-structures (e.g., one or more quantum wells), and a p-type material layer. The multiple layers of semiconductor materials may be grown on a surface of a substrate having a certain orientation. In some embodiments, to increase light extraction efficiency, a mesa that includes at least some of the layers of semiconductor materials may be formed.

(76) Controller **620** may control the image rendering operations of image source assembly **610**, such as the operations of light source **642** and/or projector **650**. For example, controller **620** may determine instructions for image source assembly **610** to render one or more display images. The instructions may include display instructions and scanning instructions. In some embodiments, the display instructions may include an image file (e.g., a bitmap file). The display instructions may be received from, for example, a console, such as console **110** described above with respect to FIG. 1. The scanning instructions may be used by image source assembly **610** to generate image light. The scanning instructions may specify, for example, a type of a source of image light (e.g., monochromatic or polychromatic), a scanning rate, an orientation of a scanning apparatus, one or more illumination parameters, or any combination thereof. Controller **620** may include a combination of hardware, software, and/or firmware not shown here so as not to obscure other aspects of the present disclosure.

(77) In some embodiments, controller **620** may be a graphics processing unit (GPU) of a display device. In other embodiments, controller **620** may be other kinds of processors. The operations performed by controller **620** may include taking content for display and dividing the content into discrete sections. Controller **620** may provide to light source **642** scanning instructions that include an address corresponding to an individual source element of light source **642** and/or an electrical bias applied to the individual source element. Controller **620** may instruct light source **642** to

sequentially present the discrete sections using light emitters corresponding to one or more rows of pixels in an image ultimately displayed to the user. Controller **620** may also instruct projector **650** to perform different adjustments of the light. For example, controller **620** may control projector **650** to scan the discrete sections to different areas of a coupling element of the waveguide display (e.g., waveguide display **580**) as described above with respect to FIG. 5B. As such, at the exit pupil of the waveguide display, each discrete portion is presented in a different respective location. While each discrete section is presented at a different respective time, the presentation and scanning of the discrete sections occur fast enough such that a user's eye may integrate the different sections into a single image or series of images.

(78) Image processor **630** may be a general-purpose processor and/or one or more application-specific circuits that are dedicated to performing the features described herein. In one embodiment, a general-purpose processor may be coupled to a memory to execute software instructions that cause the processor to perform certain processes described herein. In another embodiment, image processor **630** may be one or more circuits that are dedicated to performing certain features. While image processor **630** in FIG. 6 is shown as a stand-alone unit that is separate from controller **620** and driver circuit **644**, image processor **630** may be a sub-unit of controller **620** or driver circuit **644** in other embodiments. In other words, in those embodiments, controller **620** or driver circuit **644** may perform various image processing functions of image processor **630**. Image processor **630** may also be referred to as an image processing circuit.

(79) In the example shown in FIG. 6, light source **642** may be driven by driver circuit **644**, based on data or instructions (e.g., display and scanning instructions) sent from controller **620** or image processor **630**. In one embodiment, driver circuit **644** may include a circuit panel that connects to and mechanically holds various light emitters of light source **642**. Light source **642** may emit light in accordance with one or more illumination parameters that are set by the controller **620** and potentially adjusted by image processor **630** and driver circuit **644**. An illumination parameter may be used by light source **642** to generate light. An illumination parameter may include, for example, source wavelength, pulse rate, pulse amplitude, beam type (continuous or pulsed), other parameter(s) that may affect the emitted light, or any combination thereof. In some embodiments, the source light generated by light source **642** may include multiple beams of red light, green light, and blue light, or any combination thereof.

(80) Projector **650** may perform a set of optical functions, such as focusing, combining, conditioning, or scanning the image light generated by light source **642**. In some embodiments, projector **650** may include a combining assembly, a light conditioning assembly, or a scanning mirror assembly. Projector **650** may include one or more optical components that optically adjust and potentially re-direct the light from light source **642**. One example of the adjustment of light may include conditioning the light, such as expanding, collimating, correcting for one or more optical errors (e.g., field curvature, chromatic aberration, etc.), some other adjustments of the light, or any combination thereof. The optical components of projector **650** may include, for example, lenses, mirrors, apertures, gratings, or any combination thereof.

(81) Projector **650** may redirect image light via its one or more reflective and/or refractive portions so that the image light is projected at certain orientations toward the waveguide display. The location where the image light is redirected toward the waveguide display may depend on specific orientations of the one or more reflective and/or refractive portions. In some embodiments, projector **650** includes a single scanning mirror that scans in at least two dimensions. In other embodiments, projector **650** may include a plurality of scanning mirrors that each scan in directions orthogonal to each other. Projector **650** may perform a raster scan (horizontally or vertically), a bi-resonant scan, or any combination thereof. In some embodiments, projector **650** may perform a controlled vibration along the horizontal and/or vertical directions with a specific frequency of oscillation to scan along two dimensions and generate a two-dimensional projected image of the media presented to user's eyes. In other embodiments, projector **650** may include a lens or prism

that may serve similar or the same function as one or more scanning mirrors. In some embodiments, image source assembly **610** may not include a projector, where the light emitted by light source **642** may be directly incident on the waveguide display.

(82) The overall efficiency of a photonic integrated circuit or a waveguide-based display (e.g., in augmented reality system **400** or NED device **500** or **550**) may be a product of the efficiency of individual components and may also depend on how the components are connected. For example, the overall efficiency $\eta_{\text{sub.tot}}$ of the waveguide-based display in augmented reality system **400** may depend on the light-emitting efficiency of image source **412**, the light coupling efficiency from image source **412** into combiner **415** by projector optics **414** and input coupler **430**, and the output coupling efficiency of output coupler **440**, and thus may be determined as:

$$\eta_{\text{sub.tot}} = \eta_{\text{sub.EQE}} \times \eta_{\text{sub.in}} \times \eta_{\text{sub.out}}, \quad (1)$$

where $\eta_{\text{sub.EQE}}$ is the external quantum efficiency of image source **412**, $\eta_{\text{sub.in}}$ is the in-coupling efficiency of light from image source **412** into the waveguide (e.g., substrate **420**), and $\eta_{\text{sub.out}}$ is the outcoupling efficiency of light from the waveguide towards the user's eye by output coupler **440**. Thus, the overall efficiency $\eta_{\text{sub.tot}}$ of the waveguide-based display can be improved by improving one or more of $\eta_{\text{sub.EQE}}$, $\eta_{\text{sub.in}}$, and $\eta_{\text{sub.out}}$.

(83) The optical coupler (e.g., input coupler **430** or coupler **532**) that couples the emitted light from a light source to a waveguide may include, for example, a grating, a lens, a micro-lens, a prism. In some embodiments, light from a small light source (e.g., a micro-LED) can be directly (e.g., end-to-end) coupled from the light source to a waveguide, without using an optical coupler. In some embodiments, the optical coupler (e.g., a lens or a parabolic-shaped reflector) may be manufactured on the light source.

(84) The visible light sources, image sources, or other displays described herein may include one or more LEDs, one or more organic LEDs (OLEDs), one or more VCSELs, one or more RCLEDs, or the like. It is generally desirable that the visible light sources have small pixel sizes, high brightness, high dynamic ranges, controllable emission directions, individual addressability, large color Gamut coverages, and manufacturing scalability. LEDs and OLEDs may have fundamental limitations in brightness.

(85) A VCSEL generally includes a light-emitting active region in a laser cavity that forms a laser resonator. The light-emitting active region may include quantum wells (QWs) that emit photons when properly biased. The photons may be confined in the laser cavity by a pair of mirrors, such as distributed Bragg reflection (DBR) mirrors or high-contrast grating (HCG) mirrors. In some embodiments, one DBR mirror may be n-doped and the other DBR mirror may be p-doped. In some embodiments, a p-doped layer and an n-doped layer may be used in the laser cavity and the light-emitting active region may be between the p-doped layer and the n-doped layer. VCSELs may be based on a variety of materials. For example, VCSELs with wavelengths from about 650 nm to about 1300 nm may be based on gallium arsenide (GaAs) wafers with DBRs formed by interleaved GaAs and aluminum gallium arsenide (AlGaAs) layers. In GaAs/AlGaAs VCSELs, the lattice constants of the materials do not vary significantly as the composition is changed, thus permitting multiple lattice-matched epitaxial layers to be grown on a GaAs substrate. AlGaAs-based DBRs can have a reflectivity close to 100%, which can efficiently confine photons in the laser cavity. The refractive index of AlGaAs can vary as the Al fraction is increased, thus minimizing the number of layers used to form a DBR mirror with a high reflectivity. AlGaAs-based DBRs doped with p-type or n-type impurities can also serve as current paths. Selectively oxidizing the AlGaAs layers adjacent to the QWs may laterally confine photons and carriers.

(86) FIG. 7A illustrates an example of a VCSEL **700**. VCSEL **700** may include a substrate **710**, such as a GaAs substrate or a GaN substrate. In the illustrated example, an optional bulk DBR **720** may be formed (e.g., epitaxially grown) on substrate **710**. Bulk DBR **720** may include multiple interleaved layers of different materials that have different refractive indices, such as multiple pairs of AlGaAs/GaAs or AlAs/GaAs layers, and thus may reflect light at the interfaces between the

different material layers to achieve a high overall reflectivity. A bottom DBR **730** may be formed on bulk DBR **720** or may be part of bulk DBR **720**. Bottom DBR **730** may similarly include multiple interleaved layers of different materials with different refractive indices. VCSEL **700** may also include a cladding layer **740**, an active region **750**, and a cladding layer **760**, where cladding layers **740** and **760** may be p-doped or n-doped and may inject carriers into active region **750**. Active region **750** may include one or more quantum wells or quantum dots, and QW barrier layers. Carriers may recombine in active region **750** to emit photons. A top DBR **770** may be formed on cladding layer **760**, and may be similar to bottom DBR **730**. Top DBR **770** and bottom DBR **730** (and bulk DBR **720**) may form a plane-parallel laser cavity that can confine photons. Top DBR **770**, cladding layer **760**, active region **750**, cladding layer **740**, and bottom DBR **730** may be vertically etched to form individual VCSELs of a desired size with a desired pitch on bulk DBR **720** and substrate **710**.

(87) VCSEL **700** may have a linear dimension less than about 100 μm , 50 μm , 30 μm , 20 μm , or 10 μm . For example, in some embodiments, the parallel laser cavity may have a length about 10 μm . In the example shown in FIG. 7A, bottom DBR **730** and bulk DBR **720**, in combination, may have a reflectivity close to 100% to reflect almost all incident photons. Top DBR **770** may have a reflectivity less than 100%, such that a portion of the emitted photons may be transmitted out of the laser cavity through top DBR **770**. VCSEL **700** may emit infrared light with a high efficiency and a high power, such as from about 1 mW to about 10 mW or higher.

(88) FIG. 7B illustrates an example of a tunable VCSEL **705** according to certain embodiments. The vertical cavity in tunable VCSEL **705** may be formed by a first reflector **724** and a second reflector **752**, where first reflector **724** and second reflector **752** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for IR light, and second reflector **752** may have a low reflectivity or may be anti-reflective for visible light.

(89) Tunable VCSEL **705** may include a drive circuit **712** that may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to a VCSEL **722** by, for example, die-to-wafer bonding or wafer-to-wafer bonding. Drive circuit **712** may include various circuits formed on a silicon substrate as described above, for example, with respect to FIG. 6. Drive circuit **712** may be bonded to the electrodes of VCSEL **722** to drive VCSEL **722** to generate continuous-wave (CW) or pulsed IR light having a sufficiently long duration. The intensity of the IR light emitted by VCSEL **722** and thus the intensity of the visible light from tunable VCSEL **705** may be controlled by the drive current or voltage supplied to VCSEL **722** by drive circuit **712**.

(90) VCSEL **722** may include a first electrode **732** (e.g., anode or cathode), a second electrode **734**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **732** and second electrode **734**. The semiconductor structure may include, for example, first reflector **724**, an active region **726** that may emit IR light, and other semiconductor layers (not labeled in FIG. 7B), such as cladding layers or carrier injection layers that may be p-doped or n-doped, as described above with respect to FIG. 7.

(91) First reflector **724** and second reflector **752** may each include a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) having different refractive indices and/or thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. In some embodiments, at least one of first reflector **724** or second reflector **752** may include a high-contrast grating (HCG) that may include a layer of subwavelength grating made of materials with a large refractive index contrast. The HCG may have a broad bandwidth of high reflectivity and may be used as a tunable mirror. Active region **726** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like.

(92) In the illustrated example, tunable VCSEL **705** includes a micro-electro-mechanical-system (MEMS) device **762** in the tunable vertical cavity formed by first reflector **724** and second reflector **752**, where second reflector **752** may be formed on MEMS device **762** and thus may be movable

by MEMS device **762**. In some embodiments, other micro-actuators or nano-actuators, such as a micro-motor, a piezoelectric actuator, a ferroelectric actuator, a magnetic actuator, an ultrasonic actuator, or the like, may be used to move second reflector **752**. Light emitted by VCSEL **722** and oscillating within the vertical cavity formed by first reflector **724** and second reflector **752** may be continuously tunable by tuning the location of second reflector **752** using MEMS device **762** or another actuator to tune the optical path length and thus the resonant wavelength of the vertical cavity.

(93) As described above, the spectral coverage of lasers based on III-V semiconductors (e.g., InGaN or AlGaAs) may be limited by properties (e.g., bandgaps) of available gain media. It can be very difficult to make VCSELs for some colors (e.g., green) and having high efficiencies. It may be even more challenging to manufacture visible light laser sources for multiple colors on a same chip or wafer. Furthermore, current visible light sources may typically have large sizes and thus may not be suitable for individually addressable high-density visible light source array. Integration of III-V semiconductor devices with photonic integrated circuits (PICs) may pose additional challenges to the manufacturing.

(94) According to certain embodiments, nonlinear effects of certain nonlinear gain media may be used to generate visible light in a wide spectral range using IR pump light from VCSELs. In one example, a visible semiconductor light source may include a VCSEL that may emit light in the near-infrared (NIR) or other infrared (IR) band with a high efficiency. The visible semiconductor light source may also include a micro-resonator including a third-order nonlinear material and thus may convert the IR light into visible light using degenerate four-wave mixing (also referred to as third-order optical parametric oscillation (OPO)) caused by the nonlinear optical effect (e.g., third-order nonlinear effect $\chi^{(3)}$) of the micro-resonator.

(95) Four-wave mixing is a nonlinear effect arising from a third-order optic nonlinearity (Kerr effect) described by a $\chi^{(3)}$ coefficient. Four-wave mixing can occur when light having two frequency components ν_1 and ν_2 propagate together in an optical waveguide including a third-order nonlinear medium. A refractive index modulation due to the third-order nonlinear effect may cause the generation of light having two additional frequency components ν_3 and ν_4 , where $\nu_4 = \nu_1 + \nu_2 - \nu_3$ and the light having frequencies ν_3 and ν_4 may experience parametric amplification in the nonlinear medium. This process may be referred to as non-degenerate four-wave mixing. When the two frequency components ν_1 and ν_2 of the four frequencies coincide, degenerate four-wave mixing (DFWM) may occur, where a single-frequency pump wave (e.g., having a frequency ν_p) may cause the generation and amplification of a signal wave (having a frequency ν_s) and an idler wave (having a frequency ν_i), and where a frequency phase-matching condition $2\nu_p = \nu_s + \nu_i$ may be met. The signal wave and the idler wave may generally have different frequencies.

(96) FIGS. **8A** and **8B** illustrate an example of generating a higher frequency light signal using lower frequency pump light through degenerate four-wave mixing. Two pump photons **810** having a frequency ν_p may be summed to generate a virtual excited state **815**, which may be used to generate a pair of photons **820** and **830** with frequencies ν_s and ν_i , respectively. Due to energy conservation, frequencies ν_s and ν_i of photons **820** and **830** may be symmetrical with respect to frequency ν_p of pump photons **810** (i.e., $|\nu_s - \nu_p| = |\nu_p - \nu_i|$) as show in FIG. **8B**.

(97) Four-wave mixing is a phase-sensitive process. Its effect may accumulate over a longer distance (e.g., through many loops in a ring resonator) if a phase-matching condition for constructive interference is satisfied (which may be influenced by chromatic dispersion and/or nonlinear phase shifts). A ring resonator may include a closed-loop waveguide coupled to an input coupler and/or an output coupler. When light at a resonant wavelength of the ring resonator propagates through the closed-loop waveguide, its intensity builds up over multiple round-trips due to the constructive interference between loops. Only light of a few wavelengths may resonate

within the closed-loop waveguide. The optical path length of a ring resonator may be $2\pi r \times n_{\text{sub.eff}}$, where r is the radius of the ring resonator and $n_{\text{sub.eff}}$ is the effective refractive index of the ring resonator. To meet the resonant condition for constructive interference, the optical path length of the ring (loop) may be an integer multiple of the wavelength of the resonant light: $m \times \lambda_{\text{sub.m}} = 2\pi r \times n_{\text{sub.eff}}$, where $\lambda_{\text{sub.m}}$ is the resonant wavelength and m is the mode number (a positive integer) of the ring resonator. The resonant frequency or wavelength may be tuned by changing the effective refractive index $n_{\text{sub.eff}}$ of the ring resonator and/or by changing the wavelength of the pump light.

(98) FIG. 8C illustrates multiple longitudinal resonant modes of an example of a micro-resonator (e.g., a ring resonator). FIG. 8C shows three longitudinal resonant modes $m-1$, m , and $m+1$. The full-width half-magnitude (FWHM) of the transmission spectra of a longitudinal mode is $\delta\nu$. The difference between the frequencies of two adjacent modes is the free spectral range $\nu_{\text{sub.fsr}}$. The quality factor Q and the finesse F of the micro-resonator can be described by:

$$(99) \quad Q = \frac{\nu}{\delta\nu}, \text{ and} \\ F = \frac{\nu_{\text{fsr}}}{\delta\nu},$$

where λ is the operation wavelength. The quality factor can be used to determine the spectral range of the resonance condition for a given ring resonator, and is also useful for quantifying the amount of round-trip loss in the resonator. A low Q factor may be caused by large loss. The finesse F may also relate to the resonator loss, and thus may indicate the round-trip resonator loss.

(100) OPO is an optical parametric amplification (OPA) within an optical resonator (e.g., resonant optical cavity). For example, in a ring resonator, OPO is a cavity-enhanced DFWM, where all three light waves (pump wave, signal wave, and idler wave) meet the resonance condition of the same cavity and therefore can resonate in the ring resonator to greatly enhance the nonlinear conversion through resonance-enhanced field strength build-up. Therefore, the frequency of the pump wave may be limited to a set of longitudinal resonant modes determined by the optical path length of the ring resonator at the pump wavelength. Similarly, the frequency of the signal wave may be limited to a set of longitudinal resonant modes determined by the optical path length of the ring resonator at the signal wavelength, and the frequency of the idler wave may be limited to a set of longitudinal resonant modes determined by the optical path length of the ring resonator at the idler wavelength. Using a low-loss optical resonator (e.g., a ring resonator), the nonlinear conversion efficiency can be significantly boosted ($>10\%$) within a resonator having a compact footprint (e.g., with a radius $<10 \mu\text{m}$ for some high refractive index materials such as SiC). Since the wavelength (color) of the generated signal wave can be controlled by the optical path length of the cavity to meet the resonance condition, the resonant optical cavity (e.g., ring resonator) may be designed to generate light of any color in the visible range.

(101) According to certain embodiments, the pump light for the DFWM in a resonant optical cavity (e.g., a micro-resonator) may be IR light generated by a VCSEL, where the micro-resonator may be positioned inside or outside the VCSEL cavity in either an intra-cavity configuration or an extra-cavity configuration, respectively. The IR light emitted by the VCSEL may be coupled into the micro-resonator directly or by a coupling structure (e.g., a grating coupler). In some embodiments, the IR light emitted by the VCSEL may be coupled into a waveguide by a coupling structure (e.g., a grating coupler or nano-resonators) inside or outside the VCSEL cavity and may then be coupled from the waveguide into the micro-resonator. In some embodiments, the grating coupler may include an apodized, chirped, and/or slanted grating to achieve the desired coupling direction and the desired coupling efficiency. In some embodiments, a visible light source may include multiple coupling structures in either the extra-cavity or the intra-cavity configuration.

(102) The micro-resonator may include a low-loss structure in which light may travel for a long time before being absorbed, scattered, or converted. As described above, the color of the light generated through the OPO process can be controlled by the geometry and material (and thus the

effective refractive index) of the micro-resonator. According to certain embodiments, the micro-resonator may include, for example, a micro-ring resonator as described above, a photonic crystal point defect cavity, a photonic crystal ring (line-defect) cavity, a plasmonic resonator, a waveguide grating-based resonator, or the like. For example, when a point defect is created in a photonic crystal, the defect may pull a light mode into the band gap and trap the light mode (forming a resonant cavity) because such a state is forbidden from propagating in the bulk crystal, and the density of the states at the resonant frequency can be very high in the resonant cavity to achieve a high efficiency. A photonic crystal line-defect cavity may be formed by, for example, omitting multiples holes in a photonic crystal slab.

(103) According to certain embodiments, the visible light generated by the degenerate four-wave mixing in the resonant cavity of the micro-resonator may be coupled out of the micro-resonator into a waveguide of a PIC through side coupling, or may be coupled out of the micro-resonator into free space through vertical coupling by a coupling structure, such as a grating coupler. In some embodiments, the grating coupler may include an apodized, chirped, and/or slanted grating to achieve the desired coupling direction and high coupling efficiency.

(104) FIG. 9A shows a cross-sectional view of an example of a structure **900** including a coupling structure **920** configured to vertically couple light generated in an optical resonator **910** out of optical resonator **910** according to certain embodiments. FIG. 9B shows a top view of the example of structure **900** of FIG. 9A according to certain embodiments. In the illustrated example, optical resonator **910** may include a micro-ring resonator. In some embodiments, optical resonator **910** may have a shape different from a ring shape, such as an oval shape, a racetrack shape, a spiral shape (e.g., an Archimedean spiral shape), or another closed loop. Optical resonator **910** may include a low-loss material having a third-order nonlinearity. In some embodiments, to reduce the footprint of optical resonator **910**, optical resonator **910** may include a high refractive index material, such as SiN or SiC. Coupling structure **920** may include a grating coupler formed on optical resonator **910**, where the grating coupler may be along an inner circumference of optical resonator **910**, on top or bottom of optical resonator **910**, along an outer circumference of optical resonator **910**, or any combination of the aforementioned positions. The grating coupler may include a slanted grating having a grating vector that includes a component in the z direction, such that light propagating in a ring in an x-y plane in optical resonator **910** may be vertically coupled out of optical resonator **910** by the grating coupler.

(105) FIG. 9C illustrates a top view of an example of a structure **902** configured to couple light generated in an optical resonator **930** into an output waveguide **950** according to certain embodiments. In the example shown in FIG. 9C, IR pump light from a VCSEL may be coupled from a pump waveguide **940** into optical resonator **930**, and the generated visible light (e.g., the signal wave) may be coupled into output waveguide **950**. The idler wave may be coupled into pump waveguide **940** or output waveguide **950**. In some embodiments, a wavelength-division demultiplexer may be used to separate the signal wave and the idler wave.

(106) FIG. 9D illustrates a top view of an example of a structure **904** configured to couple light generated in an optical resonator into a waveguide **980** according to certain embodiments. In the illustrated example, IR pump light from a VCSEL may be at least partially coupled from waveguide **980** into optical resonator **960**, and the generated visible light (e.g., the signal wave) may be coupled back into waveguide **980**. The idler wave may be coupled into waveguide **980** or another waveguide **970**. In some embodiments, a wavelength-division demultiplexer may be used to separate the signal wave and the uncoupled pump wave in waveguide **980**. In some embodiments, the uncoupled pump wave may be looped back into waveguide **980** and coupled into optical resonator **960**.

(107) FIG. 10A illustrates an example of a visible light source **1000** including a micro-resonator **1040** in a vertical cavity and directly pumped by an infrared light VCSEL **1020** in the vertical cavity according to certain embodiments, where visible light generated in micro-resonator **1040** is

vertically coupled out of the vertical cavity. FIG. 10B illustrates a top view of the example of visible light source **1000** of FIG. 10A. The vertical cavity in visible light source **1000** may be formed by a first reflector **1022** and a second reflector **1050**, where first reflector **1022** and second reflector **1050** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for IR light, and second reflector **1050** may have a low reflectivity or may be anti-reflective for visible light.

(108) Visible light source **1000** may include a drive circuit **1010** that may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to VCSEL **1020** by, for example, die-to-wafer bonding or wafer-to-wafer bonding. Drive circuit **1010** may include various circuits formed on a silicon substrate as described above, for example, with respect to FIG. 6. Drive circuit **1010** may be bonded to the electrodes of VCSEL **1020** to drive VCSEL **1020** to generate continuous-wave (CW) or pulsed IR light having a sufficiently long duration. The intensity of the IR light emitted by VCSEL **1020** and thus the intensity of the visible light from visible light source **1000** may be controlled by the drive current or voltage supplied to VCSEL **1020** by drive circuit **1010**.

(109) VCSEL **1020** may include a first electrode **1030** (e.g., anode or cathode), a second electrode **1032**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1030** and second electrode **1032**. The semiconductor structure may include, for example, first reflector **1022**, an active region **1024** that may emit IR light, and other semiconductor layers (not labeled in FIG. 10A), such as cladding layers or carrier injection layers that may be p-doped or n-doped, as described above with respect to FIG. 7. First reflector **1022** may include, for example, a high-contrast grating (HCG) as described with respect to FIG. 7, or a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) having different refractive indices and/or thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. Active region **1024** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like.

(110) In some embodiments, VCSEL **1020** may include a partial reflector **1026** for IR light, where the partial reflector may partially reflect and partially transmit IR light emitted in active region **1024** to form a resonant cavity for VCSEL **1020** with first reflector **1022**. The resonant cavity formed by partial reflector **1026** and first reflector **1022** may help to narrow and select the output wavelength range of the IR light and improve the gain and the intensity of the emitted IR light. In some embodiments, VCSEL **1020** may include a polarizer **1028**. Polarizer **1028** may be used to control the polarization state of IR light emitted by VCSEL **1020** and improve the coupling efficiency of the IR light into micro-resonator **1040** by, for example, a grating coupler or nano-resonators (e.g., meta-structures), which may be polarization dependent. In some embodiments, other polarization components, such as a waveplate, a spatially-variant polarizer, or a spatially-variant waveplate, may be used instead to control the polarization state of IR light emitted by VCSEL **1020**.

(111) The IR light emitted by VCSEL **1020** may be coupled into micro-resonator **1040** directly or through a coupling structure, such as a slanted grating or nano-resonators. As described above, micro-resonator **1040** may include a closed-looped waveguide having any suitable shape (e.g., a ring, oval, spiral, or racetrack shape) and having a low loss such that a photon may propagate in the closed-looped waveguide for a long period of time (e.g., about a thousand or more loops) before being absorbed, scattered, or converted. The waveguide material may have a third-order nonlinearity such that the OPO (e.g., DFWM) process may occur in the closed-looped waveguide. The material and geometry of micro-resonator **1040** may be selected such that the IR light coupled into micro-resonator **1040**, and the visible light (signal wave) and idler wave generated by the DFWM process may resonate in micro-resonator **1040**, which may enhance the DFWM process. In some embodiments, micro-resonator **1040** may include a material that has a high refractive index,

such that the physical dimension of micro-resonator **1040** may be reduced while achieving the desired optical path length of the closed-looped waveguide. VCSEL **1020** and micro-resonator **1040** may be surrounded by dielectric materials **1060**, which may include, for example, an oxide such as silicon dioxide or a polymer material. In some embodiments, visible light source **1000** may include two or more micro-resonators arranged vertically and configured to generate visible light of the same color.

(112) Visible light generated in micro-resonator **1040** by the DFWM process may be vertically coupled out of micro-resonator **1040** by a coupling structure **1042**, which may include a grating or nano-resonators as described above, for example, with respect to FIGS. **9A** and **9B**. The visible light coupled out of micro-resonator **1040** may be transmitted by second reflector **1050** with little or no loss since second reflector **1050** may be anti-reflective for visible light as described above. As first reflector **1022**, second reflector **1050** may include, for example, an HCG, or a DBR structure formed by multiple dielectric, semiconductor, or metallic material layers having alternating refractive indices. The thicknesses and refractive indices of the dielectric, semiconductor, or metallic material layers in the DBR structure may be selected such that IR light reflected at adjacent interfaces between different materials may constructively interfere to increase the overall reflectivity of second reflector **1050** for IR light, while visible light reflected at adjacent interfaces between different materials may destructively interfere to reduce the overall reflectivity of second reflector **1050** for visible light. As such, IR light emitted by VCSEL **1020** and not coupled into micro-resonator **1040** may be reflected back to micro-resonator **1040** by second reflector **1050** and/or first reflector **1022**, and may be at least partially coupled into micro-resonator **1040** to improve the efficiency of coupling the IR light into micro-resonator **1040** and thus the efficiency of visible light source **1000**. Micro-resonator **1040**, coupling structure **1042**, and second reflector **1050** may be formed before or after bonding VCSEL **1020** to drive circuit **1010**.

(113) FIG. **11A** illustrates an example of a visible light source **1100** including a micro-resonator **1150** outside of a vertical cavity and directly pumped by an infrared light VCSEL **1120** according to certain embodiments. FIG. **11B** illustrates a top view of the example of visible light source **1100** of FIG. **11A**. Visible light source **1100** may include a drive circuit **1110** that may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to VCSEL **1120** by, for example, die-to-wafer bonding or wafer-to-wafer bonding. Drive circuit **1110** may include various circuits formed on a silicon substrate as described above, for example, with respect to FIG. **6**. Drive circuit **1110** may be bonded to the electrodes of VCSEL **1120** to drive VCSEL **1120** to generate continuous-wave (CW) or pulsed IR light having a sufficiently long duration and a desired intensity. The intensity of the IR light emitted by VCSEL **1120** and thus the intensity of the visible light from visible light source **1100** may be controlled by the drive current or voltage supplied to VCSEL **1120** by drive circuit **1110**.

(114) VCSEL **1120** may include a first electrode **1140** (e.g., anode or cathode), a second electrode **1142**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1140** and second electrode **1142**. The semiconductor structure may include, for example, a first reflector **1122**, an active region **1124** that may emit IR light, and other semiconductor layers (not labeled in FIG. **11A**), such as cladding layers or carrier injection layers that may be p-doped or n-doped, as described above with respect to FIG. **7**. First reflector **1122** may include, for example, an HCG, or a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) of different refractive indices and thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. First reflector **1122** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for IR light. Active region **1124** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like. VCSEL **1120** may also include a second reflector **1130** that may be a partial reflector configured to reflect a portion of the IR light emitted by active region **1124** while transmitting a portion of the IR light emitted by

active region **1124**. Second reflector **1130** may include, for example, an HCG, or a DBR structure formed by conductive materials, such as GaAs and AlAs (or AlGaAs). First reflector **1122** and second reflector **1130** may form the vertical cavity in visible light source **1100**. The vertical cavity may help to narrow and select the output wavelength range of the IR light and improve the gain and the intensity of the emitted IR light. In some embodiments, VCSEL **1120** may include a polarizer (not shown in FIG. **11A**) as described above with respect to FIG. **10A**. The polarizer may be used to control the polarization mode of IR light emitted by VCSEL **1120** and improve the coupling efficiency of the IR light into micro-resonator **1150** by, for example, a grating coupler or nano-resonators (e.g., meta-structures), which may be polarization dependent.

(115) The IR light emitted by VCSEL **1120** may be coupled into micro-resonator **1150** directly or through a coupling structure, such as a slanted grating or nano-resonators. As described above, micro-resonator **1150** may include a closed-looped waveguide having any suitable shape (e.g., a ring, oval, spiral, racetrack shape) and having a low loss such that a photon may propagate in the closed-looped waveguide for a long period of time (e.g., about a thousand or more loops) before being absorbed, scattered, or converted. The waveguide material may have a third-order nonlinearity such that the OPO (e.g., DFWM) process may occur in the closed-looped waveguide. The size and material of micro-resonator **1150** may be selected such that the IR light coupled into micro-resonator **1150**, and the visible light (signal wave) and idler wave generated by the DFWM process may resonate in micro-resonator **1150**, which may enhance the DFWM process. In some embodiments, micro-resonator **1150** may include a material that has a high refractive index (e.g., SiN, SiC, etc.), such that the physical dimension of micro-resonator **1150** may be reduced while achieving the desired optical path length of the closed-looped waveguide. VCSEL **1120** and micro-resonator **1150** may be surrounded by dielectric materials **1160**, which may include, for example, an oxide such as silicon dioxide.

(116) Visible light generated in micro-resonator **1150** by the DFWM process may be vertically coupled out of micro-resonator **1150** by a coupling structure **1152**, which may include a grating or nano-resonators as described above, for example, with respect to FIGS. **9A** and **9B**. The visible light coupled out of micro-resonator **1150** may be vertically coupled out of visible light source **1100**. Micro-resonator **1150** and coupling structure **1152** may be formed before or after bonding VCSEL **1120** to drive circuit **1110**. In some embodiments, the visible light generated in micro-resonator **1150** may be coupled to a waveguide as described with respect to FIGS. **9C** and **9D**.

(117) In some embodiments, a feedback cavity structure (a DBR structure or a hot mirror that reflects IR light and transmits visible light) may be formed on top of micro-resonator **1150** and coupling structure **1152** to redirect IR light that is not coupled into micro-resonator **1150** yet back to micro-resonator **1150** to improve the efficiency of coupling the IR pump light into micro-resonator **1150** and the efficiency of visible light source **1100**.

(118) FIG. **12A** illustrates an example of a visible light source **1200** including a micro-resonator **1260** pumped by an infrared light VCSEL **1220** according to certain embodiments, where the infrared light is coupled into the micro-resonator through an input coupling structure and a waveguide on a same layer as micro-resonator **1260**. FIG. **12B** illustrates a top view of the example of visible light source **1200** of FIG. **12A**. Visible light source **1200** may include a drive circuit **1210** that may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to VCSEL **1220** by, for example, die-to-wafer or wafer-to-wafer bonding. Drive circuit **1210** may include various circuits formed on a silicon substrate as described above, for example, with respect to FIG. **6**. Drive circuit **1210** may be bonded to the electrodes of VCSEL **1220** to drive VCSEL **1220** to generate continuous-wave (CW) or pulsed IR light having a sufficiently long duration and a desired intensity. The intensity of the IR light emitted by VCSEL **1220** and thus the intensity of the visible light from visible light source **1200** may be controlled by the drive current or voltage supplied to VCSEL **1220** by drive circuit **1210**.

(119) VCSEL **1220** may be similar to VCSEL **1120** and may include a first electrode **1240** (e.g.,

anode or cathode), a second electrode **1242**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1240** and second electrode **1242**. The semiconductor structure may include, for example, a first reflector **1222**, an active region **1224** that may emit IR light, and other semiconductor layers (not labeled in FIG. **12A**), such as cladding layers or carrier injection layers that may be p-doped or n-doped, as described above with respect to FIG. **7**. First reflector **1222** may include, for example, an HCG, or a DBR reflector formed by multiple pairs of dielectric or doped or undoped semiconductor materials of different refractive indices and thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. First reflector **1222** may have a high reflectivity (e.g., >80, >85%, >90%, >95%, >99%, or higher) for IR light. Active region **1224** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like. VCSEL **1220** may also include a second reflector **1230** that may be a partial reflector configured to reflect a portion of the IR light emitted by active region **1224** while transmitting a portion of the IR light emitted by active region **1224**. Second reflector **1230** may include, for example, an HCG, or a DBR structure formed by conductive materials, such as doped or undoped GaAs and AlAs (or AlGaAs). First reflector **1222** and second reflector **1230** may form the vertical cavity in visible light source **1200**. The vertical cavity may help to select the output wavelength range of the IR light and improve the gain and the intensity of the emitted IR light. In some embodiments, VCSEL **1220** may include a polarization element (e.g., a polarizer, a waveplate, a spatially-variant polarizer, or a spatially-variant waveplate, which is not shown in FIG. **12A**) as described above with respect to FIG. **10A**. The polarizer may be used to control the polarization mode of IR light emitted by VCSEL **1220** and improve the coupling efficiency of the IR light into micro-resonator **1260** by, for example, a grating coupler or nano-resonators (e.g., meta-structures), which may be polarization dependent.

(120) The IR light emitted by VCSEL **1220** may be coupled into a waveguide **1250** directly or through a coupling structure **1252** (which may be above or below waveguide **1250**), such as a slanted grating or nano-resonators. The IR light propagating in waveguide **1250** may be coupled into micro-resonator **1260**. In the illustrated example, waveguide **1250** and micro-resonator **1260** may be on a same waveguide material layer (e.g., a SiN or SiC layer). As described above, micro-resonator **1260** may include a closed-looped waveguide having any suitable shape (e.g., a ring, oval, spiral, racetrack shape) and having a low loss such that a photon may propagate in the closed-looped waveguide for a long period of time (e.g., about one thousand or more loops) before being absorbed, scattered, or converted. The waveguide material may have a third-order nonlinearity such that the OPO (e.g., DFWM) process may occur in the closed-looped waveguide. The geometry and material of micro-resonator **1260** may be selected such that the IR light coupled into micro-resonator **1260**, and the visible light (signal wave) and idler wave generated by the DFWM process may resonate in micro-resonator **1260**, which may enhance the DFWM process. In some embodiments, micro-resonator **1260** may include a material (e.g., SiN, SiC, etc.) that has a high refractive index, such that the physical dimension of micro-resonator **1260** may be reduced while achieving the desired optical path length of the closed-looped waveguide. VCSEL **1220**, waveguide **1250**, and micro-resonator **1260** may be surrounded by dielectric materials **1270**, which may include, for example, an oxide such as silicon dioxide.

(121) In some embodiments, visible light generated in micro-resonator **1260** by the DFWM process may be vertically coupled out of micro-resonator **1260** by a coupling structure, such as a grating or nano-resonators described above. The visible light coupled out of micro-resonator **1260** may be vertically coupled out of visible light source **1200** into free space. In some embodiments, visible light generated in micro-resonator **1260** may be coupled to a waveguide (e.g., waveguide **1250** or another waveguide closely coupled to micro-resonator **1260**) and a photonic integrated circuit as described with respect to FIGS. **9C** and **9D**.

(122) In some embodiments, a feedback cavity structure (a DBR structure or a hot mirror that

reflects IR light and transmits visible light) may be formed on top of waveguide **1250** and coupling structure **1252** to redirect IR light that is not coupled into waveguide **1250** yet back to waveguide **1250** to improve the efficiency of coupling the IR pump light into waveguide **1250** and the efficiency of visible light source **1200**.

(123) FIG. **12C** illustrates an example of a visible light source **1202** including a micro-resonator **1262** pumped by infrared light VCSEL **1220** according to certain embodiments, where the infrared light is coupled into micro-resonator **1262** through coupling structure **1252** and waveguide **1250** that is on a different vertical layer from micro-resonator **1262**. FIG. **12D** illustrates a top view of the example of visible light source **1202** of FIG. **12C**. Visible light source **1202** may be similar to visible light source **1200** but may differ in, for example, in visible light source **1202**, micro-resonator **1262** and waveguide **1250** are on different waveguide layers. In the illustrated example, micro-resonator **1262** may be above waveguide **1250**. In some embodiments, micro-resonator **1262** may be below waveguide **1250**. Even though not shown in FIGS. **12C** and **12D**, visible light source **1202** may include a coupling structure (e.g., a grating or nano-resonators) configured to vertically couple visible light generated in micro-resonator **1262** out of micro-resonator **1262**, or may include a waveguide closely coupled to micro-resonator **1262** and configured to couple visible light generated in micro-resonator **1262** into a photonic integrated circuit.

(124) FIG. **13A** illustrates yet another example of a visible light source **1300** including a micro-resonator **1370** pumped by an infrared light VCSEL **1320** in a vertical cavity according to certain embodiments, where the infrared light is coupled into micro-resonator **1370** through an input coupling structure **1352** in the vertical cavity and a waveguide **1350** on a same vertical layer as micro-resonator **1370**. FIG. **13B** illustrates a top view of the example of visible light source **1300** of FIG. **13A**. The vertical cavity in visible light source **1300** may be formed by a first reflector **1322** and a second reflector **1330**, where first reflector **1322** and second reflector **1330** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for IR light.

(125) Visible light source **1300** may include a drive circuit **1310** that may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to VCSEL **1320** by, for example, die-to-wafer or wafer-to-wafer bonding. Drive circuit **1310** may include various circuits formed on a silicon substrate as described above, for example, with respect to FIG. **6**. Drive circuit **1310** may be bonded to the electrodes of VCSEL **1320** to drive VCSEL **1320** to generate continuous-wave (CW) or pulsed IR light having a sufficiently long duration and a desired intensity. The intensity of the IR light emitted by VCSEL **1320** and thus the intensity of the visible light from visible light source **1300** may be controlled by the drive current or voltage supplied to VCSEL **1320** by drive circuit **1310**.

(126) VCSEL **1320** may include a first electrode **1340** (e.g., anode or cathode), a second electrode **1342**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1340** and second electrode **1342**. The semiconductor structure may include, for example, first reflector **1322**, an active region **1324** that may emit IR light, and other semiconductor layers (not labeled in FIG. **13A**), such as cladding layers or carrier injection layers that may be p-doped or n-doped, as described above with respect to FIG. **7**. First reflector **1322** may include, for example, an HCG, or a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) of different refractive indices and thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. Active region **1324** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like.

(127) In some embodiments, VCSEL **1320** may include a partial reflector **1326** for IR light, where the partial reflector may partially reflect and partially transmit IR light emitted in active region **1324** to form a resonant cavity for VCSEL **1320** with first reflector **1322**. The resonant cavity formed by partial reflector **1326** and first reflector **1322** may help to narrow and select the output wavelength range of the IR light and improve the gain and the intensity of the emitted IR light. In

some embodiments, VCSEL **1320** may include a polarizer **1328**. Polarizer **1328** may be used to control the polarization mode of IR light emitted by VCSEL **1320** and improve the coupling efficiency of the IR light into waveguide **1350** by input coupling structure **1352** (e.g., a grating coupler or nano-resonators), which may be polarization dependent. In some embodiments, other polarization components, such as a waveplate, a spatially-variant polarizer, or a spatially-variant waveplate, may be used instead to control the polarization state of IR light emitted by VCSEL **1320**.

(128) The IR light emitted by VCSEL **1320** may be coupled into waveguide **1350** by input coupling structure **1352**, such as a slanted grating or nano-resonators (e.g., meta-structures). The IR light propagating in waveguide **1350** may be coupled into micro-resonator **1370**. In the illustrated example, waveguide **1350** and micro-resonator **1370** may be on a same waveguide material layer (e.g., a SiN or SiC layer). As described above, micro-resonator **1370** may include a closed-looped waveguide having any suitable shape (e.g., a ring, oval, spiral, racetrack shape) and having a low loss such that a photon may propagate in the closed-looped waveguide for a long period of time (e.g., about 1 million or more loops) before being absorbed, scattered, or converted. The waveguide material may have a third-order nonlinearity, such that an OPO (e.g., DFWM) process may occur in the closed-looped waveguide. The size and material of micro-resonator **1370** may be selected such that the IR light coupled into micro-resonator **1370**, and the visible light (signal wave) and idler wave generated by the DFWM process may resonate in micro-resonator **1370**, which may enhance the DFWM process. In some embodiments, micro-resonator **1370** may include a material (e.g., SiN, SiC, or the like) that has a high refractive index, such that the physical dimension of micro-resonator **1370** may be reduced while still achieving the desired optical path length of the closed-looped waveguide. VCSEL **1320**, waveguide **1350**, and micro-resonator **1370** may be surrounded by dielectric materials **1360**, which may include, for example, an oxide such as silicon dioxide.

(129) In some embodiments, visible light generated in micro-resonator **1370** by the DFWM process may be vertically coupled out of micro-resonator **1370** by a coupling structure, such as a grating or nano-resonators described above. The visible light coupled out of micro-resonator **1370** may be vertically coupled out of visible light source **1300**. In some embodiments, visible light generated in micro-resonator **1370** may be coupled to a waveguide (e.g., waveguide **1350** or another waveguide closely coupled to micro-resonator **1370**) and a photonic integrated circuit as described with respect to FIGS. **9C** and **9D**.

(130) As first reflector **1322**, second reflector **1330** may include, for example, an HCG, or a DBR structure formed by multiple dielectric, semiconductor, or metallic material layers having alternating refractive indices. The thicknesses and refractive indices of the dielectric, semiconductor, or metallic material layers in the DBR structure may be selected such that IR light reflected at adjacent interfaces between different materials may constructively interfere to increase the overall reflectivity of second reflector **1330** for IR light. As such, IR light that is emitted by VCSEL **1320** and is not coupled into waveguide **1350** yet may be reflected back to waveguide **1350** by second reflector **1330** and/or first reflector **1322**, and may be at least partially coupled into waveguide **1350** to improve the efficiency of coupling the IR pump light into micro-resonator **1370** and the efficiency of visible light source **1300**.

(131) FIG. **13C** illustrates an example of a visible light source **1302** including a micro-resonator **1372** pumped by infrared light VCSEL **1320** according to certain embodiments, where infrared light emitted by infrared light VCSEL **1320** is coupled into micro-resonator **1372** through input coupling structure **1352** in the vertical cavity and waveguide **1350** on a different vertical layer from micro-resonator **1372**. FIG. **13D** illustrates a top view of the example of visible light source **1302** of FIG. **13C**. Visible light source **1302** may be similar to visible light source **1300** but may differ in, for example, in visible light source **1302**, micro-resonator **1372** and waveguide **1350** are on different waveguide layers. In the illustrated example, micro-resonator **1372** may be above waveguide **1350**. In some embodiments, micro-resonator **1372** may be below waveguide **1350**.

Even though not shown in FIGS. 13C and 13D, visible light source **1302** may include a coupling structure (e.g., a grating or nano-resonators) configured to vertically couple visible light generated in micro-resonator **1372** out of micro-resonator **1372**, or may include a waveguide closely coupled to micro-resonator **1372** and configured to couple visible light generated in micro-resonator **1372** into a photonic integrated circuit.

(132) In color image display systems, it may be desirable to integrate visible light sources for multiple colors on a same chip. To improve resolution of the displayed images, it may also be desirable to use a high-density source array with a large number of individually addressable light sources. Current visible light sources may generally have large footprints and may not be suitable for high-density source arrays with individual addressable light sources. VCSEL-pumped visible light sources described above may be used to make a high-density source array that includes individual addressable light sources for visible light of different colors.

(133) According to certain embodiments, a device may include an array of visible light sources, where the visible light sources may emit visible light of different colors, such as red, blue, or green. In one example, each visible light source may include one micro-resonator, and the micro-resonators (and/or VCSELs) in some visible light sources may be different from the micro-resonators (and/or VCSELs) in some other visible light sources, such that the visible light sources may emit light of different colors. In some embodiments, each visible light source in the array of visible light source may be configured or tunable to emit light of different colors. For example, each visible light source may include a pump VCSEL and multiple micro-resonators having different parameters, where each of the multiple micro-resonators may be configured to generate visible light of a different respective color, and, in some embodiments, each of the multiple micro-resonators may be tuned to adjust the intensity of the visible light generated by the micro-resonator. In some embodiments, a visible light source may include a tunable pump VCSEL (having a tunable cavity) that may be tuned to emit pump light having different wavelengths, and a micro-resonator that may have multiple resonant modes and may generate visible light of different colors using the pump light having different wavelengths.

(134) FIG. 14A illustrates an example of an array of visible light sources **1400** configured to emit visible light of different colors according to certain embodiments, where each visible light source in the array includes a micro-resonator in a vertical cavity and directly pumped by an infrared light VCSEL in the vertical cavity, and the visible light generated in the micro-resonator is coupled vertically out of the vertical cavity. FIG. 14A shows a red light source **1406**, a green light source **1404**, and a blue light source **1402** in the array of visible light sources **1400**. Each light source shown in FIG. 14A may be an example of visible light source **1000** or **1100**, and the visible light sources in the array of visible light sources may be fabricated on a same wafer or a same die. The wafer or die may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to a drive circuit **1410**, such as a CMOS backplane, using various wafer-to-wafer bonding techniques or die-to-wafer bonding techniques.

(135) Each light source **1402**, **1404**, or **1406** may include a VCSEL **1420** that emits IR light. As described above with respect to, for example, FIGS. 10 and 11, VCSEL **1420** may include a first electrode **1430** (e.g., anode or cathode), a second electrode **1432**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1430** and second electrode **1432**. The semiconductor structure may include, for example, first reflector **1422**, an active region **1424** that may emit IR light, and other semiconductor layers (not labeled in FIG. 14A), such as cladding layers or carrier injection layers that may be p-doped or n-doped, as described above with respect to FIG. 7. First reflector **1422** may include, for example, an HCG, or a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) of different refractive indices and thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. Active region **1424** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and

AlGaAs barrier layers, or the like. VCSELs **1420** in light sources **1402**, **1404**, and **1406** may have the same structure and may emit IR light at about the same wavelength. In some embodiments, VCSEL **1420** may include a partial reflector for IR light (such as partial reflector **1026**, not shown in FIG. **14A**), where the partial reflector may partially reflect and partially transmit IR light emitted in active region **1424** to form a resonant cavity for VCSEL **1420** with first reflector **1422**. The resonant cavity formed by the partial reflector and first reflector **1422** may help to narrow and select the output wavelength range of the IR light emitted by VCSELs **1420** and improve the gain and the intensity of the emitted IR light. In some embodiments, VCSEL **1420** may include a polarizer (not shown in FIG. **14A**), such as polarize **1028**. The polarizer may be used to control the polarization mode of IR light emitted by VCSEL **1420** and improve the coupling efficiency of the IR light into the micro-resonator by, for example, a grating coupler or nano-resonators (e.g., meta-structures), which may be polarization dependent.

(136) In the illustrated example, each light source **1402**, **1404**, or **1406** may include a micro-resonator, where the micro-resonator for each light source **1402**, **1404**, or **1406** may have a different respective design and thus may generate visible light of different wavelengths. The different respective design may include a different combination of, for example, loop shape (e.g., ring, oval, spiral, racetrack, etc.), dimension, material (and thus refractive index), and the like. For example, red light source **1406** may include a micro-resonator **1444**, the shape, dimension, and material of which may be selected such that red light may be generated in micro-resonator **1444** by DFWM using the IR light emitted by VCSEL **1420** as the pump light. Red light source **1406** may also include a coupling structure **1454** configured to vertically couple the red light generated in micro-resonator **1444** out of micro-resonator **1444**. Similarly, green light source **1404** may include a micro-resonator **1442** configured such that green light may be generated in micro-resonator **1442** by DFWM using the IR light emitted by VCSEL **1420** as the pump light, and may include a coupling structure **1452** configured to vertically couple the green light generated in micro-resonator **1442** out of micro-resonator **1442**. Blue light source **1402** may include a micro-resonator **1440** configured such that green light may be generated in micro-resonator **1440** by DFWM using the IR light emitted by VCSEL **1420** as the pump light, and may include a coupling structure **1450** configured to vertically couple the blue light generated in micro-resonator **1440** out of micro-resonator **1440**.

(137) As illustrated, each light source **1402**, **1404**, or **1406** may also include a second reflector **1460**, **1462**, or **1464** configured to reflect IR light that is emitted by VCSEL **1420** but has not been coupled into the micro-resonator yet back to the micro-resonator or a coupling structure for coupling the IR light into the micro-resonator. Second reflector **1460**, **1462**, or **1464** may have a close to 100% reflectivity for IR light emitted by VCSEL **1420** and may have a close to 0% reflectivity for the visible light generated in the corresponding micro-resonators and coupled out of the corresponding micro-resonators by corresponding coupling structures. For example, second reflector **1460** may be anti-reflective for blue light, second reflector **1462** may be anti-reflective for green light, and second reflector **1464** may be anti-reflective for red light.

(138) FIGS. **14B** and **14C** illustrate top views of examples of the array of visible light sources **1400**. The examples of the array of visible light sources **1400** shown in FIGS. **14B** and **14C** may be used as an active display panel or may be used as the light sources for the backlight units of liquid crystal displays, such as liquid crystal on silicon (LCOS) displays. In the illustrated examples, red light sources **1406** may be grouped in some columns, green light sources **1404** may be grouped in some other columns, and blue light sources **1402** may be grouped in some other columns, where the columns of light sources for different colors may be interleaved. In some embodiments, light sources **1402**, **1404**, and **1406** may be arranged in other manners. For example, the array of visible light sources may include pixel units arranged in a two-dimensional array, where each pixel unit may include a red light source **1406**, a green light source **1404**, and a blue light source **1402** arranged on the vertices of a triangle. The light sources of different colors in an array of light

sources may be fabricated on a same wafer or a same die using a same process, rather than being manufactured separately and then pick-and-placed on a CMOS backplane. The pitch of the array of visible light sources **1400** and the size of each light source may be selected based on the applications. In some embodiments, the diameters of each light source may be less than about 50 μm , less than about 30 μm , less than about 20 μm , or less than about 10 μm . The pitch of the array of visible light sources **1400** may also be less than about 50 μm , less than about 30 μm , less than about 20 μm , or less than about 10 μm .

(139) FIGS. **15A** and **15B** illustrate an example of an array of visible light sources **1500** according to certain embodiments, where each visible light source **1502** may emit visible light in multiple colors. Each visible light source **1502** in the array of visible light sources **1500** includes multiple micro-resonators positioned in a vertical cavity formed by a first reflector **1522** and a second reflector **1530**, where the multiple micro-resonators are pumped by a same IR-emitting VCSEL **1520** in the vertical cavity to generate visible light of different colors. First reflector **1522** and second reflector **1530** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for IR light. In some embodiments, first reflector **1522** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for visible light. Second reflector **1530** may be anti-reflective for visible light. The visible light of different colors generated in the micro-resonators is vertically coupled out of the micro-resonators by respective coupling structures, and may be transmitted out of the vertical cavity through second reflector **1530**.

(140) As illustrated, visible light source **1502** may include a drive circuit **1510** formed on a CMOS backplane, where the CMOS backplane may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to a wafer including VCSELs **1520** fabricated thereon. The multiple micro-resonators and second reflector **1530** may be formed before or after bonding the wafer including VCSELs **1520** to the CMOS backplane. VCSEL **1520** may include a first electrode **1540** (e.g., anode or cathode), a second electrode **1542**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1540** and second electrode **1542**. The semiconductor structure may include, for example, first reflector **1522**, an active region **1524** that may emit IR light, and other semiconductor layers (not labeled in FIG. **15A**), such as cladding layers or carrier injection layers that may be p-doped or n-doped. First reflector **1522** may include, for example, an HCG, or a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) of different refractive indices and thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. Active region **1524** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like. In some embodiments, VCSEL **1520** may include a partial reflector **1526** for IR light, where partial reflector **1526** may partially reflect and partially transmit IR light emitted in active region **1524** to form a resonant cavity for VCSEL **1520** with first reflector **1522**. The resonant cavity formed by partial reflector **1526** and first reflector **1522** may help to narrow and select the output wavelength range of the IR light emitted by VCSEL **1520** and improve the gain and the intensity of the emitted IR light. In some embodiments, VCSEL **1520** may include a polarizer **1528**. Polarizer **1528** may be used to control the polarization mode of IR light emitted by VCSEL **1520** and improve the coupling efficiency of the IR light into the micro-resonator by, for example, a grating coupler or nano-resonators (e.g., meta-structures), which may be polarization dependent. In some embodiments, other polarization components, such as a waveplate, a spatially-variant polarizer, or a spatially-variant waveplate, may be used instead to control the polarization state of IR light emitted by VCSEL **1520**.

(141) In the illustrated example, each visible light source **1502** may include a first micro-resonator **1550**, a second micro-resonator **1560**, and a third micro-resonator **1570** for generating visible light of different colors using IR light emitted by VCSEL **1520** as pump light in DFWM processes. First micro-resonator **1550**, second micro-resonator **1560**, and third micro-resonator **1570** may have

different respective designs, and thus may generate visible light of different colors using the same pump light. The different respective designs may include different combinations of, for example, loop shape (e.g., ring, oval, spiral, racetrack, etc.), dimension, material (and thus refractive index), and the like. For example, the shape, dimension, and material of third micro-resonator **1570** may be selected such that red light may be generated in third micro-resonator **1570** by DFWM using the IR light emitted by VCSEL **1520** as the pump light. A coupling structure **1572** (e.g., a grating or nano-resonators) may be configured to vertically couple the red light generated in third micro-resonator **1570** out of third micro-resonator **1570**. Similarly, the shape, dimension, and material of second micro-resonator **1560** may be selected such that green light may be generated in second micro-resonator **1560** by DFWM using the IR light emitted by VCSEL **1520** as the pump light. A coupling structure **1562** (e.g., a grating or nano-resonators) may be configured to vertically couple the green light generated in second micro-resonator **1560** out of second micro-resonator **1560**. The shape, dimension, and material of first micro-resonator **1550** may be selected such that blue light may be generated in first micro-resonator **1550** by DFWM using the IR light emitted by VCSEL **1520** as the pump light. A coupling structure **1552** (e.g., a grating or nano-resonators) may be configured to vertically couple the blue light generated in first micro-resonator **1550** out of first micro-resonator **1550**. First micro-resonator **1550**, second micro-resonator **1560**, and third micro-resonator **1570** may be arranged vertically in any suitable order. In some embodiments, each visible light source **1502** may include two or more different micro-resonators configured to generate visible light in two or more colors. In some embodiments, each visible light source **1502** may include multiple micro-resonators, where at least two of the micro-resonators may be configured to generate visible light of the same color.

(142) The visible light coupled out of first micro-resonator **1550**, second micro-resonator **1560**, and third micro-resonator **1570** may be coupled out of visible light source **1502** through second reflector **1530** with little or no loss since second reflector **1530** may be anti-reflective for visible light as described above. As first reflector **1522**, second reflector **1530** may include, for example, an HCG, or a DBR structure formed by multiple dielectric, semiconductor, or metallic material layers having alternating refractive indices. The thicknesses and refractive indices of the dielectric, semiconductor, or metallic material layers in the DBR structure may be selected such that IR light reflected at adjacent interfaces between different materials may constructively interfere to increase the overall reflectivity of second reflector **1530** for IR light, while visible light reflected at adjacent interfaces between different materials may destructively interfere to reduce the overall reflectivity of second reflector **1530** for visible light. As such, IR light that is emitted by VCSEL **1520** and is not coupled into the micro-resonators yet may be reflected back to the micro-resonators by second reflector **1530** and/or first reflector **1522**, and may be at least partially coupled into the micro-resonators to improve the efficiency of coupling the IR pump light into the micro-resonators and the efficiency of visible light source **1502**. Thus, each visible light source **1502** may emit visible light in different colors at the same time, where the intensity of the emitted visible light in different colors may be controlled by the drive voltage or current from drive circuit **1510**. In the example shown in FIGS. **15A** and **15B**, the respective intensity of the visible light in each color emitted by a same visible light source may not be individually controllable. Thus, the array of visible light sources **1500** may be used as light sources in BLU display, but may not be used as display pixels for an active display panel. The micro-resonators, the coupling structures, and second reflector **1530** in visible light source **1502** may be formed before or after bonding VCSEL **1520** to drive circuit **1510**.

(143) FIGS. **16A** and **16B** illustrate an example of an array of visible light sources **1600** according to certain embodiments, where each visible light source **1602** is configured to emit visible light in multiple colors and the respective intensity of the visible light in each color is individually controllable. Compared with the array of visible light sources **1500**, the array of visible light sources **1600** may not only have individual control over each visible light source **1602**, but also

have individual control over the micro-resonators in a same visible light source **1602** such that the respective intensity of the emitted visible light in each color may be individually tunable.

(144) As illustrated in FIG. **16A**, each visible light source **1602** in the array of visible light sources **1600** includes multiple micro-resonators in a vertical cavity formed by a first reflector **1622** and a second reflector **1630**, where the multiple micro-resonators are pumped by a same IR VCSEL **1620** in the vertical cavity to generate visible light of different colors. First reflector **1622** and second reflector **1630** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for IR light. In some embodiments, first reflector **1622** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for visible light. Second reflector **1630** may be anti-reflective for visible light. The visible light of different colors generated in the micro-resonators is vertically coupled out of the micro-resonators by respective coupling structures, and may be transmitted out of the vertical cavity through second reflector **1630**.

(145) Visible light source **1602** may include a drive circuit **1610** formed on a CMOS backplane, where the CMOS backplane may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to a wafer including VCSELs **1620** fabricated thereon. The multiple micro-resonators and second reflector **1630** may be formed before or after bonding the wafer including VCSELs **1620** to the CMOS backplane. VCSEL **1620** may include a first electrode **1640** (e.g., anode or cathode), a second electrode **1642**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1640** and second electrode **1642**. The semiconductor structure may include, for example, first reflector **1622**, an active region **1624** that may emit IR light, and other semiconductor layers (not labeled in FIG. **16A**), such as cladding layers or carrier injection layers that may be p-doped or n-doped. First reflector **1622** may include, for example, an HCG, or a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) of different refractive indices and thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. Active region **1624** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like. In some embodiments, VCSEL **1620** may include a partial reflector **1626** for IR light, where partial reflector **1626** may partially reflect and partially transmit IR light emitted in active region **1624** to form a resonant cavity for VCSEL **1620** with first reflector **1622**. The resonant cavity formed by partial reflector **1626** and first reflector **1622** may help to narrow and select the output wavelength range of the IR light emitted by IR VCSELs **1620** and improve the gain and the intensity of the emitted IR light. In some embodiments, VCSEL **1620** may include a polarizer **1628**. Polarizer **1628** may be used to control the polarization mode of the IR light emitted by VCSEL **1620** and improve the coupling efficiency of the IR light into the micro-resonator by, for example, a grating coupler or nano-resonators (e.g., meta-structures), which may be polarization dependent. In some embodiments, other polarization components, such as a waveplate, a spatially-variant polarizer, or a spatially-variant waveplate, may be used instead to control the polarization state of IR light emitted by VCSEL **1620**.

(146) In the illustrated example, each visible light source **1602** may include a first micro-resonator **1650**, a second micro-resonator **1660**, and a third micro-resonator **1670** for generating visible light of different colors using IR light emitted by VCSEL **1620** as pump light in DFWM processes. First micro-resonator **1650**, second micro-resonator **1660**, and third micro-resonator **1670** may have different respective designs and thus may generate visible light of different colors using the same pump light. The different respective designs may include different combinations of, for example, loop shape (e.g., ring, oval, spiral, racetrack, etc.), dimension, material (and thus refractive index), and the like. For example, the shape, dimension, and material of third micro-resonator **1670** may be selected such that red light may be generated in third micro-resonator **1670** by DFWM using the IR light emitted by VCSEL **1620** as the pump light. A coupling structure **1672** (e.g., a grating or nano-resonators) may be configured to vertically couple the red light generated in third micro-resonator

1670 out of third micro-resonator **1670**. Similarly, the shape, dimension, and material of second micro-resonator **1660** may be selected such that green light may be generated in second micro-resonator **1660** by DFWM using the IR light emitted by VCSEL **1620** as the pump light. A coupling structure **1662** (e.g., a grating or nano-resonators) may be configured to vertically couple the green light generated in second micro-resonator **1660** out of second micro-resonator **1660**. The shape, dimension, and material of first micro-resonator **1650** may be selected such that blue light may be generated in first micro-resonator **1650** by DFWM using the IR light emitted by VCSEL **1620** as the pump light. A coupling structure **1652** (e.g., a grating or nano-resonators) may be configured to vertically couple the blue light generated in first micro-resonator **1650** out of first micro-resonator **1650**. First micro-resonator **1650**, second micro-resonator **1660**, and third micro-resonator **1670** may be arranged vertically in any suitable order. In some embodiments, each visible light source **1602** may include two or more different micro-resonators configured to generate visible light in two or more different colors. In some embodiments, each visible light source **1602** may include multiple micro-resonators, where at least two micro-resonators of the multiple micro-resonators may be configured to generate visible light of the same color.

(147) The visible light coupled out of first micro-resonator **1650**, second micro-resonator **1660**, and third micro-resonator **1670** may be coupled out of visible light source **1602** through second reflector **1630** with little or no loss since second reflector **1630** may be anti-reflective for visible light as described above. As first reflector **1622**, second reflector **1630** may include, for example, an HCG, or a DBR structure formed by multiple dielectric, semiconductor, or metallic material layers having alternating refractive indices. The thicknesses and refractive indices of the dielectric, semiconductor, or metallic material layers in the DBR structure may be selected such that IR light reflected at adjacent interfaces between different materials may constructively interfere to increase the overall reflectivity of second reflector **1630** for IR light, while visible light reflected at adjacent interfaces between different materials may destructively interfere to reduce the overall reflectivity of second reflector **1630** for visible light. As such, IR light that is emitted by VCSEL **1620** and is not coupled into the micro-resonators yet may be reflected back to the micro-resonators by second reflector **1630** and/or first reflector **1622**, and may be at least partially coupled into the micro-resonators to improve the efficiency of coupling the IR pump light into the micro-resonators and the efficiency of visible light source **1602**. The micro-resonators, the coupling structures, and second reflector **1630** in visible light source **1602** may be formed before or after bonding VCSEL **1620** to drive circuit **1610**.

(148) Visible light source **1602** may include additional electrodes for tuning the respective intensity of the visible light of each color generated by and coupled out of the corresponding micro-resonator. For example, electrodes **1690** may be used to modulate the intensity of blue light coupled out of first micro-resonator **1650**, electrodes **1692** may be used to modulate the intensity of green light coupled out of second micro-resonator **1660**, and electrodes **1694** may be used to modulate the intensity of red light coupled out of third micro-resonator **1670**. Electrodes **1690** may be used to tune at least one of first micro-resonator **1650**, the coupling structure for coupling the IR light emitted by VCSEL **1620** into first micro-resonator **1650**, or coupling structure **1652** for coupling blue light generated in first micro-resonator **1650** to modulate the intensity of the blue light emitted from visible light source **1602**. For example, electrodes **1690** may be used to apply a voltage on an electro-optic material or to supply a current signal to a thermo-optic device to change the refractive index of first micro-resonator **1650** or the coupling structure, thereby changing the resonant condition of first micro-resonator **1650** or the coupling efficiency of the coupling structure for first micro-resonator **1650** and thus the intensity of the emitted blue light. Similarly, electrodes **1692** may be used to change the resonant condition of second micro-resonator **1660** or the coupling efficiency of the coupling structure for second micro-resonator **1660** and thus the intensity of the emitted green light. Electrodes **1694** may be used to change the resonant condition of third micro-resonator **1670** or the coupling efficiency of the coupling structure for third micro-resonator **1670**.

and thus the intensity of the emitted red light. In this way, the intensities of the red, green, and blue light emitted by visible light source **1602** may be independently tuned to desired values to represent a color pixel unit for an active display panel as shown in FIG. **16B**, where the pitch of visible light sources **1602** may be less than about 50 μm , less than about 30 μm , less than about 20 μm , or less than about 10 μm .

(149) FIGS. **17A** and **17B** illustrate an example of a visible light source **1700** that is tunable to emit visible light of different colors according to certain embodiments. Visible light source **1700** may be an example of a visible light source in an array of visible light sources. FIG. **17A** shows a cross-sectional view of visible light source **1700** and FIG. **17B** illustrates a top view of visible light source **1700**. Visible light source **1700** includes a micro-resonator that is in a tunable vertical cavity and is directly pumped by a tunable infrared light VCSEL in the tunable vertical cavity to generate visible light of different colors. The visible light generated in the micro-resonator is vertically coupled out of the vertical cavity. Compared with visible light source **1502** or **1602**, visible light source **1700** may include a single micro-resonator that may generate light of different colors at different times.

(150) In the illustrated example, visible light source **1700** includes a micro-resonator **1740** in a tunable vertical cavity formed by a first reflector **1722** and a second reflector **1750**, where second reflector **1750** may be formed on a micro-electro-mechanical-system (MEMS) device **1770** and thus is movable by MEMS device **1770**. In some embodiments, other micro-actuators or nano-actuators, such as a micro-motor, a piezoelectric actuator, a ferroelectric actuator, a magnetic actuator, an ultrasonic actuator, or the like, may be used to move second reflector **1750**. First reflector **1722** and second reflector **1750** may have a high reflectivity (e.g., 80%, >85%, >90%, >95%, >99%, or higher) for IR light. In some embodiments, first reflector **1722** may have a high reflectivity (e.g., 80%, >85%, >90%, >95%, >99%, or higher) for visible light. Second reflector **1750** may be anti-reflective for visible light. Micro-resonator **1740** may be pumped by an IR-emitting VCSEL **1720** in the vertical cavity to generate visible light. The visible light generated in micro-resonator **1740** may be vertically coupled out of micro-resonator **1740** by a coupling structure **1742**, and may be transmitted out of the vertical cavity through second reflector **1750**.

(151) Visible light source **1700** may include a drive circuit **1710** formed on a CMOS backplane, where the CMOS backplane may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to a wafer including VCSELs **1720** fabricated thereon. Micro-resonator **1740** and second reflector **1750** may be formed before or after bonding the wafer including VCSELs **1720** to the CMOS backplane. VCSEL **1720** may include a first electrode **1730** (e.g., anode or cathode), a second electrode **1732**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1730** and second electrode **1732**. The semiconductor structure may include, for example, first reflector **1722**, an active region **1724** that may emit IR light, and other semiconductor layers (not labeled in FIG. **17A**), such as cladding layers or carrier injection layers that may be p-doped or n-doped. First reflector **1722** may include, for example, an HCG, or a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) of different refractive indices and thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. Active region **1724** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like. VCSEL **1720** may optionally include a partial reflector **1726** for IR light, where partial reflector **1726** may partially reflect and partially transmit IR light emitted in active region **1724** to form a resonant cavity for VCSEL **1720** with first reflector **1722**. The resonant cavity formed by partial reflector **1726** and first reflector **1722** may help to select the output wavelength range of the IR light emitted by VCSEL **1720** and improve the gain and the intensity of the emitted IR light. In some embodiments, VCSEL **1720** may include a polarizer **1728**. Polarizer **1728** may be used to control the polarization state of IR light emitted by VCSEL **1720** and improve the coupling efficiency of the IR light into the micro-resonator by, for

example, a grating coupler or nano-resonators (e.g., meta-structures), which may be polarization dependent. In some embodiments, other polarization components, such as a waveplate, a spatially-variant polarizer, or a spatially-variant waveplate, may be used instead to control the polarization state of IR light emitted by VCSEL **1720**.

(152) As first reflector **1722**, second reflector **1750** may include, for example, an HCG, or a DBR structure formed by multiple dielectric, semiconductor, or metallic material layers having alternating refractive indices. The thicknesses and refractive indices of the dielectric, semiconductor, or metallic material layers in the DBR structure may be selected such that IR light reflected at adjacent interfaces between different materials may constructively interfere to increase the overall reflectivity of second reflector **1750** for IR light, while visible light reflected at adjacent interfaces between different materials may destructively interfere to reduce the overall reflectivity of second reflector **1750** for visible light. As such, IR light that is emitted by VCSEL **1720** and is not coupled into micro-resonator **1740** yet may be reflected back to micro-resonator **1740** by second reflector **1750** and/or first reflector **1722**, such that the IR light emitted by VCSEL **1720** may oscillate within the vertical cavity formed by first reflector **1722** and second reflector **1750** and may be coupled into micro-resonator **1740** at a higher coupling efficiency to improve the efficiency of visible light source **1700**.

(153) The wavelength of the IR light resonant in the vertical cavity may be determined by the optical path length of the vertical cavity. Thus, when second reflector **1750** is moved by MEMS device **1770** and thus the optical path length of the vertical cavity is changed, the wavelength of the IR light that resonates in the vertical cavity may be changed. The IR light may be coupled into micro-resonator **1740** directly or through a coupling structure (e.g., a grating or nano-resonator). The shape, dimension, and material of micro-resonator **1740** may be selected such that, when the wavelength of the pump light is changed by tuning the optical path length of the vertical cavity using MEMS device **1770**, visible light of different colors may be generated in micro-resonator **1740** through OPO (e.g., DFWM) processes. Coupling structure **1742** (e.g., a grating or nano-resonators) may be configured to vertically couple the visible light generated in micro-resonator **1740** out of micro-resonator **1740**. The visible light coupled out of micro-resonator **1740** may be coupled out of visible light source **1700** through second reflector **1750** with little or no loss since second reflector **1750** may be anti-reflective for visible light as described above.

(154) FIGS. **17C** and **17D** illustrate an example of generating visible light of different colors by tuning visible light source **1700**. FIG. **7C** shows that the pump light emitted by VCSEL **1720** and oscillating within the vertical cavity formed by first reflector **1722** and second reflector **1750** may be continuously tunable by tuning the location of second reflector **1750** using MEMS device **1770** or another actuator to tune the optical path length and thus the resonant wavelength of the vertical cavity. In the illustrated example, MEMS device **1770** may be driven by a control signal to move second reflector **1750** such that the wavelength of the IR light emitted by VCSEL **1720** and oscillating within the vertical cavity may be linearly changed in time as shown by a curve **1780** in FIG. **7C**. When the wavelength of the IR pump light is tuned to a first value, a resonant condition of micro-resonator **1740** may be met and the OPO process may occur to generate signal light **1790** at a first visible wavelength (e.g., red light). When the wavelength of the IR pump light is tuned to a second value, a resonant condition (for a different mode number m) of micro-resonator **1740** may again be met and the OPO process may occur to generate signal light **1792** at a second visible wavelength (e.g., green light). When the wavelength of the IR pump light is tuned to a third value, a resonant condition (for a different mode number m) of micro-resonator **1740** may again be met and the OPO process may occur to generate signal light **1794** at a third visible wavelength (e.g., blue light). In this way, visible light in many different colors may be generated by visible light source **1700**.

(155) The control signal may be a periodical signal or may be non-periodic. In some embodiments, the control signal may have a more complex waveform determined by the pixel data of the image

to be displayed. For example, the control signal may have multiple different step levels corresponding to different colors, where the duration of each step level for a color pixel in an image frame to be displayed may be determined based on the desired intensity of the corresponding color (e.g., the R, G, B values) for the color pixel of the image frame, such that the temporal combination of the visible light in the different colors emitted during different time periods of the image frame may be perceived by a viewer's eye as a visible light having a single color in the Rec. **2020** color gamut or a larger color gamut. In this way, each visible light source **1700** may be individually controlled to emit light of a desired color at a desired intensity in each image frame. Thus, an array of visible light sources **1700** may be used as an active display panel.

(156) FIGS. **18A** and **18B** illustrate an example of an array of visible light sources **1800** according to certain embodiments, where each visible light source **1802** in the array of visible light sources **1800** is configured to emit visible light in one or more colors and the respective intensity of the visible light in each color is individually controllable. As illustrated in FIG. **18A**, visible light source **1802** may include one or more micro-resonators in a tunable vertical cavity formed by a first reflector **1822** and a second reflector **1830**, where second reflector **1830** may be formed on a MEMS device **1832** and thus is movable by MEMS device **1832**. First reflector **1822** and second reflector **1830** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for IR light. In some embodiments, first reflector **1822** may have a high reflectivity (e.g., >80%, >85%, >90%, >95%, >99%, or higher) for visible light. Second reflector **1830** may be anti-reflective for visible light. The one or more micro-resonators may be directly pumped by an infrared light VCSEL **1820** in the tunable vertical cavity to generate visible light of different colors. The visible light generated in the one or more micro-resonators may be vertically coupled out of the vertical cavity.

(157) Visible light source **1802** may include a drive circuit **1810** formed on a CMOS backplane, where the CMOS backplane may be bonded directly or indirectly (e.g., through an interposer or a thin-film transistor layer) to a wafer including VCSELs **1820** fabricated thereon. The multiple micro-resonators and second reflector **1830** may be formed before or after bonding the wafer including VCSELs **1820** to the CMOS backplane. VCSEL **1820** may include a first electrode **1840** (e.g., anode or cathode), a second electrode **1842**, and a semiconductor structure (e.g., epitaxial layers) formed between first electrode **1840** and second electrode **1842**. The semiconductor structure may include, for example, first reflector **1822**, an active region **1824** that may emit IR light, and other semiconductor layers (not labeled in FIG. **18A**), such as cladding layers or carrier injection layers that may be p-doped or n-doped. First reflector **1822** may include, for example, an HCG, or a DBR reflector formed by multiple pairs of dielectric, semiconductor, or metallic material layers (doped or undoped) of different refractive indices and thicknesses, such as GaAs and AlAs (or AlGaAs) layers, oxide layers (e.g., silicon oxide and another oxide layer), or the like. Active region **1824** may include, for example, InGaAs quantum well layers and GaAs barrier layers, InAlGaAs quantum well layers and AlGaAs barrier layers, or the like. In some embodiments, VCSEL **1820** may include a partial reflector **1826** for IR light, where partial reflector **1826** may partially reflect and partially transmit IR light emitted in active region **1824** to form a resonant cavity for VCSEL **1820** with first reflector **1822**. The resonant cavity formed by partial reflector **1826** and first reflector **1822** may help to narrow and select the output wavelength range of the IR light emitted by IR VCSELs **1820** and improve the gain and the intensity of the emitted IR light. In some embodiments, VCSEL **1820** may include a polarizer **1828**. Polarizer **1828** may be used to control the polarization mode of the IR light emitted by VCSEL **1820** and improve the coupling efficiency of the IR light into the micro-resonator by, for example, a grating coupler or nano-resonators (e.g., meta-structures), which may be polarization dependent. In some embodiments, other polarization components, such as a waveplate, a spatially-variant polarizer, or a spatially-variant waveplate, may be used instead to control the polarization state of IR light emitted by VCSEL **1820**.

(158) In the illustrated example, each visible light source **1802** may include a first micro-resonator **1850**, a second micro-resonator **1860**, and a third micro-resonator **1870** for generating visible light of different colors using IR light emitted by VCSEL **1820** as pump light in DFWM processes. First micro-resonator **1850**, second micro-resonator **1860**, and third micro-resonator **1870** may have different respective designs and thus may generate visible light of different colors using the same pump light. The different respective designs may include different combinations of, for example, loop shape (e.g., ring, oval, spiral, racetrack, etc.), dimension, material (and thus refractive index), and the like. For example, the shape, dimension, and material of third micro-resonator **1870** may be selected such that red light may be generated in third micro-resonator **1870** by DFWM using the IR light emitted by VCSEL **1820** as the pump light. A coupling structure **1872** (e.g., a grating or nano-resonators) may be configured to vertically couple the red light generated in third micro-resonator **1870** out of third micro-resonator **1870**. Similarly, the shape, dimension, and material of second micro-resonator **1860** may be selected such that green light may be generated in second micro-resonator **1860** by DFWM using the IR light emitted by VCSEL **1820** as the pump light. A coupling structure **1862** (e.g., a grating or nano-resonators) may be configured to vertically couple the green light generated in second micro-resonator **1860** out of second micro-resonator **1860**. The shape, dimension, and material of first micro-resonator **1850** may be selected such that blue light may be generated in first micro-resonator **1850** by DFWM using the IR light emitted by VCSEL **1820** as the pump light. A coupling structure **1852** (e.g., a grating or nano-resonators) may be configured to vertically couple the blue light generated in first micro-resonator **1850** out of first micro-resonator **1850**. First micro-resonator **1850**, second micro-resonator **1860**, and third micro-resonator **1870** may be arranged vertically in any suitable order. In some embodiments, each visible light source **1802** may include two or more different micro-resonators configured to generate visible light in two or more different colors. In some embodiments, each visible light source **1802** may include multiple micro-resonators, where at least two micro-resonators of the multiple micro-resonators may be configured to generate visible light of the same color.

(159) The visible light coupled out of first micro-resonator **1850**, second micro-resonator **1860**, and third micro-resonator **1870** may be coupled out of visible light source **1802** through second reflector **1830** with little or no loss since second reflector **1830** may be anti-reflective for visible light as described above. As first reflector **1822**, second reflector **1830** may include, for example, an HCG, or a DBR structure formed by multiple dielectric, semiconductor, or metallic material layers having alternating refractive indices. The thicknesses and refractive indices of the dielectric, semiconductor, or metallic material layers in the DBR structure may be selected such that IR light reflected at adjacent interfaces between different materials may constructively interfere to increase the overall reflectivity of second reflector **1830** for IR light, while visible light reflected at adjacent interfaces between different materials may destructively interfere to reduce the overall reflectivity of second reflector **1830** for visible light. As such, IR light that is emitted by VCSEL **1820** and is not coupled into the micro-resonators yet may be reflected back to the micro-resonators by second reflector **1830** and/or first reflector **1822**, and may be at least partially coupled into the micro-resonators to improve the efficiency of coupling the IR pump light into the micro-resonators and the efficiency of visible light source **1802**. The micro-resonators, the coupling structures, and second reflector **1830** in visible light source **1802** may be formed before or after bonding VCSEL **1820** to drive circuit **1810**.

(160) As illustrated in FIG. **18A**, second reflector **1830** may be formed on MEMS device **1832** and thus may be movable by MEMS device **1832**. In some embodiments, other micro-actuators or nano-actuators, such as a micro-motor, a piezoelectric actuator, a ferroelectric actuator, a magnetic actuator, an ultrasonic actuator, or the like, may be used to move second reflector **1830**. The wavelength of the IR light resonant in the vertical cavity may be determined by the optical path length of the vertical cavity. Thus, when second reflector **1830** is moved by MEMS device **1832** and thus the optical path length of the vertical cavity is changed, the wavelength of the IR light that

resonates in the vertical cavity may be changed. When the wavelength of the pump light is changed by tuning the optical path length of the vertical cavity using MEMS device **1832**, the wavelengths of visible light of different colors generated in micro-resonators **1850**, **1860**, and **1870** through OPO (e.g., DFWM) processes may change as well.

(161) In the illustrated example, visible light source **1802** may include additional electrodes for tuning the respective intensity of the visible light of each color generated by and coupled out of the corresponding micro-resonator. For example, electrodes **1890** may be used to modulate the intensity of blue light coupled out of first micro-resonator **1850**, electrodes **1892** may be used to modulate the intensity of green light coupled out of second micro-resonator **1860**, and electrodes **1894** may be used to modulate the intensity of red light coupled out of third micro-resonator **1870**. Electrodes **1890** may be used to tune at least one of first micro-resonator **1850**, the coupling structure for coupling the IR light emitted by VCSEL **1820** into first micro-resonator **1850**, or coupling structure **1852** for coupling blue light generated in first micro-resonator **1850** to modulate the intensity of the blue light emitted from visible light source **1802**. For example, electrodes **1890** may be used to apply a voltage on an electro-optic material or to supply a current signal to a thermo-optic device to change the refractive index of first micro-resonator **1850** or the coupling structure, thereby changing the resonant condition of first micro-resonator **1850** or the coupling efficiency of the coupling structure for first micro-resonator **1850** and thus the intensity of the emitted blue light. Similarly, electrodes **1892** may be used to change the resonant condition of second micro-resonator **1860** or the coupling efficiency of the coupling structure for second micro-resonator **1860** and thus the intensity of the emitted green light. Electrodes **1894** may be used to change the resonant condition of third micro-resonator **1870** or the coupling efficiency of the coupling structure for third micro-resonator **1870** and thus the intensity of the emitted red light. In this way, the intensities of the red, green, and blue light emitted by visible light source **1802** may be independently tuned to desired values to represent a color pixel unit for an active display panel as shown in FIG. **18B**, where the pitch of visible light sources **1802** may be less than about 50 μm , less than about 30 μm , less than about 20 μm , or less than about 10 μm .

(162) The visible light source described in FIGS. **15A-17B** may use one VCSEL in a vertical cavity to generate light of multiple colors, such as the three primary colors and other colors consisting combinations of the three primary colors. The spatial multiplexed (overlapping) visible light of different colors generated by the spatially overlapping micro-resonators in visible light sources **1502** and **1602** or the temporal combination of light of different colors generated by a single micro-resonator in visible light sources **1700** during different time periods may be perceived by a viewer's eye as a single color in a color gamut. Therefore, an array of visible light source including visible light sources described in FIGS. **15A-17B** can have a smaller pixel size and a smaller pixel pitch than visible light sources described in FIGS. **14A-14B** where a color pixel may be achieved by a spatial combination of three visible light sources of different primary colors.

(163) Embodiments disclosed herein may be used to implement components of an artificial reality system or may be implemented in conjunction with an artificial reality system. Artificial reality is a form of reality that has been adjusted in some manner before presentation to a user, which may include, for example, a virtual reality, an augmented reality, a mixed reality, a hybrid reality, or some combination and/or derivatives thereof. Artificial reality content may include completely generated content or generated content combined with captured (e.g., real-world) content. The artificial reality content may include video, audio, haptic feedback, or some combination thereof, and any of which may be presented in a single channel or in multiple channels (such as stereo video that produces a three-dimensional effect to the viewer). Additionally, in some embodiments, artificial reality may also be associated with applications, products, accessories, services, or some combination thereof, that are used to, for example, create content in an artificial reality and/or are otherwise used in (e.g., perform activities in) an artificial reality. The artificial reality system that provides the artificial reality content may be implemented on various platforms, including an HMD

connected to a host computer system, a standalone HMD, a mobile device or computing system, or any other hardware platform capable of providing artificial reality content to one or more viewers. (164) FIG. **19** is a simplified block diagram of an example electronic system **1900** of an example near-eye display (e.g., HMD device) for implementing some of the examples disclosed herein. Electronic system **1900** may be used as the electronic system of an HMD device or other near-eye displays described above. In this example, electronic system **1900** may include one or more processor(s) **1910** and a memory **1920**. Processor(s) **1910** may be configured to execute instructions for performing operations at a number of components, and can be, for example, a general-purpose processor or microprocessor suitable for implementation within a portable electronic device. Processor(s) **1910** may be communicatively coupled with a plurality of components within electronic system **1900**. To realize this communicative coupling, processor(s) **1910** may communicate with the other illustrated components across a bus **1940**. Bus **1940** may be any subsystem adapted to transfer data within electronic system **1900**. Bus **1940** may include a plurality of computer buses and additional circuitry to transfer data.

(165) Memory **1920** may be coupled to processor(s) **1910**. In some embodiments, memory **1920** may offer both short-term and long-term storage and may be divided into several units. Memory **1920** may be volatile, such as static random access memory (SRAM) and/or dynamic random access memory (DRAM) and/or non-volatile, such as read-only memory (ROM), flash memory, and the like. Furthermore, memory **1920** may include removable storage devices, such as secure digital (SD) cards. Memory **1920** may provide storage of computer-readable instructions, data structures, program modules, and other data for electronic system **1900**. In some embodiments, memory **1920** may be distributed into different hardware modules. A set of instructions and/or code might be stored on memory **1920**. The instructions might take the form of executable code that may be executable by electronic system **1900**, and/or might take the form of source and/or installable code, which, upon compilation and/or installation on electronic system **1900** (e.g., using any of a variety of generally available compilers, installation programs, compression/decompression utilities, etc.), may take the form of executable code.

(166) In some embodiments, memory **1920** may store a plurality of application modules **1922** through **1924**, which may include any number of applications. Examples of applications may include gaming applications, conferencing applications, video playback applications, or other suitable applications. The applications may include a depth sensing function or eye tracking function. Application modules **1922-1924** may include particular instructions to be executed by processor(s) **1910**. In some embodiments, certain applications or parts of application modules **1922-1924** may be executable by other hardware modules **1980**. In certain embodiments, memory **1920** may additionally include secure memory, which may include additional security controls to prevent copying or other unauthorized access to secure information.

(167) In some embodiments, memory **1920** may include an operating system **1925** loaded therein. Operating system **1925** may be operable to initiate the execution of the instructions provided by application modules **1922-1924** and/or manage other hardware modules **1980** as well as interfaces with a wireless communication subsystem **1930** which may include one or more wireless transceivers. Operating system **1925** may be adapted to perform other operations across the components of electronic system **1900** including threading, resource management, data storage control and other similar functionality.

(168) Wireless communication subsystem **1930** may include, for example, an infrared communication device, a wireless communication device and/or chipset (such as a Bluetooth® device, an IEEE 802.11 device, a Wi-Fi device, a WiMax device, cellular communication facilities, etc.), and/or similar communication interfaces. Electronic system **1900** may include one or more antennas **1934** for wireless communication as part of wireless communication subsystem **1930** or as a separate component coupled to any portion of the system. Depending on desired functionality, wireless communication subsystem **1930** may include separate transceivers to communicate with

base transceiver stations and other wireless devices and access points, which may include communicating with different data networks and/or network types, such as wireless wide-area networks (WWANs), wireless local area networks (WLANs), or wireless personal area networks (WPANs). A WWAN may be, for example, a WiMax (IEEE 802.16) network. A WLAN may be, for example, an IEEE 802.11x network. A WPAN may be, for example, a Bluetooth network, an IEEE 802.15x, or some other types of network. The techniques described herein may also be used for any combination of WWAN, WLAN, and/or WPAN. Wireless communications subsystem **1930** may permit data to be exchanged with a network, other computer systems, and/or any other devices described herein. Wireless communication subsystem **1930** may include a means for transmitting or receiving data, such as identifiers of HMD devices, position data, a geographic map, a heat map, photos, or videos, using antenna(s) **1934** and wireless link(s) **1932**. Wireless communication subsystem **1930**, processor(s) **1910**, and memory **1920** may together comprise at least a part of one or more of a means for performing some functions disclosed herein.

(169) Embodiments of electronic system **1900** may also include one or more sensors **1990**.

Sensor(s) **1990** may include, for example, an image sensor, an accelerometer, a pressure sensor, a temperature sensor, a proximity sensor, a magnetometer, a gyroscope, an inertial sensor (e.g., a module that combines an accelerometer and a gyroscope), an ambient light sensor, or any other similar module operable to provide sensory output and/or receive sensory input, such as a depth sensor or a position sensor. For example, in some implementations, sensor(s) **1990** may include one or more IMUs and/or one or more position sensors. An IMU may generate calibration data indicating an estimated position of the HMD device relative to an initial position of the HMD device, based on measurement signals received from one or more of the position sensors. A position sensor may generate one or more measurement signals in response to motion of the HMD device. Examples of the position sensors may include, but are not limited to, one or more accelerometers, one or more gyroscopes, one or more magnetometers, another suitable type of sensor that detects motion, a type of sensor used for error correction of the IMU, or any combination thereof. The position sensors may be located external to the IMU, internal to the IMU, or any combination thereof. At least some sensors may use a structured light pattern for sensing.

(170) Electronic system **1900** may include a display module **1960**. Display module **1960** may be a near-eye display, and may graphically present information, such as images, videos, and various instructions, from electronic system **1900** to a user. Such information may be derived from one or more application modules **1922-1924**, virtual reality engine **1926**, one or more other hardware modules **1980**, a combination thereof, or any other suitable means for resolving graphical content for the user (e.g., by operating system **1925**). Display module **1960** may use LCD technology, LED technology (including, for example, OLED, ILED, μ -LED, AMOLED, TOLED, etc.), light-emitting polymer display (LPD) technology, or some other display technology.

(171) Electronic system **1900** may include a user input/output module **1970**. User input/output module **1970** may allow a user to send action requests to electronic system **1900**. An action request may be a request to perform a particular action. For example, an action request may be to start or end an application or to perform a particular action within the application. User input/output module **1970** may include one or more input devices. Example input devices may include a touchscreen, a touch pad, microphone(s), button(s), dial(s), switch(es), a keyboard, a mouse, a game controller, or any other suitable device for receiving action requests and communicating the received action requests to electronic system **1900**. In some embodiments, user input/output module **1970** may provide haptic feedback to the user in accordance with instructions received from electronic system **1900**. For example, the haptic feedback may be provided when an action request is received or has been performed.

(172) Electronic system **1900** may include a camera **1950** that may be used to take photos or videos of a user, for example, for tracking the user's eye position. Camera **1950** may also be used to take photos or videos of the environment, for example, for VR, AR, or MR applications. Camera **1950**

may include, for example, a complementary metal-oxide-semiconductor (CMOS) image sensor with a few millions or tens of millions of pixels. In some implementations, camera **1950** may include two or more cameras that may be used to capture 3-D images.

(173) In some embodiments, electronic system **1900** may include a plurality of other hardware modules **1980**. Each of other hardware modules **1980** may be a physical module within electronic system **1900**. While each of other hardware modules **1980** may be permanently configured as a structure, some of other hardware modules **1980** may be temporarily configured to perform specific functions or temporarily activated. Examples of other hardware modules **1980** may include, for example, an audio output and/or input module (e.g., a microphone or speaker), a near field communication (NFC) module, a rechargeable battery, a battery management system, a wired/wireless battery charging system, etc. In some embodiments, one or more functions of other hardware modules **1980** may be implemented in software.

(174) In some embodiments, memory **1920** of electronic system **1900** may also store a virtual reality engine **1926**. Virtual reality engine **1926** may execute applications within electronic system **1900** and receive position information, acceleration information, velocity information, predicted future positions, or any combination thereof of the HMD device from the various sensors. In some embodiments, the information received by virtual reality engine **1926** may be used for producing a signal (e.g., display instructions) to display module **1960**. For example, if the received information indicates that the user has looked to the left, virtual reality engine **1926** may generate content for the HMD device that mirrors the user's movement in a virtual environment. Additionally, virtual reality engine **1926** may perform an action within an application in response to an action request received from user input/output module **1970** and provide feedback to the user. The provided feedback may be visual, audible, or haptic feedback. In some implementations, processor(s) **1910** may include one or more GPUs that may execute virtual reality engine **1926**.

(175) In various implementations, the above-described hardware and modules may be implemented on a single device or on multiple devices that can communicate with one another using wired or wireless connections. For example, in some implementations, some components or modules, such as GPUs, virtual reality engine **1926**, and applications (e.g., tracking application), may be implemented on a console separate from the head-mounted display device. In some implementations, one console may be connected to or support more than one HMD.

(176) In alternative configurations, different and/or additional components may be included in electronic system **1900**. Similarly, functionality of one or more of the components can be distributed among the components in a manner different from the manner described above. For example, in some embodiments, electronic system **1900** may be modified to include other system environments, such as an AR system environment and/or an MR environment.

(177) The methods, systems, and devices discussed above are examples. Various embodiments may omit, substitute, or add various procedures or components as appropriate. For instance, in alternative configurations, the methods described may be performed in an order different from that described, and/or various stages may be added, omitted, and/or combined. Also, features described with respect to certain embodiments may be combined in various other embodiments. Different aspects and elements of the embodiments may be combined in a similar manner. Also, technology evolves and, thus, many of the elements are examples that do not limit the scope of the disclosure to those specific examples.

(178) Specific details are given in the description to provide a thorough understanding of the embodiments. However, embodiments may be practiced without these specific details. For example, well-known circuits, processes, systems, structures, and techniques have been shown without unnecessary detail in order to avoid obscuring the embodiments. This description provides example embodiments only, and is not intended to limit the scope, applicability, or configuration of the invention. Rather, the preceding description of the embodiments will provide those skilled in the art with an enabling description for implementing various embodiments. Various changes may

be made in the function and arrangement of elements without departing from the spirit and scope of the present disclosure.

(179) It will be apparent to those skilled in the art that substantial variations may be made in accordance with specific requirements. For example, customized or special-purpose hardware might also be used, and/or particular elements might be implemented in hardware, software (including portable software, such as applets, etc.), or both. Further, connection to other computing devices such as network input/output devices may be employed.

(180) With reference to the appended figures, components that can include memory can include non-transitory machine-readable media. The term “machine-readable medium” and “computer-readable medium” may refer to any storage medium that participates in providing data that causes a machine to operate in a specific fashion. In embodiments provided hereinabove, various machine-readable media might be involved in providing instructions/code to processing units and/or other device(s) for execution. Additionally or alternatively, the machine-readable media might be used to store and/or carry such instructions/code. In many implementations, a computer-readable medium is a physical and/or tangible storage medium. Such a medium may take many forms, including, but not limited to, non-volatile media, volatile media, and transmission media. Common forms of computer-readable media include, for example, magnetic and/or optical media such as compact disk (CD) or digital versatile disk (DVD), punch cards, paper tape, any other physical medium with patterns of holes, a RAM, a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), a FLASH-EPROM, any other memory chip or cartridge, a carrier wave as described hereinafter, or any other medium from which a computer can read instructions and/or code. A computer program product may include code and/or machine-executable instructions that may represent a procedure, a function, a subprogram, a program, a routine, an application (App), a subroutine, a module, a software package, a class, or any combination of instructions, data structures, or program statements.

(181) Terms, “and” and “or” as used herein, may include a variety of meanings that are also expected to depend at least in part upon the context in which such terms are used. Typically, “or” if used to associate a list, such as A, B, or C, is intended to mean A, B, and C, here used in the inclusive sense, as well as A, B, or C, here used in the exclusive sense. In addition, the term “one or more” as used herein may be used to describe any feature, structure, or characteristic in the singular or may be used to describe some combination of features, structures, or characteristics. However, it should be noted that this is merely an illustrative example and claimed subject matter is not limited to this example. Furthermore, the term “at least one of” if used to associate a list, such as A, B, or C, can be interpreted to mean A, B, C, or any combination of A, B, and/or C, such as AB, AC, BC, AA, ABC, AAB, AABBBCCC, or the like.

(182) Further, while certain embodiments have been described using a particular combination of hardware and software, it should be recognized that other combinations of hardware and software are also possible. Certain embodiments may be implemented only in hardware, or only in software, or using combinations thereof. In one example, software may be implemented with a computer program product containing computer program code or instructions executable by one or more processors for performing any or all of the steps, operations, or processes described in this disclosure, where the computer program may be stored on a non-transitory computer readable medium. The various processes described herein can be implemented on the same processor or different processors in any combination.

(183) Where devices, systems, components or modules are described as being configured to perform certain operations or functions, such configuration can be accomplished, for example, by designing electronic circuits to perform the operation, by programming programmable electronic circuits (such as microprocessors) to perform the operation such as by executing computer instructions or code, or processors or cores programmed to execute code or instructions stored on a non-transitory memory medium, or any combination thereof. Processes can communicate using a

variety of techniques, including, but not limited to, conventional techniques for inter-process communications, and different pairs of processes may use different techniques, or the same pair of processes may use different techniques at different times.

(184) The specification and drawings are, accordingly, to be regarded in an illustrative rather than a restrictive sense. It will, however, be evident that additions, subtractions, deletions, and other modifications and changes may be made thereunto without departing from the broader spirit and scope as set forth in the claims. Thus, although specific embodiments have been described, these are not intended to be limiting. Various modifications and equivalents are within the scope of the following claims

Claims

1. A visible light source comprising: a substrate; a vertical-cavity surface-emitting laser on the substrate and comprising: an active semiconductor region configured to emit infrared light; and a first reflector configured to reflect the infrared light emitted by the active semiconductor region; a second reflector configured to reflect the infrared light, the first reflector and the second reflector forming a vertical cavity for the infrared light; one or more micro-resonators within the vertical cavity, each of the one or more micro-resonators on a respective layer different from the active semiconductor region and configured to resonate within the respective layer, the one or more micro-resonators configured to receive the infrared light incident on the one or more micro-resonators vertically and generate visible light in one or more colors using the infrared light through optical parametric oscillation; and one or more output couplers configured to couple the visible light in one or more colors from the one or more micro-resonators into free space or into a photonic integrated circuit.
2. The visible light source of claim 1, wherein: the one or more micro-resonators include a first micro-resonator and a second micro-resonator arranged vertically with respect to each other; and the first micro-resonator and the second micro-resonator are characterized by different sizes, different shapes, different materials, or a combination thereof, and are configured to generate visible light in different respective colors.
3. The visible light source of claim 2, further comprising: a first tuning circuit configured to tune the first micro-resonator to control an intensity of the visible light generated by the first micro-resonator; and a second tuning circuit configured to tune the second micro-resonator to control an intensity of the visible light generated by the second micro-resonator.
4. The visible light source of claim 1, further comprising a micro-actuator configured to move the second reflector to change an optical path length of the vertical cavity and thus a wavelength of the infrared light emitted by the active semiconductor region, wherein a micro-resonator of the one or more micro-resonators is configured to: generate visible light of a first color using infrared light at a first wavelength; and generate visible light of a second color using infrared light at a second wavelength.
5. The visible light source of claim 1, wherein: the one or more micro-resonators are in the vertical cavity or on the vertical cavity; and each of the one or more micro-resonators is configured to receive the infrared light emitted by the active semiconductor region directly or through an input coupler.
6. The visible light source of claim 1, wherein each of the one or more output couplers includes a grating coupler, a dielectric scatterer, a metallic scatterer, or nano-resonators.
7. The visible light source of claim 6, wherein the grating coupler is slanted, apodized, chirped, or a combination thereof.
8. The visible light source of claim 1, wherein the one or more micro-resonators are configured to generate the visible light through degenerate four-wave mixing (DFWM).
9. The visible light source of claim 1, wherein: at least one micro-resonator of the one or more

micro-resonators is outside the vertical cavity and is not aligned with the vertical-cavity surface-emitting laser; and the visible light source further comprises: a waveguide optically coupled to the at least one micro-resonator; and an input coupler in the vertical cavity or on top of the vertical cavity and configured to couple the infrared light emitted by the active semiconductor region into the waveguide.

10. The visible light source of claim 1, wherein each of the first reflector and the second reflector comprises a high-contrast grating, or a distributed Bragg reflector including dielectric layers, semiconductor layers, or both.

11. The visible light source of claim 1, wherein the second reflector is anti-reflective for the visible light.

12. The visible light source of claim 1, wherein the one or more micro-resonators includes at least one of a micro-ring, a micro-disk, a waveguide-based cavity, a photonic crystal point defect cavity, a photonic-crystal ring cavity, or a plasmonic resonator.

13. The visible light source of claim 1, wherein the one or more micro-resonators are characterized by a circular-ring shape, an oval-ring shape, a spiral shape, or a racetrack shape.

14. The visible light source of claim 1, wherein the one or more output couplers are configured to couple the visible light vertically into free space or couple the visible light into a photonic integrated circuit.

15. The visible light source of claim 1, further comprising: a third reflector in the vertical cavity, wherein the third reflector is partially reflective for the infrared light; a polarization component in the vertical cavity and configured to select a polarization mode of the infrared light; or both the third reflector and the polarization component.

16. The visible light source of claim 15, wherein the polarization component includes a polarizer, a waveplate, a spatially-variant polarizer, or a spatially-variant waveplate.

17. A visible light source array comprising: a substrate including drive circuits formed thereon; and a die or a wafer bonded to the drive circuits directly or indirectly, the die or wafer including an array of visible light sources formed thereon, wherein each visible light source in the array of visible light sources is individually addressable by the drive circuits and comprises: a vertical cavity formed by a first reflector and a second reflector, the first reflector and the second reflector configured to reflect infrared light; an active region in the vertical cavity and configured to emit infrared light; one or more micro-resonators within the vertical cavity, each of the one or more micro-resonators on a respective layer different from the active region and configured to resonate within the respective layer, the one or more micro-resonators configured to receive the infrared light incident on the one or more micro-resonators vertically and generate visible light in one or more colors using the infrared light through optical parametric oscillation; and one or more output couplers configured to couple the visible light in one or more colors from the one or more micro-resonators into free space or one or more waveguides.

18. The visible light source array of claim 17, wherein each visible light source in the array of visible light sources further comprises one or more tuning circuits configured to tune the one or more micro-resonators to control a respective intensity of the visible light in each of the one or more colors.

19. The visible light source array of claim 17, wherein: each visible light source in the array of visible light sources further comprises a micro-actuator configured to move the second reflector to change an optical path length of the vertical cavity and thus a wavelength of the infrared light emitted by the active region; and a micro-resonator of the one or more micro-resonators is configured to: generate visible light of a first color using infrared light at a first wavelength; and generate visible light of a second color using infrared light at a second wavelength.

20. A visible light source array comprising: a substrate including drive circuits formed thereon; and a die or a wafer bonded to the drive circuits directly or indirectly, the die or wafer including an array of visible light sources formed thereon, wherein each visible light source in the array of

visible light sources is individually addressable by the drive circuits and comprises: a vertical cavity formed by a first reflector and a second reflector, the first reflector and the second reflector configured to reflect infrared light; an active region in the vertical cavity and configured to emit infrared light; a micro-resonator within the vertical cavity and on a layer different from the active region and configured to resonate within the layer, the micro-resonator configured to receive the infrared light incident on the micro-resonator vertically and generate visible light using the infrared light through optical parametric oscillation; and an output couplers configured to couple the visible light in from the micro-resonator into free space or a waveguide, wherein a first micro-resonator in a first visible light source of the visible light source array and a second micro-resonator in a second visible light source of the visible light source array have different sizes, different shapes, different materials, or a combination thereof, and are configured to generate visible light of different colors.
