

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12413859

Kind Code

B2

Date of Patent

September 09, 2025

Inventor(s)

Bleyer; Michael et al.

Systems and methods for generating depth information from low-resolution images

Abstract

A system for generating depth information from low-resolution images is configured to access a plurality of image frames capturing an environment, identify a first group of image frames from the plurality of image frames, and generate a first image comprising a first composite image of the environment using the first group of image frames as input. The first composite image has an image resolution that is higher than an image resolution of the image frames of the first group of image frames. The system is also configured to obtain a second image of the environment, where parallax exists between a capture perspective associated with the first image and a capture perspective associated with the second image. The system is also configured to generate depth information for the environment based on the first image and the second image.

Inventors: Bleyer; Michael (Seattle, WA), Edmonds; Christopher Douglas (Carnation, WA), Matakos; Antonios (Redmond, WA), Price; Raymond Kirk (Redmond, WA)

Applicant: Microsoft Technology Licensing, LLC (Redmond, WA)

Family ID: 81454616

Assignee: Microsoft Technology Licensing, LLC (Redmond, WA)

Appl. No.: 18/502980

Filed: November 06, 2023

Prior Publication Data

Document Identifier

US 20240073523 A1

Publication Date

Feb. 29, 2024

Related U.S. Application Data

continuation parent-doc US 17230813 20210414 US 11849220 child-doc US 18502980

Publication Classification

Int. Cl.: H04N23/68 (20230101); G06T3/4076 (20240101); G06T7/55 (20170101)

U.S. Cl.:

CPC H04N23/682 (20230101); G06T3/4076 (20130101); G06T7/55 (20170101);
H04N23/689 (20230101);

Field of Classification Search

CPC: H04N (23/682); H04N (23/689); G06T (3/4076); G06T (7/55); G06T (2207/10016);
G06T (7/579)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10880474	12/2019	Thomas	N/A	N/A
2012/0147205	12/2011	Lelescu	348/E5.024	H04N 23/62
2012/0176379	12/2011	Farrer	N/A	N/A
2014/0140579	12/2013	Takemoto	N/A	N/A
2014/0267243	12/2013	Venkataraman et al.	N/A	N/A
2015/0178988	12/2014	Montserrat Mora	345/420	G06T 17/20
2017/0359560	12/2016	Winn	N/A	H04N 23/743
2019/0166765	12/2018	Maor	N/A	N/A
2019/0364265	12/2018	Matsunobu	N/A	N/A
2020/0051265	12/2019	Kim	N/A	H04N 23/683
2020/0195910	12/2019	Han	N/A	H04N 13/25
2020/0267339	12/2019	Douady-Pleven	N/A	H04N 19/136
2021/0082086	12/2020	Bichu	N/A	G06T 5/80
2021/0092291	12/2020	Lee	N/A	H04N 25/48
2021/0243344	12/2020	Peng	N/A	H04N 23/71
2022/0270277	12/2021	Nielsen	N/A	H04N 23/698

OTHER PUBLICATIONS

U.S. Appl. No. 17/230,813, filed Apr. 14, 2021. cited by applicant

U.S. Appl. No. 17/230,859, filed Apr. 14, 2021. cited by applicant

U.S. Appl. No. 18/482,654, filed Oct. 6, 2023. cited by applicant

Notice of Allowance mailed on Aug. 15, 2024, in U.S. Appl. No. 18/482,654 (MS# 409636-US02-DIV), 09 pages. cited by applicant

Primary Examiner: Tran; Sinh

Assistant Examiner: Wu; Zhenzhen

Attorney, Agent or Firm: Workman Nydegger

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/230,813, filed on Apr. 14, 2021, and entitled “SYSTEMS AND METHODS FOR GENERATING DEPTH INFORMATION FROM LOW-RESOLUTION IMAGES”, the entirety of which is incorporated herein by reference for all purposes.

BACKGROUND

(1) Aerial images and/or videos often capture a physical environment from an overhead perspective. Aerial images and/or videos are typically captured by one or more image sensors positioned on an aerial vehicle (whether manned or unmanned). The acquisition of aerial images can serve many purposes, such as recreation, exploration, search and rescue, reconnaissance, and/or others.

(2) However, many image sensors implemented on aerial vehicles are configured to capture low-resolution images (e.g., 640×480 resolution) and may further be configured to capture images at a low framerate (e.g., 10-30 fps). Accordingly, in some instances, aerial images and/or videos are undesirable, particularly for applications that benefit from high image resolution for computer vision applications.

(3) For instance, high-resolution images may be used to generate depth information for a captured environment. Depth information may be represented in a depth map, disparity map, or other format for depicting distances between objects within the captured environment and the image sensor at an image capture time period (e.g., on a per-pixel basis). Depth information may be used to generate a 3D representation of a captured environment (e.g., in the form of a surface mesh, point cloud, or another format). A 3D representation of a captured environment may be used to facilitated mixed-reality (MR) experiences on MR systems, which may include augmented reality (AR) experiences on AR systems, virtual reality (VR) experiences on VR systems, etcetera. MR experiences that implement captured environments may be used for a variety of purposes, such as gaming, training, and/or others.

(4) The quality of depth information and/or 3D representations generated based on captured images of an environment depend on the quality of the captured images of the environment. Thus, because aerial images and/or videos often include relatively low image resolution, generating depth information and/or 3D representations based on aerial images often provides poor results.

(5) Thus, for at least the foregoing reasons, there is an ongoing need and desire for improved techniques for generating depth information from low-resolution images.

(6) The subject matter claimed herein is not limited to embodiments that solve any disadvantages or that operate only in environments such as those described above. Rather, this background is only provided to illustrate one exemplary technology area where some embodiments described herein may be practiced.

BRIEF SUMMARY

(7) Disclosed embodiments include systems, methods, and devices that facilitate the generation of depth information from low-resolution images.

(8) Some embodiments provide a system that is configured to access a plurality of image frames capturing an environment, identify a first group of image frames from the plurality of image frames, and generate a first image comprising a first composite image of the environment using the first group of image frames as input. With the use of super-resolution imaging techniques, the first composite image has an image resolution that is higher than an image resolution of the image frames of the first group of image frames. The system is also configured to obtain a second image of the environment, where parallax exists between a capture perspective associated with the first image and a capture perspective associated with the second image. The system is also configured to

generate depth information for the environment based on the first image and the second image.

(9) Some embodiments include a system that is configured to capture a plurality of image frames of an environment, select a first group of image frames from the plurality of image frames, and generate a first composite image of the environment using the first group of image frames as input. The first composite image has an image resolution that is higher than an image resolution of the image frames of the first group of image frames. The system is also configured to (i) transmit the first composite image to a remote device while refraining from transmitting the first group of image frames to the remote device, or (ii) store the first composite image in a nonvolatile manner while refraining from storing the first group of image frames in a nonvolatile manner.

(10) This Summary is provided to introduce a selection of concepts in a simplified form that are further described below in the Detailed Description. This Summary is not intended to identify key features or essential features of the claimed subject matter, nor is it intended to be used as an aid in determining the scope of the claimed subject matter.

(11) Additional features and advantages will be set forth in the description which follows, and in part will be obvious from the description, or may be learned by the practice of the teachings herein. Features and advantages of the invention may be realized and obtained by means of the instruments and combinations particularly pointed out in the appended claims. Features of the present invention will become more fully apparent from the following description and appended claims or may be learned by the practice of the invention as set forth hereinafter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to describe the manner in which the above-recited and other advantages and features can be obtained, a more particular description of the subject matter briefly described above will be rendered by reference to specific embodiments which are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments and are not therefore to be considered to be limiting in scope, embodiments will be described and explained with additional specificity and detail through the use of the accompanying drawings in which:

(2) FIG. 1 illustrates example components of an example system that may include or be used to implement one or more disclosed embodiments;

(3) FIGS. 2A-2C illustrate an example of capturing low-resolution images using an image sensor attached to an aerial vehicle;

(4) FIGS. 3A-3C illustrate an example of generating high-resolution depth information based on low-resolution images captured by an image sensor attached to an aerial vehicle;

(5) FIG. 4 illustrates an example of capturing low-resolution images using image sensors attached to different aerial vehicles;

(6) FIG. 5 illustrates an example of generating high-resolution depth information based on low-resolution images captured by image sensors attached to different aerial vehicles;

(7) FIGS. 6A and 6B illustrate examples of capturing low-resolution images using image sensors within close proximity to one another;

(8) FIG. 7 illustrates an example of generating a composite image using low-resolution images captured by image sensors within close proximity to one another during image capture;

(9) FIG. 8 illustrates an example of generating a surface mesh using depth information generated from low-resolution images;

(10) FIG. 9 illustrates an example of capturing low-resolution images using an image capture device attached to an aerial vehicle and transmitting or storing high-resolution images generated based on the low-resolution images; and

(11) FIGS. 10 and 11 illustrate example flow diagrams depicting acts associated with generating

depth information from low-resolution images.

DETAILED DESCRIPTION

(12) Disclosed embodiments include systems, methods, and devices that facilitate the generation of depth information from low-resolution images.

Examples of Technical Benefits, Improvements, and Practical Applications

(13) Those skilled in the art will recognize, in view of the present disclosure, that at least some of the disclosed embodiments may be implemented to address various shortcomings associated with generating three-dimensional depth information from low-resolution images. The following section outlines some example improvements and/or practical applications provided by the disclosed embodiments. It will be appreciated, however, that the following are examples only and that the embodiments described herein are in no way limited to the example improvements discussed herein.

(14) As described herein, groups of low-resolution image frames (whether captured by the same image sensor or not) may be combined to form high-resolution image frames. The high-resolution image frames may avoid artifacts (e.g., JPEG artifacts, motion blur artifacts, rolling shutter artifacts, etc.) and/or may include sufficient texture to be used to generate depth information for the captured environment represented in the low-resolution image frames. The low-resolution image frames may be captured by one or more image sensors attached to one or more vehicles (e.g., aerial vehicles) to advantageously facilitate rapid imaging and/or mapping of a real-world environment. In some instances, swarms of vehicles (e.g., swarms of drones) are used to further increase the rate at which a real-world environment can be captured and/or mapped for various applications.

(15) Furthermore, in some instances, the amount of data stored and/or transmitted by an image capture device may be reduced by generating high-resolution images from low-resolution images and storing or transmitting the high-resolution images while refraining from storing or transmitting the low-resolution images. Such functionality may increase the amount of data that can be stored by an image capture device and/or reduce the amount of time between the capturing of an environment and the consumption of the captured data by users and/or devices.

(16) Still furthermore, at least some principles described herein may be implemented as post-processing techniques and may operate on low-resolution images any time after they have been captured, which may allow existing low-resolution images to be used for additional applications/purposes.

(17) Having just described some of the various high-level features and benefits of the disclosed embodiments, attention will now be directed to FIGS. 1 through 11. These Figures illustrate various conceptual representations, architectures, methods, and supporting illustrations related to the disclosed embodiments.

Example Systems

(18) FIG. 1 illustrates various example components of a system **100** that may be used to implement one or more disclosed embodiments. For example, FIG. 1 illustrates that a system **100** may include processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112** (I/O system(s) **112**), and communication system(s) **114**. Although FIG. 1 illustrates a system **100** as including particular components, one will appreciate, in view of the present disclosure, that a system **100** may comprise any number of additional or alternative components.

(19) The processor(s) **102** may comprise one or more sets of electronic circuitry that include any number of logic units, registers, and/or control units to facilitate the execution of computer-readable instructions (e.g., instructions that form a computer program). Such computer-readable instructions may be stored within storage **104**. The storage **104** may comprise physical system memory and may be volatile, non-volatile, or some combination thereof. Furthermore, storage **104** may comprise local storage, remote storage (e.g., accessible via communication system(s) **114** or otherwise), or some combination thereof. Additional details related to processors (e.g., processor(s) **102**) and computer storage media (e.g., storage **104**) will be provided hereinafter.

(20) In some implementations, the processor(s) **102** may comprise or be configurable to execute any combination of software and/or hardware components that are operable to facilitate processing using machine learning models or other artificial intelligence-based structures/architectures. For example, processor(s) **102** may comprise and/or utilize hardware components or computer-executable instructions operable to carry out function blocks and/or processing layers configured in the form of, by way of non-limiting example, single-layer neural networks, feed forward neural networks, radial basis function networks, deep feed-forward networks, recurrent neural networks, long-short term memory (LSTM) networks, gated recurrent units, autoencoder neural networks, variational autoencoders, denoising autoencoders, sparse autoencoders, Markov chains, Hopfield neural networks, Boltzmann machine networks, restricted Boltzmann machine networks, deep belief networks, deep convolutional networks (or convolutional neural networks), deconvolutional neural networks, deep convolutional inverse graphics networks, generative adversarial networks, liquid state machines, extreme learning machines, echo state networks, deep residual networks, Kohonen networks, support vector machines, neural Turing machines, and/or others.

(21) The processor(s) **102** may be configured to execute instructions **106** stored within storage **104** to perform certain actions associated with the disclosed. The actions may rely at least in part on data **108** stored on storage **104** in a volatile or non-volatile manner.

(22) In some instances, the actions may rely at least in part on communication system(s) **114** for receiving data and/or instructions from remote system(s) **116**, which may include, for example, separate systems or computing devices, storage nodes, sensors, and/or others. The communications system(s) **116** may comprise any combination of software or hardware components that are operable to facilitate communication between on-system components/devices and/or with off-system components/devices. For example, the communications system(s) **116** may comprise ports, buses, or other physical connection apparatuses for communicating with other devices/components. Additionally, or alternatively, the communications system(s) **116** may comprise systems/components operable to communicate wirelessly with external systems and/or devices through any suitable communication channel(s), such as, by way of non-limiting example, Bluetooth, ultra-wideband, Wi-Fi, WLAN, infrared communication, and/or others.

(23) FIG. 1 illustrates that a system **100** may comprise or be in communication with sensor(s) **110**. Sensor(s) **110** may comprise any device for capturing or measuring data representative of perceivable phenomenon. By way of non-limiting example, the sensor(s) **110** may comprise one or more image sensors, optical scanners, microphones, thermometers, barometers, magnetometers, accelerometers, gyroscopes, and/or others.

(24) Furthermore, FIG. 1 illustrates that a system **100** may comprise or be in communication with I/O system(s) **112**. I/O system(s) **112** may include any type of input or output device such as, by way of non-limiting example, a display, a touch screen, a mouse, a keyboard, a controller, a speaker, a light source, a vibration motor, and/or others, without limitation. In some instances, I/O system(s) **112** may at least partially rely on the sensor(s) **110** (e.g., via a microphone or motion sensor system to detect user input).

(25) FIG. 1 conceptually represents that the components of the system **100** may comprise or utilize various types of devices, such as mobile electronic device **100A** (e.g., a smartphone), personal computing device **100E3** (e.g., a laptop), a mixed-reality head-mounted display **100C** (HMD **100C**), an aerial vehicle **100D** (e.g., a drone), and/or other devices (e.g., non-aerial vehicles, such as cars, boats, submarines, etc.). Although the present description focuses, in at least some respects, on utilizing one or more aerial vehicles **100D** to implement techniques of the present disclosure, additional or alternative types of systems may be used.

Example Techniques for Generating Depth Information from Low-Resolution Images

(26) FIGS. 2A-2C illustrate an example of capturing low-resolution images using an image sensor attached to an aerial vehicle. In particular, FIG. 2A illustrates a conceptual representation of a drone **202** traveling within an environment that includes a building **206**. The drone **202** is

positioned at pose **208A** within the environment. The pose **208A** may be determined by sensor(s) **110** discussed above, which may include one or more inertial measurement units (IMUS), radio-based positioning systems (e.g., GPS), and/or other systems for determining position of the drone **202** within the environment.

(27) FIG. 2A also illustrates that the drone **202** includes a camera **204** affixed thereon. As depicted in FIG. 2A, while the drone **202** is positioned according to pose **208A**, the camera **204** captures an image frame **210A** of the building **206** within the environment. Although the present example focuses, in at least some respects, on image capture facilitated by a camera positioned on a drone traveling within an environment, those skilled in the art will recognize, in view of the present disclosure, that the principles described herein may be applied to other image capture devices and/or techniques (e.g., image capture by cameras positioned on other types of aerial vehicles, cars, vessels, etc.).

(28) FIG. 2B illustrates the drone **202** positioned at a new pose **208B** within the environment relative to the building **206** (the previous pose **208A** of the drone **202** from FIG. 2A is depicted in dotted lines in FIG. 2B for reference). For example, after capturing image frame **210A** at pose **208A**, the drone **202** may continue to travel within the environment and capture another image frame **210B** of the building **206** from pose **208B**. Similarly, FIG. 2C shows additional image frames **210C**, **210D**, **210E**, and **210F** captured by the camera **204** of the drone **202** at corresponding respective poses **208C**, **208D**, **208E**, and **208F**. As illustrated in FIGS. 2A-2C, the image frames **210A-210F** are captured by the camera **204** at temporally consecutive timepoints and form a video stream **214** capturing the building **206** from similar aerial perspectives. The ellipsis **212** indicates that a video stream **214** capturing an environment may include any number of image frames.

(29) As indicated above, the image frames **210A-210F** captured by the camera **204** on the drone **202** may comprise a resolution that renders the image frames **210A-210F** generally undesirable for various applications. The image frame **210A** may include an image resolution below about 1024×1024 pixels, or below 700×500 pixels (e.g., VGA resolution e.g., 640×480 pixels). With such a low image resolution, the image frames **210A-210F** may be undesirable inputs for performing stereo matching to generate depth information describing the captured building **206**.

(30) Accordingly, techniques of the present disclosure are directed to using low-resolution image frames (e.g., image frames **210A-210F**) to generate suitable inputs for performing stereo matching (or other depth processing) for determining depth information for a captured environment.

(31) FIGS. 3A-3C illustrate an example of generating high-resolution depth information based on low-resolution images captured by an image sensor attached to an aerial vehicle. In particular, FIG. 3A illustrates the image frames **210A-210F** of the video stream **214** described above, as well as an additional image frame **210G** capturing the building **206** for illustrative purposes. The image frames **210A-210G** may be accessed by computational resources associated with the drone **202** and/or another system/device to facilitate the processing described herein for generating depth information from low-resolution images.

(32) To facilitate generation of depth information from low-resolution images, a system may define groups of image frames, and the groups of image frames may be used to generate composite image frames with a high enough image resolution for depth processing (e.g., stereo matching). FIG. 3A shows the image frames **210A-210G** divided into groups **302A** and **302B**, where group **302A** includes image frames **210A-210C** and group **302B** includes image frames **210D-210G**. Groups of image frames may include any number of image frames in accordance with the present disclosure.

(33) Image frames may be grouped using various approaches and/or grouping criteria. In some implementations, consecutively captured image frames are grouped together to form groups of one or more predetermined group sizes (e.g., groups of 10 consecutively captured image frames).

(34) In some instances, groups are identified based on pose values associated with image frames. For instance, as shown and described with reference to FIGS. 2A-2C, image frames **210A-210F** may be associated with respective poses **208A-208F** that existed for the camera **204** and/or drone

202 during capture of the image frames **210A-210F**. An image frame may thereby be grouped with other image frames based on proximity of its associated pose to poses associated with the other image frames. Proximity between poses may be determined based on various aspects, such as translational position (e.g., x-y-z position, longitude-latitude-altitude, angular orientation, etc.).

(35) In one example, a system (e.g., including the drone **202** and the camera **204**) may capture a first image frame at a first pose and may group subsequently captured image frames with the first image until the system captures a second image frame at a second pose that satisfies a threshold difference from the first pose. The system may then begin a new group that includes the second image frame and image frames captured subsequent to the second image frame at poses that do not satisfy a threshold difference from the second pose. Thus, the number of image frames in a group may be dynamic (e.g., depending on the rate of change in capture pose). Other techniques for grouping image frames may be utilized (e.g., post-processing grouping techniques).

(36) Accordingly, a group of image frames may include image frames with only a small amount of parallax between capture perspectives associated with the image frames of the group. For example, image frames **210A-210C** of FIG. 3A show the building **206** as being captured from similar capture perspectives (with the upper boundary of the building being near the top of the image frames **210A-210C**), and image frames **210D-210G** of FIG. 3A show the building **206** as being captured from similar capture perspectives (with the upper boundary of the building being lower relative to image frames **210A-210C**). Providing groups of image frames captured with minimal parallax may improve the usability of the image frames for generating composite images (e.g., via super-resolution upsampling), as described hereinafter.

(37) FIG. 3B illustrates an example of generating composite images **306A** and **306B** from the groups **302A** and **302B** of image frames. In particular, FIG. 3B shows image frames **210A**, **210B**, and **210C** of group **302A** being provided as input to super-resolution processing **304A** to generate composite image **306A**. Super-resolution processing **304A** may include one or more upsampling algorithms configured to generate a single high-resolution image from multiple low-resolution images (e.g., an algorithm for creating high-resolution images from low-resolution video). For example, super-resolution processing **304A** to generate a high-resolution image from one or more low-resolution images may employ techniques such as spatial domain approaches (e.g., sample transformation using the sampling theorem and the Nyquist theorem), frequency domain approaches (e.g., registering images using properties of the discrete Fourier transform), learning based techniques (e.g., adaptive regularization, pair matching, etc.), iterative reconstruction and interpolation based techniques (e.g., iterative back projection, pixel replication, nearest-neighbor interpolation, bilinear or bicubic interpolation, etc.), dynamic tree and wavelet based resolution techniques (e.g., mean field approaches), filtering techniques (e.g., edge-preserving filtering operations such as joint bilateral filter, guided filter, bilateral solver, etc.) and/or others.

(38) In this regard, the composite image **306A** comprises a higher image resolution than the image frames **210A-210C** used to generate the composite image **306A**. The composite image **306A** may thus be regarded as a “high-resolution image.”

(39) Furthermore, in some instances, the super-resolution processing **304A** is tailored to improve the amount of distinguishable texture (e.g., micro-texture) present in the composite image **306A** as compared to the amount of distinguishable texture present in the image frames **210A-210C**. Thus, in some instances, a composite image **306A** provides a better candidate for depth processing (e.g., stereo matching) than the individual image frames **210A-210C**.

(40) FIG. 3B also illustrates image frames **210D**, **210E**, **210F**, and **210G** of group **302B** being provided as input to super-resolution processing **304B** to generate composite image **306B**. Super-resolution processing **304B** may be similar to super-resolution processing **304A**. Accordingly, composite image **306B** comprises an image resolution that is higher than the image resolution of image frames **210D-210G**, and composite image **306B** may comprise sufficient texture for use in depth processing.

(41) FIG. 3B illustrates that parallax exists between the viewing perspective associated with composite image **306A** and the viewing perspective associated with composite image **306B**. For example, the top portion of the depiction of the building **206** in composite image **306A** is near the top of the frame of composite image **306A**, whereas the top portion of the depiction of the building **206** in composite image **306B** is lower as compared to composite image **306A**. Many depth processing techniques (e.g., stereo matching) rely on the existence of sufficient (but not excessive) parallax between images capturing a common object in an environment. Thus, composite images **306A** and **306B** may comprise desirable inputs for depth processing to determine depth information. In contrast, consecutively captured low-resolution image frames (e.g., from the set of image frames including image frames **210A-210G**) may not include sufficient resolution, texture, or parallax to comprise desirable inputs for generating depth information for a captured environment.

(42) FIG. 3C illustrates the composite images **306A** and **306B** being provided as inputs to depth processing **308** to generate a depth map **310** (other representations of depth/distance are contemplated). Depth processing **308** may comprise stereo matching or other techniques for determining depth from image data input. The depth map **310** comprises per-pixel depth information representing distance between (i) the viewing position/perspective associated with the composite images **306A**, **306B** and (ii) the object(s) depicted in the composite images **306A** and/or **306B**.

(43) Depth processing **308** to calculate depth information may be performed in various ways, including stereo matching. To perform stereo matching, a pair of images is obtained (e.g., composite images **306A** and **306B**). A rectification process is typically performed, whereby corresponding pixels in the different images of the pair of images that represent common 3D points in the environment become aligned along scanlines (e.g., horizontal scanlines, vertical scanlines, epipolar lines, etc.). For rectified images, the coordinates of the corresponding pixels in the different images only differ in one dimension (e.g., the dimension of the scanlines). A stereo matching algorithm may then search along the scanlines to identify pixels in the different images that correspond to one another (e.g., by performing pixel patch matching to identify pixels that represent common 3D points in the environment) and identify disparity values for the corresponding pixels. Disparity values may be based on the difference in pixel position between the corresponding pixels in the different images that describe the same portion of the environment. Per-pixel depth may be determined based on per-pixel disparity values, providing a depth map.

(44) Thus, in accordance with the present disclosure, low-resolution image frames (e.g., captured by a drone **202** traveling within an environment) may be used to generate composite images, which may then be used to generate depth information. The depth information represented in the depth map **310** may be used for various applications, such as generating a surface mesh of a captured environment (e.g., for use in MR environments/experiences).

(45) In the example discussed with reference to FIGS. 3A-3C, the image frames of group **302A** (used to generate composite image **306A**) and the image frames of group **302B** (used to generate composite image **306B**) were captured from the same image capture device (i.e., camera **204** associated with drone **202**), and the image frames of group **302B** were captured temporally subsequent to the image frames of group **302A**. However, the principles described herein may be implemented under other circumstances.

(46) For example, FIG. 4 illustrates drone **402** and drone **406** traveling within an environment that includes building **206**. Drone **402** is physically untethered from drone **406**. Drone **402** includes camera **404**, and drone **406** includes camera **408**. Both cameras **404** and **408** capture the building **206** as the drones **402** and **406** move within the environment. In particular, camera **404** captures image frames **410A**, **410B**, and **410C** (and/or others, indicated by ellipsis **412**) as drone **402** moves within the environment, and camera **408** captures image frames **414A**, **414B**, and **414C** (and/or others, indicated by ellipsis **416**) as drone **406** moves within the environment.

(47) As noted above, the various image frames captured by the cameras **404**, **408** may be associated with pose values that existed during image capture (e.g., corresponding to the position of the drones **402**, **406** and/or the cameras **404**, **408** during image capture). Furthermore, in some instances, the image capture timing of camera **404** may be temporally synchronized with the image capture timing of camera **408** (e.g., such that both cameras capture pairs of images corresponding timestamps). As before, the image frames **410A-410C** and **414A-414C** may be low-resolution images.

(48) FIG. 5 illustrates that low-resolution image frames captured from different image capture devices may be used to generate depth information for a captured environment. In particular, FIG. 5 shows the image frames **410A-410C** captured by camera **404** of drone **402** grouped into group **502**, and FIG. 5 shows the image frames **414A-414C** captured by camera **408** of drone **406** grouped into group **504**. Thus, groups **502** and **504** include image frames captured by image sensors attached to different vehicles (e.g., drones **402** and **406**, which are physically untethered from one another). Notwithstanding, the image frames of the groups **502** and **504** may be used to generate depth information for the captured environment.

(49) FIG. 5 depicts composite image **506** generated using image frames **410A-410C** of group **502**. FIG. 5 also depicts composite image **508** generated using image frames **414A-414C** of group **504**. The composite images **506** and **508** may be generated using super-resolution processing, as discussed above with reference to FIG. 3B (e.g., similar to super-resolution processing **304A**, **304B**). Accordingly, the composite images **506** and **508** may comprise sufficient image resolution and texture to facilitate depth computations. Furthermore, in some implementations, the capture perspective associated with camera **404** while capturing image frames **410A-410C** may have been sufficiently different from the capture perspective associated with camera **408** while capturing image frames **414A-414C** such that sufficient parallax exists between the composite images **506** and **508** to facilitate depth computations. For example, drone **402** may be traveling within the environment and capturing the building **206** at a distance from drone **406** that causes parallax between images captured by the different drones at least partially exceeds the sub-pixel level.

(50) FIG. 5 shows depth map **510** being generated using composite images **506** and **508** as inputs. Depth map **510** may be generated via depth processing such as stereo matching (e.g., similar to depth processing **308** discussed above with reference to FIG. 3C). In this regard, depth information may be generated from low-resolution images captured by image sensors associated with different vehicles (e.g., aerial vehicles, such as drones **402** and **406**).

(51) The foregoing examples have focused, at least in part, on implementations in which multiple composite images are used as inputs to generate depth information. In some implementations, a composite image (e.g., generated based on low-resolution image frames) is used as an input in combination with a captured high-resolution image (e.g., captured by a high-resolution image sensor) to generate depth information for a captured environment. In this regard, composite images may be used in combination with non-composite images (e.g., captured high-resolution images) to generate depth information for a captured environment.

(52) Furthermore, the foregoing examples have focused, at least in part, on implementations in which each composite image is generated from image frames (or a video stream) captured by a single image capture device. In some instances, a composite image may be generated using image frame inputs captured by multiple different image sensors.

(53) For example, FIGS. 6A and 6B illustrate low-resolution images being captured using image sensors within close proximity to one another. In particular, FIG. 6A illustrates drone **602** and drone **606**, which include, respectively, camera **604** and camera **608**. Camera **604** captures image frames **610A**, **610B**, and **610C** (and/or others, as indicated by ellipsis **612**), and camera **608** captures image frames **614A**, **614B**, and **614C** (and/or others, as indicated by ellipsis **616**). FIG. 6B illustrates an alternative implementation, in which the cameras **604** and **608** are implemented on a single drone **618** for capturing the image frames **610A-610C** and the image frames **614A-614C**.

(54) Similar to the image frames **210A-210C** discussed above with reference to FIGS. 2A-2C, the image frames **610A-610C** captured by camera **604** may be captured from sufficiently similar poses so as to be groupable for forming a composite image. Similarly, the image frames **614A-614C** captured by camera **608** may be captured from sufficiently similar poses so as to be groupable for forming a composite image. In addition, the separate image frames captured by the separate cameras **604** and **608** may capture image frames that depict the building **206** from substantially similar perspectives so as to render them groupable for forming composite images.

(55) For example, image frame **610A** and image frame **614A** may capture the building **206** from substantially similar poses (except from the relatively small spatial offset between them). Similarly, image frames **610B** and **614B** may capture the building **206** from substantially similar perspectives, image frames **610C** and **614C** may capture the building **206** from substantially similar perspectives, and so forth. In some implementations, the image capture timing of the cameras **604** and **608** is synchronized (e.g., wherein image frames **610A** and **614A** are captured at a same timepoint, image frames **610E3** and **614E3** are captured at a same subsequent timepoint, and so forth).

(56) In this regard, the low-resolution image frames **610A-610C** and **614A-614C** captured by the separate cameras **604** and **608** may be used within the same group of image frames to form a composite image.

(57) In this regard, the low-resolution image frames **610A-610C** and **614A-614C** captured by the separate cameras **604** and **608** may be used within the same group of image frames to form a composite image. FIG. 7 illustrates an example of generating a composite image using low-resolution images captured by separate image sensors within close proximity to one another during image capture. In particular, FIG. 7 illustrates image frames **610A-610C** (captured by camera **604**) and image frames **614A-614C** (captured by the camera **608**) grouped together in a single group of image frames to be used as input to super-resolution processing **702** to generate a composite image **712**.

(58) In some instances, utilizing additional image frame input captured from one or more additional cameras (with sufficiently similar poses at the time(s) of capture) may improve the quality of the composite image **712** generated via super-resolution processing **702**.

(59) FIG. 7 also illustrates additional inputs and/or components associated with super-resolution processing **702** that may influence the quality of composite images (e.g., composite image **712**) generated thereby. For example, FIG. 7 illustrates coarse depth information **704** that may be used as an input to super-resolution processing **702** for generating the composite image **712**. Coarse depth information **704** may be generated by performing sparse depth processing on two or more of the image frames **610A-610C** and/or **614A-614C** within the group of image frames used to generate the composite image **712**. For instance, feature extraction may be performed on two or more of the image frames, and stereo matching may be performed on the identified features to generate sparse or coarse depth information **704** that can be used to further guide the super-resolution processing **702** to generate the composite image **712**. In some instances, feature matching information may additionally or alternatively be used as an input to the super-resolution processing **702**.

(60) FIG. 7 also illustrates pose information **706** that may be used as an input to super-resolution processing **702**. The pose information **706** may comprise the pose values associated with one or more of the various low-resolution image frames **610A-610C** and **614A-614C** used as input to super-resolution processing **702** to generate the composite image **712**. The pose values may provide an indication of the relative perspectives from which the various image frames were captured and thereby improve the super-resolution processing **702** to generate the composite image **712**.

(61) FIG. 7 furthermore illustrates that super-resolution processing **702** may be associated with additional algorithms for improving the composite image **712** output from the super-resolution processing **702**. For instance, FIG. 7 depicts the super-resolution processing in association with rolling shutter correction **708** and motion blur compensation **710**. Where the image frames **610A-610C** and/or **614A-614C** are captured using rolling shutter cameras, rolling shutter correction **708**

may comprise performing per-scanline corrections to the image frame input based on per-scanline pose values recorded during rolling shutter capture of the image frames. Such corrections may be performed on the image frames prior to providing them as input to super-resolution processing **702** or may be performed as part of the super-resolution processing **702** itself. Motion blur compensation **710** may comprise any pose-based, computer-vision-based, or other type of motion blur compensation processing known in the art. Additional or alternative inputs and/or algorithms may be applied to influence the quality of the composite image **712** generated via super-resolution processing **702**.

(62) One will appreciate, in view of the present disclosure, that the types of inputs and/or algorithms for super-resolution processing **702** discussed with reference to FIG. 7 may be used in the various configurations for generating composite images, depth information, and/or other output based on low-resolution images (e.g., such as where the image frame input is captured by a single camera, or in other situations described herein or contemplated hereby).

(63) FIG. 8 illustrates a depth map **802**, which is generated based on one or more composite images as described herein (e.g., similar to depth map **310** of FIG. 3C, or depth map **510** of FIG. 5). The depth map **802** includes depth values representative of the building **206** shown previously. FIG. 8 also includes a depth map **804** representative of the building **206** from a different capture perspective than the depth map **802**. FIG. 8 illustrates that depth information from multiple depth maps (or a single depth map) may be used to generate a surface mesh **808**. The surface mesh **808** may describe the objects represented in the depth map(s) **802** and/or **804** three-dimensionally and may therefore be used for various applications that utilize 3D models (e.g., MR experiences). Depth maps may be combined utilizing various techniques, such as feature alignment/stitching. The ellipsis **806** indicates that other depth maps capturing the building **206** from additional perspectives may be used to form the surface mesh **808**.

(64) As indicated hereinabove, utilizing low-resolution images to generate composite images may reduce computer storage burden and/or bandwidth requirements associated with capturing useful aerial images of an environment. By way of example, FIG. 9 illustrates a system comprising drone **902** and camera **904**. Similar to other examples described herein, the camera **904** captures low-resolution image frames **906A**, **906B**, and **906C**, which are organized into a group **908** and provided as input to super-resolution processing **910** to form a composite image **912**. As illustrated in FIG. 9, the system may store the composite image **912** in non-volatile storage **914** such that the composite image **912** remains accessible after the system has lost power. FIG. 9 also illustrates the system transmitting the composite image **912** to remote device(s) **916**.

(65) FIG. 9 furthermore illustrates that the system may refrain from storing the image frames **906A-906C** in non-volatile storage **914** and may refrain from transmitting the image frames **906A-906C** to remote device(s) **916** (as indicated in FIG. 9 by the “X” symbols on the arrows extending from the image frames **906A-906C** to the non-volatile storage **914** and the remote device(s) **916**). The image frames **906A-906C** may instead be maintained in volatile storage until they have been provided as input to super-resolution processing **910** to generate the composite image **912**, after which the system may overwrite or delete the image frames **906A-906C**. In many instances, a composite image **912** may comprise a smaller file size than the combined size of the image frames **906A-906C** that form the group **908** of image frames used to form the composite image. In this way, storing the composite image **912** while refraining from storing the group **908** of image frames in a non-volatile manner may allow the system to store image data capturing a greater portion of an environment. Similarly, refraining from transmitting the group **908** of image frames to remote device(s) **916** may allow for reduced bandwidth for transmitting image data capturing an environment.

(66) Although at least some of the foregoing examples have referred to aerial or other vehicles “traveling” within an environment during capture of low-resolution image frames, one will appreciate, in view of the present disclosure, that low-resolution image frames may be captured

from a substantially static position in an environment, or during consecutive actions of maintaining a position within an environment and traveling/reorienting within an environment.

Example Method(s) for Generating Depth Information from Low-Resolution Images

(67) The following discussion now refers to a number of methods and method acts that may be performed by the disclosed systems. Although the method acts are discussed in a certain order and illustrated in a flow chart as occurring in a particular order, no particular ordering is required unless specifically stated, or required because an act is dependent on another act being completed prior to the act being performed. One will appreciate that certain embodiments of the present disclosure may omit one or more of the acts described herein.

(68) FIGS. **10** and **11** illustrate example flow diagrams **1000** and **1100**, respectively, depicting acts associated with generating depth information from low-resolution images. The discussion of the various acts represented in the flow diagrams include references to various hardware components described in more detail with reference to FIG. **1**.

(69) Act **1002** of flow diagram **1000** includes accessing a plurality of image frames capturing an environment. Act **1002** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some instances, the system comprises a vehicle (e.g., an aerial vehicle, or other type of vehicle) that includes an image capture device that captures the plurality of image frames while traveling within the environment.

(70) Act **1004** of flow diagram **1000** includes identifying a first group of image frames from the plurality of image frames. Act **1004** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some instances, the image frames of the first group of image frames are consecutively captured image frames. In some implementations, the image frames of the first group of image frames are identified based on pose associated with the image frames of the first group of image frames.

(71) Act **1006** of flow diagram **1000** includes generating a first image comprising a first composite image of the environment using the first group of image frames as input, the first composite image comprising an image resolution that is higher than an image resolution of the image frames of the first group of image frames. Act **1006** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some implementations, generating the first image includes using pose values associated with the first group of image frames as input. In some instances, generating the first image includes using an additional image frame as input, such as an additional frame captured by a second image capture device that is untethered from a first image capture device that captures the first group of image frames.

(72) Furthermore, in some implementations, generating the first image includes using input based on coarse depth information determined from the first group of image frames. Still furthermore, in some instances, generating the first image includes rolling shutter correction processing and/or motion blur compensation processing.

(73) Act **1008** of flow diagram **1000** includes obtaining a second image of the environment, wherein parallax exists between a capture perspective associated with the first image and a capture perspective associated with the second image. Act **1008** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some implementations, the second image comprises a second composite image of the environment. The second composite image may be generated based on a second group of image frames capturing the environment, and the second composite image may include an image resolution that is higher than an image resolution of the image frames of the second group of image frames.

(74) In some instances, the second group of image frames is captured by a second image capture

device that is untethered from a first image capture device that captures the first group of image frames. In some instances, the second group of images is captured by a same image capture device that captures the first group of image frames. Furthermore, in some instances, the second group of images is captured temporally subsequent to the first group of images.

(75) Act **1010** of flow diagram **1000** includes generating depth information for the environment based on the first image and the second image. Act **1010** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. The depth information may take on various forms, such as a depth map or a disparity map. The depth information may enable various applications, such as generating a surface reconstruction mesh of the captured environment.

(76) Act **1012** of flow diagram **1000** includes obtaining second depth information for the environment, the depth information and the second depth information representing an overlapping portion of the environment. Act **1012** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some implementations, the second depth information is obtained based on groups of image frames captured by a same image capture device that captures the first group of image frames.

(77) Act **1014** of flow diagram **1000** includes generating a composite mesh of the environment based on the depth information and the second depth information. Act **1014** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. A composite mesh of the environment may comprise a 3D representation of the environment.

(78) Referring now to FIG. **11**, act **1102** of flow diagram **1100** includes capturing a plurality of image frames of an environment. Act **1102** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some implementations, the image capture device is connected to a vehicle (e.g., an aerial vehicle or other type of vehicle) traveling within the environment during capture of the plurality of image frames.

(79) Act **1104** of flow diagram **1100** includes selecting a first group of image frames from the plurality of image frames. Act **1104** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some implementations, the image frames of the first group of image frames are consecutively captured image frames. In some instances, the image frames of the first group of image frames are identified based on pose associated with the image frames of the first group of image frames.

(80) Act **1106** of flow diagram **1100** includes generating a first composite image of the environment using the first group of image frames as input, the first composite image comprising an image resolution that is higher than an image resolution of the image frames of the first group of image frames. Act **1106** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some implementations, generating the first composite image includes using pose values associated with the first group of image frames as input. In some instances, generating the first composite image includes using an additional image frame as input, wherein the additional image frame is captured by a second image capture device that is untethered from the image capture device. Furthermore, in some implementations, generating the first composite image includes using input based on coarse depth information determined from the first group of image frames. Still furthermore, in some instances, generating the first composite image includes rolling shutter correction processing. Additionally, or alternatively, generating the first composite image includes motion blur compensation processing.

(81) Act **1108** of flow diagram **1100** includes (i) transmitting the first composite image to a remote

device while refraining from transmitting the first group of image frames to the remote device, or (ii) storing the first composite image in a nonvolatile manner while refraining from storing the first group of image frames in a nonvolatile manner. Act **1108** is performed, in some instances, by a system **100** utilizing processor(s) **102**, storage **104**, sensor(s) **110**, input/output system(s) **112**, communication system(s) **114**, and/or other components. In some implementations, act **1108** includes transmitting the first composite image to the remote device while refraining from transmitting the first group of image frames to the remote device. In some implementations, act **1108** includes storing the first composite image in a nonvolatile manner while refraining from storing the first group of image frames in a nonvolatile manner.

(82) Disclosed embodiments may comprise or utilize a special purpose or general-purpose computer including computer hardware, as discussed in greater detail below. Disclosed embodiments also include physical and other computer-readable media for carrying or storing computer-executable instructions and/or data structures. Such computer-readable media can be any available media that can be accessed by a general-purpose or special-purpose computer system. Computer-readable media that store computer-executable instructions in the form of data are one or more “physical computer storage media” or “hardware storage device(s).” Computer-readable media that merely carry computer-executable instructions without storing the computer-executable instructions are “transmission media.” Thus, by way of example and not limitation, the current embodiments can comprise at least two distinctly different kinds of computer-readable media: computer storage media and transmission media.

(83) Computer storage media (aka “hardware storage device”) are computer-readable hardware storage devices, such as RAM, ROM, EEPROM, CD-ROM, solid state drives (“SSD”) that are based on RAM, Flash memory, phase-change memory (“PCM”), or other types of memory, or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that can be used to store desired program code means in hardware in the form of computer-executable instructions, data, or data structures and that can be accessed by a general-purpose or special-purpose computer.

(84) A “network” is defined as one or more data links that enable the transport of electronic data between computer systems and/or modules and/or other electronic devices. When information is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a computer, the computer properly views the connection as a transmission medium. Transmission media can include a network and/or data links which can be used to carry program code in the form of computer-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer. Combinations of the above are also included within the scope of computer-readable media.

(85) Further, upon reaching various computer system components, program code means in the form of computer-executable instructions or data structures can be transferred automatically from transmission computer-readable media to physical computer-readable storage media (or vice versa). For example, computer-executable instructions or data structures received over a network or data link can be buffered in RAM within a network interface module (e.g., a “NIC”), and then eventually transferred to computer system RAM and/or to less volatile computer-readable physical storage media at a computer system. Thus, computer-readable physical storage media can be included in computer system components that also (or even primarily) utilize transmission media.

(86) Computer-executable instructions comprise, for example, instructions and data which cause a general-purpose computer, special purpose computer, or special purpose processing device to perform a certain function or group of functions. The computer-executable instructions may be, for example, binaries, intermediate format instructions such as assembly language, or even source code. Although the subject matter has been described in language specific to structural features and/or methodological acts, it is to be understood that the subject matter defined in the appended claims is not necessarily limited to the described features or acts described above. Rather, the

described features and acts are disclosed as example forms of implementing the claims.

(87) Disclosed embodiments may comprise or utilize cloud computing. A cloud model can be composed of various characteristics (e.g., on-demand self-service, broad network access, resource pooling, rapid elasticity, measured service, etc.), service models (e.g., Software as a Service (“SaaS”), Platform as a Service (“PaaS”), Infrastructure as a Service (“IaaS”), and deployment models (e.g., private cloud, community cloud, public cloud, hybrid cloud, etc.).

(88) Those skilled in the art will appreciate that the invention may be practiced in network computing environments with many types of computer system configurations, including, personal computers, desktop computers, laptop computers, message processors, hand-held devices, multi-processor systems, microprocessor-based or programmable consumer electronics, network PCs, minicomputers, mainframe computers, mobile telephones, PDAs, pagers, routers, switches, wearable devices, and the like. The invention may also be practiced in distributed system environments where multiple computer systems (e.g., local and remote systems), which are linked through a network (either by hardwired data links, wireless data links, or by a combination of hardwired and wireless data links), perform tasks. In a distributed system environment, program modules may be located in local and/or remote memory storage devices.

(89) Alternatively, or in addition, the functionality described herein can be performed, at least in part, by one or more hardware logic components. For example, and without limitation, illustrative types of hardware logic components that can be used include Field-programmable Gate Arrays (FPGAs), Program-specific Integrated Circuits (ASICs), Application-specific Standard Products (ASSPs), System-on-a-chip systems (SOCs), Complex Programmable Logic Devices (CPLDs), central processing units (CPUs), graphics processing units (GPUs), and/or others.

(90) As used herein, the terms “executable module,” “executable component,” “component,” “module,” or “engine” can refer to hardware processing units or to software objects, routines, or methods that may be executed on one or more computer systems. The different components, modules, engines, and services described herein may be implemented as objects or processors that execute on one or more computer systems (e.g., as separate threads).

(91) One will also appreciate how any feature or operation disclosed herein may be combined with any one or combination of the other features and operations disclosed herein. Additionally, the content or feature in any one of the figures may be combined or used in connection with any content or feature used in any of the other figures. In this regard, the content disclosed in any one figure is not mutually exclusive and instead may be combinable with the content from any of the other figures.

(92) The present invention may be embodied in other specific forms without departing from its spirit or characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

Claims

1. A system for generating depth information from low-resolution images of a captured environment, the system comprising: one or more processors; and one or more hardware storage devices storing instructions that are executable by the one or more processors to configure the system to generate depth information from low-resolution images of a captured environment by configuring the system to: access a plurality of image frames capturing an environment and acquired by one or more image capture devices; identify a first group of image frames from the plurality of image frames; generate a first image comprising a first composite image of the environment using the first group of image frames as input and using super-resolution imaging techniques, the first composite image comprising an image resolution that is higher than an image

resolution of the image frames of the first group of image frames; obtain a second image of the environment, wherein parallax exists between a capture perspective associated with the first composite image and a capture perspective associated with the second image, wherein the second image comprises an image resolution that is higher than the image resolution of the image frames of the first group of image frames; and generate depth information for the environment based on the first composite image and the second image.

2. The system of claim 1, wherein the system comprises a vehicle, and wherein the vehicle comprises an image capture device that captures the plurality of image frames while traveling within the environment.
3. The system of claim 1, wherein the image frames of the first group of image frames are consecutively captured image frames.
4. The system of claim 1, wherein the image frames of the first group of image frames are identified based on pose associated with the image frames of the first group of image frames.
5. The system of claim 1, wherein the second image comprises a second composite image of the environment, the second composite image being generated based on a second group of image frames capturing the environment, the second composite image comprising an image resolution that is higher than an image resolution of the image frames of the second group of image frames.
6. The system of claim 5, wherein the second group of image frames is captured by a second image capture device that is untethered from a first image capture device that captures the first group of image frames.
7. The system of claim 5, wherein the second group of image frames is captured by a same image capture device that captures the first group of image frames.
8. The system of claim 7, wherein the second group of image frames is captured temporally subsequent to the first group of image frames.
9. The system of claim 1, wherein generating the first image includes using pose values associated with the first group of image frames as input.
10. The system of claim 1, wherein generating the first image includes using an additional image frame as input, wherein the additional image frame is captured by a second image capture device that is untethered from a first image capture device that captures the first group of image frames.
11. The system of claim 1, wherein generating the first image includes using input based on coarse depth information determined from the first group of image frames.
12. The system of claim 1, wherein generating the first image includes rolling shutter correction processing.
13. The system of claim 1, wherein generating the first image includes motion blur compensation processing.
14. The system of claim 1, wherein the instructions are executable by the one or more processors to further configure the system to: obtain second depth information for the environment, the depth information and the second depth information representing an overlapping portion of the environment; and generate a composite mesh of the environment based on the depth information and the second depth information.
15. The system of claim 14, wherein the second depth information is obtained based on groups of image frames captured by a same image capture device that captures the first group of image frames.
16. An image capture device, comprising: an image sensor; one or more processors; and one or more hardware storage devices storing instructions that are executable by the one or more processors to configure the image capture device to capture images of an environment to facilitate generation of depth information for the environment by configuring the image capture device to: capture a plurality of image frames of an environment using the image sensor; select a first group of image frames from the plurality of image frames; generate a first composite image of the environment using the first group of image frames as input and using super-resolution imaging

techniques, the first composite image comprising an image resolution that is higher than an image resolution of the image frames of the first group of image frames, wherein generating the first composite image includes using an additional image frame as input, wherein the additional image frame is captured by a second image capture device that is untethered from the image capture device; and (i) transmit the first composite image to a remote device while refraining from transmitting the first group of image frames to the remote device, or (ii) store the first composite image in a nonvolatile manner while refraining from storing the first group of image frames in a nonvolatile manner.

17. The image capture device of claim 16, wherein the image capture device is connected to a vehicle traveling within the environment during capture of the plurality of image frames.

18. The image capture device of claim 16, wherein the image frames of the first group of image frames are consecutively captured image frames.

19. The image capture device of claim 16, wherein the image frames of the first group of image frames are identified based on pose associated with the image frames of the first group of image frames.

20. The image capture device of claim 16, wherein generating the first composite image includes using pose values associated with the first group of image frames as input.
