

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414252
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Son; Jiho et al.

Display panel and a manufacturing method thereof

Abstract

Disclosed is a display panel and a manufacturing method thereof. The display panel includes a plurality of ink layers applied in a cover window and a manufacturing method thereof.

Inventors: Son; Jiho (Paju-si, KR), Kim; Geonhyeong (Paju-si, KR), Jung; Hoyoon (Paju-si, KR)

Applicant: LG Display Co., Ltd. (Seoul, KR)

Family ID: 86991466

Assignee: LG Display Co., Ltd. (Seoul, KR)

Appl. No.: 17/976299

Filed: October 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230217619 A1	Jul. 06, 2023

Foreign Application Priority Data

KR	10-2021-0192360	Dec. 30, 2021
----	-----------------	---------------

Publication Classification

Int. Cl.: H05K5/03 (20060101); B32B7/12 (20060101); C09D11/037 (20140101); B32B17/06 (20060101); B32B27/28 (20060101); H10K59/12 (20230101)

U.S. Cl.:

CPC **H05K5/03** (20130101); **B32B7/12** (20130101); **C09D11/037** (20130101); B32B17/06 (20130101); B32B27/281 (20130101); B32B2255/10 (20130101); B32B2255/28 (20130101); B32B2307/412 (20130101); B32B2307/42 (20130101); B32B2457/20 (20130101); H10K59/12 (20230201)

Field of Classification Search

CPC: B32B (3/30); G02F (1/133331); H10K (50/8426); H10K (50/865); H10K (59/10); H10K (59/12); H10K (59/40); H10K (59/873); H10K (59/8792)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
10804486	12/2019	Kim et al.	N/A	N/A
2018/0184529	12/2017	Kim et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
110865741	12/2019	CN	G02F 1/13338
10-2018-0074270	12/2017	KR	N/A
10-2019-0031398	12/2018	KR	N/A
10-2019-0072134	12/2018	KR	N/A

OTHER PUBLICATIONS

CN 110865741 Machine Translation (Year: 2020). cited by examiner
KR 2019-0031398 Machine Translation (Year: 2019). cited by examiner
Korean Intellectual Property Office, Office Action, Korean Patent Application No. 10-2021-0192360, Nov. 13, 2024, 18 pages. cited by applicant

Primary Examiner: Davis; Zachary M

Attorney, Agent or Firm: Fenwick & West LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

(1) The present application claims priority to Republic of Korea Patent Application No. 10-2021-0192360, filed on Dec. 30, 2021, which is hereby incorporated by reference in its entirety.

BACKGROUND

Field of Technology

(2) The present disclosure relates to a display panel and a manufacturing method thereof and particularly to a display panel having a plurality of ink layers applied in a cover window and a manufacturing method thereof.

Description of the Related Art

(3) As examples of a display device, a liquid crystal display (LCD), a field emission display device (FED), an electrowetting display device (EWD) and an organic light emitting display device

(OLED) are used.

(4) Such a display device may include a cover window made of a glass or plastic material so as to protect a display panel from external shocks. An adhesive layer is applied to the cover window in order to laminate a polarizer or a panel layer below the cover window. The adhesive layer is swept in a side of the cover window while laminating the polarizer or the panel layer and the adhesive layer remains on a side of the cover window.

(5) The leftover of the adhesive layer remaining on a side of the cover window may cause a problem such as an adhesion defect and the like if adhering a set frame such as a middle frame thereto.

SUMMARY

(6) The present disclosure aims to solve such a problem, specifically, to improve a problem of leftover on a side of the cover window occurring when laminating the cover window and a panel layer.

(7) One embodiment is a display panel including: a cover window; an adhesive layer configured to be disposed below the cover window; a first ink layer configured to be disposed below the cover window; a second ink layer configured to be disposed below the first ink layer and include a coarse pattern; and a panel layer configured to be disposed below the adhesive layer.

(8) The coarse pattern may include an embossed pattern.

(9) The embossed pattern includes a plurality of beads.

(10) The second ink layer may be formed in a pad printing method, and a second ink material being applied to a printing pad may include the plurality of beads.

(11) The coarse pattern may include an engraving pattern.

(12) The second ink layer may be formed in a pad printing method, and the printing pad may have an embossed pattern in an application area of a second ink material.

(13) An end of the first ink layer protrudes further inwards than an end of the second ink layer.

(14) A display panel may further comprise a third ink layer configured to be disposed below the first ink layer.

(15) The third ink layer may be disposed more inwards than the second ink layer and the third ink layer may be attached to a middle frame.

(16) The present disclosure provides a method of manufacturing a display panel comprising: transferring a first ink material onto a printing pad; forming a first ink layer by compressing the printing pad on a cover window; transferring a second ink material onto the printing pad; forming a second ink layer on which an embossed pattern is formed by compressing the printing pad on the cover window; and laminating a panel layer by applying an adhesive layer in the cover window.

(17) The second ink material includes a plurality of beads.

(18) A method of manufacturing a display panel may further comprise: before laminating the panel layer, transferring a third ink material onto the printing pad; and forming a third ink layer by compressing the printing pad on the cover window.

(19) A method of manufacturing a display panel may further comprise attaching a middle frame to the third ink layer.

(20) The present disclosure provides a method of manufacturing a display panel comprising: transferring a first ink material onto a printing pad; forming a first ink layer by compressing the printing pad on a cover window; transferring a second ink material onto the printing pad; forming a second ink layer on which an engraving pattern is formed by compressing the printing pad on the cover window; and laminating a panel layer by applying an adhesive layer in the cover window.

(21) Transferring the second ink material may comprise compressing the printing pad on which an embossed pattern is formed on the second ink material.

(22) A method of manufacturing a display panel may further comprise: before laminating the panel layer, transferring a third ink material onto the printing pad; and forming a third ink layer by compressing the printing pad on the cover window.

- (23) A method of manufacturing a display panel may further comprise attaching a middle frame to the third ink layer.
- (24) According to the present disclosure, by forming the second ink layer that includes an embossed coarse pattern below the cover window, a problem of leftover may improve, which occurs on a side of the cover window when the adhesive layer is swept.
- (25) According to the present disclosure, by forming the second ink layer that includes an engraving coarse pattern below the cover window, a problem of leftover may improve, which occurs on a side of the cover window when the adhesive layer is swept.
- (26) According to the present disclosure, by forming the third ink layer below the cover window, adhesion with the middle frame may improve.
- (27) According to the present disclosure, by forming the first ink layer to protrude more than the second ink layer, a problem of the adhesive layer being detached from the cover window may improve.
- (28) The present disclosure may provide a method of manufacturing the display panel in which the second ink layer including an embossed coarse pattern is formed below the cover window.
- (29) The present disclosure may provide a method of manufacturing the display panel in which the second ink layer including the coarse engraving pattern is formed below the cover window.
-

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a block diagram of a display panel according to an embodiment of the present disclosure.
- (2) FIG. 2 is a circuit diagram of a sub-pixel included in a display panel according to an embodiment of the present disclosure.
- (3) FIG. 3 is a plan view of a display panel according to an embodiment of the present disclosure.
- (4) FIG. 4 is a sectional view of a panel layer taken along I-I' of FIG. 3 according to an embodiment of the present disclosure.
- (5) FIG. 5 is a sectional view of a panel layer taken along II-II' of FIG. 3 according to an embodiment of the present disclosure.
- (6) FIG. 6 is a perspective view of a flexible panel according to an embodiment of the present disclosure.
- (7) FIG. 7 is a perspective view that shows a bending status of a flexible substrate according to an embodiment of the present disclosure.
- (8) FIG. 8 is a plan view that shows a bent flexible panel according to an embodiment of the present disclosure.
- (9) FIGS. 9A and 9B show cross sections taken along A-A' of FIG. 8 according to an embodiment of the present disclosure.
- (10) FIG. 10 is a modified embodiment of the embodiment of FIG. 9 and shows a cross section taken along A-A' of FIG. 8 according to an embodiment of the present disclosure.
- (11) FIGS. 11A to 11B shows cross sections taken along A-A' of FIG. 8 according to another embodiment of the present disclosure.
- (12) FIG. 12 is a modified embodiment of the embodiment of FIG. 11 and shows a cross section taken along A-A' of FIG. 8 according to an embodiment of the present disclosure.
- (13) FIGS. 13A and 13B show cross sections taken along A-A' of FIG. 8 according to an embodiment of the present disclosure.
- (14) FIGS. 14A and 14B show cross sections taken along A-A' of FIG. 8 according to another embodiment of the present disclosure.
- (15) FIGS. 15A to 15F are drawings describing a manufacturing method of a display panel

according to an embodiment of the present disclosure.

(16) FIGS. **16A** to **16F** are drawings describing a manufacturing method of a display panel according to another embodiment of the present disclosure.

DETAILED DESCRIPTION

(17) Hereinafter, the embodiments will be described with reference to the accompanying drawings. When an element (or an area, a layer, a part and the like) is 'on' another element, is 'connected' with, or is 'coupled' with another element, the element may be directly connected with or coupled to another element or a third intervening element may be disposed therebetween.

(18) Like reference numerals of the accompanying drawings denote like elements. In addition, thicknesses, ratio and dimensions of the elements in the accompanying drawings are exaggerated for convenience of describing the specification. The term "and/or" includes any and all combinations of one or more of the associated listed items.

(19) Though terms such as 'a first', or 'a second' are used to describe various components, these components are not confined by these terms. These terms are merely used to distinguish one component from the other component. For example, without departing from the scope of the rights of various embodiments of the present invention, a first component may be referred to as a second component, and similarly, a second component may be referred to as a first component. The singular forms expressed herein are intended to include the plural forms as well, unless the context expressly indicates otherwise.

(20) Terms such as 'below', 'at a lower portion', 'on', 'at an upper portion' and the like are used to describe position relation of parts illustrated in the accompanying drawings. Such terms are of relative concept, and are explained based on the directions marked in the drawings.

(21) It should be understood that terms such as 'comprise', or 'have' and the like are used only to designate that there are features, numbers, steps, operations, components, parts or combination thereof, however such terms do not preclude existence or addition of one or more another features, numbers, steps, operations, components, parts or combination thereof.

(22) Also, the present disclosure decided to explain an organic light emitting display device as an example for convenience of description. However, the concept of the present disclosure is not confined by the organic light emitting display device, and may be applied in the same way to other types of display panels such as a liquid crystal display panel, a mini-LED display panel and the like.

(23) FIG. **1** is a block diagram of a display panel according to an embodiment of the present disclosure.

(24) Referring to FIG. **1**, a display panel **100** may include an image processor **151**, a timing controller **152**, a data driver **153**, a gate driver **154**, and a panel layer **110**.

(25) The image processor **151** may output a data enable signal (DE) and a data signal (DATA) being supplied from the outside. Apart from the data enable signal (DE), the image processor **151** may output one or more signals among a vertical synchronizing signal, a horizontal synchronization signal and a clock signal.

(26) The timing controller **152** is supplied with the data signal (DATA), and a driving signal that includes the data enable signal (DE), a vertical synchronizing signal, a horizontal synchronizing signal and a clock signal from the image processor **151**. The timing controller **152** may output a gate timing control signal (GDC) for controlling an operation timing of a gate driver **154**, and a data timing control signal (DDC) for controlling an operation timing of a data driver **153**.

(27) In response to the data timing control signal (DDC) supplied from the timing controller **152**, the data driver **153** may convert the data signal (DATA) into gamma reference voltages through sampling and latching and output it thereafter. The data driver **153** may output the data signal (DATA) through data lines (DL1~DLn).

(28) The gate driver **154** may output a gate signal while shifting a level of a gate voltage in response to the gate timing control signal (GDC) supplied by the timing controller **152**. The gate

driver **154** may output the gate signal through gate lines (GL1~GLm).

(29) The panel layer **110** may display images as sub-pixels (P) emit light by responding to the data signal (DATA) and the gate signal supplied by the data driver **153** and the gate driver **154**. Detailed structure of a sub-pixel (P) will be described with reference to FIG. 2 to FIG. 5.

(30) FIG. 2 is a circuit diagram of a sub-pixel included in a display panel **100** according to an embodiment of the present disclosure.

(31) Referring to FIG. 2, a sub-pixel of a display panel **100** may include a switching transistor (ST), a driving transistor (DT), a compensation circuit **135**, and a light emitting element **130**.

(32) The light emitting element **130** may operate to emit light responsive to a driving current formed by a driving transistor (DT).

(33) The switching transistor (ST) may operate switching so that the data signal supplied through a data line **117** responding to the gate signal provided through a gate line **116** can be saved as a data voltage in a capacitor.

(34) The driving transistor (DT) may operate to flow a regular driving current between a high potential power line (VDD) and a low potential power line (GND), by corresponding to a data voltage stored in a capacitor.

(35) The compensation circuit **135** compensates a threshold voltage of the driving transistor (DT) and the like, and the compensation circuit **135** may include one or more thin film transistors and capacitors. Configuration of the compensation circuit **135** may vary greatly depending on manners of compensation. For example, a sub-pixel in FIG. 2 is configured as 2T1C (two Transistors and one Capacitor) structure which includes a switching transistor (ST), a driving transistor (DT), a capacitor, and a light emitting element **130**. However, if a compensation circuit **135** is added thereto, the sub-pixel may be configured variously such as 3T1C, 4T2C, 5T2C, 6T1C, 6T2C, 7T1C, 7T2C and the like.

(36) FIG. 3 is a plan view of a display panel according to an embodiment of the present disclosure.

(37) FIG. 3 shows an example of a state where a panel layer of the display panel **100** is not bent.

(38) Referring to FIG. 3, the panel layer **110** may include an active area (AA) where pixels emitting light through a thin film transistor and a light emitting element are disposed upon a flexible substrate **111**, and a non-active area (NA) that is the bezel area surrounding edges of the active area (AA).

(39) In the non-active area (NA) of the flexible substrate **111**, a circuit such as a gate driver **154** to drive the panel layer **110** and the like and wirings of various signals such as a scan line (SL) and the like may be disposed.

(40) A circuit to drive the panel layer **110** may be disposed upon the flexible substrate **111** in gate in panel (GIP) manner, or be connected to the flexible substrate **111** in tape carrier package (TCP) or chip on film (COF) manner.

(41) A bending area (BA) may be formed at a side of the non-active area (NA). The bending area (BA) may refer to an area of the flexible substrate **111** that is configured to be bent in an arrow direction.

(42) In the non-active area (NA) of the flexible substrate **111**, wirings and a driving circuit in order to drive a screen are disposed. Since an image is not displayed in the non-active area (NA), the non-active area (NA) does not need to be acknowledged from a front surface of the flexible substrate **111**. Therefore, an area to position the wirings and the driving circuit can be secured while at the same time reducing the bezel, by bending some area of the non-active area (NA) of the flexible substrate **111**.

(43) Various wirings may be formed upon the flexible substrate **111**. The wiring may be formed in the active area (AA) of the substrate **111**. The wiring may be formed in the active area (AA) or in the non-active area (NA) of the flexible substrate **111**. The wiring of circuits **140** is formed of a conductive material, and may be formed of a conductive material with excellent flexibility in order to reduce a crack caused when the flexible substrate **111** is bent. The wiring of circuits **140** may be

formed of a conductive material with excellent flexibility. The wiring of circuits **140** may be formed of conductive materials having excellent flexibility such as gold (Au), silver (Ag), aluminum (Al) and the like. Alternatively, the wiring of circuits **140** may be formed of alloys of magnesium (Mg) and silver (Ag), molybdenum (Mo), chrome (Cr), titanium (Ti), nickel (Ni), neodymium (Nd) and copper (Cu). The wiring of circuits **140** may be formed in a multi-layer structure that includes various conductive materials, and for example, may be formed in a three-layer structure of titanium (Ti), aluminum (Al) and titanium (Ti).

(44) The wiring of circuits **140** formed in the bending area (BA) receives tensile force when being bent. The wiring of circuits **140** that extends in the same direction as a bending direction in the flexible substrate **111** gets the largest tensile force. Therefore, some of the wiring of circuits **140** disposed in the bending area (BA) may be formed to extend in a diagonal direction which differs from the bending direction.

(45) FIG. **4** is a sectional view of a panel layer taken along I-I' of FIG. **3** according to one embodiment.

(46) FIG. **5** is a sectional view of a panel layer taken along II-II' of FIG. **3** according to one embodiment.

(47) The panel layer **110** according to the present disclosure will be described by referring to FIG. **4** and FIG. **5**.

(48) Referring to FIG. **4**, the flexible substrate **111** is a plate-shaped configuration disposed at the bottom, and serves to support and protect other components disposed upon the flexible substrate **111**. The flexible substrate **111** may be formed of glass or plastic. For example, the flexible substrate **111** may be formed of a film including one of the groups consisting of a polyester polymer, a silicone polymer, an acrylic polymer, a polyolefin polymer, and a copolymer thereof.

(49) A buffer layer (not illustrated) may be further disposed in the flexible substrate **111**. The buffer layer prevents or at least reduces penetration of moisture or foreign substance from the outside into the flexible substrate **111**, and may flatten a surface of the flexible substrate **111**. The buffer layer is not a necessary configuration, and may be omitted depending on a kind of thin film transistor **120** disposed in the flexible substrate **111**.

(50) The thin film transistor **120** is disposed in the flexible substrate **111** and may include a gate electrode **121**, a source electrode **122**, a drain electrode **123**, and a semiconductor layer **124**. The semiconductor layer **124** may be formed of amorphous silicon or polycrystalline silicon. The semiconductor layer **124** may be formed of an oxide semiconductor. The semiconductor layer **124** may include a drain region, a source region including p-type or n-type impurities and a channel region existing between the source region and the drain region. In addition, the semiconductor layer **124** may further include a lightly-doped region in the source region or the drain region located adjacent to the channel region.

(51) The source region or the drain region are heavily doped with impurities and the source electrode **122** and the drain electrode **123** of the thin film transistor **120** may be connected thereto respectively.

(52) Depending on a structure of the thin film transistor of NMOS or PMOS, the channel region of the semiconductor layer **124** may be doped with n-type or p-type impurities.

(53) A first insulation layer **115a** may be formed of a single layer or multi-layer structure of silicon oxide (SiOx) or silicon nitride (SiNx). The first insulation layer **115a** may be disposed so that a current flowing through the semiconductor layer **124** does not flow to the gate electrode **121**.

(54) The gate electrode **121** may serve as a switch for turning on or off the thin film transistor **120** based on an electric signal transmitted from the outside through the gate line. The source electrode **122** and the drain electrode **123** are connected to the data line, and may allow an electric signal transmitted from the outside to be transmitted from the thin film transistor **120** to the light emitting element **130**.

(55) A second insulation layer **115b** may be formed on the first insulation layer **115a** and the gate

electrode **121**. The second insulation layer **115b** may be formed of a single layer or multiple layers of silicon oxide or silicon nitride to insulate the gate electrode **121**, the source electrode **122** and the drain electrode **123** with each other.

(56) A first planarization layer **115c** and a second planarization layer **115d** may be disposed on the second insulation layer **115b**. The first planarization layer **115c** and the second planarization layer **115d** may be configurations to protect the thin film transistor **120** and flatten out steps formed by the thin film transistor **120**. The first planarization layer **115c** and the second planarization layer **115d** may be formed of one or more materials among acrylic resin, epoxy resin, phenol resin, polyamide resin, unsaturated polyester resin, poly-phenylene resin, poly-phenylene sulfide resin, and benzocyclobutene.

(57) An intermediate electrode **125** may be connected to the thin film transistor **120** through a contact hole formed in the first planarization layer **115c**. The intermediate electrode **125** may electrically connect an anode electrode **131** (to be described later) and the drain electrode **123** of the thin film transistor **120**.

(58) The light emitting element **130** may be disposed on the second planarization layer **115d**. The light emitting element **130** may include the anode electrode **131**, a light-emitting portion **132**, and a cathode electrode **133**.

(59) The anode electrode **131** is disposed on the second planarization layer **115d**, and may serve to supply a hole to a light-emitting portion **132**. The anode electrode **131** may be in contact with the intermediate electrode **125** through a contact hole formed to penetrate the second planarization layer **115d**. The anode electrode **131** may be formed of indium zinc oxide, indium tin oxide and the like which are transparent conductive materials.

(60) A bank **115e** may be disposed on the anode electrode **131** and the second planarization layer **115d**. The bank **115e** may define sub-pixels by dividing areas that actually emit light. A spacer **115f** may be disposed on the bank **115e** so as to prevent damage arising upon contacting with a deposition mask.

(61) The light-emitting portion **132** may be disposed on the anode electrode **131**. The light-emitting portion **132** may serve to emit light. The light-emitting portion **132** may include organic light emitting materials that emit light by themselves by an electric signal. The light-emitting portion **132** may include organic light emitting materials that emit colors, for example, red, green, blue, white and the like.

(62) The cathode electrode **133** may be disposed on the light-emitting portion **132**. The cathode electrode **133** may serve to supply an electron to the light-emitting portion **132**. The cathode electrode **133** may be formed of metal such as magnesium (Mg), an alloy of silver and magnesium and the like. In addition, the cathode electrode **133** may be formed of transparent conductive oxides such as series of tin oxide, indium zinc oxide, indium tin oxide, indium zinc tin oxide, zinc oxide and the like.

(63) An encapsulation layer **115g** may be disposed on the cathode electrode **133**. The encapsulation layer **115g** may serve to prevent or at least reduce damage arising out of oxidization of components disposed below after moisture, oxygen, or foreign material introduced from the outside penetrate into the components. The encapsulation layer **115g** may be formed by laminating a plurality of barrier films. The encapsulation layer **115g** may be formed of aluminum oxide or silicon nitride which are inorganic substances.

(64) In describing FIG. 5, matters that are redundant with what are mentioned above will be omitted.

(65) Referring to FIG. 5, the display panel **100** according to the present disclosure may include a first wiring **141** and a second wiring **142** configured in a double-layer in the non-active area (NA) including the bending area (BA).

(66) Specifically, in the flexible substrate **111**, the first wiring **141** may be formed. On the first wiring **141**, the first planarization layer **115c** may be formed. On the first planarization layer **115c**,

the second wiring **142** may be formed. On the second wiring **142**, the second planarization layer **115d** may be formed. On the second planarization layer **115d**, a micro-coating layer **145** may be formed.

(67) The first wiring **141** and the second wiring **142** are aimed at connecting the panel layer **110** and the pad area (PA). The first wiring **141** and the second wiring **142** may be formed of conductive materials having excellent flexibility such as silver, gold, aluminum and the like. Alternatively, the first wiring **141** and the second wiring **142** may be formed of alloys of molybdenum, chrome, titanium, nickel, neodymium, copper, silver and the like.

(68) While the flexible substrate **111** is bent, a huge stress is given to the bending area (BA). A crack may occur in layers that surround wirings due to such stress. Also, a large space to arrange the wirings is required when forming wirings in a single layer. As in the present disclosure, by configuring wirings passing the bending area (BA) to be formed in a multiple-layer structure, it is possible to reduce stress occurring in layers wrapping the wirings and decrease a space to arrange the wirings.

(69) FIG. **6** is a perspective view of a flexible panel according to an embodiment of the present disclosure.

(70) FIG. **7** is a perspective view that shows a bending status of a flexible substrate according to an embodiment of the present disclosure.

(71) FIG. **8** is a plan view that shows a bent flexible panel according to an embodiment of the present disclosure.

(72) Referring to FIG. **6** to FIG. **8**, the flexible substrate according to the present disclosure will be explained.

(73) Referring to FIG. **6**, the flexible substrate **111** may be divided into the active area (AA) and the non-active area (NA) surrounding edges of the active area (AA). In the non-active area (NA), the pad area (PA) in which the pads are disposed may be divided. In the active area (AA), a plurality of sub-pixels are disposed. The sub-pixels may be divided by gate lines and data lines that cross each other.

(74) A circuit element **161** may be a configuration that is connected with the pads in the pad area (PA) of the flexible substrate **111**. The circuit element **161** may include bumps or steps. The bumps of the circuit element **161** may be connected with the pads of the pad area (PA) through an anisotropic conductive film. The circuit element **161** may be a chip on film (COF) in which a driver IC is mounted in a flexible film. In addition, the circuit element **161** may be bonded to the pads directly through chip on glass (COG) process. Also, the circuit element **161** may be a flexible circuit such as a Flexible Printed Circuit (FPC). The present disclosure will be described based on COF taken as an example of the circuit element **161**.

(75) Referring to FIG. **7**, the flexible substrate **111** may be bent in a rear direction so that a side contacting with the pad area (PA) can have a predefined curvature. As the flexible substrate **111** gets bent, the pad area (PA) may overlap with the active area (AA) in a rear direction of the active area (AA). From the front of the display panel **100**, the circuit element **161** or the driver IC **165** (as shown in FIG. **8** to be described later) may not be made visible. For bending, the flexible substrate **111** may be formed of a flexible material. For example, the flexible substrate **111** may be formed of a plastic material such as polyimide.

(76) Referring to FIG. **8**, on a surface of the bent flexible substrate **111**, the cover window **164** may be coupled. The cover window **164** is formed to be larger than the bent flexible substrate **111** so that the cover window **164** can accommodate the flexible substrate **111** in its inside.

(77) Also, on another surface of the bent flexible substrate **111**, a backplate **101** may be coupled. The backplate **101** may serve to maintain rigidity of the display panel **100**, prevent or at least reduce foreign substances from attaching to the bottom portion of the display panel **100** and absorb external shocks. The backplate **101** may be implemented as a plastic thin film made of polyimide. Forming the backplate **101** not in the bending area (BA) may be appropriate.

(78) FIGS. 9A and 9B show cross sections taken along A-A' of FIG. 8 according to an embodiment of the present disclosure.

(79) FIGS. 9A and 9B illustrate the cover window **164**, the adhesive layer **163** disposed below the cover window **164**, a first ink layer **181** disposed below the cover window **164**, a second ink layer **182** disposed below the first ink layer **181** and has the coarse pattern and the panel layer **110** disposed below the adhesive layer **163**. Between the panel layer **110** and the adhesive layer **163**, a polarizer **162** may be additionally disposed. In addition, the backplate **101** may be additionally disposed below the panel layer **110**.

(80) The cover window **164** is disposed on an uppermost surface of the display panel **100** and may be formed of glass or plastic. The cover window **164** serves as a protection layer protecting internal elements of the display panel **100** and are exposed outside.

(81) The adhesive layer **163** is disposed below the cover window **164** and serves to adhere the cover window **164** to components disposed below, for example, the polarizer **162**, the panel layer **110**, the backplate **101** and the like. The adhesive layer **163** may be, for example, optical clear adhesive (OCA) or pressure sensitive adhesive (PSA) which are transparent materials.

(82) The polarizer **162** may be formed of a film having a feature of polarization. The polarizer **162** may suppress reflection of external light and reduce luminous reflectance. The polarizer **162** may be disposed in the active area (AA).

(83) The backplate **101** is a firm structure formed below the panel layer **110** and may serve to reinforce rigidity of the panel layer **110**. The backplate **101** may be formed of a thin plastic film.

(84) According to the present disclosure, the first ink layer **181** may be disposed below the cover window **164**. In addition, the second ink layer **182** may be disposed below the first ink layer **181**. The first ink layer **181** and the second ink layer **182** may be a black ink material. Therefore, if the first ink layer **181** and the second ink layer **182** are formed along outer edges of the cover window **164**, a black bezel may be formed along the outer edges of the cover window **164**. The black bezel formed in such a method may increase luminous efficiency of the display panel. Also, the ink layers may be formed in a different color other than black depending on a design.

(85) The second ink layer **182** may include a coarse pattern. Specifically, the second ink layer **182** may include an embossed pattern. In order to implement the embossed pattern, the second ink layer **182** may include a plurality of beads (B). The second ink layer **182** may be formed in a pad printing method, and a second ink material that forms the second ink layer **182** may include a plurality of beads (B). The second ink material is transferred onto a printing pad, and the printing pad may be compressed on the cover window **164**. Consequently, the second ink layer **182** formed below the cover window **164** may include a plurality of beads. How to form the first ink layer **181** and the second ink layer **182** in a pad printing method will be described with reference to FIG. 15 below.

(86) Referring to FIG. 9A, the adhesive layer **163**, the polarizer **162**, the panel layer **110** and the backplate **101** may be laminated as a first lamination below the cover window **164** in which the first ink layer **181** and the second ink layer **182** having an embossed coarse pattern are applied. The first lamination refers to laminating layers positioned in an inner direction of the display panel. The inner direction refers to a direction towards the center of the display panel and refers to A-direction that is a cut line based on FIGS. 9A and 9B. To the contrary, an outer direction of the display panel refers to a direction towards a perimeter and refers to A'-direction which is a cut line based on FIGS. 9A and 9B.

(87) As illustrated in in FIG. 9A, after the first lamination, the adhesive layer **163** and configurations disposed below the adhesive layer **163** which are the polarizer **162**, the panel layer **110** and the backplate **101** may seem to be hung at an end of the cover window **164**. That is because the first lamination compresses the inside of the display panel.

(88) As illustrated in FIG. 9B, after a second lamination, the adhesive layer **163** and configurations disposed below the adhesive layer **163** which are the polarizer **162**, the panel layer **110** and the backplate **101** may be settled on the inside of a rear surface of the cover window **164**. That is

because the second lamination compresses the outer part of the display panel where a curve is formed in the display panel.

(89) According to the present embodiment, the first ink layer **181** and the second ink layer **182** may be applied at an end of a rear surface of the cover window **164**. In addition, since the second ink layer **182** includes a plurality of beads (B), a surface of the second ink layer **182** may have an embossed coarse pattern.

(90) According to the present embodiment, since the second ink layer **182** has the coarse pattern, problems that are the leftover of the adhesive layer **163** in the second ink layer **182** and the swept mark in the adhesive layer **163** during the second lamination process may improve.

(91) Apart from the present embodiment, assume that the second ink layer **182** does not have the coarse pattern. The rear surface of the second ink layer **182** may be smooth. The adhesive layer **163** is an OCA or PSA material, and may have viscosity before hardened. During the second lamination after the first lamination, when the adhesive layer **163** having viscosity is moved towards the inside of the cover window **164**, since the surface of the second ink layer **182** being rubbed by the adhesive layer **163** is smooth, a degree of such rubbing is big. Therefore, some of the adhesive layer **163** is left on the surface of the second ink layer **182** as a leftover.

(92) According to the present embodiment, the coarse pattern of the second ink layer **182** serves to reduce an area contacting with the adhesive layer **163**. That is, the surface of the second ink layer **182** has curves due to the embossed pattern or beads (B), the area contacting with the adhesive layer **163** becomes relatively small. Therefore, even though the adhesive layer **163** having viscosity during the second lamination after finishing the first lamination is moved toward the inside of the cover window **164**, the degree of rubbing between the adhesive layer **163** and the second ink layer **182** is relatively small. Therefore, the leftover of the adhesive layer **163** does not exist in the surface of the second ink layer **182**.

(93) FIG. **10** is a modified embodiment of the embodiment of FIG. **9** and shows a cross section taken along A-A' of FIG. **8** according to one embodiment. In describing the embodiment of FIG. **10**, matters that are redundant will be omitted.

(94) FIG. **10** illustrates the cover window **164**, the adhesive layer **163** disposed below the cover window **164**, the first ink layer **181** disposed below the cover window **164**, the second ink layer **182** disposed below the first ink layer **181** and has the coarse pattern and the panel layer **110** disposed below the adhesive layer **163**. Between the panel layer **110** and the adhesive layer **163**, the polarizer **162** may be additionally disposed. Also, the backplate **101** may be additionally disposed below the panel layer **110**.

(95) According to the present embodiment, a third ink layer **183** may be disposed below the first ink layer **181**. Specifically, the third ink layer **183** may be formed on the same layer as the second ink layer **182**. Also, the third ink layer **183** may be disposed on more inner side than the second ink layer **182**. In addition, the third ink layer **183** may not include the coarse pattern.

(96) The middle frame **190** is a configuration forming an exterior of a bottom portion of the display panel and may be coupled to the lower portion of the cover window **164**. Specifically, the middle frame **190** may be coupled to an end portion of the cover window **164** and may be coupled by an adhesive material (not illustrated). Therefore, the middle frame **190** may be in contact with the second ink layer **182** and the third ink layer **183**.

(97) Apart from the present embodiment, assume that the third ink layer **183** is not formed below the cover window **164**. The embossed coarse pattern is formed on the surface of the second ink layer **182**. Therefore, the coupling strength between the second ink layer **182** and the middle frame **190** is low. As explained above, that is because an area contacting with the adhesive material (not illustrated) or the middle frame **190** is relatively reduced thanks to the embossed coarse pattern on the surface of the second ink layer **182**. Therefore, there may be a problem that the middle frame **190** detaches from the cover window **164**.

(98) The present embodiment suggests to dispose the third ink layer **183** below the first ink layer

181, dispose the third ink layer **183** on more inner side than the second ink layer **182** and attach the third ink layer **183** to the middle frame **190**. Since the third ink layer **183** does not have the embossed coarse pattern on the surface, attachment strength between the third ink layer **183** and the middle frame **190** may increase. Consequently, the problem of detachment that the middle frame **190** detaches from the cover window **164** may improve.

(99) FIGS. **11A** and **11B** show cross sections taken along A-A' of FIG. **8** according to another embodiment of the present disclosure. In describing the embodiment of FIG. **11**, matters that are redundant with what are mentioned above will be omitted.

(100) FIGS. **11A** and **11B** illustrate the cover window **164**, the adhesive layer **163** disposed below the cover window **164**, the first ink layer **181** below the cover window **164**, the second ink layer **182** disposed below the first ink layer **181** and has the coarse pattern and the panel layer **110** disposed below the adhesive layer **163**. The polarizer **162** may be additionally disposed between the panel layer **110** and the adhesive layer **163**. In addition, the backplate **101** may be additionally disposed below the panel layer **110**.

(101) According to the present disclosure, the first ink layer **181** may be disposed below the cover window **164**. In addition, the second ink layer **182** may be disposed below the first ink layer **181**.

(102) The second ink layer **182** may have the coarse pattern. Specifically, the second ink layer **182** may have an engraving pattern. In order to implement the engraving pattern, the second ink layer **182** may include an engraved part (EP) that is formed regularly or irregularly on the surface. The second ink layer **182** may be formed in the pad printing method, and an embossed pattern (for example, embossed part) may be formed in an application area to which apply the second ink material in the printing pad to which second ink material is transferred. When the second ink material is transferred onto the printing pad and the printing pad is compressed on the cover window **164**, the engraving pattern such as the engraved part (EP) may be formed in the second ink layer **182** that is formed below the cover window **164**. A method to form the first ink layer **181** and the second ink layer **182** in the pad printing method will be described hereinbelow with reference to FIG. **16**.

(103) Referring to FIG. **11A**, below the cover window **164** where the first ink layer **181** and the second ink layer **182** including the engraved coarse pattern are applied, the adhesive layer **163**, the polarizer **162**, the panel layer **110** and the backplate **101** may be laminated as a first lamination. The first lamination refers to laminating layers in an inner direction of the display panel. The inner direction refers to a direction towards a center of the display panel and refers to A-direction that is a cut line based on FIGS. **11A** and **11B**. To the contrary, an outer direction of the display panel refers to a direction towards a perimeter and refers to A'-direction which is a cut line based on FIGS. **11A** and **11B**.

(104) As illustrated in FIG. **11A**, after the first lamination, the adhesive layer **163** and configurations disposed below the adhesive layer **163** which are the polarizer **162**, the panel layer **110** and the backplate **101** may seem to be hung at an end of the cover window **164**. That is because the first lamination compresses the inside of the display panel.

(105) As illustrated in FIG. **11B**, after a second lamination, the adhesive layer **163** and configurations disposed below the adhesive layer **163** which are the polarizer **162**, the panel layer **110** and the backplate **101** may be settled on the inside of a rear surface of the cover window **164**. That is because the second lamination compresses the outer part of the display panel where a curve is formed.

(106) According to the present embodiment, the first ink layer **181** and the second ink layer **182** may be applied at an end of the rear surface of the cover window **164**. In addition, since the second ink layer **182** includes an engraved part (EP) to form an engraving pattern, a surface of the second ink layer **182** may have an engraved coarse pattern.

(107) According to the present embodiment, since the second ink layer **182** has the coarse pattern, problems that are the leftover of the adhesive layer **163** remaining in the second ink layer **182** and

the swept mark that may occur in the adhesive layer **163** during the second lamination process may improve.

(108) Apart from the present embodiment, assume that the second ink layer **182** does not have the coarse pattern. The rear surface of the second ink layer **182** may be smooth. The adhesive layer **163** is an OCA or PSA material, and may have viscosity before hardened. During the second lamination after the first lamination, when the adhesive layer **163** having viscosity is moved towards the inside of the cover window **164**, since the surface of the second ink layer **182** being rubbed by the adhesive layer **163** is smooth, a degree of such rubbing is big. Therefore, some of the adhesive layer **163** is left on the surface of the second ink layer **182** as a leftover.

(109) According to the present embodiment, the coarse pattern of the second ink layer **182** serves to reduce an area contacting with the adhesive layer **163**. That is, the surface of the second ink layer **182** has curves due to the embossed pattern or the engraved part (EP), the area contacting with the adhesive layer **163** becomes relatively small. Therefore, even though the adhesive layer **163** having viscosity during the second lamination after finishing the first lamination is moved toward the inside of the cover window **164**, the degree of rubbing between the adhesive layer **163** and the second ink layer **182** is relatively small. Therefore, the leftover of the adhesive layer **163** does not exist in the surface of the second ink layer **182**.

(110) FIG. **12** is a modified embodiment of the embodiment of FIG. **11** and shows a cross section taken along A-A' of FIG. **8**. In describing the embodiment of FIG. **12**, matters that are redundant will be omitted.

(111) FIG. **12** illustrates the cover window **164**, the adhesive layer **163** disposed below the cover window **164**, the first ink layer **181** disposed below the cover window **164**, the second ink layer **182** disposed below the first ink layer **181** and has the coarse pattern and the panel layer **110** disposed below the adhesive layer **163**. Between the panel layer **110** and the adhesive layer **163**, the polarizer **162** may be additionally disposed. Also, the backplate **101** may be additionally disposed below the panel layer **110**.

(112) According to the present embodiment, a third ink layer **183** may be disposed below the first ink layer **181**. Specifically, the third ink layer **183** may be formed on the same layer as the second ink layer **182**. Also, the third ink layer **183** may be disposed on more inner side than the second ink layer **182**. In addition, the third ink layer **183** may not include the coarse pattern.

(113) The middle frame **190** is a configuration forming an exterior of a bottom portion of the display panel and may be attached to the lower portion of the cover window **164**. Specifically, the middle frame **190** may be coupled with an end portion of the cover window **164** and may be coupled by an adhesive material (not illustrated). Therefore, the middle frame **190** may be in contact with the second ink layer **182** and the third ink layer **183**.

(114) Apart from the present embodiment, assume that the third ink layer **183** is not formed below the cover window **164**. The engraved coarse pattern is formed on the surface of the second ink layer **182**. Therefore, the coupling strength between the second ink layer **182** and the middle frame **190** is low. As explained above, that is because an area contacting with the adhesive material (not illustrated) or the middle frame **190** is relatively reduced thanks to the engraved coarse pattern on the surface of the second ink layer **182**. Therefore, there may be a problem that the middle frame **190** detaches from the cover window **164**.

(115) The present embodiment suggests to dispose the third ink layer **183** below the first ink layer **181**, dispose the third ink layer **183** on more inner side than the second ink layer **182** and attach the third ink layer **183** to the middle frame **190**. Since the third ink layer **183** does not have the engraved coarse pattern on the surface, attachment strength between the third ink layer **183** and the middle frame **190** may increase. Consequently, the problem of detachment that the middle frame **190** detaches from the cover window **164** may improve.

(116) FIGS. **13A** and **13B** show cross sections taken along A-A' of FIG. **8** according to an embodiment of the present disclosure.

(117) According to the present embodiment, the first ink layer **181** may be formed below the cover window **164**. Below the first ink layer **181**, the second ink layer **182** may be formed. In the second ink layer **182**, the embossed coarse pattern including beads (B) may be formed.

(118) An end of the first ink layer **181** protrudes further inwards than an end of the second ink layer **182**. In other words, an end of the first ink layer **181** shown in D region in FIG. **13B** protrudes further inwards than an end of the second ink layer **182**. Consequently, the first ink layer **181** and the second ink layer **182** together may take a form of steps. Between the first ink layer **181**, the second ink layer **182** and the adhesive layer **163**, a space (H2) may be formed.

(119) In comparison with FIG. **13B**, in FIG. **13A**, an end of the first ink layer **181** protrudes to an extent the same as an end of the second ink layer **182**. That is, an end of the first ink layer **181** shown in C region of FIG. **13A** protrudes to an extent the same as an end of the second ink layer **182**. Consequently, the first ink layer **181** and the second ink layer **182** together take a form of rising high rather than steps. Between the first ink layer **181**, the second ink layer **182** and the adhesive layer **163**, a space (H1) may be formed.

(120) The space (H2) according to an embodiment (FIG. **13B**) of the present disclosure is smaller than the space (H1) of the compared example (FIG. **13A**). If the space (H1) is big, the adhesive layer **163** may be easily detached from the cover window **164**. If the space (H2) is small, the adhesive layer **163** may not be easily detached cover window **164**.

(121) Therefore, since an end of the first ink layer **181** protrudes further inwards than an end of the second ink layer **182** according to the present embodiment, a problem that the adhesive layer **163** detaches from the cover window **164** may be solved.

(122) FIGS. **14A** and **14B** show cross sections taken along A-A' of FIG. **8** according to another embodiment of the present disclosure.

(123) According to the present embodiment, the first ink layer **181** may be formed below the cover window **164**. Below the first ink layer **181**, the second ink layer **182** may be formed. In the second ink layer **182**, the engraving coarse pattern including an engraved part (EP) may be formed.

(124) An end of the first ink layer **181** protrudes further inwards than an end of the second ink layer **182**. In other words, an end of the first ink layer **181** shown in D region in FIG. **14B** protrudes further inwards than an end of the second ink layer **182**. Consequently, the first ink layer **181** and the second ink layer **182** together may take a form of steps. Between the first ink layer **181**, the second ink layer **182** and the adhesive layer **163**, a space (H2) may be formed.

(125) In comparison with FIG. **14B**, in FIG. **14A**, an end of the first ink layer **181** protrudes to an extent the same as an end of the second ink layer **182**. That is, an end of the first ink layer **181** shown in C region of FIG. **14A** protrudes to an extent the same as an end of the second ink layer **182**. Consequently, the first ink layer **181** and the second ink layer **182** together take a form of rising high rather than steps. Between the first ink layer **181**, the second ink layer **182** and the adhesive layer **163**, a space (H1) may be formed.

(126) The space (H2) according to an embodiment (FIG. **14B**) of the present disclosure is smaller than the space (H1) of the compared example (FIG. **14A**). If the space (H1) is big, the adhesive layer **163** may be easily detached from the cover window **164**. If the space (H2) is small, the adhesive layer **163** may not be easily detached cover window **164**.

(127) Therefore, since an end of the first ink layer **181** protrudes further inwards than an end of the second ink layer **182** according to the present embodiment, a problem that the adhesive layer **163** detaches from the cover window **164** may improve.

(128) FIGS. **15A** to **15F** are drawings describing a manufacturing method of a display panel according to an embodiment of the present disclosure.

(129) Referring to FIGS. **15A** to **15F**, a method of pad printing may be used to form the first ink layer **181** and the second ink layer **182** in the cover window **164**. Other methods comparable to the pad printing method may be a spray printing, lamination after film printing and the like. A spray printing refers to forming ink layers by spraying ink onto a surface of the cover window **164**.

Lamination after film printing refers to a method in which ink is screen-printed onto a film made of polyethylene terephthalate (PET) and laminate the film onto which screen-printing is applied with the cover window **164**. The pad printing provided by the present disclosure refers to a method in which ink is transferred onto a printing pad and compress the printing pad onto which ink is transferred on the cover window **164**.

(130) Referring to FIG. **15A**, the printing pad **600** is compressed on a plate **700** in which a first ink material **181M** is filled. The plate **700** may have the engraving pattern and the first ink material **181M** may be filled in the engraving pattern. When the printing pad **600** is compressed on the plate **700**, the first ink material **181M** may be transferred onto a certain part of the printing pad **600**.

Consequently, the first ink layer **181** may be formed on the printing pad **600**.

(131) Referring to FIG. **15B**, the printing pad **600** may be moved to an upper side of a jig **800** to which the cover window **164** is fixed. The jig **800** is a device to fix a printing object, and may be a component to fix the cover window **164** in the present disclosure. The printing pad **600** on which the first ink layer **181** is formed is compressed on the cover window **164**.

(132) Referring to FIG. **15C**, the first ink layer **181** may be formed on the cover window **164**.

(133) Referring to FIG. **15D**, the printing pad **600** is compressed on the plate **700** in which the second ink material **182M** is filled. The plate **700** and the printing pad **600** may be different from those in FIGS. **15A** to **15C**. The second ink material **182M** may include a plurality of beads (B). When the printing pad **600** is compressed on the plate **700**, the second ink material **182M** may be transferred onto certain parts of the printing pad **600**. Consequently, the second ink layer **182** may be formed on the printing pad **600**. In addition, the second ink layer **182** formed on the printing pad **600** may include beads (B).

(134) Referring to (FIG. **15E**, the printing pad **600** may be moved to an upper side of a jig **800** to which the cover window **164** is fixed. At this time, the first ink layer **181** may be formed on the cover window **164** from the previous step shown in FIG. **15C**. The printing pad **600** on which the second ink layer **182** is formed is compressed on the cover window **164**.

(135) Referring to FIG. **15F**, the second ink layer **182** may be formed on the cover window **164** on which the first ink layer **181** is formed.

(136) By doing so, on the cover window **164**, the second ink layer **182** with the embossed coarse pattern therein formed on the first ink layer **181** and the first ink layer **181** may be formed.

(137) Thereafter, a step to apply an adhesive layer on the cover window **164** and laminate a panel layer on the cover window **164** may be further fulfilled. Accordingly, a display panel according to an embodiment of the present disclosure may be manufactured.

(138) Further, in the same way as the previously described process, before laminating the panel layer after forming the second ink layer **182** on the cover window **164**, by transferring a third ink material onto the printing pad and compressing the printing pad on which the third ink layer is formed on the cover window **164**, the third ink layer may be formed. Also, after laminating the panel layer, a step to attach the middle frame to the third ink layer may be fulfilled.

(139) FIGS. **16A** to **16F** are drawings describing a manufacturing method of a display panel according to another embodiment of the present disclosure. In describing FIGS. **16A** to **16F**, matters that are redundant with what are mentioned above will be omitted.

(140) Referring to FIGS. **16A** to **16F**, the pad printing method may be used to form the first ink layer **181** and the second ink layer **182** on the cover window **164**.

(141) Referring to FIG. **16A**, the printing pad **600** is compressed on the plate **700** in which the first ink material **181M** is filled. The plate **700** may have the engraving pattern and the first ink material **181M** may be filled in the engraving pattern. When the printing pad **600** is compressed on the plate **700**, the first ink material **181M** may be transferred onto a certain part of the printing pad **600**.

Consequently, the first ink layer **181** may be formed on the printing pad **600**.

(142) Referring to FIG. **16B**, the printing pad **600** may be moved to an upper side of the jig **800** to which the cover window **164** is fixed. The jig **800** is a device to fix a printing object, and may be a

component to fix the cover window **164** in the present disclosure. The printing pad **600** on which the first ink layer **181** is formed is compressed on the cover window **164**.

(143) Referring to FIG. **16C**, the first ink layer **181** may be formed on the cover window **164**.

(144) Referring to FIG. **16D**, the printing pad **600** is compressed on the plate **700** in which a second ink material **182M** is filled. The plate **700** and the printing pad **600** may differ from what are used in the previous steps in FIGS. **16A** and **16C**. At this time, an embossed pattern may be formed on the printing pad **600**. The embossed pattern may be regular or irregular, and may be protruded from the bottom surface of the printing pad **600**. When the printing pad **600** is compressed on the plate **700**, the second ink material **182M** may be transferred onto a certain part of the printing pad **600**. Consequently, the second ink layer **182** may be formed on the printing pad **600**.

(145) Referring to FIG. **16E**, the printing pad **600** may be moved to an upper side of the jig **800** to which the cover window **164** is fixed. At this time, the first ink layer **181** may be formed on the cover window **164** from the previous step (c). The printing pad **600** on which the second ink layer **182** is formed is compressed on the cover window **164**.

(146) Referring to FIG. **16F**, the second ink layer **182** may be formed on the cover window **164** on which the first ink layer **181** is formed. On the surface of the second ink layer **182** being formed, the engraving pattern (EP) may be formed. That is because the embossed pattern has been formed at the bottom portion of the printing pad **600** at steps shown in FIGS. **16D** and **16E**. In other words, at an upper portion of the second ink layer **182** after removing the printing pad **600** having the embossed pattern, the engraving pattern (EP) contrary to the embossed pattern may be formed.

(147) By doing so, on the cover window **164**, the second ink layer **182** with the engraved coarse pattern therein formed on the first ink layer **181** and the first ink layer **181** may be formed.

(148) Thereafter, a step to apply an adhesive layer on the cover window **164** and laminate a panel layer on the cover window **164** may be further fulfilled. Accordingly, a display panel according to an embodiment of the present disclosure may be manufactured.

(149) Further, in the same way as the previously described process, before laminating the panel layer after forming the second ink layer **182** on the cover window **164**, by transferring a third ink material onto the printing pad and compressing the printing pad on which the third ink layer is formed on the cover window **164**, the third ink layer may be formed on the cover window **164**. Also, after laminating the panel layer, a step to attach the middle frame to the third ink layer may be fulfilled.

(150) Those skilled in the art may understand that the present disclosure described herein may be implemented in other concrete forms without departing from the technical concept or essential features thereof. Thus, it should be understood that embodiments described hereinabove are examples in all aspects, and do not limit the present disclosure. The scope of the present disclosure will be denoted by the claims that are provided hereinbelow, rather than the detailed description. In addition, it should be construed that all modifications or variations that are derived from the meaning, scope and the concept of equivalence of the claims are covered in the scope of the present disclosure.

REFERENCE NUMERALS

(151) **100**: display panel **110**: panel layer **101**: backplate **164**: cover window **163**: adhesive layer **162**: polarizer **173**: heat dissipation sheet **181**: first ink layer **182**: second ink layer **183**: third ink layer B: beads EP: engraved part

Claims

1. A display panel comprising: a cover window; an adhesive layer below the cover window; a first ink layer below the cover window; a second ink layer below the first ink layer, the second ink layer including a coarse pattern; and a panel layer below the adhesive layer, wherein one surface of the

first ink layer is in direct contact with the cover window, and another surface opposite to the one surface of the first ink layer is in direct contact with the second ink layer.

2. The display panel of claim 1, wherein the coarse pattern includes an embossed pattern.

3. The display panel of claim 2, wherein the embossed pattern includes a plurality of beads.

4. The display panel of claim 3, wherein the second ink layer is formed in a pad printing method, and wherein a second ink material applied to a printing pad includes the plurality of beads.

5. The display panel of claim 1, wherein the coarse pattern includes an engraving pattern.

6. The display panel of claim 5, wherein the second ink layer is formed in a pad printing method, and an application area of a second ink material has an embossed pattern.

7. The display panel of claim 1, wherein an end of the first ink layer protrudes further towards a center of the display panel than an end of the second ink layer.

8. The display panel of claim 1, further comprising: a third ink layer below the first ink layer.

9. The display panel of claim 8, wherein the third ink layer is more towards a center of the display panel than the second ink layer and the third ink layer is attached to a middle frame.

10. The display panel of claim 8, wherein the third ink layer is on a same layer as the second ink layer.

11. The display panel of claim 8, wherein the third ink layer lacks the coarse pattern.

12. The display panel of claim 1, wherein the first ink layer and the second ink layer are along outer edges of the cover window.

13. The display panel of claim 1, further comprising: a third ink layer below the first ink layer, wherein the third ink layer covers a side surface of the second ink layer.

14. The display panel of claim 1, further comprising: a third ink layer below the first ink layer, wherein the first ink layer is in direct contact with the second ink layer and the third ink layer.

15. The display panel of claim 1, wherein the cover window includes a flat area and a bending area, wherein the first ink layer and the second ink layer are disposed in the bending area.

16. The display panel of claim 15, wherein the panel layer is bent along the bending area.
