

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250273927
Kind Code	A1
Publication Date	August 28, 2025
Inventor(s)	MU; Jianwei et al.

OPTICAL MODULE

Abstract

An optical module provided in the present disclosure includes: a circuit board provided with a through-hole; a light emission component configured for generating an optical signal; a driver located beside the light emission component and electrically connected to the light emission component; a lens component connected to the circuit board at its bottom and is covered over the light emission component, configured for changing a transmission direction of the optical signal generated by the light emission component; a support component, which has a top located inside the through-hole and is connected to the circuit board; a temperature regulating mechanism located below the lens assembly and connected to the support component at its bottom; wherein the temperature regulating mechanism is located below or beside the light emission component, configured for regulating an operating temperature of the light emission component.

Inventors:	MU; Jianwei (Qingdao, CN), WU; Tao (Qingdao, CN), JIN; Shuang (Qingdao, CN), YANG; Sigeng (Qingdao, CN), SHAO; Qian (Qingdao, CN), BIAN; Huizheng (Qingdao, CN), LUO; Chengshuang (Qingdao, CN), SU; Jingqi (Qingdao, CN)
Applicant:	HISENSE BROADBAND MULTIMEDIA TECHNOLOGIES CO., LTD. (Qingdao, CN)
Family ID:	1000008007059
Assignee:	HISENSE BROADBAND MULTIMEDIA TECHNOLOGIES CO., LTD. (Qingdao, CN)
Appl. No.:	18/759754
Filed:	June 28, 2024

Foreign Application Priority Data

CN	2024 1 0208556.3	Feb. 26, 2024
CN	2024 1 0208801.0	Feb. 26, 2024
CN	2024 2 0351756.X	Feb. 26, 2024

Related U.S. Application Data

parent WO continuation PCT/CN2024/084431 20240328 PENDING child US 18759754

Publication Classification

Int. Cl.: **H01S5/024** (20060101); **H01S5/026** (20060101)

U.S. Cl.:

CPC **H01S5/02415** (20130101); **H01S5/0261** (20130101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of the application filed on Mar. 28, 2024, with the application number PCT/CN2024/084431, which claims the priority to the application No. 202410208556.3 filed with the China National Intellectual Property Administration on Feb. 26, 2024, the priority to the application No. 202410208801.0 filed with the China National Intellectual Property Administration on Feb. 26, 2024, and the priority to the application No. 202420351756.X filed with the China National Intellectual Property Administration on Feb. 26, 2024, which are incorporated herein by references in their entirety.

FIELD OF THE INVENTION

[0002] The present disclosure relates to the field of optical communication technologies, and in particular to an optical module.

BACKGROUND OF THE INVENTION

[0003] With the development of cloud computing, mobile Internet, video, artificial intelligence and other new services and application models, the development and progress of optical communication technology has become increasingly important. In optical communication technology, the optical module is a tool for achieving mutual conversion of optical and electric signals, is one of the key devices in optical communication equipment, and is at a core position in optical communication.

SUMMARY OF THE INVENTION

[0004] One aspect of the present disclosure provides an optical module, including a circuit board, a light emission component, a lens component, a support component, and a temperature regulating mechanism. The circuit board is provided with a through-hole. The light emission component is electrically connected to the circuit board, for generating an optical signal. The driver is electrically connected to the circuit board and is located beside the light emission component, and the driver is electrically connected to the light emission component. The lens component is connected to the circuit board at its bottom and is covered over the light emission component, configured for changing a transmission direction of the optical signal generated by the light emission component. The top of the support component is located inside the through-hole, and the support component connects with the circuit board. The thermal conductivity coefficient of the support component is greater than or equal to that of the circuit board. The temperature regulating mechanism is located below the lens component and its bottom is connected to the support component. The temperature regulating mechanism is located below or beside the light emission component, configured for regulating the operating temperature of the light emission component.

[0005] Another aspect of the present disclosure provides an optical module, including: a circuit

board, which is provided with a through-hole; a lens component, the bottom of which is connected to the circuit board, configured for changing the transmission direction of an optical signal; an optical chip, which is located below the lens component, and includes at least one of a light emission component and a light reception component; a support component, which is connected to the circuit board, with its top located inside the through-hole; wherein the support component supports and connects with the optical chip, and the thermal conductivity coefficient of the support component is greater than that of the circuit board.

[0006] Yet another aspect of the present disclosure provides an optical module, including: a circuit board, which is provided with a through-hole; a lens component, the bottom of which is connected to the circuit board, configured for changing a transmission direction of an optical signal; an optical chip, which is located below the lens component, and includes at least one of a light emission component and a light reception component; a matching chip, which is located below the lens component and beside the optical chip and correspondingly connected to the optical chip by wire bonding, and includes at least one of a driver and a TIA; a support component, which is connected to the circuit board, and the top of the support component is located inside the through-hole; wherein the support component supports and connects with the optical chip and the matching chip, and the thermal conductivity coefficient of the support component is greater than that of the circuit board.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0007] To more clearly describe the technical solutions of the present disclosure, the accompanying drawings to be used in the embodiments will be described briefly below. Apparently, the accompanying drawings as described below are only those of some embodiments of the present disclosure, and for those skilled in the art, other accompanying drawings may also be derived from these accompanying drawings. In addition, the accompanying drawings as described below can be regarded as schematic diagrams and are not intended to limit the actual size of the product, the actual process of the method, or the actual timing of the signal involved in the disclosed embodiments.

[0008] FIG. 1 is a partial architecture view of an optical communication system provided according to some embodiments of the present disclosure;

[0009] FIG. 2 is a partial structure view of a master computer provided according to some embodiments of the present disclosure;

[0010] FIG. 3 is a structure view of an optical module provided according to some embodiments of the present disclosure;

[0011] FIG. 4 is an exploded view of an optical module provided according to some embodiments of the present disclosure;

[0012] FIG. 5 is an exploded diagram of an internal structure of the optical module provided according to some embodiments of the present disclosure;

[0013] FIG. 6 is a partially enlarged view of portion A in FIG. 5;

[0014] FIG. 7 is a structural diagram of a first heater provided according to some embodiments of the present disclosure;

[0015] FIG. 8 is a usage state view of a support component provided according to some embodiments of the present disclosure;

[0016] FIG. 9 is an assembly diagram I of a support component provided according to some embodiments of the present disclosure;

[0017] FIG. 10 is an assembly diagram II of a support component provided according to some embodiments of the present disclosure;

[0018] FIG. **11** is an internal structure diagram of another optical module provided according to some embodiments of the present disclosure;

[0019] FIG. **12** is an exploded diagram of the internal structure of another optical module provided according to some embodiments of the present disclosure;

[0020] FIG. **13** is a partially enlarged diagram of portion B in FIG. **12**;

[0021] FIG. **14** is a structural diagram of a circuit board provided according to some embodiments of the present disclosure;

[0022] FIG. **15** is a structural diagram of another support component provided according to some embodiments of the present disclosure;

[0023] FIG. **16** is a usage state view of another support component provided according to some embodiments of the present disclosure;

[0024] FIG. **17** is a partial assembly diagram I of another support component provided according to some embodiments of the present disclosure;

[0025] FIG. **18** is a partial assembly diagram II of another support component provided according to some embodiments of the present disclosure;

[0026] FIG. **19** is a section view of another optical module provided according to some embodiments of the present disclosure;

[0027] FIG. **20** is an exploded diagram I of the internal structure of another optical module provided according to some embodiments of the present disclosure;

[0028] FIG. **21** is an exploded diagram II of the internal structure of another optical module provided according to some embodiments of the present disclosure;

[0029] FIG. **22** is a structural diagram I of another support component provided according to some embodiments of the present disclosure;

[0030] FIG. **23** is a partially enlarged view of another support component provided according to some embodiments of the present disclosure;

[0031] FIG. **24** is a structural diagram II of another support component provided according to some embodiments of the present disclosure;

[0032] FIG. **25** is a usage state view of another support component provided according to some embodiments of the present disclosure;

[0033] FIG. **26** is an internal structure diagram of yet another optical module provided according to some embodiments of the present disclosure;

[0034] FIG. **27** is an exploded diagram I of the internal structure of yet another optical module provided according to some embodiments of the present disclosure;

[0035] FIG. **28** is a partial diagram of the internal structure of yet another optical module provided according to some embodiments of the present disclosure;

[0036] FIG. **29** is an exploded diagram II of the internal structure of yet another optical module provided according to some embodiments of the present disclosure;

[0037] FIG. **30** is a structural diagram I of yet another support component provided according to some embodiments of the present disclosure;

[0038] FIG. **31** is a structural diagram II of yet another support component provided according to some embodiments of the present disclosure;

[0039] FIG. **32** is a structural diagram III of yet another support component provided according to some embodiments of the present disclosure;

[0040] FIG. **33** is a usage state view of yet another support component provided according to some embodiments of the present disclosure;

[0041] FIG. **34** is a partially enlarged view of the usage state of yet another support component provided according to some embodiments of the present disclosure;

[0042] FIG. **35** is an assembly section view I of yet another support component and a circuit board provided according to some embodiments of the present disclosure;

[0043] FIG. **36** is an assembly section view II of yet another support component and a circuit board

provided according to some embodiments of the present disclosure;

[0044] FIG. **37** is a partial diagram of another lower shell part provided according to some embodiments of the present disclosure.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0045] Some embodiments of the present disclosure will be described clearly and in detail with reference to the accompanying drawings below. Obviously, these embodiments as described are merely some, but not all, of the embodiments of the present disclosure. All other embodiments obtained by those skilled in the art based on the embodiments of the present disclosure shall be included in the protection scope of the present disclosure.

[0046] In optical communication technology, in order to establish information transmission between information processing devices, it is necessary to load information onto light and thus achieve transmission of the information by use of propagation of light. Herein, the light loaded with information is an optical signal. The optical signal propagated in the information transmission devices can reduce loss of optical power, and thus achieve high-speed, long-distance, and low-cost information transmission. The information that can be recognized and processed by the information processing device is an electrical signal. Optical network units (ONU), gateways, routers, switches, mobile phones, computers, servers, tablets, and televisions are common information processing devices, while optical fibers and waveguides are common information transmission devices.

[0047] Conversion of the optical signals and the electrical signals between the information processing device and the information transmission device can be achieved by use of the optical module. For example, at least one of optical signal input terminal and optical signal output terminal of the optical module connects with an optical fiber, and at least one of electrical signal input terminal and electrical signal output terminal of the optical module connects with an optical network unit. A first optical signal from the optical fiber is transmitted to the optical module, which converts the first optical signal into a first electrical signal, and then transmits the first electrical signal to the optical network unit. A second electrical signal from the optical network unit is transmitted to the optical module, which converts the second electrical signal into a second optical signal, and then transmits the second optical signal into the optical fiber. Since the information transmission among information processing devices can be performed via electrical signals, at least one of the information processing devices needs to be directly connected to the optical module, and it is unnecessary for all of the information processing devices to be directly connected to the optical module. Herein, the information processing device directly connected to the optical module is called as a master computer of the optical module. In addition, the optical signal input terminal or the optical signal output terminal of the optical module can be referred to as “optical port”, and the electrical signal input terminal or the electrical signal output terminal of the optical module can be referred to as “electrical port”.

[0048] FIG. **1** is a partial architecture view of an optical communication system provided according to some embodiments of the present disclosure. As shown in FIG. **1**, the optical communication system mainly includes a remote information processing device **1000**, a local information processing device **2000**, a master computer **100**, an optical module **200**, an optical fiber **101**, and a network cable **103**.

[0049] One end of the optical fiber **101** extends towards the remote information processing device **1000**, and the other end of the optical fiber **101** is coupled to the optical module **200** via an optical port of the optical module **200**. The optical signal can undergo a total reflection in the optical fiber **101**, and propagation of the optical signal in a total reflection direction can almost maintain an original optical power. The optical signal undergoes multiple total reflections in the optical fiber **101**, such that the optical signal from the remote information processing device **1000** is transmitted into the optical module **200**, or the optical signal from the optical module **200** is transmitted to the remote information processing device **1000**, thereby achieving long-distance and low-power-loss information transmission.

[0050] There may be one optical fiber **101** or a plurality of optical fibers **101**. The optical fiber **101** can be connected to the optical module **200** in a pluggable manner or a fixed connection manner. The master computer **100** is configured to provide data signals to the optical module **200** or receive data signals from the optical module, or to monitor or control working status of the optical module **200**.

[0051] The master computer **100** includes a generally cuboid housing, and an optical module interface **102** provided on the housing. The optical module interface **102** is configured to be coupled to the optical module **200**, thereby establishing a unidirectional or bidirectional electrical signal connection between the master computer **100** and the optical module **200**.

[0052] The master computer **100** has an external electrical interface, which can be coupled to the electrical signal network. For example, the external electrical interface includes a Universal Serial Bus (USB) or a network cable interface **104**. The network cable interface **104** is configured to be coupled with the network cable **103**, thereby establishing a unidirectional or bidirectional electrical signal connection between the master computer **100** and the network cable **103**. One end of the network cable **103** is connected to the local information processing device **2000**, and the other end of the network cable **103** is connected to the master computer **100**, so as to establish an electrical signal connection between the local information processing device **2000** and the master computer **100**. For example, a third electrical signal emitted by the local information processing device **2000** is transmitted to the master computer **100** through the network cable **103**. The master computer **100** generates a second electrical signal based on the third electrical signal, and the second electrical signal from the master computer **100** is transmitted to the optical module **200**. The optical module **200** converts the second electrical signal into a second optical signal, and transmits the second optical signal to the optical fiber **101**. The second optical signal is transmitted to the remote information processing device **1000** through the optical fiber **101**. For example, a first optical signal from the remote information processing device **1000** propagates through the optical fiber **101**. The first optical signal from the optical fiber **101** is transmitted to the optical module **200**. The optical module **200** converts the first optical signal into the first electrical signal, and transmits the first electrical signal to the master computer **100**. The master computer **100** generates a fourth electrical signal based on the first electrical signal, and transmits the fourth electrical signal into the local information processing device **2000**. It should be noted that the optical module is a tool for achieving the conversion between optical and electrical signals, and during the conversion between optical and electrical signals as described above, no change is made to the information, but methods for encoding and decoding the information can be changed.

[0053] In addition to the Optical Network Unit, the master computer may include Optical Line Terminal (OLT), Optical Network Terminal (ONT), Data Center Server and so on.

[0054] FIG. 2 is a partial structure view of a master computer provided according to some embodiments of the present disclosure. In order to clearly illustrate the connection relationship between the optical module **200** and the master computer **100**, FIG. 2 only shows the structure of the master computer **100** related to the optical module **200**. As shown in FIG. 2, the master computer **100** further includes a PCB circuit board **105** disposed within a housing, a cage **106** disposed on a surface of the PCB circuit board **105**, a radiator **107** disposed on the cage **106**, and an electrical connector disposed inside the cage **106**. The electrical connector is configured to be coupled to the electrical port of the optical module **200**, and the radiator **107** has a raised structure, such as a fin, that increases heat dissipation area.

[0055] The optical module **200** is inserted into the cage **106** of the master computer **100** and is secured by the cage **106**. Heat generated by the optical module **200** is conducted to the cage **106**, and then dissipated via the radiator **107**. After the optical module **200** is inserted into the cage **106**, the electrical port of the optical module **200** is connected to the electrical connector provided inside the cage **106**, thereby establishing a bidirectional electrical signal connection between the optical module **200** and the master computer **100**. Also, the optical port of the optical module **200** is

coupled with the optical fiber **101**, thereby establishing a bidirectional optical signal connection between the optical module **200** and the master computer **100**.

[0056] FIG. **3** is a structure view of an optical module provided according to some embodiments of the present disclosure, and FIG. **4** is an exploded view of an optical module provided according to some embodiments of the present disclosure. As shown in FIGS. **3** and **4**, the optical module **200** includes a shell, and a circuit board **300** and a lens component **400** provided within the shell.

[0057] The shell may include an upper shell part **201** and a lower shell part **202**. The upper shell part **201** is covered on the lower shell part **202** to form the aforementioned shell having two openings **203** and **204**. The outer contour of the shell is generally in a cuboid shape.

[0058] In some embodiments, the lower shell part **202** includes a bottom plate **2021** and two lower side plates **2022** located on opposite sides of the bottom plate **2021** and disposed perpendicular to the bottom plate **2021**, and the upper shell part **201** includes a cover plate **2011**. The cover plate **2011** is covered on the two lower side plates **2022** of the low shell part **202** so as to form the above-mentioned shell.

[0059] In some embodiments, the lower shell part **202** includes a bottom plate **2021** and two lower side plates located on opposite sides of the bottom plate **2021** and disposed perpendicular to the bottom plate **2021**, and the upper shell part **201** includes a cover plate **2011** and two upper side plates **2012** located on opposite sides of the cover plate **2011** and disposed perpendicular to the cover plate **2011**, such that the two upper side plates **2012** are combines with the two lower side plates **2022** to achieve the covering of the upper shell part **201** on the lower shell part **202**.

[0060] The direction along a connecting line between the two openings **203** and **204** may be consistent with the length direction of the optical module **200** or inconsistent with the length direction of the optical module **200**. For example, the opening **203** is located at an end of the optical module **200** (right end in FIG. **3**), and the opening **204** is also located at an end of the optical module **200** (left end in FIG. **3**). Alternatively, the opening **203** is located at an end of the optical module **200**, while the opening **204** is located at a side of the optical module **200**. The opening **203** is an electrical port and a gold finger of the circuit board **300** extends from the electrical port and is inserted into the master computer (e.g., Optical Network Unit **100**). The opening **204** is an optical port configured to be coupled by the optical fiber **101** such that the optical fiber **101** is connected with the optical module **200**.

[0061] The assembling way in which the upper shell part **201** is combined with the lower shell part **202** facilitates mounting the circuit board **300**, the lens component **400** and the like into the shell, such that these components may be encapsulated and protected by the upper shell part **201** and the lower shell part **202**. In addition, when assembling the circuit board **300**, the lens component **400** and the like, this assembling way facilitates the deployment of the positioning elements, the heat dissipation elements, and the electromagnetic shielding elements for these components, which is conducive to automated production.

[0062] In some embodiments, the upper shell part **201** and lower shell part **202** are generally made of metal materials, which facilitates achieving electromagnetic shielding and heat dissipation.

[0063] In some embodiments, the optical module **200** further includes an unlocking component **600** located outside the shell thereof. The unlocking component **600** is configured to achieve a fixed connection between the optical module **200** and the master computer or release the fixed connection between the optical module **200** and the master computer.

[0064] For example, the unlocking component **600** is located outside of the two lower side plates **2022** of the lower shell part **202**, and includes a snapping part that matches with the cage **106** of the master computer **100**. When the optical module **200** is inserted into the cage **106**, the snapping part of the unlocking component **600** secures the optical module **200** within the cage **106**. As the unlocking component **600** is pulled, the snapping part of the unlocking component **600** moves accordingly, and thus the connection relationship between the snapping part and the master computer is changed, thereby releasing the fixed connection between the optical module **200** and

the master computer, such that the optical module **200** can be drawn out from the cage **106**.

[0065] The circuit board **300** includes circuit wiring, electronic elements, and chips. The electronic elements and chips are connected together by the circuit wiring according to a circuit design so as to achieve various functions such as power supply, electrical signal transmission, and grounding. For example, the electronic elements may include capacitors, resistors, triodes, and Metal-Oxide-Semiconductor Field-Effect Transistors (MOSFETs). For example, the chips may include lasers, photodetectors, microcontroller units (MCUs), laser driver chips, transimpedance amplifiers (TIAs), limiting amplifiers (LAs), clock and data recovery (CDR) chips, power management chips, digital signal processing (DSP) chips and the like.

[0066] The circuit board **300** is generally a hard circuit board. Due to its relatively hard material, the hard circuit board can also achieve a load-bearing function, e.g., can stably bear the above-mentioned electronic elements and chips. The hard circuit board can also be inserted into the electrical connector in the cage **106** of the master computer **100**.

[0067] The circuit board **300** further includes a gold finger formed on the surface of an end thereof, which is composed of a plurality of pins independent from each other. The circuit board **300** is inserted into the cage **106** and is conductively connected to the electrical connector disposed inside the cage **106** via the gold finger. The gold finger may be disposed only on one surface of the circuit board **300** (e.g., an upper surface shown in FIG. 4), or on both upper and lower surfaces of the circuit board **300** to provide more pins so as to be suitable to applications where a larger number of pins are required. The gold finger is configured to establish an electrical connection with the master computer to achieve power supply, grounding, Inter-Integrated Circuit (I2C) signal transmission, data signal transmission or the like. Of course, some of the optical modules can also use a flexible circuit board. The flexible circuit board is generally used in conjunction with the hard circuit board, as a supplement to the hard circuit board.

[0068] In some embodiments, a bottom of the lens component **400** is connected to the circuit board **300** and is covered over the optical chip. The optical chip includes a light emission component and/or a light reception component, etc., which are electrically connected to the circuit board **300**. The lens component **400** has an optical surface such as a transmissive surface and/or a reflective surface to adjust transmission directions of optical emission and/or reception signals by a combination of the transmissive and reflective surfaces, such that the optical emission signal generated by the light emission component can be output from the optical module, and the optical signal input into the optical module can be transmitted to the light reception component. The light emission component includes a laser, and the light reception component includes a photodetector. In some embodiments, a matching chip may also be provided below the lens component **400**, and the matching chip includes a driver and/or TIA, etc.

[0069] In some embodiments, the lens component **400** connects with an optical fiber strip **410**, and the optical signal generated by the light emission component is transmitted to the optical fiber strip **410** via the lens component **400**; alternatively, the optical signal input through the optical fiber strip **410** is transmitted to the lens component **400**, and then transmitted to the light reception component via the lens component **400**. Of course, in some embodiments, the lens component **400** is arranged beside the optical port of the optical module **200**, and the lens component **400** directly connects with the external optical fiber.

[0070] An optical fiber connector is provided at an end of the optical fiber strip **410** for connecting the external optical fiber. In some embodiments, the optical fiber connector is laid flat in the optical port, that is, a main plane of the optical fiber connector is parallel or approximately parallel to the load-bearing plane of the optical port. Of course, in some embodiments, the optical fiber connector is laid upright in the optical port, that is, the main plane of the optical fiber connector is perpendicular or approximately perpendicular to the load-bearing plane of the optical port. FIG. 4 shows an optical fiber connector in a laid flat state.

[0071] FIG. 5 is an exploded diagram of the internal structure of an optical module provided

according to some embodiments of the present disclosure, and FIG. 6 is a partially enlarged view of portion A in FIG. 5. As shown in FIGS. 5 and 6, a light emission component **310** is provided below the lens component **400**, and the light emission component **310** is electrically connected to the circuit board **300**. The optical signal generated by the light emission component **310** is transmitted to the lens component **400**, transmitted to the optical fiber strip **410** via the lens component **400**, and out of the optical module through the optical fiber strip **410**. In some embodiments, the light emission component **310** may be provided on the circuit board **300**, such that the top surface of the light emission component **310** is higher than the top surface of the circuit board **300**.

[0072] In some embodiments, a driver **330** is provided below the lens component **400** and beside the light emission component **310**, and the driver **330** is electrically connected to the circuit board **300** and to the light emission component **310**. The driver **330** can be provided on the circuit board **300**, such that the top surface of the driver **330** is higher than the top surface of the circuit board **300**. The light emission component **310** can be connected to the driver **330** by wire bonding, and the driver **330** can be connected to the circuit board **300** by wire bonding.

[0073] In some embodiments, a light reception component **320** is provided below the lens component **400**. The optical signal transmitted to the lens component **400** through the optical fiber strip **410** is then transmitted to the light reception component **320** via the lens component **400**. The light reception component **320** can be provided beside the light emission component **310**, and the light reception component **320** can be provided on the circuit board **300**, such that the top surface of the light reception component **320** is higher than the top surface of the circuit board **300**.

[0074] In some embodiments, a TIA **340** is provided below the lens component **400** and beside the light reception component **320**, and the TIA **340** is electrically connected to the circuit board **300** and to the light reception component **320**. The TIA **340** can be provided on the circuit board **300**, such that the top surface of the TIA **340** is higher than the top surface of the circuit board **300**. The light reception component **320** can be connected to the TIA **340** by wire bonding, and the TIA **340** can be connected to the circuit board **300** by wire bonding.

[0075] In some embodiments, the light reception component **320** is located beside the light emission component **310**. For example, the light reception component **320** and the light emission component **310** are arranged side by side in a width direction of the circuit board **300**.

[0076] In some embodiments, a plurality of lasers is packaged in the light emission component **310**. There may be four VCSEL lasers to be packaged in the light emission component **310**, but in some embodiments of the present disclosure, the light emission component **310** is not limited to packaging four VCSEL lasers therein. In some embodiments, a transmission rate of the VCSEL lasers is 50 Gb/s, 100 Gb/s, 200 Gb/s, etc. As the transmission rate of the VCSEL laser in the light emission component **310** is higher, the high-frequency performance of the VCSEL laser is more sensitive to operating temperature of the laser. For example, the VCSEL laser can maintain its high-frequency performance only within a very small temperature range. Therefore, in order to ensure that the optical module **200** can operate in an environmental temperature range of 0° C. to 70° C., it is necessary to maintain the operating temperature of the light emission component **310** within a certain temperature range, thereby reducing the impact of the environmental temperature on its operating temperature.

[0077] In some embodiments, a plurality of photodetectors is packaged in the light reception component **320**. There may be four photodetectors to be packaged in the light reception component **320**, but in some embodiments of the present disclosure, the light reception component **320** is not limited to packaging four photodetectors therein.

[0078] In some embodiments, the optical module **200** includes a temperature regulating mechanism **500**, which is located below the lens component **400** and is electrically connected to the circuit board **300**, such that the temperature regulating mechanism **500** can generate or absorb heat to maintain the operating temperature of the light emission component **310** within a relatively constant range, thereby ensuring the high-frequency performance of the light emission component

310 by stabilizing the operating temperature of the light emission component **310** within a predetermined range. The light emission component **310** can be provided on the top of the temperature regulating mechanism **500** or beside the temperature regulating mechanism **500**. The temperature regulating mechanism **500** may include a heating element, or the temperature regulating mechanism **500** may include a Thermo Electric Cooler (TEC).

[0079] In some embodiments, the optical module **200** includes a support component **700**, which is located below the lens component **400**, and supports and connects with the light emission component **310** or the light reception component **320**, etc. For example, the circuit board **300** is provided with a through-hole **301** located below the lens component **400**, and the support component **700** is connected to the through-hole **301** such that a portion of the support component **700** is located inside the through-hole **301**. For example, the top of the support component **700** is embedded in the through-hole **301**.

[0080] In some embodiments, the thermal conductivity coefficient of the support component **700** is greater than or equal to that of the circuit board **300**. The use of the support component **700** facilitates heat dissipation of optical chips and other devices, stabilizing the operating temperature of the optical chips and other devices within a predetermined range.

[0081] In some embodiments, the support component **700** may use metal or the other materials having good thermal conductivity, such as tungsten and copper. This facilitates the heat dissipation of the optical chips and other devices mounted on it, helping to maintain a relatively constant operating temperature of the optical chips and other devices on the support component **700**. The shape and size of the through-hole **301** are determined with reference to the dimension of lens component **400**, the available space on the circuit board **300**, and the dimensions of the optical chips and other components.

[0082] In some embodiments, the support component **700** may support and connect with the light emission component **310**.

[0083] In some embodiments, the support component **700** may support and connect with the temperature regulating mechanism **500**. For example, the bottom of the temperature regulating mechanism **500** is connected to the top of the support component **700**.

[0084] In some embodiments, as shown in FIG. 6, the light emission component **310** and the heating element **500a** are arranged on the top of the support component **700**, and the optical reception component **320**, the driver **330**, and the TIA **340** are located outside the support component **700**.

[0085] In some embodiments, the support member **700** can be fixedly connected to the circuit board **300** by thermal conductive gel and the like.

[0086] In some embodiments, the support component **700** may support and connect with at least one of the optical reception component **320**, the driver **330**, and the TIA **340**.

[0087] In some embodiments, the temperature regulating mechanism **500** includes a heating element **500a**, which is located beside or below the light emission component **310**. The heating element **500a** is electrically connected to the circuit board **300**. The heating element **500a** is energized to generate heat, which can increase the temperature of the light emission component **310** and the environment temperature, thereby stabilizing the operating temperature of the light emission component **310** within a certain range, and ensuring the stability of the performance of the light emission component **310**.

[0088] In some embodiments, the heating element **500a** is provided below the light emission component **310**, that is, the heating element **500a** supports and connects with the light emission component **310**.

[0089] In some embodiments, the support component **700** supports and connects with the heating element **500a**. The support component **700** is configured to assist the heating element **500a** in maintaining the operating temperature of the light emission component **310**.

[0090] In some embodiments, the light emission component **310** is provided on the heating element

500a, the light reception component **320** is provided on the circuit board **300** and beside the light emission component **310**, such that the light reception component **320** and the light emission component **310** are arranged side by side in the width direction of the circuit board **300**. The TIA **340** is located beside the light reception component **320** and the driver **330**, such that the TIA **340** and the driver **330** are arranged side by side in the width direction of the circuit board **300** to fully utilize the space provided below the lens component **400** and facilitate the size control of the lens component **400**.

[0091] In some embodiments, there is a gap between the light reception component **320** and the heating element **500a** so as to reduce the impact of heat generated by the heating element **500a** on the light reception component **320**.

[0092] FIG. 7 is a structural diagram of a heating element provided according to some embodiments of the present disclosure. As shown in FIG. 7, the heating element **500a** includes a substrate **511** and a heating layer **512**. The heating layer **512** is provided on the substrate **511**, and the heating layer **512** is electrically connected to the circuit board **300** so as to be energized to generate heat. The heating layer **512** can be provided on the top surface of the substrate **511**. The substrate **511** can be a ceramic substrate, but not limited to the ceramic substrate. The heating layer **512** may use resistance wires or circuit patterns formed on the substrate **511**.

[0093] In some embodiments, the heating layer **512** may be provided on an edge of the top of the substrate **511**. When the heating element **500a** supports and connects with the light emission component **310**, the heating layer **512** is located beside the light emission component **310** to ensure that the heat generated by the heating element **500a** is uniformly transmitted to the light emission component **310**, thereby stabilizing the operating temperature of each laser in the light emission component **310**. In some embodiments, the heating layer **512** is located on an edge of the top of the substrate **511** that is away from the driver **330**.

[0094] In some embodiments, the heating layer **512** extends from one end of the light emission component **310** to the other end of the light emission component **310**, i.e. a length of the heating layer **512** is greater than or equal to that of the light emission component **310**, such that the heat generated by the heating layer **512** can be uniformly transmitted to the light emission component **310**.

[0095] In some embodiments, the heating element **500a** further comprises a first pad **513** and a second pad **514**, with the first pad **513** electrically connected to one end of the heating layer **512**, and the second pad **514** electrically connected to the other end of the heating layer **512**. The first pad **513** and the second pad **514** are used to facilitate the electrical connection of the heating layer **512** to the circuit board **300**.

[0096] The first pad **513** and the second pad **514** can be provided on the top surface of the substrate **511**, with the first pad **513** located at one end of the heating layer **512** and the second pad **514** located at the other end of the heating layer **512**. The first pad **513** and the second pad **514** can also be provided on a side surface of the substrate **511**, and the heating layer **512** extends from the top surface of the substrate **511** to the side surface of the substrate **511**.

[0097] FIG. 8 is a usage state view of a support component provided according to some embodiments of the present disclosure. As shown in FIG. 8, the support component **700** includes a support portion **711** and a connection portion **712**. The top of the support portion **711** is connected to the bottom of the heating element **500a**, and the bottom of the support portion **711** is connected to the connection portion **712**. The connection portion **712** is used to connect the circuit board **300**, and the support portion **711** is configured to be embedded in the through-hole **301**.

[0098] In some embodiments, the top of the support portion **711** can directly support the light emission component **310**, that is, the bottom of the light emission component **310** is connected to the top of the support portion **711**.

[0099] In some embodiments, the cross-sectional size of the connection portion **712** is larger than that of the supporting portion **711**, such that a stepped surface **713** is formed around the bottom of

the supporting portion **711**. The stepped surface **713** can facilitate the connection of the support component **700** to the circuit board **300** and the adjustment of a relative height between the top of the support portion **711** and the surface of the circuit board **300**. The support component **700** can be connected to the circuit board **300** by dispensing glue on the stepped surface **713**. In some embodiments, the stepped surface **713** is connected to the back side of the circuit board **300**.

[0100] FIG. **9** is an assembly diagram I of a support component provided according to some embodiments of the present disclosure. As shown in FIG. **9**, the support portion **711** of the support component **700** is located inside the through-hole **301**, the top of the support portion **711** connects with the bottom of the heating element **500a**, and the light emission component **310** is provided at the top of the heating element **500a**. The top surface of the support portion **711** is lower than the top surface **300a** of the circuit board **300**, so as to control the height of the top of the light emission component **310**. The connection portion **712** is located on the other side of the circuit board **300** that is away from the top surface **300a**, and the connection portion **712** is connected to the circuit board **300** by the thermal conductive gel. For example, the thermal conductive gel wraps side edges of the connection portion **712** and the back side of the circuit board **300**. In this way, the support component **700** can not only facilitate the installation of heating element **500a** and light emission component **310**, but also facilitate the connection of the circuit board **300**, and also facilitate the transfer of excessive heat to the back side of the circuit board **300**, thereby reducing intensive heat transfer above the top surface **300a** of the circuit board **300**, and thus reducing adverse effects of excessive heat on the devices provided on the top surface **300a**.

[0101] In some embodiments, the height of the support portion **711** is higher than the height of the connection portion **712**, such that the top of the support portion **711** is inserted into the through-hole **301** when the support component **700** is connected to the circuit board **300**.

[0102] In some embodiments, the side wall of the through-hole **301** includes two circular arc faces, which are located at two ends of the side wall of the through-hole **301** to facilitate the assembly and connection between the through-hole **301** and the support component **700**.

[0103] In some embodiments, the bottom of the connection portion **712** does not contact the shell of the optical module such as the lower shell part **202**, so that the heat generated by the heating element **500a** and directly transmitted to the shell of the optical module via the support component **700** is reduced, thereby ensuring utilization rate of the heat generated by the heating element **500a**. Also, when the heating element **500a** is not working, the support component **700** can facilitate the heat dissipation of the light emission component **310** to some extent, effectively avoiding an impact of a high temperature on the performance of the light emission component **310**.

[0104] In some embodiments, the bottom of the connection portion **712** contacts with the lower shell part **202** to facilitate the transfer of heat generated by the light emission component **310** and the like to the lower shell part **202** via the support component **700**, thereby ensuring the stability of the operating temperature of the light emission component **310**.

[0105] In some existing technologies, a support block of metal or other materials is provided below the chip, mainly for heat dissipation and chip height adjustment. For example, the top of the support block supports the chip, and the bottom of the support block contacts and connects with the shell of the optical module to directly transfer the heat generated by the chip to the shell of the optical module via the support block, thereby improving efficiency of the heat dissipation of the heat generated by the chip; alternatively, the support block supports the chip such that the top surface of the chip is flush with the top surface of the circuit board, thereby facilitating the length control of the wire bonding between the chip and the circuit board.

[0106] In some embodiments, the stepped surface **713** supports and connects with the back side of the circuit board **300**, thereby facilitating the connection of the connection portion **712** with the circuit board **300**. For example, the thermal conductive gel connects the stepped surface **713** with the back side of the circuit board **300**, and the thermal conductive gel also wraps the side edges of the connection portion **712**.

[0107] FIG. **10** is an assembly diagram II of a support component provided according to some embodiments of the present disclosure. As shown in FIG. **10**, the support portion **711** is located inside the through-hole **301**, and the top of the support portion **711** supports and connects with the bottom of the heating element **500a** and the bottom of the light emission component **310**, with the light emission component **310** located between the heating element **500a** and the driver **330**. The top surface of the support portion **711** is flush with the top surface **300a** of the circuit board **300**, so as to control a height of the top of the light emission component **310**. The connection portion **712** is located on the back side of the circuit board **300**, and is assembled and connected to the back side of the circuit board **300** by the stepped surface **713**. In some embodiments, the connection portion **712** is connected to the back side of the circuit board **300** via the thermal conductive gel, and the thermal conductive gel wraps the side edges of the connection portion **712** and connects with the circuit board **300**.

[0108] FIG. **11** is an internal structure diagram of another optical module provided according to the embodiment of the present disclosure, FIG. **12** is an exploded diagram of the internal structure of another optical module provided according to the embodiment of the present disclosure, and FIG. **13** is a partially enlarged diagram of portion B in FIG. **12**, in which FIG. **11** shows a state where an optical fiber joint is vertically arranged. As shown in FIGS. **11** to **13**, a TEC **500b** is provided below the lens component **400**, and the top of the TEC **500b** supports and connects with the light emission component **310**. The TEC **500b** is electrically connected to the circuit board **300**. The TEC **500b** can be energized to release or absorb heat, thereby adjusting the temperature around the light emission component **310** to maintain the operating temperature of the light emission component **310** within a relatively stable range.

[0109] In some embodiments, a temperature detection element is provided on the TEC **500b**, for detecting the temperature around the light emission component **310**. The temperature detection element can sample thermistors or the like.

[0110] In some embodiments, the support component **700** supports and connects with the TEC **500b**. The top of the support component **700** is connected to the bottom of the TEC **500b**, and the top of the TEC **500b** supports and connects with the light emission component **310**. The support component **700** is connected to the circuit board **300**, such that the TEC **500b** is located inside the through-hole **301**.

[0111] In some embodiments, the light emission component **310** is located on an edge of the top of the TEC **500b**, the driver **330** is located on the circuit board **300** and beside the light emission component **310**. The top surface of the TEC **500b** can be lower than the top surface of the circuit board **300**, or the top surface of the TEC **500b** can be flush with the top surface of the circuit board **300**, so as to facilitate the control of the relative height between the top surface of the light emission component **310** and the top surface of the driver **330**.

[0112] In some embodiments, the light emission component **310** is located on the edge of the top of the TEC **500b**, and the light reception component **320** is located beside the light emission component **310** and on the edge of the through-hole **301**, such that the light reception component **320** and the light emission component **310** are arranged side by side in the width direction of the circuit board **300**. The TIA **340** is located beside the light reception component **320** and the driver **330**, such that the TIA **340** and the driver **330** are arranged side by side in the width direction of the circuit board **300**, to fully utilize the space provided below the lens component **400** and facilitate the size control of the lens component **400**.

[0113] In some embodiments, the driver **330** may be provided on the top of the TEC **500b**, and the driver **330** may be located beside the light emission component **310**.

[0114] FIG. **14** is a structural diagram of a circuit board provided according to some embodiments of the present disclosure. As shown in FIG. **14**, an avoidance portion **3011** is provided at the side wall of the through-hole **301**, such that the through-hole **301** can avoid the TEC **500b** by the avoidance portion **3011**, thereby facilitating the assembling of the TEC **500b**. In some

embodiments, the through-hole **301** is a prismatic through-hole, and the avoidance portion **3011** is provided at the corner of the through-hole **301** and formed as a rounded corner. The size of the through-hole **301** is relatively expanded at the corner of the through-hole **301**, which can facilitate the assembling of the TEC **500b** and effectively control the overall size of the through-hole **301** to avoid excessive overall size of the through-hole **301**.

[0115] FIG. **15** is a structural diagram of another support component provided according to some embodiments of the present disclosure, and FIG. **16** is a usage state view of another support component provided according to some embodiments of the present disclosure. As shown in FIG. **15**, the support component **700** includes a support portion **711** and a connection portion **712**. The top of the support portion **711** supports and connects with the TEC **500b**, the bottom of the support portion **711** connects to the connection portion **712**, and the connection portion **712** is used to connect with the circuit board **300**.

[0116] In some embodiments, a height of the support portion **711** is lower than that of the connection portion **712**, which facilitates the connection of the support component **700** with the circuit board **300**, and also facilitates the adaptation of the height of the TEC **500b**.

[0117] In some embodiments, a cross-sectional size of the connection portion **712** is larger than that of the support portion **711**, thereby forming a stepped surface **713** around the bottom of the support portion **711**. The stepped surface **713** can facilitate the connection of the support component **700** to the circuit board **300** and the adjustment of the heights of the top surface of the TEC **500b** and the surface of the circuit board **300**. The stepped surface **713** can be connected to the bottom surface of the circuit board **300** by dispensing glue.

[0118] FIG. **17** is a partial assembly diagram I of another support component provided according to some embodiments of the present disclosure, and FIG. **18** is a partial assembly diagram II of another support component provided according to some embodiments of the present disclosure. As shown in FIG. **17**, the top of the support portion **711** is located inside the through-hole **301**, and the bottom of the support portion **711** is located outside the through-hole **301**, such that the top surface of the TEC **500b** is flush with or lower than the top surface of the circuit board **300**, in order to ensure that the top surface of the light emission component **310** is flush with the top surface of the driver **330**. As shown in FIG. **18**, the thermal conductive gel **01** surrounds the sides of the connection portion **712**, and the connection portion **712** is connected to the circuit board **300** by the thermal conductive gel **01**.

[0119] FIG. **19** is a section view of another optical module provided according to some embodiments of the present disclosure. As shown in FIG. **19**, the bottom plate **2021** is formed with a support platform **2023**. The top of the support platform **2023** contacts and connects with the bottom of the connection portion **712** to facilitate the heat transfer to the lower shell part **202** through the support component **700**. The top of the support platform **2023** can be connected to the connection portion **712** by thermal conductive grease or thermal conductive gel.

[0120] FIG. **20** is an exploded diagram I of the internal structure of another optical module provided according to some embodiments of the present disclosure, and FIG. **21** is an exploded diagram II of the internal structure of another optical module provided according to some embodiments of the present disclosure. As shown in FIGS. **20** and **21**, a light emission component **310**, a light reception component **320**, a driver **330**, a TIA **340**, and a support component **700** are provided below the lens component **400**. The support component **700** is connected to the circuit board **300**, and the top of the support component **700** supports and connects with the light emission component **310**, the light reception component **320**, the driver **330**, and the TIA **340**. The support component **700** can use metal or the other materials having a good thermal conductivity, such as tungsten and copper. The operating temperature of the light emission component **310**, the light reception component **320**, the driver **330**, and the TIA **340** can be effectively stabilized by the support component **700**.

[0121] In some embodiments, the top of the support component **700** is located inside the through-

hole **301**, and a pad is provided on the edge of the through-hole **301**. The drivers **330** and TIA **340** are respectively connected to the pad located on the edge of the through-hole **301** by wire bonding. [0122] FIG. **22** is a structural diagram I of another support component provided according to some embodiments of the present disclosure, FIG. **23** is a partially enlarged view of another support component provided according to some embodiments of the present disclosure, and FIG. **24** is a structural diagram II of another support component provided according to some embodiments of the present disclosure. As shown in FIGS. **22-24**, in some embodiments, the support component **700** includes a support portion **711** and a connection portion **712**. The connection portion **712** is located at the bottom of the support portion **711**, and the top of the connection portion **712** is formed with a stepped surface **713**, which surrounds side edges of the bottom of the support portion **711** and is used to connect with the circuit board **300**.

[0123] A glue-dispensing groove **714** is formed on the connection portion **712**, and the glue-dispensing groove **714** is located on the edge of the bottom of the support portion **711**. The top surface of the connection portion **712** is recessed to form the glue-dispensing groove **714**, such that a bottom surface of the glue-dispensing groove **714** is lower than the stepped surface **713**. The glue-dispensing groove **714** is used for positioning the glue during the assembly of the support component **700**, facilitating glue-dispensing and glue-bearing of the support component **700**.

[0124] In some embodiments, the width of the glue-dispensing groove **714** is greater than or equal to one-third of the width of the stepped surface **713**, and the width of the glue-dispensing groove **714** is less than or equal to half of the width of the stepped surface **713**. For example, the width of the glue-dispensing groove **714** is greater than one-third of the width of the stepped surface **713** and less than half of the width of the stepped surface **713**. For example, the width of the glue-dispensing groove **714** is two-fifth of the width of the stepped surface **713**. In this way, it facilitates the coordination and control of the glue-dispensing amount of the glue-dispensing groove **714** to control the assembly of support component **700** and circuit board **300**.

[0125] In some embodiments, there are four glue-dispensing grooves **714** in the connection portion **712**, and the four glue-dispensing grooves **714** are distributed at the bottom of four corners of the supporting portion **711**. Of course, in the embodiment of the present disclosure, the stepped surface **713** may not be limited to include four glue-dispensing grooves **714** in the connection portion **712**, but may include two or three glue-dispensing grooves **714**, and etc.

[0126] In some embodiments, a glue-dispensing positioning groove **715** is provided on a bottom surface of the glue-dispensing groove **714**, for assisting in the positioning of the glue-dispensing groove **714**, such that a glue-dispensing machine can accurately dispense glue into the glue-dispensing groove **714** during dispensing glue into it. The bottom surface of glue-dispensing positioning groove **715** is lower than the bottom surface of glue dispensing groove **714**. In some embodiments, a positioning protrusion can be provided in the glue-dispensing groove **714**, for positioning the dispensed glue.

[0127] In some embodiments, a guiding groove **716** is provided in the connection portion **712**. The guiding groove **716** is communicated with the glue-dispensing groove **714**. The guiding groove **716** is used for guiding the glue, thereby effectively reducing poor assembly accuracy of the support component **700** to the circuit board **300** due to excessive glue dispensing. For example, the guiding groove **716** is provided between two adjacent glue-dispensing grooves **714**, with one end of the guiding groove **716** communicated with an edge of one glue-dispensing groove **714**, and the other end of the guiding groove **716** communicated with an edge of the other glue-dispensing groove **714**.

[0128] In some embodiments, the glue-dispensing groove **714** has an approximately cubic structure, and the guiding groove **716** extends along a side of the glue-dispensing groove **714** that is away from the support portion **711**.

[0129] In some embodiments, the bottom of the connection portion **712** is provided with an installation positioning groove **717**. The installation positioning groove **717** is configured for the

assembly positioning of the support component **700** to the circuit board **300** during assembly, to facilitate achieving the assembly and securement of the support component **700** and the circuit board **300**.

[0130] FIG. **25** is a usage state view of another support component provided according to some embodiments of the present disclosure. As shown in FIG. **25**, in some embodiments, the light emission component **310** and the light reception component **320** are arranged side by side in the width direction of the support component **700** and at a top of the support component **700**, the driver **330** is arranged on a side of the light emission component **310** that is away from the optical port of the light module **200**, and the TIA **340** and the driver **330** are arranged side by side in the width direction of the support component **700** and at the top of the support component **700**.

[0131] The support portion **711** is located inside the through-hole **301**, such that the light reception component **320** and the light emission component **310** are arranged side by side in the width direction of the circuit board **300**. The TIA **340** is located beside the light reception component **320** and the driver **330**, such that the TIA **340** and the driver **330** are arranged side by side in the width direction of the circuit board **300**, which facilitates making full use of the space at the top of the support portion **711**. It can also facilitate making full use of the space provided below the lens component **400**, so as to control the size of the lens component **400**.

[0132] FIG. **26** is an internal structure diagram of yet another optical module provided according to some embodiments of the present disclosure, FIG. **27** is an exploded diagram I of the internal structure of yet another optical module provided according to some embodiments of the present disclosure, FIG. **28** is a partial diagram of the internal structure of yet another optical module provided according to some embodiments of the present disclosure, and FIG. **29** is an exploded diagram II of the internal structure of yet optical module provided according to some embodiments of the present disclosure. As shown in FIGS. **26** to **29**, in some embodiments, a light emission component **310**, a light reception component **320**, a driver **330**, a TIA **340**, a TEC **500b**, and a support component **700** are provided below the lens component **400**. The support component **700** supports and connects with the light reception component **320**, the driver **330**, the TIA **340**, and the TEC **500b**. The TEC **500b** supports and connects with the light emission component **310**.

[0133] When the transmission rate of the laser in the light emission component **310** is not less than 200 Gb/s, it is necessary to stabilize the operating temperature of the light emission component **310** within a range of a predetermined temperature $\pm 1^{\circ}$ C. to ensure the performance of the laser. The support component **700** is made of materials having a good heat dissipation performance such as tungsten and copper, and the support component **700** is combined with the TEC **500b** to accurately maintain the operating temperature of the light emission component **310**, the light reception component **320**, the driver **330**, and the TIA **340** within a certain range, thereby reducing thermal crosstalk among the light emission component **310**, light reception component **320**, driver **330**, and TIA **340**. This can more effectively maintain the operating temperature of the light emission component **310**, thereby ensuring the stability of the performance of the light emission component.

[0134] In some embodiments, the circuit board **300** includes a first edge **3012**, a second edge **3013**, a third edge **3014**, and a fourth edge **3015**. The first edge **3012**, the second edge **3013**, the third edge **3014**, and the fourth edge **3015** are sequentially connected around the edge of the through-hole **301**. The first edge **3012** is located on a side of the through-hole **301** that is close to the optical port of the optical module **200**, the third edge **3014** is located on a side of the through-hole **301** that is away from the optical port of the optical module **200**, and the second edge **3013** and the fourth edge **3015** extend along a length direction of the circuit board **300**.

[0135] The light emission component **310** is connected to the driver **330** by wire bonding, the driver **330** is connected to the circuit board **300** by wire bonding, the light reception component **320** is connected to the TIA **340** by wire bonding, the TIA **340** is connected to the circuit board **300** by wire bonding, and the TEC **500b** is connected to the circuit board **300** by wire bonding. For example, the driver **330** is connected to the second edge **3013** and the third edge **3014** by wire

bonding, the TIA **340** is connected to the third edge **3014** and the fourth edge **3015** by wire bonding, the TEC **500b** is connected to the second edge **3013** by wire bonding, and a plurality of pads are provided on the second edge **3013**, third edge **3014**, and fourth edge **3015**, respectively. [0136] FIG. **30** is a structural diagram I of yet another support component provided according to some embodiments of the present disclosure, FIG. **31** is a structural diagram II of yet another support component provided according to some embodiments of the present disclosure, FIG. **32** is a structural diagram III of yet another support component provided according to some embodiments of the present disclosure, FIG. **33** is a usage state view of yet another support component provided according to some embodiments of the present disclosure, and FIG. **34** is a partially enlarged view of the usage state of yet another support component provided according to some embodiments of the present disclosure. In some embodiments, a thermistor component **350** may be provided below the lens component **400**. The thermistor component **350** is located on the TEC **500b** and beside the light emission component **310**. Of course, in some embodiments, the support component **700** supports and connects with the thermistor component **350**, that is, the thermistor component **350** is directly provided on the support component **700**. The thermistor component **350** is used to detect the operating temperature of the light emission component **310**, so as to provide a reference basis for controlling the TEC **500b**.

[0137] As shown in FIGS. **30** to **32**, in some embodiments, the support component **700** includes a support portion **711** and a connection portion **712**. The connection portion **712** is located at the bottom of the support portion **711**, and the top of the connection portion **712** and the support portion **711** forms a stepped surface **713**, which surrounds side edges of the bottom of the support portion **711**. The support portion **711** is formed with a cut-off corner **718** at an edge of one side thereof, which extends towards the connection portion **712**.

[0138] In some embodiments, an installation groove **719** is provided at the top of the connection portion **712**. The bottom surface of the installation groove **719** is lower than the stepped surface **713**, and the stepped surface **713** surrounds a side of the installation groove **719**. The other side of the installation groove **719** extends to the bottom of the cut-off corner **718**, such that the installation groove **719** is surrounded by the support portion **711** and the stepped surface **713**.

[0139] In some embodiments, an edge of the connection portion **712** is provided with a glue-dispensing groove **714**. An edge of the glue-dispensing groove **714** on one side extends to the bottom of the support portion **711** and an edge thereof on the other side extends to the edge of the connection portion **712**. The bottom of the glue-dispensing groove **714** is lower than the stepped surface **713**. The glue-dispensing groove **714** is used to bear glue so as to facilitate dispensing glue. In some embodiments, the edge of the installation groove **719** is not provided with any glue-dispensing groove **714** to reduce the risk of glue contamination to the TEC **500b**.

[0140] In some embodiments, there are three glue-dispensing grooves **714** in the connection portion **712**, and the three dispensing grooves **714** are distributed at the bottom of the three corners of the supporting portion **711**.

[0141] In some embodiments, a glue-dispensing positioning groove **715** is provided on the bottom surface of the glue-dispensing groove **714**. The glue-dispensing positioning groove **715** is used to assist in the positioning of the glue-dispensing groove **714**, such that a glue-dispensing machine can accurately dispense glue into the dispensing groove **714** during dispensing glue into it.

[0142] In some embodiments, an installation positioning groove **717** is provided at the bottom of the connection portion **712**. The installation positioning groove **717** is configured for the assembly positioning of the support component **700** to the circuit board **300** during assembly, to facilitate achieving the assembly and securement of the support component **700** to the circuit board **300**.

[0143] As shown in FIGS. **33** and **34**, the TEC **500b** is provided within the cut-off corner **718**, and the bottom surface of the installation groove **719** supports and connects with the bottom of the TEC **500b**. The top of the TEC **500b** supports and connects with the thermistor component **350** and the light emission component **310**, and the thermistor component **350** is provided beside the light

emission component **310**. A light reception component **320**, a driver **330**, and a TIA **340** are provided on the top of the support portion **711**, and the driver **330** is located on the side of the light emission component **310** that is away from the thermistor component **350**.

[0144] In some embodiments, one side of the driver **330** is flush with one side edge of the support portion **711**, and the TIA **340** is provided on the other side of the driver **330**. There is a gap between one side of the TIA **340** and the other side of the driver **330**, and the gap has a width that is less than or equal to the width of the light emission component **310**. The other side of the TIA **340** is flush with the other side of support portion **711**, and the light reception component **320** is located beside the TIA **340**. The gap is provided between the TIA **340** and the driver **330** to reduce thermal crosstalk between the TIA **340** and the driver **330**.

[0145] In some embodiments, the thermistor component **350** includes a thermistor **351** and a thermistor substrate **352**. A first metal layer **353** and a second metal layer **354** are provided on the top surface of the thermistor substrate **352** and form a circuit pattern on the top of the thermistor substrate **352**. The top of the TEC **500b** is connected to the thermistor substrate **352**. The thermistor **351** is attached to the first metal layer **353** and electrically connected to the first metal layer **353**, and the thermistor **351** is also connected to the second metal layer **354** by wire bonding. The first metal layer **353** and the second metal layer **354** are also connected to the circuit board **300** by wire bonding, respectively.

[0146] In some embodiments, a laser substrate **311** is also provided below the light emission component **310**. The bottom of the laser substrate **311** is connected to the top of the TEC **500b**, and the top of the laser substrate **311** is connected to the light emission component **310**. The thermal expansion coefficient of the laser substrate **311** is similar to that of the top of the TEC **500b**. In this way, the stress generated by the thermal expansion and contraction deformation of the TEC **500b** can be buffered by the laser substrate **311**, so that the adverse effect of the TEC **500b** thermal expansion and contraction on the light emission component **310** is reduced. The laser substrate **311** can use a ceramic substrate.

[0147] In some embodiments, the width of the laser substrate **311** is greater than the width of the light emission component **310**, and the length of the laser substrate **311** is greater than the length of the light emission component **310**, such that the laser substrate **311** can balance the temperature across different areas of the light emission component **310**.

[0148] In some embodiments, the TEC **500b** includes a first electrode **521** and a second electrode **522**. The first electrode **521** is located beside one end of the thermistor substrate **352** and the second electrode **522** is located beside one end of the light emission component **310**. A cold surface of the TEC **500b** supports and connects with the thermistor component **350** and the light emission component **310**, which facilitates maintaining the operating temperature of the light emission component **310** within a relatively stable range to ensure the working performance of the light emission component **310**.

[0149] FIG. **35** is an assembly section view I of yet another support component and a circuit board provided according to some embodiments of the present disclosure, and FIG. **36** is an assembly section view II of yet another support component and a circuit board provided according to some embodiments of the present disclosure. As shown in FIGS. **35-36**, the support portion **711** is located inside the through-hole **301**, the connection portion **712** is located below the circuit board **300**, and the stepped surface **713** is connected to the bottom surface of the circuit board **300**.

[0150] In some embodiments, the top surface of the support portion **711** is flush with the top surface of the circuit board **300**, and the top surface of the laser substrate **311** is flush with the top surface of the circuit board **300**, which facilitates the control of arc heights of the wire-bonding connections between the light emission component **310** and the driver **330**, between the optical reception component **320** and the TIA **340**, and between the driver **330** and TIA **340** and the circuit board **300**, thereby ensuring the high-frequency signal transmission performance of the wires for transmitting high-frequency signals. Of course, in some embodiments, the top surface of the

support portion **711** may be lower than the top surface of the circuit board **300**, and the top surface of the laser substrate **311** may be lower than the top surface of the circuit board **300**, such that the top surfaces of the light emission component **310**, the light reception component **320**, the driver **330**, and the TIA **340** are respectively flush with the top surface of the circuit board **300**.

[0151] FIG. **37** is a partial diagram of another lower shell part provided according to some embodiments of the present disclosure. As shown in FIG. **37**, an accommodation groove **2024** is provided in the bottom plate **2021**. The accommodation groove **2024** is configured for accommodating thermal conductive silicone grease or thermal conductive gel, etc. The thermal conductive silicone grease or the thermal conductive gel, etc. connects the bottom plate **2021** and the bottom of connection portion **712** to achieve contact and connection between the connection portion **712** and the lower shell part **202** by the thermal conductive silicone grease or the thermal conductive gel, etc., thereby facilitating heat transfer between the connection portion **712** and the lower shell portion **202**.

[0152] In some embodiments, a protrusion **2025** is provided within the accommodation groove **2024**. There is a gap between an edge of the protrusion **2025** and an edge of the accommodation groove **2024** for containing spilled thermal conductive silicone grease or thermal conductive gel, etc., such that the protrusion **2025** supports the bottom of the connection portion **712**. The combination of the accommodation groove **2024** and the protrusion **2025** can improve the heat transfer efficiency between the connection portion **712** and the lower shell part **202**, thereby fully ensuring the heat dissipation of the support component **700**.

[0153] In some embodiments, the optical module **200** is not limited to include one lens component **400**, but may include two or more lens components. In the case that there are two lens components **400** in the optical module **200**, the arrangement of the devices below the two lens components **400** can refer to that of the devices below one lens component **400** of the optical module **200** mentioned above.

[0154] Finally, it should be noted that the above embodiments are used to illustrate the technical solution of the present disclosure rather than provide a limit to it. Although detailed explanations of the present disclosure have been provided with reference to the aforementioned embodiments, those skilled in the art should understand that they can still modify the technical solutions recorded in the aforementioned embodiments, or equivalently replace some of the technical features therein. These modifications or replacements do not make the essence of the corresponding technical solutions deviate from the spirit and scope of the technical solutions disclosed in the present disclosure.

Claims

1. An optical module comprising: a circuit board, which is provided with a through-hole; a light emission component for generating an optical signal; a driver, which is electrically connected to the circuit board, located beside the light emission component, and electrically connected to the light emission component; a lens component, which is connected to the circuit board at its bottom and is covered over the light emission component, configured to change a transmission direction of the optical signal generated by the light emission component; a support component, which has a top located inside the through-hole and is connected to the circuit board, with a thermal conductivity coefficient of the support component being greater than or equal to that of the circuit board; and a temperature regulating mechanism, which is located below the lens component and its bottom is connected to the support component; wherein the temperature regulating mechanism is located below or beside the light emission component, configured to regulate an operating temperature of the light emission component.

2. The optical module according to claim 1, wherein the support component comprises a support portion located inside the through-hole and a connection portion connected to the circuit board;

wherein a cut-off corner is formed at one side of the support portion, and a top of the support portion supports and connects with the driver; wherein the temperature regulating mechanism comprises a TEC provided within the cut-off corner, and a top of the TEC supports and connects with the light emission component; wherein the TEC is electrically connected to the circuit board and is configured to regulate the operating temperature of the light emission component.

3. The optical module according to claim 2, further comprising a light reception component and a TIA, wherein the light reception component and the TIA are located below the lens component, and the light reception component and the TIA are provided at the top of the support component; wherein the light reception component and the driver are respectively located beside the cut-off corner, and the TIA is located beside the driver and the light reception component; and wherein the optical emission component is connected to the driver by wire bonding, and the driver is connected to the circuit board by wire bonding; and the light reception component is connected to the TIA by wire bonding, and the TIA is connected to the circuit board by wire bonding.

4. The optical module according to claim 2, wherein a top of the connection portion is formed with a stepped surface and a glue-dispensing groove, and the stepped surface surrounds a side edge of a bottom of the support portion and is connected to the circuit board; and wherein the glue-dispensing groove is located at an edge of the bottom of the support portion, and a bottom surface of the glue-dispensing groove is lower than the stepped surface; wherein the glue-dispensing groove is used for providing a glue-dispensing positioning groove therein, with a bottom surface of the glue-dispensing positioning groove being lower than a bottom surface of the glue-dispensing groove.

5. The optical module according to claim 2, wherein a top of the TEC is further provided with a thermistor component, which is located on a side of the light emission component that is away from the driver; wherein the thermistor component comprises a thermistor and a thermistor substrate, a first metal layer and a second metal layer are provided on a top surface of the thermistor substrate, and the thermistor is mounted on the first metal layer and connected to the second metal layer by wire bonding; and wherein the first metal layer and the second metal layer are respectively connected to the circuit board by wire bonding.

6. The optical module according to claim 5, wherein a top of the TEC is further provided with a laser substrate, with a bottom of the laser substrate being connected to the TEC, and a top of the laser substrate supporting and connecting with the light emission component; wherein a width of the laser substrate is greater than that of the light emission component, and a length of the laser substrate is greater than that of the light emission component; and there is a gap between the laser substrate and the thermistor substrate.

7. The optical module according to claim 1, further comprising a lower shell part, wherein a bottom plate of the lower shell part is provided with an accommodation groove, a protrusion is provided within the accommodation groove, and the protrusion supports and connects with the bottom of the support component; and wherein conductive grease or thermal conductive gel are filled in a gap formed between the accommodation groove and the protrusion.

8. The optical module according to claim 1, wherein the temperature regulating mechanism comprises a TEC provided at the top of the support component, and a top of the TEC supports and connects with the light emission component.

9. The optical module according to claim 8, wherein the driver is provided on the circuit board and is located beside the through-hole, and the driver is connected to the light emission component by wire bonding.

10. The optical module according to claim 7, wherein the support component comprises a support portion located inside the through-hole and a connection portion connected to the circuit board by wire bonding; and wherein the TEC is provided at the top of the support portion, and a height of the support portion is lower than that of the connection portion; an avoidance portion is provided on a side wall of the through-hole, and is located at a corner of the through-hole.

- 11.** The optical module according to claim 8, wherein the top of the TEC supports and connects with the driver, and the driver is connected to the circuit board by wire bonding; and wherein the top surface of the TEC is lower than the top surface of the circuit board, or the top surface of the TEC is flush with the top surface of the circuit board.
- 12.** The optical module according to claim 8, further comprising a light reception component and a TIA, wherein the light reception component and the TIA are located below the lens component; wherein the light reception component and the TIA are respectively located at the top of the support component; or wherein the light reception component and the TIA are provided on the circuit board and beside the through-hole, the light reception component and the light emission component are arranged side by side in a width direction of the circuit board, the TIA is located beside the driver, and the TIA and the driver are arranged side by side in the width direction of the circuit board.
- 13.** The optical module according to claim 1, wherein the temperature regulating mechanism comprises a heating element, the heating element is provided at the top of the support component, and the heating element is provided beside the light emission component or below the light emission component.
- 14.** The optical module according to claim 13, wherein the heating element comprises a substrate, and a heating layer, a first pad, and a second pad are provided on the substrate, with one end of the heating layer being connected to the first pad, the other end of the heating layer being connected to the second pad, and the heating layer extending from one end of the light emission component to the other end of the light emission component; and the first pad and the second pad are electrically connected to the circuit board.
- 15.** The optical module according to claim 13, wherein the support component is connected to the circuit board by adhesive, and the bottom of the support component does not contact the shell of the optical module.
- 16.** The optical module according to claim 14, wherein the driver is provided beside the through-hole; and wherein the heating layer is provided on an edge of the top of the substrate, located on a side edge of the substrate that is away from the driver; and a bottom of the light emission component is connected to the substrate.
- 17.** The optical module according to claim 3, wherein the circuit board comprises a first edge, a second edge, a third edge, and a fourth edge sequentially surround side edges of the through-hole; wherein the first edge is located on a side of the through-hole that is near an optical port of the optical module, and the third edge is located on a side of the through-hole that is away from the optical port of the optical module; and wherein the second edge, the third edge, and the fourth edge are respectively provided with pads, and the driver is connected to the second edge and the third edge by wire bonding, and the TIA is connected to the third edge and the fourth edge by wire bonding.
- 18.** An optical module comprising: a circuit board, which is provided with a through-hole; a lens component, a bottom of which is connected to the circuit board, wherein the lens component is configured for changing a transmission direction of an optical signal; an optical chip, which is provided below the lens component, and comprises at least one of a light emission component and a light reception component; and a support component, which connects with the circuit board, and has a top located inside the through-hole; the support component supports and connects with the optical chip, and a thermal conductivity coefficient of the support component is greater than that of the circuit board.
- 19.** The optical module according to claim 18, further comprising a temperature regulating mechanism, wherein the temperature regulating mechanism is located below the lens component and its bottom is connected to the support component, and the temperature regulating mechanism is located below or beside the optical chip.
- 20.** An optical module comprising: a circuit board, which is provided with a through-hole; a lens component, a bottom of which is connected to the circuit board, wherein the lens component is

configured for changing a transmission direction of an optical signal; an optical chip, which is located below the lens component, and comprises at least one of a light emission component and a light reception component; a matching chip, which is located below the lens component and beside the optical chip, correspondingly connected to the optical chip by wire bonding; and the matching chip comprises at least one of a driver and a TIA; and a support component, which connects with the circuit board, and has a top located inside the through-hole; the support component supports and connects with the optical chip and the matching chip, and a thermal conductivity coefficient of the support component is greater than that of the circuit board.
