

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414540
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Xiao; Zhihai et al.

Feeder

Abstract

A feeder for food storage which includes a mount provided with a food outlet hole and a door assembly. The door assembly includes a door panel with a movable side and a fixed side which is configured to close or open the food outlet hole; a rotating shaft; and a pressing member. The fixed side of the door panel is fixedly connected to the rotating shaft, the rotating shaft is rotatably connected to the mount, and the movable side of the door panel is rotatable with respect to the mount via the rotating shaft. The pressing member rotatably mounted to the mount, the pressing member including a first pressing portion configured to exert a pressure to the door panel to reduce a gap between the door panel and the food outlet hole.

Inventors:	Xiao; Zhihai (Shenzhen, CN), Yan; Chao (Shenzhen, CN)
Applicant:	Shenzhen Libro Technology Co., Ltd. (Shenzhen, CN)
Family ID:	1000008822090
Assignee:	SHENZHEN LIBRO TECHNOLOGY CO., LTD. (Shenzhen, CN)
Appl. No.:	18/386997
Filed:	November 03, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240407330 A1	Dec. 12, 2024

Foreign Application Priority Data

CN	202310688947.5	Jun. 09, 2023
CN	202321477213.4	Jun. 09, 2023

Publication Classification

Int. Cl.: A01K5/02 (20060101)

U.S. Cl.:

CPC A01K5/0225 (20130101);

Field of Classification Search

CPC: A01K (5/0225); A01K (5/0275)

USPC: 222/548

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
533197	12/1894	Jaeger	222/335	G07F 17/166
1301051	12/1918	Hart	119/51.01	A01K 5/0114
1733905	12/1928	Randolph	294/68.24	B61D 7/26
3727584	12/1972	Permann	119/56.1	A01K 5/0225
4044722	12/1976	Bradshaw	119/51.13	A01K 5/0291
5109799	12/1991	Lader	119/51.13	A01K 5/0291
5372093	12/1993	Pooshs	119/51.11	A01K 5/0291
5709166	12/1997	Evans	119/51.11	A01K 5/02
6009835	12/1999	Boschert	222/650	A01K 61/85
11895990	12/2023	Johnson	N/A	A01K 61/85
2022/0132799	12/2021	Wang	119/57.91	A01K 5/0291
2023/0180714	12/2022	Wu	119/57	A01K 5/0142

OTHER PUBLICATIONS

Translation of KR 20220111979 A (Year: 2022). cited by examiner

Primary Examiner: Perry; Monica L

Assistant Examiner: Lowery; Brittany A

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present application claims priority to Chinese patent Application No. 2023106889475, filed on Jun. 9, 2023, and claims priority to Chinese patent Application No. 2023214772134, filed on Jun. 9, 2023, the contents of which are incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to the technical field of food storage, in particular to a feeder.

BACKGROUND

(3) At present, poultry, pets and some other animals can be fed through feeders. The feeder usually includes an accommodating chamber for storing food such as feed and grains. The accommodating chamber outputs the food through structures such as food outlet holes and food outlet channels. In

order to prevent food from going bad due to damp and other reasons, it is usually necessary to form a negative pressure in the accommodating chamber. In this case, it is necessary to use a door assembly to cover the corresponding food outlet channel or food outlet hole to ensure the negative pressure in the accommodating chamber.

(4) In the related technology, a linkage mechanism is used to open or close the door assembly, and the door assembly is fixed by means of a dead point position of the linkage mechanism. However, the dead point position of the linkage mechanism is easy to be released, for example, it can be released by applying a slight lateral force. In addition, a seal formed by the door assembly is easy to be damaged, and the seal of the door assembly needs to be improved.

SUMMARY

(5) The main object of the present disclosure is to overcome the defects of the related technology by providing a feeder with good sealing performance.

(6) To achieve the above object, the present disclosure provides a feeder, including: a mount provided with a food outlet hole and a door assembly. A plane perpendicular to an axis of the food outlet hole is inclined with respect to a horizontal plane or parallel to the horizontal plane. The door assembly includes: a door panel configured to close or open the food outlet hole, a second rotating shaft and a pressing member. The door panel includes a movable side and a fixed side. In a position in which the door panel closes the food outlet hole, the movable side of the door panel is higher in a longitudinal direction than the fixed side, or the movable side of the door panel is flush with the fixed side in the longitudinal direction. The fixed side of the door panel is fixedly connected to the second rotating shaft, the second rotating shaft is rotatably connected to the mount, and the movable side of the door panel is rotatable with respect to the mount via the second rotating shaft. The pressing member is rotatably mounted to the mount, the pressing member includes a first pressing portion, and the first pressing portion is configured to exert a pressure onto the door panel to reduce a gap between the door panel and the food outlet hole.

(7) In the feeder of the present disclosure, the door assembly includes the door panel and the pressing member. During the closing of the door panel, when the door panel rotates to a position near the food outlet hole, the first pressing portion exerts a pressure onto the door panel. In this way, it is beneficial for the door panel to reach a preset cooperating position with the food outlet hole, beneficial to improve the abutment tightness between the door panel and the food outlet hole, and beneficial to improve the sealing performance of the feeder.

(8) In the feeder of the present disclosure, when the angle between the door panel and the plane perpendicular to the axis of the food outlet hole **2021** is less than or equal to the first preset angle, the first pressing portion is activated to exert the pressure onto the door panel, so as to reduce the gap between the door panel and the food outlet hole and improve the sealing performance of the feeder.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order to explain more clearly technical solutions of the embodiments of the disclosure or the related technology, the drawings for the description of the embodiments and the related technology will be introduced below. Apparently, the drawings in the below description are only used for some embodiments of the disclosure, and other drawings may be acquired based on the structure shown in these drawings by those skilled in the art without creative efforts.

(2) FIG. 1 is a perspective view of an embodiment of a feeder of the present disclosure.

(3) FIG. 2 is a schematic view showing a cooperation between a door assembly and a food outlet hole in an embodiment of a feeder of the present disclosure.

(4) FIG. 3 is a perspective view in an upward visual angle of an embodiment of a feeder of the

present disclosure (a part of the structure is hidden).

(5) FIG. 4 is an enlarged partial view showing area M of FIG. 3.

(6) FIG. 5 is a schematic view showing a cooperation between a door assembly and a food outlet hole under another status in an embodiment of a feeder of the present disclosure.

(7) FIG. 6 is a perspective view of a door assembly in an embodiment of the present disclosure (a part of the structure is hidden).

(8) FIG. 7 is a cross-sectional view of a door assembly in an embodiment of the present disclosure.

(9) TABLE-US-00001 Refer- Refer- ence ence Symbol Element Symbol Element 2000 barrel 2001 accommodating chamber 2021 food outlet hole 3200 food outlet channel 3300 door assembly 3310 door panel 3311 connecting through hole 3312 second rotating shaft 3313 first bump 3320 boss 3321 body 3322 elastic cap 3323 elastic annular plate 3324 connecting post 3325 abutment block 3331 first pressing portion 3332 second batten 3333 third batten 3334 first rotating shaft 3335 second bump 3341 pressure driving device 3342 door driving device 3351 first position switch 3352 third position switch 3353 second position switch 3361 vacuum pump 3362 solenoid valve 3363 negative pressure switch 3371 first through hole 3372 second through hole 3373 third through hole 3381 exhaust pipe 3382 intake pipe 3383 negative pressure tube 3510 mount 4000 food bowl

(10) The implementation of objectives, functional characteristics and advantages of the disclosure will be further described with reference to accompanying drawings in combination with embodiments.

DETAILED DESCRIPTION

(11) Hereinafter a clear and complete description will be given for explaining the technical solution in the embodiments of the present disclosure with reference to the drawings of the embodiments of the present disclosure. It should be noted that the described embodiments are only part of and not all of the embodiments of the present disclosure. All other embodiments obtained by those of ordinary skill in the art based on the embodiments in the present disclosure without creative efforts fall within the scope of protection of the present disclosure.

(12) It should be noted that directional and positional terms in the embodiments of the present disclosure, such as “upper”, “lower”, “left”, “right”, “front” and “rear” are used to explain the relative position relationship and movement of the elements in a specific attitude. It should be understood that these directional terms may correspondingly change when the specific attitude is changed.

(13) In the embodiments of the present disclosure, the terms “first” and “second” are used merely for descriptive purposes, and are not to be construed as indicating or implying relative importance or implicitly specifying the quantity of indicated technical features. Thus, the features defined as “first”, “second” may explicitly or implicitly mean that there is at least one said features. In addition, the meaning of the term “and/or” or “and/or” includes any and all combinations of one or more of the associated listed items. For example, “A and/or B” includes scheme A, scheme B, or a scheme including both A and B. In addition, the technical solutions of the various embodiments may be combined with each other as long as the person of ordinary skill in the art can realize it. If the combination of the technical solutions results in a contradictory or the combination of the technical solutions is impossible to realize, it should be considered that the combination of the technical solutions does not exist and is not within the scope of protection of the present disclosure.

(14) In the related technology, a linkage mechanism is used to open or close a door assembly, and the door assembly is fixed by means of a dead point position of the linkage mechanism. However, the dead point position of the linkage mechanism is easy to be released, for example, it can be released by applying a slight lateral force. In addition, a seal formed by the door assembly is easy to be damaged, and the seal stability of the door assembly needs to be improved.

(15) Therefore, the present disclosure provides a feeder to improve the sealing stability of a door assembly.

(16) Referring to FIGS. 1 and 2, in an embodiment of the present disclosure, the feeder includes a

mount **3510** and a door assembly **3300**. In the mount **3510**, a food outlet hole **2021** is provided, and a plane **P1** perpendicular to an axis **X-X'** of the food outlet hole **2021** is inclined with respect to a horizontal plane or parallel to the horizontal plane. The horizontal plane refers to a plane on which the feeder is placed normally, such as the ground, table top or countertop. Referring to FIG. 2, the door assembly **3300** includes a door panel **3310** and a pressing member. The door panel **3310** is configured to close or open the food outlet hole **2021**. The door panel **3310** includes a movable side and a fixed side. When the door panel **3310** is located at a position in which the door panel **3310** closes the food outlet hole **2021**, the movable side of the door panel **3310** is higher in a longitudinal direction than the fixed side, or the movable side of the door panel **3310** is flush with the fixed side in the longitudinal direction. The fixed side of the door panel **3310** is fixedly connected to a second rotating shaft **3312**. The second rotating shaft **3312** is rotatably connected to the mount **3510**. The movable side of the door panel **3310** can rotate relative to the mount **3510** through the second rotating shaft **3312**.

(17) The pressing member is rotatably mounted to the mount **3510**, and includes a first pressing portion **3331**. The first pressing portion **3331** may exert a pressure onto the door panel **3310** to reduce a gap between the door panel **3310** and the food outlet hole **2021**, thereby improving the abutment tightness between an outer peripheral wall of a boss **3320** and an inner peripheral wall of the food outlet hole **2021**. The feeder may also include a barrel **2000**. The barrel **2000** defines an accommodating chamber **2001**, so that food can be accommodated by the accommodating chamber, and can be outputted by communicating the accommodating chamber **2001** with the food outlet hole **2021**. In addition, the feeder may also be provided with a food outlet channel **3200** and a food bowl **4000**. The food outlet channel **3200** is in communication with the food outlet hole **2021**, and an outlet of the food outlet channel **3200** is arranged to be opposite to the food bowl **4000**, so that the food may pass through the food outlet hole **2021** and the food outlet channel **3200** in turn and then reach the food bowl **4000**. In the feeder, the flow of food is guided by the food outlet channel **3200**, which can reduce the dispersion of food after being outputted. Of course, the feeder can directly output food to the food bowl **4000** through the food outlet hole **2021** instead of providing the food outlet channel **3200**. The door panel **3310** may be arranged in the food outlet channel **3200**, to enhance the structural compactness of the whole feeder. It should be noted that the door panel **3310** may also be arranged at the outlet of the food outlet channel **3200**, but the embodiment of the present disclosure is not limited thereto.

(18) Referring to FIG. 2, one side of the door panel **3310** is rotatably mounted to the mount **3510**, and the door panel **3310** is provided with the boss **3320**. The outer peripheral wall of the boss **3320** is adapted to abut against the inner peripheral wall of the food outlet hole **2021**, thereby allowing a tight fit such as an interference fit by the abutment.

(19) In this embodiment, the door assembly **3300** includes the door panel **3310** and the pressing member. As such, in the closing process of the door panel **3310**, after the door panel **3310** pivots to cause the outer peripheral wall of the boss **3320** to approach or abut against the inner peripheral wall of the food outlet hole **2021**, the first pressing portion **3331** applies a pressure to the door panel **3310**. This is beneficial to bring the door panel **3310** and the boss **3320** to a preset cooperating position with the food outlet hole **2021**, beneficial to improve the abutment tightness between the door panel **3310** and the food outlet hole **2021**, and beneficial to improve the sealing stability of the door assembly **3300**.

(20) In some embodiments, the first pressing portion **3331** may be configured to abut against the other side of the door panel **3310** opposite to a rotational connection side to move the door panel **3310** toward the food outlet hole **2021**. For example, in FIG. 2, the right side of the door panel **3310** is the rotational connection side with the mount **3510**, and the left side of the door panel **3310** is abutted by the first pressing portion **3331**. Since one side of the door panel **3310** is rotatably connected to the mount **3510**, for example, in a pivotal manner, the restriction on the pivot of the first pressing portion **3310** can be released when the door panel **3331** is able to move to the outside

the pivot envelope circle of the door panel **3310**. Alternatively, the first pressing portion **3331** is set to have a large movement range, so as to avoid the first pressing portion **3331** excessively limiting an opening degree of the door panel **3310**, so that the door panel **3310** can reach a preset opening degree.

(21) In this embodiment, since the first pressing portion **3331** abuts against the other side of the door panel **3310** opposite to the rotational connection side, the acting moment is larger. For the same acting force, the embodiment of the present disclosure is more beneficial to improve the abutment tightness between the boss **3320** and the food outlet hole **2021**, and to improve the sealing stability of the door assembly **3300**.

(22) Specifically, the door assembly **3300** may include a second rotating shaft **3312** rotatably connected to the mount **3510**. A first rotating shaft **3334** and the second rotating shaft **3312** are disposed on opposite sides of the food outlet hole **2021**. The first rotating shaft **3334** corresponds to the rotational connection side of the door panel **3310** and the mount **3510**.

(23) In some embodiments, the pressing member also includes a second pressing portion that may exert a pressure onto the door panel **3310** to increase the gap between the door panel **3310** and the food outlet hole **2021**. For example, the second pressing portion is configured for abutting against a surface of the door panel **3310** facing the boss **3320**, to move the door panel **3310** in a direction away from the food outlet hole **2021**, thereby reducing the abutment tightness between the boss **3320** and the food outlet hole **2021** and enlarging the gap between the door panel **3310** and the food outlet hole **2021**. In this way, door panel **3310** is tilted, which makes it easier for the door panel **3310** to turn to the open state. Correspondingly, the first pressing portion **3331** is configured to abut against a surface of door panel **3310** away from the boss **3320**, so as to move door panel **3310** towards the food outlet hole **2021**, thereby reducing the gap between the door panel **3310** and the food outlet hole **2021**.

(24) Referring to FIGS. 3 and 4, the pressing member may also include a first rotating shaft **3334**, the first rotating shaft **3334** is rotatably to the mount **3510**. The first pressing portion **3331** and the second pressing portion may be provided on an outer peripheral wall of the first rotating shaft **3334**. Referring to FIGS. 5 and 6, the second pressing portion may include a second batten **3332** and a third batten **3333**. The second batten **3332** and the third batten **3333** are spaced apart from each other in an axial direction of the first rotating shaft **3334**. The second batten **3332** and the third batten **3333** may be provided on the same generatrix of the outer peripheral wall of the first rotating shaft **3334**. The second batten **3332** and the third batten **3333** are configured to abut against the door panel **3310** so as to assist in opening the door panel **3310**. The second batten **3332** and the third batten **3333** are spaced apart from each other in the axial direction of the first rotating shaft **3334**. The second batten **3332** and the third batten **3333** can act on two spaced positions of the door panel **3310**, for example, each of the second batten **3332** and the third batten **3333** abuts against a respective one of two corners of the door panel **3310**. After the two spaced positions of the door panel **3310** are abutted by the battens, the plate plane of the door panel **3310** will warp slightly, which will force the outer peripheral wall of the boss **3320** to warp correspondingly. The abutment tightness degree at the abutment position of the outer peripheral wall of the boss **3320** and the inner peripheral wall of the food outlet hole **2021** can be reduced locally at first, and then the abutment tightness degree at other positions are reduced, which is beneficial to reduce the force for opening the door panel **3310**, and beneficial to open the door assembly **3300**. When there is a residual negative pressure in the accommodating chamber **2001**, the corresponding warp of the outer peripheral wall of the boss **3320** is beneficial to relieve the negative pressure more quickly, which facilitates the opening of the door assembly **3300**.

(25) In some embodiments, referring to FIGS. 5 and 6, the second batten **3332** is L-shaped, one end of the L-shape is connected to the first rotating shaft **3334**, and the other end of the L-shape extends in a direction away from the first rotating shaft **3334**. The second batten **3332** is configured to abut against the surface of the door panel **3310** adjacent to the boss **3320**, to cause door panel **3310** to

sink. The second batten **3332** is L-shaped, which can reduce the risk of interference with the rotation of the door panel **3310** and improve the rotation smoothness of the door panel **3310**. The second batten **3332** may include a longitudinal extension portion and a transverse extension portion which are connected to each other to form the L-shape. The longitudinal extension portion may be configured to extend in a radial direction of the first rotating shaft **3334** and be connected to the first rotating shaft **3334**, and the transverse extension portion is connected to an end of the longitudinal extension portion away from the first rotating shaft **3334**. The transverse extension portion is intended to move into the gap between the food outlet hole **2021** and the surface of the door panel **3310** adjacent to the boss **3320**, so as to increase the gap between the door panel **3310** and the food outlet hole **2021** and reduce the interference with the rotation of the door panel **3310**, by abutting the transverse extension portion against the surface of door panel **3310** adjacent to the boss **3320**.

(26) In addition, the first pressing portion **3331** may be configured to be fixedly connected to the second pressing portion. For example, the first pressing portion **3331** is fixedly connected to the second pressing portion directly, or the first pressing portion **3331** is fixedly connected to the second pressing portion through an intermediate connection structure such as the first rotating shaft **3334**. The first pressing portion **3331** and the second pressing portion may be fixedly connected to the outer peripheral wall of the first rotating shaft **3334**, for example, the first pressing portion **3331**, the second pressing portion and the first rotating shaft **3334** may be formed in one piece, or the first pressing portion **3331** and the second pressing portion may be fixedly connected to the first rotating shaft **3334** by means of bolt connection, slot connection, snap connection, etc. This embodiment is not limited thereto. The first pressing portion **3331** and the second pressing portion may be disposed at intervals in the circumferential direction of the first rotating shaft **3334** so as to form a circumferential angle. In this case, when the first rotating shaft **3334** is in a position in which the first pressing portion **3331** abuts against the door panel **3310**, the second pressing portion acts on the door panel **3310** only after the first rotating shaft **3334** continues to rotate by a certain angle, which reduces the risk that the first pressing portion **3331** and the second pressing portion act on the door panel **3310** at the same time, and reduces the risk that the door assembly **3300** is accidentally opened when it needs to be closed or the door assembly **3300** is blocked when it needs to be opened.

(27) Referring to FIGS. 5 and 6, the first pressing portion **3331** includes a first batten. The first batten extends in the axial direction of the first rotating shaft **3334** such that the first batten is in the shape of a rectangle extending in the axial direction of the first rotating shaft **3334**. The first batten is configured to abut against the surface of the door panel **3310** away from the boss **3320** to lift the door panel **3310** upward. In this embodiment, the first batten is configured to abut against the surface of the door panel **3310** away from the boss **3320** to move the door panel **3310** toward the food outlet hole **2021**, i.e., to assist in closing the door panel **3310**. Before closing the door panel **3310**, the food outlet hole **2021** is in an open state, and the accommodation chamber **2001** is in a normal pressure state or a slight negative pressure state due to the early opening of a pump such as a vacuum pump, which results in less resistance to closing the door panel **3310**. The first batten extends in the axial direction of the first rotating shaft **3334**. The first batten is in the shape of a rectangle extending in the axial direction of the first rotating shaft **3334**, which can increase the action area with the door panel **3310**, make the door assembly **3300** to close the food outlet hole **2021** more smoothly, reduce the local action of the door assembly **3300** when cooperating with the food outlet hole **2021**, and reduce the risk of damage to the door assembly **3300**.

(28) In some embodiments, referring to FIGS. 5 and 6, the boss **3320** includes a body **3321**, which may be formed in one piece with the door panel **3310**, and an elastic cap **3322**, which may be made of a plastic material having elasticity. The elastic cap **3322** is arranged around the boss body **3321**. An outer peripheral wall of the elastic cap **3322** is configured to abut against the inner peripheral wall of the food outlet hole **2021**. In this embodiment, since the elastic cap **3322** itself has

elasticity, the stability of a tight fit between the outer peripheral wall of the elastic cap **3322** and the inner peripheral wall of the food outlet hole **2021** formed after the elastic cap **3322** abuts against the inner peripheral wall of the food outlet hole **2021** can be improved, and thus the stability of the closing of the food outlet hole **2021** by the door assembly **3300** can be further improved.

(29) In some embodiments, referring to FIGS. **6** and **7**, the outer peripheral wall of the elastic cap **3322** is provided with an elastic annular plate **3323**. The elastic annular plate extends in a circumferential direction of the elastic cap **3322**. In the process of closing the door assembly **3300**, the elastic annular plate **3323** can be folded when it is abutted. Due to the elastic force generated after the folding, the stability of tight fit with the inner peripheral wall of the food outlet hole **2021** is further improved, and the stability of the closing of the food outlet hole **2021** by the door assembly **3300** can be further improved.

(30) In some embodiments, referring to FIG. **5**, the outer peripheral wall of the elastic cap **3322** is inclined, and the cross-sectional area of a top of the elastic cap **3322** is less than the cross-sectional area of a bottom of the elastic cap **3322** to facilitate access of the boss **3320** into the food outlet hole **2021**. Correspondingly, the inner peripheral wall of the food outlet hole **2021** may also be inclined, and the diameter of the food outlet hole **2021** increases in a direction away from the accommodating chamber **2001**. An angle between a surface of the elastic annular plate **3323** and the outer peripheral wall at the bottom of the elastic cap **3322** is less than 90 degrees (see an angle **N** in FIG. **7**). In this embodiment, when closing the door assembly **3300**, the elastic annular plate **3323** is liable to inclined backward, so that the elastic annular plate **3323** is barb-shaped after the door assembly is closed. In this way, the resistance to the opening of the door assembly **3300** is enhanced, and the stability of the closing of the food outlet hole **2021** by the door assembly **3300** is further improved. The outer peripheral wall of the elastic cap **3322** may be provided with at least two elastic annular plates **3323**. The elastic annular plates **3323** are arranged at intervals in a height direction of the elastic cap **3322**, to further enhance the resistance to the opening of the door assembly **3300** and further improve the stability of the closing of the food outlet hole **2021** by the door assembly **3300**.

(31) Referring to FIG. **7**, in order to improve the stability of the elastic cap **3322** arranged around the body **3321**, the door panel **3310** may be provided with a connecting through hole **3311**, and the bottom of the elastic cap **3322** may be provided with a connecting post **3324** and an abutment block **3325** which is provided on a side of the door panel **3310** away from the elastic cap **3322**. The connecting post **3324** passes through the connecting through hole **3311** and is connected to the abutment block **3325**. The abutment block **3325** abuts against the door panel **3310**, thereby better preventing the elastic cap **3322** from falling off by the abutment block **3325**. The elastic cap **3322**, the elastic annular plate **3323**, the connecting post **3324**, and the abutment block **3325** may be made in one piece on the door panel **3310** by, for example, an encapsulation process. Of course, the elastic cap **3322**, the elastic annular plate **3323**, the connecting post **3324** and the abutment block **3325** may be made in one piece at first, and then the abutment block **3325** may be squeezed through the connecting through hole **3311** by means of the elasticity of the abutment block **3325**. This embodiment is not limited thereto.

(32) In some embodiments, the door assembly **3300** further includes a pressure driving device **3341** that drives the pressing member into rotation through the first shaft **3334**. The door assembly **3300** also includes a door driving device **3342** that drives the door panel **3310** into rotation through the second rotating shaft **3312**. The pressure driving device **3341** may be connected to the first pressing portion **3331**. The pressure driving device **3341** may be directly connected to the first pressing portion **3331**, or the pressure driving device **3341** may also be connected to the first pressing portion **3331** through an intermediate connection structure of the first rotating shaft **3334** described above. Because the first pressing portion **3331** is fixedly connected to the second pressing portion, the pressure driving device **3341** can drive the first pressing portion **3331** or the second pressing portion to abut against the door panel **3310**. The door driving device **3342** may be connected to the

door panel **3310**, for example, the door driving device **3342** may be connected to the door panel **3310** through the above-mentioned second rotating shaft **3312**, so as to drive the door panel **3310** to pivot. Each of the pressure driving device **3341** and the door driving device **3342** may be a drive motor, a drive cylinder, a drive hydraulic cylinder, etc. This embodiment is not limited thereto. If necessary, a transmission mechanism and an intermediate connection structure can be provided between the pressure driving device **3341** and the first pressing portion **3331** or the second pressing portion, or between the door driving device **3342** and the door panel **3310**. In this embodiment, the pressure driving device **3341** and the door driving device **3342** can be independently driven. For example, the pressure driving device **3341** can be supplied with a driving current, a driving air pressure or a driving hydraulic pressure greater than that for the door driving device **3342**, because the pressure driving device **3341** needs to hold the door assembly **3300** tightly. Therefore, each of the pressure driving device **3341** and the door driving device **3342** can be selected from models having a narrow power range and a narrow application range, which is conducive to reducing the cost of the pressure driving device **3341** and the door driving device **3342**. In addition, since the pressure driving device **3341** and the door driving device **3342** can be driven independently, the intermediate transmission structure can be eliminated, which is beneficial to the miniaturization of the feeder.

(33) In some embodiments, the door assembly **3300** may include a first position switch **3351** for detecting a pivot angle of the door panel **3310**. The first position switch **3351** may be electrically connected to the pressure driving device **3341**. The first position switch **3351** may be in the form of a limit switch, a travel switch, a photoelectric sensor, or a laser rangefinder, an encoder corresponding to a driving motor, but the embodiment is not limited thereto. When an angle between the surface of the door panel **3310** facing the boss **3320** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** is less than or equal to a first preset angle, the first position switch **3351** generates a first position information, and in response to the first position information, the pressure driving device **3341** drives the first pressing portion **3331** to exert a pressure onto the door panel **3310**. In this embodiment, when the door assembly **3300** pivots to a position close to the food outlet hole **2021** or to a position in which the door assembly **3300** abuts against the food outlet hole **2021**, the first position information is used to cause the abutment action of the first pressing portion **3331** to the door panel **3310**. In this way, the waiting time of the first pressing portion **3331** in the process of closing the door assembly **3300** can be reduced and the closing efficiency of the door assembly **3300** can be improved.

(34) In some embodiments, the door assembly **3300** may also include a second position switch **3353** for detecting the position of one of the first pressing portion **3331** and the second pressing portion. Since the first pressing portion **3331** and the second pressing portion are fixedly connected to each other, the position of the other of the first pressing portion **3331** and the second pressing portion can be deduced. The second position switch **3353** may be in the form of a limit switch, a travel switch, a photoelectric sensor, or a laser rangefinder, an encoder corresponding to a driving motor, but the embodiment is not limited thereto. The second position switch **3353** may be electrically connected to the pressure driving device **3341**. When the first pressing portion **3331** abuts against the door panel **3310** and moves to a preset position (that is, after the outer peripheral wall of the boss **3320** abuts against the inner peripheral wall of the food outlet hole **2021** to a certain extent), the second position switch **3353** generates a second position information, and the pressure driving device **3341** stops the movement and stops the power output according to the second position information. In this embodiment, after the outer peripheral wall of the boss **3320** and the inner peripheral wall of the food outlet hole **2021** reach the desired cooperation position, the pressure driving device **3341** can stop the movement and stop the power output according to the second position information, thereby reducing the power consumption of the pressure driving device **3341**.

(35) In addition, the first position switch **3351** may be electrically connected to the door driving

device **3342**. When the angle between the surface of the door panel **3310** facing the boss **3320** and the plane **P1** perpendicular to the axis **X-X'** of the food outlet hole **2021** is greater than the first preset angle, the first position switch **3351** generates a fourth position information, and the door driving device **3342** drives the door panel **3310** to move away from the food outlet hole **2021** according to the fourth position information. In this embodiment, when the door assembly **3300** is opened to a preset degree at the position in which the door assembly is tightly engaged with the food outlet hole **2021**, an interaction force between the door assembly **3300** and the food outlet hole **2021** is small. At this time, according to the fourth position information, the door driving device **3342** is switched to be available to drive the door panel **3310** to move away from the food outlet hole **2021**, which can save the power output of the pressure driving device **3341** which has higher power. In this embodiment, the waiting time for the switching between the pressure driving device **3341** and the door driving device **3342** is shorter in two different stages (i.e., a stage of releasing the tight cooperation of the door assembly **3300** and a stage of continuing the opening of the door assembly), which is beneficial to improving the opening efficiency of the door assembly **3300**.

(36) In some embodiments, the door assembly **3300** may also include a third position switch **3352**. The third position switch **3352** generates a third position information when the angle between the surface of the door panel **3310** facing the boss **3320** and the plane **P1** perpendicular to the axis **X-X'** of the food outlet hole **2021** is greater than or equal to a second preset angle which is greater than the first preset angle. The third position switch **3352** may be electrically connected to the door driving device **3342**. When the angle between the surface of the door panel **3310** facing the boss **3320** and the plane **P1** perpendicular to the axis **X-X'** of the food outlet hole **2021** is greater than or equal to the second preset angle, the door driving device **3342** stops power output according to the third door position information. In this embodiment, the door driving device **3342** can stop the power output after the door panel **3310** is opened to a required large degree, thereby reducing the energy consumption of the door driving device **3342**.

(37) Referring to FIG. 4, a peripheral wall of the second rotating shaft **3312** may be provided with a first bump **3313** configured to trigger the first position switch **3351** and the third position switch **3352**. The door panel **3310**, the first bump **3313**, and the second rotating shaft **3312** may be formed in one piece by a process such as injection molding or metal casting. When the angle between the surface of the door panel **3310** facing the boss **3320** and the plane **P1** perpendicular to the axis **X-X'** of the food outlet hole **2021** is less than or equal to the first preset angle, the first bump **3313** abuts against the first position switch **3351**, which in turn generates the first position information. When the angle between the surface of the door panel **3310** facing the boss **3320** and the plane **P1** perpendicular to the axis **X-X'** of the food outlet hole **2021** is greater than the first preset angle, the first bump **3313** disengages from the first position switch **3351**, which in turn generates the fourth position information. Thanks to the first position switch **3351**, the occupied installation space can be reduced and the structural compactness of the feeder can be improved. The installation space occupied by the third position switch **3352** is also small, which is also beneficial to reduce the volume of the feeder.

(38) In addition, a second bump **3335** suitable for triggering the second position switch **3353** is provided on a peripheral wall of the first rotating shaft **3334**. The first rotating shaft **3334** and the second bump **3335** may be formed in one piece by a process such as injection molding or metal casting. When the first pressing portion **3331** abuts against the door panel **3310** and moves to the preset position, the second bump **3335** abuts against the second position switch **3353**, which in turn generates the second position information. Thanks to the second position switch **3353**, the occupied installation space can be reduced and the structural compactness of the feeder can be improved.

(39) Referring to FIG. 3, the feeder may also include a vacuum pump **3361**. The feeder also includes a first through hole **3371** in communication with the accommodating chamber **2001**, and the vacuum pump **3361** is in communication with the first through hole **3371** through an exhaust

pipe **3381**. The second position switch **3353** is electrically connected to the vacuum pump **3361** which is actuated according to the second position information. In this embodiment, since the second position information is generated when the first pressing portion **3331** abuts against the door panel **3310** and moves to the preset position, the vacuum pump **3361** can be activated and perform the vacuumizing operation after the door assembly **3300** is closed, thereby reducing the waiting time for the vacuumizing operation and improving the vacuumizing efficiency.

(40) The feeder may also include a negative pressure switch **3363** which may be in the form of an electronic pressure switch or the like. The feeder also includes a third through hole **3373** in communication with the accommodating chamber **2001**, and the negative pressure switch **3363** is in communication with the third through hole **3373** through a negative pressure pipe **3383**. The negative pressure switch **3363** may be electrically connected to the vacuum pump **3361**. When a vacuum degree in the accommodating chamber **2001** is greater than or equal to a first preset vacuum degree, the negative pressure switch **3363** outputs a first pressure signal. The vacuum pump **3361** is stopped according to the first pressure signal, thereby reducing the power loss of the vacuum pump **3361**.

(41) The feeder may also include a solenoid valve **3362**, and the feeder further includes a second through hole **3372** in communication with the accommodating chamber **2001**. The solenoid valve **3362** is in communication with the second through hole **3372** through an intake pipe **3382**. The solenoid valve **3362** is configured to allow or prevent the communication between the accommodating chamber **2001** and the outside, so that the pressure of the accommodating chamber **2001** under the negative pressure can be relieved or maintained by the solenoid valve **3362**. The negative pressure switch **3363** may be electrically connected to the pressure driving device **3341**. When the vacuum degree in the accommodating chamber **2001** is less than or equal to a second preset vacuum degree lower than the first preset vacuum degree, the negative pressure switch **3363** outputs a second pressure signal. The pressure driving device **3341** drives the second pressing portion to abut against the door panel **3310** according to a door opening instruction and the second pressure signal, so as to tilt the door panel **3310** and facilitate the subsequent opening of the door panel **3310**. Since the pressure driving device **3341** drives the second pressing portion to abut against the door panel **3310** according to the door opening instruction and the second pressure signal, the time of door opening action can be reduced, a unexpected opening can also be avoided by combining the door opening instruction and the second pressure signal (for example, when the accommodating chamber **2001** is damaged and the vacuum degree becomes to be less than or equal to the second preset vacuum degree due to the air leakage, the unexpected opening of the door assembly **3300** in the absence of the door opening instruction can be avoided).

(42) The feeder includes the barrel **2000** and the vacuum pump **3361**. The barrel **2000** is mounted at the mount **3510**, the barrel **2000** defines the accommodating chamber **2001** for storing food, and the food outlet hole is in communication with the accommodating chamber **2001**. The vacuum pump **3361** is in communication with the accommodating chamber **2001**.

(43) The feeder may also include an electronic control board. The vacuum pump **3361**, the negative pressure switch **3363**, the solenoid valve **3362**, the first position switch **3351**, the second position switch **3353**, the third position switch **3352**, the pressure driving device **3341** and the door driving device **3342** are respectively electrically connected to the electric control board, thereby reducing the total length of the connecting wires of the feeder by the electric control board and improving the space utilization rate of the feeder.

(44) In addition, the door assembly **3300** includes the first position switch **3351** which generates the first position information when the angle between the door panel **3310** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** is less than or equal to the first preset angle. The feeder can be controlled by the following operations of:

(45) acquiring a door closing instruction and controlling the door panel **3310** to move in the direction towards the food outlet hole **2021** (for example, the door driving device **3342** drives the

second rotating shaft **3312** into rotation, thereby moving the door panel **3310** in the direction towards the food outlet hole **2021**); and

(46) controlling the first pressing portion **3331** to exert a pressure onto the door panel **3310** in response to the first position information (for example, the pressure driving device **3341** drives the first pressing portion **3331** to exert the pressure onto the door panel **3310**).

(47) In this embodiment, in the closing process of the door panel **3310**, after the door panel **3310** pivots to the position near the food outlet hole **2021** (i.e., when the angle between the door panel **3310** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** is less than or equal to the first preset angle), the first pressing portion **3331** applies a pressure to the door panel **3310**. This is beneficial to bring the door panel to the preset cooperating position with the food outlet hole **2021**, beneficial to improve the abutment tightness between the door panel **3310** and the food outlet hole **2021**, and beneficial to improve the sealing stability of the door assembly **3300**.

(48) In this embodiment, the door panel **3310** is provided with the boss **3320**, and the outer peripheral wall of the boss **3320** is configured to abut against the inner peripheral wall of the food outlet hole **2021**. The angle between the door panel **3310** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** can be an angle between the surface of the door panel **3310** facing the boss **3320** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021**. The door assembly **3300** also includes the second position switch **3353** which generates the second position information when the first pressing portion **3331** reaches the preset position. The feeder can also be controlled by the following operation of:

(49) after the operation of “controlling the first pressing portion to exert the pressure onto the door panel in response to the first position information”, controlling the first pressing portion **3331** to stop moving in response to the second position information (for example, the driving of the first pressing portion **3331** is stopped by stopping the pressure driving device **3341**).

(50) In this embodiment, during the closing of the door panel **3310**, the movement of the first pressing portion **3331** is stopped after the first pressing portion **3331** exerts the pressure to the door panel **3310** to cause the door panel **3310** to abut against the food outlet hole **2021**, which can reduce the loss and interference of the elements and enhance the stability of the device.

(51) In some embodiments, the pressing member also includes the second pressing portion which may exert the pressure onto the door panel **3310** to increase the gap between the door panel **3310** and the food outlet hole **2021**. The door assembly **3300** includes the third position switch **3352**. When the angle between the door panel **3310** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** is greater than or equal to the second preset angle, the third position switch **3352** generates the third position information, in which the second preset angle is greater than the first preset angle. The feeder can also be controlled by the following operations of:

(52) acquiring the door opening instruction and controlling the second pressing portion to exert the pressure onto the door panel **3310** (for example, the pressure driving device **3341** drives the second pressing portion to exert the pressure onto the door panel **3310** to increase the gap between the door panel **3310** and the food outlet hole **2021**);

(53) controlling the door panel **3310** to move in the direction away from the food outlet hole **2021** (for example, the door driving device **3342** drives the second rotating shaft **3312** into rotation, thereby moving the door panel **3310** in the direction away from the food outlet hole **2021**); and

(54) in response to the third position information, controlling the door panel **3310** to stop moving (for example, by stopping the aforementioned door driving device **3342**).

(55) In this embodiment, during the opening of the door panel **3310**, the second pressing portion exerts the pressure onto the door panel **3310** to tilt the door panel **3310**, so as to facilitate the subsequent rotation and open of the door panel **3310**.

(56) In particular, the feeder is provided with the vacuum pump **3361**, and when vacuumizing the food accommodating chamber by the vacuum pump **3361** after the door panel **3310** is closed, the second pressing portion will greatly help the opening of the door panel **3310**. At this time, the food

accommodating chamber is in a negative pressure state, and it is difficult to open the door panel. In this embodiment, a downward pressure is exerted onto the door panel **3310** by the second pressing portion, which is beneficial to reduce the working difficulty of the door driving device **3342**.

(57) It should be understood that, even if the feeder does not include the vacuum device, sometimes the negative pressure will be formed in the sealed food accommodating chamber, which makes it difficult to open the door panel. In this case, the structure of the present embodiment can also be used to reduce the working difficulty of the door driving device and improve the stability and efficiency.

(58) In this embodiment, the door panel **3310** is provided with the boss **3320**, and the outer peripheral wall of the boss **3320** is configured to abut against the inner peripheral wall of the food outlet hole **2021**. The angle between the door panel **3310** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** can be an angle between the surface of the door panel **3310** facing the boss **3320** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021**.

(59) When closing the door assembly **3300**, the feeder can control the door driving device **3342** to drive the door panel **3310** to close from a position with a large opening degree (for example, a position in which the angle between the door panel **3310** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** is greater than or equal to the second preset angle, and the first bump **3313** abuts against the third position switch **3352**) to a position with a small opening degree (for example, a position in which the angle between the door panel **3310** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** is less than or equal to the first preset angle, and the first bump **3313** abuts against the first position switch **3351**).

(60) When the door panel **3310** is closed to the position with the small opening degree, the first position switch **3351** generates the first position information, and the pressure driving device **3341** drives the first pressing portion **3331** to abut against the door panel **3310** according to the first position information, so that the opening degree of the door panel **3310** is further reduced and the door assembly **3300** is placed in the abutment position.

(61) It should be noted that the door panel **3310** is provided with the boss **3320**, and the outer peripheral wall of the boss **3320** is configured to abut the inner peripheral wall of the food outlet hole **2021**. The abutment position of the door assembly **3300** corresponds to the position in which the outer peripheral wall of the boss **3320** abuts against the inner peripheral wall of the food outlet hole **2021**.

(62) After the door assembly **3300** is at the abutment position (for example, corresponding to the position in which the first pressing portion **3331** abuts against the door panel **3310** and moves to the preset position, and the second bump **3335** abuts against the second position switch **3353**), the second position switch **3353** generates the second position information, and the pressure driving device **3341** stops the power output according to the second position information, to complete the closing of the door assembly **3300**.

(63) After the closing of the door assembly **3300**, the accommodating chamber **2001** can be vacuumed according to the above-mentioned second position information (for example, the vacuum pump **3361** is activated to vacuum the accommodating chamber), while the solenoid valve **3362** can isolate the accommodating chamber **2001** from the outside according to the second position information. When the vacuum degree in the accommodating chamber **2001** is greater than or equal to the first preset vacuum degree, the negative pressure switch **3363** outputs a first pressure signal, and the vacuum pump **3361** is stopped according to the first pressure signal, to complete the vacuuming operation for the accommodating chamber **2001**.

(64) When the door assembly **3300** needs to be opened, the accommodating chamber **2001** can be communicated with the outside according to the door opening instruction (for example, by switching the above-mentioned solenoid valve **3362** to an open state), and the negative pressure in the accommodating chamber **2001** can be relieved. When the vacuum degree in the accommodating chamber **2001** is less than or equal to the second preset vacuum degree (the second preset vacuum

degree is less than the first preset vacuum degree), that is, when the pressure relief is completed or substantially completed, the negative pressure switch **3363** outputs the second pressure signal. The pressure driving device **3341** drives the second pressing portion to abut against the door panel **3310** according to the door opening instruction and the second pressure signal, so as to tilt the door panel **3310**.

(65) After the door panel **3310** is tilted to present a certain opening degree (in this embodiment, for example, to the position in which the angle between the surface of door panel **3310** facing the boss **3320** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** is greater than the first preset angle, and the first bump **3313** disengages from the first position switch **3351**), the first position switch **3351** outputs the fourth position information, and the door driving device **3342** drives the door panel **3310** to move away from the food outlet hole **2021** according to the fourth position information, so as to continue to increase the opening degree of the door panel **3310**.

(66) After the opening degree of the door panel **3310** is increased to a desired position (in this embodiment, for example, corresponding to the position in which the angle between the surface of door panel **3310** facing the boss **3320** and the plane P1 perpendicular to the axis X-X' of the food outlet hole **2021** is greater than or equal to the second preset angle, and the first bump **3313** abuts against the third position switch **3352**), the third position switch **3352** generates the third position information, the door driving device **3342** stops the power output according to the third position information, and the opening of the door assembly **3300** is completed.

(67) What described is merely preferable embodiments of the disclosure, and is not intended to limit the scope of protection of the disclosure. All equivalent structures made using the specification and accompanying drawings of the disclosure, or direct or indirect applications of the disclosure to other related technical fields should be included within the scope of protection of the disclosure.

Claims

1. A feeder, comprising: a mount provided with a food outlet hole; and a door assembly comprising: a door panel configured to close or open the food outlet hole, wherein the door panel comprises a movable side and a fixed side, and wherein the movable side of the door panel is higher in a longitudinal direction than the fixed side or is flush with the fixed side in the longitudinal direction; a pressing member rotatably mounted to the mount, the pressing member comprising a first pressing portion and a first rotating shaft rotatably connected to the mount, the first pressing portion being configured to act on the door panel to exert a pressure onto the door panel so as to reduce a gap between the door panel and the food outlet hole; and a second rotating shaft, wherein the fixed side of the door panel is fixedly connected to the second rotating shaft, the second rotating shaft is rotatably connected to the mount, and the movable side of the door panel is rotatable with respect to the mount via the second rotating shaft; wherein the pressing member further comprises a second pressing portion, the second pressing portion being configured to act on the door panel to exert a pressure onto the door panel so as to increase a gap between the door panel and the food outlet hole.
2. The feeder according to claim 1, wherein the door panel is provided with a boss, an outer peripheral wall of the boss being configured to abut against an inner peripheral wall of the food outlet hole.
3. The feeder according to claim 2, wherein the first pressing portion and the second pressing portion are arranged at an outer peripheral wall of the first rotating shaft, the first pressing portion and the second pressing portion are arranged at intervals in a circumferential direction of the first rotating shaft.
4. The feeder according to claim 3, wherein the first pressing portion comprises a first batten, the first batten being in a shape of a rectangle extending in an axial direction of the first rotating shaft,

the first batten being configured to abut against a surface of the door panel away from the boss in order to lift the door panel.

5. The feeder according to claim 4, wherein the second pressing portion comprises a second batten, the second batten being L-shaped, one end of the L-shape being connected to the first rotating shaft and the other end of the L-shape extending in a direction away from the first rotating shaft, wherein the second batten is configured to abut against a surface of the door panel adjacent to the boss to cause the door panel to sink.

6. The feeder according to claim 3, wherein the first rotating shaft and the second rotating shaft are arranged on opposite sides of the food outlet hole, the door assembly further comprising a pressure driving device which drives the pressing member into rotation through the first rotating shaft, the door assembly further comprising a door driving device which drives the door panel into rotation through the second rotating shaft.

7. The feeder according to claim 3, wherein the boss comprises a body and an elastic cap arranged around the body, and wherein an outer peripheral wall of the elastic cap is configured to abut against the inner peripheral wall of the food outlet hole.

8. The feeder according to claim 7, wherein the outer peripheral wall of the elastic cap is provided with an elastic annular plate extending in a circumferential direction of the elastic cap.

9. The feeder according to claim 7, wherein the outer peripheral wall of the elastic cap is inclined, and a cross-sectional area of a top of the elastic cap is less than a cross-sectional area of a bottom of the elastic cap.

10. The feeder according to claim 7, wherein the door panel is further provided with a connecting through hole, the bottom of the elastic cap being provided with a connecting post and an abutment block arranged on a side of the door panel away from the elastic cap, the connecting post passing through the connecting through hole and being connected to the abutment block which abuts against the door panel.

11. The feeder according to claim 7, wherein the feeder comprises a barrel mounted at the mount and a vacuum pump, the barrel defining an accommodating chamber for storing food, wherein the food outlet hole and the vacuum pump are in communication with the accommodating chamber.
