

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414544
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Crabtree, III; Richard

Pet exercise ball containment device

Abstract

The invention is directed to a pet exercise ball containment device comprising a receptacle having a substantially concave-shaped surface; three or more bearings attached to the substantially concave-shaped surface and arranged to receive the pet exercise ball; and one or more base components arranged on the receptacle to stabilize the pet exercise ball containment device. In some embodiments, the device can comprise an absorbent pad to collect waste from the pet. In some embodiments, the device can comprise an opening in the receptacle that allows waste to be emitted from the pet to a removable tray below the opening.

Inventors:	Crabtree, III; Richard (Westerville, OH)
Applicant:	Crabtree, III; Richard (Westerville, OH)
Family ID:	1000008822083
Appl. No.:	18/502936
Filed:	November 06, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250143264 A1	May. 08, 2025

Publication Classification

Int. Cl.:	A01K15/02 (20060101)
U.S. Cl.:	
CPC	A01K15/027 (20130101);

Field of Classification Search

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8161913	12/2011	Barfield	119/703	A01K 15/027
D670040	12/2011	Aboujaoude	N/A	N/A
2005/0120972	12/2004	Aboujaoude et al.	N/A	N/A
2014/0326194	12/2013	Waswo et al.	N/A	N/A
2015/0237830	12/2014	Sternal et al.	N/A	N/A
2020/0305393	12/2019	Ho	N/A	N/A
2021/0282372	12/2020	Haber et al.	N/A	N/A
2022/0132805	12/2021	Haber et al.	N/A	N/A

OTHER PUBLICATIONS

Alley Cats Bowling Ball Cup Stand with Ball Bearing Spinner Holder,
<https://alleycatsproducts.com/product/b08bcfr47y/>, accessed Oct. 30, 2023 (2 pages). cited by applicant
Bowling Ball Spinner and Cleaning Stand, Etsy, <https://www.etsy.com/uk/listing/1283369242/bowling-ball-spinner-and-cleaning-stand>, accessed Oct. 30, 2023 (5 pages). cited by applicant
PSA: Clean Your Balls People!,
https://www.reddit.com/r/Bowling/comments/yx8tay/psa_clean_your_balls_people_i_feel_this_is_highly/?rdt=56975, accessed Oct. 30, 2023 (8 pages). cited by applicant
SpinBusterz Bowling Ball Cup Spinner Sand Polish Clean Maintain Abralon,
<https://www.ebay.com/itm/255978082837>, accessed Oct. 30, 2023 (6 pages). cited by applicant

Primary Examiner: Wong; Jessica B

Attorney, Agent or Firm: Wilmer Cutler Pickering Hale and Dorr LLP

Background/Summary

FIELD OF THE INVENTION

(1) The present invention relates to pet exercise toys. More particularly, the present invention relates to pet exercise ball containment devices and methods of providing a containment device for a pet exercise ball.

BACKGROUND OF THE INVENTION

(2) Many small pets, such as hamsters, utilize various devices as a means for exercising and playing. Exercise wheels, for example, provide small pets with a means for continuously running, but do not provide them with a protective self-containing structure and can be noisy. In contrast, ball containers, such as pet exercise balls, allow small pets to be safely secured in a structure while they exercise and play. However, uncontained pet exercise balls pose many issues for the pet and its owner. If not contained, pet exercise balls can lead to the pet roaming freely about a home. This can be dangerous for the pet which can be kicked around or can fall down a flight of stairs. This can also be dangerous for other animals or people who can trip over the pet exercise ball. Pet owners must also ensure an area is clear of obstacles so a pet in an uncontained pet exercise ball is able to roam freely. An additional issue is the pet's waste can escape through holes in the uncontained pet exercise ball to the floor, causing a mess. Therefore, there is a need for a pet exercise ball containment device that

provides a protective enclosure for the small pet, contains the enclosure itself in a single and safe location, and allows for the entrapment of the pet's waste.

SUMMARY OF THE INVENTION

(3) The present disclosure is directed to pet exercise ball containment devices. The following embodiments recite non-limiting permutations of combinations of features of the inventions described. Other permutations of combinations of features are also contemplated and/or described throughout the disclosure.

(4) In some embodiments, a pet exercise ball containment device is provided, comprising a receptacle having a substantially concave-shaped surface; three or more bearings attached to the substantially concave-shaped surface and arranged to receive the pet exercise ball; and one or more base components arranged on the receptacle to stabilize the pet exercise ball containment device. The receptacle can be a bowl and the substantially concave-shaped surface can be the interior of the bowl. In some embodiments, the substantially concave-shaped surface is substantially between 4 and 6 inches in diameter. The bearings can be spaced equidistant from each other on the substantially concave-shaped surface. In some embodiments, the bearings can have a diameter of at least 0.25 inches. The bearings of the pet exercise ball containment device can include a ball housed in a unit which can function as the base component.

(5) In some embodiments, the pet exercise ball containment device can include a substantially concave-shaped surface that further comprises an absorbent pad to collect waste from the pet. In some embodiments, the receptacle can comprise an opening that allows waste to be emitted from the pet to a removable tray below the opening. The removable tray can be placed on a shelf below the opening and, in some embodiments, an absorbent pad can be placed on the removable tray.

(6) In some embodiments, a method of providing a pet exercise ball containment device is provided, the method comprising providing a receptacle having a substantially concave-shaped surface; attaching three or more bearings to the substantially concave-shaped surface and arranging them to receive the pet exercise ball; and providing one or more base components arranged on the receptacle to stabilize the pet exercise ball containment device. In some embodiments, the method can include the step of providing a receptacle having a substantially concave-shaped surface further includes providing the receptacle is a bowl and the substantially concave-shaped surface is the interior of the bowl. The step of providing a substantially concave-shaped surface can further include providing the substantially concave-shaped surface is substantially between 4 and 6 inches in diameter. In some embodiments, the step of providing bearings can further include spacing the bearings equidistant from each other and/or providing the bearing have a diameter of at least 0.25 inches. The step of providing bearings can further include providing the bearings include a ball housed in a unit which can function as the base component.

(7) In some embodiments, the step of providing a substantially concave-shaped surface can further comprise providing an absorbent pad on the substantially concave-shaped surface to collect waste from the pet. The step of providing a receptacle can further comprise providing an opening in the receptacle that allows waste to be emitted from the pet to a removable tray below the opening. In some embodiments, the method of providing a pet exercise ball containment device can further comprise placing the removable tray on a shelf below the opening in the receptacle. The method can also include providing an absorbent pad on the removable tray.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1A is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.

(2) FIG. 1B is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.

- (3) FIG. 2 is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.
- (4) FIG. 3 is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.
- (5) FIG. 4 is a top view of an exemplary embodiment of a pet exercise ball containment device described herein.
- (6) FIG. 5 is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.
- (7) FIG. 6 is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.
- (8) FIG. 7 is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.
- (9) FIG. 8 is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.
- (10) FIG. 9 is a front view of an exemplary embodiment of a pet exercise ball containment device described herein.

DETAILED DESCRIPTION OF THE INVENTION

- (11) In the following description, numerous specific details are set forth regarding the structures, systems, and methods of the disclosed subject matter and the environment in which such structures, systems, and methods may operate, etc., in order to provide a thorough understanding of the disclosed subject matter. It will be apparent to one skilled in the art, however, that the disclosed subject matter may be practiced without such specific details, and that certain features, which are well known in the art, are not described in detail in order to avoid complication of the disclosed subject matter. In addition, it will be understood that the examples provided below are exemplary, and that it is contemplated that there are other structures, systems, and methods that are within the scope of the disclosed subject matter.
- (12) The disclosed structures, systems, and methods can provide a stable containment device for a pet exercise ball to allow the pet exercise ball to remain in one location while still allowing the pet to freely move around inside the rotating ball.
- (13) FIGS. 1A-1B show a pet exercise ball containment device **100**, according to various embodiments described herein. The pet exercise ball containment device **100** comprises a receptacle **110** having a substantially concave-shaped surface **120**, three or more bearings **130a-130c** attached to the substantially concave-shaped surface **120** and arranged to receive the pet exercise ball **150**, such as a hamster ball, and one or more base components **140a-140b** arranged on the receptacle **110** to stabilize the pet exercise ball containment device **100**. The pet exercise ball **150** includes small holes to allow the pet to breathe while preventing the pet from getting its hands and feet stuck in the holes.
- (14) The receptacle **110** can be constructed in a variety of shapes. For example, the receptacle **110** can be substantially in the shape of a hemisphere, sphere, ellipse, cylinder, polyhedron, or any other three-dimensional shapes known to those in the art, and any combination thereof. In one embodiment, for example, the receptacle **110** is in the shape of a bowl.
- (15) The receptacle **110** includes a substantially concave-shaped surface **120**. In certain embodiments, the substantially concave-shaped surface **120** can be the interior of a bowl. The substantially concave-shaped surface **120** is sized to receive a pet exercise ball **150**. In certain embodiments, the diameter of the substantially concave-shaped surface **120** can be substantially between 4 and 6 inches. In an example embodiment, the diameter of the substantially concave-shaped surface **120** can be 5 inches. In certain embodiments, the substantially concave-shaped surface **120** can be constructed from the receptacle **110** itself. In certain embodiments, the substantially concave-shaped surface **120** can be a separate structure attached to the receptacle **110**.
- (16) The receptacle **110** can include one or more base components **140a-140b** arranged on the receptacle **110** to stabilize the pet exercise ball containment device **100**. In certain embodiments, the pet exercise ball containment device **100** can contain two, three, four, five, or more base components

140. The one or more base components **140a-140b** can protrude from receptacle **110** and make contact with a surface **160**, such as a horizontal tabletop or a floor, thereby stabilizing the pet exercise ball containment device **100**. The one or more base components **140a-140b** can be constructed in a variety of two-dimensional or three-dimensional shapes. For example, in certain embodiments, the one or more base components **140a-140b** can be substantially in the shape of a circle, square, rectangle, polygon, sphere, ellipse, cylinder, cube, polyhedron, or any other shapes known to those in the art, and any combination thereof.

(17) In certain embodiments, the one or more base components **140a-140b** can be separate structures attached to the receptacle **110** by known means, such as screws, nails, pegs, glue, tape, insertion, and so on. In one example embodiment, the one or more base components **140a-140b** can be cylindrical structures, as shown in FIGS. **1A-1B**. As shown in FIG. **1B**, for example, one or more base components **140a** and **140b** each protrude from the receptacle **110** and make contact with surface **160**. In certain embodiments, one base component **140a** can be a cuboidal structure, as shown in FIG. **2**. In such embodiments, base component **140a** in FIG. **2** acts as a platform to support and stabilize the device. In certain embodiments, the receptacle **110** can in-and-of-itself include a base component **140a** formed into receptacle **110** that stabilizes the receptacle. For example, base component **140a** can be formed as a substantially flat bottom surface of receptacle **110**, as shown in FIG. **3**, that stabilizes the receptacle when positioned on a horizontal surface, such as a table, shelf, or floor.

(18) The receptacle **110**, the substantially concave-shaped surface **120**, and the one or more base components **140a-140b** can be constructed from any material that is sufficiently rigid and sturdy to support the weight of a small animal. For example, they can be constructed from plastic, metal, steel, ceramic, wood, rubber, a substantially abrasive material, or any other sufficiently rigid and sturdy materials known to those in the art, and any combination thereof. Each of the receptacle **110**, the substantially concave-shaped surface **120**, and the one or more base components **140a-140b** can be constructed from the same or different materials. In one embodiment, the receptacle **110** is formed of plastic in the shape of a bowl. In certain embodiments where the pet exercise ball containment device **100** is comprised of more than one base component **140**, each base component can be constructed from different materials.

(19) In certain embodiments, at least one of the receptacle **110**, the substantially concave-shaped surface **120**, the one or more base components **140a-140b**, and/or the bearings **130a-130c** can be constructed from or filled with materials that provide the pet exercise ball containment device **100** with enough weight to remain stabilized and immobile. For example, the receptacle **110** can be made of a solid metal material or be filled internally with sand to add weight to the pet exercise ball containment device **100**.

(20) The substantially concave-shaped surface **120** includes three or more bearings **130a-130c** attached to the substantially concave-shaped surface **120** and arranged to receive a pet exercise ball **150**. In one embodiment, the pet exercise ball containment device **100** is comprised of three bearings **130a-130c**. In certain embodiments, the bearings **130a-130c** can be at least 0.25 inches in diameter. In certain embodiments, the bearings **130a-130c** can be less than or greater than 0.25 inches in diameter. Using bearings **130a-130c** with a relatively small diameter (e.g., less than 0.25 inches) can require using more than three bearings **130a-130c** to stabilize the pet exercise ball containment device **100**. In certain embodiments, the bearings **130a-130c** can be constructed from plastic, metal, steel, ceramic, wood, or any other sufficiently rigid and sturdy materials known to those in the art, or any combination thereof. In an example embodiment, the bearings **130a-130c** are constructed from metal.

(21) In an example embodiment, the bearings **130a-130c** are spherical balls. In another example embodiment, the bearings **130a-130c** are ball transfer bearings where a ball is housed in a transfer unit. In this embodiment, the ball can be positioned inside of the receptacle **110** while the transfer unit can extend outside of the receptacle **110** to function as a base component **140**. In certain embodiments, the bearings **130a-130c** are attached to the substantially concave-shaped surface **120** by being glued, taped, welded, screwed, nailed, inserted, or any combination thereof, into the

substantially concave-shaped surface **120**.

(22) FIG. **4** shows a top view of an exemplary embodiment of a pet exercise ball containment device **100** described herein. In certain embodiments, the bearings **130a-130c** are spaced equidistant from each other at a distance “d” on the substantially concave-shaped surface **120**, as shown in FIG. **4**. In other embodiments, the bearings **130a-130c** can be positioned at varying distances from each other. In embodiments where more than three bearings **130** are used, those more than three bearings **130** can be positioned with equidistant or varying spacing from each other.

(23) The pet exercise ball containment device **100** can allow for the removal of the pet's waste (e.g., urine, fecal matter, vomit, saliva) through small holes in the pet exercise ball **150** and onto, into, or through the receptacle **110**. As an example, the substantially concave-shaped surface **120** of the receptacle **110** can catch waste which the pet owner can then remove. In an example embodiment, the substantially concave-shaped surface **120** can detach from the receptacle **110** to allow for the easy removal of the pet's waste. Room for the collection of waste is created in a volume between the substantially concave-shaped surface **120** of the receptacle **110** and the top of the bearings **130a-130c**. Bearings **130a-130c** with a larger diameter can be used to create more room for the collection of waste. FIG. **5** shows an example embodiment where the top of the receptacle **110** includes a hollow cavity **170** which would be located below the pet exercise ball **150** to provide more room for the collection of waste in the receptacle **110**. The hollow cavity **170** can include an absorbent pad **180**, described in more detail below. The hollow cavity **170** can also include a removable container to aid in the easy removal of waste. This removable container can be an extension of the substantially concave-shaped surface.

(24) FIG. **6** shows an example embodiment where the substantially concave-shaped surface **120** of the receptacle **110** includes an absorbent pad **180** that can aid in the collection of waste released from the pet exercise ball **150**. Examples of the absorbent pad **180** can be a paper towel, napkin, or cotton pad. The absorbent pad does not need to be attached to the substantially concave-shaped surface **120** of the receptacle **110**. However, the absorbent pad **180** can attach to the substantially concave-shaped surface **120** of the receptacle **110** with adhesive material (e.g., glue, tape, Velcro) or by being pinned or sewn onto the substantially concave-shaped surface **120**.

(25) FIG. **7** shows another example embodiment where the pet exercise ball containment device **100** allows for the removal of the pet's waste. In this embodiment, the bottom of the receptacle **110** includes an opening **190** which allows the pet's waste to escape through the opening **190**. An absorbent pad **180** is placed on a flat surface underneath the opening **190** to collect waste. Room for the collection of waste is created in a volume between the bottom of the receptacle **110** and the one or more base components **140a-140b** on the flat surface. FIG. **8** shows another example embodiment where a removable tray **200** is placed on the flat surface underneath the opening **190** to collect the waste. The removable tray **200** can include a handle **210** to allow the pet owner to easily grab and remove it. The removable tray **200** can contain an absorbent pad **180** to aid in the collection and removal of waste. The removable tray **200** can be flat or have a concave-shaped structure.

(26) The removable tray **200** can be removably attached to the pet exercise ball containment device **100**. FIG. **9** shows an embodiment where a shelf **220** is attached to the base components **140-140b** and is used to hold the removable tray **200** and to position the removable tray **200** below the opening **190** to collect waste. The removable tray **200** can contain an absorbent pad **180** to aid in the collection and removal of waste. The shelf can also only contain an absorbent pad **180**. In an example embodiment, the removable tray **200** is removably attached to the receptacle **110** and configured like a drawer that can collect waste and can slide out of the receptacle **110** to dispose of waste.

(27) In certain embodiments, the pet exercise ball containment device **100** can include light features, such as LED lighting. Light features can be integrated into or onto any component of the pet exercise ball containment device **100**. In an example embodiment, light features are integrated around the perimeter of the substantially concave-shaped surface **120** of the receptacle **110**. In another example embodiment, light features are integrated inside of the receptacle **110** and shines light out of the

receptacle **110** through holes in the receptacle **110** or due to the receptacle **110** being translucent or transparent.

Claims

1. A pet exercise ball containment device, comprising: a receptacle having a substantially concave-shaped surface comprising an absorbent pad arranged to collect waste from a pet; three or more bearings attached to the substantially concave-shaped surface and arranged to receive a pet exercise ball; and one or more base components arranged on the receptacle to stabilize the pet exercise ball containment device.
 2. The pet exercise ball containment device of claim 1, wherein the receptacle is a bowl and the substantially concave-shaped surface is the interior of the bowl.
 3. The pet exercise ball containment device of claim 1, wherein the substantially concave-shaped surface is substantially between 4 and 6 inches in diameter.
 4. The pet exercise ball containment device of claim 1, wherein the bearings are spaced equidistant from each other on the substantially concave-shaped surface.
 5. The pet exercise ball containment device of claim 1, wherein the bearings have a diameter of at least 0.25 inches.
 6. The pet exercise ball containment device of claim 1, wherein the receptacle further comprises an opening that allows waste to be emitted from the pet to a removable tray below the opening.
 7. The pet exercise ball containment device of claim 6, wherein the removable tray is placed on a shelf below the opening.
 8. The pet exercise ball containment device of claim 6, wherein an absorbent pad is placed on the removable tray.
 9. A method of providing a pet exercise ball containment device, comprising: providing a receptacle having a substantially concave-shaped surface comprising an absorbent pad arranged to collect waste from a pet; attaching three or more bearings to the substantially concave-shaped surface and arranging them to receive a pet exercise ball; and providing one or more base components arranged on the receptacle to stabilize the pet exercise ball containment device.
 10. The method of providing a pet exercise ball containment device of claim 9, wherein the step of providing a receptacle having a substantially concave-shaped surface further includes providing the receptacle is a bowl and the substantially concave-shaped surface is the interior of the bowl.
 11. The method of providing a pet exercise ball containment device of claim 9, wherein the step of providing a substantially concave-shaped surface further includes providing the substantially concave-shaped surface is substantially between 4 and 6 inches in diameter.
 12. The method of providing a pet exercise ball containment device of claim 9, wherein the step of providing bearings further includes spacing the bearings equidistant from each other.
 13. The method of providing a pet exercise ball containment device of claim 9, wherein the step of providing bearings further includes providing the bearings have a diameter of at least 0.25 inches.
 14. The method of providing a pet exercise ball containment device of claim 9, wherein the step of providing a receptacle further comprises providing an opening in the receptacle that allows waste to be emitted from the pet to a removable tray below the opening.
 15. The method of providing a pet exercise ball containment device of claim 14, further comprising placing the removable tray on a shelf below the opening in the receptacle.
 16. The method of providing a pet exercise ball containment device of claim 14, further comprising providing an absorbent pad on the removable tray.
-