

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12414781
Kind Code	B2
Date of Patent	September 16, 2025
Inventor(s)	Lee; Hong Jae

Cervical spine endplate preparation apparatus

Abstract

A cervical spine endplate preparation apparatus is provided. To this end, the present invention comprises: a handle part having a handle to be held by hand and a leading rod extending from the handle in the length direction and for guiding to a space inside the spine of a part to be operated on; a rotating shaft part having an adjustment grip, which generates a driving force by means of rotation by hand, and a rotating shaft passing through the inside of the handle and leading rod; and a shaver part which has a case, provided on the leading rod and inserted into the space of the spine, and a shaver installed inside the case and mating with the rotating shaft to rotate by means of the driving force of the adjustment grip, and having a part of a blade exposed to the top of the case and rotating.

Inventors:	Lee; Hong Jae (Daejeon, KR)
Applicant:	THE CATHOLIC UNIVERSITY OF KOREA INDUSTRY-ACADEMIC COOPERATION FOUNDATION (Seoul, KR)
Family ID:	1000008821998
Assignee:	THE CATHOLIC UNIVERSITY OF KOREA INDUSTRY-ACADEMIC COOPERATION FOUNDATION (Seoul, KR)
Appl. No.:	18/265819
Filed (or PCT Filed):	December 01, 2021
PCT No.:	PCT/KR2021/018041
PCT Pub. No.:	WO2022/124691
PCT Pub. Date:	June 16, 2022

Prior Publication Data

Document Identifier	Publication Date
----------------------------	-------------------------

Foreign Application Priority Data

KR

10-2020-0170488

Dec. 08, 2020

Publication Classification**Int. Cl.:** A61B17/16 (20060101); A61F2/46 (20060101); A61F2/30 (20060101)**U.S. Cl.:****CPC** A61B17/1671 (20130101); A61F2/4611 (20130101); A61F2002/30622 (20130101)**Field of Classification Search****CPC:** A61B (17/1671)

References Cited**U.S. PATENT DOCUMENTS**

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6443956	12/2001	Ray	606/80	A61B 17/1671
2004/0092941	12/2003	Jansen	606/84	A61B 17/1671
2005/0149192	12/2004	Zucherman	623/17.11	A61B 17/1671
2014/0121773	12/2013	Patel et al.	N/A	N/A
2015/0182234	12/2014	Mahoney	606/79	A61B 17/1642
2019/0142603	12/2018	Tanaka	N/A	N/A
2019/0343655	12/2018	Bruffey	N/A	A61F 2/4611
2020/0281743	12/2019	Jimenez et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2106023	12/2019	KR	N/A

OTHER PUBLICATIONSInternational Search Report for PCT/KR2021/018041 dated Mar. 21, 2022. cited by applicant

Primary Examiner: Sevilla; Christian A*Attorney, Agent or Firm:* Sughrue Mion, PLLC

Background/Summary**CROSS REFERENCE TO RELATED APPLICATIONS**

(1) This application is a National Stage of International Application No. PCT/KR2021/018041 filed Dec. 1, 2021, claiming priority based on Korean Patent Application No. 10-2020-0170488 filed Dec. 8, 2020, the entire disclosures of which are incorporated herein by reference.

TECHNICAL FIELD

(2) The present invention relates to a cervical spine endplate preparation apparatus.

BACKGROUND ART

(3) Basically, the basic purpose of modern spine surgery is decompression of compressive offending pathology and stability restoration, and spinal fusion surgery for stability restoration is also very important for the cervical spine where motion preservation surgery such as TDR is successfully performed.

(4) The spinal fusion surgery is basically performed in the form of interbody fusion, and proper (fast, micro motion and no deformation) fusion of a vertebral body serving as a fusion bed and an interbody cage is an important factor in determining the patient's prognosis.

(5) Permanent stability is due to bony fusion.

(6) When the permanent stability fails, additional posterior cervical foraminotomy is often performed due to radiculopathy caused by subsidence (subsidence of the cage into the vertebral body).

(7) In the case of the cervical spine, it is important to accurately remove the hypertrophied uncovertebral joint and insert a cage according to the degree of the accurate removal.

(8) In the case of a ceramic cervical cage, especially a bio-ceramic cage that reacts with the bone, for stable fusion of the bone and a ceramic material, the cage needs to be positioned between the bone and the material without micro-movement to be fixed in an optimal position between the vertebrae.

(9) To this end, bone-work should be performed between the vertebrae as much as possible in the same shape as the cage, and this process is called end-plate preparation.

(10) This process uses a drilling and a curette, but excessive decortication may cause subsidence (subsidence into the vertebral body of the cage), and in the opposite case, fusion delay or failure may be caused.

(11) This technology is a surgical apparatus (device) designed to make such end-plate preparation more precise and efficient.

(12) This technology is a technology capable of maximizing a bone fusion function by minimizing the micro-movement that may occur after surgery by performing the end-plate preparation in the same shape as the cage through this apparatus.

(13) The apparatus is widely used in medical treatment, especially in surgery and surgical procedures, and has various shapes depending on the purpose.

(14) A curette with sharp edges is used to curette tissues or bones, and the basic shapes are a double-headed curette and a single-headed curette.

(15) In addition, in the shape of a spoon, the curette has a hollow spoon called a JOMW uterine curette and a SIMS uterine curette as well as a circle and an ellipse.

(16) There are various sizes in the size of a spoon and the length of a handle.

(17) A curette with blunt edges is called a blunt curette. These curettes approach a surgical site at a location of the disc in the spine, and the curette is subjected to a preparation to remove the disc at the location and install an end plate by a rotational force.

DISCLOSURE

Technical Problem

(18) An object of the present invention is to enable an operator to perform an end-plate preparation of a vertebral body in a desired shape by removing a disc and installing an end plate in a narrow space of the spine.

(19) Another object of the present invention is to achieve an exposed height of a shaver by manipulating a shaver part in the end-plate preparation of the vertebral body.

Technical Solution

(20) There is provided a cervical spine endplate preparation apparatus.

(21) To this end, the present invention includes: a handle part having a handle to be held by hand

and a leading rod extending from the handle in the length direction and for guiding to a space inside the spine of a part to be operated on; a rotating shaft part having an adjustment grip, which generates a driving force by means of rotation by hand, and a rotating shaft passing through the inside of the handle and leading rod; and a shaver part which has a case, provided on the leading rod and inserted into the space of the spine, and a shaver installed inside the case and mating with the rotating shaft to rotate by means of the driving force of the adjustment grip, and having a part of a blade exposed to the top of the case and rotating.

Advantageous Effects

(22) According to the present invention, as the rotatable shaver rotates in an axial direction of the entire structure, the blade of the shaver contacts the upper endplate of the internal space of the spine to accurately perform bone-work.

(23) In addition, according to the present invention, the shaft is connected to the shaver part to enable the rotation of the shaver, and a handle is attached to the distal end of the shaft, so that there is an advantage that the operator can arbitrarily operate the blades of the shaver by rotating the handle, and can select the exposure degree of the blade.

Description

DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a plane state diagram to which the present invention is applied.

(2) FIG. 2 is a perspective view of a shaver part of the present invention.

(3) FIG. 3 is a perspective view of a state in which a rotating shaft part and the shaver part of the present invention are separated from each other.

(4) FIG. 4 is a cross-sectional view of FIG. 3 taken along line A-A'.

(5) FIG. 5 is a top cross-sectional view of the shaver part of the present invention.

(6) FIG. 6 is a side state diagram of the shaver part of the present invention.

(7) FIG. 7 is a separated perspective view of an exemplary embodiment of coupling the rotating shaft part and the shaver part of the present invention.

(8) FIG. 8 is a plan view of an exemplary embodiment of a coupling structure formed in a case of the present invention.

(9) FIG. 9 is a cross-sectional view showing a state in which the rotating shaft part and the shaver part of the present invention are coupled with each other in another coupling structure.

(10) FIG. 10 is a perspective view showing a shaver exposure height adjustment structure provided in the case of the present invention.

(11) FIG. 11 is a perspective view of the shaver exposure height adjustment structure provided in the case of the present invention when viewed from the bottom.

(12) FIG. 12 is a top cross-sectional view showing the shaver exposure height adjustment structure provided in the case of the present invention.

(13) FIG. 13 is a state view of the shaver exposure height adjustment structure of the present invention when viewed in a rotating shaft direction.

(14) FIG. 14 is a state view of the shaver exposure height adjustment structure of the present invention when viewed in a length direction from the case side.

(15) FIG. 15 is a side view showing a state in which the exposure height of the shaver is adjusted in the present invention.

MODES OF THE INVENTION

(16) FIG. 1 is a plane state diagram to which the present invention is applied and FIG. 2 is a perspective view of a shaver part of the present invention.

(17) A cervical spine endplate preparation apparatus **100** of the present invention is formed with a handle part **200** having a leading rod **220** that extends in the length direction from a handle **210**

formed to be held by hand and guides to a space inside the spine of a part to be operated on.

(18) In addition, the cervical spine endplate preparation apparatus **100** is formed with a rotating shaft part **300** having an adjustment grip **310**, which generates a driving force by means of rotation by hand, and a rotating shaft **320** passing through the inside of the handle **210** and the leading rod **220**.

(19) A case **410** provided on the leading rod **220** and inserted into the space of the spine to cut the installation site mates with the rotating shaft **320** installed inside the case **410** to rotate by means of the driving force of the adjustment grip **310**.

(20) A shaver part **400** having a part of a blade **421** exposed to the top of the case **410** and rotating is formed to be used for forming an installation site of so-called intervertebral body.

(21) FIG. **3** is a perspective view of a state in which the rotating shaft part and the shaver part of the present invention are separated from each other, and a structure of coupling the handle part **200** held by hand of a medical staff and the shaver part **400** that performs cutting in an operating site of the cervical spine will be described.

(22) A fastening end **230** having a smaller diameter than the leading rod is formed at the end of the leading rod **220** formed in the length direction from one side of the handle **210** of the handle part **200** and a screw part **233** is formed on the outer diameter of the fastening end **230** so that the case **410** of the shaver part **400** is coupled and separated.

(23) The leading rod **220** of the handle part **200** is formed in a hollow tube with a thin diameter to have an assembled state in which the rotating shaft **320** of the rotating shaft part **300** is inserted into the hollow tube at the position of the handle **210** to reach a tip of the leading rod extending from the handle.

(24) The adjustment grip **310** for forming a driving force is installed at one end of the rotating shaft **320** inserted into the hollow tube of the leading rod, and a shaft groove **330** for transmitting the driving force to the shaver part **400** is formed at the other end exposed from the tip of the leading rod **220**.

(25) The shaft groove **33** is preferably formed as a rectangular concave groove for assembly with the shaver part **400** and transmission of the driving force.

(26) The shaver part **400** has the case **410** having a frame shape with a hollow space to be coupled at the fastening end **233** of the leading rod **220**, and a shaver **420** installed inside the case **410** and mating with the rotating shaft **320**.

(27) The case **410** is configured so that for easy and stable insertion into the internal space of the cervical spin, a lower surface becomes horizontal while an upper surface slopes from the rear to the front, a support hole **413a** for installing the shaver **420** is perforated in the front surface of the frame of the case **410**, and a fixing hole **414a** for coupling at the fastening end **230** of the leading rod **220** is perforated in the rear surface thereof.

(28) When the height of a rear surface **414** is greater than that of a front surface **413** forming the case **410**, the inclined shape of the case **410** is formed to the front end from the rear end of a side surface **415** connected between the front surface and the rear surface, and an inclined shape of the side surface **415** is formed in a curved or straight line.

(29) In addition, the support hole **413a** for rotating and supporting the shaver **410** is formed in the front surface **413** of the case **410**, and in the rear surface **414**, the fixing hole **414a** to which the fastening end **230** formed on the leading rod **220** of the handle part **200** is coupled is formed.

(30) In addition, the shaver **420** installed inside the case **410** and rotated by a driving force is formed in a thin plate shape of an appropriate size to be rotated in the space of the case.

(31) The shaver **420** is formed with blades **421** on both sides, and both ends of the blade **421** have a convex arc shape for efficient cutting.

(32) In forming the shaver **420**, a protruding shaft **425** mating with the shaft groove **330** formed at the end of the rotating shaft **320** is formed at one end of the shaver **420** formed in a thin plate shape, and a support shaft **423** is formed at the other end to be assembled to the case **410** to be

rotated and supported.

(33) While the shaver part **400** couples the fixing hole **410a** formed in the case **410** to the fastening end **230** formed at the end of the leading rod **220**, the screw threads and the screw grooves formed in the fastening end **230** and the fixing hole **410a** are mutually fastened to each other.

(34) In using the cervical spine endplate preparation apparatus **100** assembled as described above, while the handle **210** of the handle part **200** is gripped, the shaver part **400** coupled to the tip of the leading rod **220** is moved to the operating site to allow the case **410** to be inserted into the operating site, that is, the space inside the cervical spine through the cutting portion.

(35) At this time, the case **410** of the shaver part **400** to be inserted has an inclined upper end and a horizontal lower end to be easily inserted into the internal space of the cervical spine.

(36) When the entering state of the case **410** into the internal space of the cervical spine is confirmed through an operating device, the adjustment grip **310** of the rotating shaft part **300** provided on one side of the handle **210** is operated by the other hand.

(37) When the adjustment grip **310** is operated, the rotating shaft **320** rotates inside the handle **210** of the handle part **200**, and at this time, since the rotation is transferred to the shaver **420** of the shaver part **400** installed in the case **410** coupled to the fastening end **230**, the disc and the installation site are cut by a rotational motion in the cervical spine space.

(38) After the installation site is cut, a separate intervertebral body is inserted into the corresponding space.

(39) In the cutting state of the shaver **420** in the case **410**, while the front surface **413** is formed at a height lower than the rear surface **414** as shown in FIG. 6, the shaver **420** is installed eccentrically upward in the case **410** as shown in FIG. 4 so that the blades **421** at both ends are partially exposed only to the inclined upper end of the case **410** when rotating the shaver **420**.

(40) As such, while the shaver **420** is partially exposed to the upper end of the case **410** of the shaver part **400**, the rotation may make precisely and smoothly the endplate preparation for installing the end plate of the body in the internal space of the spine where the work space is narrow.

(41) As described above, since the endplate preparation for installing the end plate of the body in the internal space of the spine is precisely performed, in order to improve the preparation efficiency, the size of the shaver part **400** coupled to the fastening end **230** is formed in stages in the form of 3 mm, 4 mm, 5 mm, and 6 mm to perform cervical spine surgery while selectively replacing the shaver part **400** with a size suitable for the preparation form.

(42) In order to easily and safely couple the fastening end **230** and the case **410** of the shaver part **400**, the screw part **233** is formed on the fastening end **230**, and the screw groove **414a** is formed in the fixing hole **414a** perforated in the rear surface **414** of the case **410**, so as to be coupled and separated in the form of a screw.

Exemplary Embodiment 1

(43) The coupling and separation of the rotating shaft part **300** and the shaver part **400** may be configured as an exemplary embodiment in an insertion fastening method rather than a screw fastening method.

(44) An exemplary embodiment of the insertion fastening method shows a separation state for the coupling of the rotating shaft part and the shaver part of FIG. 7 and a plan state of the coupling structure formed in the case of FIG. 8.

(45) The cervical spine endplate preparation apparatus **100** of the present invention has a circular protrusion **235** formed in the rotating shaft part **300** and the shaver part **400** and protruding from the fastening end **230** provided in the leading rod **220** of the handle part **200** in the insertion fastening method, and a locking groove **417** for inserting the circular protrusion **235**, guiding the coupling, and locking in the fixing hole **414a** formed in the case **410** of the shaver part **400**.

(46) In the insertion fastening method formed as described above, while coupling the fixing hole **414a** formed in the case **410** of the shaver part **400** to the fastening end **230** of the leading rod **220**,

the circular protrusion **235** protruding from the fastening end **230** is inserted and twisted into the lock groove **417** formed in the fixing hole **414a** of the case **410**.

(47) The circular protrusion **235** is inserted and guided into the lock groove **417** and locked to the lock groove **417**, so that the insertion-guided locking operation of the circular protrusion **235** and the lock groove **417** may easily replace the shaver part **400** rather than the screw part and maintain a stable installation state after replacing.

Exemplary Embodiment 2

(48) Another exemplary embodiment of the rotating shaft part **300** and the shaver part **400** may be configured in a slider adjustment method other than the insertion fastening method.

(49) In the present invention, another slider adjustment method for the rotating shaft part **300** and the shaver part **400** will be illustrated in detail in FIGS. **10** to **15**.

(50) The shaver part **400** includes first and second slide holes **430** and **440** formed by cutting the front surface **413** and the rear surface **414** of the case **410**, and is assembled in the first and second slide holes **430** and **440**.

(51) The shaver part **400** consists of first and second blocks **432** and **442** in which the leading rod **220** and the shaver **420** are installed, a through hole **452** perforated from the lower surface of the case **410**, and an adjustment screw **450** inserted into the through hole **452** and screwed to the second block **442**.

(52) The shaver part **400** is formed with scales **520** on the front surface **413** and the rear surface **414** of the case **410** where the first and second slide holes **430** and **440** are formed. In addition, the scales **520** are also formed on the first and second blocks **432** and **442** so that the protruding heights of the first and second blocks **432** and **442** are selectively controlled at the upper end of the case **410**.

(53) According to Exemplary Embodiment, in the endplate preparation for installing the end plate of the body in the internal space of the cervical spine where the preparation space is narrow, the first block **432** and the second block **442** are moved in the first slide hole **430** and the second slide hole **440** by adjusting the adjustment screw **450**.

(54) Since the position of the shaver **420** is adjusted to the height exposed to the upper end in the space **411** of the case **410**, the replacement of the shaver part **400** is not required.

(55) Moving scales **520** are formed in the first block **432** and the second block **42** that are moved by the adjustment of the adjustment screw **450**, and corresponding reference scales **500** are also formed around the first slide hole **430** of the front surface **413** and the second slide hole **440** of the rear surface **414** of the case **410**. Accordingly, it is possible to set the protruding height of the block, that is, the exposure height of the shaver **420**, which can select the amount of cutting, according to a surgical situation.

Claims

1. A cervical spine endplate preparation apparatus comprising: a handle part having a handle to be held by hand and a leading rod extending from the handle in a length direction and for guiding to a space inside the spine of a part to be operated on; a rotating shaft part having an adjustment grip, which generates a driving force by means of rotation by hand, and a rotating shaft passing through an inside of the handle and leading rod; and a shaver part which has a case, provided on the leading rod and capable of being inserted into the space of the spine, and a shaver installed inside the case and mating with the rotating shaft to rotate by means of the driving force of the adjustment grip, and the shaver having a part of a blade exposed to a top of the case, the shaver being configured to rotate.

2. The cervical spine endplate preparation apparatus of claim 1, wherein in the handle part, a fastening end having a smaller diameter than the leading rod is formed at an end of the leading rod and threads are formed on an outer diameter of the fastening end.

3. The cervical spine endplate preparation apparatus of claim 1, wherein: the rotating shaft is capable of being inserted to a tip of the leading rod through the handle; the rotating shaft part includes an adjustment grip formed at one end of the rotating shaft to form a driving force on the handle part; and the rotating shaft part includes a shaft groove formed at an end of the rotating shaft capable of being exposed at the tip of the leading rod, the shaft groove being configured to be coupled to and to be separated from the shaver part.
 4. The cervical spine endplate preparation apparatus of claim 1, wherein the shaver part includes the case having a frame with a hollow space, wherein the shaver part is capable of being to be detached from the leading rod, wherein a lower surface of the case is horizontal while an upper surface of the case is inclined from the rear to the front, wherein a support hole for the shaver is perforated in a front surface of the frame, and a fixing hole for the leading rod is perforated in a rear surface of the frame.
 5. The cervical spine endplate preparation apparatus of claim 1, wherein the shaver is formed in a thin plate shape in an appropriate size to be rotated in a space of the case, wherein a protruding shaft of the shaver capable of mating with a shaft groove of the rotating shaft is formed at one end of the shaver, and a support shaft is formed at the other end of the shaver to be rotated and supported on the case, and wherein blades are formed on both sides of the shaver, each blade having a convex arc shape.
 6. The cervical spine endplate preparation apparatus of claim 1, wherein the leading rod of the handle part includes: a circular protrusion formed on a fastening end of the leading rod, and a lock groove is formed on a fixing hole formed in the case of the shaver part to be inserted, coupled, and locked to the circular protrusion.
 7. The cervical spine endplate preparation apparatus of claim 1, wherein the shaver installed in the case is capable of being rotated while a convex portion of the blade is exposed to an inclined upper end of the case.
 8. The cervical spine endplate preparation apparatus of claim 1, wherein the shaver part includes: first and second slide holes formed in a front surface and a rear surface of the case, first and second blocks assembled with the first and second slide holes, the blocks being capable of being installed with the leading rod and the blade, a through hole perforated from a lower surface of the case, and an adjustment screw capable of being inserted into the through hole to be screwed to one of the blocks.
 9. The cervical spine endplate preparation apparatus of claim 8, wherein the shaver part has scales formed on a front surface and a rear surface of the case where the first and second slide holes are formed, and scales are formed on the first and second blocks so that protruding heights of the blocks can be selectively controlled.
-