

**Safety Data Sheet** 

BB9216 Ceramic Prep Solution

#### Section 1. Product and Company Identification

BB9216 Ceramic Prep Solution **Product Identifier** 

Product Use Description:

Thin clear bright blue liquid with a glycol / isopropanol odor for use as a final

**Page** 

surface cleaner prior to coating application

Manufacturer or suppliers' details

Babes Boat Products Emergency Number: 800-255-3924 20943 Cabot Blvd Customer Service: 510-732-2628 Hayward CA 94545 Business Fax: 510-732-2632

#### Section 2. Hazards Identification

**GHS Classification** 

Flammable Liquids: Category 4 Skin Irritation: Category 2 Eve Irritation: Category 2A

#### **GHS Label Elements**

**Hazard Pictograms** 



**Hazard Word** Warning

#### **Hazard Statements**

H227: Combustible liquid H302: Harmful if swallowed

H312: Harmful in contact with skin

H332: Harmful if inhaled H315: Causes skin irritation

H319: Causes serious eve irritation

#### **Precautionary Statements**

P261: Avoid breathing dust/fume/gas/mist/vapours/spray

P264: Wash skin thoroughly after handling

P270: Do not eat, drink or smoke when using this product

P271: Use only outdoors or in a well-ventilated area

P280: Wear protective gloves/protective clothing/eye protection/face protection

P301+312: **Response:** 

P330: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel

P302+352: **unwell** 

P305+351+338: Rinse mouth

P337+313: IF ON SKIN: Wash with soap and water

 $_{\mbox{\footnotesize IARC}}\,$  IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing



**Safety Data Sheet** 

BB9216 Ceramic Prep Solution

**ACGIH OSHA** NTP

#### If eye irritation persists get medical advice/attention Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH. No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA. No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

**Page** 

#### 3. Composition Information on Ingredients

CAS Number	Wt %	<b>Component Name</b>
67-63-0	1-5%	Isopropanol, 2-Propanol
67-64-1	.4-5%	2-Propanone
111-76-2	1-5%	Ethylene Glycol n-Butyl Ether

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

#### 4. First Aid Measures

#### Inhalation:

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

Ingestion: Give large amounts of water to drink. Never give anything by mouth to an unconscious person. Get medical attention.

Skin Contact: Immediately flush skin with plenty of water for at least 15 minutes. Call a physician if irritation develops.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention immediately.

#### 5. Fire Fighting Measures

Listed fire data is for Pure Isopropyl Alcohol.

#### **Explosion:**

Above flash point, vapor-air mixtures are explosive within flammable limits noted above.

Contact with strong oxidizers may cause fire or explosion. Vapors can flow along surfaces to distant ignition source and flash back. Sensitive to static discharge.

Fire Extinguishing Media:

Water spray, dry chemical, alcohol foam, or carbon dioxide. Water spray may be used to keep fire exposed containers cool, dilute spills to nonflammable mixtures, protect personnel attempting to stop leak and disperse vapors.

Special Information:

In the event of a fire, wear full protective clothing and NIOSH-approved self-contained breathing apparatus with full facepiece operated in the pressure demand or other positive pressure mode.

#### 6. Accidental Release Measures

Ventilate area of leak or spill. Remove all sources of ignition. Wear appropriate personal



## Babe's Boat Products

**Safety Data Sheet** 

BB9216 Ceramic Prep Solution

Page 3

Revision Date: 12/16/2024

protective equipment as specified in Section 8. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Contain and recover liquid when possible. Use non-sparking tools and equipment. Collect liquid in an appropriate container or absorb with an inert material (e. g., vermiculite, dry sand, earth), and place in a chemical waste container. Do not use combustible materials, such as saw dust. Do not flush to sewer! If a leak or spill has not ignited, use water spray to disperse the vapors, to protect personnel attempting to stop leak, and to flush spills away from exposures.

#### 7. Handling and Storage

Protect against physical damage. Store in a cool, dry well-ventilated location, away from any area where the fire hazard may be acute. Outside or detached storage is preferred. Separate from incompatibles. Containers should be bonded and grounded for transfers to avoid static sparks. Storage and use areas should be No Smoking areas. Use non-sparking type tools and equipment, including explosion proof ventilation. Containers of this material may be hazardous when empty since they retain product residues (vapors, liquid); observe all warnings and precautions listed for the product. Small quantities of peroxides can form on prolonged storage. Exposure to light and/or air significantly increases the rate of peroxide formation. If evaporated to a residue, the mixture of peroxides and isopropanol may explode when exposed to heat or shock.

#### 8. Exposure Controls and Personal Protection

67-63-0 Isopropanol, 2-Propanol	200 ppm TLV (ACGIH 8 hour)
	400 ppm (OSHA PEL) TWA
67-64-1 2-Propanone	500 ppm (ACGIH 8 hour) TWA
·	1000 ppm (OSHA PEL)
	20 ppm (OSHA TLV)
	25 ppm (OSHA PEL)

#### **VENTILATION**

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

#### RESPIRATORY PROTECTION

Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

#### PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

#### **EYE PROTECTION**

Use splash goggles or face shield when eye contact may occur.

#### OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS



## Babe's Boat Products

**Safety Data Sheet** 

BB9216 Ceramic Prep Solution

Revision Date: 12/16/2024

**Page** 

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

#### 9. Physical and Chemical Properties

Flash Point 62°C (143.6°F) TCC **Upper Flamability Limit** 12.7 % Auto Ignition 399°C (750°F) **Lower Flamability Limit** 2.0 %

Physical State liquid Color Blue Vapor Press 44 mmHg

**pH** 5.5 Specific Gravity .987 Viscosity thin

Melting Point °F -11°F Vapor Density (Air=1) 2.1 **Odor** IPA/Fruity

VOC Content < 2.48% accounting for VOC Water Solubility complete excepted solvent, 24.47 g/L

10. Stability and Reactivity

Stability Stable Hazardous Polymerization Not Expected to Occur

Conditions to Avoid Keep away from extreme heat, Strong Acids, Alkalies and Oxidizers such as

Chlorine, other Halogens, Hydrogen Peroxide and Oxygen

Hazardous No substances are readily identifiable from composition but no degradation

**Decomposition Products** data is available.

#### 11. Toxicological Information

Oral rat LD50: 5045 mg/kg; skin rabbit LD50: 12.8 gm/kg; inhalation rat LC50: 16,000 ppm/8hour; investigated as a tumorigen, mutagen, reproductive effector.

#### 12. Ecological Information

#### **Environmental Fate:**

When released into the soil, this material is expected to guickly evaporate, may leach into groundwater and may biodegrade to a moderate extent. When released to water, this material is expected to quickly evaporate, have a half-life between 1 and 10 days and may biodegrade to a moderate extent. This material is not expected to significantly bioaccumulate. When released into the air, this material is expected to be readily degraded by reaction with photochemically produced hydroxyl radicals, to have a half-life between 1 and 10 days and may be removed from the atmosphere to a moderate extent by wet deposition.

Environmental Toxicity: The LC50/96-hour values for fish are over 100 mg/l. This material is not expected to be toxic to aquatic life.

#### 13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.



## Babe's Boat Products

**Safety Data Sheet** 

BB9216 Ceramic Prep Solution

Revision Date: 12/16/2024

**Page** 

#### 14. Transportation Information

Domestic (Land, D.O.T.)

------

Proper Shipping Name: This Product is NOT considered a Flammable hazard for domestic

shipments, 173.150 (e)(2)

International (Water, I.M.O.)

-----

Proper Shipping Name: Not Regulated

Information reported for product/size: 32 oz up to 55 gallon drum.

#### 15. Regulatory Information

**OSHA Hazards**: Combustible Liquid, Moderate eye irritant, Moderate respiratory irritant

**EPCRA - Emergency Planning and Community Right-to-Know** 

**CERCLA Reportable Quantity -** Calculated RQ exceeds reasonably attainable upper limit.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards: Fire Hazard, Acute Health Hazard, Chronic Health hazard

**SARA 302:** No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

**SARA 313: SARA 313: :** The following components are subject to reporting levels established by SARA Title III, Section 313: 111-76-2, 2-butoxy ethanol

**California Prop. 65:** This product does not contain any chemicals known to the State of California to cause cancer, birth, or any other reproductive defects.

#### 16. Other Information Revision Date 12/16/2024

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

#### Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH American Conference of Government Industrial Hygienists LD50 Lethal Dose 50% AICS Australia, Inventory of Chemical Substances LOAEL Lowest Observed Adverse Effect Level



### **Safety Data Sheet**

BB9216 Ceramic Prep Solution

DSL Canada, Domestic Sub- stances List

NFPA National Fire Protection Agency

NDSL Canada, Non-Domestic Sub- stances List

NIOSH National Institute for Occupational Safety & Health

CNS Central Nervous System

NTP National Toxicology Program

CAS Chemical Abstract Service

NZIoC New Zealand Inventory of Chemicals

EC50 Effective Concentration

NOAEL No Observable Adverse Effect Level

EC50 Effective Concentration 50%

NOEC No Observed Effect Concentration

EGEST EOSCA Generic Exposure Scenario Tool

OSHA Occupational Safety & Health Administration

EOSCA European Oilfield Specialty Chemicals Association

PEL Permissible Exposure Limit

EINECS European Inventory of Exist- ing Chemical Substances

PICCS Philipines Inventory of Commercial Chemical Substances

MAK Germany Maximum Concentration Values

PRNT Presumed Not Toxic

GHS Globally Harmonized System

RCRA Resource Conservation Recovery Act

>= Greater Than or Equal To

STEL Short-term Exposure Limit

IC50 Inhibition Concentration 50%

SARA Superfund Amendments and Reauthorization Act.

IARC International Agency for Re- search on Cancer

TLV Threshold Limit Value

IECSC Inventory of Existing Chemical Substances in China

TWA Time Weighted Average

ENCS Japan, Inventory of Existing and New Chemical Sub- stances

TSCA Toxic Substance Control Act

KECI Korea, Existing Chemical Inventory

UVCB Unknown or Variable Composition, Complex Reaction Products, and Biological Materials

<= Less Than or Equal To

WHMIS Workplace Hazardous Materials In- formation System

LC50 Lethal Concentration 50%



BB9216 Ceramic Prep Solution

Page



# Babe's Boat Products Safety Data Sheet Page 8 Revision Date: 12/16/2024

BB9216 Ceramic Prep Solution

Page