

FLOOR WASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Identification

Product form : Mixture
 Product name : FLOOR WASH
 Product code : GT19105,55

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Floor Cleaner

1.3. Details of the supplier of the safety data sheet

Gliptone Manufacturing Inc.
 1740 Julia Goldbach Avenue
 Ronkonkoma, NY 11779 - United States of America
 T 1-631-285-7250 - F 1-631-589-5487
www.gliptone.com

1.4. Emergency telephone number

Emergency number : 1-800-424-9300 International: 1-703-527-3887

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

Classification (GHS-US)

Not classified

2.2. Label elements

GHS-US labeling

No labeling applicable

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

| Name | Product identifier | % | Classification (GHS-US) |
|-------------------------------|-----------------------|--------|--|
| Trade Secret Non-Ionic Blend* | (CAS No) Trade Secret | 5 - 25 | Not classified |
| butyl glycoether | (CAS No) 111-76-2 | 1 - 10 | Flam. Liq. 4, H227 Acute Tox. 4 (Oral), H302 Acute Tox. 3 (Dermal), H311 Acute Tox. 4 (Inhalation), H332 Skin Irrit. 2, H315 |

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- | | |
|---------------------------------------|---|
| First-aid measures after inhalation | : Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, give oxygen. If breathing stops, give artificial respiration. Obtain medical attention. |
| First-aid measures after skin contact | : Remove/Take off immediately all contaminated clothing. Rinse immediately with plenty of water for 15 minutes. Obtain medical attention. Wash clothing before re-using. |
| First-aid measures after eye contact | : Wash immediately with plenty water (during 20 minutes), also under eyelids. Obtain medical attention. |
| First-aid measures after ingestion | : Do not induce vomiting. Rinse mouth out with water. Drink two glasses of water. Obtain medical attention. Never give anything by mouth to an unconscious person. |

FLOOR WASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after skin contact : Irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact : Irritation to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Dry powder. Foam. Carbon dioxide. Water fog.

5.2. Special hazards arising from the substance or mixture

- Fire hazard : Not flammable. Under fire conditions closed containers may rupture or explode.

5.3. Advice for firefighters

- Firefighting instructions : Move containers away from the fire area if this can be done without risk. Cool down the containers/equipment exposed to heat with a water spray. Ensure that there is no direct contact between the water and the product.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Combustion generates : Carbon oxides (CO, CO₂). Phosphorous oxide. Nitrogen oxides. irritating fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- General measures : Keep public away.

6.1.1. For non-emergency personnel

- Protective equipment : Use chemically protective clothing.
Emergency procedures : Ventilate spillage area. NO open flames, NO sparks, and NO smoking. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8 Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Do not allow into drains or water courses or dispose of where ground or surface waters may be affected.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Ventilate well. Stop leak without risks if possible. Take up liquid spill into inert absorbent material. Notify authorities if product enters sewers or public waters. Notify environmental authorities.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8 : Exposure-controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Additional hazards when processed : TOXIC LIQUID, ORGANIC, N.O.S. Use chemically protective clothing. Store in well ventilated area. Avoid inhalation of vapors. Avoid contact with skin, eyes and clothing. Keep away from oxidizing agents. Keep container closed when not in use.
Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only non-sparking tools. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray. Keep container closed when not in use.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. No smoking. Inspect frequently to identify any sing of warping or leak of the containers.
Special rules on packaging : Always keep in containers made of the same material as the supply container.

FLOOR WASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| butyl glycolether (111-76-2) | | |
|------------------------------|-----------------|---|
| ACGIH | ACGIH TWA (ppm) | 20 ppm (2-Butoxyethanol (EGBE); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value) |

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Materials for protective clothing : Wear long sleeves.
- Hand protection : Impermeable protective gloves.
- Eye protection : Safety glasses.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Environmental exposure controls : Avoid release to the environment.
- Other information : Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|---|--|
| Physical state | : Liquid |
| Color | : Bright Green |
| Odor | : Pleasant Sweet floral odor to pungent detergent odor |
| Odor threshold | : No data available |
| pH | : No data available |
| pH solution | : 10 |
| Melting point | : Not applicable |
| Freezing point | : No data available |
| Boiling point | : > 100 °C |
| Flash point | : 98 °C |
| Relative evaporation rate (butyl acetate=1) | : No data available |
| Flammability (solid, gas) | : No data available |
| Explosion limits | : No data available |
| Explosive properties | : No data available |
| Oxidizing properties | : No data available |
| Vapor pressure | : < 20 mm Hg |
| Relative density | : 1.04 |
| Relative vapor density at 20 °C | : < 1 |
| Solubility | : soluble in water. |
| Log Pow | : No data available |
| Auto-ignition temperature | : No data available |
| Decomposition temperature | : No data available |
| Viscosity | : No data available |
| Viscosity, kinematic | : No data available |
| Viscosity, dynamic | : No data available |

9.2. Other information

| | |
|-------------|---------|
| VOC content | : < 5 % |
|-------------|---------|

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

FLOOR WASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, No sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

Keep away from: strong oxidants. acids.

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Likely routes of exposure : Skin contact.; Eyes contact.; Inhalation; Ingestion.

Acute toxicity : Not classified

butyl glycolether (111-76-2)

| | |
|----------------------------|--|
| LD50 dermal rat | > 2000 mg/kg body weight (Rat; Experimental value; OECD 402: Acute Dermal Toxicity) |
| LD50 dermal rabbit | 435 mg/kg body weight (Rabbit; Experimental value; OECD 402: Acute Dermal Toxicity; 435 mg/kg bodyweight; Rabbit; Weight of evidence; Equivalent or similar to OECD 402) |
| LC50 inhalation rat (mg/l) | 2.17 mg/l/4h (Rat; Experimental value; 2.35 mg/l/4h; Rat; Experimental value) |
| LC50 inhalation rat (ppm) | 450-486, Rat; Weight of evidence |
| ATE US (oral) | 500.000 mg/kg body weight |
| ATE US (dermal) | 435.000 mg/kg body weight |
| ATE US (gases) | 4500.000 ppmV/4h |
| ATE US (vapors) | 2.170 mg/l/4h |
| ATE US (dust, mist) | 2.170 mg/l/4h |

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

butyl glycolether (111-76-2)

| | |
|--|--|
| IARC group | 3 - Not Classifiable |
| Reproductive toxicity | : Not classified |
| Specific target organ toxicity (single exposure) | : Not classified |
| Specific target organ toxicity (repeated exposure) | : Not classified |
| Aspiration hazard | : Not classified |
| Symptoms/injuries after skin contact | : Irritation. May cause an allergic skin reaction. |
| Symptoms/injuries after eye contact | : Irritation to eyes. |
| Other information | : CNS depression. |

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment. Do not discharge into drains or the environment.

Trade Secret Non-Ionic Blend

| | |
|-------------------------|-------------------------------------|
| LC50 fish 2 | 7 mg/l (LC50; 96 h; Leuciscus idus) |
| Threshold limit algae 1 | 500 mg/l (EC50) |

FLOOR WASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

| butyl glycolether (111-76-2) | |
|---------------------------------|---|
| Persistence and degradability | Readily biodegradable in water. Biodegradable in the soil. Photodegradation in the air. |
| Biochemical oxygen demand (BOD) | 0.71 g O ₂ /g substance |
| Chemical oxygen demand (COD) | 2.20 g O ₂ /g substance |
| ThOD | 2.305 g O ₂ /g substance |
| BOD (% of ThOD) | 0.31 |

| Trade Secret Non-Ionic Blend | |
|-------------------------------|-------------------------------------|
| Persistence and degradability | Not readily biodegradable in water. |

12.3. Bioaccumulative potential

| butyl glycolether (111-76-2) | |
|------------------------------|--|
| Log Pow | 0.81 (Experimental value; BASF test; 25 °C) |
| Bioaccumulative potential | Low potential for bioaccumulation (Log Kow < 4). |

| Trade Secret Non-Ionic Blend | |
|------------------------------|-----|
| Log Pow | > 4 |

12.4. Mobility in soil

| butyl glycolether (111-76-2) | |
|------------------------------|-------------------|
| Surface tension | 0.027 N/m (25 °C) |

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations : Dispose in a safe manner in accordance with local/national regulations.
Additional information : Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not regulated as dangerous goods or hazardous material.

TDG

Not regulated as dangerous goods or hazardous material.

Transport by sea

Not regulated as dangerous goods or hazardous material.

Air transport

Not regulated as dangerous goods or hazardous material.

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory

This product or mixture does not contain a toxic chemical or chemicals in excess of the applicable de minimis concentration as specified in 40 CFR §372.38(a) subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

| Trade Secret Non-Ionic Blend | |
|------------------------------|--|
| EPA TSCA Regulatory Flag | XU - XU - indicates a substance exempt from reporting under the Inventory Update Reporting Rule, i.e., Partial Updating of the TSCA Inventory Data Base Production and Site Reports (40 CFR 710(C)). |

FLOOR WASH

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

15.2. International regulations

CANADA

During the transition period (June 2015-June 2017), Canadian regulation requires that the supplier must provide a document that conforms to either *Controlled Products Regulations* (WHMIS 1988) or HPR (WHMIS 2015), and not a combination of both. This document conforms to the post June 2017 HPR (WHMIS 2015) for a specific controlled or hazardous product. The classification, label and (material) SDS fully complies with the specific regulation chosen by the supplier.

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer and/or reproductive harm

butyl glycolether (111-76-2)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

| | |
|---------------------------|--|
| Acute Tox. 3 (Dermal) | Acute toxicity (dermal) Category 3 |
| Acute Tox. 4 (Inhalation) | Acute toxicity (inhalation) Category 4 |
| Acute Tox. 4 (Oral) | Acute toxicity (oral) Category 4 |
| Flam. Liq. 4 | Flammable liquids Category 4 |
| Skin Irrit. 2 | Skin corrosion/irritation Category 2 |
| H227 | Combustible liquid |
| H302 | Harmful if swallowed |
| H311 | Toxic in contact with skin |
| H315 | Causes skin irritation |
| H332 | Harmful if inhaled |

NFPA health hazard


: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.

NFPA fire hazard

: 1 - Must be preheated before ignition can occur.

NFPA reactivity

: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

- Health : 2 Moderate Hazard - Temporary or minor injury may occur
- Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)
- Physical : 1 Slight Hazard - Materials that are normally stable but can become unstable (self-react) at high temperatures and pressures. Materials may react non-violently with water or undergo hazardous polymerization in the absence of inhibitors.

Legend: ACGIH: American Conference of Governmental Industrial Hygienists

NIOSH: National Institute of Occupational Safety and Health

CAS: Chemical Abstract Services

DOT: Department of Transportation

HMIS: Hazardous Materials Identification System

IARC: International Agency for Research on Cancer

N/Av: not available

OSHA: Occupational Safety and Health Administration

SARA: Superfund Amendments & Reauthorization Act

TLV: Threshold Limit Values

SDS US (GHS HazCom 2012)

CFR: Code of Federal Regulations

EPA: Environmental Protection Agency

N/Ap: not applicable

NFPA: National Fire Protection Association

PEL: Permissible Exposure Limit

STEL: Short Term Exposure Limit

TSCA: Toxic Substance Control Act

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product