

Technical Data: TEKNAbond[®] Updated: 06/17/24



TEKNAbond®

Multi-Purpose Wall Size/Adhesive

Dry Wallcovering Adhesive Product Number(s): 015398

Base: Starch

Product Information

General Properties: Multi-purpose product, used to prepare (size) walls and to hang wallcovering.

- For all types of wallcoverings
- Excellent for pre-pasted papers
- Stir thoroughly before use
- Mix with cold water

Compatible Coatings: All ROMAN® Primers

Mildew-Resistant: All Roman products have a bactericide and mildewcide for in-can protection.

Application Instructions

Surface Preparation: Surface must be free from grease and other residues, dry, smooth and structurally sound. Check surfaces for paint bonding, loose wallcoverings, damaged wallboard or plaster. Repair all unsound surfaces. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Mixing Instructions: Following chart below, slowly stir entire contents of package into cold water. Continue stirring for 30 seconds. Let stand for 10 minutes, stirring occasionally. Stir thoroughly before use.

<u>Usage</u>	<u>Water</u>	Coverage
Sizing	16 pints	650 sq. ft.
Adhesive for Prepasted Wallcovering	16 pints	14-16 rolls
Adhesive for Light Weight Wallcovering	16 pints	12-14 rolls
Adhesive for Medium Weight Wallcovering	12 pints	10-12 rolls
Adhesive for Grasscloths, Silks, Strings and other Natural or Delicate Wallcoverings	10 pints	8-10 rolls



Technical Data: TEKNAbond[®] Updated: 06/17/24

Application Method: Use only when the room temperature is above 50°F. Apply paste evenly to back of wallcovering with clean 3/8" nap paint roller. Book according to the wallcovering manufacturer's instructions. Set aside for 3 to 5 minutes. Hang strips by pressing air pockets and excess paste from center outward toward seams. Avoid adhesive contact with the surface of embossed, textured or delicate wallcoverings.

Clean-Up: Before the adhesive dries, remove the excess with clean water. Additional effort may be required if the adhesive is allowed to contact the surface of embossed or textured vinyl wallcoverings.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Products, LLC warrants that it will replace this product free of charge, if, within 24 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.