Date Printed: 1/31/2022 Page 1 / 5

# Safety Data Sheet



www.testors.com

**Revision Date:** 

# 1. Identification

Product Name: TSTRS 12PK .5OZ ROOF BROWN FLAT

TRI

Product Identifier: 4884 Supercedes Date: 2/14/2018

Recommended Use: Model Master Paint/Water-Based Acrylic

Supplier: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Manufacturer: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

1/31/2022

Preparer: Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

## 2. Hazards Identification

#### Classification

#### Symbol(s) of Product

No symbol is required per 2012 OSHA Hazard Communication Standard 29 CFR 1910.1200.

#### Signal Word

No Signal Word has been assigned.

#### Possible Hazards

21% of the mixture consists of ingredient(s) of unknown acute toxicity.

# 3. Composition / Information on Ingredients

#### **HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>                          | CAS-No.    | Wt.%<br>Range | GHS Symbols   | GHS Statements |
|---|------------|---------------|---------------|----------------|
| Propylene Glycol Monobutyl Ether              | 5131-66-8  | 2.5-10        | GHS07         | H302-315-319   |
| Hydrous Magnesium Silicate                    | 14807-96-6 | 2.5-10        | Not Available | Not Available  |
| Dipropylene Glycol Monobutyl Ether            | 29911-28-2 | 1.0-2.5       | Not Available | Not Available  |
| 2,2,4-Trimethyl-1,3-Pentanediol Diisobutyrate | 6846-50-0  | 1.0-2.5       | GHS06         | H331           |
| Titanium Dioxide                              | 13463-67-7 | 1.0-2.5       | Not Available | Not Available  |
| Carbon Black                                  | 1333-86-4  | 0.1-1.0       | Not Available | Not Available  |
| Octylphenol Ethoxylate                        | 9036-19-5  | 0.1-1.0       | GHS07         | H302           |
| Aqueous Ammonia                               | 1336-21-6  | 0.1-1.0       | GHS05-GHS07   | H302-314-335   |

Date Printed: 1/31/2022 Page 2 / 5

#### 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

# 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

## 6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

# 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

#### 8. Exposure Controls / Personal Protection

| Chemical Name                                     | CAS-No.    | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-<br>TWA | OSHA PEL-<br>CEILING |
|---|------------|-----------------------|-------------------|--------------------|------------------|----------------------|
| Propylene Glycol Monobutyl<br>Ether               | 5131-66-8  | 10.0                  | N.E.              | N.E.               | N.E.             | N.E.                 |
| Hydrous Magnesium Silicate                        | 14807-96-6 | 10.0                  | 2 mg/m3           | N.E.               | N.E.             | N.E.                 |
| Dipropylene Glycol Monobutyl<br>Ether             | 29911-28-2 | 5.0                   | N.E.              | N.E.               | N.E.             | N.E.                 |
| 2,2,4-Trimethyl-1,3-<br>Pentanediol Diisobutyrate | 6846-50-0  | 5.0                   | N.E.              | N.E.               | N.E.             | N.E.                 |
| Titanium Dioxide                                  | 13463-67-7 | 5.0                   | 10 mg/m3          | N.E.               | 15 mg/m3         | N.E.                 |
| Carbon Black                                      | 1333-86-4  | 1.0                   | 3 mg/m3           | N.E.               | 3.5 mg/m3        | N.E.                 |
| Octylphenol Ethoxylate                            | 9036-19-5  | 1.0                   | N.E.              | N.E.               | N.Ē.             | N.E.                 |
| Agueous Ammonia                                   | 1336-21-6  | 1.0                   | N.E.              | N.E.               | N.E.             | N.E.                 |

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

Date Printed: 1/31/2022 Page 3 / 5

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

## 9. Physical and Chemical Properties

Appearance: Physical State: Liquid Liquid Odor: Odor Threshold: Solvent Like N.E. Specific Gravity: 1.101 pH: N.D. Freeze Point, °C: Viscosity: N.D. N.D. Solubility in Water: Partition Coefficient, n-octanol/ Miscible N.D. Decomposition Temp., °C: N.D. Boiling Range, °C: **Explosive Limits, vol%:** 1.3 - 12.6 100 - 537 Flammability: Flash Point. °C: 94 Does not Support Combustion **Evaporation Rate:** Slower than Ether Auto-Ignition Temp., °C: N.D. Vapor Density: Vapor Pressure: Heavier than Air N.D.

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat. Keep from freezing.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

**Hazardous Polymerization:** Will not occur under normal conditions. **Stability:** This product is stable under normal storage conditions.

## 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Constituents of this product include crystalline silica dust which ,if inhalable, can may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula. Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

Date Printed: 1/31/2022 Page 4 / 5

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.    | Chemical Name                                 | Oral LD50        | Dermal LD50        | Vapor LC50    |
|------------|---|------------------|--------------------|---------------|
| 5131-66-8  | Propylene Glycol Monobutyl Ether              | 1900 mg/kg Rat   | >2000 mg/kg Rat    | N.E.          |
| 14807-96-6 | Hydrous Magnesium Silicate                    | 6000             | N.Ĕ.               | 30            |
| 29911-28-2 | Dipropylene Glycol Monobutyl Ether            | N.E.             | N.E.               | 25            |
| 6846-50-0  | 2,2,4-Trimethyl-1,3-Pentanediol Diisobutyrate | >3200 mg/kg Rat  | >2000 mg/kg Rabbit | >5.3 mg/L Rat |
| 13463-67-7 | Titanium Dioxide                              | >10000 mg/kg Rat | 2500 mg/kg         | N.E.          |
| 1333-86-4  | Carbon Black                                  | >15400 mg/kg Rat | N.E.               | N.E.          |
| 9036-19-5  | Octylphenol Ethoxylate                        | 1700 mg/kg Rat   | N.E.               | N.E.          |
| 1336-21-6  | Aqueous Ammonia                               | 350 mg/kg Rat    | N.E.               | N.E.          |

N.E. - Not Established

# 12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components. No ecotoxicity data was found for this product.

## 13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances.

## 14. Transport Information

| UN Number:                                     | <u>Domestic (USDOT)</u> | International (IMDG) | <u>Air (IATA)</u> | TDG (Canada)  |
|--|-------------------------|----------------------|-------------------|---------------|
|  | N.A.                    | N.A.                 | N.A.              | N.A.          |
| Proper Shipping Name:                          | Not Regulated           | Not Regulated        | Not Regulated     | Not Regulated |
| Hazard Class: Packing Group: Limited Quantity: | N.A.                    | N.A.                 | N.A.              | N.A.          |
|  | N.A.                    | N.A.                 | N.A.              | N.A.          |
|  | No                      | No                   | No                | No            |

# 15. Regulatory Information

## U.S. Federal Regulations:

## **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

None Known

#### **SARA Section 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Aqueous Ammonia1336-21-6

#### Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

Date Printed: 1/31/2022 Page 5 / 5

# U.S. State Regulations:

## California Proposition 65

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

# 16. Other Information

**HMIS RATINGS** 

Health: 1\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 1 Flammability: 1 Instability: 0

Volatile Organic Compounds: 346 g/L SDS REVISION DATE: 1/31/2022

REASON FOR REVISION: Revision Description Changed

Substance Hazard Threshold % Changed

**Product Composition Changed** 

Substance and/or Product Properties Changed in

Section(s):

03 - Composition / Information on Ingredients 08 - Exposure Controls / Personal Protection

09 - Physical & Chemical Properties
11 - Toxicological Information
15 - Regulatory Information
16 - Other Information

Substance Hazardous Flag Changed Substance Chemical Name Changed Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.