



Revision Date: 6/26/2019

## Rust-Oleum Multi Component Product Information Sheet

**236041 CPS 4-GL 8000OKRETEOP-KIT-LTGRN is a multi component product composed of the following individual chemical components:**

236039 CPS 4-GL 8000OKRETEOP-A-LTGRN

236032 CPS 4-GL 8000OKRETEOP-B

SDSs for each component follow this cover sheet.

### Transportation Information

|   | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u>      | <u>TDG (Canada)</u>    |
|---|-------------------------|-----------------------------|------------------------|------------------------|
| UN Number:                                      | 3066                    | 3066                        | 3066                   | 3066                   |
| Proper Shipping Name:                           | Paint Related Material  | Paint Related Material      | Paint Related Material | Paint Related Material |
| Hazard Class:                                   | 8                       | 8                           | 8                      | 8                      |
| Packing Group:                                  | II                      | II                          | II                     | II                     |
| Limited Quantity:                               | No                      | No                          | Cargo Aircraft Only    | No                     |
| Finished Good Schedule B Harmonized Tariff Code | 3907.30.0000            |                             |                        |                        |

# Safety Data Sheet



## 1. Identification

|                             |   |                         |  |
|-----------------------------|---|-------------------------|--|
| <b>Product Name:</b>        | CPS 4-GL 8000OKRETEOP-A-LTGRN   | <b>Revision Date:</b>   | 8/7/2018   |
| <b>Product Identifier:</b>  | 236039  | <b>Supersedes Date:</b> | 2/15/2018  |
| <b>Recommended Use:</b>     | Floor Coating/ Part A Epoxy   |                         |  |
| <b>Supplier:</b>            | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA  | <b>Manufacturer:</b>    | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
|                             | Rust-Oleum Canada (ROCA)<br>200 Confederation Parkway<br>Concord, ON L4K 4T8<br>Canada<br>Emergency Phone: 800-387-3625 |                         |  |
| <b>Preparer:</b>            | Regulatory Department   |                         |  |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 847-367-7700   |                         |  |

## 2. Hazard Identification

### Classification

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

6% of the mixture consists of ingredient(s) of unknown acute toxicity.

### GHS HAZARD STATEMENTS

|  |      |                                      |
|--|------|--------------------------------------|
| Germ Cell Mutagenicity, category 1B    | H340 | May cause genetic defects.           |
| Carcinogenicity, category 1B           | H350 | May cause cancer.                    |
| STOT, single exposure, category 3, RT1 | H335 | May cause respiratory irritation.    |
| Skin Irritation, category 2            | H315 | Causes skin irritation.              |
| Eye Irritation, category 2A            | H319 | Causes serious eye irritation.       |
| Skin Sensitizer, category 1            | H317 | May cause an allergic skin reaction. |

### GHS LABEL PRECAUTIONARY STATEMENTS

|           |  |
|-----------|--|
| P201      | Obtain special instructions before use.                                    |
| P280      | Wear protective gloves/protective clothing/eye protection/face protection. |
| P308+P313 | IF exposed or concerned: Get medical advice/attention.                     |
| P405      | Store locked up.   |

|                |  |
|----------------|--|
| P501           | Dispose of contents/container in accordance with local, regional and national regulations.                                       |
| P261           | Avoid breathing dust/fume/gas/mist/vapors/spray.   |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P312           | Call a POISON CENTER or doctor/physician if you feel unwell.   |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P264           | Wash hands thoroughly after handling.  |
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.  |
| P321           | For specific treatment see label   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P272           | Contaminated work clothing should not be allowed out of the workplace.   |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.   |

**GHS SDS PRECAUTIONARY STATEMENTS**

P363 Wash contaminated clothing before reuse.

### 3. Composition / Information On Ingredients

**HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>              | <u>CAS-No.</u> | <u>Wt.%</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|-----------------------------------|----------------|-------------|--------------------|-----------------------|
| Bisphenol A Epoxy Resin           | 25085-99-8     | 83          | GHS07              | H315-317-319-335      |
| Epichlorohydrin-bisphenol A resin | 25068-38-6     | 6.5         | GHS07              | H315-317-319-335      |
| Titanium Dioxide                  | 13463-67-7     | 3.7         | Not Available      | Not Available         |
| Alkyl Glycidyl Ether              | 68609-97-2     | 2.6         | GHS07              | H315-317              |
| Ethylbenzene                      | 100-41-4       | 0.2         | GHS02-GHS07-GHS08  | H225-304-332-351-373  |
| Solvent Naphtha, Light Aromatic   | 64742-95-6     | 0.2         | GHS07-GHS08        | H304-332-340-350      |
| Glycerin                          | 56-81-5        | 0.1         | GHS06              | H330                  |

### 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

### 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted. Keep containers tightly closed.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

**Special Fire and Explosion Hazard (Combustible Dust):** No Information

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Avoid contact with eyes. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Keep from freezing. Keep container closed when not in use. Store in a dry, well ventilated place. Keep container tightly closed when not in use.

**Advice on Safe Handling of Combustible Dust:** No Information

## 8. Exposure Controls / Personal Protection

| Chemical Name                     | CAS-No.    | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|-----------------------------------|------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Bisphenol A Epoxy Resin           | 25085-99-8 | 85.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| Epichlorohydrin-bisphenol A resin | 25068-38-6 | 10.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| Titanium Dioxide                  | 13463-67-7 | 5.0                   | 10 mg/m3          | N.E.               | 15 mg/m3     | N.E.                 |
| Alkyl Glycidyl Ether              | 68609-97-2 | 5.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Ethylbenzene                      | 100-41-4   | 1.0                   | 20 ppm            | N.E.               | 100 ppm      | N.E.                 |
| Solvent Naphtha, Light Aromatic   | 64742-95-6 | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Glycerin                          | 56-81-5    | 1.0                   | N.E.              | N.E.               | 15 mg/m3     | N.E.                 |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

**Engineering Measures for Combustible Dust:** No Information

## 9. Physical and Chemical Properties

|                                 |                             |  |           |
|---------------------------------|-----------------------------|--|-----------|
| <b>Appearance:</b>              | Liquid                      | <b>Physical State:</b>                         | Liquid    |
| <b>Odor:</b>                    | Solvent Like                | <b>Odor Threshold:</b>                         | N.E.      |
| <b>Specific Gravity:</b>        | 1.191                       | <b>pH:</b>                                     | N.A.      |
| <b>Freeze Point, °C:</b>        | N.D.                        | <b>Viscosity:</b>                              | N.D.      |
| <b>Solubility in Water:</b>     | Negligible                  | <b>Partition Coefficient, n-octanol/water:</b> | N.D.      |
| <b>Decomposition Temp., °C:</b> | N.D.                        | <b>Explosive Limits, vol%:</b>                 | 1.2 - 6.8 |
| <b>Boiling Range, °C:</b>       | 135 - 2,500                 | <b>Flash Point, °C:</b>                        | 99        |
| <b>Flammability:</b>            | Does not Support Combustion | <b>Auto-ignition Temp., °C:</b>                | N.D.      |
| <b>Evaporation Rate:</b>        | Slower than Ether           | <b>Vapor Pressure:</b>                         | N.D.      |
| <b>Vapor Density:</b>           | Heavier than Air            |  |           |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid contact with strong acid and strong bases.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Low hazard for usual industrial handling or commercial handling by trained personnel. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)IARC lists Ethylbenzene as a possible human carcinogen (group 2B).

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>              | <u>Oral LD50</u> | <u>Dermal LD50</u>  | <u>Vapor LC50</u> |
|----------------|-----------------------------------|------------------|---------------------|-------------------|
| 25085-99-8     | Bisphenol A Epoxy Resin           | >5000            | >20000              | >20               |
| 25068-38-6     | Epichlorohydrin-bisphenol A resin | 11400 mg/kg Rat  | >5000               | 25 g/L            |
| 13463-67-7     | Titanium Dioxide                  | >10000 mg/kg Rat | 2500 mg/kg          | N.E.              |
| 68609-97-2     | Alkyl Glycidyl Ether              | 17100 mg/kg Rat  | >3987 mg/kg Rabbit  | N.E.              |
| 100-41-4       | Ethylbenzene                      | 3500 mg/kg Rat   | 15400 mg/kg Rabbit  | 17.4 mg/L Rat     |
| 64742-95-6     | Solvent Naphtha, Light Aromatic   | 8400 mg/kg Rat   | >2000 mg/kg Rabbit  | N.E.              |
| 56-81-5        | Glycerin                          | 12600 mg/kg Rat  | >10000 mg/kg Rabbit | >.6 mg/L Rat      |

N.E. - Not Established

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

### 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

### 14. Transport Information

|                       | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u>                                       | <u>Air (IATA)</u>   | <u>TDG (Canada)</u> |
|-----------------------|-------------------------|---|---|---------------------|
| UN Number:            | N.A.                    | 3082  | 3082  | N.A.                |
| Proper Shipping Name: | Not Regulated           | Environmentally Hazardous Substance, liquid, n.o.s. (Epoxy Resin) | Environmentally Hazardous Substance, liquid, n.o.s. (Epoxy Resin) | Not Regulated       |
| Hazard Class:         | N.A.                    | 9   | 9   | N.A.                |
| Packing Group:        | N.A.                    | III   | III   | N.A.                |
| Limited Quantity:     | No                      | No  | No  | No                  |

### 15. Regulatory Information

#### U.S. Federal Regulations:

##### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

##### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Ethylbenzene         | 100-41-4       |

##### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

#### U.S. State Regulations:

##### California Proposition 65:

**WARNING:** No Prop. 65 warning is required.

**16. Other Information****HMIS RATINGS**

**Health:** 2\*      **Flammability:** 1      **Physical Hazard:** 0      **Personal Protection:** X

**NFPA RATINGS**

**Health:** 2      **Flammability:** 1      **Instability:** 0

**Volatile Organic Compounds** 18 g/L

**SDS REVISION DATE:** 8/7/2018

**REASON FOR REVISION:** Revision Description Changed  
Substance and/or Product Properties Changed in Section(s):  
02 - Hazard Identification  
08 - Exposure Controls/Personal Protection  
15 - Regulatory Information  
16 - Other Information  
Substance Chemical Name Changed  
Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

# Safety Data Sheet



## 1. Identification

|                             |   |                         |  |
|-----------------------------|---|-------------------------|--|
| <b>Product Name:</b>        | CPS 4-GL 8000OKRETEOP-B   | <b>Revision Date:</b>   | 8/7/2018   |
| <b>Product Identifier:</b>  | 236032  | <b>Supersedes Date:</b> | 1/11/2018  |
| <b>Recommended Use:</b>     | Floor Coating/ Part B Activator   |                         |  |
| <b>Supplier:</b>            | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA  | <b>Manufacturer:</b>    | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
|                             | Rust-Oleum Canada (ROCA)<br>200 Confederation Parkway<br>Concord, ON L4K 4T8<br>Canada<br>Emergency Phone: 800-387-3625 |                         |  |
| <b>Preparer:</b>            | Regulatory Department   |                         |  |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 847-367-7700   |                         |  |

## 2. Hazard Identification

### Classification

### Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

|  |      |  |
|--|------|--|
| Reproductive Toxicity, category 2      | H361 | Suspected of damaging fertility or the unborn child. |
| Acute Toxicity, Oral, category 4       | H302 | Harmful if swallowed.                                |
| Acute Toxicity, Dermal, category 4     | H312 | Harmful in contact with skin.                        |
| Acute Toxicity, Inhalation, category 2 | H330 | Fatal if inhaled.                                    |
| Skin Corrosion, category 1             | H314 | Causes severe skin burns and eye damage.             |
| Skin Sensitizer, category 1            | H317 | May cause an allergic skin reaction.                 |

### GHS LABEL PRECAUTIONARY STATEMENTS

|           |  |
|-----------|--|
| P201      | Obtain special instructions before use.  |
| P280      | Wear protective gloves/protective clothing/eye protection/face protection.                 |
| P308+P313 | IF exposed or concerned: Get medical advice/attention.                                     |
| P405      | Store locked up.   |
| P501      | Dispose of contents/container in accordance with local, regional and national regulations. |
| P264      | Wash hands thoroughly after handling.  |



|                |  |
|----------------|--|
| P301+P312      | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.   |
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.  |
| P321           | For specific treatment see label   |
| P361+P364      | Take off immediately all contaminated clothing and wash it before reuse.   |
| P260           | Do not breathe dust/fume/gas/mist/vapors/spray.  |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P285           | In case of inadequate ventilation wear respiratory protection.   |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P320           | Specific treatment is urgent (see label for more information).   |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P310           | If exposed immediately call a POISON CENTER or doctor/physician.   |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P272           | Contaminated work clothing should not be allowed out of the workplace.   |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.   |

**GHS SDS PRECAUTIONARY STATEMENTS**

|      |   |
|------|---|
| P270 | Do not eat, drink or smoke when using this product. |
| P363 | Wash contaminated clothing before reuse.            |

**3. Composition / Information On Ingredients****HAZARDOUS SUBSTANCES**

| <b><u>Chemical Name</u></b>         | <b><u>CAS-No.</u></b> | <b><u>Wt. %</u></b> | <b><u>GHS Symbols</u></b> | <b><u>GHS Statements</u></b> |
|-------------------------------------|-----------------------|---------------------|---------------------------|------------------------------|
| Polyoxypropylenediamine             | 9046-10-0             | 44                  | GHS05                     | H314                         |
| Diethylenetriamine                  | 111-40-0              | 23                  | GHS05-GHS06               | H302-311-314-317-330         |
| 4-Nonylphenol, Branched             | 84852-15-3            | 19                  | GHS05-GHS07-GHS08         | H302-312-314-361             |
| 4,4'-(1-Methylethylidene) Bisphenol | 80-05-7               | 10.0                | GHS05-GHS07               | H317-318-332-335             |
| Glycerin                            | 56-81-5               | 0.6                 | GHS06                     | H330                         |
| Stoddard Solvent                    | 8052-41-3             | 0.2                 | GHS08                     | H304-372                     |

**4. First-Aid Measures**

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Immediately flush skin with plenty of water for at least 15 minutes while removing clothing. Get medical attention immediately. Wash clothing separately before reuse. Destroy contaminated shoes.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

## 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** No unusual fire or explosion hazards noted. Keep containers tightly closed.

**SPECIAL FIREFIGHTING PROCEDURES:** Containers can rupture and release highly toxic material if exposed to heat. Substance is non-combustible but reacts with many metals to form explosive hydrogen gas. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

**Special Fire and Explosion Hazard (Combustible Dust):** No Information

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Avoid runoff into sewers and waterways. Provide ventilation and approach spill from upwind using proper personal protective equipment as indicated in Section 8. Carefully neutralize spill with sodium bicarbonate (NaHCO<sub>3</sub>). Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust.

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use.

**Advice on Safe Handling of Combustible Dust:** No Information

## 8. Exposure Controls / Personal Protection

| Chemical Name                          | CAS-No.    | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA         | OSHA PEL-<br>CEILING |
|--|------------|-----------------------|-------------------|--------------------|----------------------|----------------------|
| Polyoxypropylenediamine                | 9046-10-0  | 45.0                  | N.E.              | N.E.               | N.E.                 | N.E.                 |
| Diethylenetriamine                     | 111-40-0   | 25.0                  | 1 ppm             | N.E.               | N.E.                 | N.E.                 |
| 4-Nonylphenol, Branched                | 84852-15-3 | 20.0                  | N.E.              | N.E.               | N.E.                 | N.E.                 |
| 4,4'-(1-Methylethylidene)<br>Bisphenol | 80-05-7    | 10.0                  | N.E.              | N.E.               | N.E.                 | N.E.                 |
| Glycerin                               | 56-81-5    | 1.0                   | N.E.              | N.E.               | 15 mg/m <sup>3</sup> | N.E.                 |
| Stoddard Solvent                       | 8052-41-3  | 1.0                   | 100 ppm           | N.E.               | 500 ppm              | N.E.                 |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Provide general dilution of local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

**Engineering Measures for Combustible Dust:** No Information

## 9. Physical and Chemical Properties

|                                 |                             |  |             |
|---------------------------------|-----------------------------|--|-------------|
| <b>Appearance:</b>              | Liquid                      | <b>Physical State:</b>                         | Liquid      |
| <b>Odor:</b>                    | Amine                       | <b>Odor Threshold:</b>                         | N.E.        |
| <b>Specific Gravity:</b>        | 1.002                       | <b>pH:</b>                                     | Alkaline    |
| <b>Freeze Point, °C:</b>        | N.D.                        | <b>Viscosity:</b>                              | N.D.        |
| <b>Solubility in Water:</b>     | Slight                      | <b>Partition Coefficient, n-octanol/water:</b> | N.D.        |
| <b>Decomposition Temp., °C:</b> | N.D.                        | <b>Explosive Limits, vol%:</b>                 | N.A. - N.A. |
| <b>Boiling Range, °C:</b>       | 35 - 537                    | <b>Flash Point, °C:</b>                        | 99          |
| <b>Flammability:</b>            | Does not Support Combustion | <b>Auto-ignition Temp., °C:</b>                | N.D.        |
| <b>Evaporation Rate:</b>        | Slower than Ether           | <b>Vapor Pressure:</b>                         | N.D.        |
| <b>Vapor Density:</b>           | Heavier than Air            |  |             |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**CONDITIONS TO AVOID:** Avoid contact with metals.

**INCOMPATIBILITY:** Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces. Incompatible with strong oxidizing agents, strong acids and strong alkalis.

**HAZARDOUS DECOMPOSITION:** Decomposition produces hydrogen chloride, chlorine and hydrogen gases.

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Substance causes severe eye irritation. Injury may be permanent.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Severely irritating; may cause permanent skin damage.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Corrosive and may cause severe and permanent damage to mouth, throat and stomach. Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Repeated exposure to low concentrations of HCl vapor or mist may cause bleeding of nose and gums.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>                | <u>Oral LD50</u> | <u>Dermal LD50</u>  | <u>Vapor LC50</u> |
|----------------|-------------------------------------|------------------|---------------------|-------------------|
| 9046-10-0      | Polyoxypropylenediamine             | 2885 mg/kg Rat   | 2979 mg/kg Rabbit   | 25 mg/L           |
| 111-40-0       | Diethylenetriamine                  | 1080 mg/kg Rat   | 672 mg/kg Rabbit    | 0.3 mg/l Rat      |
| 84852-15-3     | 4-Nonylphenol, Branched             | 1300 mg/kg Rat   | 2000 mg/kg Rabbit   | 25 mg/L           |
| 80-05-7        | 4,4'-(1-Methylethylidene) Bisphenol | 3300 mg/kg Rat   | 3577 mg/kg Rabbit   | 2100 mg/L         |
| 56-81-5        | Glycerin                            | 12600 mg/kg Rat  | >10000 mg/kg Rabbit | >.6 mg/L Rat      |

N.E. - Not Established

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems. RCRA Hazardous Waste: This material, when discarded or disposed of, could be a hazardous waste according to federal regulations (40 CFR 261) due to the characteristic of corrosivity (D002). Check state and local regulations for disposal requirements. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate, or otherwise inappropriate.

## 14. Transport Information

|                       | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u>      | <u>TDG (Canada)</u>    |
|-----------------------|-------------------------|-----------------------------|------------------------|------------------------|
| UN Number:            | 3066                    | 3066                        | 3066                   | 3066                   |
| Proper Shipping Name: | Paint Related Material  | Paint Related Material      | Paint Related Material | Paint Related Material |
| Hazard Class:         | 8                       | 8                           | 8                      | 8                      |
| Packing Group:        | II                      | II                          | II                     | II                     |
| Limited Quantity:     | No                      | No                          | Cargo Aircraft Only    | No                     |

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u>                | <u>CAS-No.</u> |
|-------------------------------------|----------------|
| 4-Nonylphenol, Branched             | 84852-15-3     |
| 4,4'-(1-Methylethylidene) Bisphenol | 80-05-7        |

#### Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

| <u>Chemical Name</u>    | <u>CAS-No.</u> |
|-------------------------|----------------|
| 4-Nonylphenol, Branched | 84852-15-3     |

### U.S. State Regulations:

#### California Proposition 65:

**WARNING:** No Prop. 65 warning is required.

**16. Other Information****HMIS RATINGS**

Health: 3\*      Flammability: 1      Physical Hazard: 1      Personal Protection: B

**NFPA RATINGS**

Health: 3      Flammability: 1      Instability: 1

Volatile Organic Compounds 2 g/L

SDS REVISION DATE: 8/7/2018

REASON FOR REVISION: Revision Description Changed  
Substance and/or Product Properties Changed in Section(s):  
03 - Composition/Information on Ingredients  
11 - Toxicological Information  
14 - Transport Information  
15 - Regulatory Information  
16 - Other Information  
Substance Chemical Name Changed  
Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.