Date Printed: 11/6/2019 Page 1 / 5

# Safety Data Sheet



www.modernmasters.com

### 1. Identification

11/6/2019 **Product Name:** MSTCL 5-G MC SUPREME SATIN **Revision Date:** 

Product Identifier: MCS902GAL5 Supercedes Date: New SDS

Recommended Use: Topcoat/Waterbased

**Rust-Oleum Corporation Rust-Oleum Corporation** Supplier: Manufacturer:

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

11 Hawthorn Parkway

Vernon Hills, IL 60061

**USA** 

Preparer: Regulatory Department

24 Hour Hotline: 847-367-7700 **Emergency Telephone:** 

# 2. Hazard Identification

#### Classification

Symbol(s) of Product



### Signal Word

Danger

### GHS HAZARD STATEMENTS

Respiratory Sensitizer, category 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.

### **GHS LABEL PRECAUTIONARY STATEMENTS**

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.

P272 Contaminated work clothing should not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. P280

P285 In case of inadequate ventilation wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position

comfortable for breathing.

P321 For specific treatment see label

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. P501 Dispose of contents/container in accordance with local, regional and national regulations.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P363 Wash contaminated clothing before reuse.

# 3. Composition / Information On Ingredients

Date Printed: 11/6/2019 Page 2 / 5

### **HAZARDOUS SUBSTANCES**

| Chemical Name                                     | CAS-No.         | Wt.%<br>Range | GHS Symbols           | GHS Statements               |
|---|-----------------|---------------|-----------------------|------------------------------|
| Dipropylene Glycol Monobutyl Ether                | 29911-28-2      | 0.1-1.0       | Not Available         | Not Available                |
| Dimethylethanolamine                              | 108-01-0        | 0.1-1.0       | GHS02-GHS05-<br>GHS06 | H226-302-312-314-331-335     |
| Secondary Alcohol Ethoxylate                      | 84133-50-6      | 0.1-1.0       | Not Available         | Not Available                |
| Aqueous Ammonia                                   | 1336-21-6       | 0.1-1.0       | GHS05-GHS07           | H302-314-335                 |
| Polymeric Benzotriazole                           | 104810-48-<br>2 | 0.1-1.0       | GHS07                 | H317                         |
| bis(1,2,2,6,6-Pentamethyl-4-Piperidinyl) Sebacate | 41556-26-7      | 0.1-1.0       | GHS07                 | H317                         |
| Ammonium Persulfate                               | 7727-54-0       | 0.1-1.0       | GHS03-GHS07-<br>GHS08 | H272-302-315-317-319-334-335 |
| Ethylene Glycol Monobutyl Ether                   | 111-76-2        | 0.1-1.0       | GHS07                 | H302-312-315-319-332         |
| Dipropylene glycol monomethyl ether               | 34590-94-8      | 0.1-1.0       | Not Available         | Not Available                |

# 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

# 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

### Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

# 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

Date Printed: 11/6/2019 Page 3 / 5

# 8. Exposure Controls / Personal Protection

| Chemical Name   | CAS-No.     | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|---|-------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Dipropylene Glycol Monobutyl<br>Ether                 | 29911-28-2  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Dimethylethanolamine                                  | 108-01-0    | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Secondary Alcohol Ethoxylate                          | 84133-50-6  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Aqueous Ammonia                                       | 1336-21-6   | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Polymeric Benzotriazole                               | 104810-48-2 | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| bis(1,2,2,6,6-Pentamethyl-4-<br>Piperidinyl) Sebacate | 41556-26-7  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Ammonium Persulfate                                   | 7727-54-0   | 1.0                   | 0.1 mg/m3         | N.E.               | N.E.         | N.E.                 |
| Ethylene Glycol Monobutyl<br>Ether                    | 111-76-2    | 1.0                   | 20 ppm            | N.E.               | 50 ppm       | N.E.                 |
| Dipropylene glycol monomethyl ether                   | 34590-94-8  | 1.0                   | 100 ppm           | 150 ppm            | 100 ppm      | N.E.                 |

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

# 9. Physical and Chemical Properties

| Liquid                      | Physical State:   | Liquid  |
|-----------------------------|---|---|
| Solvent Like                | Odor Threshold:   | N.E.  |
| 1.040                       | pH:   | N.A.  |
| N.D.                        | Viscosity:  | N.D.  |
| Slight                      | Partition Coefficient, n-octanol/   | N.D.  |
| N.D.                        | water:  | N.D.  |
| 100 - 100                   | Explosive Limits, vol%:   | N.A N.A.  |
| Does not Support Combustion | Flash Point, °C:  | 94  |
| Slower than Ether           | Auto-ignition Temp., °C:  | N.D.  |
| Heavier than Air            | Vapor Pressure:   | N.D.  |
|                             | Solvent Like 1.040 N.D. Slight N.D. 100 - 100 Does not Support Combustion Slower than Ether | Solvent Like  1.040  N.D.  Slight  N.D.  Slight  N.D.  100 - 100  Does not Support Combustion Slower than Ether  Odor Threshold:  pH:  Viscosity:  Partition Coefficient, n-octanol/ water:  Explosive Limits, vol%:  Flash Point, °C: Auto-ignition Temp., °C: |

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

**CONDITIONS TO AVOID: No Information** 

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

### 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Low hazard for usual industrial handling or commercial handling by trained personnel.

Page 4 / 5 Date Printed: 11/6/2019

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.    | Chemical Name  | Oral LD50      | Dermal LD50         | Vapor LC50   |
|------------|--|----------------|---------------------|--------------|
| 29911-28-2 | Dipropylene Glycol Monobutyl Ether                   | N.E.           | N.E.                | 25           |
| 108-01-0   | Dimethylethanolamine                                 | 1803 mg/kg Rat | 1220 mg/kg Rabbit   | N.E.         |
| 84133-50-6 | Secondary Alcohol Ethoxylate                         | 2100 mg/kg Rat | N.E.                | N.E.         |
| 1336-21-6  | Aqueous Ammonia                                      | 350 mg/kg Rat  | N.E.                | N.E.         |
| 41556-26-7 | bis(1,2,2,6,6-Pentamethyl-4-Piperidinyl)<br>Sebacate | 2615 mg/kg Rat | N.E.                | N.E.         |
| 7727-54-0  | Ammonium Persulfate                                  | 495 mg/kg Rat  | >10000 mg/kg Rabbit | 520 mg/L Rat |
| 111-76-2   | Ethylene Glycol Monobutyl Ether                      | 470 mg/kg Rat  | 1,060 mg/kg Rabbit  | 11 mg/L      |
| 34590-94-8 | Dipropylene glycol monomethyl ether                  | 5350 mg/kg Rat | 9500 mg/kg Rabbit   | >20 mg/L     |

N.E. - Not Established

# 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

### 13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances.

# Transport Information

|                       | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u> | TDG (Canada)  |
|-----------------------|------------------|----------------------|-------------------|---------------|
| UN Number:            | N.A.             | N.A.                 | N.A.              | N.A.          |
| Proper Shipping Name: | Not Regulated    | Not Regulated        | Not Regulated     | Not Regulated |
| Hazard Class:         | N.A.             | N.A.                 | N.A.              | N.A.          |
| Packing Group:        | N.A.             | N.A.                 | N.A.              | N.A.          |
| Limited Quantity:     | No               | No                   | No                | No            |

### 15. Regulatory Information

# U.S. Federal Regulations:

### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Respiratory or Skin Sensitization

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

**Chemical Name** CAS-No.

Aqueous Ammonia

1336-21-6

Date Printed: 11/6/2019 Page 5 / 5

Ammonium Persulfate 7727-54-0 Ethylene Glycol Monobutyl Ether 111-76-2

### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

## **U.S. State Regulations:**

### California Proposition 65:

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

### 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

**NFPA RATINGS** 

Health: 2 Flammability: 1 Instability 0

Volatile Organic Compounds 49 g/L SDS REVISION DATE: 11/6/2019

**REASON FOR REVISION:** 

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.