

# Safety Data Sheet



## 1. Identification

|                             |  |                         |  |
|-----------------------------|--|-------------------------|--|
| <b>Product Name:</b>        | RO 1GL 2PK 985 SILICONE ROOF COAT WHT  | <b>Revision Date:</b>   | 11/12/2021   |
| <b>Product Identifier:</b>  | 363836   | <b>Supersedes Date:</b> | 3/11/2020  |
| <b>Recommended Use:</b>     | Roof Coating   |                         |  |
| <b>Supplier:</b>            | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA | <b>Manufacturer:</b>    | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
| <b>Preparer:</b>            | Regulatory Department  |                         |  |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 847-367-7700  |                         |  |

## 2. Hazards Identification

### Classification

#### Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

12% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### GHS HAZARD STATEMENTS

|  |      |  |
|--|------|--|
| Flammable liquid, category 4           | H227 | Combustible liquid.  |
| Skin Sensitizer, category 1            | H317 | May cause an allergic skin reaction.                               |
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled.  |
| Carcinogenicity, category 1B           | H350 | May cause cancer.  |
| Reproductive Toxicity, category 2      | H361 | Suspected of damaging fertility or the unborn child.               |
| STOT, Repeated Exposure, category 2    | H373 | May cause damage to organs through prolonged or repeated exposure. |

#### GHS LABEL PRECAUTIONARY STATEMENTS

|      |  |
|------|--|
| P201 | Obtain special instructions before use.  |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. NO SMOKING. |
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray.  |
| P271 | Use only outdoors or in a well-ventilated area.  |
| P272 | Contaminated work clothing should not be allowed out of the workplace.                         |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.                     |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell.                                   |
| P321 | For specific treatment see label.  |

|           |   |
|-----------|---|
| P405      | Store locked up.  |
| P501      | Dispose of contents/container in accordance with local, regional and national regulations.            |
| P302+P352 | IF ON SKIN: Wash with plenty of soap and water.   |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                            |
| P308+P313 | IF exposed or concerned: Get medical advice/attention.  |
| P333+P313 | If skin irritation or rash occurs: Get medical advice/attention.                                      |
| P370+P378 | In case of fire: Use alcohol film forming foam, carbon dioxide, dry chemical, dry sand to extinguish. |
| P403+P235 | Store in a well-ventilated place. Keep cool.  |

**GHS SDS PRECAUTIONARY STATEMENTS**

P363 Wash contaminated clothing before reuse.

### 3. Composition / Information on Ingredients

**HAZARDOUS SUBSTANCES**

| <b>Chemical Name</b>                     | <b>CAS-No.</b> | <b>Wt.%<br/>Range</b> | <b>GHS Symbols</b>          | <b>GHS Statements</b>                        |
|--|----------------|-----------------------|-----------------------------|--|
| Polydimethylsiloxane, Hydroxy Terminated | 70131-67-8     | 50-75                 | GHS06                       | H331   |
| Titanium Dioxide                         | 13463-67-7     | 2.5-10                | GHS08                       | H351   |
| Methyltri(Ethylmethylketoxime)Silane     | 22984-54-9     | 2.5-10                | GHS07-GHS08                 | H317-319-373                                 |
| Octamethylcyclotetrasiloxane             | 556-67-2       | 1.0-2.5               | GHS08                       | H361   |
| Methyl Ethyl Ketoxime                    | 96-29-7        | 0.1-1.0               | GHS05-GHS06-<br>GHS07-GHS08 | H302-312-315-317-318-331-336<br>-350-370-373 |

### 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, get medical attention.

### 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Combustible liquid and vapor. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

**Special Fire and Explosion Hazard (Combustible Dust):** No Information

### 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

### 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Avoid excess heat. Store in a dry, well ventilated place. Keep container tightly closed when not in use.

**Advice on Safe Handling of Combustible Dust:** No Information

## 8. Exposure Controls / Personal Protection

| Chemical Name                            | CAS-No.    | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|--|------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Polydimethylsiloxane, Hydroxy Terminated | 70131-67-8 | 55.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| Titanium Dioxide                         | 13463-67-7 | 10.0                  | 10 mg/m3          | N.E.               | 15 mg/m3     | N.E.                 |
| Methyltri(Ethylmethylketoxime) Silane    | 22984-54-9 | 5.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Octamethylcyclotetrasiloxane             | 556-67-2   | 5.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Methyl Ethyl Ketoxime                    | 96-29-7    | 1.0                   | 10 ppm            | N.E.               | N.E.         | N.E.                 |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

**Engineering Measures for Combustible Dust:** No Information

## 9. Physical and Chemical Properties

|                                 |                     |   |                     |
|---------------------------------|---------------------|---|---------------------|
| <b>Appearance:</b>              | Viscous Liquid      | <b>Physical State:</b>                              | Liquid              |
| <b>Odor:</b>                    | Mild                | <b>Odor Threshold:</b>                              | N.E.                |
| <b>Specific Gravity:</b>        | 1.374               | <b>pH:</b>  | Not Determined      |
| <b>Freeze Point, °C:</b>        | N.D.                | <b>Viscosity:</b>                                   | 10, 000- 16,000 cps |
| <b>Solubility in Water:</b>     | Miscible            | <b>Partition Coefficient, n-octanol/<br/>water:</b> | N.D.                |
| <b>Decomposition Temp., °C:</b> | N.D.                | <b>Explosive Limits, vol%:</b>                      | N.A. - N.A.         |
| <b>Boiling Range, °C:</b>       | 110 - 537           | <b>Flash Point, °C:</b>                             | 81                  |
| <b>Flammability:</b>            | Supports Combustion | <b>Auto-Ignition Temp., °C:</b>                     | N.D.                |
| <b>Evaporation Rate:</b>        | Slower than Ether   | <b>Vapor Pressure:</b>                              | N.D.                |
| <b>Vapor Density:</b>           | Heavier than Air    |   |                     |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**Conditions to Avoid:** No Information

**Incompatibility:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**Hazardous Decomposition:** When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

**Hazardous Polymerization:** Will not occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

## 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Substance causes moderate eye irritation.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Substance may cause slight skin irritation.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Irritating to the nose, throat and respiratory tract. Harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.    | Chemical Name                            | Oral LD50        | Dermal LD50         | Vapor LC50     |
|------------|--|------------------|---------------------|----------------|
| 70131-67-8 | Polydimethylsiloxane, Hydroxy Terminated | >15400 mg/kg Rat | >15632 mg/kg Rabbit | >8.8 mg/L Rat  |
| 13463-67-7 | Titanium Dioxide                         | >10000 mg/kg Rat | 2500 mg/kg          | N.E.           |
| 22984-54-9 | Methyltri(Ethylmethylketoxime)Silane     | N.E.             | >2000 mg/kg Rat     | N.E.           |
| 556-67-2   | Octamethylcyclotetrasiloxane             | 4800 mg/kg Rat   | > 2400 mg/kg Rat    | 36 mg/L Rat    |
| 96-29-7    | Methyl Ethyl Ketoxime                    | 930 mg/kg Rat    | 1100 mg/kg Rabbit   | >4.83 mg/L Rat |

N.E. - Not Established

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not incinerate closed containers.

## 14. Transport Information

|                       | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u> | <u>TDG (Canada)</u> |
|-----------------------|-------------------------|-----------------------------|-------------------|---------------------|
| UN Number:            | N.A.                    | N.A.                        | N.A.              | N.A.                |
| Proper Shipping Name: | Not Regulated           | Not Regulated               | Not Regulated     | Not Regulated       |
| Hazard Class:         | N.A.                    | N.A.                        | N.A.              | N.A.                |
| Packing Group:        | N.A.                    | N.A.                        | N.A.              | N.A.                |
| Limited Quantity:     | No                      | No                          | No                | No                  |

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

**SARA Section 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| Aluminum Oxide       | 1344-28-1      |

**Toxic Substances Control Act**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

| <u>Chemical Name</u>         | <u>CAS-No.</u> |
|------------------------------|----------------|
| Octamethylcyclotetrasiloxane | 556-67-2       |

**U.S. State Regulations:****California Proposition 65**

**WARNING:** Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**16. Other Information****HMIS RATINGS**

|         |    |               |   |                  |   |                      |   |
|---------|----|---------------|---|------------------|---|----------------------|---|
| Health: | 2* | Flammability: | 2 | Physical Hazard: | 0 | Personal Protection: | X |
|---------|----|---------------|---|------------------|---|----------------------|---|

**NFPA RATINGS**

|         |   |               |   |              |   |
|---------|---|---------------|---|--------------|---|
| Health: | 2 | Flammability: | 2 | Instability: | 0 |
|---------|---|---------------|---|--------------|---|

**Volatile Organic Compounds:** 44 g/L

**SDS REVISION DATE:** 11/12/2021

**REASON FOR REVISION:** Substance and/or Product Properties Changed in Section(s):  
01 - Identification  
02 - Hazard Identification  
03 - Composition / Information on Ingredients  
09 - Physical & Chemical Properties  
11 - Toxicological Information  
15 - Regulatory Information  
Substance Hazard Threshold % Changed  
Product Composition Changed  
Substance Chemical Name Changed  
Revision Statement(s) Changed

**Legend:** N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.