Date Printed: 4/4/2025 Page 1 / 5

# Safety Data Sheet



\* Trusted Quality Since 1921 \* www.rustoleum.com

# 1. Identification

Name on Label: Varathane Fill Stick

Product Name: VARA FIL STCK 4PK ERLY AMER Revision Date: 4/4/2025

Product Identifier: 398987 Supercedes Date: New SDS

Recommended Use: Fill Stick/Varathane

Supplier: Rust-Oleum Corporation Manufacturer: Rust-Oleum Corporation 11 Hawthorn Parkway 11 Hawthorn Parkway

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Vernon Hills, IL 60061 USA

Preparer: Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

# 2. Hazard Identification

### Classification

Symbol(s) of Product



# Signal Word

Danger

### Possible Hazards

90% of the mixture consists of ingredient(s) of unknown acute toxicity.

### **GHS Hazard Statements**

Acute Toxicity, Inhalation, category 3 H331 Toxic if inhaled.

**GHS Label Precautionary Statements** 

P261 Avoid breathing dust, fumes, gas, mists, vapours, or spray.

P271 Use only outdoors or in a well-ventilated area.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P311 Call a POISON CENTER or doctor/physician.
P321 Specific treatment (see notice on this label).

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P501 Dispose of contents and container in accordance with local, regional and national regulations.

# 3. Composition / Information on Ingredients

Date Printed: 4/4/2025 Page 2 / 5

### HAZARDOUS SUBSTANCES

<u>Chemical Name</u>	CAS-No.	Wt.% Range	GHS Symbols	GHS Statements
Microcrystalline Hydrocarbon Wax	63231-60-7	30-60	Not Available	Not Available
Hydrocarbon Wax	8002-74-2	15-40	Not Available	Not Available
Stearic Acid	57-11-4	7.0-13	Not Available	Not Available
1-Octadecanol	112-92-5	1.0-5.0	Not Available	Not Available
1-Hexadecanol	36653-82-4	1.0-5.0	GHS06	H330
Yellow Iron Oxide	51274-00-1	1.0-5.0	Not Available	Not Available
1-Tetradecanol	112-72-1	0.1-1.0	GHS06	H330
Barium Sulfate	7727-43-7	0.1-1.0	GHS07	H332

Actual concentrations of ingredients are withheld as trade secret.

### 4. First Aid Measures

**First Aid - Eye Contact:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**First Aid - Inhalation:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**First Aid - Ingestion:** If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

### 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Aqueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed. No unusual fire or explosion hazards noted.

**Special Fire Fighting Procedures:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): Not a combustible dust.

### Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

### 7. Handling and Storage

**Handling:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing. Do not swallow.

Storage: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

Date Printed: 4/4/2025 Page 3 / 5

# 8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Microcrystalline Hydrocarbon Wax	63231-60-7	45.0	N.E.	N.E.	N.E.	N.E.
Hydrocarbon Wax	8002-74-2	35.0	2 mg/m3	N.E.	N.E.	N.E.
Stearic Acid	57-11-4	15.0	10 mg/m3	N.E.	N.E.	N.E.
1-Octadecanol	112-92-5	5.0	N.È.	N.E.	N.E.	N.E.
1-Hexadecanol	36653-82-4	5.0	N.E.	N.E.	N.E.	N.E.
Yellow Iron Oxide	51274-00-1	5.0	N.E.	N.E.	N.E.	N.E.
1-Tetradecanol	112-72-1	1.0	N.E.	N.E.	N.E.	N.E.
Barium Sulfate	7727-43-7	1.0	5 mg/m3	N.E.	15 mg/m3	N.E.

### PERSONAL PROTECTION

**Engineering Controls:** Provide general dilution of local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 (U.S.) and/or SOR/86-304 Part XII 12.13 and CSA Standard Z180.1 (Canada) requirements must be followed whenever workplace conditions warrant a respirator's use. A NIOSH/MSHA approved air purifying respirator with organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits.

Skin Protection: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

# 9. Physical and Chemical Properties

Physical State	Liquid	Decomposition Temperature, °C	N.D.	
Color	Not Yet Specified	pH	N.A.	
Odor	Mild	Kinematic Viscosity	N.D.	
Odor Threshold	Threshold N.E.	Solubility in Water	None	
Freezing Point / Melting Point, °C	N.D.	Partition Coefficient, n-octanol/water	N.D.	
Boiling Range, °C	294 - 665	Vapor Pressure	N.D.	
Flammability	Does not Support Combustion	Evaporation Rate	Slower than Ether	
Lower Explosion Limit, vol%	N.A.	Specific Gravity	0.996	
Upper Explosion Limit, vol%	N.A.	Vapor Density	Heavier than Air	
Flash Point, °C	149		N.A.	
Auto-Ignition Temperature, °C	N.D.	Particle Characteristics		

(See "Other information" Section for abbreviation legend)

Conditions to Avoid: Avoid excess heat.

10. Stability and Reactivity

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Date Printed: 4/4/2025 Page 4 / 5

Stability: This product is stable under normal storage conditions.

# 11. Toxicological Information

Effects of Overexposure - Eye Contact: Irritating, and may injure eye tissue if not removed promptly.

Effects of Overexposure - Skin Contact: Low hazard for usual industrial handling or commercial handling by trained personnel.

**Effects of Overexposure - Inhalation:** Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

**Effects of Overexposure - Ingestion:** Highly toxic. Substance may be harmful if swallowed. Aspiration hazard if swallowed; can enter lungs and cause damage.

Effects of Overexposure - Chronic Hazards: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
63231-60-7	Microcrystalline Hydrocarbon Wax	>5000 mg/kg Rat	>3600 mg/kg Rabbit	N.E.
8002-74-2	Hydrocarbon Wax	>5000 mg/kg Rat	>3600 mg/kg Rabbit	N.E.
57-11-4	Stearic Acid	4600 mg/kg Rat	>2000 mg/kg Rabbit	N.E.
112-92-5	1-Octadecanol	5000 mg/kg Rat	3000 mg/kg Rabbit	N.E.
36653-82-4	1-Hexadecanol	5000 mg/kg Rat	11300 mg/kg Rabbit	>1.5 mg/L Rat
112-72-1	1-Tetradecanol	20000 mg/kg Rat	8000 mg/kg Rabbit	>1.5 mg/L Rat
7727-43-7	Barium Sulfate	307000 mg/kg Rat	Ň.E.	N.E.

N.E. - Not Established

# 12. Ecological Information

Ecological Information: No ecotoxicity data was found for this product.

# 13. Disposal Considerations

**Disposal:** Dispose of material in accordance to local, state, and federal regulations and ordinances. EPA Hazardous Waste Number (RCRA): D005 (Barium). Dispose of in accordance with U.S. EPA 40 CFR 262 for concentrations at or above the Regulatory level. Regulatory level- 100.0 mg/L.

# 14. Transport Information

UN Number:	Domestic (USDOT) N.A.	International (IMDG) N.A.	<u>Air (IATA)</u> N.A.	TDG (Canada) N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class: Packing Group: Limited Quantity:	N.A. N.A. No	N.A. N.A. No	N.A. N.A. No	N.A. N.A. No

# 15. Regulatory Information

### U.S. Federal Regulations:

### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure)

Date Printed: 4/4/2025 Page 5 / 5

### **SARA Section 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

 Chemical Name
 CAS-No.

 Brown Iron Oxide
 12713-03-0

 Barium Sulfate
 7727-43-7

### **Toxic Substances Control Act**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

# U.S. State Regulations:

### California Proposition 65

WARNING: No Prop. 65 warning is required.

### 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 1 Physical Hazard: 0 Personal Protection: X

**NFPA RATINGS** 

Health: 2 Flammability: 1 Instability: 0

Volatile Organic Compounds: 0 g/L SDS REVISION DATE: 4/4/2025

**REASON FOR REVISION:** 

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.