Page 1 / 5 Date Printed: 10/18/2024

Safety Data Sheet



* Trusted Quality Since 1921 * www.rustoleum.com

Revision Date:

Supercedes Date:

1. Identification

CC 6 X 3PK 1.48KG MOISTURE GRAB Product Name:

HANG FF

Product Identifier: 396759

Recommended Use: Desiccant

Rust-Oleum Canada (ROCA) Supplier:

200 Confederation Parkway Concord, ON L4K 4T8

Canada

Phone: 1-800-387-3625

Preparer: Regulatory Department

24 Hour Hotline: 847-367-7700 **Emergency Telephone:**

CORPORATION

Rust-Oleum Canada (ROCA) Manufacturer:

200 Confederation Parkway Concord, ON L4K 4T8

Canada

10/18/2024

New SDS

Phone: 1-800-387-3625

2. Hazards Identification

Classification

Symbol(s) of Product



Signal Word Warning

GHS Hazard Statements

Acute Toxicity, Oral, category 4 H302 Harmful if swallowed. Eye Irritation, category 2A H319 Causes serious eye irritation.

GHS Label Precautionary Statements

P264 Wash thoroughly after handling.

P280 Wear protective gloves / protective clothing / eye protection / face protection.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present

and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P330 Rinse mouth.

P337+P317 If eye irritation persists: Get medical help.

P501 Dispose of contents and container in accordance with local, regional and national regulations.

GHS SDS Precautionary Statements

P270 Do not eat, drink or smoke when using this product.

3. Composition / Information on Ingredients

Date Printed: 10/18/2024 Page 2 / 5

HAZARDOUS SUBSTANCES

Chemical Name	CAS-No.	<u>Wt.%</u> <u>Range</u>	GHS Symbols	GHS Statements
Calcium Chloride	10043-52-4	50-75	GHS07	H302-319
Sodium Polyacrylate	9003-04-7	2.5-10	Not Available	Not Available

4. First-Aid Measures

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. If swallowed, get medical attention.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: None Known

Unusual Fire and Explosion Hazards: Keep containers tightly closed. No unusual fire or explosion hazards noted.

Special Fire Fighting Procedures: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): Not a combustible dust.

6. Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Local authorities should be advised if significant spillages cannot be contained.

7. Handling and Storage

Handling: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Do not get in eyes, on skin or clothing. Do not swallow.

Storage: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Calcium Chloride	10043-52-4	70.0	N.E.	N.E.	N.E.	N.E.
Sodium Polyacrylate	9003-04-7	10.0	N.E.	N.E.	N.E.	N.E.

PERSONAL PROTECTION

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Date Printed: 10/18/2024 Page 3 / 5

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 (U.S.) and/or SOR/86-304 Part XII 12.13 and CSA Standard Z180.1 (Canada) requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Appearance: Solid **Physical State:** Liquid Odor: Solvent Like Odor Threshold: N.E. Specific Gravity: pH: N.A. 2.023 Freeze Point, °C: Viscosity: N.D. N.D. Partition Coefficient, n-octanol/ Solubility in Water: Slight N.D. water: Decomposition Temp., °C: N.D. Boiling Range, °C: 537 - 537 **Explosive Limits, vol%:** N.A. - N.A. Flammability: Flash Point, °C: Does not Support Combustion 537 **Evaporation Rate:** Auto-Ignition Temp., °C: Slower than Ether N.D. Vapor Density: Vapor Pressure: Heavier than Air N.D.

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions. **Stability:** This product is stable under normal storage conditions.

11. Toxicological Information

Effects of Overexposure - Eye Contact: Can cause severe eye irritation. Causes eye and skin irritation which may lead to dermatitis with repeated exposures. Irritating, and may injure eye tissue if not removed promptly.

Effects of Overexposure - Skin Contact: Low hazard for usual industrial handling or commercial handling by trained personnel.

Effects of Overexposure - Inhalation: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

Effects of Overexposure - Ingestion: Harmful if swallowed.

Effects of Overexposure - Chronic Hazards: No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

 CAS-No.
 Chemical Name
 Oral LD50
 Dermal LD50
 Vapor LC50

 10043-52-4
 Calcium Chloride
 1000 mg/kg Rat
 >5000 mg/kg Rabbit
 N.E.

 9003-04-7
 Sodium Polyacrylate
 40000 mg/kg Rat
 N.E.
 N.E.

N.E. - Not Established

12. Ecological Information

Ecological Information: No ecotoxicity data was found for this product.

13. Disposal Information

Disposal: Dispose of material in accordance to local, state, and federal regulations and ordinances.

Date Printed: 10/18/2024 Page 4 / 5

14. Transport Information

Domestic (USDOT) International (IMDG) Air (IATA) TDG (Canada) **UN Number:** N.A. N.A. N.A. N.A. **Proper Shipping Name:** Not Regulated Not Regulated Not Regulated Not Regulated **Hazard Class:** N.A. N.A. N.A. N.A. **Packing Group:** N.A. N.A. N.A. N.A.

Nο

Nο

Nο

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Serious eye damage or eye irritation

Nο

SARA Section 313

Limited Quantity:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

California Proposition 65

WARNING: No Prop. 65 warning is required.

16. Other Information

HMIS RATINGS

Health: 2* Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 1 Instability: 0

Volatile Organic Compounds: 0.00%

SDS REVISION DATE: 10/18/2024

REASON FOR REVISION:

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

Date Printed: 10/18/2024 Page 5 / 5

Rust-Oleum Canada believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Canada makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.