Date Printed: 4/26/2012 Page 1 / 4

# Material Safety Data Sheet

24 Hour Assistance: 1-847-367-7700

Rust-Oleum Corp. www.rustoleum.com

## 1. Identification

TRANSF 24PK HP LG CNTR TP COAT A BRT Revision Date: Product Name: 4/26/2012

STK

**Identification Number:** 258011

Product Use/Class: Topcoat/ Activator Part B

Rust-Oleum Corporation Supplier:

11 Hawthorn Parkway Vernon Hills, IL 60061

**USA** 

**Rust-Oleum Corporation** Manufacturer:

> 11 Hawthorn Parkway Vernon Hills, IL 60061

**USA** 

Preparer: Regulatory Department

## 2. Hazard Identification

EMERGENCY OVERVIEW: Causes severe skin and eye burns. Harmful if swallowed. Causes eye burns. Causes skin irritation. May cause allergic skin reaction.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Extremely irritating to the eyes and may cause severe damage, including blindness. Causes eye burns.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Causes skin burns. Contact causes skin irritation. May cause skin sensitization, an allergic reaction, which becomes evident on re-exposure to this material.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High vapor concentrations are irritating to the eyes, nose, throat and lungs.

EFFECTS OF OVEREXPOSURE - INGESTION: Can burn mouth, throat and stomach. Aspiration hazard if swallowed; can enter lungs and cause damage.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

# 3. Composition/Information On Ingredients

| Chemical Name | CAS-No.     | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|---------------|-------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Amine         | Proprietary | 105.0                 | N.E.              | N.E.               | N.E.         | N.E.                 |

### 4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

Date Printed: 4/26/2012 Page 2 / 4

# 5. Fire-fighting Measures

Flash Point, °F 199 (Setaflash)

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Combustion generates toxic fumes of carbon monoxide, carbon dioxide and other

gases.

SPECIAL FIREFIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance.

#### 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

# 7. Handling and Storage

HANDLING: Wash thoroughly after handling. Use with adequate ventilation. Avoid prolonged or repeated contact with skin.

STORAGE: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame.

# 8. Exposure Controls/Personal Protection

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

# 9. Physical and Chemical Properties

Vapor Density HEAVIER THAN AIR Odor: Solvent Like

Appearance: Liquid Evaporation Rate: Slower than Ether

Solubility in Water:SlightFreeze Point:N.D.Specific Gravity:0.950pH:N.A.

Physical State: Liquid

(See section 16 for abbreviation legend)

## 10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid all possible sources of ignition.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Date Printed: 4/26/2012 Page 3 / 4

**HAZARDOUS DECOMPOSITION:** By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

**STABILITY:** This product is stable under normal storage conditions.

## 11. Toxicological Information

| Chemical Name | <u>LD50</u>            | LC50 |
|---------------|------------------------|------|
| Amine         | 3500 mg/kg (Rat, Oral) | N.E. |

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

# 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state and federal regulations and ordinances. Do not allow to enter storm drains or sewer systems.

# 14. Transport Information

|                       | Domestic (USDOT)   | International (IMDG)          | Air (IATA)                    |
|-----------------------|--------------------|-------------------------------|-------------------------------|
| Proper Shipping Name: | Consumer Commodity | Paint, Paint Related Material | Paint, Paint Related Material |
| Hazard Class:         | ORM-D              | 8                             | 8                             |
| UN Number:            | N.A.               | UN3066                        | UN3066                        |
| Packing Group:        | N.A.               | II                            | II                            |
| Limited Quantity:     | No                 | Yes                           | No                            |

# 15. Regulatory Information

## U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard

#### **SARA SECTION 313:**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### TOXIC SUBSTANCES CONTROL ACT:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b)components exist in this product.

Date Printed: 4/26/2012 Page 4 / 4

# International Regulations:

#### **CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

Canadian WHMIS Class: B3 D2B E

### 16. Other Information

**HMIS Ratings:** 

Health: 3\* Flammability: 2 Physical Hazard: 0 Personal Protection: X

NFPA Ratings:

Health: 3 Flammability: 2 Instability 1

VOLATILE ORGANIC COMPOUNDS, g/L: 0

**REASON FOR REVISION:** Regulatory Update

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.