Date Printed: 5/15/2017 Page 1 / 5

Safety Data Sheet



1. Identification

Product Name: NEVERWET DRUM NEVERWET OEM DWR - 55 GALLONS

Revision Date:

5/15/2017

Product Identifier: 316733

Supercedes Date: 5

5/12/2017

Product Use/Class: Textile finishing

Supplier: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Manufacturer: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Rust-Oleum Consumer Brands Canada

(RCBC)

200 Confederation Parkway Concord, ON L4K 4T8

Canada

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 847-367-7700

2. Hazard Identification

Classification

Symbol(s) of Product







Signal Word Danger

Possible Hazards

91% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

Acute Toxicity, Inhalation, category 4 H332 Harmful if inhaled.

Carcinogenicity, category 1B H350 May cause cancer.

Flammable Liquid, category 3 H226 Flammable liquid and vapour.

Germ Cell Mutagenicity, category 1B H340 May cause genetic defects.

Reproductive Toxicity, category 1A H360 May damage fertility or the unborn child.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P233 Keep container tightly closed.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray.
P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

Date Printed: 5/15/2017 Page 2 / 5

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P370+P378 In case of fire: Use alcohol film forming foam, carbon dioxide, dry chemical, dry sand to

extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local, regional and national regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

3. Composition/Information On Ingredients

HAZARDOUS SUBSTANCES

| Chemical Name | CAS-No. | <u>Wt.%</u> | GHS Symbols | GHS Statements |
|-----------------------------|------------|-------------|-----------------------|----------------|
| 1-Methoxy-2-Propyl Acetate | 108-65-6 | 68 | GHS02 | H226 |
| Naphtha, Hydrotreated Heavy | 64742-48-9 | 23 | GHS08 | H304-340-350 |
| Diacetone Alcohol | 123-42-2 | 5.0 | GHS06 | H319-331 |
| 2-Methoxy-1-Propyl Acetate | 70657-70-4 | 0.2 | GHS02-GHS07- GHS08 | H226-335-360 |

4. First-aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

FIRST AID - SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, get medical attention.

5. Fire-fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Combustible liquid and vapor. No unusual fire or explosion hazards noted.

SPECIAL FIREFIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

7. Handling and Storage

Date Printed: 5/15/2017 Page 3 / 5

HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Avoid excess heat.

8. Exposure Controls/Personal Protection

| Chemical Name | CAS-No. | Weight % Less Than | ACGIH TLV- TWA | ACGIH TLV- STEL | OSHA PEL-TWA | OSHA PEL- CEILING |
|-----------------------------|------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| 1-Methoxy-2-Propyl Acetate | 108-65-6 | 70.0 | N.E. | N.E. | N.E. | N.E. |
| Naphtha, Hydrotreated Heavy | 64742-48-9 | 25.0 | N.E. | N.E. | N.E. | N.E. |
| Diacetone Alcohol | 123-42-2 | 5.0 | 50 ppm | N.E. | 50 ppm | N.E. |
| 2-Methoxy-1-Propyl Acetate | 70657-70-4 | 1.0 | N.E. | N.E. | N.E. | N.E. |

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

9. Physical and Chemical Properties

| Appearance: | Liquid | Physical State: | Liquid |
|-------------------------|---------------------|-----------------------------------|-----------|
| Odor: | Solvent Like | Odor Threshold: | N.E. |
| Relative Density: | 0.907 | pH: | N.A. |
| Freeze Point, °C: | N.D. | Viscosity: | N.D. |
| Solubility in Water: | Slight | Partition Coefficient, n-octanol/ | N.D. |
| Decompostion Temp., °C: | N.D. | water: | N.D. |
| Boiling Range, °C: | 100 - 179 | Explosive Limits, vol%: | 0.7 - 7.0 |
| Flammability: | Supports Combustion | Flash Point, °C: | 42 |
| Evaporation Rate: | Slower than Ether | Auto-ignition Temp., °C: | N.D. |
| Vapor Density: | Heavier than Air | Vapor Pressure: | N.D. |

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Substance causes moderate eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation.

EFFECTS OF OVEREXPOSURE - INHALATION: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to the nose, throat and respiratory tract. Harmful if swallowed.

Date Printed: 5/15/2017 Page 4 / 5

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 |
|------------|-----------------------------|-----------------|--------------------|----------------|
| 108-65-6 | 1-Methoxy-2-Propyl Acetate | 8532 mg/kg Rat | >5000 mg/kg Rabbit | N.I. |
| 64742-48-9 | Naphtha, Hydrotreated Heavy | >5000 mg/kg Rat | >3160 mg/kg Rabbit | N.I. |
| 123-42-2 | Diacetone Alcohol | >4000 mg/kg Rat | 13630 mg/kg Rabbit | >7.23 mg/L Rat |

N.I. - No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

14. Transport Information

| | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u> | TDG (Canada) |
|-----------------------|------------------|--|---|---------------|
| UN Number: | N.A. | 1993 | 1993 | N.A. |
| Proper Shipping Name: | Not Regulated | Flammable Liquid, n.o.s. (Petroleum Distillates, Hydrotreated Heavy) | Flammable Liquid, n.o.s. (Petroleum Distillates, Hydrotreated Heavy) | Not Regulated |
| Hazard Class: | N.A. | 3 | 3 | N.A. |
| Packing Group: | N.A. | III | III | N.A. |
| Limited Quantity: | No | No | Cargo Aircraft Only | No |

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

Date Printed: 5/15/2017 Page 5 / 5

16. Other Information

HMIS RATINGS

Health: 2* Flammability: 2 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 2 Instability 0

VOLATILE ORGANIC COMPOUNDS, g/L: 878

SDS REVISION DATE: 5/15/2017

REASON FOR REVISION:

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.