Date Printed: 8/20/2015 Page 1 / 4

# Safety Data Sheet



#### 1. Identification

Product Name: TSTRS 6PK 2OZ OPAQUE RED ACRYLIC Revision Date: 8/18/2015

Product Identifier: 9446 Supercedes Date: New SDS

Product Use/Class: Aztek Airbrush Paint/Water-Based

Acrylic

Supplier: The Testors Corporation

440 Blackhawk Park Drive

Rockford, IL 61104

**USA** 

Preparer: Regulatory Department

**Emergency Telephone:** 24 Hour Hotline: 847-367-7700

Manufacturer:

The Testors Corporation 440 Blackhawk Park Drive

Rockford, IL 61104

USA

#### 2. Hazard Identification

Classification

Symbol(s) of Product

Not a hazardous substance or mixture.

Signal Word

No Signal Word has been assigned.

# 3. Composition/Information On Ingredients

#### **HAZARDOUS SUBSTANCES**

Chemical Name	CAS-No.	Wt.% Range	GHS Symbols	GHS Statements
Propylene Glycol Monobutyl Ether	5131-66-8	2.5-10	GHS07	H302-315-319
Dipropylene Glycol Monobutyl Ether	29911-28-2	1.0-2.5	No Information	No Information
2,2,4-Trimethyl-1,3-Pentanediol Diisobutyrate	6846-50-0	1.0-2.5	No Information	No Information
Hydrous Magnesium Silicate	14807-96-6	1.0-2.5	No Information	No Information

#### 4. First-aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

Date Printed: 8/20/2015 Page 2 / 4

**FIRST AID - INGESTION:** If swallowed, rinse mouth with water. If feeling unwell, get medical attention. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention.

## 5. Fire-fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

#### 6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

STORAGE: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

## 8. Exposure Controls/Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Propylene Glycol Monobutyl Ether	5131-66-8	10.0	N.E.	N.E.	N.E.	N.E.
Dipropylene Glycol Monobutyl Ether	29911-28-2	5.0	N.E.	N.E.	N.E.	N.E.
2,2,4-Trimethyl-1,3-Pentanediol Diisobutyrate	6846-50-0	5.0	N.E.	N.E.	N.E.	N.E.
Hydrous Magnesium Silicate	14807-96-6	5.0	2 mg/m3	N.E.	N.E.	N.E.

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Date Printed: 8/20/2015 Page 3 / 4

N.D.

## 9. Physical and Chemical Properties

Appearance:LiquidPhysical State:LiquidOdor:Solvent LikeOdor Threshold:N.E.Relative Density:1.029pH:N.D.

Freeze Point, °C: N.D. Viscosity: No Information

Solubility in Water: Miscible Partition Coefficient, n-octanol/

Decompostion Temp., °C: N.D. water:

Boiling Range, °C: 93 - 281 Explosive Limits, vol%: 2.4 - 17.4

Flammability:Does not Support CombustionFlash Point, °C:94Evaporation Rate:Slower than EtherAuto-ignition Temp., °C:N.D.Vapor Density:Heavier than AirVapor Pressure:N.D.

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

**INCOMPATIBILITY:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

## 11. Toxicological information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** No Information

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
5131-66-8	Propylene Glycol Monobutyl Ether	1900 mg/kg Rat	N.I.	N.I.
6846-50-0	2,2,4-Trimethyl-1,3-Pentanediol Diisobutyrate	>3200 mg/kg Rat	N.I.	N.I.

N.I. - No Information

# 12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL INFORMATION:** Dispose of material in accordance to local, state, and federal regulations and ordinances. Do not allow to enter waterways, wastewater, soil, storm drains or sewer systems.

Date Printed: 8/20/2015 Page 4 / 4

## 14. Transport Information

	Domestic (USDOT)	International (IMDG)	<u>Air (IATA)</u>	TDG (Canada)
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No

## 15. Regulatory Information

## U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Fire Hazard, Reactive Hazard, Acute Health Hazard, Chronic Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

#### 16. Other Information

**HMIS RATINGS** 

Health: 1 Flammability: 1 Physical Hazard: 0 Personal Protection: X

**NFPA RATINGS** 

Health: 1 Flammability: 1 Instability 0

VOLATILE ORGANIC COMPOUNDS, g/L: 403

SDS REVISION DATE: 8/18/2015

**REASON FOR REVISION:** 

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.