



Revision Date: 5/22/2023

## Rust-Oleum Industrial Flooring Multi Component Product Information Sheet

**370920 CONSAV 6700 EPOXY SAFTEY GREEN 1G KIT is a multi component product composed of the following individual chemical components:**

375770A SAFETY GREEN BASE PART A

80201 6700 PART B ACTIVATOR

SDSs for each component follow this cover sheet.

### Transportation Information

|   | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u>      | <u>TDG (Canada)</u>    |
|---|-------------------------|-----------------------------|------------------------|------------------------|
| UN Number:                                      | 3066                    | 3066                        | 3066                   | 3066                   |
| Proper Shipping Name:                           | Paint Related Material  | Paint Related Material      | Paint Related Material | Paint Related Material |
| Hazard Class:                                   | 8                       | 8                           | 8                      | 8                      |
| Packing Group:                                  | II                      | II                          | II                     | II                     |
| Limited Quantity:                               | No                      | No                          | Cargo Aircraft Only    | No                     |
| Finished Good Schedule B Harmonized Tariff Code | 3907.30.0000            |                             |                        |                        |

# Safety Data Sheet



## 1. Identification

|                             |  |                         |  |
|-----------------------------|--|-------------------------|--|
| <b>Product Name:</b>        | SAFETY GREEN BASE PART A   | <b>Revision Date:</b>   | 5/22/2023  |
| <b>Product Identifier:</b>  | 375770A  | <b>Supersedes Date:</b> | 1/10/2022  |
| <b>Recommended Use:</b>     | SLE 100% Solids/ Part A Epoxy Resin  |                         |  |
| <b>Supplier:</b>            | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA | <b>Manufacturer:</b>    | Rust-Oleum Corporation<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
| <b>Preparer:</b>            | Regulatory Department  |                         |  |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 847-367-7700  |                         |  |

## 2. Hazards Identification

### Classification

#### Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

22% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### GHS HAZARD STATEMENTS

|  |      |   |
|--|------|---|
| Skin Irritation, category 2            | H315 | Causes skin irritation.                   |
| Skin Sensitizer, category 1            | H317 | May cause an allergic skin reaction.      |
| Eye Irritation, category 2A            | H319 | Causes serious eye irritation.            |
| STOT, Single Exposure, category 3, RTI | H335 | May cause respiratory irritation.         |
| Reproductive Toxicity, category 1B     | H360 | May damage fertility or the unborn child. |

#### GHS LABEL PRECAUTIONARY STATEMENTS

|      |  |
|------|--|
| P201 | Obtain special instructions before use.  |
| P261 | Avoid breathing dust/fume/gas/mist/vapors/spray.   |
| P264 | Wash hands thoroughly after handling.  |
| P271 | Use only outdoors or in a well-ventilated area.  |
| P272 | Contaminated work clothing should not be allowed out of the workplace.                     |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.                 |
| P312 | Call a POISON CENTER or doctor/physician if you feel unwell.                               |
| P321 | For specific treatment see label.  |
| P405 | Store locked up.   |
| P501 | Dispose of contents/container in accordance with local, regional and national regulations. |

|                |  |
|----------------|--|
| P302+P352      | IF ON SKIN: Wash with plenty of soap and water.  |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P362+P364      | Take off contaminated clothing and wash it before reuse.   |

**GHS SDS PRECAUTIONARY STATEMENTS**

P363 Wash contaminated clothing before reuse.

### 3. Composition / Information on Ingredients

**HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>                  | <u>CAS-No.</u> | <u>Wt.%<br/>Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|---------------------------------------|----------------|-----------------------|--------------------|-----------------------|
| Epichlorohydrin-Bisphenol A Resin     | 25068-38-6     | 50-75                 | GHS07              | H315-317-319-335      |
| Hydrous Magnesium Silicate            | 14807-96-6     | 10-25                 | Not Available      | Not Available         |
| Tetrahydro-2-Furanmethanol            | 97-99-4        | 2.5-10                | GHS07-GHS08        | H302-319-360          |
| Titanium Dioxide                      | 13463-67-7     | 2.5-10                | Not Available      | Not Available         |
| 3-(Glycidyloxypropyl)trimethoxysilane | 2530-83-8      | 0.1-1.0               | Not Available      | Not Available         |
| Amorphous Silica                      | 7631-86-9      | 0.1-1.0               | Not Available      | Not Available         |
| C.I. Pigment Yellow 14                | 5468-75-7      | 0.1-1.0               | GHS06              | H330                  |
| Crystalline Silica / Quartz           | 14808-60-7     | 0.1-1.0               | Not Available      | Not Available         |
| Dodecamethylcyclohexasiloxane         | 540-97-6       | <0.1                  | Not Available      | Not Available         |

### 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

### 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

**Special Fire and Explosion Hazard (Combustible Dust):** No Information

## 6. Accidental Release Measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use.

**Advice on Safe Handling of Combustible Dust:** No Information

## 8. Exposure Controls / Personal Protection

| Chemical Name                          | CAS-No.    | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|--|------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Epichlorohydrin-Bisphenol A Resin      | 25068-38-6 | 65.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| Hydrous Magnesium Silicate             | 14807-96-6 | 15.0                  | 2 mg/m3           | N.E.               | 20 mppcf     | N.E.                 |
| Tetrahydro-2-Furanmethanol             | 97-99-4    | 10.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| Titanium Dioxide                       | 13463-67-7 | 10.0                  | 0.2 mg/m3         | N.E.               | 15 mg/m3     | N.E.                 |
| 3-(Glycidyloxypropyl) trimethoxysilane | 2530-83-8  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Amorphous Silica                       | 7631-86-9  | 1.0                   | N.E.              | N.E.               | 50 µg/m3     | N.E.                 |
| C.I. Pigment Yellow 14                 | 5468-75-7  | 1.0                   | N.E.              | N.E.               | N.E.         | N.E.                 |
| Crystalline Silica / Quartz            | 14808-60-7 | 1.0                   | 0.025 mg/m3       | N.E.               | 50 µg/m3     | N.E.                 |
| Dodecamethylcyclotetrasiloxane         | 540-97-6   | 0.1                   | N.E.              | N.E.               | N.E.         | N.E.                 |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

**Engineering Measures for Combustible Dust:** No Information

## 9. Physical and Chemical Properties

|                                 |                             |  |           |
|---------------------------------|-----------------------------|--|-----------|
| <b>Appearance:</b>              | Liquid                      | <b>Physical State:</b>                         | Liquid    |
| <b>Odor:</b>                    | Solvent Like                | <b>Odor Threshold:</b>                         | N.E.      |
| <b>Specific Gravity:</b>        | 1.348                       | <b>pH:</b>                                     | N.A.      |
| <b>Freeze Point, °C:</b>        | N.D.                        | <b>Viscosity:</b>                              | N.D.      |
| <b>Solubility in Water:</b>     | Slight                      | <b>Partition Coefficient, n-octanol/water:</b> | N.D.      |
| <b>Decomposition Temp., °C:</b> | N.D.                        | <b>Explosive Limits, vol%:</b>                 | 1.5 - 9.7 |
| <b>Boiling Range, °C:</b>       | 178 - 2,500                 | <b>Flash Point, °C:</b>                        | 94        |
| <b>Flammability:</b>            | Does not Support Combustion | <b>Auto-Ignition Temp., °C:</b>                | N.D.      |
| <b>Evaporation Rate:</b>        | Slower than Ether           | <b>Vapor Pressure:</b>                         | N.D.      |
| <b>Vapor Density:</b>           | Heavier than Air            |  |           |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**Conditions to Avoid:** Avoid excess heat. Keep from freezing.

**Incompatibility:** Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**Hazardous Decomposition:** When heated to decomposition, it emits acrid smoke and irritating fumes.

**Hazardous Polymerization:** Will not occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

## 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Irritating, and may injure eye tissue if not removed promptly.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Low hazard for usual industrial handling or commercial handling by trained personnel.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. Constituents of this product include crystalline silica dust which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010)

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>                  | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|---------------------------------------|------------------|--------------------|-------------------|
| 25068-38-6     | Epichlorohydrin-Bisphenol A Resin     | 11400 mg/kg Rat  | >5000              | 25 g/L            |
| 14807-96-6     | Hydrous Magnesium Silicate            | 6000             | N.E.               | 30                |
| 97-99-4        | Tetrahydro-2-Furanmethanol            | 1600 mg/kg Rat   | N.E.               | N.E.              |
| 13463-67-7     | Titanium Dioxide                      | >10000 mg/kg Rat | 6000               | N.E.              |
| 2530-83-8      | 3-(Glycidyloxypropyl)trimethoxysilane | 7010 mg/kg Rat   | 4252 mg/kg Rabbit  | N.E.              |
| 7631-86-9      | Amorphous Silica                      | 7900 mg/kg Rat   | >5000 mg/kg Rabbit | 25 mg/L           |
| 5468-75-7      | C.I. Pigment Yellow 14                | 5000 mg/kg Rat   | N.E.               | N.E.              |
| 14808-60-7     | Crystalline Silica / Quartz           | 5500 mg/kg Rat   | 5500               | 100 mg/L          |
| 540-97-6       | Dodecamethylcyclotetrasiloxane        | 50000 mg/kg Rat  | >2000 mg/kg Rat    | N.E.              |

N.E. - Not Established

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components. No ecotoxicity data was found for this product.

### 13. Disposal Information

**DISPOSAL:** Dispose of material in accordance to local, state, and federal regulations and ordinances.

### 14. Transport Information

|                       | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u> | <u>TDG (Canada)</u> |
|-----------------------|-------------------------|-----------------------------|-------------------|---------------------|
| UN Number:            | N.A.                    | N.A.                        | N.A.              | N.A.                |
| Proper Shipping Name: | Not Regulated           | Not Regulated               | Not Regulated     | Not Regulated       |
| Hazard Class:         | N.A.                    | N.A.                        | N.A.              | N.A.                |
| Packing Group:        | N.A.                    | N.A.                        | N.A.              | N.A.                |
| Limited Quantity:     | No                      | No                          | No                | No                  |

### 15. Regulatory Information

#### U.S. Federal Regulations:

##### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

##### SARA Section 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u>       | <u>CAS-No.</u> |
|----------------------------|----------------|
| Pigment Green 7            | 1328-53-6      |
| Copper Phthalocyanine Blue | 12239-87-1     |

##### Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

#### U.S. State Regulations:

##### California Proposition 65

**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

**16. Other Information****HMIS RATINGS**

Health: 2\*      Flammability: 1      Physical Hazard: 0      Personal Protection: X

**NFPA RATINGS**

Health: 2      Flammability: 1      Instability: 0

Volatile Organic Compounds: 110 g/L

SDS REVISION DATE: 5/22/2023

REASON FOR REVISION: Product Composition Changed  
Substance and/or Product Properties Changed in  
Section(s):  
08 - Exposure Controls / Personal Protection  
11 - Toxicological Information  
15 - Regulatory Information  
Substance Hazard Threshold % Changed  
Substance Hazardous Flag Changed  
Revision Statement(s) Changed

**Legend:** N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

# Safety Data Sheet



www.toughandeasyfloors.com

## 1. Identification

|                             |  |                         |  |
|-----------------------------|--|-------------------------|--|
| <b>Product Name:</b>        | 6700 PART B ACTIVATOR  | <b>Revision Date:</b>   | 7/1/2021   |
| <b>Product Identifier:</b>  | 80201  | <b>Supersedes Date:</b> | 4/15/2020  |
| <b>Recommended Use:</b>     | Part B Activator   |                         |  |
| <b>Supplier:</b>            | Rust-Oleum Industrial Flooring<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA | <b>Manufacturer:</b>    | Rust-Oleum Industrial Flooring<br>11 Hawthorn Parkway<br>Vernon Hills, IL 60061<br>USA |
| <b>Preparer:</b>            | Regulatory Department  |                         |  |
| <b>Emergency Telephone:</b> | 24 Hour Hotline: 847-367-7700  |                         |  |

## 2. Hazards Identification

### Classification

#### Symbol(s) of Product



#### Signal Word

Danger

#### Possible Hazards

78% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### GHS HAZARD STATEMENTS

|  |      |  |
|--|------|--|
| Eye Irritation, category 2B            | H320 | Causes eye irritation                    |
| Acute Toxicity, Oral, category 4       | H302 | Harmful if swallowed.                    |
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled.                      |
| Skin Corrosion, category 1             | H314 | Causes severe skin burns and eye damage. |

#### GHS LABEL PRECAUTIONARY STATEMENTS

|                |  |
|----------------|--|
| P260           | Do not breathe dust/fume/gas/mist/vapors/spray.  |
| P264           | Wash hands thoroughly after handling.  |
| P271           | Use only outdoors or in a well-ventilated area.  |
| P280           | Wear protective gloves/protective clothing/eye protection/face protection.                 |
| P310           | If exposed immediately call a POISON CENTER or doctor/physician.                           |
| P321           | For specific treatment see label.  |
| P405           | Store locked up.   |
| P501           | Dispose of contents/container in accordance with local, regional and national regulations. |
| P301+P312      | IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.                 |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.   |



P303+P361+P353

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313

If eye irritation persists: Get medical advice/attention.

**GHS SDS PRECAUTIONARY STATEMENTS**

P270

Do not eat, drink or smoke when using this product.

**3. Composition / Information on Ingredients****HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>     | <u>CAS-No.</u>   | <u>Wt.%<br/>Range</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|--------------------------|------------------|-----------------------|--------------------|-----------------------|
| Cycloaliphatic Polyamine | 1220986-58<br>-2 | 50-75                 | Not Available      | Not Available         |
| Benzyl Alcohol           | 100-51-6         | 10-25                 | GHS07              | H302-312-320-332      |
| Polyethylene Wax         | 2549-93-1        | 10-25                 | GHS05-GHS06        | H302-311-314          |

**4. First-Aid Measures**

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Immediately flush skin with plenty of water for at least 15 minutes while removing clothing. Get medical attention immediately. Wash clothing separately before reuse.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

**5. Fire-Fighting Measures**

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Keep containers tightly closed. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Containers can rupture and release highly toxic material if exposed to heat. Substance is non-combustible but reacts with many metals to form explosive hydrogen gas. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

**Special Fire and Explosion Hazard (Combustible Dust):** No Information

**6. Accidental Release Measures**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. Avoid runoff into sewers and waterways. Provide ventilation and approach spill from upwind using proper personal protective equipment as indicated in Section 8. Carefully neutralize spill with sodium bicarbonate (NaHCO<sub>3</sub>).

**7. Handling and Storage**

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use.

**Advice on Safe Handling of Combustible Dust:** No Information

## 8. Exposure Controls / Personal Protection

| Chemical Name            | CAS-No.      | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|--------------------------|--------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Cycloaliphatic Polyamine | 1220986-58-2 | 70.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| Benzyl Alcohol           | 100-51-6     | 25.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |
| Polyethylene Wax         | 2549-93-1    | 15.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |

### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Provide general dilution of local exhaust ventilation in volume and pattern to keep TLV of hazardous ingredients below acceptable limits. Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**SKIN PROTECTION:** Use impervious gloves to prevent skin contact and absorption of this material through the skin.

**EYE PROTECTION:** Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

**Engineering Measures for Combustible Dust:** No Information

## 9. Physical and Chemical Properties

|                                 |                             |   |             |
|---------------------------------|-----------------------------|---|-------------|
| <b>Appearance:</b>              | Liquid                      | <b>Physical State:</b>                              | Liquid      |
| <b>Odor:</b>                    | Ammonia Like                | <b>Odor Threshold:</b>                              | N.E.        |
| <b>Specific Gravity:</b>        | 1.021                       | <b>pH:</b>  | N.D.        |
| <b>Freeze Point, °C:</b>        | N.D.                        | <b>Viscosity:</b>                                   | N.D.        |
| <b>Solubility in Water:</b>     | Slight                      | <b>Partition Coefficient, n-octanol/<br/>water:</b> | N.D.        |
| <b>Decomposition Temp., °C:</b> | N.D.                        | <b>Explosive Limits, vol%:</b>                      | N.A. - N.A. |
| <b>Boiling Range, °C:</b>       | 537 - 537                   | <b>Flash Point, °C:</b>                             | 94          |
| <b>Flammability:</b>            | Does not Support Combustion | <b>Auto-Ignition Temp., °C:</b>                     | N.D.        |
| <b>Evaporation Rate:</b>        | Slower than Ether           | <b>Vapor Pressure:</b>                              | N.D.        |
| <b>Vapor Density:</b>           | Heavier than Air            |   |             |

(See "Other information" Section for abbreviation legend)

## 10. Stability and Reactivity

**Conditions to Avoid:** Avoid contact with metals.

**Incompatibility:** Incompatible with strong oxidizing agents, strong acids and strong alkalies. Product slowly corrodes copper, aluminum, zinc, and galvanized surfaces.

**Hazardous Decomposition:** Decomposition produces hydrogen chloride, chlorine and hydrogen gases.

**Hazardous Polymerization:** Will not occur under normal conditions.

**Stability:** This product is stable under normal storage conditions.

## 11. Toxicological Information

**EFFECTS OF OVEREXPOSURE - EYE CONTACT:** Substance causes severe eye irritation. Injury may be permanent.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:** Severely irritating; may cause permanent skin damage.

**EFFECTS OF OVEREXPOSURE - INHALATION:** Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

**EFFECTS OF OVEREXPOSURE - INGESTION:** Corrosive and may cause severe and permanent damage to mouth, throat and stomach. Substance may be harmful if swallowed.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:** Repeated exposure to low concentrations of HCl vapor or mist may cause bleeding of nose and gums.

**PRIMARY ROUTE(S) OF ENTRY:** Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Chemical Name</u>     | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|--------------------------|------------------|--------------------|-------------------|
| 1220986-58-2   | Cycloaliphatic Polyamine | N.E.             | 6000               | N.E.              |
| 100-51-6       | Benzyl Alcohol           | 1230 mg/kg Rat   | 2000 mg/kg Rabbit  | 11 mg/L Rat       |
| 2549-93-1      | Polyethylene Wax         | 530 mg/kg Rat    | N.E.               | N.E.              |

N.E. - Not Established

## 12. Ecological Information

**ECOLOGICAL INFORMATION:** Product is a mixture of listed components.

## 13. Disposal Information

**DISPOSAL:** Dispose of material in accordance to local, state, and federal regulations and ordinances. RCRA Hazardous Waste: This material, when discarded or disposed of, could be a hazardous waste according to federal regulations (40 CFR 261) due to the characteristic of corrosivity (D002). Check state and local regulations for disposal requirements. Chemical additions, processing or otherwise altering this material may make the waste management information presented in this SDS incomplete, inaccurate, or otherwise inappropriate.

## 14. Transport Information

|                              | <u>Domestic (USDOT)</u> | <u>International (IMDG)</u> | <u>Air (IATA)</u>       | <u>TDG (Canada)</u>     |
|------------------------------|-------------------------|-----------------------------|-------------------------|-------------------------|
| <b>UN Number:</b>            | 3066                    | 3066                        | 3066                    | 3066                    |
| <b>Proper Shipping Name:</b> | Paint Related Materials | Paint Related Materials     | Paint Related Materials | Paint Related Materials |
| <b>Hazard Class:</b>         | 8                       | 8                           | 8                       | 8                       |
| <b>Packing Group:</b>        | II                      | II                          | II                      | II                      |
| <b>Limited Quantity:</b>     | No                      | No                          | Cargo Aircraft Only     | No                      |

## 15. Regulatory Information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Skin Corrosion or Irritation

#### SARA Section 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No SARA 313 components exist in this product.

#### Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
|----------------------|----------------|

Cycloaliphatic Polyamine

1220986-58-2

**U.S. State Regulations:****California Proposition 65****WARNING:**Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).**16. Other Information****HMIS RATINGS**

|         |    |               |   |                  |   |                      |   |
|---------|----|---------------|---|------------------|---|----------------------|---|
| Health: | 2* | Flammability: | 1 | Physical Hazard: | 0 | Personal Protection: | X |
|---------|----|---------------|---|------------------|---|----------------------|---|

**NFPA RATINGS**

|         |   |               |   |              |   |
|---------|---|---------------|---|--------------|---|
| Health: | 2 | Flammability: | 1 | Instability: | 0 |
|---------|---|---------------|---|--------------|---|

Volatile Organic Compounds: 0 g/L

SDS REVISION DATE: 7/1/2021

REASON FOR REVISION: Substance and/or Product Properties Changed in Section(s):  
15 - Regulatory Information  
Revision Statement(s) Changed

**Legend:** N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

Rust-Oleum Industrial Flooring believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Industrial Flooring makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.