# Material Safety Data Sheet

24 Hour Assistance: 1-847-367-7700 Rust-Oleum Corp. www.rustoleum.com

## Section 1 - Chemical Product / Company Information

INT DARK BROWN TEXT 5-GL CAP

Product Name: PAINT Revision Date: 09/02/2010

Identification

Number: 241784

Product Use/Class: Intermediate/Cap Paint Supplier: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Preparer: Regulatory Department

Manufacturer: Rust-Oleum Corporation

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

# Section 2 - Composition / Information On Ingredients

		Weight % Less				
Chemical Name	CAS Number	<u>Than</u>	<b>ACGIH TLV-TWA</b>	<b>ACGIH TLV-STEL</b>	OSHA PEL-TWA	OSHA PEL CEILING
Acetone	67-64-1	40.0	500 ppm	750 ppm	1000 ppm	N.E.
Alkyd Resin	PROPRIETARY	25.0	N.E.	N.E.	N.E.	N.E.
n-Butyl Acetate	123-86-4	15.0	150 ppm	200 ppm	150 ppm	N.E.
Xylene	1330-20-7	10.0	100 ppm	150 ppm	100 ppm	N.E.
Methyl Ethyl Ketone	78-93-3	10.0	200 ppm	300 ppm	200 ppm	N.E.
Propylene Glycol Monobutyl Ether	5131-66-8	5.0	N.E.	N.E.	N.E.	N.E.
Polypropylene	9003-07-0	5.0	N.E.	N.E.	5 mg/m3	N.E.
Ethylbenzene	100-41-4	5.0	100 ppm	125 ppm	100 ppm	N.E.
Carbon Black	1333-86-4	1.0	3.5 mg/m3	N.E.	3.5 mg/m3	N.E.

## Section 3 - Hazards Identification

\*\*\* Emergency Overview \*\*\*: No Information.

Effects Of Overexposure - Eye Contact: No Information.

Effects Of Overexposure - Skin Contact: No Information.

Effects Of Overexposure - Inhalation: No Information.

Effects Of Overexposure - Ingestion: No Information.

Effects Of Overexposure - Chronic Hazards: IARC lists Ethylbenzene as a possible human carcinogen (group 2B). Overexposure to xylene in laboratory animals has been associated with liver abnormalities, kidney, lung, spleen, eye and blood damage as well as reproductive disorders. Effects in humans, due to chronic overexposure, have included liver, cardiac abnormalities and nervous system damage. Overexposure to methyl ethyl ketone in laboratory animals has been associated with liver abnormalities, kidney and lung damage. Fetotoxic/embryotoxic effects from inhalation have been seen in rats exposed to >1000ppm during gestation.

Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats

experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Ingestion, Eye Contact

#### Section 4 - First Aid Measures

First Aid - Eye Contact: No Information.

First Aid - Skin Contact: No Information.

First Aid - Inhalation: No Information.

First Aid - Ingestion: No Information.

## Section 5 - Fire Fighting Measures

Flash Point: -4 F (Calculated)

Extinguishing Media: Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

Unusual Fire And Explosion Hazards: No unusual Hazards

Special Firefighting Procedures: No Information.

#### Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Isolate and dispose of in accordance with state and federal regualtions.

# Section 7 - Handling And Storage

Handling: No Information.

Storage: No Information.

# Section 8 - Exposure Controls / Personal Protection

Engineering Controls: No Information.

Respiratory Protection: No Information.

Skin Protection: No Information.

Eye Protection: No Information.

Other protective equipment: No Information.

Hygienic Practices: No Information.

## **Section 9 - Physical And Chemical Properties**

Vapor Density:Heavier than AirOdor:Solvent LikeAppearance:LiquidEvaporation Rate:Slower than Ether

Solubility in H2O: Slight Freeze Point: N.D. Specific Gravity: 0.948 PH: N.E.

Physical State: Liquid

(See section 16 for abbreviation legend)

## **Section 10 - Stability And Reactivity**

Conditions To Avoid: No Information.

Incompatibility: No Information.

Hazardous Decomposition: Will not occur under normal conditions

Hazardous Polymerization: Will not occur under normal conditions

Stability: Stable under normal conditions

## **Section 11 - Toxicological Information**

Chemical Name LD50 LC50

Acetone 5800 mg/kg (Rat) 50100 mg/m3 (Rat, 8Hr)

Alkyd Resin N.E. N.E.

n-Butyl Acetate 13100 mg/kg (Rat, Oral) 2000 ppm (Rat, Inhalation, 4 Hr) Xylene 4300 mg/kg (Rat, Oral) 5000 ppm (Rat, Inhalation, 4Hr)

Methyl Ethyl Ketone N.E. N.E.

Propylene Glycol Monobutyl Ether 2200 mg/kg (Rat, Oral) N.E. Polypropylene N.E. N.E. N.E. Ethylbenzene 3500 mg/kg (Rat, Oral) N.E.

Ethylbenzene 3500 mg/kg (Rat, Oral) N.E. Carbon Black >8000 mg/kg (Rat, Oral) N.E.

# Section 12 - Ecological Information

Ecological Information: No Information.

## Section 13 - Disposal Information

Disposal Information: Dispose of in accordance with state and federal regulations

## Section 14 - Transportation Information

	Domestic (USDOT)	International (IMDG)	Air (IATA)
Proper Shippping Name:	Paint	Paint	Paint
Hazard Class:	3	3	3
UN Number:	UN1263	UN1263	UN1263
Packing Group:	II	II	II
Limited Quantity:	No	IMDG 34-08, 3.4.7	No

## Section 15 - Regulatory Information

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD

#### **SARA Section 313:**

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

 Chemical Name
 CAS Number

 Xylene
 1330-20-7

 Methyl Ethyl Ketone
 78-93-3

 Ethylbenzene
 100-41-4

#### **Toxic Substances Control Act:**

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of TSCA 12(B) if exported from the United States:

#### U.S. State Regulations: As follows -

#### **New Jersey Right-to-Know:**

The following materials are non-hazardous, but are among the top five components in this product.

None

#### Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

None

#### International Regulations: As follows -

#### **CANADIAN WHMIS:**

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS: B2 D2A D2B

#### **Section 16 - Other Information**

**NFPA Ratings:** 

Health: 2 Flammability: 3 Instability: 0

**VOLATILE ORGANIC COMPOUNDS, g/I:** 518

**REASON FOR REVISION:** Regulatory Update

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

Rust-Oleum Corporation believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this material safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Rust-Oleum Corporation makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.