

Material Safety Data Sheet

Sierra Performance Coatings
by Rustoleum
24 Hour Assistance:
1-847-367-7700
Rust-Oleum Corp.
www.rustoleum.com

Section 1 - Chemical Product / Company Information

Product Name: INT 230H SIE 740-772 GREEN Revision Date: 08/10/2006
Identification Number: 209494
Product Use/Class: Intermediate/Sierra
Supplier: Rust-Oleum Corporation Manufacturer: Rust-Oleum Corporation
11 Hawthorn Parkway 11 Hawthorn Parkway
Vernon Hills, IL 60061 Vernon Hills, IL 60061
USA USA
Preparer: Department, Regulatory

Section 2 - Composition / Information On Ingredients

Chemical Name	CAS Number	Weight % Less Than	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL-CEILING
Toluene	108-88-3	20.0	50 PPM	150 PPM	200 PPM	300 PPM
Acetone	67-64-1	20.0	500 PPM	750 PPM	750 PPM	N.E.
Isopropyl Alcohol	67-63-0	15.0	400 PPM	500 PPM	400 PPM	N.E.

Section 3 - Hazards Identification

*** Emergency Overview ***: No Information.

Effects Of Overexposure - Eye Contact: No Information.

Effects Of Overexposure - Skin Contact: No Information.

Effects Of Overexposure - Inhalation: No Information.

Effects Of Overexposure - Ingestion: No Information.

Effects Of Overexposure - Chronic Hazards: Overexposure to toluene in laboratory animals has been associated with liver abnormalities, kidney, lung and spleen damage. Effects in humans have included liver and cardiac abnormalities.

Primary Route(s) Of Entry: Skin Contact, Skin Absorption, Inhalation, Eye Contact

Section 4 - First Aid Measures

First Aid - Eye Contact: No Information.

First Aid - Skin Contact: No Information.

First Aid - Inhalation: No Information.

First Aid - Ingestion: No Information.

Section 5 - Fire Fighting Measures

Flash Point: -4 F
(Calculated)

LOWER EXPLOSIVE LIMIT: 1.0 %
UPPER EXPLOSIVE LIMIT : 12.8 %

Extinguishing Media: Dry Chemical, Foam, Water Fog

Unusual Fire And Explosion Hazards: No Unusual Hazards

Special Firefighting Procedures: No Information.

Section 6 - Accidental Release Measures

Steps To Be Taken If Material Is Released Or Spilled: Isolate and dispose of in accordance with state and federal regulations.

Section 7 - Handling And Storage

Handling: No Information.

Storage: No Information.

Section 8 - Exposure Controls / Personal Protection

Engineering Controls: No Information.

Respiratory Protection: No Information.

Skin Protection: No Information.

Eye Protection: No Information.

Other protective equipment: No Information.

Hygienic Practices: No Information.

Section 9 - Physical And Chemical Properties

Boiling Range: 69 - 350 F
Odor: N.A.
Appearance: Liquid
Solubility in H2O: Soluble

Vapor Density: Heavier than Air
Odor Threshold:
Evaporation Rate: Slower than Ether

Freeze Point: ND
Vapor Pressure: ND
Physical State: Liquid

Specific Gravity: 0.984
PH: NE

(See section 16 for abbreviation legend)

Section 10 - Stability And Reactivity

Conditions To Avoid: No Information.

Incompatibility: No Information.

Hazardous Decomposition: Will not occur under normal conditions

Hazardous Polymerization: Will not occur under normal conditions

Stability: Stable under normal conditions

Section 11 - Toxicological Information

Product LD50: ND

Product LC50: ND

Chemical Name

Toluene

Acetone

Isopropyl Alcohol

LD50

N.D.

N.D.

5840 mg/kg (ORAL, RAT)

LC50

N.D.

N.D.

N.D.

Section 12 - Ecological Information

Ecological Information: No Information.

Section 13 - Disposal Information

Disposal Information: Dispose of in accordance with state and federal regulations

Section 14 - Transportation Information

DOT Proper Shipping Name: Paint Related Material

DOT Technical Name: ---

DOT Hazard Class: 3

DOT UN/NA Number: ----

Packing Group: II

Hazard Subclass: ---

Resp. Guide Page: ---

Section 15 - Regulatory Information

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA "Hazard Categories" promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD

SARA Section 313:

Listed below are the substances (if any) contained in this product that are subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS Number</u>
Toluene	108-88-3

Toxic Substances Control Act:

Product is a mixture of components either listed or exempt from TSCA requirements.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS Number</u>
Epoxy Resin	25036-25-3
Pigment Green 7	1328-53-6

Pennsylvania Right-to-Know:

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS Number</u>
Epoxy Resin	25036-25-3

California Proposition 65:

This product contains no listed substances known to the State of California to cause cancer and/or birth defects or other reproductive harm, at levels which would require a warning under the statute.

International Regulations: As follows -

CANADIAN WHMIS:

This MSDS has been prepared in compliance with Controlled Product Regulations except for the use of the 16 headings.

CANADIAN WHMIS CLASS: B2 D2B

Section 16 - Other Information

HMIS Ratings:

Health: 2*

Flammability: 3

Reactivity: 0

Personal Protection: H

REASON FOR REVISION: Regulatory Update**Legend:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The information contained on this MSDS has been checked and should be accurate. However, it is the responsibility of the user to comply with all Federal, State, and Local laws and regulations.