

Safety Data Sheet



www.modernmasters.com

1. Identification

Name on Label:	Modern Masters Metallic Paint Collection Exterior Satin Finish Excalibur		
Product Name:	MODMAS QT EXT MET EXCALIBUR	Revision Date:	6/5/2025
Product Identifier:	337158	Supersedes Date:	4/23/2018
Recommended Use:	Acrylic/Exterior Metallic		
Supplier:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA	Manufacturer:	Rust-Oleum Corporation 11 Hawthorn Parkway Vernon Hills, IL 60061 USA
Preparer:	Regulatory Department		
Emergency Telephone:	24 Hour Hotline: 847-367-7700		

2. Hazard Identification

Classification

Symbol(s) of Product



Signal Word
Danger

Possible Hazards

10% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS Hazard Statements

Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Reproductive Toxicity, category 1B	H360	May damage fertility or the unborn child.

GHS Label Precautionary Statements

P201	Obtain special instructions before use.
P261	Avoid breathing dust, fumes, gas, mists, vapours, or spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves, protective clothing, eye protection, and face protection.
P285	In case of inadequate ventilation wear respiratory protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P308+P313	IF exposed or concerned: Get medical advice.
P321	Specific treatment (see notice on this label).

P333+P313

If skin irritation or rash occurs: Get medical advice.

P342+P311

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P405

Store locked up.

P501

Dispose of contents and container in accordance with local, regional and national regulations.

GHS SDS Precautionary Statements

P363

Wash contaminated clothing before reuse.

3. Composition / Information on Ingredients**HAZARDOUS SUBSTANCES**

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. % Range</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
Mica	12001-26-2	3.0-7.0	Not Available	Not Available
Titanium Dioxide	13463-67-7	1.0-5.0	Not Available	Not Available
Propylene Glycol	57-55-6	1.0-5.0	Not Available	Not Available
Polypropylene Glycol	25322-69-4	1.0-5.0	Not Available	Not Available
Dipropylene Glycol Monobutyl Ether	29911-28-2	0.1-1.0	Not Available	Not Available
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate	25265-77-4	0.1-1.0	GHS06	H331
N-Methyl 2-Pyrrolidone	872-50-4	0.1-1.0	GHS07-GHS08	H315-319-332-335-360
Aqueous Ammonia	1336-21-6	0.1-1.0	GHS04-GHS05- GHS06-GHS07	H280-302-314-331-335
Ammonium Persulfate	7727-54-0	0.1-1.0	GHS03-GHS07- GHS08	H272-302+H332-315-317-319-334-335
bis(1,2,2,6,6-Pentamethyl-4-Piperidiny) Sebacate	41556-26-7	0.1-1.0	GHS07-GHS08	H317-361
Polymeric Benzotriazole	104810-48-2	0.1-1.0	GHS07	H317
Polymeric Benzotriazole	104810-47-1	0.1-1.0	GHS07	H317
Dipropylene Glycol Monomethyl Ether	34590-94-8	0.1-1.0	Not Available	Not Available

Actual concentrations of ingredients are withheld as trade secret.

4. First Aid Measures

First Aid - Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. Remove contact lenses, if present and easy to do. Continue rinsing.

First Aid - Skin Contact: Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists. Wash contaminated clothing and decontaminate footwear before reuse.

First Aid - Inhalation: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

First Aid - Ingestion: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Aqueous Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

Unusual Fire and Explosion Hazards: Keep containers tightly closed. No unusual fire or explosion hazards noted.

Special Fire Fighting Procedures: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): Not a combustible dust.

6. Accidental Release Measures

Steps to Be Taken If Material Is Released or Spilled: If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

Handling: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid prolonged or repeated contact with skin. Avoid contact with eyes, skin and clothing.

Storage: Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
Mica	12001-26-2	10.0	0.1 mg/m3	N.E.	N.E.	N.E.
Titanium Dioxide	13463-67-7	5.0	0.2 mg/m3	N.E.	15 mg/m3	N.E.
Propylene Glycol	57-55-6	5.0	N.E.	N.E.	N.E.	N.E.
Polypropylene Glycol	25322-69-4	5.0	N.E.	N.E.	N.E.	N.E.
Dipropylene Glycol Monobutyl Ether	29911-28-2	1.0	N.E.	N.E.	N.E.	N.E.
2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate	25265-77-4	1.0	N.E.	N.E.	N.E.	N.E.
N-Methyl 2-Pyrrolidone	872-50-4	1.0	N.E.	N.E.	N.E.	N.E.
Aqueous Ammonia	1336-21-6	1.0	25 ppm	35 ppm	50 ppm	N.E.
Ammonium Persulfate	7727-54-0	1.0	0.1 mg/m3	N.E.	N.E.	N.E.
bis(1,2,2,6,6-Pentamethyl-4-Piperidiny) Sebacate	41556-26-7	1.0	N.E.	N.E.	N.E.	N.E.
Polymeric Benzotriazole	104810-48-2	1.0	N.E.	N.E.	N.E.	N.E.
Polymeric Benzotriazole	104810-47-1	1.0	N.E.	N.E.	N.E.	N.E.
Dipropylene Glycol Monomethyl Ether	34590-94-8	1.0	50 ppm	N.E.	100 ppm	N.E.

PERSONAL PROTECTION

Engineering Controls: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

Respiratory Protection: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 (U.S.) and/or SOR/86-304 Part XII 12.13 and CSA Standard Z180.1 (Canada) requirements must be followed whenever workplace conditions warrant a respirator's use.

Skin Protection: Use impervious gloves to prevent skin contact and absorption of this material through the skin.

Eye Protection: Use safety eyewear designed to protect against splash of liquids.

Other Protective Equipment: Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

Hygienic Practices: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

9. Physical and Chemical Properties

Physical State	Liquid	Decomposition Temperature, °C	N.D.
Color	Gray	pH	N.A.
Odor	Mild	Kinematic Viscosity	N.D.
Odor Threshold	N.E.	Solubility in Water	Miscible
Freezing Point / Melting Point, °C	N.D.	Partition Coefficient, n-octanol/water	N.D.
Boiling Range, °C	100 - 537	Vapor Pressure	N.D.
Flammability	Does not Support Combustion	Evaporation Rate	Slower than Ether
Lower Explosion Limit, vol%	2.6	Specific Gravity	1.099
Upper Explosion Limit, vol%	12.6	Vapor Density	Heavier than Air
Flash Point, °C	94	Particle Characteristics	N.A.
Auto-Ignition Temperature, °C	N.D.		

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

Conditions to Avoid: Avoid excess heat.

Incompatibility: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

Hazardous Decomposition: When heated to decomposition, it emits acrid smoke and irritating fumes.

Hazardous Polymerization: Will not occur under normal conditions.

Stability: This product is stable under normal storage conditions.

11. Toxicological Information

Effects of Overexposure - Eye Contact: Irritating, and may injure eye tissue if not removed promptly.

Effects of Overexposure - Skin Contact: Prolonged or repeated skin contact may cause irritation. Causes skin irritation. Allergic reactions are possible. May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis). Low hazard for usual industrial handling or commercial handling by trained personnel.

Effects of Overexposure - Inhalation: High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

Effects of Overexposure - Ingestion: Substance may be harmful if swallowed.

Effects of Overexposure - Chronic Hazards: May damage fertility or the unborn child. Contains Titanium Dioxide. Titanium Dioxide is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC. No significant exposure to Titanium Dioxide is thought to occur during the use of products in which Titanium Dioxide is bound to other materials, such as in paints during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of Titanium Dioxide in the formula. (Ref: IARC Monograph, Vol. 93, 2010) Prolonged or repeated skin contact may cause dermatitis. May cause genetic defects.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
12001-26-2	Mica	N.E.	N.E.	25000
13463-67-7	Titanium Dioxide	>2000 mg/kg Rat	6000	N.E.
57-55-6	Propylene Glycol	20000 mg/kg Rat	20800 mg/kg Rabbit	>20 mg/L
25322-69-4	Polypropylene Glycol	3750 mg/kg Rat	>3000 mg/kg Rabbit	N.E.
29911-28-2	Dipropylene Glycol Monobutyl Ether	N.E.	N.E.	25
25265-77-4	2,2,4-Trimethyl-1,3-Pentanediol Monoisobutyrate	6500 mg/kg Rat	>15200 mg/kg Rat	>3.55 mg/L Rat
872-50-4	N-Methyl 2-Pyrrolidone	3914 mg/kg Rat	8000 mg/kg Rabbit	20 mg/L Rat
1336-21-6	Aqueous Ammonia	350 mg/kg Rat	N.E.	N.E.
7727-54-0	Ammonium Persulfate	495 mg/kg Rat	>10000 mg/kg Rabbit	N.E.

41556-26-7	bis(1,2,2,6,6-Pentamethyl-4-Piperidinyl) Sebacate	2369 - 3920 mg/kg Rat	N.E.	N.E.
104810-48-2	Polymeric Benzotriazole	>5000 mg/kg Rat	N.E.	N.E.
34590-94-8	Dipropylene Glycol Monomethyl Ether	5350 mg/kg Rat	9500 mg/kg Rabbit	>20 mg/L

N.E. - Not Established

12. Ecological Information

Ecological Information: No ecotoxicity data was found for this product.

13. Disposal Considerations

Disposal: Dispose of material in accordance to local, state, and federal regulations and ordinances.

14. Transport Information

	<u>Domestic (USDOT)</u>	<u>International (IMDG)</u>	<u>Air (IATA)</u>	<u>TDG (Canada)</u>
UN Number:	N.A.	N.A.	N.A.	N.A.
Proper Shipping Name:	Not Regulated	Not Regulated	Not Regulated	Not Regulated
Hazard Class:	N.A.	N.A.	N.A.	N.A.
Packing Group:	N.A.	N.A.	N.A.	N.A.
Limited Quantity:	No	No	No	No

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Reproductive toxicity, Respiratory or Skin Sensitization

SARA Section 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
N-Methyl 2-Pyrrolidone	872-50-4
Aqueous Ammonia	1336-21-6
Ammonium Persulfate	7727-54-0
Pigment Blue 15	147-14-8

Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
N-Methyl 2-Pyrrolidone	872-50-4

U.S. State Regulations:

California Proposition 65

WARNING:

Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

Modern Masters Metallic Paint Collection Exterior Satin Finish Excalibur Quart

16. Other Information**HMIS RATINGS**

Health: 2* Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 1 Instability: 0

Volatile Organic Compounds: 119 g/L

SDS REVISION DATE: 6/5/2025

REASON FOR REVISION: Revision Description Changed
Product Composition Changed
Substance and/or Product Properties Changed in
Section(s):
01 - Identification
02 - Hazard Identification
03 - Composition / Information on Ingredients
05 - Fire-Fighting Measures
08 - Exposure Controls / Personal Protection
09 - Physical & Chemical Properties
11 - Toxicological Information
14 - Transport Information
15 - Regulatory Information
16 - Other Information
Substance Hazard Threshold % Changed
Substance Hazardous Flag Changed
Substance Regulatory CAS Number Changed
Substance Chemical Name Changed
Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.