Date Printed: 2/12/2020 Page 1 / 5

# Safety Data Sheet



www.multicolorpaint.com

## 1. Identification

Product Name: INT S FL BR REACH AERO BLACK FLECK Revision Date: 2/12/2020

Product Identifier: 346895 Supercedes Date: New SDS

Recommended Use: Intermediate

Supplier: Multicolor Specialties, Inc. Manufacturer: Multicolor Specialties, Inc.

1200 Storbeck Drive 1200 Storbeck Drive Waupun, WI 53963 Waupun, WI 53963

USA

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 847-367-7700

**USA** 

## 2. Hazard Identification

#### Classification

Symbol(s) of Product



#### Signal Word

Warning

## Possible Hazards

3% of the mixture consists of ingredient(s) of unknown acute toxicity.

#### **GHS HAZARD STATEMENTS**

Flammable Liquid, category 3 H226 Flammable liquid and vapor.

#### **GHS LABEL PRECAUTIONARY STATEMENTS**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. NO

SMOKING.

P233 Keep container tightly closed.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/

shower.

P370+P378 In case of fire: Use alcohol film forming foam, carbon dioxide, dry chemical, dry sand to extinguish.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local, regional and national regulations.

#### **GHS SDS PRECAUTIONARY STATEMENTS**

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

Date Printed: 2/12/2020 Page 2 / 5

# 3. Composition / Information On Ingredients

#### **HAZARDOUS SUBSTANCES**

| <u>Chemical Name</u>                          | CAS-No.    | Wt.%<br>Range | GHS Symbols   | GHS Statements |
|---|------------|---------------|---------------|----------------|
| Hydrotreated Light Distillate                 | 64742-47-8 | 25-50         | GHS08         | H304           |
| n-Nonane                                      | 111-84-2   | 1.0-2.5       | GHS07         | H332           |
| Carbon Black                                  | 1333-86-4  | 1.0-2.5       | Not Available | Not Available  |
| Barium Sulfate                                | 7727-43-7  | 1.0-2.5       | GHS07         | H332           |
| 2,2,4-Trimethyl-1,3-Pentanediol Diisobutyrate | 6846-50-0  | 0.1-1.0       | GHS06         | H331           |
| Polyacrylic Acid                              | 9003-01-4  | 0.1-1.0       | GHS06         | H330           |

## 4. First-Aid Measures

**FIRST AID - EYE CONTACT:** Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**FIRST AID - SKIN CONTACT:** Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

**FIRST AID - INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, get medical attention.

## 5. Fire-Fighting Measures

**EXTINGUISHING MEDIA:** Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Dry Sand, Water Fog

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Closed containers may explode when exposed to extreme heat due to buildup of steam. Keep containers tightly closed. Combustible liquid and vapor. No unusual fire or explosion hazards noted.

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate area and fight fire from a safe distance. Use water spray to keep fire-exposed containers cool. Containers may explode when heated.

Special Fire and Explosion Hazard (Combustible Dust): No Information

## 6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers.

## 7. Handling and Storage

**HANDLING:** Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

**STORAGE:** Store in a dry, well ventilated place. Keep container tightly closed when not in use. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Avoid excess heat.

Advice on Safe Handling of Combustible Dust: No Information

# 8. Exposure Controls / Personal Protection

| Chemical Name                 | CAS-No.    | Weight %<br>Less Than | ACGIH TLV-<br>TWA | ACGIH TLV-<br>STEL | OSHA PEL-TWA | OSHA PEL-<br>CEILING |
|-------------------------------|------------|-----------------------|-------------------|--------------------|--------------|----------------------|
| Hydrotreated Light Distillate | 64742-47-8 | 40.0                  | N.E.              | N.E.               | N.E.         | N.E.                 |

Date Printed: 2/12/2020 Page 3 / 5

| n-Nonane                        | 111-84-2  | 5.0 | 200 ppm | N.E.  | N.E.      | N.E.  |
|---------------------------------|-----------|-----|---------|-------|-----------|-------|
| Carbon Black                    | 1333-86-4 | 5.0 | 3 mg/m3 | N.E.  | 3.5 mg/m3 | N.E.  |
| Barium Sulfate                  | 7727-43-7 | 5.0 | 5 mg/m3 | N.E.  | 15 mg/m3  | N.E.  |
| 2,2,4-Trimethyl-1,3-Pentanediol | 6846-50-0 | 1.0 | N.E.    | N.E.  | N.E.      | N.E.  |
| Diisobutyrate                   | 0040-30-0 | 1.0 | IN.⊑.   | IN.⊑. | IN.⊑.     | IN.⊑. |
| Polyacrylic Acid                | 9003-01-4 | 1.0 | N.E.    | N.E.  | N.E.      | N.E.  |

#### PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

**RESPIRATORY PROTECTION:** A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

**OTHER PROTECTIVE EQUIPMENT:** Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

**HYGIENIC PRACTICES:** Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

## 9. Physical and Chemical Properties

| Appearance:             | Liquid              | Physical State:                   | Liquid    |
|-------------------------|---------------------|-----------------------------------|-----------|
| Odor:                   | Solvent Like        | Odor Threshold:                   | N.E.      |
| Specific Gravity:       | 0.936               | pH:                               | N.A.      |
| Freeze Point, °C:       | N.D.                | Viscosity:                        | N.D.      |
| Solubility in Water:    | Slight              | Partition Coefficient, n-octanol/ | ND        |
| Decompostion Temp., °C: | N.D.                | water:                            | N.D.      |
| Boiling Range, °C:      | 100 - 537           | Explosive Limits, vol%:           | 0.7 - 6.0 |
| Flammability:           | Supports Combustion | Flash Point, °C:                  | 46        |
| Evaporation Rate:       | Slower than Ether   | Auto-ignition Temp., °C:          | N.D.      |
| Vapor Density:          | Heavier than Air    | Vapor Pressure:                   | N.D.      |

(See "Other information" Section for abbreviation legend)

# 10. Stability and Reactivity

**CONDITIONS TO AVOID:** No Information

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

**HAZARDOUS DECOMPOSITION:** When heated to decomposition, it emits acrid smoke and irritating fumes. Contains solvents which may form carbon monoxide, carbon dioxide, and formaldehyde.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

# 11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Substance causes moderate eye irritation.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Substance may cause slight skin irritation.

**EFFECTS OF OVEREXPOSURE - INHALATION:** High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation.

EFFECTS OF OVEREXPOSURE - INGESTION: Irritating to the nose, throat and respiratory tract. Harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Contains carbon black. Chronic inflammation, lung fibrosis, and lung tumors have been observed in some rats experimentally exposed for long periods of time to excessive concentrations of carbon black and several insoluble fine dust particles. Tumors have not been observed in other animal species (i.e., mouse and hamster) under similar circumstances and study conditions. Epidemiological studies of North American workers show no evidence of clinically significant adverse health effects due to occupational exposure to carbon black.

Date Printed: 2/12/2020 Page 4 / 5

Carbon black is listed as a Group 2B-"Possibly carcinogenic to humans" by IARC and is proposed to be listed as A4- "not classified as a human carcinogen" by the American Conference of Governmental Industrial Hygienists. Significant exposure is not anticipated during brush application or drying. Risk of overexposure depends on duration and level of exposure to dust from repeated sanding of surfaces or spray mist and the actual concentration of carbon black in the formula.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

#### **ACUTE TOXICITY VALUES**

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No.    | Chemical Name                                 | Oral LD50        | Dermal LD50        | Vapor LC50     |
|------------|---|------------------|--------------------|----------------|
| 64742-47-8 | Hydrotreated Light Distillate                 | >5000 mg/kg Rat  | >2000 mg/kg Rabbit | >5000 mg/L Rat |
| 1333-86-4  | Carbon Black                                  | >15400 mg/kg Rat | N.E.               | N.E.           |
| 7727-43-7  | Barium Sulfate                                | 307000 mg/kg Rat | N.E.               | N.E.           |
| 6846-50-0  | 2,2,4-Trimethyl-1,3-Pentanediol Diisobutyrate | >3200 mg/kg Rat  | N.E.               | >5.3 mg/L Rat  |
| 9003-01-4  | Polyacrylic Acid                              | 2500 mg/kg Rat   | N.E.               | 1.71 mg/L Rat  |

N.E. - Not Established

## 12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

# 13. Disposal Information

**DISPOSAL INFORMATION:** Do not incinerate closed containers. Dispose of material in accordance to local, state, and federal regulations and ordinances.

## 14. Transport Information

|                       | Domestic (USDOT) | International (IMDG) | <u>Air (IATA)</u>   | TDG (Canada)  |
|-----------------------|------------------|----------------------|---------------------|---------------|
| UN Number:            | N.A.             | 1263                 | 1263                | N.A.          |
| Proper Shipping Name: | Not Regulated    | Paint                | Paint               | Not Regulated |
| Hazard Class:         | N.A.             | 3                    | 3                   | N.A.          |
| Packing Group:        | N.A.             | III                  | III                 | N.A.          |
| Limited Quantity:     | No               | No                   | Cargo Aircraft Only | No            |

# 15. Regulatory Information

## U.S. Federal Regulations:

#### **CERCLA - SARA Hazard Category**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids)

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

#### **Toxic Substances Control Act:**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>Chemical Name</u> <u>CAS-No.</u>

Date Printed: 2/12/2020 Page 5 / 5

n-Nonane 111-84-2

# U.S. State Regulations:

## California Proposition 65:

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.

## 16. Other Information

**HMIS RATINGS** 

Health: 2\* Flammability: 2 Physical Hazard: 0 Personal Protection: X

**NFPA RATINGS** 

Health: 2 Flammability: 2 Instability 0

Volatile Organic Compounds 586 g/L SDS REVISION DATE: 2/12/2020

**REASON FOR REVISION:** 

Legend: N.A. - Not Applicable, N.D. - Not Determined, N.E. - Not Established

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.