Date Printed: 6/25/2019 Page 1 / 6

Safety Data Sheet



* Trusted Quality Since 1921 * www.rustoleum.com

Rust-Oleum Corporation

11 Hawthorn Parkway

Vernon Hills, IL 60061

1. Identification

Product Name: CPS 1-GL 4600BRITECASTSC SEALER-B Revision Date: 6/25/2019

Product Identifier: 236899 Supercedes Date: 8/8/2018

Recommended Use: Sealer kit/Activator

Supplier: Rust-Oleum Corporation Manufacturer:

11 Hawthorn Parkway Vernon Hills, IL 60061

USA

Rust-Oleum Canada (ROCA) 200 Confederation Parkway Concord, ON L4K 4T8

Canada

USA

Emergency Phone: 800-387-3625

Preparer: Regulatory Department

Emergency Telephone: 24 Hour Hotline: 847-367-7700

2. Hazard Identification

Classification

Symbol(s) of Product



Signal Word Danger

Possible Hazards

32% of the mixture consists of ingredient(s) of unknown acute toxicity.

GHS HAZARD STATEMENTS

STOT, repeated exposure, category 2 H373 May cause damage to organs through prolonged or repeated exposure.

Acute Toxicity, Oral, category 4 H302 Harmful if swallowed.

Acute Toxicity, Inhalation, category 4 H332 Harmful if inhaled.

Skin Corrosion, category 1 H314 Causes severe skin burns and eye damage.
Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.

GHS LABEL PRECAUTIONARY STATEMENTS

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P501 Dispose of contents/container in accordance with local, regional and national regulations.

P264 Wash hands thoroughly after handling.

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

P271 Use only outdoors or in a well-ventilated area.

Date Printed: 6/25/2019 Page 2 / 6

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing. P280 Wear protective gloves/protective clothing/eye protection/face protection.

IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. P301+P330+P331

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and

easy to do. Continue rinsing.

P310 If exposed immediately call a POISON CENTER or doctor/physician.

P321 For specific treatment see label

P405 Store locked up.

P272 Contaminated work clothing should not be allowed out of the workplace.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

GHS SDS PRECAUTIONARY STATEMENTS

P270 Do not eat, drink or smoke when using this product.

P363 Wash contaminated clothing before reuse.

3. Composition / Information On Ingredients

HAZARDOUS SUBSTANCES

Chemical Name	CAS-No.	<u>Wt.%</u>	GHS Symbols	GHS Statements
4,4'-Methylene-bis-Cyclohexylamine	1761-71-3	39	GHS05-GHS07- GHS08	H302-314-317-373
Proprietary Cycloaliphatic Amine	PROPRIET ARY	32	GHS05-GHS07- GHS08	H314-317-373
Benzyl Alcohol	100-51-6	29	GHS07	H302-312-320-332

4. First-Aid Measures

FIRST AID - EYE CONTACT: Immediately flush eyes with plenty of water for at least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed. If exposed to fumes or vapors, flush eyes with plenty of water for at least 15 minutes. Get medical attention.

FIRST AID - SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash contaminated clothing and decontaminate footwear before reuse. Wash skin with soap and water. Remove contaminated clothing. Get medical attention if irritation develops or persists.

FIRST AID - INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cupfuls of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively. Swallowing less than an ounce will not cause significant harm. For larger amounts, do not induce vomiting, but give one or two glasses of water to drink and get medical attention. If swallowed, rinse mouth with water. If feeling unwell, get medical attention.

5. Fire-Fighting Measures

EXTINGUISHING MEDIA: Alcohol Film Forming Foam, Carbon Dioxide, Dry Chemical, Water Fog

UNUSUAL FIRE AND EXPLOSION HAZARDS: Combustion generates toxic fumes of carbon monoxide, carbon dioxide and other gases. No unusual fire or explosion hazards noted. Keep containers tightly closed. FLASH POINT IS TESTED TO BE GREATER THAN 200 DEGREES F.

Date Printed: 6/25/2019 Page 3 / 6

SPECIAL FIREFIGHTING PROCEDURES: Evacuate area and fight fire from a safe distance. Water may be used to cool closed containers to prevent pressure buildup and possible autoignition or explosion. Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

Special Fire and Explosion Hazard (Combustible Dust): No Information

6. Accidental Release Measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Remove all sources of ignition, ventilate area and remove with inert absorbent and non-sparking tools. Dispose of according to local, state (provincial) and federal regulations. Do not incinerate closed containers. If spilled, contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container, and unused contents in accordance with local, state, and federal regulations. Do not incinerate closed containers

7. Handling and Storage

HANDLING: Wash thoroughly after handling. Use only with adequate ventilation. Avoid prolonged or repeated contact with skin. Use only in a well-ventilated area. Avoid contact with eyes, skin and clothing. Wash hands before eating. Remove contaminated clothing and launder before reuse. Follow all SDS and label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist.

STORAGE: Keep containers tightly closed. Isolate from heat, electrical equipment, sparks and open flame. Keep container closed when not in use. Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Advice on Safe Handling of Combustible Dust: No Information

8. Exposure Controls / Personal Protection

Chemical Name	CAS-No.	Weight % Less Than	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL-TWA	OSHA PEL- CEILING
4,4'-Methylene-bis- Cyclohexylamine	1761-71-3	40.0	N.E.	N.E.	N.E.	N.E.
Proprietary Cycloaliphatic Amine	PROPRIETARY	35.0	N.E.	N.E.	N.E.	N.E.
Benzyl Alcohol	100-51-6	30.0	N.E.	N.E.	N.E.	N.E.

PERSONAL PROTECTION

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve crossventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use impervious gloves to prevent skin contact and absorption of this material through the skin. Nitrile or Neoprene gloves may afford adequate skin protection. Use gloves to prevent prolonged skin contact.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

Engineering Measures for Combustible Dust: No Information

Date Printed: 6/25/2019 Page 4 / 6

9. Physical and Chemical Properties

Physical State: Appearance: Liquid Liauid Odor: **Odor Threshold:** Amine N.E. Specific Gravity: 1.041 pH: N.A. Freeze Point, °C: Viscosity: N.D. N.D. Partition Coefficient, n-Solubility in Water: Slight N.D. octanol/water: Decompostion Temp., °C: N.D. Boiling Range, °C: 204 - 204 **Explosive Limits, vol%:** N.A. - N.A. Flammability: **Does not Support Combustion** Flash Point, °C: 118 **Evaporation Rate:** Auto-ignition Temp., °C: Slower than Ether N.D. Vapor Density: Vapor Pressure: Heavier than Air N.D.

(See "Other information" Section for abbreviation legend)

10. Stability and Reactivity

CONDITIONS TO AVOID: Avoid all possible sources of ignition. Avoid temperatures above 120°F (49°C).

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalies.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

11. Toxicological Information

EFFECTS OF OVEREXPOSURE - EYE CONTACT: Causes eye burns. Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

EFFECTS OF OVEREXPOSURE - SKIN CONTACT: Contact causes skin irritation. May cause skin sensitization, an allergic reaction, which becomes evident upon re-exposure to this material. Causes skin irritation. Allergic reactions are possible. Low hazard for usual industrial handling or commercial handling by trained personnel.

EFFECTS OF OVEREXPOSURE - INHALATION: High vapor concentrations are irritating to the eyes, nose, throat and lungs. Prolonged or excessive inhalation may cause respiratory tract irritation. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

EFFECTS OF OVEREXPOSURE - INGESTION: Can burn mouth, throat and stomach. Aspiration hazard if swallowed; can enter lungs and cause damage. Substance may be harmful if swallowed.

EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS: High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis, and blurred vision) and/or damage. Effects of overexposure may include irritation of the nose and throat, irritation of the digestive tract and signs of nervous system depression (e.g., headache, drowsiness, loss of coordination and fatigue). Prolonged or repeated overexposure may cause lung damage.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact

ACUTE TOXICITY VALUES

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50
1761-71-3	4,4'-Methylene-bis-Cyclohexylamine	1000 mg/kg Rat	2500 mg/kg Rat	25
100-51-6	Benzyl Alcohol	1230 mg/kg Rat	2000 mg/kg Rabbit	11 mg/L Rat

N.E. - Not Established

12. Ecological Information

ECOLOGICAL INFORMATION: Product is a mixture of listed components.

13. Disposal Information

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances.

Date Printed: 6/25/2019 Page 5 / 6

14. Transport Information TDG (Canada) **Domestic (USDOT)** International (IMDG) Air (IATA) **UN Number:** 3066 3066 3066 3066 **Proper Shipping Name:** Paint Related Material Paint Related Material Paint Related Material Paint Related Material 8 **Hazard Class:** 8 8 8 Ш Ш Ш Packing Group: Ш **Limited Quantity:** Nο Nο Cargo Aircraft Only Nο

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. State Regulations:

California Proposition 65:

WARNING: No Prop. 65 warning is required.

Date Printed: 6/25/2019 Page 6 / 6

16. Other Information

HMIS RATINGS

Health: 2* Flammability: 1 Physical Hazard: 0 Personal Protection: X

NFPA RATINGS

Health: 2 Flammability: 1 Instability 0

Volatile Organic Compounds 75 g/L SDS REVISION DATE: 6/25/2019

REASON FOR REVISION: Revision Description Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

09 - Physical & Chemical Properties

14 - Transport Information16 - Other Information

Revision Statement(s) Changed

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

The manufacturer believes, to the best of its knowledge, information and belief, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. The manufacturer makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.